

- Basic:

1. Retrieve the total number of orders placed.

```
select count(order_id) as total_orders from orders;
```

2. Calculate the total revenue generated from pizza sales.

```
SELECT
    ROUND(SUM(order_details.quantity * pizzas.price),
          2) AS total_sales
```

```
FROM
    order_details
    JOIN
    pizzas ON pizzas.pizza_id = order_details.pizza_id
```

-- Identify the highest-priced pizza.

```
SELECT
    pizza_types.name, pizzas.price
FROM
    pizza_types
    JOIN
    pizzas ON pizza_types.pizza_type_id = pizzas.pizza_type_id
ORDER BY pizzas.price DESC
LIMIT 1;
```

3. Identify the highest-priced pizza.

```
SELECT
    pizza_types.name, pizzas.price
FROM
    pizza_types
    JOIN
    pizzas ON pizza_types.pizza_type_id = pizzas.pizza_type_id
ORDER BY pizzas.price DESC
LIMIT 1;
```

4. Identify the most common pizza size ordered.

```
select quantity, count(order_details_id)
from order_details group by quantity;
```

5. List the top 5 most ordered pizza types along with their quantities.

```

SELECT
    pizza_types.name, SUM(order_details.quantity) AS quantity
FROM
    pizza_types
    JOIN
    pizzas ON pizza_types.pizza_type_id = pizzas.pizza_type_id
    JOIN
    order_details ON order_details.pizza_id = pizzas.pizza_id
GROUP BY pizza_types.name
ORDER BY quantity DESC
LIMIT 5;

```

- Intermediate:

1. Join the necessary tables to find the total quantity of each pizza category ordered.

```

SELECT
    pizza_types.category,
    SUM(order_details.quantity) AS quantity
FROM
    pizza_types
    JOIN
    pizzas ON pizza_types.pizza_type_id = pizzas.pizza_type_id
    JOIN
    order_details ON order_details.pizza_id = pizzas.pizza_id
GROUP BY pizza_types.category
ORDER BY quantity DESC;

```

2. Determine the distribution of orders by hour of the day.

```

select hour(order_time), count(order_id) from orders
group by hour(order_time);

```

3. Join relevant tables to find the category-wise distribution of pizzas.

```

select category , count(name) from pizza_types
group by category;

```

4. Group the orders by date and calculate the average number of pizzas ordered per day.

```

SELECT
    ROUND(AVG(quantity), 0) as avg_pizza_ordered_per_day
FROM

```

```
(SELECT
    orders.order_date, SUM(order_details.quantity) AS quantity
FROM
    orders
JOIN order_details ON orders.order_id = order_details.order_id
GROUP BY orders.order_date) AS order_quantity;
```

5. Determine the top 3 most ordered pizza types based on revenue.

```
SELECT
    pizza_types.name,
    SUM(order_details.quantity * pizzas.price) AS revenue
FROM
    pizza_types
    JOIN
    pizzas ON pizzas.pizza_type_id = pizza_type.pizza_type_id
    JOIN
    order_details ON order_details.pizza_id = pizzas.pizza_id
GROUP BY pizza_types.name
ORDER BY revenue DESC
LIMIT 3;
```

- Advanced:

1. Calculate the percentage contribution of each pizza type to total revenue.

```
SELECT
    pizza_types.category,
    ROUND(SUM(order_details.quantity * pizzas.price) /
        (SELECT SUM(order_details.quantity * pizzas.price)
         FROM order_details
         JOIN pizzas ON pizzas.pizza_id = order_details.pizza_id) * 100, 2) AS
percentage_contribution
FROM
    pizza_types
    JOIN
    pizzas ON pizza_types.pizza_type_id = pizzas.pizza_type_id
    JOIN
    order_details ON order_details.pizza_id = pizzas.pizza_id
GROUP BY
    pizza_types.category
ORDER BY
    percentage_contribution DESC;
```

2. Analyze the cumulative revenue generated over time.

```
select order_date,  
sum(revenue) over(order by order_date) as cum_revenue  
from  
(select orders.order_date,  
sum(order_details.quantity * pizzas.price) as revenue  
from order_details join pizzas  
on order_details.pizza_id = pizzas.pizza_id  
join orders  
on orders.order_id = order_details.order_id  
group by orders.order_date) as sales;
```

3. Determine the top 3 most ordered pizza types based on revenue for each pizza category.

```
select name, revenue from  
(select category, name, revenue,  
rank() over(partition by category order by revenue desc) as rn  
from  
(select pizza_types.category, pizza_types.name,  
sum((order_details.quantity) * pizzas.price) as revenue  
from pizza_types join pizzas  
on pizza_types.pizza_type_id = pizzas.pizza_type_id  
join order_details  
on order_details.pizza_id = pizzas.pizza_id  
group by pizza_types.category, pizza_types.name) as a) as b  
where rn <= 3;
```