

Keystone Developer Guide

API v2.0 (Apr 23, 2011)

DRAFT

Keystone Developer Guide

API v2.0 (2011-04-23)

Copyright © 2010, 2011 OpenStack All rights reserved.

This document is intended for software developers interested in developing applications which utilize the Cloud Identity Service for authentication. This document also includes details on how to integrate services with the Cloud Identity Service.

Licensed under the Apache License, Version 2.0 (the "License"); you may not use this file except in compliance with the License. You may obtain a copy of the License at

<http://www.apache.org/licenses/LICENSE-2.0>

Unless required by applicable law or agreed to in writing, software distributed under the License is distributed on an "AS IS" BASIS, WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied. See the License for the specific language governing permissions and limitations under the License.

Table of Contents

| | |
|---|----|
| 1. Overview | 1 |
| 2. Concepts | 2 |
| 2.1. Token | 2 |
| 2.2. Tenant | 2 |
| 2.3. User | 2 |
| 2.4. Role | 2 |
| 2.5. Group | 2 |
| 3. General API Information | 3 |
| 3.1. Request/Response Types | 3 |
| 3.2. Content Compression | 4 |
| 3.3. Paginated Collections | 4 |
| 3.4. Versions | 8 |
| 3.5. Extensions | 15 |
| 3.6. Faults | 19 |
| 4. Service Developer Operations | 21 |
| 4.1. Overview | 21 |
| 4.2. Token Operations | 21 |
| 4.2.1. Authenticate | 21 |
| 4.2.2. Validate Token | 23 |
| 4.2.3. Revoke Token | 24 |
| 4.3. Tenant Operations | 24 |
| 4.3.1. Create a Tenant | 24 |
| 4.3.2. Get Tenants | 25 |
| 4.3.3. Get a Tenant | 26 |
| 4.3.4. Update a Tenant | 27 |
| 4.3.5. Delete a Tenant | 28 |
| 4.4. Base URLs | 28 |
| 4.4.1. Get Base URLs | 28 |
| 4.4.2. Get Base URL | 30 |
| 4.4.3. Get Base URLs for a Tenant | 31 |
| 4.4.4. Add Base URL to a Tenant | 32 |
| 4.4.5. Remove Base URLs from a Tennat | 33 |
| 4.5. Roles | 33 |
| 4.5.1. Get roles | 33 |
| 4.5.2. Get Role | 34 |
| 4.5.3. Get roles for a User | 34 |
| 4.5.4. Add Role to a User | 35 |
| 4.5.5. Remove roles from a User | 36 |

List of Tables

3.1. Response Types 3

3.2. Compression Headers 4

3.3. Fault Types 20

List of Examples

| | |
|---|----|
| 3.1. JSON Request with Headers | 3 |
| 3.2. XML Response with Headers | 3 |
| 3.3. Tenant Collection, First Page: XML | 5 |
| 3.4. Tenant Collection, First Page: JSON | 5 |
| 3.5. Tenant Collection, Second Page: XML | 5 |
| 3.6. Tenant Collection, Second Page: JSON | 6 |
| 3.7. Tenant Collection, Last Page: XML | 6 |
| 3.8. Tenant Collection, Last Page: JSON | 6 |
| 3.9. Paginated Groups in a User: XML | 7 |
| 3.10. Paginated Groups in an User: JSON | 7 |
| 3.11. Request with MIME type versioning | 8 |
| 3.12. Request with URI versioning | 8 |
| 3.13. Multiple Choices Response: XML | 9 |
| 3.14. Multiple Choices Response: JSON | 9 |
| 3.15. Versions List Request | 11 |
| 3.16. Versions List Response: XML | 11 |
| 3.17. Versions List Response: Atom | 11 |
| 3.18. Versions List Response: JSON | 12 |
| 3.19. Version Details Request | 13 |
| 3.20. Version Details Response: XML | 13 |
| 3.21. Version Details Response: Atom | 13 |
| 3.22. Version Details Response: JSON | 14 |
| 3.23. Extensions Response: XML | 15 |
| 3.24. Extensions Response: JSON | 16 |
| 3.25. Extension Response: xml | 17 |
| 3.26. Extensions Response: JSON | 17 |
| 3.27. Extended User Response: XML | 18 |
| 3.28. Extended User Response: JSON | 18 |
| 3.29. XML Fault Response | 19 |
| 3.30. JSON Fault Response | 19 |
| 3.31. XML Not Found Fault | 19 |
| 3.32. JSON Not Found Fault | 20 |
| 4.1. XML Auth Request | 21 |
| 4.2. JSON Auth Request | 21 |
| 4.3. XML Auth Response | 21 |
| 4.4. JSON Auth Response | 22 |
| 4.5. XML Validate Token Response | 23 |
| 4.6. JSON Validate Token Response | 23 |
| 4.7. XML Tenant Create Request | 24 |
| 4.8. JSON Tenant Create Request | 25 |
| 4.9. XML Tenant Create Response | 25 |
| 4.10. JSON Tenant Create Response | 25 |
| 4.11. XML Tenants Response | 25 |
| 4.12. JSON Tenants Response | 26 |
| 4.13. XML Tenant Response | 26 |
| 4.14. JSON Tenant Response | 26 |
| 4.15. XML Tenant Update Request | 27 |
| 4.16. JSON Tenant Update Request | 27 |

| | |
|--|----|
| 4.17. XML Tenant Update Response | 27 |
| 4.18. JSON Tenant Update Response | 27 |
| 4.19. Base URLs Response: XML | 28 |
| 4.20. Base URLs Response: JSON | 29 |
| 4.21. Base URL Response: XML | 30 |
| 4.22. Base URL Response: JSON | 30 |
| 4.23. Base URL Refs Response: XML | 31 |
| 4.24. Base URL Refs Response: JSON | 31 |
| 4.25. Add Base URL Request: XML | 32 |
| 4.26. Add Base URL Request: JSON | 32 |
| 4.27. Roles Response: XML | 33 |
| 4.28. Roles Response: JSON | 33 |
| 4.29. Role Response: XML | 34 |
| 4.30. Role Response: JSON | 34 |
| 4.31. Role Refs Response: XML | 34 |
| 4.32. Role Refs Response: JSON | 35 |
| 4.33. Add Role Request: XML | 35 |
| 4.34. Add Role Request: JSON | 35 |

1. Overview

The Keystone Identity Service allows applications to obtain tokens that can be used to access OpenStack resources. This document is intended for software developers interested in developing applications which utilize the Cloud Identity Service for authentication. This document also includes details on how to integrate services with the Cloud Identity Service.

This Guide assumes the reader is familiar with RESTful web services, HTTP/1.1, and JSON and/or XML serialization formats.

2. Concepts

The Keystone Identity Service has several key concepts that are important to understand:

2.1. Token

A token is an arbitrary bit of text that is used to access resources. Each token has a scope which describes which resources are accessible with it. A token may be revoked at anytime and is valid for a finite duration.

2.2. Tenant

Depending on the operator, a tenant may map to a customer, account, organization, or project.

2.3. User

Users have a login and may be assigned tokens to access resources.

2.4. Role

A role that an identity is associated with that allows it to perform certain operations. Roles are managed by services and operators. Tenant administrators may assign roles to users.

2.5. Group

A group of users. Global groups are managed by operators. They are used to organize and assign privileges to a group of related users. For example, an operator may create a "delinquent" group, which will assign limited privileges to users who have past due bills.

3. General API Information

The Keystone API is implemented using a RESTful web service interface. All requests to authenticate and operate against the Keystone API are performed using SSL over HTTP (HTTPS) on TCP port 443.

3.1. Request/Response Types

The Keystone API supports both the JSON and XML data serialization formats. The request format is specified using the `Content-Type` header and is required for operations that have a request body. The response format can be specified in requests using either the `Accept` header or adding an `.xml` or `.json` extension to the request URI. Note that it is possible for a response to be serialized using a format different from the request (see example below). If no response format is specified, JSON is the default. If conflicting formats are specified using both an `Accept` header and a query extension, the query extension takes precedence.

Table 3.1. Response Types

| Format | Accept Header | Query Extension | Default |
|--------|------------------|-----------------|---------|
| JSON | application/json | .json | Yes |
| XML | application/xml | .xml | No |

Example 3.1. JSON Request with Headers

```
POST /v2.0/tokens HTTP/1.1
Host: identity.api.openstack.org
Content-Type: application/json
Accept: application/xml
```

```
<?xml version="1.0" encoding="UTF-8"?>
<passwordCredentials
  xmlns="http://docs.openstack.org/identity/api/v2.0"
  password="P@ssword1" username="testuser"
  tenantId="77654"/>
```

Example 3.2. XML Response with Headers

```
HTTP/1.1 200 OKAY
Date: Mon, 12 Nov 2010 15:55:01 GMT
Content-Length:
Content-Type: application/xml; charset=UTF-8
```

```
<?xml version="1.0" encoding="UTF-8"?>
<auth xmlns="http://docs.openstack.org/identity/api/v2.0">
  <token expires="2010-11-01T03:32:15-05:00"
    id="ab48a9efdfedb23ty3494"/>
  <serviceCatalog>
```

```
<service name="service1">
  <endpoint
    region="DFW"
    publicURL="https://service1.public.com/v2.0/blah-blah"
    internalURL="https://service1.internal.com/v2.0/blah-
blah"/>
  <endpoint
    region="ORD"
    publicURL="https://service1.public.com/v2.0/blah-blah"
    internalURL="https://service1.internal.com/v2.0/blah-
blah"/>
</service>
<service name="service2">
  <endpoint
    region="DFW"
    publicURL="https://service2.public.com/v2.0/blah-blah"/>
  <endpoint
    region="ORD"
    publicURL="https://service2.public.com/v2.0/blah-blah"/>
</service>
<service name="service3">
  <endpoint
    publicURL="https://service3.public.com/v2.0/blah-blah"/>
</service>
</serviceCatalog>
</auth>
```

3.2. Content Compression

Request and response body data may be encoded with gzip compression in order to accelerate interactive performance of API calls and responses. This is controlled using the `Accept-Encoding` header on the request from the client and indicated by the `Content-Encoding` header in the server response. Unless the header is explicitly set, encoding defaults to disabled.

Table 3.2. Compression Headers

| Header Type | Name | Value |
|-------------------|------------------|-------|
| HTTP/1.1 Request | Accept-Encoding | gzip |
| HTTP/1.1 Response | Content-Encoding | gzip |

3.3. Paginated Collections

To reduce load on the service, list operations will return a maximum number of items at a time. The maximum number of items returned is determined by the IDM provider. To navigate the collection, the parameters *limit* and *marker* can be set in the URI (e.g. *?limit=100&marker=1234*). The *marker* parameter is the ID of the last item in the previous list. Items are sorted by update time. When an update time is not available they are sorted by ID. The *limit* parameter sets the page size. Both parameters are optional. If the client requests a *limit* beyond that which is supported by the deployment an `overLimit (413)` fault may be thrown. A marker with an invalid ID will return an `itemNotFound (404)` fault.



Note

Paginated collections never return itemNotFound (404) faults when the collection is empty — clients should expect an empty collection.

For convenience, collections contain atom "next" and "previous" links. The first page in the list will not contain a "previous" link, the last page in the list will not contain a "next" link. The following examples illustrate three pages in a collection of tenants. The first page was retrieved via a **GET** to <http://identity.api.openstack.org/v2.0/1234/tenants?limit=1>. In these examples, the *limit* parameter sets the page size to a single item. Subsequent "next" and "previous" links will honor the initial page size. Thus, a client may follow links to traverse a paginated collection without having to input the *marker* parameter.

Example 3.3. Tenant Collection, First Page: XML

```
<?xml version="1.0" encoding="UTF-8"?>
<tenants xmlns="http://docs.openstack.org/identity/api/v2.0"
  xmlns:atom="http://www.w3.org/2005/Atom">
  <tenant enabled="true" id="1234">
    <description>A description...</description>
  </tenant>
  <atom:link
    rel="next"
    href="http://identity.api.openstack.org/v2.0/1234/tenants?limit=1&
    amp;marker=1234"/>
</tenants>
```

Example 3.4. Tenant Collection, First Page: JSON

```
{
  "tenants": {
    "values" : [
      {
        "id": "1234",
        "description": "A description ...",
        "enabled": true
      }
    ],
    "links" : [
      {
        "rel" : "next",
        "href" : "http://identity.api.openstack.org/v2.0/1234/tenants?
        limit=1&marker=1234"
      }
    ]
  }
}
```

Example 3.5. Tenant Collection, Second Page: XML

```
<?xml version="1.0" encoding="UTF-8"?>
<tenants xmlns="http://docs.openstack.org/identity/api/v2.0"
  xmlns:atom="http://www.w3.org/2005/Atom">
  <tenant enabled="true" id="3645">
```

```

        <description>A description...</description>
      </tenant>
      <atom:link
        rel="previous"
        href="http://identity.api.openstack.org/v2.0/1234/tenants?limit=1"/>
      <atom:link
        rel="next"
        href="http://identity.api.openstack.org/v2.0/1234/tenants?limit=1&
amp;marker=3645"/>
    </tenants>

```

Example 3.6. Tenant Collection, Second Page: JSON

```

{
  "tenants": {
    "values" : [
      {
        "id": "3645",
        "description": "A description ...",
        "enabled": true
      }
    ],
    "links" : [
      {
        "rel" : "next",
        "href" : "http://identity.api.openstack.org/v2.0/1234/tenants?
limit=1&marker=3645"
      },
      {
        "rel" : "previous",
        "href" : "http://identity.api.openstack.org/v2.0/1234/tenants?
limit=1"
      }
    ]
  }
}

```

Example 3.7. Tenant Collection, Last Page: XML

```

<?xml version="1.0" encoding="UTF-8"?>
<tenants xmlns="http://docs.openstack.org/identity/api/v2.0"
  xmlns:atom="http://www.w3.org/2005/Atom">
  <tenant enabled="true" id="9999">
    <description>A description...</description>
  </tenant>
  <atom:link
    rel="previous"
    href="http://identity.api.openstack.org/v2.0/1234/tenants?limit=1&
amp;marker=1234"/>
</tenants>

```

Example 3.8. Tenant Collection, Last Page: JSON

```

{
  "tenants": {

```

```

    "values" : [
      {
        "id": "9999",
        "description": "A description ...",
        "enabled": true
      }
    ],
    "links" : [
      {
        "rel" : "previous",
        "href" : "http://identity.api.openstack.org/v2.0/1234/tenants?
limit=1&marker=1234"
      }
    ]
  }
}

```

In the JSON representation, paginated collections contain a values property that contains the items in the collections. Links are accessed via the links property. The approach allows for extensibility of both the collection members and of the paginated collection itself. It also allows collections to be embedded in other objects as illustrated below. Here, a subset of groups are presented within a user. Clients must follow the "next" link to continue to retrieve additional groups belonging to a user.

Example 3.9. Paginated Groups in a User: XML

```

<?xml version="1.0" encoding="UTF-8"?>
<user xmlns="http://docs.openstack.org/identity/api/v2.0"
      xmlns:atom="http://www.w3.org/2005/Atom"
      enabled="true" email="john.smith@example.org"
      tenantId="1234" id="jqsmith">
  <groups>
    <group tenantId="1234" id="Admin"/>
    <group tenantId="1234" id="DBUser"/>
    <group id="Super"/>
    <atom:link
      rel="next"
      href="http://identity.api.openstack.org/v2.0/1234/tenants/1234/
users/jqsmith/groups?marker=Super"/>
  </groups>
</user>

```

Example 3.10. Paginated Groups in an User: JSON

```

{
  "user": {
    "groups": {
      "values": [
        {
          "tenantId" : "1234",
          "id": "Admin"
        },
        {
          "tenantId" : "1234",
          "id" : "DBUser"
        },
        {

```

```

        "id" : "Super"
      }
    ],
    "links" : [
      {
        "rel" : "next",
        "href" : "http://identity.api.openstack.org/v2.0/1234/
tenants/1234/users/jqsmith/groups?marker=Super"
      }
    ]
  },
  "id": "jqsmith",
  "tenantId": "1234",
  "email": "john.smith@example.org",
  "enabled": true
}

```

3.4. Versions

The OpenStack Identity API uses both a URI and a MIME type versioning scheme. In the URI scheme, the first element of the path contains the target version identifier (e.g. `https://identity.api.openstack.org/v2.0/...`). The MIME type versioning scheme uses HTTP content negotiation where the `Accept` or `Content-Type` headers contains a MIME type that identifies the version (`application/vnd.openstack.identity-v1.1+xml`). A version MIME type is always linked to a base MIME type (`application/xml` or `application/json`). If conflicting versions are specified using both an HTTP header and a URI, the URI takes precedence.

Example 3.11. Request with MIME type versioning

```

GET /tenants HTTP/1.1
Host: identity.api.openstack.org
Accept: application/vnd.openstack.identity-v1.1+xml
X-Auth-Token: eaaafd18-0fed-4b3a-81b4-663c99ec1cbb

```

Example 3.12. Request with URI versioning

```

GET /v1.1/tenants HTTP/1.1
Host: identity.api.openstack.org
Accept: application/xml
X-Auth-Token: eaaafd18-0fed-4b3a-81b4-663c99ec1cbb

```



Note

The MIME type versioning approach allows for the creating of permanent links, because the version scheme is not specified in the URI path: `https://api.identity.openstack.org/tenants/12234`.

If a request is made without a version specified in the URI or via HTTP headers, then a multiple-choices response (300) will follow providing links and MIME types to available versions.

Example 3.13. Multiple Choices Response: XML

```
<?xml version="1.0" encoding="UTF-8"?>

<choices xmlns="http://docs.openstack.org/common/api/v1.0"
  xmlns:atom="http://www.w3.org/2005/Atom">

  <version id="v1.0" status="DEPRECATED">
    <media-types>
      <media-type base="application/xml"
        type="application/vnd.openstack.identity-v2.0+xml"/>
      <media-type base="application/json"
        type="application/vnd.openstack.identity-v2.0+json"/>
    </media-types>

    <atom:link rel="self"
      href="http://identity.api.openstack.org/v2.0"/>
  </version>

  <version id="v1.1" status="CURRENT">
    <media-types>
      <media-type base="application/xml"
        type="application/vnd.openstack.identity-v1.1+xml"/>
      <media-type base="application/json"
        type="application/vnd.openstack.identity-v1.1+json"/>
    </media-types>

    <atom:link rel="self"
      href="http://identity.api.openstack.org/v1.1"/>
  </version>
</choices>
```

Example 3.14. Multiple Choices Response: JSON

```
{
  "choices" : {
    "values" : [
      {
        "id" : "v1.0",
        "status" : "DEPRECATED",
        "links": [
          {
            "rel" : "self",
            "href" : "http://identity.api.openstack.org/v2.0"
          }
        ],
        "media-types": {
          "values" : [
            {
              "base" : "application/xml",
              "type" : "application/vnd.openstack.identity-v1.0+xml"
            },
            {
              "base" : "application/json",
              "type" : "application/vnd.openstack.identity-v1.0+json"
            }
          ]
        }
      }
    ]
  }
}
```

```

    }
  ],
  {
    "id" : "v1.1",
    "status" : "CURRENT",
    "links": [
      {
        "rel" : "self",
        "href" : "http://identity.api.openstack.org/v1.1"
      }
    ],
    "media-types": {
      "values" : [
        {
          "base" : "application/xml",
          "type" : "application/vnd.openstack.identity-v1.
1+xml"
        },
        {
          "base" : "application/json",
          "type" : "application/vnd.openstack.identity-v1.
1+json"
        }
      ]
    }
  },
  {
    "id" : "v2.0",
    "status" : "CURRENT",
    "links": [
      {
        "rel" : "self",
        "href" : "http://identity.api.openstack.org/v2.0"
      }
    ],
    "media-types": {
      "values" : [
        {
          "base" : "application/xml",
          "type" : "application/vnd.openstack.identity-v2.
0+xml"
        },
        {
          "base" : "application/json",
          "type" : "application/vnd.openstack.identity-v2.
0+json"
        }
      ]
    }
  }
]
}

```

New features and functionality that do not break API-compatibility will be introduced in the current version of the API as extensions (see below) and the URI and MIME types will remain unchanged. Features or functionality changes that would necessitate a break in API-compatibility will require a new version, which will result in URI and MIME type

version being updated accordingly. When new API versions are released, older versions will be marked as `DEPRECATED`. Providers should work with developers and partners to ensure there is adequate time to migrate to the new version before deprecated versions are discontinued.

Your application can programmatically determine available API versions by performing a `GET` on the root URL (i.e. with the version and everything to the right of it truncated) returned from the authentication system. Note that an Atom representation of the versions resources is supported when issuing a request with the `Accept` header containing `application/atom+xml` or by adding a `.atom` to the request URI. This allows standard Atom clients to track version changes.

Example 3.15. Versions List Request

```
GET HTTP/1.1
Host: identity.api.openstack.org
```

Normal Response Code(s): 200, 203

Error Response Code(s): `badRequest` (400), `identityFault` (500), `serviceUnavailable` (503)

This operation does not require a request body.

Example 3.16. Versions List Response: XML

```
<?xml version="1.0" encoding="UTF-8"?>

<versions xmlns="http://docs.openstack.org/common/api/v1.0"
  xmlns:atom="http://www.w3.org/2005/Atom">

  <version id="v1.0" status="DEPRECATED"
    updated="2009-10-09T11:30:00Z">
    <atom:link rel="self"
      href="http://identity.api.openstack.org/v2.0/" />
  </version>

  <version id="v1.1" status="CURRENT"
    updated="2010-12-12T18:30:02.25Z">
    <atom:link rel="self"
      href="http://identity.api.openstack.org/v1.1/" />
  </version>

</versions>
```

Example 3.17. Versions List Response: Atom

```
<?xml version="1.0" encoding="UTF-8"?>
<feed xmlns="http://www.w3.org/2005/Atom">
  <title type="text">Available API Versions</title>
  <updated>2010-12-12T18:30:02.25Z</updated>
  <id>http://identity.api.openstack.org/</id>
  <author><name>Rackspace</name><uri>http://www.rackspace.com/</uri></author>
```

```

<link rel="self" href="http://identity.api.openstack.org/" />
<entry>
  <id>http://identity.api.openstack.org/v1.1/</id>
  <title type="text">Version v1.1</title>
  <updated>2010-12-12T18:30:02.25Z</updated>
  <link rel="self" href="http://identity.api.openstack.org/v1.1/" />
  <content type="text">Version v1.1 CURRENT (2010-12-12T18:30:02.25Z)</
content>
</entry>
<entry>
  <id>http://identity.api.openstack.org/v1.0/</id>
  <title type="text">Version v1.0</title>
  <updated>2009-10-09T11:30:00Z</updated>
  <link rel="self" href="http://identity.api.openstack.org/v2.0/" />
  <content type="text">Version v1.0 DEPRECATED (2009-10-09T11:30:00Z)</
content>
</entry>
</feed>

```

Example 3.18. Versions List Response: JSON

```

{
  "versions" : {
    "values" : [
      {
        "id" : "v1.0",
        "status" : "DEPRECATED",
        "updated" : "2009-10-09T11:30:00Z",
        "links": [
          {
            "rel" : "self",
            "href" : "http://identity.api.openstack.org/v2.0/"
          }
        ]
      },
      {
        "id" : "v1.1",
        "status" : "CURRENT",
        "updated" : "2010-12-12T18:30:02.25Z",
        "links": [
          {
            "rel" : "self",
            "href" : "http://identity.api.openstack.org/v1.1/"
          }
        ]
      }
    ]
  }
}

```

You can also obtain additional information about a specific version by performing a **GET** on the base version URL (e.g. <https://identity.api.openstack.org/v1.1/>). Version request URLs should always end with a trailing slash (/). If the slash is omitted, the server may respond with a 302 redirection request. Format extensions may be placed after the slash (e.g. <https://identity.api.openstack.org/v1.1/.xml>). Note that this is a special case that does not hold true for other API requests. In general, requests such as `/tenants.xml` and `tenants/.xml` are handled equivalently.

Example 3.19. Version Details Request

```
GET HTTP/1.1
Host: identity.api.openstack.org/v1.1/
```

Normal Response Code(s): 200, 203

Error Response Code(s): badRequest (400), identityFault (500), serviceUnavailable(503)

This operation does not require a request body.

Example 3.20. Version Details Response: XML

```
<?xml version="1.0" encoding="UTF-8"?>
<version xmlns="http://docs.openstack.org/common/api/v1.0"
  xmlns:atom="http://www.w3.org/2005/Atom"
  id="v2.0" status="CURRENT" updated="2011-01-21T11:33:21-06:00">

  <media-types>
    <media-type base="application/xml"
      type="application/vnd.openstack.identity-v2.0+xml"/>
    <media-type base="application/json"
      type="application/vnd.openstack.identity-v2.0+json"/>
  </media-types>

  <atom:link rel="self"
    href="http://identity.api.openstack.org/v2.0/" />

  <atom:link rel="describedby"
    type="application/pdf"
    href="http://docs.rackspacecloud.com/identity/api/v2.0/
identity-devguide-20110125.pdf" />

  <atom:link rel="describedby"
    type="application/vnd.sun.wadl+xml"
    href="http://docs.rackspacecloud.com/identity/api/v2.0/
application.wadl" />
</version>
```

Example 3.21. Version Details Response: Atom

```
<?xml version="1.0" encoding="UTF-8"?>
<feed xmlns="http://www.w3.org/2005/Atom">
  <title type="text">About This Version</title>
  <updated>2011-01-21T11:33:21-06:00</updated>
  <id>http://identity.api.openstack.org/v2.0/</id>
  <author><name>Rackspace</name><uri>http://www.rackspace.com/</uri></author>
  <link rel="self" href="http://identity.api.openstack.org/v2.0/" />
  <entry>
    <id>http://identity.api.openstack.org/v2.0/</id>
    <title type="text">Version v2.0</title>
    <updated>2011-01-21T11:33:21-06:00</updated>
    <link rel="self" href="http://identity.api.openstack.org/v2.0/" />
    <link rel="describedby" type="application/pdf"
```

```

        href="http://docs.openstack.org/identity/api/v2.0/identity-
devguide-20110125.pdf"/>
        <link rel="describedby" type="application/vnd.sun.wadl+xml"
            href="http://docs.openstack.org/identity/api/v2.0/application.
wadl"/>
        <content type="text">Version v2.0 CURRENT (2011-01-21T11:33:21-06:00)</
content>
    </entry>
</feed>

```

Example 3.22. Version Details Response: JSON

```

{
  "version" : {
    "id" : "v2.0",
    "status" : "CURRENT",
    "updated" : "2011-01-21T11:33:21-06:00",
    "links": [
      {
        "rel" : "self",
        "href" : "http://identity.api.openstack.org/v2.0/"
      },
      {
        "rel" : "describedby",
        "type" : "application/pdf",
        "href" : "http://docs.rackspacecloud.com/identity/api/v2.0/
identity-devguide-20110125.pdf"
      },
      {
        "rel" : "describedby",
        "type" : "application/vnd.sun.wadl+xml",
        "href" : "http://docs.rackspacecloud.com/identity/api/v2.0/
application.wadl"
      }
    ],
    "media-types": [
      {
        "base" : "application/xml",
        "type" : "application/vnd.openstack.identity-v2.0+xml"
      },
      {
        "base" : "application/json",
        "type" : "application/vnd.openstack.identity-v2.0+json"
      }
    ]
  }
}

```

The detailed version response contains pointers to both a human-readable and a machine-processable description of the API service. The machine-processable description is written in the Web Application Description Language (WADL).



Note

If there is a discrepancy between the two specifications, the WADL is authoritative as it contains the most accurate and up-to-date description of the API service.

3.5. Extensions

The OpenStack Identity API is extensible. Extensions serve two purposes: They allow the introduction of new features in the API without requiring a version change and they allow the introduction of vendor specific niche functionality. Applications can programmatically determine what extensions are available by performing a **GET** on the /extensions URI. Note that this is a versioned request — that is, an extension available in one API version may not be available in another.

| Verb | URI | Description |
|------|-------------|--|
| GET | /extensions | Returns a list of available extensions |

Normal Response Code(s):200, 203

Error Response Code(s): badRequest (400), identityFault (500), serviceUnavailable(503)

This operation does not require a request body.

Each extension is identified by two unique identifiers, a namespace and an alias. Additionally an extension contains documentation links in various formats.

Example 3.23. Extensions Response: XML

```
<?xml version="1.0" encoding="UTF-8"?>

<extensions xmlns="http://docs.openstack.org/common/api/v1.0"
  xmlns:atom="http://www.w3.org/2005/Atom">
  <extension
    name="Reset Password Extension"
    namespace="http://docs.rackspacecloud.com/identity/api/ext/rpe/v1.0"
    alias="RS-RPE"
    updated="2011-01-22T13:25:27-06:00">

    <description>
      Adds the capability to reset a user's password. The user is
      emailed when the password has been reset.
    </description>

    <atom:link rel="describedby"
      type="application/pdf"
      href="http://docs.rackspacecloud.com/identity/api/ext/identity-rpe-20111111.pdf"/>
    <atom:link rel="describedby"
      type="application/vnd.sun.wadl+xml"
      href="http://docs.rackspacecloud.com/identity/api/ext/identity-rpe.wadl"/>
  </extension>
  <extension
    name="User Metadata Extension"
    namespace="http://docs.rackspacecloud.com/identity/api/ext/meta/v2.0"
    alias="RS-META"
    updated="2011-01-12T11:22:33-06:00">
    <description>
      Allows associating arbitrary metadata with a user.
    </description>

    <atom:link rel="describedby"
```

```

        type="application/pdf"
        href="http://docs.rackspacecloud.com/identity/api/ext/
identity-meta-20111201.pdf"/>
        <atom:link rel="describedby"
        type="application/vnd.sun.wadl+xml"
        href="http://docs.rackspacecloud.com/identity/api/ext/
identity-meta.wadl"/>
    </extension>
</extensions>

```

Example 3.24. Extensions Response: JSON

```

{
  "extensions" : {
    "values" : [
      {
        "name" : "Reset Password Extension",
        "namespace" : "http://docs.rackspacecloud.com/identity/api/
ext/rpe/v1.0",
        "alias" : "RS-RPE",
        "updated" : "2011-01-22T13:25:27-06:00",
        "description" : "Adds the capability to reset a user's
password. The user is emailed when the password has been reset.",
        "links" : [
          {
            "rel" : "describedby",
            "type" : "application/pdf",
            "href" : "http://docs.rackspacecloud.com/identity/api/
ext/identity-rpe-20111111.pdf"
          },
          {
            "rel" : "describedby",
            "type" : "application/vnd.sun.wadl+xml",
            "href" : "http://docs.rackspacecloud.com/identity/api/
ext/identity-rpe.wadl"
          }
        ]
      },
      {
        "name" : "User Metadata Extension",
        "namespace" : "http://docs.rackspacecloud.com/identity/api/
ext/meta/v2.0",
        "alias" : "RS-META",
        "updated" : "2011-01-12T11:22:33-06:00",
        "description" : "Allows associating arbitrary metadata with a
user.",
        "links" : [
          {
            "rel" : "describedby",
            "type" : "application/pdf",
            "href" : "http://docs.rackspacecloud.com/identity/api/
ext/identity-meta-20111201.pdf"
          },
          {
            "rel" : "describedby",
            "type" : "application/vnd.sun.wadl+xml",
            "href" : "http://docs.rackspacecloud.com/identity/api/
ext/identity-meta.wadl"
          }
        ]
      }
    ]
  }
}

```

```

    }
  ]
}

```

Extensions may also be queried individually by their unique alias. This provides the simplest method of checking if an extension is available as an unavailable extension will issue an `itemNotFound` (404) response.

| Verb | URI | Description |
|------|---------------------------|--------------------------------------|
| GET | /extensions/ <i>alias</i> | Return details of a single extension |

Normal Response Code(s):200, 203

Error Response Code(s): `itemNotFound` (404), `badRequest` (400), `identityFault` (500), `serviceUnavailable`(503)

This operation does not require a request body.

Example 3.25. Extension Response: xml

```

<?xml version="1.0" encoding="UTF-8"?>

<extension xmlns="http://docs.openstack.org/common/api/v1.0"
  xmlns:atom="http://www.w3.org/2005/Atom"
  name="User Metadata Extension"
  namespace="http://docs.rackspacecloud.com/identity/api/ext/meta/v2.0"
  alias="RS-META"
  updated="2011-01-12T11:22:33-06:00">

  <description>
    Allows associating arbitrary metadata with a user.
  </description>

  <atom:link rel="describedby"
    type="application/pdf"
    href="http://docs.rackspacecloud.com/identity/api/ext/identity-meta-20111201.pdf"/>
  <atom:link rel="describedby"
    type="application/vnd.sun.wadl+xml"
    href="http://docs.rackspacecloud.com/identity/api/ext/identity-meta.wadl"/>

</extension>

```

Example 3.26. Extensions Response: JSON

```

{
  "extension" : {
    "name" : "User Metadata Extension",

```

```

    "namespace" : "http://docs.rackspacecloud.com/identity/api/ext/meta/v2.0",
    "alias" : "RS-META",
    "updated" : "2011-01-12T11:22:33-06:00",
    "description" : "Allows associating arbitrary metadata with a user.",
    "links" : [
      {
        "rel" : "describedby",
        "type" : "application/pdf",
        "href" : "http://docs.rackspacecloud.com/identity/api/ext/identity-meta-20111201.pdf"
      },
      {
        "rel" : "describedby",
        "type" : "application/vnd.sun.wadl+xml",
        "href" : "http://docs.rackspacecloud.com/identity/api/ext/identity-cbs.wadl"
      }
    ]
  }
}

```

Extensions may define new data types, parameters, actions, headers, states, and resources. In XML, additional elements and attributes may be defined. These elements must be defined in the extension's namespace. In JSON, the alias must be used. The volumes element in the Examples 3.27 and 3.28 is defined in the RS-META namespace. Extended headers are always prefixed with X- followed by the alias and a dash: (X-RS-META-HEADER1). Parameters must be prefixed with the extension alias followed by a colon.



Important

Applications should be prepared to ignore response data that contains extension elements. Also, applications should also verify that an extension is available before submitting an extended request.

Example 3.27. Extended User Response: XML

```

<?xml version="1.0" encoding="UTF-8"?>
<user xmlns="http://docs.openstack.org/identity/api/v2.0"
  enabled="true" email="john.smith@example.org"
  tenantId="1234" id="jqsmith">
  <groups>
    <group tenantId="1234" id="Admin"/>
  </groups>
  <metadata
    xmlns="http://docs.rackspacecloud.com/identity/api/ext/meta/v2.0">
    <meta key="MetaKey1">MetaValue1</meta>
    <meta key="MetaKey2">MetaValue2</meta>
  </metadata>
</user>

```

Example 3.28. Extended User Response: JSON

```

{ "user" :
  {

```



```

    "groups": {
      "values": [
        {
          "tenantId": "1234",
          "id": "Admin"
        }
      ],
      "id": "jqsmith",
      "tenantId": "1234",
      "email": "john.smith@example.org",
      "enabled": true,
      "RS-META:metadata": {
        "values": {
          "MetaKey1": "MetaValue1",
          "MetaKey2": "MetaValue2"
        }
      }
    },
  },
}

```

3.6. Faults

When an error occurs the system will return an HTTP error response code denoting the type of error. The system will also return additional information about the fault in the body of the response.

Example 3.29. XML Fault Response

```

<?xml version="1.0" encoding="UTF-8"?>
<identityFault xmlns="http://docs.openstack.org/identity/api/v2.0"
  code="500">
  <message>Fault</message>
  <details>Error Details...</details>
</identityFault>

```

Example 3.30. JSON Fault Response

```

{"identityFault":
  {
    "message": "Fault",
    "details": "Error Details...",
    "code": 500
  }
}

```

The error code is returned in the body of the response for convenience. The message section returns a human readable message. The details section is optional and may contain useful information for tracking down an error (e.g a stack trace).

The root element of the fault (e.g. identityFault) may change depending on the type of error. The following is an example of an itemNotFound error.

Example 3.31. XML Not Found Fault

```
<?xml version="1.0" encoding="UTF-8"?>
<itemNotFound xmlns="http://docs.openstack.org/identity/api/v2.0"
               code="404">
  <message>Item not found.</message>
  <details>Error Details...</details>
</itemNotFound>
```

Example 3.32. JSON Not Found Fault

```
{ "itemNotFound":
  {
    "message": "Item not found.",
    "details": "Error Details...",
    "code": 404
  }
}
```

The following is a list of possible fault types along with their associated error codes.

Table 3.3. Fault Types

| Fault Element | Associated Error Code | Expected in All Requests |
|--------------------|-----------------------|--------------------------|
| identityFault | 500, 400 | ✓ |
| serviceUnavailable | 503 | ✓ |
| badRequest | 400 | ✓ |
| unauthorized | 401 | ✓ |
| overLimit | 413 | |
| userDisabled | 403 | |
| forbidden | 403 | |
| itemNotFound | 404 | |
| tenantConflict | 409 | |

From an XML schema perspective, all API faults are extensions of the base fault type `identityFault`. When working with a system that binds XML to actual classes (such as JAXB), one should be capable of using `identityFault` as a “catch-all” if there's no interest in distinguishing between individual fault types.

4. Service Developer Operations

4.1. Overview

The operations described in this chapter allow service developers to get and validate access tokens, manage users, and manage tenants.

4.2. Token Operations

4.2.1. Authenticate

| Verb | URI | Description |
|------|---------|-----------------------------------|
| POST | /tokens | Authenticate to generate a token. |

Normal Response Code(s): 200, 203

Error Response Code(s): unauthorized (401), userDisabled (403), badRequest (400), identityFault (500), serviceUnavailable(503)

TenantID is optional and may be used to specify that a token should be returned that has access for resources that particular tenant.

Example 4.1. XML Auth Request

```
<?xml version="1.0" encoding="UTF-8"?>
<passwordCredentials
  xmlns="http://docs.openstack.org/identity/api/v2.0"
  password="P@ssword1" username="testuser"
  tenantId="77654"/>
```

Example 4.2. JSON Auth Request

```
{
  "passwordCredentials" : {
    "username" : "test_user",
    "password" : "a86850deb2742ec3cb41518e26aa2d89",
    "tenantId" : "77654"
  }
}
```

Example 4.3. XML Auth Response

```
<?xml version="1.0" encoding="UTF-8"?>
<auth xmlns="http://docs.openstack.org/identity/api/v2.0">
  <token expires="2010-11-01T03:32:15-05:00"
    id="ab48a9efdfedb23ty3494"/>
  <serviceCatalog>
```

```

        <service name="service1">
          <endpoint
            region="DFW"
            publicURL="https://service1.public.com/v2.0/blah-blah"
            internalURL="https://service1.internal.com/v2.0/blah-
blah"/>
          <endpoint
            region="ORD"
            publicURL="https://service1.public.com/v2.0/blah-blah"
            internalURL="https://service1.internal.com/v2.0/blah-
blah"/>
        </service>
        <service name="service2">
          <endpoint
            region="DFW"
            publicURL="https://service2.public.com/v2.0/blah-blah"/>
          <endpoint
            region="ORD"
            publicURL="https://service2.public.com/v2.0/blah-blah"/>
        </service>
        <service name="service3">
          <endpoint
            publicURL="https://service3.public.com/v2.0/blah-blah"/>
        </service>
      </serviceCatalog>
    </auth>

```

Example 4.4. JSON Auth Response

```

{
  "auth" : {
    "token" : {
      "id" : "asdasdasd-adsasdads-asdasdasd-adsadsasd",
      "expires" : "2010-11-01T03:32:15-05:00"
    },
    "serviceCatalog" : {
      "service1" : [
        {
          "region" : "DFW",
          "publicURL" : "https://service1-public/v1/blah-blah",
          "internalURL" : "https://service1-internal/v1/blah-
blah"
        },
        {
          "region" : "ORD",
          "publicURL" : "https://service1-public-ord/v1/blah-blah",
          "internalURL" : "https://service1-internal-ord/v1/blah-
blah"
        }
      ],
      "service2" : [
        {
          "region" : "DFW",
          "publicURL" : "https://service2-public-dfw/v1/blah-blah",
          "internalURL" : "https://service2-public-dfw/v1/blah-
blah"
        },
        {
          "region" : "ORD",
          "publicURL" : "https://service2-public-ord/v1/blah-
blah"
        }
      ]
    }
  }
}

```

```

    ],
    "service3" : [
      {
        "publicURL" : "https://service3-public/v1/blah-blah",
      }
    ]
  }
}

```

4.2.2. Validate Token

| Verb | URI | Description |
|------|---|--|
| GET | /tokens/ <i>tokenId</i> ?belongsTo= <i>tenantId</i> | Check that a token is valid and that it belongs to a particular user and return the permissions relevant to a particular client. |

Normal Response Code(s): 200, 203

Error Response Code(s): unauthorized (401), forbidden (403), userDisabled(403), badRequest (400), itemNotFound (404), identityFault(500), serviceUnavailable(503)

This operation does not require a request body.

Valid tokens will exist in the /tokens/*tokenId* path and invalid tokens will not. In other words, a user should expect an itemNotFound (404) fault for an invalid token.

Example 4.5. XML Validate Token Response

```

<?xml version="1.0" encoding="UTF-8"?>
<auth xmlns="http://docs.openstack.org/identity/api/v2.0">
  <token expires="2010-11-01T03:32:15-05:00"
        id="ab48a9efdfedb23ty3494"/>
  <user tenantId="1245" username="jqsmith">
    <groups>
      <group tenantId="1245" name="Admin"/>
    </groups>
    <roleRefs>
      <roleRef href="https://.openstack.org/identity/v2.0/roles/
admin" id="3" tenantId="tenantId"/>
      <roleRef href="https://.openstack.org/identity/v2.0/roles/
test" id="4" tenantId="tenantId"/>
    </roleRefs>
  </user>
</auth>

```

Example 4.6. JSON Validate Token Response

```

{
  "auth" : {
    "token": {
      "id": "ab48a9efdfedb23ty3494",
      "expires": "2010-11-01T03:32:15-05:00"
    }
  }
}

```

```
    },
    "user" : {
      "groups": {
        "group": [
          {
            "tenantId" : "1234",
            "name": "Admin"
          }
        ],
        "roleRefs": {
          "roleRef" : [
            {
              "id" : 1,
              "href" : "https://.openstack.org/identity/v2.0/roles/
admin",
              "tenantId" : "one"
            }
          ],
          "username": "jqsmith",
          "tenantId": "1234",
        }
      }
    }
  }
}
```

4.2.3. Revoke Token

| Verb | URI | Description |
|--------|-------------------------|---------------------------|
| DELETE | /tokens/ <i>tokenId</i> | Revoke an existing token. |

Normal Response Code(s):204

Error Response Code(s): unauthorized (401), forbidden (403), userDisabled(403), badRequest (400), itemNotFound (404), identityFault(500), serviceUnavailable(503)

This operation does not require a request body.

4.3. Tenant Operations

4.3.1. Create a Tenant

| Verb | URI | Description |
|------|----------|-----------------|
| POST | /tenants | Create a tenant |

Normal Response Code(s):201

Error Response Code(s): unauthorized (401), forbidden(403), badRequest (400), identityFault (500), serviceUnavailable(503)

Example 4.7. XML Tenant Create Request

```
<?xml version="1.0" encoding="UTF-8"?>
<tenant xmlns="http://docs.openstack.org/identity/api/v2.0"
```

```
    enabled="true" id="1234">
      <description>A description...</description>
    </tenant>
```

Example 4.8. JSON Tenant Create Request

```
{ "tenant":
  {
    "id": "1234",
    "description": "A description ...",
    "enabled": true
  }
}
```

Example 4.9. XML Tenant Create Response

```
<?xml version="1.0" encoding="UTF-8"?>
<tenant xmlns="http://docs.openstack.org/identity/api/v2.0"
  enabled="true" id="1234">
  <description>A description...</description>
</tenant>
```

Example 4.10. JSON Tenant Create Response

```
{ "tenant":
  {
    "id": "1234",
    "description": "A description ...",
    "enabled": true
  }
}
```

4.3.2. Get Tenants

| Verb | URI | Description |
|------|----------|------------------------|
| GET | /tenants | Get a list of tenants. |

Normal Response Code(s):200, 203

Error Response Code(s): unauthorized (401), forbidden(403), overLimit(413), badRequest (400), identityFault (500), serviceUnavailable(503)

The operation returns a list of tenants. The list may be filtered to return only those tenants which the caller has access to.

This operation does not require a request body.

Example 4.11. XML Tenants Response

```
<?xml version="1.0" encoding="UTF-8"?>
<tenants xmlns="http://docs.openstack.org/identity/api/v2.0">
  <tenant enabled="true" id="1234">
    <description>A description...</description>
  </tenant>
  <tenant enabled="true" id="3645">
    <description>A description...</description>
  </tenant>
</tenants>
```

Example 4.12. JSON Tenants Response

```
{ "tenants": {
  "values" : [
    {
      "id": "1234",
      "description": "A description ...",
      "enabled": true
    },
    {
      "id": "3456",
      "description": "A description ...",
      "enabled": true
    }
  ]
}
```

4.3.3. Get a Tenant

| Verb | URI | Description |
|------|---------------------------|---------------|
| GET | /tenants/ <i>tenantId</i> | Get a tenant. |

Normal Response Code(s):200, 203

Error Response Code(s): unauthorized (401), forbidden(403), itemNotFound(404), badRequest (400), identityFault (500), serviceUnavailable(503)

This operation does not require a request body.

Example 4.13. XML Tenant Response

```
<?xml version="1.0" encoding="UTF-8"?>
<tenant xmlns="http://docs.openstack.org/identity/api/v2.0"
  enabled="true" id="1234">
  <description>A description...</description>
</tenant>
```

Example 4.14. JSON Tenant Response

```
{ "tenant":
```


DRAFT - DRAFT - DRAFT - DRAFT - DRAFT - DRAFT -

DRAFT - DRAFT - DRAFT - DRAFT - DRAFT - DRAFT -

DRAFT - DRAFT - DRAFT - DRAFT - DRAFT - DRAFT -

DRAFT - DRAFT - DRAFT - DRAFT - DRAFT - DRAFT -

DRAFT - DRAFT - DRAFT - DRAFT - DRAFT - DRAFT -

DRAFT - DRAFT - DRAFT - DRAFT - DRAFT - DRAFT -

DRAFT - DRAFT - DRAFT - DRAFT - DRAFT - DRAFT -

DRAFT - DRAFT - DRAFT - DRAFT - DRAFT - DRAFT -

DRAFT - DRAFT - DRAFT - DRAFT - DRAFT - DRAFT -

DRAFT - DRAFT - DRAFT - DRAFT - DRAFT - DRAFT -

DRAFT - DRAFT - DRAFT - DRAFT - DRAFT - DRAFT -

DRAFT - DRAFT - DRAFT - DRAFT - DRAFT - DRAFT -

DRAFT - DRAFT - DRAFT - DRAFT - DRAFT - DRAFT -

4.3.5. Delete a Tenant

| Verb | URI | Description |
|--------|---------------------------|------------------|
| DELETE | /tenants/ <i>tenantId</i> | Delete a Tenant. |

Normal Response Code(s):204

Error Response Code(s): unauthorized (401), badRequest (400), forbidden (403), itemNotFound (404), identityFault (500), serviceUnavailable(503)

This operation does not require a request body.

4.4. Base URLs

4.4.1. Get Base URLs

| Verb | URI | Description |
|------|--|----------------------------------|
| GET | /baseURLs? <i>serviceName</i> =ServiceName | Get a list of base URLs. |
| GET | /baseURLs/enabled? <i>serviceName</i> =ServiceName | Get a list of enabled base URLs. |

Normal Response Code(s): 200, 203

Error Response Code(s): unauthorized (401), forbidden (403), badRequest (400), authFault (500), serviceUnavailable (503)

This operation does not require a request body.

Example 4.19. Base URLs Response: XML

```
<?xml version="1.0" encoding="UTF-8"?>

<baseURLs xmlns="http://docs.openstack.org/identity/api/v2.0">
  <baseURL
    id="1"
    region="DFW"
    default="true"
    serviceName="service1"
    publicURL="https://service1.public.com/v1"
    internalURL="https://service1.internal.clouddrive.com/v1"
    enabled="true"
  />
  <baseURL
    id="2"
    region="ORD"
    serviceName="service2"
    publicURL="https://service2.public.com/v1"
    internalURL="https://service2.internal.public.com/v1"
    enabled="false"
  />
  <baseURL
    id="3"
    region="DFW"
    default="true"
```

```
    serviceName="service1"
    publicURL="https://service1.public.com/v1"
    enabled="true"
  />
  <baseURL
    id="4"
    region="ORD"
    serviceName="service2"
    publicURL="https://service2.public.com/v1"
    enabled="true"
  />
  <baseURL
    id="5"
    default="true"
    serviceName="service3"
    publicURL="https://service3.public.com/v1"
  />
</baseURLs>
```

Example 4.20. Base URLs Response: JSON

```
{
  "baseURLs" : [
    {
      "id" : 1,
      "region" : "DFW",
      "default" : true,
      "serviceName" : "service1",
      "publicURL" : "https://service1.public.com/v1",
      "internalURL" : "https://service1.internal.com/v1",
      "enabled" : true
    },
    {
      "id" : 2,
      "region" : "ORD",
      "serviceName" : "service2",
      "publicURL" : "https://service2.public.com/v1",
      "internalURL" : "https://service2.internal.com/v1",
      "enabled" : false
    },
    {
      "id" : 3,
      "region" : "DFW",
      "default" : true,
      "serviceName" : "service1",
      "publicURL" : "https://service.public.com/v1",
      "enabled" : true
    },
    {
      "id" : 4,
      "region" : "ORD",
      "serviceName" : "service2",
      "publicURL" : "https://service2.public.com/v1",
      "enabled" : true
    },
    {
      "id" : 5,
```

```
    "default" : true,
    "serviceName" : "service3",
    "publicURL" : "https://service3.public.com/v1.0",
    "enabled" : true
  }
]
```

4.4.2. Get Base URL

| Verb | URI | Description |
|------|-----------------------------|-----------------|
| GET | /baseURLs/ <i>baseURLId</i> | Get a base URL. |

Normal Response Code(s): 200, 203

Error Response Code(s): unauthorized (401), forbidden (403), badRequest (400), authFault (500), serviceUnavailable (503)

This operation does not require a request body.

Example 4.21. Base URL Response: XML

```
<?xml version="1.0" encoding="UTF-8"?>

<baseURL
  xmlns="http://docs.openstack.org/identity/api/v2.0"
  id="1"
  region="DFW"
  default="true"
  serviceName="service1"
  publicURL="https://service-public.com/v1"
  internalURL="https://service-internal.com/v1"
  enabled="true"
/>
```

Example 4.22. Base URL Response: JSON

```
{
  "baseURL" :
  {
    "id" : 1,
    "region" : "DFW",
    "default" : true,
    "serviceName" : "service1",
    "publicURL" : "https://service-public.com/v1",
    "internalURL" : "https://service-internal.com/v1",
    "enabled" : true
  }
}
```

4.4.3. Get Base URLs for a Tenant

| Verb | URI | Description |
|------|--|---------------------------------------|
| GET | /tenants/ <i>tenantId</i> /baseURLRefs | Get a list of base URLs for a tenant. |

Normal Response Code(s): 200, 203

Error Response Code(s): unauthorized (401), forbidden (403), badRequest (400), authFault (500), serviceUnavailable (503)

This operation does not require a request body.

Example 4.23. Base URL Refs Response: XML

```
<?xml version="1.0" encoding="UTF-8"?>
<baseURLRefs
  xmlns="http://docs.openstack.org/identity/api/v2.0">
  <baseURLRef
    href="https://auth.keystone.com/v2.0/baseURLs/1"
    id="1" />
  <baseURLRef
    href="https://auth.keystone.com/v2.0/baseURLs/2"
    id="2" />
  <baseURLRef
    href="https://auth.keystone.com/v2.0/baseURLs/3"
    id="3" />
  <baseURLRef
    href="https://auth.keystone.com/v2.0/baseURLs/4"
    id="4" />
  <baseURLRef
    href="https://auth.keystone.com/v2.0/baseURLs/5"
    id="5" />
</baseURLRefs>
```

Example 4.24. Base URL Refs Response: JSON

```
{
  "baseURLRefs" : [
    {
      "id" : 1,
      "href" : "https://auth.keystone.com/v2.0/baseURLs/1"
    },
    {
      "id" : 2,
      "href" : "https://auth.keystone.com/v2.0/baseURLs/2"
    },
    {
      "id" : 3,
      "href" : "https://auth.keystone.com/v2.0/baseURLs/3"
    },
    {
      "id" : 4,
      "href" : "https://auth.keystone.com/v2.0/baseURLs/4"
    }
  ]
}
```

```
    },
    {
      "id" : 5,
      "href" : "https://auth.keystone.com/v2.0/baseURLs/5"
    }
  ]
}
```

4.4.4. Add Base URL to a Tenant.

| Verb | URI | Description |
|------|--|-----------------------------|
| POST | /tenants/ <i>tenantId</i> /baseURLRefs | Add a base URL to a tenant. |

Normal Response Code(s): 201

Error Response Code(s): unauthorized (401), forbidden (403), badRequest (400), itemNotFound (404), authFault (500), serviceUnavailable (503)

Expect a badRequest (400) response if a disabled base URL is added or if the base URL had been previously added.

Example 4.25. Add Base URL Request: XML

```
<?xml version="1.0" encoding="UTF-8"?>

<baseURL
  xmlns="http://docs.openstack.org/identity/api/v2.0"
  id="1"
  region="DFW"
  default="true"
  serviceName="service1"
  publicURL="https://service-public.com/v1"
  internalURL="https://service-internal.com/v1"
  enabled="true"
/>
```

Example 4.26. Add Base URL Request: JSON

```
{
  "baseURL" :
  {
    "id" : 1,
    "region" : "DFW",
    "default" : true,
    "serviceName" : "service1",
    "publicURL" : "https://service-public.com/v1",
    "internalURL" : "https://service-internal.com/v1",
    "enabled" : true
  }
}
```

4.4.5. Remove Base URLs from a Tennat

| Verb | URI | Description |
|--------|---|------------------------------|
| DELETE | /tenant/ <i>tenantId</i> /baseURLRefs/ <i>baseURLId</i> | Remove Base URL from a user. |

Normal Response Code(s): 204

Error Response Code(s): unauthorized (401), forbidden (403), badRequest (400), itemNotFound (404), authFault (500), serviceUnavailable (503)

This operation does not require a request body.

4.5. Roles

4.5.1. Get roles

| Verb | URI | Description |
|------|--------|----------------------|
| GET | /roles | Get a list of roles. |

Normal Response Code(s): 200, 203

Error Response Code(s): unauthorized (401), forbidden (403), badRequest (400), authFault (500), serviceUnavailable (503)

This operation does not require a request body.

Example 4.27. Roles Response: XML

```
<?xml version="1.0" encoding="UTF-8"?>

<roles xmlns="http://docs.openstack.org/identity/api/v2.0">
  <role id="Admin" description="All Access" />
  <role id="Guest" description="Guest Access" />
</roles>
```

Example 4.28. Roles Response: JSON

```
{
  "roles" : [
    {
      "id" : "Admin",
      "description" : "All access"
    },
    {
      "id" : "Guest",
      "description" : "Guest Access"
    }
  ]
}
```

4.5.2. Get Role

| Verb | URI | Description |
|------|-----------------------|-------------|
| GET | /roles/ <i>roleId</i> | Get a role. |

Normal Response Code(s): 200, 203

Error Response Code(s): unauthorized (401), forbidden (403), badRequest (400), authFault (500), serviceUnavailable (503)

This operation does not require a request body.

Example 4.29. Role Response: XML

```
<?xml version="1.0" encoding="UTF-8"?>

<role xmlns="http://docs.openstack.org/identity/api/v2.0" id="Admin"
  description="All Access" />
```

Example 4.30. Role Response: JSON

```
{
  "role" :
  {
    "id" : "Admin",
    "description" : "All access"
  }
}
```

4.5.3. Get roles for a User

| Verb | URI | Description |
|------|---------------------------------|---------------------------------|
| GET | /users/ <i>userId</i> /roleRefs | Get a list of roles for a user. |

Normal Response Code(s): 200, 203

Error Response Code(s): unauthorized (401), forbidden (403), badRequest (400), authFault (500), serviceUnavailable (503)

This operation does not require a request body.

Example 4.31. Role Refs Response: XML

```
<?xml version="1.0" encoding="UTF-8"?>

<roleRefs
  xmlns="http://docs.openstack.org/identity/api/v2.0">
  <roleRef xmlns="http://docs.openstack.org/identity/api/v2.0"
    roleId="admin" id="3" tenantId="tenantId"/>
```



```
<roleRef xmlns="http://docs.openstack.org/identity/api/v2.0"
          roleId="test" id="4" tenantId="tenantId"/>
</roleRefs>
```

Example 4.32. Role Refs Response: JSON

```
{
  "roleRefs" : [
    {
      "id" : 1,
      "roleId" : "admin",
      "tenantId" : "one"
    },
    {
      "id" : 2,
      "roleId" : "test",
      "tenantId" : "two"
    }
  ]
}
```

4.5.4. Add Role to a User

| Verb | URI | Description |
|------|---------------------------------|-----------------------|
| POST | /users/ <i>userId</i> /roleRefs | Add a role to a user. |

Normal Response Code(s): 201

Error Response Code(s): unauthorized (401), forbidden (403), badRequest (400), itemNotFound (404), authFault (500), serviceUnavailable (503)

Example 4.33. Add Role Request: XML

```
<?xml version="1.0" encoding="UTF-8"?>

<roleRef xmlns="http://docs.openstack.org/identity/api/v2.0"
          id="1" roleId="Admin" tenantId="tenantId"/>
```

Example 4.34. Add Role Request: JSON

```
{
  "roleRef" : {
    "id" : 1,
    "roleId" : "admin",
    "tenantId" : "one"
  }
}
```

4.5.5. Remove roles from a User

| Verb | URI | Description |
|--------|---|----------------------------|
| DELETE | <code>/users/<i>userId</i>/roleRefs/<i>roleRefId</i></code> | Remove a role from a user. |

Normal Response Code(s): 204

Error Response Code(s): unauthorized (401), forbidden (403), badRequest (400), itemNotFound (404), authFault (500), serviceUnavailable (503)

This operation does not require a request body.