

# Cloud Identity

## Developer Guide

API v1.0 (Apr. 14, 2011)

DRAFT



# Cloud Identity Developer Guide

API v1.0 (2011-04-14)

Copyright © 2010, 2011 Rackspace Hosting, Inc. All rights reserved.

This document is intended for software developers interested in developing applications which utilize the Cloud Identity Service for authentication. This document also includes details on how to integrate services with the Cloud Identity Service.

Licensed under the Apache License, Version 2.0 (the "License"); you may not use this file except in compliance with the License. You may obtain a copy of the License at

<http://www.apache.org/licenses/LICENSE-2.0>

Unless required by applicable law or agreed to in writing, software distributed under the License is distributed on an "AS IS" BASIS, WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied. See the License for the specific language governing permissions and limitations under the License.

## Table of Contents

1. Overview .....	1
2. Concepts .....	2
2.1. Token .....	2
2.2. Tenant .....	2
2.3. User .....	2
2.4. Group .....	2
3. General API Information .....	3
3.1. Request/Response Types .....	3
3.2. Content Compression .....	4
3.3. Paginated Collections .....	4
3.4. Versions .....	8
3.5. Extensions .....	16
3.6. Faults .....	21
4. Service Developer Operations .....	23
4.1. Overview .....	23
4.2. Token Operations .....	23
4.2.1. Authenticate .....	23
4.2.2. Validate Token .....	24
4.2.3. Revoke Token .....	25
4.3. Tenant Operations .....	25
4.3.1. Create a Tenant .....	25
4.3.2. Get Tenants .....	26
4.3.3. Get a Tenant .....	27
4.3.4. Update a Tenant .....	28
4.3.5. Delete a Tenant .....	29

DRAFT - DRAFT - DRAFT - DRAFT - DRAFT - DRAFT - DRAFT -

DRAFT - DRAFT - DRAFT - DRAFT - DRAFT - DRAFT - DRAFT -

## List of Examples

3.1. JSON Request with Headers .....	3
3.2. XML Response with Headers .....	3
3.3. Tenant Collection, First Page: XML .....	5
3.4. Tenant Collection, First Page: JSON .....	5
3.5. Tenant Collection, Second Page: XML .....	5
3.6. Tenant Collection, Second Page: JSON .....	6
3.7. Tenant Collection, Last Page: XML .....	6
3.8. Tenant Collection, Last Page: JSON .....	6
3.9. Paginated Groups in a User: XML .....	7
3.10. Paginated Groups in an User: JSON .....	7
3.11. Request with MIME type versioning .....	8
3.12. Request with URI versioning .....	8
3.13. Multiple Choices Response: XML .....	9
3.14. Multiple Choices Response: JSON .....	10
3.15. Versions List Request .....	11
3.16. Versions List Response: XML .....	11
3.17. Versions List Response: Atom .....	12
3.18. Versions List Response: JSON .....	12
3.19. Version Details Request .....	13
3.20. Version Details Response: XML .....	13
3.21. Version Details Response: Atom .....	14
3.22. Version Details Response: JSON .....	15
3.23. Extensions Response: XML .....	16
3.24. Extensions Response: JSON .....	17
3.25. Extension Response: xml .....	18
3.26. Extensions Response: JSON .....	19
3.27. Extended User Response: XML .....	20
3.28. Extended User Response: JSON .....	20
3.29. XML Fault Response .....	21
3.30. JSON Fault Response .....	21
3.31. XML Not Found Fault .....	21
3.32. JSON Not Found Fault .....	21
4.1. XML Auth Request .....	23
4.2. JSON Auth Request .....	23
4.3. XML Auth Response .....	23
4.4. JSON Auth Response .....	24
4.5. XML Validate Token Response .....	24
4.6. JSON Validate Token Response .....	25
4.7. XML Tenant Create Request .....	26
4.8. JSON Tenant Create Request .....	26
4.9. XML Tenant Create Response .....	26
4.10. JSON Tenant Create Response .....	26
4.11. XML Tenants Response .....	27
4.12. JSON Tenants Response .....	27
4.13. XML Tenant Response .....	28
4.14. JSON Tenant Response .....	28
4.15. XML Tenant Update Request .....	28
4.16. JSON Tenant Update Request .....	28

DRAFT - DRAFT - DRAFT - DRAFT - DRAFT - DRAFT - DRAFT -

# 1. Overview

The Cloud Identity Service allows applications to obtain tokens that can be used to access OpenStack resources. This document is intended for software developers interested in developing applications which utilize the Cloud Identity Service for authentication. This document also includes details on how to integrate services with the Cloud Identity Service.

This Guide assumes the reader is familiar with RESTful web services, HTTP/1.1, and JSON and/or XML serialization formats.

## 2. Concepts

The Cloud Identity Service has several key concepts that are important to understand:

### 2.1. Token

A token is an arbitrary bit of text that is used to access resources. Each token has a scope which describes which resources are accessible with it. A token may be revoked at anytime and is valid for a finite duration.

### 2.2. Tenant

Depending on the operator, a tenant may map to a customer, account, organization, or project.

### 2.3. User

Users have a login and may be assigned tokens to access resources.

### 2.4. Group

A group of users. Global groups are managed by operators. They are used to organize and assign privileges to a group of related users. For example, an operator may create a "delinquent" group, which will assign limited privileges to users who have past due bills.



## 3. General API Information

The IdM API is implemented using a RESTful web service interface. All requests to authenticate and operate against the IdM API are performed using SSL over HTTP (HTTPS) on TCP port 443.

### 3.1. Request/Response Types

The IdM API supports both the JSON and XML data serialization formats. The request format is specified using the `Content-Type` header and is required for operations that have a request body. The response format can be specified in requests using either the `Accept` header or adding an `.xml` or `.json` extension to the request URI. Note that it is possible for a response to be serialized using a format different from the request (see example below). If no response format is specified, JSON is the default. If conflicting formats are specified using both an `Accept` header and a query extension, the query extension takes precedence.

**Table 3.1. Response Types**

Format	Accept Header	Query Extension	Default
JSON	application/json	.json	Yes
XML	application/xml	.xml	No

#### Example 3.1. JSON Request with Headers

```
POST /v1.0/token HTTP/1.1
Host: idm.api.rackspace.com
Content-Type: application/json
Accept: application/xml
```

```
<?xml version="1.0" encoding="UTF-8"?>
<passwordCredentials
  xmlns="http://docs.openstack.org/idm/api/v1.0"
  password="P@ssword1" username="testuser"
  tenantId="77654"/>
```

#### Example 3.2. XML Response with Headers

```
HTTP/1.1 200 OKAY
Date: Mon, 12 Nov 2010 15:55:01 GMT
Server: Apache
Content-Length:
Content-Type: application/xml; charset=UTF-8
```

```
<?xml version="1.0" encoding="UTF-8"?>
<auth xmlns="http://docs.openstack.org/oidm/api/v1.0">
  <token expires="2010-11-01T03:32:15-05:00"
        id="ab48a9efdfedb23ty3494"/>
  <user tenantId="1245" username="jqsmith">
    <groups>
      <group tenantId="1245" id="Admin"/>
    </groups>
  </user>
</auth>
```

## 3.2. Content Compression

Request and response body data may be encoded with gzip compression in order to accelerate interactive performance of API calls and responses. This is controlled using the `Accept-Encoding` header on the request from the client and indicated by the `Content-Encoding` header in the server response. Unless the header is explicitly set, encoding defaults to disabled.

**Table 3.2. Compression Headers**

Header Type	Name	Value
HTTP/1.1 Request	Accept-Encoding	gzip
HTTP/1.1 Response	Content-Encoding	gzip

## 3.3. Paginated Collections

To reduce load on the service, list operations will return a maximum number of items at a time. The maximum number of items returned is determined by the IDM provider. To navigate the collection, the parameters *limit* and *marker* can be set in the URI (e.g. `?limit=100&marker=1234`). The *marker* parameter is the ID of the last item in the previous list. Items are sorted by update time. When an update time is not available they are sorted by ID. The *limit* parameter sets the page size. Both parameters are optional. If the client requests a *limit* beyond that which is supported by the deployment an `overLimit` (413) fault may be thrown. A marker with an invalid ID will return an `itemNotFound` (404) fault.



### Note

Paginated collections never return `itemNotFound` (404) faults when the collection is empty — clients should expect an empty collection.

For convenience, collections contain atom "next" and "previous" links. The first page in the list will not contain a "previous" link, the last page in the list will not contain a "next" link. The following examples illustrate three pages in a collection of tenants. The first page was retrieved via a **GET** to `http://idm.api.openstack.org/v1.0/1234/tenants?limit=1`. In these examples, the *limit* parameter sets the page size to a single item. Subsequent "next" and "previous" links will honor the initial page size. Thus, a client may follow links to traverse a paginated collection without having to input the *marker* parameter.

### Example 3.3. Tenant Collection, First Page: XML

```
<?xml version="1.0" encoding="UTF-8"?>
<tenants xmlns="http://docs.openstack.org/idm/api/v1.0"
  xmlns:atom="http://www.w3.org/2005/Atom">
  <tenant enabled="true" id="1234">
    <description>A description...</description>
  </tenant>
  <atom:link
    rel="next"
    href="http://idm.api.openstack.org/v1.0/1234/tenants?
limit=1&marker=1234"/>
</tenants>
```

### Example 3.4. Tenant Collection, First Page: JSON

```
{
  "tenants": {
    "values" : [
      {
        "id": "1234",
        "description": "A description ...",
        "enabled": true
      }
    ],
    "links" : [
      {
        "rel" : "next",
        "href" : "http://idm.api.openstack.org/v1.0/1234/
tenants?limit=1&marker=1234"
      }
    ]
  }
}
```

### Example 3.5. Tenant Collection, Second Page: XML

```
<?xml version="1.0" encoding="UTF-8"?>
<tenants xmlns="http://docs.openstack.org/idm/api/v1.0"
  xmlns:atom="http://www.w3.org/2005/Atom">
  <tenant enabled="true" id="3645">
    <description>A description...</description>
  </tenant>
  <atom:link
    rel="previous"
    href="http://idm.api.openstack.org/v1.0/1234/tenants?
limit=1"/>
  <atom:link
    rel="next"
```

```

        href="http://idm.api.openstack.org/v1.0/1234/tenants?
limit=1&marker=3645"/>
</tenants>

```

### Example 3.6. Tenant Collection, Second Page: JSON

```

{
  "tenants": {
    "values" : [
      {
        "id": "3645",
        "description": "A description ...",
        "enabled": true
      }
    ],
    "links" : [
      {
        "rel" : "next",
        "href" : "http://idm.api.openstack.org/v1.0/1234/
tenants?limit=1&marker=3645"
      },
      {
        "rel" : "previous",
        "href" : "http://idm.api.openstack.org/v1.0/1234/
tenants?limit=1"
      }
    ]
  }
}

```

### Example 3.7. Tenant Collection, Last Page: XML

```

<?xml version="1.0" encoding="UTF-8"?>
<tenants xmlns="http://docs.openstack.org/idm/api/v1.0"
  xmlns:atom="http://www.w3.org/2005/Atom">
  <tenant enabled="true" id="9999">
    <description>A description...</description>
  </tenant>
  <atom:link
    rel="previous"
    href="http://idm.api.openstack.org/v1.0/1234/tenants?
limit=1&marker=1234"/>
</tenants>

```

### Example 3.8. Tenant Collection, Last Page: JSON

```

{

```

```

"tenants": {
  "values" : [
    {
      "id": "9999",
      "description": "A description ...",
      "enabled": true
    }
  ],
  "links" : [
    {
      "rel" : "previous",
      "href" : "http://idm.api.openstack.org/v1.0/1234/
tenants?limit=1&marker=1234"
    }
  ]
}

```

In the JSON representation, paginated collections contain a values property that contains the items in the collections. Links are accessed via the links property. The approach allows for extensibility of both the collection members and of the paginated collection itself. It also allows collections to be embedded in other objects as illustrated below. Here, a subset of groups are presented within a user. Clients must follow the "next" link to continue to retrieve additional groups belonging to a user.

### Example 3.9. Paginated Groups in a User: XML

```

<?xml version="1.0" encoding="UTF-8"?>
<user xmlns="http://docs.openstack.org/idm/api/v1.0"
  xmlns:atom="http://www.w3.org/2005/Atom"
  enabled="true" email="john.smith@example.org"
  tenantId="1234" id="jqsmith">
  <groups>
    <group tenantId="1234" id="Admin"/>
    <group tenantId="1234" id="DBUser"/>
    <group id="Super"/>
    <atom:link
      rel="next"
      href="http://idm.api.openstack.org/v1.0/1234/
tenants/1234/users/jqsmith/groups?marker=Super"/>
  </groups>
</user>

```

### Example 3.10. Paginated Groups in an User: JSON

```

{
  "user": {
    "groups": {
      "values": [

```

```

    {
      "tenantId" : "1234",
      "id": "Admin"
    },
    {
      "tenantId" : "1234",
      "id" : "DBUser"
    },
    {
      "id" : "Super"
    }
  ],
  "links" : [
    {
      "rel" : "next",
      "href" : "http://idm.api.openstack.org/
v1.0/1234/tenants/1234/users/jqsmith/groups?marker=Super"
    }
  ]
},
"id": "jqsmith",
"tenantId": "1234",
"email": "john.smith@example.org",
"enabled": true
}

```

## 3.4. Versions

The OpenStack IDM API uses both a URI and a MIME type versioning scheme. In the URI scheme, the first element of the path contains the target version identifier (e.g. `https://idm.api.openstack.org/v1.0/...`). The MIME type versioning scheme uses HTTP content negotiation where the `Accept` or `Content-Type` headers contains a MIME type that identifies the version (`application/vnd.openstack.idm-v1.1+xml`). A version MIME type is always linked to a base MIME type (`application/xml` or `application/json`). If conflicting versions are specified using both an HTTP header and a URI, the URI takes precedence.

### Example 3.11. Request with MIME type versioning

```

GET /tenants HTTP/1.1
Host: idm.api.openstack.org
Accept: application/vnd.openstack.idm-v1.1+xml
X-Auth-Token: eaaafd18-0fed-4b3a-81b4-663c99ec1cbb

```

### Example 3.12. Request with URI versioning

```

GET /v1.1/tenants HTTP/1.1

```

```
Host: idm.api.openstack.org
Accept: application/xml
X-Auth-Token: eaaafd18-0fed-4b3a-81b4-663c99ec1cbb
```



### Note

The MIME type versioning approach allows for the creating of permanent links, because the version scheme is not specified in the URI path: <https://api.idm.openstack.org/tenants/12234>.

If a request is made without a version specified in the URI or via HTTP headers, then a multiple-choices response (300) will follow providing links and MIME types to available versions.

### Example 3.13. Multiple Choices Response: XML

```
<?xml version="1.0" encoding="UTF-8"?>

<choices xmlns="http://docs.openstack.org/common/api/v1.0"
  xmlns:atom="http://www.w3.org/2005/Atom">

  <version id="v1.0" status="DEPRECATED">
    <media-types>
      <media-type base="application/xml"
        type="application/vnd.openstack.idm-v1.0+xml"/>
      <media-type base="application/json"
        type="application/vnd.openstack.idm-v1.0+json"/>
    </media-types>

    <atom:link rel="self"
      href="http://idm.api.openstack.org/v1.0/
tenants/12"/>
  </version>

  <version id="v1.1" status="CURRENT">
    <media-types>
      <media-type base="application/xml"
        type="application/vnd.openstack.idm-v1.1+xml"/>
      <media-type base="application/json"
        type="application/vnd.openstack.idm-v1.1+json"/>
    </media-types>

    <atom:link rel="self"
      href="http://idm.api.openstack.org/v1.1/
tenants/12"/>
  </version>
</choices>
```

**Example 3.14. Multiple Choices Response: JSON**

```

{
  "choices" : {
    "values" : [
      {
        "id" : "v1.0",
        "status" : "DEPRECATED",
        "links": [
          {
            "rel" : "self",
            "href" : "http://idm.api.openstack.org/
v1.0/tenants/12"
          }
        ],
        "media-types": {
          "values" : [
            {
              "base" : "application/xml",
              "type" : "application/
vnd.openstack.idm-v1.0+xml"
            },
            {
              "base" : "application/json",
              "type" : "application/
vnd.openstack.idm-v1.0+json"
            }
          ]
        }
      },
      {
        "id" : "v1.1",
        "status" : "CURRENT",
        "links": [
          {
            "rel" : "self",
            "href" : "http://idm.api.openstack.org/
v1.1/tenants/12"
          }
        ],
        "media-types": {
          "values" : [
            {
              "base" : "application/xml",
              "type" : "application/
vnd.openstack.idm-v1.1+xml"
            },
            {
              "base" : "application/json",
              "type" : "application/
vnd.openstack.idm-v1.1+json"
            }
          ]
        }
      }
    ]
  }
}

```



DRAFT - DRAFT - DRAFT - DRAFT - DRAFT - DRAFT - DRAFT -

DRAFT - DRAFT - DRAFT - DRAFT - DRAFT - DRAFT - DRAFT -

DRAFT - DRAFT - DRAFT - DRAFT - DRAFT - DRAFT - DRAFT -

DRAFT - DRAFT - DRAFT - DRAFT - DRAFT - DRAFT - DRAFT -

DRAFT - DRAFT - DRAFT - DRAFT - DRAFT - DRAFT - DRAFT -

DRAFT - DRAFT - DRAFT - DRAFT - DRAFT - DRAFT - DRAFT -

DRAFT - DRAFT - DRAFT - DRAFT - DRAFT - DRAFT - DRAFT -

DRAFT - DRAFT - DRAFT - DRAFT - DRAFT - DRAFT - DRAFT -

DRAFT - DRAFT - DRAFT - DRAFT - DRAFT - DRAFT - DRAFT -

DRAFT - DRAFT - DRAFT - DRAFT - DRAFT - DRAFT - DRAFT -

```

        updated="2010-12-12T18:30:02.25Z">
        <atom:link rel="self"
            href="http://idm.api.openstack.org/v1.1/">
    </version>
</versions>

```

### Example 3.17. Versions List Response: Atom

```

<?xml version="1.0" encoding="UTF-8"?>
<feed xmlns="http://www.w3.org/2005/Atom">
    <title type="text">Available API Versions</title>
    <updated>2010-12-12T18:30:02.25Z</updated>
    <id>http://idm.api.openstack.org/</id>
    <author><name>Rackspace</name><uri>http://www.rackspace.com/</
uri></author>
    <link rel="self" href="http://idm.api.openstack.org/">
    <entry>
        <id>http://idm.api.openstack.org/v1.1/</id>
        <title type="text">Version v1.1</title>
        <updated>2010-12-12T18:30:02.25Z</updated>
        <link rel="self" href="http://idm.api.openstack.org/v1.1/"
>
        <content type="text">Version v1.1 CURRENT
(2010-12-12T18:30:02.25Z)</content>
    </entry>
    <entry>
        <id>http://idm.api.openstack.org/v1.0/</id>
        <title type="text">Version v1.0</title>
        <updated>2009-10-09T11:30:00Z</updated>
        <link rel="self" href="http://idm.api.openstack.org/v1.0/"
>
        <content type="text">Version v1.0 DEPRECATED
(2009-10-09T11:30:00Z)</content>
    </entry>
</feed>

```

### Example 3.18. Versions List Response: JSON

```

{
    "versions" : {
        "values" : [
            {
                "id" : "v1.0",
                "status" : "DEPRECATED",
                "updated" : "2009-10-09T11:30:00Z",
                "links": [

```

```

        {
            "rel" : "self",
            "href" : "http://idm.api.openstack.org/
v1.0/"
        }
    ],
    {
        "id" : "v1.1",
        "status" : "CURRENT",
        "updated" : "2010-12-12T18:30:02.25Z",
        "links": [
            {
                "rel" : "self",
                "href" : "http://idm.api.openstack.org/
v1.1/"
            }
        ]
    }
]
}

```

You can also obtain additional information about a specific version by performing a **GET** on the base version URL (e.g. <https://idm.api.openstack.org/v1.1/>). Version request URLs should always end with a trailing slash (/). If the slash is omitted, the server may respond with a 302 redirection request. Format extensions may be placed after the slash (e.g. <https://idm.api.openstack.org/v1.1.xml>). Note that this is a special case that does not hold true for other API requests. In general, requests such as `/tenants.xml` and `/tenants/.xml` are handled equivalently.

### Example 3.19. Version Details Request

```

GET HTTP/1.1
Host: idm.api.openstack.org/v1.1/

```

Normal Response Code(s):200, 203

Error Response Code(s): badRequest (400), idmFault (500), serviceUnavailable(503)

This operation does not require a request body.

### Example 3.20. Version Details Response: XML

```

<?xml version="1.0" encoding="UTF-8"?>
<version xmlns="http://docs.openstack.org/common/api/v1.0"
        xmlns:atom="http://www.w3.org/2005/Atom"

        id="v1.0" status="CURRENT" updated="2011-01-21T11:33:21-06:00">

```

```

    <media-types>
      <media-type base="application/xml"
        type="application/vnd.openstack.idm-v1.0+xml"/>
      <media-type base="application/json"
        type="application/vnd.openstack.idm-v1.0+json"/>
    </media-types>

    <atom:link rel="self"
      href="http://idm.api.openstack.org/v1.0/">

    <atom:link rel="describedby"
      type="application/pdf"
      href="http://docs.rackspacecloud.com/idm/api/v1.0/
idm-devguide-20110125.pdf" />

    <atom:link rel="describedby"
      type="application/vnd.sun.wadl+xml"
      href="http://docs.rackspacecloud.com/idm/api/v1.0/
application.wadl" />
  </version>

```

### Example 3.21. Version Details Response: Atom

```

<?xml version="1.0" encoding="UTF-8"?>
<feed xmlns="http://www.w3.org/2005/Atom">
  <title type="text">About This Version</title>
  <updated>2011-01-21T11:33:21-06:00</updated>
  <id>http://idm.api.openstack.org/v1.0/</id>
  <author><name>Rackspace</name><uri>http://www.rackspace.com/</
uri></author>
  <link rel="self" href="http://idm.api.openstack.org/v1.0/">
  <entry>
    <id>http://idm.api.openstack.org/v1.0/</id>
    <title type="text">Version v1.0</title>
    <updated>2011-01-21T11:33:21-06:00</updated>
    <link rel="self" href="http://idm.api.openstack.org/v1.0/">
    <link rel="describedby" type="application/pdf"
      href="http://docs.rackspacecloud.com/idm/api/v1.0/idm-
devguide-20110125.pdf"/>
    <link rel="describedby" type="application/vnd.sun.wadl+xml"
      href="http://docs.rackspacecloud.com/idm/api/v1.0/
application.wadl"/>
    <content type="text">Version v1.0 CURRENT
(2011-01-21T11:33:21-06:00)</content>
  </entry>
</feed>

```

**Example 3.22. Version Details Response: JSON**

```

{
  "version" : {
    "id" : "v1.0",
    "status" : "CURRENT",
    "updated" : "2011-01-21T11:33:21-06:00",
    "links": [
      {
        "rel" : "self",
        "href" : "http://idm.api.openstack.org/v1.0/"
      },
      {
        "rel" : "describedby",
        "type" : "application/pdf",
        "href" : "http://docs.rackspacecloud.com/idm/api/v1.0/idm-devguide-20110125.pdf"
      },
      {
        "rel" : "describedby",
        "type" : "application/vnd.sun.wadl+xml",
        "href" : "http://docs.rackspacecloud.com/idm/api/v1.0/application.wadl"
      }
    ],
    "media-types": [
      {
        "base" : "application/xml",
        "type" : "application/vnd.openstack.idm-v1.0+xml"
      },
      {
        "base" : "application/json",
        "type" : "application/vnd.openstack.idm-v1.0+json"
      }
    ]
  }
}

```

The detailed version response contains pointers to both a human-readable and a machine-processable description of the API service. The machine-processable description is written in the Web Application Description Language (WADL).

**Note**

If there is a discrepancy between the two specifications, the WADL is authoritative as it contains the most accurate and up-to-date description of the API service.

## 3.5. Extensions

The OpenStack IDM API is extensible. Extensions serve two purposes: They allow the introduction of new features in the API without requiring a version change and they allow the introduction of vendor specific niche functionality. Applications can programmatically determine what extensions are available by performing a **GET** on the /extensions URI. Note that this is a versioned request — that is, an extension available in one API version may not be available in another.

Verb	URI	Description
GET	/extensions	Returns a list of available extensions

Normal Response Code(s):200, 203

Error Response Code(s): badRequest (400), idmFault (500), serviceUnavailable(503)

This operation does not require a request body.

Each extension is identified by two unique identifiers, a namespace and an alias. Additionally an extension contains documentation links in various formats.

### Example 3.23. Extensions Response: XML

```
<?xml version="1.0" encoding="UTF-8"?>

<extensions xmlns="http://docs.openstack.org/common/api/v1.0"
  xmlns:atom="http://www.w3.org/2005/Atom">
  <extension
    name="Reset Password Extension"
    namespace="http://docs.rackspacecloud.com/idm/api/ext/rpe/
v1.0"
    alias="RS-RPE"
    updated="2011-01-22T13:25:27-06:00">

    <description>
      Adds the capability to reset a user's password. The
      user is
      emailed when the password has been reset.
    </description>

    <atom:link rel="describedby"
      type="application/pdf"
      href="http://docs.rackspacecloud.com/idm/api/
ext/idm-rpe-20111111.pdf"/>
    <atom:link rel="describedby"
      type="application/vnd.sun.wadl+xml"
      href="http://docs.rackspacecloud.com/idm/api/
ext/idm-rpe.wadl"/>
    </extension>
  </extension>
```

```

        name="User Metadata Extension"
        namespace="http://docs.rackspacecloud.com/idm/api/ext/
meta/v1.0"
        alias="RS-META"
        updated="2011-01-12T11:22:33-06:00">
        <description>
            Allows associating arbitrary metadata with a user.
        </description>

        <atom:link rel="describedby"
            type="application/pdf"
            href="http://docs.rackspacecloud.com/idm/api/
ext/idm-meta-20111201.pdf"/>
        <atom:link rel="describedby"
            type="application/vnd.sun.wadl+xml"
            href="http://docs.rackspacecloud.com/idm/api/
ext/idm-meta.wadl"/>
        </extension>
    </extensions>

```

### Example 3.24. Extensions Response: JSON

```

{
  "extensions" : [
    {
      "name" : "Reset Password Extension",
      "namespace" : "http://docs.rackspacecloud.com/idm/api/
ext/rpe/v1.0",
      "alias" : "RS-RPE",
      "updated" : "2011-01-22T13:25:27-06:00",
      "description" : "Adds the capability to reset a
user's password. The user is emailed when the password has been
reset.",
      "links" : [
        {
          "rel" : "describedby",
          "type" : "application/pdf",
          "href" : "http://docs.rackspacecloud.com/idm/
api/ext/idm-rpe-20111111.pdf"
        },
        {
          "rel" : "describedby",
          "type" : "application/vnd.sun.wadl+xml",
          "href" : "http://docs.rackspacecloud.com/idm/
api/ext/idm-rpe.wadl"
        }
      ]
    },
    {

```

```

        "name" : "User Metadata Extension",
        "namespace" : "http://docs.rackspacecloud.com/idm/api/
ext/meta/v1.0",
        "alias" : "RS-META",
        "updated" : "2011-01-12T11:22:33-06:00",
        "description" : "Allows associating arbitrary
metadata with a user.",
        "links" : [
            {
                "rel" : "describedby",
                "type" : "application/pdf",
                "href" : "http://docs.rackspacecloud.com/idm/
api/ext/idm-meta-20111201.pdf"
            },
            {
                "rel" : "describedby",
                "type" : "application/vnd.sun.wadl+xml",
                "href" : "http://docs.rackspacecloud.com/idm/
api/ext/idm-cbs.wadl"
            }
        ]
    }
]
}

```

Extensions may also be queried individually by their unique alias. This provides the simplest method of checking if an extension is available as an unavailable extension will issue an `itemNotFound` (404) response.

Verb	URI	Description
GET	<code>/extensions/<i>alias</i></code>	Return details of a single extension

Normal Response Code(s): 200, 203

Error Response Code(s): `itemNotFound` (404), `badRequest` (400), `idmFault` (500), `serviceUnavailable`(503)

This operation does not require a request body.

### Example 3.25. Extension Response: xml

```

<?xml version="1.0" encoding="UTF-8"?>

<extension xmlns="http://docs.openstack.org/common/api/v1.0"
  xmlns:atom="http://www.w3.org/2005/Atom"
  name="User Metadata Extension"
  namespace="http://docs.rackspacecloud.com/idm/api/ext/
meta/v1.0"
  alias="RS-META"
  updated="2011-01-12T11:22:33-06:00">

```



```

<description>
  Allows associating arbitrary metadata with a user.
</description>

<atom:link rel="describedby"
           type="application/pdf"
           href="http://docs.rackspacecloud.com/idm/api/ext/
idm-meta-20111201.pdf"/>
  <atom:link rel="describedby"
           type="application/vnd.sun.wadl+xml"
           href="http://docs.rackspacecloud.com/idm/api/ext/
idm-meta.wadl"/>

</extension>

```

### Example 3.26. Extensions Response: JSON

```

{
  "extension" : {
    "name" : "User Metadata Extension",
    "namespace" : "http://docs.rackspacecloud.com/idm/api/ext/
meta/v1.0",
    "alias" : "RS-META",
    "updated" : "2011-01-12T11:22:33-06:00",
    "description" : "Allows associating arbitrary metadata with
a user.",
    "links" : [
      {
        "rel" : "describedby",
        "type" : "application/pdf",
        "href" : "http://docs.rackspacecloud.com/idm/api/
ext/idm-meta-20111201.pdf"
      },
      {
        "rel" : "describedby",
        "type" : "application/vnd.sun.wadl+xml",
        "href" : "http://docs.rackspacecloud.com/idm/api/
ext/idm-cbs.wadl"
      }
    ]
  }
}

```

Extensions may define new data types, parameters, actions, headers, states, and resources. In XML, additional elements and attributes may be defined. These elements must be defined in the extension's namespace. In JSON, the alias must be used. The volumes element in the Examples 3.27 and 3.28 is defined in the RS-META namespace. Extended

headers are always prefixed with X- followed by the alias and a dash: (X-RS-META-HEADER1). Parameters must be prefixed with the extension alias followed by a colon.



### Important

Applications should be prepared to ignore response data that contains extension elements. Also, applications should also verify that an extension is available before submitting an extended request.

#### Example 3.27. Extended User Response: XML

```
<?xml version="1.0" encoding="UTF-8"?>
<user xmlns="http://docs.openstack.org/oidm/api/v1.0"
      enabled="true" email="john.smith@example.org"
      tenantId="1234" id="jqsmith">
  <groups>
    <group tenantId="1234" id="Admin"/>
  </groups>
  <metadata
    xmlns="http://docs.rackspacecloud.com/oidm/api/ext/meta/
v1.0">
    <meta key="MetaKey1">MetaValue1</meta>
    <meta key="MetaKey2">MetaValue2</meta>
  </metadata>
</user>
```

#### Example 3.28. Extended User Response: JSON

```
{ "user":
  {
    "groups": {
      "values": [
        {
          "tenantId" : "1234",
          "id": "Admin"
        }
      ],
      "id": "jqsmith",
      "tenantId": "1234",
      "email": "john.smith@example.org",
      "enabled": true,
      "RS-META:metadata" : {
        "values" : {
          "MetaKey1" : "MetaValue1",
          "MetaKey2" : "MetaValue2"
        }
      }
    }
  }
}
```

## 3.6. Faults

When an error occurs the system will return an HTTP error response code denoting the type of error. The system will also return additional information about the fault in the body of the response.

### Example 3.29. XML Fault Response

```
<?xml version="1.0" encoding="UTF-8"?>
<idmFault xmlns="http://docs.openstack.org/idm/api/v1.0"
  code="500">
  <message>Fault</message>
  <details>Error Details...</details>
</idmFault>
```

### Example 3.30. JSON Fault Response

```
{ "idmFault":
  {
    "message": "Fault",
    "details": "Error Details...",
    "code": 500
  }
}
```

The error code is returned in the body of the response for convenience. The message section returns a human readable message. The details section is optional and may contain useful information for tracking down an error (e.g a stack trace).

The root element of the fault (e.g. idmFault) may change depending on the type of error. The following is an example of an itemNotFound error.

### Example 3.31. XML Not Found Fault

```
<?xml version="1.0" encoding="UTF-8"?>
<itemNotFound xmlns="http://docs.openstack.org/idm/api/v1.0"
  code="404">
  <message>Item not found.</message>
  <details>Error Details...</details>
</itemNotFound>
```

### Example 3.32. JSON Not Found Fault

```
{ "itemNotFound":
  {
```

```
    "message": "Item not found.",  
    "details": "Error Details...",  
    "code": 404  
  }  
}
```

The following is a list of possible fault types along with their associated error codes.

**Table 3.3. Fault Types**

Fault Element	Associated Error Code	Expected in All Requests
idmFault	500, 400	✓
serviceUnavailable	503	✓
badRequest	400	✓
unauthorized	401	✓
overLimit	413	
userDisabled	403	
forbidden	403	
itemNotFound	404	
tenantConflict	409	

From an XML schema perspective, all API faults are extensions of the base fault type `idmFault`. When working with a system that binds XML to actual classes (such as JAXB), one should be capable of using `idmFault` as a “catch-all” if there's no interest in distinguishing between individual fault types.

## 4. Service Developer Operations

### 4.1. Overview

The operations described in this chapter allow service developers to get and validate access tokens, manage users, and manage tenants.

### 4.2. Token Operations

#### 4.2.1. Authenticate

Verb	URI	Description
POST	/token	Authenticate to generate a token.

Normal Response Code(s):200, 203

Error Response Code(s): unauthorized (401), userDisabled (403), badRequest (400), idmFault (500), serviceUnavailable(503)

TenantID is optional and may be used to specify that a token should be returned that has access for resources that particular tenant.

##### Example 4.1. XML Auth Request

```
<?xml version="1.0" encoding="UTF-8"?>
<passwordCredentials
  xmlns="http://docs.openstack.org/idm/api/v1.0"
  password="P@ssword1" username="testuser"
  tenantId="77654"/>
```

##### Example 4.2. JSON Auth Request

```
{
  "passwordCredentials" : {
    "username" : "test_user",
    "password" : "a86850deb2742ec3cb41518e26aa2d89",
    "tenantId" : "77654"
  }
}
```

##### Example 4.3. XML Auth Response

```
<?xml version="1.0" encoding="UTF-8"?>
<auth xmlns="http://docs.openstack.org/idm/api/v1.0">
  <token expires="2010-11-01T03:32:15-05:00">
```

```
        id="ab48a9efdfedb23ty3494"/>
<user tenantId="1245" username="jqsmith">
  <groups>
    <group tenantId="1245" id="Admin"/>
  </groups>
</user>
</auth>
```

Example 4.4. JSON Auth Response

```
{
  "auth" : {
    "token" : {
      "id": "ab48a9efdfedb23ty3494",
      "expires": "2010-11-01T03:32:15-05:00"
    },
    "user" : {
      "groups": {
        "group": [
          {
            "tenantId" : "1234",
            "id": "Admin"
          }
        ]
      },
      "username": "jqsmith",
      "tenantId": "1234"
    }
  }
}
```

4.2.2. Validate Token

Verb	URI	Description
GET	/token/tokenId?belongsTo=tenantId	Check that a token is valid and that it belongs to a particular user and return the permissions relevant to a particular client.

Normal Response Code(s):200, 203

Error Response Code(s): unauthorized (401), forbidden (403), userDisabled(403), badRequest (400), itemNotFound (404), idmFault(500), serviceUnavailable(503)

This operation does not require a request body.

Example 4.5. XML Validate Token Response

```
<?xml version="1.0" encoding="UTF-8"?>
<auth xmlns="http://docs.openstack.org/oidm/api/v1.0">
  <token expires="2010-11-01T03:32:15-05:00"
```

```
        id="ab48a9efdfedb23ty3494"/>
<user tenantId="1245" username="jqsmith">
  <groups>
    <group tenantId="1245" name="Admin"/>
  </groups>
</user>
</auth>
```

#### Example 4.6. JSON Validate Token Response

```
{
  "auth" : {
    "token" : {
      "id": "ab48a9efdfedb23ty3494",
      "expires": "2010-11-01T03:32:15-05:00"
    },
    "user" : {
      "groups": {
        "group": [
          {
            "tenantId" : "1234",
            "name": "Admin"
          }
        ]
      },
      "username": "jqsmith",
      "tenantId": "1234",
    }
  }
}
```

### 4.2.3. Revoke Token

Verb	URI	Description
DELETE	/token/ <i>tokenId</i>	Revoke an existing token.

Normal Response Code(s):204

Error Response Code(s): unauthorized (401), forbidden (403), userDisabled(403), badRequest (400), itemNotFound (404), idmFault(500), serviceUnavailable(503)

This operation does not require a request body.

## 4.3. Tenant Operations

### 4.3.1. Create a Tenant

Verb	URI	Description
POST	/tenants	Create a tenant

Normal Response Code(s):201

Error Response Code(s): unauthorized (401), forbidden(403), badRequest (400), idmFault (500), serviceUnavailable(503)

#### Example 4.7. XML Tenant Create Request

```
<?xml version="1.0" encoding="UTF-8"?>
<tenant xmlns="http://docs.openstack.org/idm/api/v1.0"
  enabled="true" id="1234">
  <description>A description...</description>
</tenant>
```

#### Example 4.8. JSON Tenant Create Request

```
{ "tenant":
  {
    "id": "1234",
    "description": "A description ...",
    "enabled": true
  }
}
```

#### Example 4.9. XML Tenant Create Response

```
<?xml version="1.0" encoding="UTF-8"?>
<tenant xmlns="http://docs.openstack.org/idm/api/v1.0"
  enabled="true" id="1234">
  <description>A description...</description>
</tenant>
```

#### Example 4.10. JSON Tenant Create Response

```
{ "tenant":
  {
    "id": "1234",
    "description": "A description ...",
    "enabled": true
  }
}
```

### 4.3.2. Get Tenants

Verb	URI	Description
GET	/tenants	Get a list of tenants.



Normal Response Code(s):200, 203

Error Response Code(s): unauthorized (401), forbidden(403), overLimit(413), badRequest (400), idmFault (500), serviceUnavailable(503)

The operation returns a list of tenants. The list may be filtered to return only those tenants which the caller has access to.

This operation does not require a request body.

#### Example 4.11. XML Tenants Response

```
<?xml version="1.0" encoding="UTF-8"?>
<tenants xmlns="http://docs.openstack.org/identity/api/v1.0">
  <tenant enabled="true" id="1234">
    <description>A description...</description>
  </tenant>
  <tenant enabled="true" id="3645">
    <description>A description...</description>
  </tenant>
</tenants>
```

#### Example 4.12. JSON Tenants Response

```
{ "tenants": {
  "values" : [
    {
      "id": "1234",
      "description": "A description ...",
      "enabled": true
    },
    {
      "id": "3456",
      "description": "A description ...",
      "enabled": true
    }
  ]
}
```

### 4.3.3. Get a Tenant

Verb	URI	Description
GET	/tenants/ <i>tenantId</i>	Get a tenant.

Normal Response Code(s):200, 203

Error Response Code(s): unauthorized (401), forbidden(403), itemNotFound(404), badRequest (400), idmFault (500), serviceUnavailable(503)

This operation does not require a request body.

#### Example 4.13. XML Tenant Response

```
<?xml version="1.0" encoding="UTF-8"?>
<tenant xmlns="http://docs.openstack.org/idm/api/v1.0"
        enabled="true" id="1234">
  <description>A description...</description>
</tenant>
```

#### Example 4.14. JSON Tenant Response

```
{ "tenant":
  {
    "id": "1234",
    "description": "A description ...",
    "enabled": true
  }
}
```

### 4.3.4. Update a Tenant

Verb	URI	Description
PUT	/tenants/ <i>tenantId</i>	Update a tenant..

Normal Response Code(s):200

Error Response Code(s): unauthorized (401), forbidden(403), itemNotFound(404), badRequest (400), idmFault (500), serviceUnavailable(503)

#### Example 4.15. XML Tenant Update Request

```
<?xml version="1.0" encoding="UTF-8"?>
<tenant xmlns="http://docs.openstack.org/idm/api/v1.0">
  <description>A NEW description...</description>
</tenant>
```

#### Example 4.16. JSON Tenant Update Request

```
{ "tenant":
  {
    "description": "A NEW description..."
  }
}
```

### Example 4.17. XML Tenant Update Response

```
<?xml version="1.0" encoding="UTF-8"?>
<tenant xmlns="http://docs.openstack.org/identity/api/v1.0"
  enabled="true" id="1234">
  <description>A NEW description...</description>
</tenant>
```

### Example 4.18. JSON Tenant Update Response

```
{ "tenant":
  {
    "id": "1234",
    "description": "A NEW description...",
    "enabled": true
  }
}
```

## 4.3.5. Delete a Tenant

Verb	URI	Description
DELETE	/tenants/ <i>tenantId</i>	Delete a Tenant.

Normal Response Code(s):204

Error Response Code(s): unauthorized (401), badRequest (400), forbidden (403), itemNotFound (404), idmFault (500), serviceUnavailable(503)

This operation does not require a request body.