

Sinusoidal plus Residual Modeling

Xavier Serra

Music Technology Group

Universitat Pompeu Fabra, Barcelona

<http://mtg.upf.edu>

Index

- Sinusoidal plus residual model
- Sinusoidal subtraction
- Stochastic modeling
- Stochastic approximation of residual
- Implementation

Sinusoidal plus Residual model

$$y[n] = \sum_{r=1}^R A_r[n] \cos(2\pi f_r[n]n) + yr[n]$$

R : number of sinusoidal components

$A_r[n]$: instantaneous amplitude

$f_r[n]$: instantaneous frequency

$yr[n]$: residual signal

when $yr[n]$ is a stochastic signal, it can be modeled as filtered white noise:

$$yr_l[n] = ys_l[n] = \sum_{k=0}^{N-1} u[n] h_l[n-k]$$

$u[n]$: white noise

$h[n]$: impulse response of filter

l : frame number

otherwise:
$$yr[n] = x[n] - \sum_{r=1}^R A_r[n] \cos(2\pi f_r[n]n)$$

Spectral view of model

$$Y_l[k] = \sum_{r=1}^{R_l} A_{(r,l)} W[k - \hat{f}_{(r,l)}] + Yr_l[k]$$

W : spectrum of analysis window

R_l : number of sinusoidal components

$A_{(r,l)}$: Amplitude of sinusoid

$\hat{f}_{(r,l)}$: Normalized frequency of sinusoid

Yr_l : residual spectrum

l : frame number

when $e[n]$ is an stochastic signal, it can be modeled as filtered white noise:


$$Yr_l[k] = Ys_l[k] = U[k] H_l[k]$$

U : white noise spectrum


H_l : frequency response of filter




otherwise: $Yr_l[k] = X_l[k] - Y_l[k]$




X spectrogram + peaks ("sax-phrase-short.wav")











X residual spectrogram










```

xw = x[pin-hM1:pin+hM2] * w
fftbuffer[:hM1] = xw[hM2:]
fftbuffer[N-hM2:] = xw[:hM2]
X = fft(fftbuffer)
mX = 20 * np.log10(abs(X[:hN]))
ploc = PP.peakDetection(mX, hN, t)
pX = np.unwrap(np.angle(X[:hN]))
iploc, ipmag, ipphase = PP.peakInterp(mX, pX, ploc)
iploc = (iploc!=0) * (iploc*Ns/N)
ri = pin-hNs-1
xr = x[ri:ri+Ns]*wr
fftbuffer[:hNs] = xr[hNs:]
fftbuffer[hNs:] = xr[:hNs]
Xr = fft(fftbuffer)
Ys = GS.genSpecSines(iploc, ipmag, ipphase, Ns)
Yr = Xr-Ys;
fftbuffer = np.real(ifft(Ys))
ysw[:hNs-1] = fftbuffer[hNs+1:]
ysw[hNs-1:] = fftbuffer[:hNs+1]
fftbuffer = np.real(ifft(Yr))
yrw[:hNs-1] = fftbuffer[hNs+1:]
yrw[hNs-1:] = fftbuffer[:hNs+1]

```

Stochastic signals

- Stochastic processes
 - described by the laws of probability, mean, variance, probability distributions

- Autocorrelation

$$Z_{xx}[k] = \sum_{n=0}^{N-1-k} x[n]x[n+k] \quad k = -N+1, \dots, N-1$$

- Power spectral density

$$Xp[k] = \lim_{N \rightarrow \infty} |X[k]|^2$$

$$\text{where } X[k] = \sum_{n=0}^{N-1} x[n]e^{-j2\pi kn/N} \quad k = 0, \dots, N-1$$

Stochastic modeling

$$y_S[n] = \sum_{k=0}^{N-1} u[n] h[n-k]$$

$u[n]$: white noise

$h[n]$: impulse response of filter


Spectral view:

$$Y_{S_l}[k] = |\tilde{X}_l[k]| e^{\angle U[k]}$$


$|\tilde{X}[k]|$: approximation of magnitude spectrum of input signal

$\angle U[k]$: spectral phases of noise


l : frame number




mX (blue), mY (red)



pX (blue), pY (red)



yw



```

def stochasticModel(x, w, N, H, stocf) :
    hN = N/2
    hM = (w.size)/2
    pin = hM
    pend = x.size-hM
    yw = np.zeros(w.size)
    y = np.zeros(x.size)
    w = w / sum(w)
    ws = hanning(w.size)*2
    while pin<pend:
        xw = x[pin-hM:pin+hM] * w
        X = fft(xw)
        mX = 20 * np.log10( abs(X[:hN]) )
        mXenv = resample(np.maximum(-200, mX), mX.size*stocf)
        mY = resample(mXenv, hN)
        pY = 2*np.pi*np.random.rand(hN)
        Y[:hN] = 10**(mY/20) * np.exp(1j*pY)
        Y[hN+1:] = 10**(mY[:0:-1]/20) * np.exp(-1j*pY[:0:-1])
        fftbuffer = np.real(ifft(Y))
        y[pin-hM:pin+hM] += H*ws*fftbuffer
        pin += H
    return y

```


Stochastic modeling of residual

$$y[n] = \sum_{r=1}^R A_r[n] \cos(2\pi f_r[n]n) + y_s[n]$$

R : number of sinusoidal components

$A_r[n]$: instantaneous amplitude

$f_r[n]$: instantaneous frequency

$y_s[n]$: stochastic signal

Spectral

view:

$$Y_{S_l}[k] = |\tilde{X}r_l[k]| e^{\angle U[k]}$$

$|\tilde{X}r_l[k]|$: approximation of magnitude spectrum of input signal

$\angle U[k]$: spectral phases of noise

l : frame number

IIR model of residual



$$\text{LPC model: } y[n] = \sum_{k=1}^K a_k x[n-k] + Au[n]$$

$$\hat{x}[n] = -\sum_{k=1}^K a_k x[n-k]$$


$$e[n] = x[n] - \hat{x}[n] = x[n] + \sum_{k=1}^K a_k x[n-k]$$

$$E = \sum_{n=-\infty}^{\infty} e[n]^2 = \sum_{n=-\infty}^{\infty} \left(x[n] + \sum_{k=1}^K a_k x[n-k] \right)^2$$


The error is minimized by minimizing the mean of the total squared error with respect to each of the parameters.




X spectrogram + peaks



X residual spectrogram




X residual stochastic approx. spectrogram




Residual synthesis

- Noise generation:
 - Algorithms for random number generation
 - White noise, other types of noises
 - Gaussian noise




direct form
structure




lattice
structure

Noise synthesis using IFFT



Implementation: HpS model



References

- https://ccrma.stanford.edu/~jos/sasp/Spectrum_Analysis_Sinusoids.html
- http://en.wikipedia.org/wiki/Stochastic_process
- http://en.wikipedia.org/wiki/Linear_predictive_coding
- Sounds: <http://www.freesound.org/people/xserra/packs/13038/>

Credits

All the slides of this presentation are released under an Attribution-Noncommercial-Share Alike license.