SIMATS ENGINEERING (SAVEETHA SCHOOL OF ENGINEERING)

Department of Computer Science and Engineering

CO1 ASSESSMENT TOOL 1 – Case Study Analysis

Course Code:	CSA10 / CSA1021	**Course Title:**	Software Engineering
CO Assessed:	CO1	**Assessment:**	Assessment Tool 1 – Case Study Analysis
Weightage:	20%	**Total Marks:**	25
CO1 Statement:	*Apply advanced methodologies and agile project management techniques to manage software projects effectively*		
Student Name:	P.Vishwa Nandan	**Reg. No.:**	192473015
Date:	10-10-2026	**Duration:**	60 minutes

Code of Conduct

I P.Vishwa Nandan *(Name / Reg No) certify that this submission is my original work and that I have adhered to the guidelines specified for this assessment. I understand that any violation of academic integrity rules will result in disciplinary action.*

Signature of the Student: vishwanandan

Annexure A – Case Study Analysis

Instructions to Students:

Each student will be allotted **one problem statement**. Analyze the assigned problem systematically by following the steps given below. Your report should demonstrate your understanding of software engineering concepts and your ability to design an appropriate software solution.

Based on your allotted problem statement, prepare a report by answering the following questions:

1. **Understand the Problem Statement**
   - Explain the problem in your own words.
   - Identify the objectives of the proposed system.
   - State the scope of the problem.
2. **Identify Key Stakeholders and Challenges**
   - Identify all the stakeholders involved in the system.
   - Explain the roles and responsibilities of each stakeholder.
   - Discuss the major challenges and issues faced by the stakeholders.
3. **Analyze the Current Approach**
   - Describe the existing system or current process.
   - Identify its strengths and limitations.
   - Analyze the problems or gaps that need to be addressed.
4. **Propose a Suitable Solution Using Software Engineering Principles**
   - Design a software-based solution for the given problem.
   - Describe the major functional modules of the proposed system.
   - Identify the functional and non-functional requirements.
   - Explain how software engineering principles such as modularity, scalability, maintainability, reliability, usability, and security are incorporated into your solution.
5. **Justify the Chosen Methodology/Framework**

- Select an appropriate Software Development Life Cycle (SDLC) model or software development framework (e.g., Agile, Scrum, Waterfall, Spiral, DevOps).
- Justify why the selected methodology/framework is suitable for the proposed system.
- Explain how it supports successful project development and maintenance.

6. **Discuss Expected Outcomes and Limitations**
   - Describe the expected benefits of the proposed solution.
   - Explain how the solution addresses the identified challenges.
   - Discuss potential risks, implementation challenges, and limitations.
   - Suggest possible future enhancements.

Rubrics for Calculation

Criteria	Excellent (5 Marks)	Good (3 Marks)	Satisfactory (2 Marks)	Needs Improvement (1 Mark)
Problem Understanding (30%)	Clearly explains the problem, objectives, and scope with complete understanding.	Explains the problem with minor omissions.	Basic understanding with limited explanation.	Poor understanding; objectives and scope are unclear or missing.
Stakeholder & Challenge Analysis (25%)	Identifies all stakeholders, their roles, and challenges with clear analysis.	Identifies most stakeholders and challenges with adequate analysis.	Identifies only a few stakeholders or challenges.	Stakeholders and system analysis are incomplete or inaccurate.
Current System Analysis (20%)	Thoroughly analyzes the existing system, strengths, weaknesses, and identifies all gaps.	Good analysis with most strengths and weaknesses identified.	Limited analysis with partial identification of issues.	Proposed solution is unclear or inappropriate; requirements are largely missing.
Proposed Software Solution & Software Engineering Principles (15%)	Proposes an innovative, feasible solution applying appropriate software engineering principles (modularity, scalability, maintainability, security, etc.).	Suitable solution with good application of software engineering principles.	Basic solution with limited application of software engineering principles.	Methodology is inappropriate, poorly justified, or not discussed.
Methodology/ Framework Justification	Selects the most suitable SDLC/model/fram	Suitable methodology selected with	Methodology selected but justification is	Outcomes, limitations, or future enhancements

(10%)	ework and provides strong technical justification.	adequate justification.	weak.	are missing; report lacks organization and clarity.

Criteria	**Mark**
Problem Understanding (30%)	/5
Stakeholder & Challenge Analysis (25%)	/5
Current System Analysis (20%)	/5
Proposed Software Solution & Software Engineering Principles (15%)	/5
Methodology/ Framework Justification (10%)	/5
TOTAL	/25

Industry Context:

Deep-sea mining is an emerging field aimed at collecting valuable battery metals (like cobalt and nickel) from the ocean floor. However, scraping the seabed stirs up massive clouds of sediment (turbidity plumes) that can suffocate marine life if they drift outside the mining zone. Environmental protection rules require mining companies to track these sediment plumes continuously and stop operations immediately if they cross strict safety boundaries.

Problem Statement:

Design and develop a fault-tolerant Deep-Sea Mining Environmental Compliance System that tracks underwater sediment plumes and enforces environmental boundaries. The system architecture must coordinate fleets of surface buoys and autonomous underwater drones. It must ingest real-time data streams—including water turbidity, current direction variables, acoustic sound profiles, and tool depth coordinates—to manage compliance checks.

1. Understand the Problem Statement

1.1 Introduction

Deep-sea mining is an emerging industry that extracts valuable metals, such as cobalt and nickel, from the ocean floor. These metals are used in batteries, electric vehicles, and other technologies. However, mining activities disturb the seabed and create sediment clouds known as **turbidity plumes**.

These sediment plumes can spread beyond the permitted mining area and affect marine organisms, water quality, and underwater ecosystems. Therefore, mining companies must continuously monitor the underwater environment and stop mining operations whenever environmental safety boundaries are crossed.

The proposed Deep-Sea Mining Environmental Compliance System is a fault-tolerant software system that collects real-time environmental data from surface buoys and autonomous underwater drones. It analyzes the collected data, detects environmental risks, generates alerts, and initiates mining shutdown procedures when necessary.

The system is designed to continue monitoring and enforcing safety rules even when individual sensors, communication links, or software components fail.

1.2 Problem Explanation

The main problem is that sediment plumes created during deep-sea mining can spread unpredictably because of underwater currents and changing environmental conditions.

Monitoring this movement is difficult because mining operations take place deep underwater, where communication is limited and environmental conditions change continuously.

The proposed system coordinates multiple surface buoys and autonomous underwater drones to collect and analyze the following real-time data:

1. **Water turbidity:** Measures the cloudiness of water caused by suspended particles.
2. **Current direction and speed:** Helps estimate the movement and spread of sediment plumes.
3. **Acoustic sound profiles:** Provide underwater acoustic information that can support environmental monitoring and identify unusual underwater conditions.
4. **Tool depth coordinates:** Identify the depth and position of mining equipment.
5. **Device health information:** Indicates whether sensors, drones, buoys, and communication systems are functioning correctly.

The software compares environmental measurements with approved safety boundaries. If a plume crosses a permitted boundary or another defined safety condition occurs, the system alerts the operators and initiates the required mining shutdown procedure.

1.3 Objectives of the Proposed System

The main objectives are:

1. To continuously monitor underwater sediment plumes using surface buoys and autonomous underwater drones.
2. To collect and process real-time environmental data from multiple sensors.

3. To identify sediment plume movement and predict potential boundary violations.
4. To detect environmental safety violations and immediately notify mining operators.
5. To automatically initiate a safe shutdown when defined compliance conditions are violated.
6. To maintain reliable monitoring when individual sensors or communication links fail.
7. To securely store environmental measurements, alerts, shutdown events, and compliance reports.
8. To help mining companies demonstrate compliance with environmental regulations.

1.4 Scope of the Problem

The scope of the proposed system includes:

1. Monitoring environmental conditions around the authorized mining area.
2. Coordinating multiple surface buoys and autonomous underwater drones.
3. Collecting, validating, processing, and storing sensor data.
4. Displaying environmental information on a centralized dashboard.
5. Comparing sensor measurements against approved environmental limits and geographical boundaries.
6. Detecting potential environmental risks and issuing alerts.
7. Communicating shutdown requests to the mining control system.
8. Monitoring equipment health and detecting communication failures.
9. Maintaining historical records and generating compliance reports.
10. Providing secure access to environmental data and safety-related functions.

The system focuses on environmental monitoring, safety enforcement, fault detection, and regulatory reporting.

It does not directly manage metal extraction, mineral processing, or the commercial operations of the mining company. It also cannot completely eliminate environmental damage; instead, it helps detect and control environmental risks.

2. Identify Key Stakeholders and Challenges

2.1 Key Stakeholders

1. Mining Company

Roles and Responsibilities:

- Operates the deep-sea mining equipment.
- Ensures compliance with environmental regulations.
- Provides the required monitoring equipment and infrastructure.
- Maintains safe mining operations.

Challenges:

- Avoiding environmental violations.
- Managing operational costs.
- Ensuring continuous environmental monitoring.
- Preventing delays caused by equipment failures.

2. Mining Operators

Roles and Responsibilities:

- Monitor environmental conditions through the dashboard.
- Review alerts generated by the compliance system.
- Supervise mining operations.
- Respond to environmental warnings and shutdown notifications.

Challenges:

- Making timely decisions when environmental conditions change rapidly.
- Understanding complex environmental information.
- Responding to multiple alerts.
- Ensuring that shutdown procedures are completed correctly.

3. Environmental Regulators

Roles and Responsibilities:

- Define or approve environmental limits and safety boundaries.
- Monitor compliance with applicable environmental regulations.
- Review environmental monitoring reports.
- Investigate reported violations.

Challenges:

- Verifying compliance with environmental requirements.
- Ensuring that monitoring records are accurate.
- Identifying violations that occur during mining operations.
- Reviewing large amounts of environmental data.

4. Marine Scientists

Roles and Responsibilities:

- Study sediment plume movement and marine ecosystems.
- Analyze turbidity, current measurements, and acoustic information.
- Evaluate potential environmental impacts.

- Help define scientifically appropriate monitoring rules.

Challenges:

- Understanding complex underwater conditions.
- Predicting plume movement accurately.
- Working with incomplete or uncertain measurements.
- Identifying the potential effects of sediment on marine organisms.

5. Surface Buoy Operators

Roles and Responsibilities:

- Maintain surface buoys and their sensors.
- Monitor communication equipment.
- Ensure that data are transmitted correctly.
- Report equipment failures.

Challenges:

- Equipment failures caused by harsh marine conditions.
- Communication interruptions.
- Sensor calibration problems.
- Damage caused by saltwater and rough weather.

6. Autonomous Drone Engineers

Roles and Responsibilities:

- Develop and maintain underwater drones.
- Integrate environmental sensors into the drones.
- Maintain navigation and communication systems.
- Ensure that drones collect accurate measurements.

Challenges:

- Limited underwater communication.
- Battery and operating-time constraints.
- Equipment failures at considerable depths.
- Difficulties in navigation and sensor maintenance.

7. Software Developers

Roles and Responsibilities:

- Design and develop the compliance software.
- Integrate the sensor data collection system.

- Implement environmental analysis and boundary detection.
- Test and maintain the software.

Challenges:

- Integrating devices from different manufacturers.
- Designing fault-tolerant software.
- Meeting strict safety requirements.
- Handling real-time data processing and system failures.

8. Data Engineers

Roles and Responsibilities:

- Manage environmental data collection and storage.
- Validate sensor readings.
- Process real-time data streams.
- Maintain data quality and synchronization.

Challenges:

- Handling large volumes of sensor data.
- Identifying inaccurate or missing measurements.
- Managing delayed data from underwater devices.
- Maintaining data consistency during communication failures.

9. Environmental Auditors

Roles and Responsibilities:

- Review environmental monitoring records.
- Verify compliance reports.
- Examine alerts and shutdown events.
- Check whether required procedures were followed.

Challenges:

- Ensuring the completeness of historical records.
- Identifying missing or inconsistent data.
- Verifying the accuracy of compliance reports.
- Maintaining reliable audit evidence.

10. Maintenance and Support Teams

Roles and Responsibilities:

- Inspect and repair sensors, drones, and buoys.

- Replace faulty equipment.
- Monitor device health.
- Restore equipment after failures.

Challenges:

- Identifying faults in remote underwater locations.
- Reaching damaged equipment.
- Reducing equipment downtime.
- Maintaining equipment under high-pressure marine conditions.

2.2 Major Challenges of the System

1. Unpredictable Sediment Plume Movement

Ocean currents may carry sediment clouds beyond the authorized mining area. The system must continuously analyze turbidity and current measurements to identify possible boundary violations.

2. Limited Underwater Communication

Underwater devices cannot always maintain fast and reliable communication with the surface. Delays or interruptions may prevent sensor readings and shutdown commands from reaching their destinations on time.

3. Sensor Failures and Inaccurate Readings

Sensors may produce incorrect or incomplete measurements because of damage, fouling, calibration problems, or environmental conditions. Incorrect readings can cause false alarms or missed environmental violations.

4. Coordination of Multiple Devices

The system must coordinate several surface buoys and autonomous underwater drones operating at different locations and depths. Sensor readings must include reliable timestamps and location information to support accurate analysis.

5. Immediate Shutdown Requirements

Mining operations must stop when defined environmental safety conditions are violated. Delays in detecting violations or delivering shutdown commands could increase environmental damage.

6. System Reliability

A sensor, communication link, database, or software component may fail during monitoring. The system must handle such failures without losing essential safety functions.

7. Data Security and Integrity

Environmental data and shutdown records must be protected against unauthorized access, alteration, or deletion. Reliable historical records are important for environmental audits.

8. Harsh Operating Conditions

Saltwater corrosion, pressure, extreme temperatures, and rough sea conditions can damage underwater equipment. The software must account for equipment failure and communication interruptions.

3. Analyze the Current Approach

3.1 Existing System or Current Process

The problem statement does not describe a specific existing implementation. Therefore, this analysis considers a typical monitoring approach that may use separate sensors, manual supervision, and independent monitoring tools.

In such an approach, surface buoys and autonomous underwater drones collect environmental measurements. Operators or separate monitoring applications review the information and decide whether mining activities can continue.

Environmental information may be stored in different systems, making it difficult to combine measurements from different locations and devices.

When an abnormal reading is identified, operators may need to investigate the situation and communicate with the mining control team before stopping operations.

Although this approach can provide useful environmental information, it may not provide sufficiently coordinated, automated, and fault-tolerant compliance enforcement.

3.2 Strengths of the Current Approach

1. **Environmental Data Collection:** Sensors provide information about water quality and underwater conditions.
2. **Human Supervision:** Operators can investigate unusual measurements and consider operational circumstances.
3. **Independent Equipment Operation:** Separate devices may continue collecting data even when another device encounters a problem.
4. **Historical Monitoring:** Recorded measurements support environmental analysis and report preparation.
5. **Flexible Decision-Making:** Human operators can investigate unusual situations that require additional judgment.

3.3 Limitations of the Current Approach

1. **Delayed Response:** Manual review and communication may delay the identification of environmental violations.
2. **Limited Data Integration:** Measurements collected by different devices may not be combined in real time.
3. **Communication Dependency:** Remote monitoring may become ineffective when underwater communication is interrupted.
4. **Lack of Centralized Monitoring:** Operators may need to switch between different applications to understand the overall environmental situation.
5. **Limited Fault Detection:** Sensor or communication failures may remain unnoticed until equipment status is reviewed.

6. **Possible Data Loss:** Interrupted connections may cause gaps in environmental records.
7. **Human Error:** Operators may overlook alerts or interpret measurements incorrectly during complex operations.
8. **Insufficient Automated Enforcement:** A system that relies heavily on manual intervention may not initiate a shutdown quickly enough.

3.4 Gaps That Need to Be Addressed

1. Delayed Identification of Environmental Risks

The proposed system will use automated and continuous compliance monitoring to identify safety violations promptly.

2. Separate Sensor Data Sources

A centralized data collection system will integrate measurements from surface buoys and underwater drones.

3. Unreliable Communication

Local data buffering, edge processing, and alternative communication paths where available will help manage communication interruptions.

4. Sensor Failures

Device-health monitoring, data validation, and redundant measurements will help identify faulty sensors.

5. Delayed Shutdown

Automated safety rules and an independent local safety mechanism will support prompt shutdown initiation.

6. Data Loss During Outages

Local storage and synchronization after connectivity returns will reduce data loss.

7. Incomplete Environmental Records

Timestamped audit logs will record sensor measurements, alerts, faults, and shutdown events.

8. Unauthorized Access

Authentication, role-based access control, and encrypted communication will help protect environmental data and safety-related controls.

Conclusion: A coordinated software-based system is required to integrate environmental measurements, detect safety violations, tolerate failures, and support prompt enforcement of environmental boundaries.

4. Propose a Suitable Solution Using Software Engineering Principles

4.1 Proposed Software Solution

The proposed solution is a **Fault-Tolerant Deep-Sea Mining Environmental Compliance System** that integrates real-time data from surface buoys and autonomous underwater drones.

The system collects environmental measurements, analyzes plume behavior, checks environmental boundaries, and initiates predefined safety actions when violations occur.

A centralized dashboard allows mining operators, environmental specialists, and authorized regulators to monitor environmental conditions and review compliance records.

The architecture combines centralized processing with local safety controls. Centralized services provide overall coordination, while safety-critical functions must be capable of responding locally when communication with the central system is lost.

4.2 Proposed System Architecture

Subtitle for documentation: System Architecture of the Proposed Deep-Sea Mining Environmental Compliance System

The proposed system consists of the following layers.

Layer 1: Data Collection Layer

Surface buoys and autonomous underwater drones collect the following information:

- Water turbidity readings.
- Current direction and speed measurements.
- Acoustic sound profiles.
- Mining tool depth and position coordinates.
- Device status, battery level, and sensor-health information.

Each observation should include a timestamp, device identifier, measurement value, location where available, and data-quality information.

Layer 2: Communication Layer

This layer transfers environmental data from the devices to processing services using communication methods suitable for the available equipment.

Possible methods include:

- Underwater acoustic communication between submerged devices and surface buoys.
- Satellite communication from surface buoys to remote monitoring platforms.
- Other suitable communication links supported by the deployed equipment.

Because connectivity may be interrupted, devices or nearby controllers should temporarily store data locally and forward it when connectivity returns.

Layer 3: Data Processing Layer

This layer validates incoming data and checks for:

1. Missing sensor readings.
2. Duplicate messages.
3. Invalid timestamps.
4. Unexpected sensor values.

5. Inconsistent device locations.
6. Delayed or outdated measurements.

The system combines measurements from different devices to build a more complete understanding of environmental conditions.

Layer 4: Environmental Compliance Engine

The compliance engine compares validated measurements with authorized environmental limits and geographical boundaries.

It uses turbidity measurements, current information, device locations, tool depth coordinates, and suitable acoustic indicators to assess environmental conditions.

Where sufficient validated data are available, the system estimates plume movement and identifies potential boundary crossings.

If the required safety conditions are met, the engine classifies the situation and generates an alert or shutdown request according to the approved operating rules.

Layer 5: Safety Enforcement Layer

This layer communicates the required response to the mining control system.

If a defined safety boundary is crossed, it initiates the configured shutdown procedure.

If essential monitoring becomes unavailable, the system follows an approved fail-safe policy rather than assuming that conditions are safe.

A local safety controller or hardwired interlock should protect against failures of the central application or communication network.

The system should verify shutdown acknowledgements where supported.

Layer 6: User Interface and Reporting Layer

The user interface provides a real-time view of the monitoring operation.

It displays:

- Sensor readings.
- Device locations.
- Environmental boundaries.
- Plume indicators.
- System-health status.
- Environmental alerts.
- Mining shutdown events.

Authorized users can generate environmental reports and review historical compliance information.

4.3 System Workflow


Subtitle for documentation: Working Process of the Deep-Sea Mining Environmental Compliance System

The proposed system follows these steps.

1. Surface buoys and underwater drones collect environmental sensor readings.
2. The communication layer transfers the measurements to the processing system.
3. The data processing module validates the readings and identifies missing or unreliable data.
4. The environmental analysis engine combines the available sensor measurements and estimates plume movement.
5. The compliance engine compares environmental conditions with the approved limits and boundaries.
6. If a possible violation is detected, the system raises an alert and evaluates the required safety response.
7. If a shutdown condition is confirmed under the approved rules, the system initiates a stop command through the mining control system.
8. The safety controller verifies the response where possible.
9. The application records the event and notifies authorized personnel.
10. Environmental data, system faults, alerts, and shutdown actions are stored for subsequent analysis and compliance reporting.

If a critical monitoring failure prevents the system from establishing that operations are safe, the approved safety policy should require the appropriate safe state, such as suspending mining until monitoring is restored.

4.4 Flowchart of the Proposed System



4.5 Major Functional Modules

1. Device Management Module

- Registers surface buoys and underwater drones.
- Maintains device information.
- Tracks device operating status.
- Monitors battery level and device availability.

2. Sensor Data Collection Module

- Collects real-time readings from environmental sensors.
- Receives data from turbidity, current, acoustic, and depth sensors.
- Associates each measurement with its source device and timestamp.

3. Data Validation Module

- Checks for invalid measurements.
- Detects missing or duplicate data.
- Identifies stale sensor readings.
- Marks measurements with quality problems.

4. Communication Management Module

- Manages data transmission.
- Tracks communication status.
- Supports local buffering during connection failures.
- Synchronizes stored measurements when connectivity returns.

5. Environmental Analysis Module

- Combines sensor readings.
- Estimates sediment plume movement.
- Analyzes environmental changes.
- Identifies conditions that may lead to boundary violations.

6. Compliance Monitoring Module

- Stores approved environmental limits and geographical boundaries.
- Compares environmental conditions against the permitted limits.
- Identifies potential safety violations.
- Classifies environmental risk according to approved rules.

7. Alert and Shutdown Module

- Generates environmental warning messages.

- Notifies authorized operators.
- Initiates shutdown requests when defined conditions are violated.
- Records shutdown commands and acknowledgements.

8. Fault Detection and Recovery Module

- Identifies sensor and communication failures.
- Monitors application health.
- Supports recovery from supported software failures.
- Activates the approved fail-safe response when critical monitoring becomes unavailable.

9. Dashboard and Visualization Module

- Displays environmental measurements.
- Shows buoy and drone locations.
- Presents plume indicators and safety boundaries.
- Displays alerts and device-health information.

10. Reporting and Audit Module

- Stores environmental measurements.
- Maintains a history of alerts and faults.
- Records shutdown events and operator actions.
- Generates compliance reports.

11. User and Access Management Module

- Authenticates system users.
- Assigns permissions according to user roles.
- Restricts access to sensitive information.
- Records important user activities.

4.6 Functional Requirements

Functional requirements describe what the system must do.

FR1: Sensor Data Collection

The system shall collect turbidity, current direction and speed, acoustic profile, and tool depth or position data from supported devices.

FR2: Device Identification

The system shall identify the source device for each measurement.

FR3: Data Validation

The system shall detect invalid, missing, delayed, and duplicate sensor readings.

FR4: Real-Time Monitoring

The system shall display current environmental conditions and device status to authorized users.

FR5: Plume Analysis

The system shall combine relevant environmental measurements to estimate sediment plume movement and potential environmental impact.

FR6: Boundary Monitoring

The system shall compare measured or estimated plume conditions with the approved environmental safety boundaries.

FR7: Automatic Alerts

The system shall generate alerts when environmental conditions approach or cross configured safety limits.

FR8: Mining Shutdown

The system shall initiate the required shutdown procedure when a defined environmental violation occurs and shall record the result of the shutdown request.

FR9: Fault Detection

The system shall detect communication failures, unresponsive devices, and important sensor faults.

FR10: Fault-Tolerant Monitoring

The system shall support continued monitoring through available redundant devices and communication paths when individual components fail.

FR11: Data Storage

The system shall store sensor measurements, system-health events, alerts, and shutdown records.

FR12: Report Generation

The system shall generate environmental monitoring and compliance reports for authorized users.

FR13: User Access Control

The system shall restrict access to sensitive information and safety-related controls based on user roles.

FR14: Recovery and Synchronization

The system shall synchronize buffered sensor data after connectivity is restored and identify gaps that cannot be recovered.

4.7 Non-Functional Requirements

Non-functional requirements define the quality, performance, and operational characteristics of the system.

1. Reliability

The system must produce dependable monitoring results and process safety events correctly.

2. Fault Tolerance

A single sensor, communication link, or application component failure should not unnecessarily disable the entire monitoring system.

3. Performance

Data processing and shutdown initiation must satisfy the response-time limits established by the approved safety requirements.

4. Availability

Monitoring services should remain available during expected component failures and maintenance activities.

5. Scalability

The architecture should support the addition of more buoys, drones, sensors, and monitoring locations.

6. Maintainability

Individual modules should be easy to test, repair, update, and replace.

7. Usability

The dashboard should present environmental conditions, faults, and critical alerts clearly.

8. Security

The system must protect data and controls through authentication, authorization, encryption, and secure configuration.

9. Data Integrity

Environmental readings and compliance records must be protected against unauthorized or accidental modification.

10. Recoverability

The system should recover from supported failures and synchronize buffered records after connectivity returns.

11. Interoperability

The software should support integration with compatible sensors, underwater devices, and mining control equipment.

12. Auditability

The system must maintain traceable records of important alerts, operator actions, and shutdown events.

The actual performance limits, availability targets, sampling rates, and shutdown response times must be established during detailed requirements analysis.

4.8 Incorporating Software Engineering Principles

1. Modularity

The system is divided into independent modules, such as data collection, environmental analysis, compliance monitoring, shutdown control, and reporting.

For example, the data validation module can be improved without completely redesigning the dashboard.

Benefit: Modularity simplifies development, testing, troubleshooting, and future modifications.

2. Scalability

The system uses a modular architecture that can support additional buoys, drones, and monitoring locations.

Data processing and storage capacity can be expanded as the number of connected devices increases.

Benefit: The system can grow as the mining operation expands.

3. Maintainability

The software uses clear interfaces, documentation, automated tests, and separate modules.

Device drivers, environmental rules, and reporting logic are separated so that changes to one component do not unnecessarily affect the others.

Benefit: Updates and repairs become easier, reducing maintenance effort.

4. Reliability

The system validates sensor data, uses redundant monitoring where practical, and maintains traceable records.

Critical calculations and safety rules should be independently tested and reviewed. Important shutdown commands should have acknowledgement and verification mechanisms.

Benefit: The system is less likely to make unsafe decisions because of incorrect data or software faults.

5. Fault Tolerance

The system is designed to handle failures without losing essential monitoring capabilities.

The following mechanisms are proposed:

- Use overlapping buoy and drone coverage where practical.
- Monitor the health of sensors and communication links.
- Store data locally during temporary communication outages.
- Use redundant services and storage where justified by safety requirements.
- Detect stale readings instead of treating old measurements as current.
- Use watchdogs and automatic recovery for supported software failures.
- Keep critical shutdown protection independent of the main monitoring application where possible.

- Apply an approved safe-state policy whenever essential monitoring becomes unavailable.

Benefit: The system can tolerate selected failures while continuing available monitoring functions or moving operations to a safe state.

6. Usability

The dashboard presents essential information, such as plume location, turbidity, device health, environmental limits, and active alerts.

Critical alerts should have a clear priority and should not be hidden among ordinary notifications.

Benefit: Operators can understand the environmental situation and respond more quickly.

7. Security

The system uses role-based access control, secure communication, appropriate encryption, audit logs, and controlled software updates.

For example, an environmental scientist may review measurements and reports, while only authorized personnel or approved control logic may initiate or modify safety-related operations.

Benefit: Security controls reduce the risk of unauthorized access, data manipulation, and unsafe control changes.

8. Separation of Safety-Critical Functions

Environmental analysis, operator interfaces, general reporting, and emergency shutdown protection should not all depend on one application or communication path.

Critical protection should have a separately engineered control mechanism with a defined safe state.

Benefit: A dashboard failure or database outage is less likely to prevent the required emergency response.

5. Justify the Chosen Methodology/Framework

5.1 Selected Methodology: Spiral Model

The Spiral Model is selected for developing the Deep-Sea Mining Environmental Compliance System.

The Spiral Model is a risk-driven software development approach. Development proceeds through repeated cycles involving planning, risk analysis, engineering, and evaluation.

This methodology is suitable because the proposed system has complex sensor integration requirements, uncertain underwater operating conditions, strict environmental obligations, and potentially serious consequences if monitoring or shutdown functions fail.

5.2 Why the Spiral Model Is Suitable

1. High-Risk System Development

A failure to detect a sediment plume or stop mining operations could cause environmental damage.

The Spiral Model allows major safety risks to be identified and addressed early in development.

2. Complex Technical Requirements

Integrating surface buoys, underwater drones, environmental sensors, communication systems, and mining controls requires extensive testing.

Each development cycle can evaluate a specific technical challenge.

3. Changing Environmental Requirements

Monitoring rules and system behavior may need adjustments following environmental studies, regulatory review, or field testing.

The Spiral Model accommodates controlled refinement across development cycles.

4. Early Prototyping

The team can build an initial prototype that receives simulated turbidity and current measurements.

Later prototypes can incorporate plume estimation, boundary detection, alerts, and shutdown integration.

5. Continuous Stakeholder Feedback

Mining operators, marine scientists, regulators, and safety engineers can evaluate each prototype and provide feedback.

6. Risk Reduction Before Deployment

The team can test how the system behaves when sensors fail, data become stale, or communication links are lost before using the software in a real mining operation.

5.3 Development Phases of the Spiral Model

Subtitle for documentation: Spiral Model Development Phases

Phase 1: Requirements and Planning

- Identify stakeholders and their requirements.
- Define environmental rules and system boundaries.
- Determine the project scope.
- Identify hardware and software requirements.
- Prepare the initial project plan.

Expected Output: Requirements document and project plan.

Phase 2: Risk Analysis and Prototype Development

- Identify sensor accuracy risks.
- Analyze communication limitations.

- Evaluate data quality problems.
- Identify shutdown and safety risks.
- Develop an initial prototype.

Expected Output: Risk assessment and initial prototype.

Phase 3: Core System Development

- Develop sensor data collection.
- Implement data validation.
- Develop device management.
- Implement environmental data storage.

Expected Output: Working environmental data collection system.

Phase 4: Environmental Analysis

- Implement plume analysis.
- Develop boundary detection.
- Implement environmental risk classification.
- Validate environmental calculations.

Expected Output: Environmental monitoring and compliance engine.

Phase 5: Safety and Fault-Tolerance Development

- Implement fault detection.
- Introduce redundancy where appropriate.
- Develop shutdown request handling.
- Implement recovery mechanisms.
- Integrate local safety controls.

Expected Output: Fault-tolerant monitoring and safety-control integration.

Phase 6: Integration and Testing

- Test integration between devices and software.
- Simulate sensor faults.
- Test communication failures.
- Test environmental boundary conditions.
- Verify shutdown behavior.
- Conduct security and performance testing.

Expected Output: Tested integrated system and test reports.

Phase 7: Deployment and Maintenance

- Deploy the system under controlled conditions.
- Monitor system performance.
- Correct identified defects.
- Implement approved improvements.
- Maintain documentation and test records.

Expected Output: Operational system and maintenance plan.

Each cycle begins with planning and risk assessment. Testing and stakeholder feedback help determine the next development cycle.

5.4 How the Methodology Supports Successful Development

1. Risk Management

Important risks are analyzed before more development effort is invested.

2. Early Validation

Prototypes help confirm whether the proposed technology and architecture are suitable.

3. Continuous Improvement

Feedback and test results guide improvements to the system.

4. Better Quality Assurance

Testing can focus on sensor failures, communication loss, boundary violations, and shutdown procedures.

5. Controlled Changes

New requirements can be assessed during later cycles without abandoning the entire project.

6. Long-Term Maintenance

The modular architecture and repeated risk assessments support safe improvements after deployment.

Choosing the Spiral Model does not automatically guarantee system safety. The development process must also include requirements traceability, independent safety reviews, verification and validation, fault-injection tests, and controlled approval of changes to safety-related functions.

6. Discuss Expected Outcomes and Limitations

6.1 Expected Benefits of the Proposed System

1. Improved Environmental Monitoring

The integration of buoys and underwater drones provides a broader view of environmental conditions around the mining area.

2. Faster Detection of Environmental Violations

Automated processing and boundary checks allow the system to identify potential violations without depending entirely on manual data review.

3. Prompt Shutdown Initiation

When a defined safety condition is violated, the system can initiate the approved shutdown procedure and record the event.

4. Improved Fault Detection

The system monitors the health of sensors, drones, buoys, and communication links. It can identify faults before they are mistaken for normal environmental measurements.

5. Reduced Data Loss

Local buffering and later synchronization help preserve measurements collected during temporary communication outages.

6. Improved Decision-Making

Operators and environmental specialists can use the dashboard to review environmental conditions, device health, plume movement, and previous alerts.

7. Better Regulatory Compliance

Timestamped measurements, alert histories, and shutdown records help demonstrate whether environmental monitoring and response procedures were followed.

8. Greater Operational Reliability

Redundant monitoring components and independent safety controls reduce dependence on any single device or application.

6.2 How the Proposed Solution Addresses the Identified Challenges

1. Unpredictable Plume Movement

The system analyzes turbidity and current measurements with spatial and depth information.

Expected Result: Earlier identification of potential plume spread.

2. Communication Interruptions

The system buffers data locally and uses available alternative communication paths.

Expected Result: Fewer data losses and improved recovery after connection failures.

3. Sensor Failures

The system monitors device health and validates measurements.

Expected Result: Sensor faults are more likely to be detected.

4. Delayed Environmental Response

The system automates compliance checks and shutdown initiation.

Expected Result: Reduced dependence on manual intervention.

5. Failure of a Single Component

The system uses redundancy and separates critical safety functions from ordinary application functions.

Expected Result: Improved fault tolerance.

6. Incomplete Environmental Records

The system stores timestamped measurements, alerts, and shutdown events.

Expected Result: Better traceability and environmental reporting.

7. Unauthorized System Access

The system uses authentication, permissions, and secure communications.

Expected Result: Improved protection of environmental data and safety controls.

6.3 Potential Risks and Implementation Challenges

1. Sensor Accuracy

Turbidity sensors may produce inaccurate results or become fouled. Incorrect measurements could lead to false alarms or failure to detect a real problem.

Mitigation: Use calibration procedures, sensor-health checks, suitable redundant measurements, and data-quality validation.

2. Underwater Communication Failure

Underwater communication may be delayed or interrupted, preventing real-time information from reaching the central application.

Mitigation: Use local processing, data buffering, redundant communications where practical, and independent local safety controls.

3. False Positives and False Negatives

A false positive occurs when the software identifies a violation that has not occurred. A false negative occurs when a real violation is not detected.

Mitigation: Validate detection algorithms using realistic simulations, field measurements, and independent testing. Do not treat uncertain or outdated measurements as proof that conditions are safe.

4. Complex Environmental Conditions

Ocean currents and underwater terrain may affect sediment plume movement in ways that are difficult to predict precisely.

Mitigation: Validate plume models against scientific observations, represent uncertainty, and use conservative safety margins approved by environmental specialists.

5. Failure of the Shutdown Mechanism

The shutdown command may not reach the mining control equipment or may fail to produce the required response.

Mitigation: Provide an independent safety controller or interlock, verify the shutdown response, raise an alarm when acknowledgement is missing, and test the complete control path.

6. High Implementation and Maintenance Costs

Specialized underwater drones, marine sensors, communication equipment, and reliable computing infrastructure can be expensive.

Mitigation: Develop the system in stages, prioritize safety-critical capabilities, and conduct cost-benefit analysis before deployment.

7. Cybersecurity Threats

Unauthorized users or compromised devices could manipulate environmental readings or interfere with control commands.

Mitigation: Apply strong access control, encryption, device authentication, secure updates, system monitoring, and incident-response procedures.

8. Integration Difficulties

Sensors and devices from different manufacturers may use different data formats, communication protocols, and interfaces.

Mitigation: Define standard interfaces, implement device adapters, document APIs, and test integration throughout development.

9. Dependence on Environmental Models

The software may not predict sediment movement accurately in every situation.

Mitigation: Treat predictions as estimates, test models under different environmental conditions, and establish conservative compliance rules based on approved scientific and regulatory requirements.

6.4 Limitations of the Proposed System

1. **No Perfect Environmental Prediction:** The system cannot guarantee exact predictions of plume movement under every ocean condition.
2. **Dependence on Sensor Quality:** Incorrect measurements may affect the accuracy of environmental analysis.
3. **Communication Constraints:** Real-time communication cannot be guaranteed in every underwater location.
4. **Hardware Limitations:** Drones may have limited battery life, operating depth, sensing range, and carrying capacity.
5. **High Development Costs:** Implementing and validating a fault-tolerant monitoring system requires specialized equipment and expertise.
6. **Model Uncertainty:** Environmental analysis may be inaccurate when measurements are incomplete or conditions differ from those used to validate the model.
7. **Safety Certification Requirements:** The software and shutdown controls require appropriate engineering assurance and regulatory review before operational deployment.
8. **Limited Environmental Coverage:** The system can only monitor locations adequately covered by its deployed devices and validated measurement methods.

These limitations mean that the system should support, rather than replace, scientific assessment, qualified operational supervision, and regulatory oversight.

6.5 Future Enhancements

1. Artificial Intelligence-Based Plume Prediction

Machine-learning models could analyze historical environmental measurements to estimate plume movement and identify patterns associated with potential violations.

These models must be validated and must not override essential safety protections.

2. Digital Twin of the Mining Environment

A digital twin could represent the mining area, seabed, devices, environmental boundaries, and predicted plume movement.

Operators could use it to investigate possible scenarios before changing operating conditions.

3. Autonomous Drone Coordination

Future versions could coordinate drone movement based on plume direction, sensor coverage, battery level, and detected environmental risks.

4. Improved Sensor Networks

Additional monitoring devices could improve environmental coverage and provide independent measurements to help detect faulty sensors.

5. Advanced Anomaly Detection

The system could identify unusual acoustic patterns, sudden turbidity changes, or sensor behavior that indicates equipment damage or unexpected environmental conditions.

6. Cloud-Based Environmental Analytics

Cloud infrastructure could support large-scale historical data analysis, compliance reporting, and comparisons between different mining sites, subject to connectivity and security requirements.

7. Predictive Maintenance

Device-health information could be analyzed to predict when sensors, batteries, and communication equipment may require maintenance.

8. Enhanced Regulatory Reporting

Future versions could provide configurable report templates, automated compliance summaries, and secure data-sharing facilities for authorized environmental regulators.

Any future enhancement to safety-related behavior should undergo appropriate verification, validation, and approval before deployment.

7. Conclusion

The **Fault-Tolerant Deep-Sea Mining Environmental Compliance System** provides a software-based approach to monitoring sediment plumes and enforcing environmental safety boundaries during deep-sea mining.

The system integrates real-time data from surface buoys and autonomous underwater drones, validates sensor measurements, analyzes environmental conditions, and compares plume behavior against approved safety limits. When a defined safety condition is violated, it initiates the required shutdown procedure and records the event for compliance reporting.

The proposed architecture applies important software engineering principles, including modularity, scalability, maintainability, reliability, usability, security, and fault tolerance. It also separates centralized monitoring from essential local safety controls, reducing the risk that a single software or communication failure will prevent an appropriate safety response.

The Spiral Model is suitable for development because it supports risk-driven planning, iterative prototyping, continuous testing, and stakeholder feedback. However, successful implementation requires accurate sensors, reliable safety controls, realistic environmental validation, and appropriate regulatory approval.

Overall, the proposed system can improve environmental monitoring, strengthen compliance enforcement, support faster responses to environmental hazards, and provide reliable records of deep-sea mining activities. It offers a structured foundation for safer and more accountable underwater mining operations.