

Zeek ATT&CK Metrics

Allan Thomson CTO LookingGlass Oct 29th 2019

3 Things



What is it **Zeek Background** Why it matters STIX2.1 Intelligence to **Zeek Script Data Preparation Programming** ATT&CK Mapping Intelligence & Zeek/Behavior ATT&CK **Data Processing** correlation normalization




Zeek Background

Basic Architecture


Zeek Background





Zeek Ecosystem






Zeek Based Detection




- Zeek monitor receives copy of all traffic
- Zeek employs an event-based programming model
- Zeek scripts run to perform analysis on the network traffic
- Identify stateful analysis on specific network patterns or network behavior
- Can also identify user application behaviors
 (i.e. nefarious activity)




Zeek Processing and Distribution




- Supports Actor-Framework
 (https://actor-framework.org/)
- Distributed Messaging & Processing
 - Event Processing
 - Cross-Event Correlation
 - Behavioral Identification
 - Intelligence Correlation
 - ATT&CK Analysis
 - Multi-node
 - Multi-processing





Applying Zeek For ATT&CK/Intelligence Correlation







Data Preparation

Intelligence & Zeek Updates for ATT&CK

Threat Intelligence & ATT&CK



How we modelled Threat Intelligence



How we related Intelligence to ATT&CK



How we correlated intel with activities (net, sys, user)



How we applied action based on Intelligence/ATT&CK



Data Preparation: Intel to ATT&CK Mapping



- 90 different intelligence feeds
- ~1800 *Unique* intelligence attack-patterns, intrusion sets, actors
 - Data-driven Mapping to ATT&CK
 - Include ATT&CK Mapping when producing STIX2.1 Intelligence

```
"lgc_obs_id_s": "Observed Malware Distribution",

"mitre_tactic": {

    "mitre_tactic_id": "TA0001",

    "mitre_tactic_name": "Initial Access"
},

"mitre_tech_list": [ {

    "mitre_tech_id": "T1189", "mitre_tech_name": "Drive-by Compromise", "mitre_tech_uuid": "attack-pattern--d742a578-d70e-440e-96a6-02a9c30204e6" }, {

    "mitre_tech_id": "T1199", "mitre_tech_name": "Exploit Public-Facing Application", "mitre_tech_uuid": "attack-pattern--3f886f2a-874f-4333-b794-aa6075009b1c"

    "mitre_tech_id": "T1133", "mitre_tech_name": "External Remote Services", "mitre_tech_uuid": "attack-pattern--10d51417-ee35-4589-b1ff-b6df1c334e8d" }, {

    "mitre_tech_id": "T1195", "mitre_tech_name": "Supply Chain Compromise", "mitre_tech_uuid": "attack-pattern--3f18edba-28f4-4bb9-82c3-8aa60dcac5f7" }

}
```

Data Preparation: Intel to ATT&CK Mapping



- Tactics mapped using kill-chain property on Intel Feed
 - Attack-Pattern SDO
 - Intrusion Set SDO
 - Actor SDO

```
"type": "attack-pattern",
"name": "CoreFlood",
"description": "Coreflood is a trojan horse and botnet created by a
"id": "attack-pattern--38c47d93-d984-4fd9-b87b-d69d0841628d",
"created by ref": "identity--826d4837-a92b-44a3-91c9-107ec7982c1d",
"created": "2016-05-07T11:22:30.000000Z",
"modified":"2016-05-07T11:22:30.000000Z",
"labole" • ["command-and-control"]
"kill_chain_phases": [
    "kill_chain_name": "mitre-attack",
    "phase_name": "command and control"
```

Data Preparation: Intel to ATT&CK Mapping



Intel Feed Attack-Patterns related to ATT&CK Attack-Patterns using SROs

```
// define the relationship from this specific attack-pattern to MITRE ATT&CK attack-patterns
// Commonly Used Ports: attack-pattern--f879d51c-5476-431c-aedf-f14d207e4d1e
{
    "type": "relationship",
    "id": "relationship--7aebe2f0-28d6-48a2-9c3e-b0aaa60266ee",
    "created_by_ref": "identity--826d4837-a92b-44a3-91c9-107ec7982c1d",
    "created": "2016-05-09T08:17:27.000000Z",
    "modified": "2016-05-09T08:17:27.000000Z",
    "relationship_type": "related-to",
    "source_ref": "attack-pattern--38c47d93-d984-4fd9-b87b-d69d0841628d",
    "target_ref": "attack-pattern--f879d51c-5476-431c-aedf-f14d207e4d1e"
}
```

Points to ATT&CK UUID



Data Processing

Correlation, Alerting

An Intelligence Question





- Find IP ranges and CIDRs that are associated with the NAICS Industry of 'Carpet and Rug Mills';
 - discover all active IPs contained within these ranges,
 - and
 - find FQDNs associated with them where those FQDNs have active threats
 - that include
 - Attack-Pattern Exploitation of Remotes Services and
 - Attack-Pattern Pass the Hash

The problem answering that question?



- Many different sources assert essentially the same data
 - i.e. FeedA asserts that IP 10.0.0.1 has Malware A, and FeedB asserts the same
- Much of the metadata is the same across temporal series
 - Repeated fact assertions and threat associations
 - i.e. FeedB asserts that Actor BB, associated with Intrusion Set AA, using Attack-Pattern ZZZ Drive-by Compromise malware YY on Infrastructure CC at time X, and again, at time Y
- Different attributes with different data representation that communicate the same semantic information
 - i.e. country_s of "United States" and "United States of America" and country_code_s of "US", and "USA"
- Multiple different object/entity types, billions of instances that requires large-scale
 join across data-sets where those data-sets are being updated in real-time

Solution: Unified Data Modelling




Entity

- Contains information about an **Entity** that will never change
- Metadata such as name, and IP ranges in **Entities** allows **Facts** to only contain reference

Fact

- Asserts attributes on Entity and relationships to other Entities
- If Facts contained temporal and source/provider attributes, it would be multiple Fact Record for each




Assertion

- Asserts one or more Facts by Source Entity and Provider Entity
- Contains all temporal attributes Observed At, and Asserted At


Impact on Data



Records: 150 mm/day \rightarrow 19 mm/day.



Bytes: ~150GB/day → ~25-30GB/day.




Zeek Intelligence Basic Lookup Pipeline



Zeek Intelligence Framework Lookup Intel::match_no_items Zeek In-Memory Event Intel Store (30m TTL) new_connection seen: Intel::Seen Intelligence Correlation **Broker Publisher** dns_request Intel::seen Function **Function** http_message_done **Broker Subscriber** STIX/ATT&CK Ingestor msg: Broker Message seen: Intel::Seen Event **Function** Loop c: connection msg: Broker Message stix: STIX File is_orig: bool Query Transformer Function Function Intel::intel_update stix: STIX File ent: Entity **Raw Events** Event items: set[Intel::Seen] seen: Intel::Seen Intel::intel_update **Event** Intelligence Found items: set[Intel::Seen] Intel EFA seen: Intel::Seen Database (N-days TTL) **Event** Broker Publisher **Broker Subscriber** Function Function msg: Broker Message msg: Broker Message Intelligence & **ATT&CK Correlation**


Zeek ATT&CK Report Event Dissection





Zeek ATT&CK Report Event Analysis






Summary




- Zeek provides effective and flexible framework for collection and correlation
- Data preparation & modelling can have big impact on analysis effectiveness
- Data correlation at scale requires end-to-end approach

Questions?











Thank You

Looking Glass Cyber.com



@LookingGlassCyber



@LG_Cyber



/company/LookingGlass



/LookingGlassCyber