

A Deep Dive Into Splunk LDAP
Authentication and How it Affects Cluster
Performance

Jacky Chen - Developer - Atlassian

October 2018

### Forward-Looking Statements

During the course of this presentation, we may make forward-looking statements regarding future events or the expected performance of the company. We caution you that such statements reflect our current expectations and estimates based on factors currently known to us and that actual events or results could differ materially. For important factors that may cause actual results to differ from those contained in our forward-looking statements, please review our filings with the SEC.

The forward-looking statements made in this presentation are being made as of the time and date of its live presentation. If reviewed after its live presentation, this presentation may not contain current or accurate information. We do not assume any obligation to update any forward-looking statements we may make. In addition, any information about our roadmap outlines our general product direction and is subject to change at any time without notice. It is for informational purposes only and shall not be incorporated into any contract or other commitment. Splunk undertakes no obligation either to develop the features or functionality described or to include any such feature or functionality in a future release.

Splunk, Splunk>, Listen to Your Data, The Engine for Machine Data, Splunk Cloud, Splunk Light and SPL are trademarks and registered trademarks of Splunk Inc. in the United States and other countries. All other brand names, product names, or trademarks belong to their respective owners. © 2018 Splunk Inc. All rights reserved.




#### How we scaled Splunk LDAP auth to handle hundreds of users and groups





## Logging @ Atlassian


#### Logging @ Atlassian



.CONF 2017 Talk: Traversing the Cloud: Atlassian's Journey Building a Logging Pipeline with Splunk on AWS



## Logging @ Atlassian







#### **Access Control Model**

#### **Access Control**

\* jira-sre
development developers
production customer-support

#### Generates

#### authorize.conf:

```
[role_jira_all_environments_read]
importRoles = user
srchIndexesAllowed = jira

[role_jira_development_read]
importRoles = user
srchIndexesAllowed = jira
srchFilter = environment = development


[role_jira_production_read]
importRoles = user
srchIndexesAllowed = jira
srchFilter = environment = production
```

#### authentication.conf:

```
[roleMap_ldap]
role_jira_all_environments_read = jira-sre
role_jira_development_read = developers
role_jira_production_read = customer-support
```



## Config Deployment Process






#### Our Scale









#### LDAP component slowness

~4s login time on average



~17s login + page load


AVAILABILITY	DOWNTIME	AVERAGE TIME
95.138%	1 hr 17 min	17,536.305 ms





## Active Directory (AD) server load


Splunk instance does the most queries and 98% of the big queries





## Slow auth config deployment

#### ~1 hour deployment time




7:123] "GET /product.screen?category\_id=GIFTs&JSESSIONID=SDISL4FF10ADFF10 HTTP 1.1" 40% /-:56:136] "GET /product.screen?product\_id=FL-DSH-01&JSESSIONID=SD5SL7FF6ADFF9 HTTP 1.1"
)" 468 125.17 14 --""D. 368 125.17 14 --\*\*The screen?category\_id=SU\*\*
""D. 368 125.17 14 ---\*\*The screen?category\_id=SU\*\*
""D. 368 125.17 14 ---\*\*The screen?category\_id=SU\*\*
""D. 368 125.17 14 ----\*\*The screen?category\_id=SU\*\*
\*\*The screen.category\_id=SU\*\*
\*\*The sc



## Auth config bundle deployment failures

1/4 of our bundle deployment failed



#### Questions to answer

- Why is LDAP component (e.g. login) slow?
  - What LDAP queries does Splunk perform?
  - Why are they slow?
  - Why are they resource heavy?


- Why is bundle deployment slow and error-prone?
  - What does bundle deployment do?
  - Which part of the bundle deployment is slow?





## What LDAP queries are being done?

- ScopedLDAPConnection = DEBUG
  - 400k LDAP searches in 15 minute!





## What is querying LDAP?

- Components that queries LDAP
  - 1 User login = 300+ LDAP searches
  - Any components that need user roles:
    - Search scheduler
    - Search dispatcher
    - Data model

#### Why are queries expensive?


- Two key factors:
  - The number of LDAP groups
  - Depth of LDAP group nesting

#### E.g. a troublesome group:

- atlassian-staff:
  - member\_groups (55):
    - exec-team
      - Scott
      - Mike
      - \_
    - sydney-staff
      - observability-team
      - ..
    - mountain-view-staff
    - customer-support
      - amsterdam-support
      - ...



### LDAP query breakdown





## What does bundle deployment do?





#### Access Logs

Deployer: sourcetype=splunkd\_access uri\_path="/services/apps/deploy"


_time ‡	from \$	to \$	1	method \$	uri_path ‡	status 🗘 🖊	spent_ms 🗘 🖊
2018-06-25 17:30:34.799	127.0.0.1	ip-10-124-124-197		POST	/services/apps/deploy	200	413

Searchhead: sourcetype=splunkd\_access uri\_path="/services/apps/local"

_time \$	from ‡	to \$	method 🗘 🗾	uri_path \$	status 🗘 🖊	spent_ms \( \rightarrow \)
2018-06-21 17:05:18.553	10.124.124.197	ip-10-124-124-42	POST	/services/apps/local	200	454364
2018-06-21 16:57:59.024	10.124.124.197	ip-10-124-124-247	POST	/services/apps/local	200	439463
2018-06-21 16:50:17.429	10.124.124.197	ip-10-124-124-83	POST	/services/apps/local	200	461520



#### Bundle Deployment - Putting them together





#### **Bundle Installation - Loggers**

- Again, we enabled some useful debug logs:
  - AppsDeployHandler
  - LocalAppsAdminHandler
  - ApplicationManager
  - ApplicationUpdater
  - UserManagerPro

#### Bundle Installation - Debug logs

```
02-20-2018 05:10:20.075 ApplicationUpdater - Reload atlassian config app: simple reload handler for app
02-20-2018 05:10:20.075 ApplicationUpdater - Reloading via GET on /servicesNS/nobody/atlassian config app/authentication/providers/services/ reload
02-20-2018 05:10:20.085 UserManagerPro - Bouncing auth system as user="splunk-system-user"
02-20-2018 05:10:20.090 UserManagerPro - Entering load authentication
02-20-2018 05:10:20.090 UserManagerPro - authType=ldap
02-20-2018 05:10:20.090 AuthenticationManagerLDAP - Init called: Clearing the user cache
02-20-2018 05:10:20.090 UserManagerPro - LoadLDAPUsersThread: Limiting precaching to 0 users
02-20-2018 05:10:20.090 MultiFactorAuthManager - Reloading MultiFactorAuthManager with updated MfaVendorImpl
02-20-2018 05:10:20.090 UserManagerPro - LoadLDAPUsersThread: Exited
02-20-2018 05:10:20.090 ApplicationUpdater - Reloading via GET on /servicesNS/nobody/atlassian config app/authentication/providers/services/ reload
02-20-2018 05:10:20.097 UserManagerPro - Bouncing auth system as user="splunk-system-user"
02-20-2018 05:10:20.102 UserManagerPro - Entering load authentication
02-20-2018 05:10:20.102 UserManagerPro - authType=ldap
02-20-2018 05:10:20.102 AuthenticationManagerLDAP - Init called: Clearing the user cache
02-20-2018 05:10:20.103 UserManagerPro - LoadLDAPUsersThread: Limiting precaching to 0 users
02-20-2018 05:10:20.103 MultiFactorAuthManager - Reloading MultiFactorAuthManager with updated MfaVendorImpl
02-20-2018 05:10:20.103 UserManagerPro - LoadLDAPUsersThread: Exited
02-20-2018 05:10:20.103 ApplicationUpdater - Reloading via GET on /servicesNS/nobody/atlassian config app/storage/collections/config/ reload
02-20-2018 05:10:20.108 UserManagerPro - Filling info for the system user="splunk-system-user"
02-20-2018 05:10:20.109 UserManagerPro - Filling info for the system user="splunk-system-user"
02-20-2018 05:10:20.117 ApplicationUpdater - Reload atlassian config app: simple reload handler for eventtypes
02-20-2018 05:10:20.117 ApplicationUpdater - Reload atlassian config app: simple reload handler for lookups
02-20-2018 05:10:20.117 ApplicationUpdater - Reloading via GET on /servicesNS/nobody/atlassian config app/admin/transforms-reload/ reload
02-20-2018 05:10:21.363 UserManagerPro - Login work for user started
02-20-2018 05:10:21.365 UserManagerPro - user="admin" successfully logged in
```




#### Bundle Installation - Debug logs

```
02-20-2018 05:10:20.075 ApplicationUpdater - Reloading via GET on /servicesNS/nobody/atlassian config app/authentication/providers/services/ reload
02-20-2018 05:10:20.085 UserManagerPro - Bouncing auth system as user="splunk-system-user"
02-20-2018 05:10:20.090 UserManagerPro - Entering load authentication
02-20-2018 05:10:20.090 UserManagerPro - authType=ldap
02-20-2018 05:10:20.090 AuthenticationManagerLDAP - Init called: Clearing the user cache
   02-20-2018 05:10:20.090 MultiFactorAuthManager - Reloading MultiFactorAuthManager with updated MfaVendorImpl
02-20-2018 05:10:20.090 ApplicationUpdater - Reloading via GET on /servicesNS/nobody/atlassian config app/authentication/providers/services/ reload
02-20-2018 05:10:20.097 UserManagerPro - Bouncing auth system as user="splunk-system-user"
02-20-2018 05:10:20.102 UserManagerPro - Entering load authentication
02-20-2018 05:10:20.102 UserManagerPro - authType=ldap
02-20-2018 05:10:20.102 AuthenticationManagerLDAP - Init called: Clearing the user cache
   02-20-2018 05:10:20.103 MultiFactorAuthManager - Reloading MultiFactorAuthManager with updated MfaVendorImpl
  02-20-2018 05:10:20.108 UserManagerPro - Filling info for the system user="splunk-system-user"
  02-20-2018 05:10:20.109 UserManagerPro - Filling info for the system user="splunk-system-user"
  02-20-2018 05:10:20.117 ApplicationUpdater - Reload atlassian config app: simple reload handler for eventtypes
  02-20-2018 05:10:20.117 ApplicationUpdater - Reload atlassian config app: simple reload handler for lookups
  02-20-2018 05:10:21.363 UserManagerPro - Login work for user started
```




#### Bundle Deployment - Putting them together

#### /authentication/\_reload






### Flamegraphs



Source: http://www.brendangregg.com/FlameGraphs/cpu-linux-execs.svg



#### Bundle Installation Flamegraph



LocalAppsAdminHandler::reloadAppEndpoints(Str

#### LocalAppsAdminHandler::handleInstall(ConfigInfo&,

"GET /product.screen?category\_id=GIFTS&JSESSIONID=SDISL4FF10ADFF10 HTTP 1.1" 404 720 - 115522 | GET /product.screen?product\_id=FL-DSH-01&JSESSIONID=SDSSL7F6ADFF9 HTTP 1.1" 404 //but | http://but

```
MConfigHandler::executeHandler(ConfigInfo&)

MConfigHandler::go(ConfigInfo&)

AdminManagerReplyDataProvider::go()

ServicesEndpointReplyDataProvider::rawHandle()

RawRestHttpHandler::getPreBody(HttpServerTransaction*)

HttpThreadedCommunicationHandler::communicate(TcpSyncDataBuffer&)

TcpChannelThread::main()

Thread::callMain(void*)

start_thread

clone

all
```




#### Recap

- LDAP component slowness
  - Splunk needs to query a big tree of LDAP groups for each user.


- AD server load
  - Compounding the problem above, a lot of components in Splunk also need to query user info.
- Slow bundle deployment
  - Bundle installation includes reloading authentication information for everyone twice.

## Solutions

#### **Previous Architecture**



#### LDAP Cache?





#### Possible Solutions

- Restructure LDAP groups
- Change authentication scheme





#### **Script Functions**

- userLogin
  - Can be a basic LDAP bind



- getUserInfo
  - **Determines ACL**
  - Gets called frequently and concurrently
  - Unrealistic to do LDAP query






#### **Script Functions**


- getUsers
  - Roles are not used for ACL (7.0.4)
  - Determines if schedule search gets run




#### **New Architecture**



Login API (4s -> 0.7s)




Login API + Page load (17s -> 14s)






No more LDAP query spamming






Faster and less erroneous bundle deployment (8mins -> 1.5mins)





Lower saved search skip ratio (75% -> 8%)







# Key Takeaways LDAP auth

- Nested LDAP structure and the number of groups can negatively affect performance
- Use ScopedLDAPConnection to profile your LDAP queries
- 3. Beware of auth reloads when deploying authorize.conf and authentication.conf via bundle

# Key Takeaways Splunk Debuging

- 1. Loggers are great, enable them for troubleshooting
- 2. Flamegraph can help with finding problematic components
- 3. Access log gives you a glimpse of the internal workings of Splunk

# Key Takeaways Scripted Auth

- 1. Instrument your auth script
- Ingest script logs back into Splunk for debugging
- 3. The script need to be implemented efficiently

## Thank You

Don't forget to rate this session in the .conf18 mobile app

.Conf18
splunk>