RSAC Sandbox

RSAConference2020

HUMAN ELEMENT

SESSION ID: **SBX1-W1**

Mitigating Network-Based Attacks Using MUD

Improving Security of Small-Business and Home IoT Devices

Practical Use of the MUD Specification

Dr. Parisa Grayeli

Principal Information Systems Engineer
MITRE/NIST National Cybersecurity Center of Excellence (NCCoE)

Blaine Mulugeta

Cyber Engineer
MITRE/NIST National Cybersecurity Center of Excellence (NCCoE)

NIST NCCoE's Mission

RSAC Sandbox

Engagement and Business Model

RSAC Sandbox

DEFINE

OUTCOME:
Define a scope of work with industry to solve a pressing cybersecurity challenge

ASSEMBLE

OUTCOME:
Assemble teams of industry orgs, govt agencies, and academic institutions to address all aspects of the cybersecurity challenge

BUILD



OUTCOME:
Build a practical, usable, repeatable implementation to address the cybersecurity challenge

ADVOCATE

OUTCOME:
Advocate adoption of the example implementation by using the practice guide

Introduction

- There will be 25 billion connected things in use by 2021 (per Gartner)
- As IoT devices become more common in homes and businesses, security concerns are also increasing
- IoT devices represent one of the largest attack surfaces – Some have minimal security, are unprotected or are difficult to secure
- IoT devices have been exploited to launch DDoS attacks (e.g. Mirai)



Mitigating Network-Based Attacks Using MUD

Improving the security of small-business and home IoT devices

RSAC Sandbox

Challenge

- IoT devices are given full connectivity to the internet by default
- Device security may not be a priority due to processing, timing, memory, and power constraints
- Networked devices can be detected within minutes and exploited due to known security flaws, leading to easily scalable attacks

Solution

- NCCoE developed a proof of concept implementation for the home or small business network to address some of these security concerns in collaboration with Industry collaborators
- Use network gateway components and security-aware IoT devices that leverage the Manufacturer Usage Description (MUD) Specification (RFC 8520)
- Using MUD the network will automatically permit the IoT device to send and receive the traffic it requires to perform as intended, and the network will prohibit all other communication with device

Typical Home/Small Business Network (Without MUD)



RSAC Sandbox



RSAC Sandbox



RSAC Sandbox



RSAC Sandbox



RSAC Sandbox


RSAC Sandbox
Attacker
Target
Manufacturer Server
Internet
Home/Small Business
COOLING
28°C



RSAC Sandbox



RSAC Sandbox



RSAC Sandbox



RSAC Sandbox

Typical Home/Small Business Network (With MUD)



RSAC Sandbox


RSAC Sandbox
Attacker
Target
Manufacturer Server
Internet
Home/Small Business
COOLING
28°C


RSAC Sandbox
Attacker
Target
Manufacturer Server
Internet
Home/Small Business
COOLING
28°C


RSAC Sandbox
Attacker
Target
Manufacturer Server
Internet
Home/Small Business
COOLING
28°C



RSAC Sandbox

Architecture Overview

Reference Architecture



Lab Architecture

RSAC Sandbox



Project Status

RSAC Sandbox

- Build 1, 2 and 4 Practice Guide SP 1800-15
  - Preliminary Draft Published in Nov. 2019

- Currently working on Build 3
  - Includes MUD and DPP (Device Provisioning Protocol)

https://www.nccoe.nist.gov/projects/building-blocks/mitigating-iot-based-ddos

Collaborators

Build 1 Demo Presentation

BUILD 1 – CISCO

- Cisco MUD Manager and FreeRadius
- Cisco Catalyst Switch
- NCCoE hosted MUD File Server
- MUD File
- DigiCert certificates
- MUD-capable IoT devices:
  - Molex PoE GW and Light Engine
  - Devkits
- Non-MUD-capable IoT devices
- NCCoE hosted Update Server
- NCCoE hosted Unapproved Server
- NCCoE hosted MQTT Broker Server
- Forescout and Forescout Enterprise Manager

BUILD 2 – MASTERPEACE & GCA

- Yikes! Router including MUD Manager
- Yikes! Cloud & Yikes! Mobile App
- MasterPeace hosted MUD File Server
- MUD File
- DigiCert certificates
- MUD-capable IoT devices - Devkits
- Non-MUD-capable IoT devices
- NCCoE hosted Update Server
- NCCoE hosted Unapproved Server
- GCA Quad9 Threat Agent integrated into Yikes! Router
- GCA Quad9 Threat Signaling MUD Manager integrated into Yikes! Router
- GCA Quad9 Threat-Signaling DNS Services
- GCA Quad9 Threat API
- ThreatSTOP Threat MUD File Server
- ThreatSTOP Threat MUD File

BUILD 4 - NIST

- OpenDaylight SDN Controller including MUD Manager
- NCCoE hosted MUD File Server
- MUD File
- Wireless SDN Switch
- DigiCert certificates
- MUD-capable IoT devices - Devkits
- Non-MUD-capable IoT devices
- NCCoE hosted Unapproved Server
- Approved Server

BUILD 3 - CABLELABS

- Micronets Gateway
- Micronets Manager
- MUD Manager
- MUD Registry
- MSO Portal
- MUD File Server
- MUD File
- DigiCert certificates
- MUD-capable IoT devices - Devkits
- Non-MUD-capable IoT devices
- Update Server
- Unapproved Server
- Micronets Mobile App

PHASE 1 → **PHASE 2** → **PHASE 3**

Logical Architecture – Build 1



Step 1: Connect Device



Step 1: Connect Device

RSAC Sandbox

1. No session on interface

Router or Switch

```
Build1#sho access-session int g1/0/19 det
No sessions match supplied criteria.
```

2. Connect MUD enabled IoT Device

Devices

```
pi@raspberrypi:~ $ sudo dhclient -v
```

3. Interface state changed to up

Router or Switch

```
Build1#sho access-session int g1/0/19 det
No sessions match supplied criteria.

Build1#
*Mar 26 14:19:29.140: %LINK-3-UPDOWN: Interface GigabitEthernet1/0/19, changed state to up
*Mar 26 14:19:30.141: %LINEPROTO-5-UPDOWN: Line protocol on Interface GigabitEthernet1/0/19,
```

Step 2a/2b: Send MUD URL to MUD Manager



Step 2a/2b: Send MUD URL to MUD Manager

RSAC Sandbox

FreeRadius

1. FreeRadius service receives and passes MUD URL

```
FreeRadius Server started:
 Ready to process requests

Accounting Request from Switch:
(0) Received Accounting-Request Id 198 from 192.168.11.1:43714 to 192.168.11.45:1813 length 944
(0)   Cisco-AVPair = "dhcp-option=\\000\\014\\000\\013raspberrypi"
(0)   Cisco-AVPair = "dhcp-option=\\000\\377\\000aspberrypi\\241\\036https://mudfileserver/ciscopi27\\r\
\\001\\034\\002\\003\\017\\006w\\014,/\\032y*\\377\\367\\007D\\212\\221$\\316\\004c\\021\\303A\\026\\370\
\\035W\\230\\233\\224\\346o\\276L\\203E\\022\\317g\\270\\320\\332\\027e\\223\\365UT\\262\\305E"
(0)   User-Name = "b827ebeb6c8b"

MUD URL and Hardware Address extracted:
rlm_perl: Returning MUD URL from DHCP Option: https://mudfileserver/ciscopi2
rlm_perl: Returning User-Name from 'User-Name': b827ebeb6c8b

Post sent to MUD Manager:
(0) rest: Sending HTTP POST to "http://127.0.0.1:8000//getaclname"
(0) rest: EXPAND \{"%\{Url-DataType\}":"%\{Url-Data\}","%\{Url-AddDataType\}":"%\{Url-AddData\}","%\{Url-
NasType\}":"%\{Url-Nas\}","%\{Url-SessidType\}":"%\{Url-Sessid\}"\}
(0) rest:     --> \{"MAC_ADDR":"b827ebeb6c8b","MUD_URI":"https://mudfileserver/
ciscopi2","NAS":"192.168.11.1","SESS_ID":"00000006"\}
```

Step 2b: Send MUD URL to MUD Manager

RSAC Sandbox

2. MUD Manager receives MUD enabled IoT Device information from FreeRadius Service

MUD Manager

```
MUD Manager started:
***MUDC [INFO][main:2992]--> Starting RESTful server on port 8000
Post received:
***MUDC [INFO][mudc_print_request_info:2185]--> print parsed HTTP request header info
***MUDC [INFO][mudc_print_request_info:2186]--> request method: POST
***MUDC [INFO][mudc_print_request_info:2187]--> request uri: /getaclname
***MUDC [INFO][mudc_print_request_info:2199]--> header(1): name: <User-Agent>, value: <FreeRADIUS 3.0.17>
Check Database for Hardware Address of Device:
***MUDC [INFO][handle_get_aclname:2506]--> Mac address <b827ebeb6c8b>
***MUDC [INFO][handle_get_aclname:2522]--> No URL found in macaddr db for MAC address b827ebeb6c8b
```

Step 3/4: Get MUD and Signature File



Step 3/4: Get MUD and Signature File

RSAC Sandbox

1. Get MUD and Signature file

MUD Manager

```
Get MUD File:
***MUDC [INFO][handle_get_aclname:2558]--> Got URL from message <https://mudfileserver/ciscopi2>
***MUDC [STATUS][send_mudfs_request:2005]-> Request URI <https://mudfileserver/ciscopi2> </home/
mudtester/mud-intermediate.pem>
> GET /ciscopi2.json HTTP/1.1
***MUDC [INFO][send_mudfs_request:2033]--> MUD file successfully retrieved
Get MUD Signature:
***MUDC [STATUS][send_mudfs_request:2060]--> Request signature URI <https://mudfileserver/ciscopi2.p7s>
</home/mudtester/mud-intermediate.pem>
> GET /ciscopi2.p7s HTTP/1.1
***MUDC [INFO][send_mudfs_request:2088]--> MUD signature file successfully retrieved
```

2. Verify MUD file

MUD Manager

```
Verify MUD File:
***MUDC [INFO][verify_mud_content:1609]--> Verification Successful
```

Step 5a: Send Device Traffic Filters



Step 5a: Send Device Traffic Filters

RSAC Sandbox

MUD Manager

1. MUD File parsed and translated to ACL (rules)

```
MUD File Parsed and Rules Create:
***MUDC [INFO][create_cisco_dacl_policy:63]--> ACLName <mud-81726-v4fr> 0
***MUDC [INFO][create_cisco_dacl_policy:95]--> Ace Count <7>
***MUDC [INFO][create_cisco_dacl_policy:243]--> Returning parsed_json [{
        "DACL_Name":   "ACS:CiscoSecure-Defined-ACL=mud-81726-v4fr.in",
        "DACL":["ip:inacl#10=permit tcp any host 192.168.4.7 range 80 80 syn ack", "ip:inacl#20=permit tcp
any host 192.168.10.104 range 80 80", "ip:inacl#30=permit tcp any host 192.168.10.105 range 80 80",
"ip:inacl#40=permit tcp any host 192.168.10.125 range 80 80", "ip:inacl#50=permit tcp any 192.168.10.0
0.0.0.255 range 80 80", "ip:inacl#60=permit tcp any 192.168.13.0 0.0.0.255 range 80 80",
"ip:inacl#70=permit tcp any 192.168.14.0 0.0.0.255 range 80 80", "ip:inacl#80=permit tcp any eq 22 any",
"ip:inacl#81=permit udp any eq 68 any eq 67", "ip:inacl#82=permit udp any any eq 53", "ip:inacl#83=deny
ip any any"],
        "VLAN":3
    }]
```

MUD Manager

2. MUD Manager sends ACL

```
Send Rules to Switch through FreeRadius Server:
***MUDC [INFO][attempt_coa:1915]--> Initiating CoA for Acct-Session-Id: 00000006
Sent CoA-Request Id 89 from 0.0.0.0:36772 to 192.168.11.1:1700 length 89
```

Step 5a: Send Device Traffic Filters

RSAC Sandbox

FreeRadius

3. FreeRadius receives ACL from MUD Manager

```
Post sent to MUD Manager:
(0) rest: Sending HTTP POST to "http://127.0.0.1:8000//getaclname"
(0) rest: EXPAND \{"%\{Url-DataType\}":"%\{Url-Data\}","%\{Url-AddDataType\}":"%\{Url-Add
NasType\}":"%\{Url-Nas\}","%\{Url-SessidType\}":"%\{Url-Sessid\}"\}
(0) rest:    --> \{"MAC_ADDR":"b827ebeb6c8b","MUD_URI":"https://mudfileserver/
ciscopi2","NAS":"192.168.11.1","SESS_ID":"00000006"\}
ACL received:
(0) rest: Parsing attribute "Cisco-AVPair"
(0) rest: EXPAND ACS:CiscoSecure-Defined-ACL=mud-81726-v4fr.in
(0) rest:    --> ACS:CiscoSecure-Defined-ACL=mud-81726-v4fr.in
(0) rest: Cisco-AVPair := "ACS:CiscoSecure-Defined-ACL=mud-81726-v4fr.in"
```

Step 5b: Send Device Traffic Filters



Step 5b: Send Device Traffic Filters

RSAC Sandbox

FreeRadius

1. FreeRadius sends ACL to switch

```
Sending ACLs to Switch:

Sent Accounting-Response Id 198 from 192.168.11.45:1813 to 192.168.11.1:43714 length 0
(0)    Cisco-AVPair = "ACS:CiscoSecure-Defined-ACL=mud-81726-v4fr.in"

Request completed:

(0) Finished request
```

Router or Switch

2. ACL received, and configurations applied

```
Build1#sho access-session int g1/0/19 det
No sessions match supplied criteria.

Build1#
*Mar 26 14:19:29.140: %LINK-3-UPDOWN: Interface GigabitEthernet1/0/19, change
*Mar 26 14:19:30.141: %LINEPROTO-5-UPDOWN: Line protocol on Interface Gigabi
*Mar 26 14:20:14.301: %LINK-3-UPDOWN: Interface Vlan3, changed state to up
*Mar 26 14:20:15.301: %LINEPROTO-5-UPDOWN: Line protocol on Interface Vlan3,
```

Step 6: IP Address Assigned



Step 6: IP address assigned

RSAC Sandbox

1. IoT Device receives IP address

Devices

```
DHCPDISCOVER on eth0 to 255.255.255.255 port 67 interval 16
DHCPREQUEST of 192.168.13.22 on eth0 to 255.255.255.255 port 67
DHCPOFFER of 192.168.13.22 from 192.168.13.1
DHCPACK of 192.168.13.22 from 192.168.13.1
Too few arguments.
Too few arguments.
bound to 192.168.13.22 -- renewal in 19835 seconds.
pi@raspberrypi:~ $
```

Step 6: IP address assigned

RSAC Sandbox

1. Show access-session

Router or Switch

```
Build1#sho access-session int g1/0/19 det
            Interface:  GigabitEthernet1/0/19
               IIF-ID:  0x125ECD95
          MAC Address:  b827.ebcf.7b81
         IPv6 Address:  Unknown
         IPv4 Address:  192.168.13.22
            User-Name:  b827ebcf7b81
               Status:  Authorized
               Domain:  DATA
      Oper host mode:  multi-auth
    Oper control dir:  both
     Session timeout:  N/A
   Common Session ID:  C0A80A0200000068BA5F00E3
     Acct Session ID:  0x00000012
              Handle:  0x9b00005e
      Current Policy:  mud-mab-test


Server Policies:
             ACS ACL:  mud-81726-v4fr.in
         Vlan Group:  Vlan: 3


Method status list:
       Method           State
          mab           Authc Success
```

2. Show access-lists

Router or Switch

```
Build1#sho access-lists
Extended IP access list mud-81726-v4fr.in
    10 permit tcp any host 192.168.4.7 eq www ack syn
    20 permit tcp any host 192.168.10.104 eq www
    30 permit tcp any host 192.168.10.105 eq www
    40 permit tcp any host 192.168.10.125 eq www
    50 permit tcp any 192.168.10.0 0.0.0.255 eq www
    60 permit tcp any 192.168.13.0 0.0.0.255 eq www
    70 permit tcp any 192.168.14.0 0.0.0.255 eq www
    80 permit tcp any eq 22 any
    81 permit udp any eq bootpc any eq bootps
    82 permit udp any any eq domain
    83 deny ip any any
```

Step 7: Test communication



Step 7: Test communication

RSAC Sandbox

1. Test browsing to "Update Server"



2. Test browsing to unapproved server



Build 2 Demo Presentation

BUILD 1 – CISCO

- Cisco MUD Manager and FreeRadius
- Cisco Catalyst Switch
- NCCoE hosted MUD File Server
- MUD File
- DigiCert certificates
- MUD-capable IoT devices:
  - Molex PoE GW and Light Engine
  - Devkits
- Non-MUD-capable IoT devices
- NCCoE hosted Update Server
- NCCoE hosted Unapproved Server
- NCCoE hosted MQTT Broker Server
- Forescout and Forescout Enterprise Manager

BUILD 2 – MASTERPEACE & GCA

- Yikes! Router including MUD Manager
- Yikes! Cloud & Yikes! Mobile App
- MasterPeace hosted MUD File Server
- MUD File
- DigiCert certificates
- MUD-capable IoT devices - Devkits
- Non-MUD-capable IoT devices
- NCCoE hosted Update Server
- NCCoE hosted Unapproved Server
- GCA Quad9 Threat Agent integrated into Yikes! Router
- GCA Quad9 Threat Signaling MUD Manager integrated into Yikes! Router
- GCA Quad9 Threat-Signaling DNS Services
- GCA Quad9 Threat API
- ThreatSTOP Threat MUD File Server
- ThreatSTOP Threat MUD File

BUILD 4 - NIST

- OpenDaylight SDN Controller including MUD Manager
- NCCoE hosted MUD File Server
- MUD File
- Wireless SDN Switch
- DigiCert certificates
- MUD-capable IoT devices - Devkits
- Non-MUD-capable IoT devices
- NCCoE hosted Unapproved Server
- Approved Server

BUILD 3 - CABLELABS

- Micronets Gateway
- Micronets Manager
- MUD Manager
- MUD Registry
- MSO Portal
- MUD File Server
- MUD File
- DigiCert certificates
- MUD-capable IoT devices - Devkits
- Non-MUD-capable IoT devices
- Update Server
- Unapproved Server
- Micronets Mobile App

PHASE 1 → **PHASE 2** → **PHASE 3**

Logical Architecture – Build 2

RSAC Sandbox



Step 1-5: Processing, applying, and viewing MUD File Rules



Step 1-5: Processing, applying, and viewing MUD File Rules

RSAC Sandbox

1. View all MUD devices on network

yikes!
Mobile Application



2. Expand device's profile

yikes!
Mobile Application



Logical Architecture – Build 2 (Threat Signaling)

RSAC Sandbox



Step 1-2: Device attempts to communicate with compromised site

RSAC Sandbox



Step 3: Router receives DNS response from Quad9 DNS Service

RSAC Sandbox



Step 4-6: Threat found and local Quad9 MUD Manager notified

RSAC Sandbox



Step 7-9: Threat MUD file and signature file requested, verified, and applied on router

RSAC Sandbox



Apply What You Have Learned Today

RSAC Sandbox

- Short term:
  - Review published Practice Guide for more details
  - Join NCCoE IoT MUD Community of Interest - mitigating-iot-ddos-nccoe@nist.gov
- Long term:
  - IoT device manufacturers, and network equipment manufacturers could implement MUD to improve the security of their products and of their customers' networks
  - IoT device users could purchase MUD-capable devices, when available, to protect their IoT devices from network-based attacks

https://www.nccoe.nist.gov/projects/building-blocks/mitigating-iot-based-ddos

Acknowledgements

- **NIST:**
  - Donna Dodson, Douglas Montgomery, Tim Polk, Mudumbai Ranganathan, Murugiah Souppaya
- **Arm:**
  - Allaukik Abhishek
- **CableLabs:**
  - Steve Johnson, Ashwini Kadam, Craig Pratt, Darshak Thakore, Mark Walker, Tao Wan
- **Cisco:**
  - Russ Gyurek, Eliot Lear, Peter Romness, Brian Weis
- **CTIA:**
  - Rob Cantu
- **Dakota Consulting:**
  - William Barker
- **DigiCert:**
  - Dean Coclin, Avesta Hojjati, Clint Wilson
- **Forescout:**
  - Katherine Gronberg, Tim Jones
- **Global Cyber Alliance:**
  - Adnan Baykal
- **MasterPeace Solutions:**
  - Drew Cohen, Nate Lesser, Kevin Yeich
- **The MITRE Corporation:**
  - Yemi Fashina, Joshua Harrington, Joshua Klosterman, Mary Raguso, Susan Symington, Paul Watrobski
- **Molex:**
  - Mo Alhroub, Jaideep Singh
- **Patton Electronics:**
  - Bryan Dubois, Stephen Ochs
- **Symantec:**
  - Matt Boucher, Bruce McCorkendale, Susanta Nanda, Yun Shen
- **Vigil Security:**
  - Russ Housley

Contact Information

RSAC Sandbox

https://www.nccoe.nist.gov/projects/building-blocks/mitigating-iot-based-ddos

mitigating-iot-ddos-nccoe@nist.gov

Backups

Logical Architecture – Build 2 (Threat Signaling)

RSAC Sandbox



Step 1-2: Device attempts to communicate with compromised site

RSAC Sandbox



Step 1-2: Device attempts to communicate with compromised site

RSAC Sandbox

1. Device Pings known malicious host




```
$ ping www.dangeroussite.org
ping: cannot resolve www.dangeroussite.org: Unknown host
```

Step 3: Router receives DNS response from Quad9 DNS Service

RSAC Sandbox



Step 3: Router receives DNS response from Quad9 DNS Service

RSAC Sandbox



1. Quad9 Agent receives DNS response

```
9.9.9.9.53 > 192.168.5.2.17847: [udp sum ok] 26864 NXDomain- q: A?
dangerousSite.org. 0/0/0 (29)
A? - dangerousSite.org - https://api.quad9.net/search
```

Step 4-6: Threat found and local Quad9 MUD Manager notified

RSAC Sandbox



Step 4-6: Threat found and local Quad9 MUD Manager notified

RSAC Sandbox

1. Quad9 Agent queries Quad9 API to confirm potential threat


```
DEBUG: runQuad9(): Calling Quad9 on:curl -s  -o /tmp/dangerousSite.org.q9
https://api.quad9.net/search/dangerousSite.org
DEBUG: runQuad9(): Search returned
{"domain":“dangerousSitre.org","blocked":true,"blocked_by":["threatstop"],"meta":[{"name":"ThreatSTOP
"}]} stored in /tmp/dangerousSite.org.q9
```

2. Quad9 Agent parses threat query response from Quad9 API and validates that site is blocked




```
DEBUG: runQuad9(): Download success via Quad9 threat API.
DEBUG: isQuad9Blocked(): Calling: jq  .blocked /tmp/dangerousSite.org.q9
https://api.quad9.net/search/dangerousSite.org
DEBUG: isQuad9Blocked(): Command result: true
DEBUG: isBlockedByProvider(): Calling: jq  -c .blocked_by /tmp/dangerousSite.org.q9
https://api.quad9.net/search/dangerousSite.org
DEUBG: isBlockedByProvider(): ["threatstop"] ---===--- threatstop
WARN: isBlockedByProvider(): Threat WAS FOUND TO BE BAD by threatstop
```

3. Quad9 Agent notifies Quad9 MUD Manager that threat has been found




```
DEBUG: runQuad9(): Threat provider threatstop: They found  to be bad. Call them now for more
detailed threat response information.
```

Step 7-9: Threat MUD file and signature file requested, verified, and applied on router

RSAC Sandbox



Step 7-9: Threat MUD file and signature file requested, verified, and applied on router

RSAC Sandbox

1. Quad9 MUD Manager requests Threat MUD and Signature file and validates respectively

```
DEBUG: retrieveThreatProviderFile(): Calling: curl -s  -o /etc/q9thrt/state/mudfiles/dangerousSite.org.json
https://mud.threatstop.com/dangerousSite.org.json
INFO: retrieveThreatProviderFile(): MUD FILE RETRIEVED
DEBUG: retrieveThreatProviderFile(): Calling: curl -s  -o /etc/q9thrt/state/mudfiles/dangerousSite.org.p7s
https://mud.threatstop.com/dangerousSite.org.p7s
INFO: retrieveThreatProviderFile(): SIGNATURE FILE RETRIEVED
DEBUG: testMudFile(): Calling: jq  -r '.["ietf-mud:mud"]["mud-version"]'
/etc/q9thrt/state/mudfiles/dangerousSite.org.json
DEBUG: testMudFile(): Valid Mud file: MudVersion = 1
DEBUG: testMudFileSignature(): Calling: openssl asn1parse -in /etc/q9thrt/state/mudfiles/dangerousSite.org.p7s
-inform der | grep -i error | wc -l
DEBUG: testMudFileSignature(): Valid Mud file signature.
DEBUG: validateThreatMudFile(): Both the MUD file and MUD p7s signature files are valid. Now test signature.
DEBUG: validateThreatMudFile(): Calling: openssl cms -verify -in
/etc/q9thrt/state/mudfiles/dangerousSite.org.p7s -inform DER -content
/etc/q9thrt/state/mudfiles/dangerousSite.org.json > /dev/null
INFO: validateThreatMudFile(): MUD FILE SIGNATURE PASSED
```



Step 7-9: Threat MUD file and signature file requested, verified, and applied on router

RSAC Sandbox

2. Quad9 MUD Manager builds and applies policies to local DNS and Firewall




```
DEBUG: runQuad9(): Installing valid mud file:
/etc/q9thrt/state/mudfiles/dangerousSite.org.json
DEBUG: installMudFile(): Calling:
/etc/q9thrt/build_policies.sh -e dangerousSite.org -m
/etc/q9thrt/state/mudfiles/dangerousSite.org.json -s lan -d
wan -k /etc/q9thrt/state/rules
INFO: installMudFile(): MUD FILE INSTALLED
DEBUG: installMudFile(): Calling:
/etc/q9thrt/build_policies.sh -e dangerousSite.org -m
/etc/q9thrt/state/mudfiles/dangerousSite.org.json -s wan -d
lan -k /etc/q9thrt/state/rules
INFO: installMudFile(): MUD FILE INSTALLED
DEBUG: commitThreatConfiguration(): Calling:
/etc/q9thrt/commit_threat_rules.sh -d
/etc/q9thrt/state/rules -t /tmp/q9thrt_tmp_dir
```

3. Quad9 Firewall Rules




```
# Q9THREATRULES start
config ipset
    option enabled 1
    option name Q9TS-dangerousSite_orgFD
    option match dest_ip
    option storage hash
    option family ipv4
    option external Q9TS-dangerousSite_orgFD
config ipset
    option enabled 1
    option name Q9TS-dangerousSite_orgTD
    option match src_ip
    option storage hash
    option family ipv4
    option external Q9TS-dangerousSite_orgTD
 config rule
        option enabled   '1'
        option name      'Q9TS-dangerousSite_orgFD'
        option target    REJECT
        option src       lan
        option dest      wan
        option proto     all
        option family    ipv4
        option ipset     Q9TS-dangerousSite_orgFD
        option src_ip    any
 config rule
        option enabled   '1'
        option name      'Q9TS-dangerousSite_orgTD'
        option target    REJECT
        option src       wan
        option dest      lan
        option proto     all
        option family    ipv4
        option ipset     Q9TS-dangerousSite_orgTD
        option dest_ip    any
# Q9THREATRULES end
```

Step 7-9: Threat MUD file and signature file requested, verified, and applied on router

RSAC Sandbox

4. Device attempts to communicate with malicious host after rules are applied – DNS now resolves dangerousSite.org to IoT device loopback address




```
$ ping www.dangerousSite.org
PING www.dangerousSite.org(127.0.0.1): 56 data bytes
64 bytes from 127.0.0.1: icmp_seq=0 ttl=64 time=0.049 ms
64 bytes from 127.0.0.1: icmp_seq=1 ttl=64 time=0.073 ms
64 bytes from 127.0.0.1: icmp_seq=2 ttl=64 time=0.082 ms
64 bytes from 127.0.0.1: icmp_seq=3 ttl=64 time=0.139 ms
64 bytes from 127.0.0.1: icmp_seq=4 ttl=64 time=0.079 ms
64 bytes from 127.0.0.1: icmp_seq=5 ttl=64 time=0.072 ms
64 bytes from 127.0.0.1: icmp_seq=6 ttl=64 time=0.123 ms
64 bytes from 127.0.0.1: icmp_seq=7 ttl=64 time=0.073 ms
ç64 bytes from 127.0.0.1: icmp_seq=8 ttl=64 time=0.066 ms
^C
--- www.dangerousSite.org ping statistics ---
9 packets transmitted, 9 packets received, 0.0% packet loss
round-trip min/avg/max/stddev = 0.049/0.084/0.139/0.027 ms
```

MUD File maker - MUDMaker.org

RSAC Sandbox

Please enter host and model the intended MUD-URL for this device:

https://www.test.com / (model name here->)RSACSandbox

Manufacturer Name Test

Please provide a URL to documentation about this device:

https://www.test.com/readme.txt

How will this device communicate on the network?

Type of access	Allow?
Internet communication Select this type to enter domain names of services that you want this device to access.	☑
Access to controllers specific to this device (no need to name a class). This is "my-controller".	☐
Controller access Access to **classes** of devices that are known to be controllers. Use this when you want different types of devices to access the same controller.	☐
Local communication Access to/from **any** local host for specific services (like COAP or HTTP)	☐
Devices to named manufacturers Access to of devices that are identified by the domain names in their MUD URLs	☐
Access to devices to/from the same manufacturer based on the domain name in the MUD URL.	☑

This device speaks IPv4

This device speaks IPv4

Create rules below

Internet Hosts

www.google.com Protocol TCP +

Local Port any Remote Port 443 Initiated by Thing

Same Manufacturer

(filled in by system) Protocol UDP +

Local Port any Remote Port 5000

SUBMIT RESET

NCCoE NATIONAL CYBERSECURITY CENTER OF EXCELLENCE

RSAConference2020

Sample MUD File


```
{
 "ietf-mud:mud": {
  "mud-version": 1,
  "mud-url": "https://www.test.com/RSACSandbox",
  "last-update": "2020-01-14T19:45:00+00:00",
  "cache-validity": 48,
  "is-supported": true,
  "systeminfo": "Test MUD File for RSAC 2020",
  "mfg-name": "Test",
  "documentation": "https://www.test.com/readme.txt",
  "model-name": "RSACSandbox",
  "from-device-policy": {
   "access-lists": {
    "access-list": [
     {
      "name": "mud-33577-v4fr"
     }
    ]
   }
  },
  "to-device-policy": {
   "access-lists": {
    "access-list": [
     {
      "name": "mud-33577-v4to"
[.....]
[.....]
 "ietf-access-control-list:acls": {
  "acl": [
   {
    "name": "mud-33577-v4to",
    "type": "ipv4-acl-type",
    "aces": {
     "ace": [
      {
       "name": "cl0-todev",
       "matches": {
        "ipv4": {
         "ietf-acldns:src-dnsname": "www.google.com",
         "protocol": 6
        },
        "tcp": {
         "ietf-mud:direction-initiated": "from-device",
         "source-port": {
          "operator": "eq",
          "port": 443
         }
        }
       },
       "actions": {
        "forwarding": "accept"
       }
      },

[....]
```