My Bro The ELK

Obtaining Security Context from Security Events

black hat®
USA 2015

Travis Smith
tsmith@tripwire.com

UBM
Tech

Agenda

- What is the problem?
- Who is the Bro?
- What is an ELK?
- Beefing up the ELK
- Making Your Bro the ELK Intelligent
- Visualization w/ Kibana
- Introducing the TARDIS framework

Full Packet Capture

PSTR
(packet string)

Session

Log,
Alerts
Stats

Source: Applied Network Security Monitoring

Full Packet Capture

Bro

conn.log
dhcp.log
dnp3.log
dns.log
ftp.log
http.log
irc.log
known_services.log
modbus.log
ius.log
smtp.log
snmp.log
ssh.log
ssl.log
syslog.log
tunnel.log
intel.log
notice.log

FILE	TCP/UDP	STDIN	40+ More

FILTERS

GROK	GEOIP	TRANSLATE	TRANSLATE	30+ More

OUTPUTS

ElasticSearch	Syslog	Email	STDOUT	50+ More

SECURITY DATA > BIG DATA

Threat Intelligence Made Easy

black hat USA 2015

Critical Stack Agent

98 Threat Feeds

ID	NAME	LAST UPDATED	INDICATOR COUNT
1	Matsnu-Botnet-(Master-Feed)	04/03/15-10:20-am-(-0400)	9
2	C&Cs-IP-List	04/15/15-10:30-am-(-0400)	134
3	Cryptolocker-(Master-Feed)	04/14/15-01:43-pm-(-0400)	0
4	Post-Tovar-GameOver-Zeus-(Master-Feed)	03/26/15-02:12-pm-(-0400)	0
5	Tinybanker-/-Tinba-(Master-Feed)	03/26/15-02:12-pm-(-0400)	132
6	PushDo-Malware-(Master-Feed)	03/26/15-02:12-pm-(-0400)	0
7	Known-Tor-Exit-Nodes	04/16/15-11:16-am-(-0400)	6567
8	Cyber-Crime-Tracker	04/17/15-02:30-pm-(-0400)	3163
9	Zeus-Tracker:-Configs	03/26/15-02:14-pm-(-0400)	88
10	Zeus-Tracker:-Drop-Zones	03/26/15-02:14-pm-(-0400)	50
11	Zeus-Tracker:-Binaries	04/16/15-11:35-am-(-0400)	59
12	SSL-Blacklist-(SSLBL)	03/26/15-02:12-pm-(-0400)	546
13	Palevo:-Domain-Block-List	04/07/15-11:58-am-(-0400)	15
14	Palevo:-IP-Block-List	03/26/15-02:13-pm-(-0400)	14
15	Zeus-Tracker:-Domain-Block-List	03/30/15-01:23-pm-(-0400)	589
16	SpyEye:-IP-Block-List	02/19/15-01:08-pm-(-0500)	84
17	SpyEye:-Domain-Block-List	02/25/15-05:57-pm-(-0500)	127
18	PhishTank-Intel-Feed-(Verified)	04/16/15-04:57-pm-(-0400)	27734
19	Abuse-Reporting-and-Blacklisting	04/16/15-11:27-am-(-0400)	7666
20	DShield-Domain-List-(Low-Sev)	03/26/15-02:12-pm-(-0400)	4400
21	DShield-Domain-List-(High-Sev)	04/17/15-01:17-pm-(-0400)	4039
22	DShield-Domain-List-(Medium-Sev)	03/26/15-02:12-pm-(-0400)	4231
23	Malware-Domains	04/17/15-01:16-pm-(-0400)	11659
24	Scam-Domains-(Fake/Malware/Drive-By)	04/16/15-11:27-am-(-0400)	4833
25	ET:-Known-Compromised-Hosts	04/16/15-03:01-pm-(-0400)	1080
26	C&Cs-Domains	04/15/15-10:30-am-(-0400)	473
27	IP-Bad-Reputation-(Mail)	04/14/15-06:42-pm-(-0400)	101
28	IP-Bad-Reputation-(HTTP/HTTPS)	02/13/15-01:46-pm-(-0500)	87
29	IP-Bad-Reputation-(Scan)	04/01/15-04:51-pm-(-0400)	414
30	Ponmocup:-Malware-Domains	03/26/15-02:13-pm-(-0400)	12
31	Ponmocup:-Malware-IPs	04/03/15-03:38-pm-(-0400)	31
32	Ponmocup:-Botnet-IPs	04/15/15-03:57-pm-(-0400)	8
33	MTA:-Suspicious-ip/domain-(All)	03/17/15-07:43-am-(-0400)	129
34	Bebloh:-IP-List	03/27/15-07:25-pm-(-0400)	7
35	Bebloh:-Domain-List	03/26/15-02:12-pm-(-0400)	17

800,000+ Indicators

Logstash Filtering

- Utilizing Custom Patterns

- GROK Message Filtering

- Adding Custom Fields

- Adding Geo IP Data

- Date Match

- Using Translations for Threat Intel

Logstash Configuration

```
filter {
    grok {
        match => {
            "message" => "%{IP:client} %{WORD:method} %{URIPATHPARAM:request}
%{NUMBER:bytes} %{NUMBER:duration}"
        }
    }
}
```

Utilize Custom Patterns

```
filter {
    grok {
        patterns_dir => "/opt/logstash/custom_patterns"
        match => {
            message => "%{291001}"
        }
    }
}
```

/opt/logstash/custom_patterns/bro.rule

291001 (?<start_time>\d{10}\.\d{6})\t(?<evt_srcip>[\d\.]+)\t(?<evt_dstip>[\d\.]+)\t(?<evt_srcport>\d+)\t...

Message Filtering

```
filter {
        if [message] =~ /^((\d{10}\.\d{6})\t([\d\.]+)([\d\.]+)\t(\d+)\t(\d+)\t(\w+))/ {
                grok {
                        patterns_dir => "/opt/logstash/custom_patterns"
                        match => {
                                message => "%{291001}"
                        }
                }
        }
}
```

Remove Capture Groups

291001 (?<start_time>\d{10}\.\d{6})\t(?<evt_srcip>[\d\.]+)\t(?<evt_dstip>[\d\.]+)\t(?<evt_srcport>\d+)\t...

Add Custom Fields

```
filter {

    if [message] =~ /^((\d{10}\.\d{6})\t([\d\.]+)([\d\.]+)\t(\d+)\t(\d+)\t(\w+))/ {

        grok {

            patterns_dir => "/opt/logstash/custom_patterns"
            match => {

                message => "%{291001}"

            }
            add_field => [ "rule_id", "291001" ]
            add_field => [ "Device Type", "IPSIDSDevice" ]
            add_field => [ "Object", "NetworkTraffic" ]
            add_field => [ "Action", "General" ]
            add_field => [ "Status", "Informational" ]

        }

    }

}
```

Geo IP

```
filter {

    …..all normalization code above here….

    geoip {

        source => "evt_dstip"

        target => "geoip_dst"

        database => "/etc/logstash/conf.d/GeoLiteCity.dat"

        add_field => [ "[geoip_dst][coordinates]", "%{[geoip_dst][longitude]}" ]

        add_field => [ "[geoip_dst][coordinates]", "%{[geoip_dst][latitude]}" ]

        add_field => [ "[geoip_dst][coordinates]", "%{[geoip_dst][city\_name]}" ]

        add_field => [ "[geoip_dst][coordinates]", "%{[geoip_dst][continent\_code]}" ]

        add_field => [ "[geoip_dst][coordinates]", "%{[geoip_dst][country\_name]}" ]

        add_field => [ "[geoip_dst][coordinates]", "%{[geoip_dst][postal\_code]}" ]}

    mutate {

        convert => [ "[geoip_dst][coordinates]", "float"]

    }

}
```

New ElasticSearch Template Needed

GeoIP Template Update

```
curl -XGET localhost:9200/_template/logstash
{"logstash":{
        "order":0,
        "template":"logstash-*",
        "settings":{
                "index.refresh_interval":"5s"
        },
        "mappings":{
                "properties":{
                        "geoip":{
                                "dynamic":true,
                                "properties":{
                                        "location":{
                                                "type":"geo_point"
                                        }
                                },
                                "type":"object"
                        },
                        …
```

```
{"logstash":{
        "order":0,
        "template":"logstash-*",
        "settings":{
                "index.refresh_interval":"5s"
        },
        "mappings":{
                "properties":{
                        "geoip_dst":{
                                "dynamic":true,
                                "properties":{
                                        "location":{
                                                "type":"geo_point"
                                        }
                                },
                                "type":"object"
                        },
                        …
```

curl -XPUT localhost:9200/_template/logstash -d '….'

Date Match

```
filter {

        ....all normalization code above here....

        ....all GeoIP code here....

        date {

                match => [ "start_time", "UNIX" ]

        }

}
```

Threat Intel

```
filter {
    ....all normalization code above here....
    ....all GeoIP code here....
    translate {
        field => "evt_dstip"
        destination => "tor_exit_IP"
        dictionary_path => '/etc/logstash/conf.d/torexit.yaml'
    }
}
```

torexil.yaml

```
"162.247.72.201": "YES"
"24.187.20.8": "YES"
"193.34.117.51": "YES"
```

- Run Scripts to update the YAML files on a regular basis
- Logstash will check the YAML for updates every 300 seconds
  - Configurable by adding refresh_interval => numSeconds

Custom Fields:
"Device Type" => "IPSIDSDevice"
"Object" => "HTTP"
"Action" => "General"
"Status" => "Informational"

Threat Intel Translations:
"tor_exit_IP" => "YES"
"malicious_IP" => "YES"

Geo IP Data:
"country_code2" => "RU"
"country_code3" => "RUS"
"country_name" => "Russian Federation"
"continent_code" => "EU"
"city_name" => "Moscow"
"postal_code" => "121087"
"latitude" => 55.75219999999999
"longitude" => 37.6156
"timezone" => "Europe/Moscow"

The TARDIS Framework

- Threat Analysis, Reconnaissance, & Data Intelligence System

- Historical exploit/IOC detection

- Time Lord of forensic log data

- Available at

https://github.com/tripwire/tardis

- Demo at Arsenal Thursday @ 12:45

STIX
Structured Threat Information eXpression

CybOX

TRIPWIRE LOG CENTER

logstash

splunk>

Import

Search

TARDIS

```
10.10.10.10 - - [06/Aug/2015:05:00:38 -0400] "GET /cgi-bin/test.cgi HTTP/1.1" 200 525 "-" "() { test;};echo \"Content-type: text/plain\"; echo; echo; /bin/cat /etc/passwd"
10.10.10.10 - - [06/Aug/2015:05:00:39 -0400] "GET /cgi-bin/test.cgi HTTP/1.1" 200 525 "-" "() { test;};echo \"Content-type: text/plain\"; echo; echo; /bin/cat /etc/passwd"
10.10.10.10 - - [06/Aug/2015:05:00:40 -0400] "GET /cgi-bin/test.cgi HTTP/1.1" 200 525 "-" "() { test;};echo \"Content-type: text/plain\"; echo; echo; /bin/cat /etc/passwd"
10.10.10.10 - - [06/Aug/2015:05:00:41 -0400] "GET /cgi-bin/test.cgi HTTP/1.1" 200 525 "-" "() { test;};echo \"Content-type: text/plain\"; echo; echo; /bin/cat /etc/passwd"
10.10.10.10 - - [06/Aug/2015:05:00:42 -0400] "GET /cgi-bin/test.cgi HTTP/1.1" 200 525 "-" "() { test;};echo \"Content-type: text/plain\"; echo; echo; /bin/cat /etc/passwd"
10.10.10.10 - - [06/Aug/2015:05:00:43 -0400] "GET /cgi-bin/test.cgi HTTP/1.1" 200 525 "-" "() { test;};echo \"Content-type: text/plain\"; echo; echo; /bin/cat /etc/passwd"
```

Sound Bytes

- Use NSM With Log

- Security Tools Are Better With Intelligence

- Take Integrations to the Next Level With TARDIS

Thank You

Travis Smith

tsmith@tripwire.com

https://github.com/Tripwire/tardis

https://github.com/TravisFSmith/MyBroElk