

# HEC Yeah!! How Priceline Uses HEC to Ingest 4TB of Data Every Day?

Jagadeesh Motamarri | Senior Software Engineer Mukund N Murthy | Software Engineer

priceline

October 2018

# Forward-Looking Statements

During the course of this presentation, we may make forward-looking statements regarding future events or the expected performance of the company. We caution you that such statements reflect our current expectations and estimates based on factors currently known to us and that actual events or results could differ materially. For important factors that may cause actual results to differ from those contained in our forward-looking statements, please review our filings with the SEC.

The forward-looking statements made in this presentation are being made as of the time and date of its live presentation. If reviewed after its live presentation, this presentation may not contain current or accurate information. We do not assume any obligation to update any forward-looking statements we may make. In addition, any information about our roadmap outlines our general product direction and is subject to change at any time without notice. It is for informational purposes only and shall not be incorporated into any contract or other commitment. Splunk undertakes no obligation either to develop the features or functionality described or to include any such feature or functionality in a future release.

Splunk, Splunk>, Listen to Your Data, The Engine for Machine Data, Splunk Cloud, Splunk Light and SPL are trademarks and registered trademarks of Splunk Inc. in the United States and other countries. All other brand names, product names, or trademarks belong to their respective owners. © 2018 Splunk Inc. All rights reserved.



### About us



JAGADEESH MOTAMARRI

Sr. Software Engineer, priceline




MUKUND N MURTHY

**Software Engineer, priceline** 

### **About Priceline**

priceline is part of Booking Holdings, the world leader in online travel & related services.

priceline offers more ways to save and more deals than anyone else in travel.



priceline Booking.com














# How we got here... The problem we set out to solve


From 08/16/2017 14:21:39

We had a collection of bespoke monitoring systems, evolved over 18+ years; weren't investing enough to get the full value from them.

Separate systems meant that we sometimes had difficulty seeing data across applications or application layers in the same context



## Legacy Architecture



# So, What the HEC? Narrowing the field

- Splunk is a fully features, powerful platform for collecting, searching, monitoring and analyzing machine data.
  - Rich ecosystem of 3<sup>rd</sup> party apps
     Crowdstrike, F5 BIG-IP, Cisco, \*nix, Windows, Palo Alto, Catchpoint, AWS, GCP
  - Flexible data ingestion architecture
     HTTP/REST (HEC), log scraping, dedicated apps

# Stats

**Beast mode ON** 



# of Applications




Daily Ingestion



Unique Sourcetypes



Queries per day



# HEC Yeah!!


The driving force

priceline



# HEC Yeah!! What is HEC?

- Token based API for collection of events
- Send events directly from anywhere
- Easy to Configure and works out of the box
- Easy to Secure
- Highly Performant ,scalable and available



Source: https://www.slideshare.net/Splunk/splunk-http-event-collector/2



# HEC Yeah

#### **Set-up and Usage**

Enable HTTP Event Collector

Create/Get a token



- Send events to Splunk using the token
  - Use HTTP Directly
  - Use logging libraries

Schaing Data
<pre>curl -v http://localhost:8088/services/collector -H "Authorization: Splunk 9F7F64FC-8E3F-4D85- B7F3-F6EC5B71ED1B" -d '{"event":{"uid":"hrottenberg","action","login"}} '</pre>

Sending Data


Files & Directories Upload a file, index a local file, or monitor an entire directory.	Configure a new token for receiving data over HTTP. Learn More [2]			
HTTP Event Collector Configure tokens that clients can use to send data over HTTP or HTTPS.	Name Source name override?	HEC - DEV TOKEN		
TCP / UDP Configure Splunk to listen on a network port.	Description?	optional		
Scripts Get data from any API, service, or database with a script.	Output Group (optional)	None ➤		
Catchpoint Modular Input Stream specified test metrics into Splunk from Catchpoint	Enable indexer acknowledgement			



### **HEC Yeah**

#### **Distributed Deployment**

Adopted Pattern # Traffic load balancer, no Heavy Forwarder, pool of indexers, using cluster master



### Priceline Data Collection Platform

**Core Modules** 

**Data Collection** 


Data Processing / Ingestion


**Dynamic Configuration** 

**Management Console** 

### Priceline Data Collection Platform

**High Level Architecture** 





with HTTP Event Collector



# Management Console

**Config System for managing meta-data** 

priceline



# Management Console

#### Priceline's home grown application

rs Is Existin	g Stream: 🗹	Stream Nam	e to Use in Producing	Application: HS	SLOG	
eessors Name:	HSLOG	Owner:	All Products	Application:	HSLOG →	
Topic Name:	hslog ▼	Volume:	High <b>→</b>	Share AMD:	No ▼	
Partition:	Partition Key	Description:	High Speed Log Data	Long Description:	High Speed Log Data from F5	
D LDAP Stre	am Properties:					
		·				
Strea	mToSplunkIndexMapping	→ hslog			-	
Strea	mToDateTimeMapping •	TIMEINMILL	S		-	
Field	sTolgnoreForSplunk •	QP_CC_NUMB	ER,ACCEPT,ACCEPT_I	ENCODING,ACC	EEPT	
LogS	StreamgestServerInfo +	true			-	
Selec	ct +			+		






# Management Console

#### Priceline's home grown application

Group Name: Volume:	streamgest_cg_two-splunk	Topics:	hslog <del>▼</del>				
		Topics:	hslog ▼				
Volume:	- 4 1		noicy .				
	Default ▼	Default Database:	default database for stream				
Processor:	com.priceline.streamgest.proc	essors.splunk.txn.SplunkBatchProcessorWith	LDAPConfigFactory ▼				
Application:	STREAMGEST ▼						
Clusters:							
Click on the Cluster Name to view the Cluster Location.							
KafkaBatchSize -	50000						
ConsumerInstances	PerServer ▼ 1						
KafkaAutoOffsetRes	et - largest	-					
KafkaBatchDuration	Millis ▼ 10000	-					
Command → star	t	-					
KafkaConsumerTime	eout - 10000						
MaxSplunkHECBuck	kets → 15						
Select ▼							
OBIGUT *							
	Consumer Propert KafkaBatchSize   ConsumerInstances  KafkaAutoOffsetRes  KafkaBatchDuration  Command   star  KafkaConsumerTime  MaxSplunkHECBuck  Select	Click on the Cluster Name to vie  Consumer Properties:  KafkaBatchSize ▼ 50000  ConsumerInstancesPerServer ▼ 1  KafkaAutoOffsetReset ▼ largest  KafkaBatchDurationMillis ▼ 10000  Command ▼ start  KafkaConsumerTimeout ▼ 10000  MaxSplunkHECBuckets ▼ 15  Select ▼	Click on the Cluster Name to view the Cluster Location.  Consumer Properties:  KafkaBatchSize   50000  ConsumerInstancesPerServer  1  KafkaAutoOffsetReset   largest  KafkaBatchDurationMillis  10000  Command  start  KafkaConsumerTimeout  10000  -  MaxSplunkHECBuckets  15  Select   +	Click on the Cluster Name to view the Cluster Location.  Consumer Properties:  KafkaBatchSize \( \sigma 50000 \)  ConsumerInstancesPerServer \( \square \) 1  KafkaAutoOffsetReset \( \square \) largest  KafkaBatchDurationMillis \( \square \) 10000  Command \( \square \) start  KafkaConsumerTimeout \( \square \) 10000  MaxSplunkHECBuckets \( \square \) 15  Select \( \square \)			








# Data Collection


**Embedded JVM Agent and REST** 

priceline



# Data Collection – Embedded JVM Agent








**Streaming + Ingestion = Streamgest** 


priceline

splunk> .confis










# Data Processor (Monitoring) Streamgest – Priceline's home grown application

#### VA - Message Rate vs Consumption Rate

#### Click on events to drilldown

DATA_CENTER \$	CONSUMER_GROUP \$	Message Rate ‡	Consumption Rate \$
VA-STREAM	streamgest_cg_eleven-splunk	8590/s	8672/s
VA-STREAM	streamgest_cg_htl_hrapi-splunk	5030/s	5001/s
VA-STREAM	streamgest_cg_three-splunk	4011/s	4027/s
VA-STREAM	streamgest_cg_six-splunk	3581/s	3625/s
VA-STREAM	streamgest_cg_common_one-splunk	3474/s	3487/s
VA-STREAM	streamgest_cg_ten-splunk	3165/s	3133/s

#### Lag Threshold



#### **Current Streamgest Consumer Lag (Status=Alert)**

GROUP \$	CLUSTER \$	TOTAL_LAG \$	values(TOPIC) \$
streamgest_cg_htl_hrapi-splunk	VA-STREAM	28224	bam_hrapi
streamgest_cg_seti_one-splunk	VA-STREAM	27929	ace-stats_splunk bam_setisvcs
streamgest_cg_three-splunk	NY-STREAM	27604	bam_hcfetch
streamgest_cg_eleven-splunk	VA-STREAM	25347	appmetrics bundlebook_data bundleprice bundlesearch_data hrcs_ops plconnect_ops





## Data Processor (Alerts)

#### Streamgest – Priceline's home grown application



**Splunk** APP 2:30 PM

Kafka Consumer Lag

This alert is triggered if Kafka Consumer Lag > 250K per consumer group!

**Trigger History Search Results:** 

VA-STREAM streamgest\_cg\_common\_logs-splunk 1478680



Splunk APP 11:50 AM

CPS-STREAMGEST-APPLNLOG-ERROR

This alert is triggered if number of error are more than 3 in Streamgest Servers

**Trigger History Search Results:** 

ny-





# **Key Takeaways**

**Lessons Learned** 

## **HEC Tuning**



Do. Defaults are good, but customization may be better. [limits.conf]

Example: `max\_content\_length` has been modified to suit our bandwidth requirement.

# Key Takeaways

**Lessons Learned** 

# Client-side Tuning



Do. Send events in **batches** to maximize HEC performance

# Client-side Tuning



Do. Keep-Alive allows HTTP clients to reuse the same connection for multiple batches.

# **Key Takeaways**

**Lessons Learned** 

# Key Takeaways

**Lessons Learned** 



Send data over HTTPS only when required. More performance while sending data over HTTP.

# Key Takeaways

**Lessons Learned** 

## Handling Errors



Do. HEC errors should be handled gracefully and iteratively to prevent loss of data.



Jagadeesh Motamarri | Senior Software Engineer
Mukund Narayana Murthy | Software Engineer
priceline

priceline



# Thank You

Don't forget to rate this session in the .conf18 mobile app

.CONf18
splunk>