

# Multi-tenancy Management


Andre Tucker
Solutions Architect - ReliaQuest
atucker@reliaquest.com



### About Me

- ReliaQuest Solutions Architect
- IT Experience:
  - System Administrator
  - Web Development / Database administration
  - SIEM Content Development
  - Software Development
- 3 year Splunk developer / enthusiast / evangelist

# What is Multi-tenancy



Multi-tenancy - an architecture in which a single instance of a software application serves multiple customers.

- Child Companies
- Business Units
- Any Sub-Entity

# Multi-tenancy Goals

# Well executed multi-tenancy should:


- Provide complete autonomy for each unit/entity
  - Data Visibility
  - Content (reports, dashboards, alerts)
- Minimize content duplication
  - Granular changes per entity
- Allow for overall program visibility and conformation
  - Reporting on groupings of entities.
  - All entities have the conform to enterprise program

# The Approach

Data Indexing


Data Classification

Data Manipulation





# The Approach



:123] "GET / GET /



# Order of Operations

Search-time operation order	Operation name	Can be configured via Splunk Web?	Location of file configuration
First	Inline field extraction (no field transform)	Yes	EXTRACT- <class> In a props.conf stanza</class>
Second	Field extraction that uses a field transform	Yes	REPORT- <class> In a props.conf stanza.</class>
Third	Automatic key-value field extraction	No	props.conf stanzas, where KV_MODE IS set to a valid value other than none. If no KV_MODE value is specified for a stanza, it is set to auto by default.
Fourth	Field aliasing	Yes	FIELDALIAS- <class> In a props.conf stanza</class>
Fifth	Calculated fields	Yes	EVAL- <fieldname> In a props.conf stanza</fieldname>
Sixth	Lookups	Yes	LOOKUP- <class> In a props.conf stanza.</class>
Seventh	Event types	Yes	eventtypes.conf stanza
Eighth	Tags	Yes	tags.conf stanza

http://docs.splunk.com/Documentation/Splunk/7.0.3/Knowledge/Searchtimeoperationssequence



### Data Indexing

# Naming Conventions

- Prefix indices based on entity
- Follow prefix by categorical name

<entity>\_<category> = pod1\_firewall

# Routing

Route based on host or source

### **Permissions**

Align indexes with necessary roles

#### Data Classification

*Transforms* – First get the entity prefix from the index name

```
[index prefix]
SOURCE KEY = MetaData:Index
REGEX = ^{(.*?)}
FORMAT = index_prefix::$1
```

pod1 firewall

Lookups – Enrich Splunk data by adding field-value combinations found in the lookup.

Match index patterns to entity names

mtf_	tag_index.csv	Import	Export	Refresh	Revert to previous versi			
• Right-click the table for editing options								
1	bunit	index_prefix				bunit_name		
2	abc	pod1			ABC Financ	cials		
3	xyz	pod2			XYZ Health	care		



### Data Classification

**Eventtypes** – Next we search for all events that should belong to the entity.

Index=\* bunit=abc

Name *	
abc	
Search string *	
index=* bunit=abc	
Tag(s)	
abc	
Enter a comma-separated list of tags.	
Color	
none	•
Priority	
1 (Highest)	•
Highest priority shows up first in a result.	

*Tags* – And group them together.



# Data Manipulation

- Control production / development entities using lookups, tags, and incident review states
- Craft *emails* based on entity using eval
- Control logic using a mixture of lookups and macros.
  - (Wanna go crazy? Try the "map" command)
- Change *dashboard* views / panels using tokens

### Thank You

atucker@reliaquest.com

