# splunk> Turbo Charging the Elephant

Search Performance Optimization Techniques for Splunk Analytics for Hadoop

Holger Sesterhenn | Staff Sales Engineer Raanan Dagan | Principal Architect

2018-08-30 | Orlando, FL

# Forward-Looking Statements

During the course of this presentation, we may make forward-looking statements regarding future events or the expected performance of the company. We caution you that such statements reflect our current expectations and estimates based on factors currently known to us and that actual events or results could differ materially. For important factors that may cause actual results to differ from those contained in our forward-looking statements, please review our filings with the SEC.

The forward-looking statements made in this presentation are being made as of the time and date of its live presentation. If reviewed after its live presentation, this presentation may not contain current or accurate information. We do not assume any obligation to update any forward-looking statements we may make. In addition, any information about our roadmap outlines our general product direction and is subject to change at any time without notice. It is for informational purposes only and shall not be incorporated into any contract or other commitment. Splunk undertakes no obligation either to develop the features or functionality described or to include any such feature or functionality in a future release.

Splunk, Splunk>, Listen to Your Data, The Engine for Machine Data, Splunk Cloud, Splunk Light and SPL are trademarks and registered trademarks of Splunk Inc. in the United States and other countries. All other brand names, product names, or trademarks belong to their respective owners. © 2018 Splunk Inc. All rights reserved.



# Who we are

### **Holger Sesterhenn**

- Staff Sales Engineer from Germany
- With Splunk for 6 years
- Focus on large accounts and complex architecture
- Loves craft beer
- Enjoys Marvel movies
- Pretends to do sports... sometimes



### Raanan Dagan

- Principal Architect, **Open Source**
- Focused on open source technologies & integration
- ▶ 20+ years of experience building large scale data platforms
- Joined Splunk in 2012
- Avid soccer (football) player

# Splunk and Hadoop

What is slow and why it's different?

"Splunk Enterprise is optimized for time serialized data using an index —

Hadoop/HDFS/MR are for batch processing"

Don't mix the use cases!





# Splunk Analytics and Hadoop


### What we are doing

- Main use case = Analyze Hadoop Data using Hadoop Processing (HDFS+MR)
  - It's just the search head... no Splunk Indexers anymore, but you can go hybrid
- Connect Splunk SH to Hadoop Cluster using a provider
  - You can connect multiple Hadoop Clusters to one Splunk SH
- Define a virtual index (VIX) for every data source you want to search
  - Usually you don't mix different sourcetypes in the same file/directory
- Schema on read is still used
  - props.conf and transforms.conf can be used to extract fields of interest

Use your SPL foo to search your data lake



# UseCase: Windfarm



Category.screen?category\_id=GIFTS&JSESSIONID=SDISL4FF10ADFF10 HTTP 1.1"

CET /product category\_id=GIFTS&JSESSIONID=SDISL4FF10ADFF10 HTTP 1.1"

'Category.screen?category\_id=GIFTs&lsEssioNiD=SDISL4FF10ADFF10 HTTP 1.1" 404 720 "http:// 66:136] "GET /Product.screen?product\_id=FL-DSH-01&JSESSIONID=SDSSL7FF6ADFF9 HTTP 1.1" +404 3322 468 125.17 'Old[ink?item\_id=EST-26&JSESSIONID=SDSSL9FF1ADFF3 HTTP 1.1" 200 1318 "Http://cart



# **Example Virtual Index**

### Connect a Hadoop HDFS cluster with a Splunk Analytics SearchHead

# HDFS = /user/splunk/datalake/windfarm/20180824/09/windmill01/power.gz

```
[windfarm]
vix.provider = MyHadoopProvider
vix.input.1.path = /user/splunk/datalake/windfarm/*/*/${windmill}/...
vix.input.1.accept = \.gz$
vix.input.1.et.regex = .*?/datalake/windfarm/.*/(\d+)/(\d+)/.*?.gz
vix.input.1.et.format = yyyyMMddHH
vix.input.1.et.offset = 0
vix.input.1.lt.regex = .*?/datalake/windfarm/.*/(\d+)/(\d+)/.*?.gz
vix.input.1.lt.format = yyyyMMddHH
vix.input.1.lt.format = yyyyMMddHH
vix.input.1.lt.offset = 3600
```

http://docs.splunk.com/Documentation/Splunk/latest/HadoopAnalytics/Virtualindexes



# Running a Splunk Analytics Search in Hadoop

### Streaming, Hadoop MR and the like

- index=windfarm | head 1000
  - A streaming search: just reading files from HDFS and stream them back to the splunkd process
- (smart mode) index=windfarm | stats count by windmill
  - Read some files directly from HDFS return results immediately / event timeline updates
  - Start MR jobs to search the majority of files (higher increments of events processed)
- (verbose mode) index=windfarm | stats count by windmill
  - Don't start MR jobs at all! ONLY streaming!

# Verify a MapReduce job is running

### Screenshot of JobInspector/Logfile

					—			
31.89	erp.hdp25.MR	1!	5	4 4				
0.03	dispatch.writeStatus	19	9					
0.00	dispatch.stream.local		1					
31.89	erp.hdp25 MR SPLK sandbox.hortonworks.com_1535624712.300_0	) 1!	5	4 4				
0.00	erp.hdp25.MR.failed.tasks	:	2					
0.00	erp.hdpz5.MH.failed.tasks.SPLK_sandbox.hortonworks.com_153	35624712.300_0	2					
22.91	erp.hdp25.report.delay		1					
8.51	erp.hdp25.report.wait	;	3					
0.11	erp.hdp25.setup		1					
0.02	erp.hdp25.setup.splunk		1					
0.00	erp.hdp25.setup.bundles	Additional info			search log	( erp_hdp25_	tacke	)
0.38	erp.hdp25.stream.bytes			Sear Cir. 10g	( erp_nap25_	Lasks		
1.83	erp.hdp25.stream.delay							
0.00	erp.hdp25.vix.windfarm.dirs.filter.search		7					
0.00	erp.hdp25.vix.windfarm.dirs.filter.time	;	3		-			
0.16	erp.hdp25.vix.windfarm.dirs.listed	•	7					
0.16	erp.hdp25.vix.windfarm.files.listed		4					
0.26	erp.hdp25.vix.windfarm.splits.generation.time		5		-			
'								

08-30-2018 10:25:18.413 INFO ERP.hdp25 - SplunkBaseMapper - using class=com.splunk.mr.input.SplunkLineRecordReader to process split=/user/root/data/windfarm/opc/20180804/12/Power/windfarm\_03-20180804\_12-Power.opc.txt.gz:0+24275



# Behind the Scenes

- 1. Splunk SH is creating search bundles for every Hadoop DataNode/TaskTracker
- SplunkD process on every DataNode/TaskTracker either streams data or gets results from MapReduce jobs
- 3. SplunkD is processing the data (schema on read) and filters
  - Lookups are applied on the TaskTracker!
- Data is sent back to Splunk SH (Hadoop Analytics)


This is a full event scan because there is no index (TSIDX) involved - a lot of work to do if you just search for a "needle in a haystack" (AKA IP address e.g.)

# DEMO 1

Examples
Simple search
Show logfiles/Job inspector

# Backup Screenshot

### Simple search with lookup data



0:57:1231 "GET /category.screen?category\_id=GIFTS&JSESSIONID=SDISLAFF1@ADFF1@ HTTP 1.1" 404 720 "NLSW-1:10:56:136[ET /product.screen?product\_id=FL-DSH-ol&JSESSIONID=SDSL7FF6ADFF9 HTTP 1.1" 404 3322 (322) " 468 125:17 | 461 | 462 | 463 | 463 | 463 | 463 | 463 | 463 | 463 | 463 | 463 | 463 | 463 | 463 | 463 | 463 | 463 | 463 | 463 | 463 | 463 | 463 | 463 | 463 | 463 | 463 | 463 | 463 | 463 | 463 | 463 | 463 | 463 | 463 | 463 | 463 | 463 | 463 | 463 | 463 | 463 | 463 | 463 | 463 | 463 | 463 | 463 | 463 | 463 | 463 | 463 | 463 | 463 | 463 | 463 | 463 | 463 | 463 | 463 | 463 | 463 | 463 | 463 | 463 | 463 | 463 | 463 | 463 | 463 | 463 | 463 | 463 | 463 | 463 | 463 | 463 | 463 | 463 | 463 | 463 | 463 | 463 | 463 | 463 | 463 | 463 | 463 | 463 | 463 | 463 | 463 | 463 | 463 | 463 | 463 | 463 | 463 | 463 | 463 | 463 | 463 | 463 | 463 | 463 | 463 | 463 | 463 | 463 | 463 | 463 | 463 | 463 | 463 | 463 | 463 | 463 | 463 | 463 | 463 | 463 | 463 | 463 | 463 | 463 | 463 | 463 | 463 | 463 | 463 | 463 | 463 | 463 | 463 | 463 | 463 | 463 | 463 | 463 | 463 | 463 | 463 | 463 | 463 | 463 | 463 | 463 | 463 | 463 | 463 | 463 | 463 | 463 | 463 | 463 | 463 | 463 | 463 | 463 | 463 | 463 | 463 | 463 | 463 | 463 | 463 | 463 | 463 | 463 | 463 | 463 | 463 | 463 | 463 | 463 | 463 | 463 | 463 | 463 | 463 | 463 | 463 | 463 | 463 | 463 | 463 | 463 | 463 | 463 | 463 | 463 | 463 | 463 | 463 | 463 | 463 | 463 | 463 | 463 | 463 | 463 | 463 | 463 | 463 | 463 | 463 | 463 | 463 | 463 | 463 | 463 | 463 | 463 | 463 | 463 | 463 | 463 | 463 | 463 | 463 | 463 | 463 | 463 | 463 | 463 | 463 | 463 | 463 | 463 | 463 | 463 | 463 | 463 | 463 | 463 | 463 | 463 | 463 | 463 | 463 | 463 | 463 | 463 | 463 | 463 | 463 | 463 | 463 | 463 | 463 | 463 | 463 | 463 | 463 | 463 | 463 | 463 | 463 | 463 | 463 | 463 | 463 | 463 | 463 | 463 | 463 | 463 | 463 | 463 | 463 | 463 | 463 | 463 | 463 | 463 | 463 | 463 | 463 | 463 | 463 | 463 | 463 | 463 | 463 | 463 | 463 | 463 | 463 | 463 | 463 | 463 | 463 | 463 | 463 | 463 | 463 | 463 | 463 | 463 | 463 | 463 | 463 | 463 | 463 | 463 | 463

# Backup Screenshot Loglines to show partition pruning

Search: index="windfarm" sourcetype=opc f\_tag="Power"

08-30-2018 10:49:55.384 DEBUG ERP.hdp25 - VirtualIndex - Updating source in search context to a dir=/user/root/data/windfarm/opc/20180804/12/Power/
08-30-2018 10:49:55.384 DEBUG ERP.hdp25 - VirtualIndex - Dir meets the search criteria. Will consider it, path=hdfs://172.17.0.1:8020/user/root/data/windfarm/opc/20180804/12/Power
08-30-2018 10:49:55.384 DEBUG ERP.hdp25 - VirtualIndex - Dir meets time heuristic path=hdfs://172.17.0.1:8020/user/root/data/windfarm/opc/20180804/12/Power, search.et=1533384000, search.lt=1533387600, file.et=1533384000, file.lt=1533387600, file.mtime=1534341390

08-30-2018 10:49:55.384 DEBUG ERP.hdp25 - VirtualIndex - Updating source in search context to a dir=/user/root/data/windfarm/opc/20180804/12/Wind\_Speed/
08-30-2018 10:49:55.384 DEBUG ERP.hdp25 - VirtualIndex - Dir does not meet the search criteria. Will not consider it, path=hdfs://172.17.0.1:8020/user/root/data/windfarm/opc/20180804/12/Wind\_Speed

08-30-2018 10:49:55.469 DEBUG ERP.hdp25 - VirtualIndex - **Dir meets the search criteria**. Will consider it, path=hdfs://172.17.0.1:8020/user/root/data/windfarm/opc/20180804/10 08-30-2018 10:49:55.469 DEBUG ERP.hdp25 - VirtualIndex - **Dir does not satisfy time heuristic,** path=hdfs://172.17.0.1:8020/user/root/data/windfarm/opc/**20180804/10**, search.et=1533384000, search.lt=1533387600, file.et=1533376800, file.lt=1533380400, file.mtime=1534341389

0.00	erp.hdp25.vix.windfarm.dirs.filter.search	7
0.00	erp.hdp25.vix.windfarm.dirs.filter.time	3
0.16	erp.hdp25.vix.windfarm.dirs.listed	7
0.16	erp.hdp25.vix.windfarm.files.listed	4



# Best Practices - Part 1 -

### Make sure the directory structure is useful

### This is BAD

/datalake/user/dir/<allfiles>...

This is GOOD (use the time picker to prune directories)

- /datalake/windfarm/opc/20180801/0900/<somefiles>....
- /datalake/windfarm/opc/20180802/1000/<otherfiles>....

This is BETTER (automatic field extraction!)

- /datalake/windfarm/\${sourcetype}/20180801/0900/metric=power/<fewer files>...
- /datalake/windfarm/\${sourcetype}/20180801/1000/metric=wind\_speed/<fewer files>...

Reduce the amount of files scanned/read from HDFS Structure by directory not by filename!

http://docs.splunk.com/Documentation/Splunk/latest/HadoopAnalytics/Setupvirtualindexes





# Get results faster

# Want your dashboards fast? Cache is king

### **Overview of options**

- Splunk (scheduled) saved search
  - https://docs.splunk.com/Documentation/Splunk/latest/SearchReference/Loadjob
  - <a href="http://docs.splunk.com/Documentation/Splunk/latest/Report/Schedulereports">http://docs.splunk.com/Documentation/Splunk/latest/Report/Schedulereports</a>
- 2. Splunk summary index
  - Store the results of a search in Splunk Enterprise
  - http://docs.splunk.com/Documentation/Splunk/latest/Knowledge/Usesummaryindexing
- 3. Hadoop Analytics Report Acceleration
  - http://docs.splunk.com/Documentation/Splunk/latest/HadoopAnalytics/Workwithreportacceleration
- 4. Datamodel Acceleration, not just nice looking...
  - http://docs.splunk.com/Documentation/Splunk/latest/HadoopAnalytics/Datamodelacceleration

# Hadoop Analytics Report Acceleration

### Some more details

- You need a transforming search
- Don't work in verbose mode
- Store the results in HDFS
  - hdfs:///user/root/splunkmr702/cache/windfarm/d5b3fea992e7a90fabd20e71e2bf269c/\_no\_id/c ompacts/78967737-5757-44e9-a8f2-e7d258e8b97f
- ▶ Files are stored in vix.splunk.search.cache.path
- Works like Splunk Enterprise Report Acceleration

http://docs.splunk.com/Documentation/Splunk/latest/HadoopAnalytics/Configurereportacceleration

# Hadoop Analytics Data Model Acceleration

### Some more details


- Configure a Splunk Enterprise Data Model
  - The constraint is using a VIX!
- Switch on accleleration
  - Mapreduce jos are running on a fixed schedule
  - Results are stored in ORC or Parquet file format
- Information about the DMA summary files stored in KV Store!
- Actual DMA files are stored in HDFS
- You can use "|tstats" to search
  - http://docs.splunk.com/Documentation/Splunk/latest/HadoopAnalytics/Configuredatamodelacceleration

Hadoop Analytics DMA does not use TSIDX files!



# The Windfarm Data Model

- Take fields from the lookup
- No need to do a lookup on TaskTracker anymore
- Store summary in HDFS structure
- TSTATS will run MR jobs on pre-computed summaries



hdfs://localhost:8020/user/root/splunkmr702/datamodel/6026C1EB-B03C-405E-92F4-7EB40D25D0F0\_DM\_demo\_hadoop\_windfarm\_windfarm/windfarm




# DEMO 2

Examples
Scheduled Search
Accelereated Search
Data Model

# Backup Screenshots

### **Scheduled Search**




"GET /product.screen?category\_id=GIFTS&JSESSIONID=SDISL4FF10ADFF10 HTTP 1.1"
6] "GET /product.screen?product\_id=FL-DSH-01&JSESSIONID=SDSSL7FF6ADFF9 HTTP 1.1"
200 1318
2.0ET /oldlinb:



# **Backup Screenshots**

### Accelerated vs. Non-Accelerated Dashboard Panel




%ET /Category.screen?category\_id~GIFTS&JSESSIONID=SDISLAFF10ADFF10 HTTP 1.1" 404 720 "http:// \$6:156] "GET /product.screen?product\_id=FL-DSH-01&JSESSIONID=SDSSL7FF6ADFF9 HTTP 1.1" 404 3322 # 468 1-2 GET /oldlink2+en?product\_id=FL-DSH-01&JSESSIONID=SDSSL7FF6ADFF9 HTTP 1.1" 200 1318 http://cart



# Backup Screenshots

### **Choropleth Example with Data Model**





# Best Practices - Part 2 -

### Choose the right method for your use case

- Summary Indexing and Saved Searches store data on the SH!
  - Fast but not flexible
- Report Acceleration stores data on HDFS
  - Enough storage available
  - Not Flexible (only similar searches are accelerated)
  - Quite fast because just streaming no MR jobs
- Data Model Acceleration stores data on HDFS but creates summary files per original data file and spawn MR jobs
  - More flexible but slower than Report Acceleration
  - Remember, no TSIDX, no Random Access



# What if the elephant burbs?

How to troubleshot if something goes wrong

# Troubleshooting Splunk Analytics for Hadoop

- Open the JobInspector first! -> search.log (maybe create an input?)
- Switch on debugging: vix.splunk.search.debug=1 (provider)
- Doublecheck the provider settings (ports mixed?)
- Check: does a simple search works? HDFS streaming
  - index=hadoop|head 10
- Hadoop resource manager web page checked ("All Applications")?
  - Ressource Manager runs usually on <RM-IP>:8088/cluster
- Monitor the YARN logs
  - https://www.splunk.com/blog/2014/05/14/hunkonhunk.html
- https://conf.splunk.com/session/2015/conf2015\_RDagan\_Splunk\_BigData\_HUNKPerfo rmanceandTroubleshooting.pdf

# For Reference

### If you want to read more...

- http://docs.splunk.com/Documentation/Splunk/latest/HadoopAnalytics/Performancebestpractic es
- http://docs.splunk.com/Documentation/Splunk/latest/HadoopAnalytics/TroubleshootSplunkAna lyticsforHadoop
- <a href="https://www.splunk.com/blog/2015/05/05/caching-hadoop-data-with-splunk-and-hunk.html">https://www.splunk.com/blog/2015/05/05/caching-hadoop-data-with-splunk-and-hunk.html</a>

# **Key Takeaways**

This is where the subtitle goes

- 1. Understand your use case
- 2. Structure your data in HDFS
- 3. Cache is KING!

Happy splunking!!!



Q&A

splunk> .conf18

# Thank You

Don't forget to rate this session in the .conf18 mobile app

.Conf18
splunk>