

Nepal College Of Information Technology
Balkumari, lalitpur

Applied Operating System Assignment Sheet -2 Solution

Prepared By: Amit Kr. Shrivastava

Q.1 Explain the difference between internal and external fragmentation.

Answer: **Internal Fragmentation** is the area in a region or a page that is not used by the job occupying that region or page. This space is unavailable for use by the system until that job is finished and the page or region is released. Internal Fragmentation occurs when allotted memory blocks are of fixed size i.e when paging is employed.

When there are small and non-contiguous memory blocks which cannot be assigned to any process, the problem is termed as **External Fragmentation**. External Fragmentation occurs when allotted memory blocks are of varying size i.e when segmentation is employed. External fragmentation can be reduced by compaction or shuffle memory contents to place all free memory together in one large block. To make compaction feasible, relocation should be dynamic.

Q.2 Given five memory partitions of 100 KB, 500 KB, 200 KB, 300 KB, and 600 KB (in order), how would each of the first-fit, best-fit, and worst-fit algorithms place processes of 212 KB, 417 KB, 112 KB, and 426 KB (in order)? Which algorithm makes the most efficient use of memory?

Answer:

- a. First-fit:
- b. 212K is put in 500K partition
- c. 417K is put in 600K partition
- d. 112K is put in 288K partition (new partition $288K = 500K - 212K$)
- e. 426K must wait
- f. Best-fit:
- g. 212K is put in 300K partition
- h. 417K is put in 500K partition
- i. 112K is put in 200K partition
- j. 426K is put in 600K partition
- k. Worst-fit:
- l. 212K is put in 600K partition
- m. 417K is put in 500K partition
- n. 112K is put in 388K partition
- o. 426K must wait

In this example, Best-fit turns out to be the best.

Q.3 Why are segmentation and paging sometimes combined into one scheme?

Answer: Segmentation and paging are often combined in order to improve upon each other. Segmented paging is helpful when the page table becomes very large. A large contiguous section of the page table that is unused can be collapsed into a single segment table entry with a page table address of zero. Paged segmentation handles the case of

having very long segments that require a lot of time for allocation. By paging the segments, we reduce wasted memory due to external fragmentation as well as simplify the allocation.

Q.4 Consider the following segment table:

Segment	Base	Length
0	219	600
1	2300	14
2	90	100
3	1327	580
4	1952	96

What are the physical addresses for the following logical addresses?

- a. 0,430
- b. 1,10
- c. 2,500
- d. 3,400
- e. 4,112

Answer:

- a. $219 + 430 = 649$
- b. $2300 + 10 = 2310$
- c. illegal reference, trap to operating system
- d. $1327 + 400 = 1727$
- e. illegal reference, trap to operating system

Q.5 What is the purpose of paging the page tables?

Answer: In certain situations the page tables could become large enough that by paging the page tables, one could simplify the memory allocation problem (by ensuring that everything is allocated as fixed-size pages as opposed to variable-sized chunks) and also enable the swapping of portions of page table that are not currently used.

Q.6 What is the minimum number of page faults for an optimal page replacement strategy for the following reference string with four page frames? Now repeat this problem for LRU.

1, 2, 3, 4, 5, 3, 4, 1, 6, 7, 8, 7, 8, 9, 7, 8, 9, 5, 4, 5, 4, 2.

Answer: 11 page faults(for optimal)

13 page faults(for LRU)

Q.7 What is the cause of thrashing? How does the system detect thrashing? Once it detects thrashing, what can the system do to eliminate this problem?

Answer: Thrashing is caused by underallocation of the minimum number of pages required by a process, forcing it to continuously page fault. The system can detect thrashing by evaluating the level of CPU utilization as compared to the level of multiprogramming. It can be eliminated by reducing the level of multiprogramming.

Q.8 A computer has four page frames. The time of loading, time of last access, and the **R** and **M** bits for each page are as shown below (the times are in clock ticks):

Page	Loaded	Last ref.	R	M
0	126	280	1	0

1	230	265	0	1
2	140	270	0	0
3	110	285	1	1

- (a) Which page will NRU replace?
(b) Which page will FIFO replace?
(c) Which page will LRU replace?
(d) Which page will second chance replace?

Answer: NRU removes page 2. FIFO removes page 3. LRU removes page 1. Second chance removes page 2.

Q.9 Consider a file system that uses a modified contiguous-allocation scheme with support for extents. A file is a collection of extents, with each extent corresponding to a contiguous set of blocks. A key issue in such systems is the degree of variability in the size of the extents. What are the advantages and disadvantages of the following schemes?

- a. All extents are of the same size, and the size is predetermined.
b. Extents can be of any size and are allocated dynamically.
c. Extents can be of a few fixed sizes, and these sizes are predetermined.

Answer: If all extents are of the same size, and the size is predetermined, then it simplifies the block allocation scheme. A simple bit map or free list for extents would suffice. If the extents can be of any size and are allocated dynamically, then more complex allocation schemes are required. It might be difficult to find an extent of the appropriate size and there might be external fragmentation. One could use the Buddy system allocator discussed in the previous chapters to design an appropriate allocator. When the extents can be of a few fixed sizes, and these sizes are predetermined, one would have to maintain a separate bitmap or free list for each possible size. This scheme is of intermediate complexity and of intermediate flexibility in comparison to the earlier schemes.

Q.10 Fragmentation on a storage device could be eliminated by recompaction of the information. Typical disk devices do not have relocation or base registers (such as are used when memory is to be compacted), so how can we relocate files? Give three reasons why recompact and relocation of files often are avoided.

Answer: Relocation of files on secondary storage involves considerable overhead—data blocks would have to be read into main memory and written back out to their new locations. Furthermore, relocation registers apply only to *sequential* files, and many disk files are not sequential. For this same reason, many new files will not require contiguous disk space; even sequential files can be allocated noncontiguous blocks if links between logically sequential blocks are maintained by the disk system.

Q.11 Suppose that a disk drive has 5000 cylinders, numbered 0 to 4999. The drive is currently serving a request at cylinder 143, and the previous request was at cylinder 125. The queue of pending requests, in FIFO order, is

86, 1470, 913, 1774, 948, 1509, 1022, 1750, 130

Starting from the current head position, what is the total distance (in cylinders) that the disk arm moves to satisfy all the pending requests, for each of the following disk-scheduling algorithms?

- a. FCFS
- b. SSTF
- c. SCAN
- d. C-SCAN

Answer:

- a. The FCFS schedule is 143, 86, 1470, 913, 1774, 948, 1509, 1022, 1750, 130. The total seek distance is 7081.
- b. The SSTF schedule is 143, 130, 86, 913, 948, 1022, 1470, 1509, 1750, 1774. The total seek distance is 1745.
- c. The SCAN schedule is 143, 913, 948, 1022, 1470, 1509, 1750, 1774, 4999, 130, 86. The total seek distance is 9769.
- e. The C-SCAN schedule is 143, 913, 948, 1022, 1470, 1509, 1750, 1774, 4999, 86, 130. The total seek distance is 4986.

Q.12 What are the advantages and disadvantages of supporting memory mapped I/O to device control registers?

Answer: The advantage of supporting memory-mapped I/O to device control registers is that it eliminates the need for special I/O instructions from the instruction set and therefore also does not require the enforcement of protection rules that prevent user programs from executing these I/O instructions. The disadvantage is that the resulting flexibility needs to be handled with care; the memory translation units need to ensure that the memory addresses associated with the device control registers are not accessible by user programs in order to ensure protection.

Q.13 Explain the difference between deadlock, livelock and starvation.

Answer: A deadlock occurs when a set of processes are blocked waiting for an event that only some other process in the set can cause. On the other hand, processes in a livelock are not blocked. Instead, they continue to execute checking for a condition to become true that will never become true. Thus, in addition to the resources they are holding, processes in livelock continue to consume precious CPU time. Finally, starvation of a process occurs because of the presence of other processes as well as a stream of new incoming processes that end up with higher priority than the process being starved. Unlike deadlock or livelock, starvation can terminate on its own, e.g. when existing processes with higher priority terminate and no new processes with higher priority arrive.

Q.14 Differentiate between segmentation and paging.

Answer:

No.	Key	Paging	Segmentation
1	Memory Size	In Paging, a process address space is broken into fixed sized blocks called pages.	In Segmentation, a process address space is broken in varying sized blocks called sections.
2	Accountability	Operating System divides	Compiler is responsible to

No.	Key	Paging	Segmentation
		the memory into pages.	calculate the segment size, the virtual address and actual address.
3	Size	Page size is determined by hardware.	Section size is determined by the user.
4	Speed	Paging technique is faster in terms of memory access.	Segmentation is slower than paging.
5	Fragmentation	Paging can cause internal fragmentation as some pages may go underutilized.	Segmentation can cause external fragmentation as some memory block may not be used at all.
6	Logical Address	During paging, a logical address is divided into page number and page offset.	During segmentation, a logical address is divided into section number and section offset.

Q.15 Explain Producer Consumer Problem using semaphore.

Answer: Refer Lecture note.