# DJANGI TOOLBOX

// SOURCE CODE EXPORT  •  39 file(s)

## components.json

F:\Tools\CodeZipper\components.json

```
{
  "$schema": "https://ui.shadcn.com/schema.json",
  "style": "radix-rhea",
  "rsc": false,
  "tsx": true,
  "tailwind": {
    "config": "",
    "css": "src/index.css",
    "baseColor": "neutral",
    "cssVariables": true,
    "prefix": ""
  },
  "iconLibrary": "lucide",
  "rtl": false,
  "aliases": {
    "components": "@/components",
    "utils": "@/lib/utils",
    "ui": "@/components/ui",
    "lib": "@/lib",
    "hooks": "@/hooks"
  },
  "menuColor": "default",
  "menuAccent": "subtle",
  "registries": {}
}
```

## index.html

F:\Tools\CodeZipper\index.html

```
<!doctype html>
<html lang="en">

<head>
  <meta charset="UTF-8" />
  <link rel="icon" type="image/svg+xml" href="/vite.svg" />
  <meta name="viewport" content="width=device-width, initial-scale=1.0" />
  <title>Code Zipper</title>

  <script>
    (function () {
      try {
        var saved = localStorage.getItem('codezipper.theme');
        var isDark =
          saved === 'dark' ||
          ((!saved || saved === 'system') &&
            window.matchMedia('(prefers-color-scheme: dark)').matches);
        if (isDark) document.documentElement.classList.add('dark');
        document.documentElement.style.colorScheme = isDark ? 'dark' : 'light';
      } catch (e) { }
    })();
  </script>

  <link rel="preconnect" href="https://fonts.googleapis.com" />
  <link rel="preconnect" href="https://fonts.gstatic.com" crossorigin />
  <link href="https://fonts.googleapis.com/css2?family=Inter:wght@400;500;600&display=swap" rel="stylesheet" />
</head>

<body>
  <div id="root"></div>
  <script type="module" src="/src/main.tsx"></script>
</body>

</html>
```

## package-lock.json

F:\Tools\CodeZipper\package-lock.json

```
{
  "name": "codezipper",
  "version": "0.1.0",
  "lockfileVersion": 3,
  "requires": true,
```

```
  "packages": {
    "": {
      "name": "codezipper",
      "version": "0.1.0",
      "dependencies": {
        "@radix-ui/react-checkbox": "^1.1.2",
        "@radix-ui/react-dialog": "^1.1.2",
        "@radix-ui/react-slot": "^1.1.0",
        "@radix-ui/react-switch": "^1.1.1",
        "@tauri-apps/api": "^2",
        "@tauri-apps/plugin-dialog": "^2.8.3",
        "@tauri-apps/plugin-opener": "^2",
        "@types/node": "^26.6.5",
        "class-variance-authority": "^0.7.1",
        "clsx": "^2.1.1",
        "lucide-react": "^1.59.0",
        "react": "^19.1.0",
        "react-dom": "^19.1.0",
        "tailwind-merge": "^2.5.5"
      },
      "devDependencies": {
        "@tailwindcss/vite": "^4.0.0",
        "@tauri-apps/cli": "^2",
        "@types/react": "^19.1.8",
        "@types/react-dom": "^19.1.6",
        "@vitejs/plugin-react": "^6.0.2",
        "tailwindcss": "^4.0.0",
        "tw-animate-css": "^1.2.5",
        "typescript": "~6.0.3",
        "vite": "^8.0.16"
      }
    },
    "node_modules/@jridgewell/gen-mapping": {
      "version": "0.3.13",
      "resolved": "https://registry.npmjs.org/@jridgewell/gen-mapping/-/gen-mapping-0.3.13.tgz",
      "integrity": "sha512-2kkt/7niJ6MgEPxF0bYdQ6etZaA+fQvDcLKckhy1yIQOzaoKjBBjSj63/aLVjYE3qhRt5dvM+uUyfCg6UKCBbA==",
      "dev": true,
      "license": "MIT",
      "dependencies": {
        "@jridgewell/sourcemap-codec": "^1.5.0",
        "@jridgewell/trace-mapping": "^0.3.24"
      }
    },
    "node_modules/@jridgewell/remapping": {
      "version": "2.3.5",
      "resolved": "https://registry.npmjs.org/@jridgewell/remapping/-/remapping-2.3.5.tgz",
      "integrity": "sha512-LI9u/+laYG4Ds1TDKSJW2YPrIlcVYOwi2fUC6xB43lueCjgxV4lffOCZCtYFiH6TNOX+tQKXx97T4IKHbhyHEQ==",
      "dev": true,
      "license": "MIT",
      "dependencies": {
        "@jridgewell/gen-mapping": "^0.3.5",
        "@jridgewell/trace-mapping": "^0.3.24"
      }
    },
    "node_modules/@jridgewell/resolve-uri": {
      "version": "3.1.2",
      "resolved": "https://registry.npmjs.org/@jridgewell/resolve-uri/-/resolve-uri-3.1.2.tgz",
      "integrity": "sha512-bRISgCIjP20/tbWSPWMEi54QVPRZExkuD9lJL+UIxUKtwVJA8wW1Trb1jMs1RFXo1CBTNZ/5hpC9QvmKWdopKw==",
      "dev": true,
      "license": "MIT",
      "engines": {
        "node": ">=6.0.0"
      }
    },
    "node_modules/@jridgewell/sourcemap-codec": {
      "version": "1.6.0",
      "resolved": "https://registry.npmjs.org/@jridgewell/sourcemap-codec/-/sourcemap-codec-1.6.0.tgz",
      "integrity": "sha512-T7jf+5zgsZHwNJ4lvQ7/aezbyk0nNX+zJVWpmHA7VYsEx7a7qr5Rg5IbtJFqkgze5Y2sruq1RUY8Q837Od7iFw==",
      "dev": true,
      "license": "MIT"
    },
    "node_modules/@jridgewell/trace-mapping": {
      "version": "0.3.31",
      "resolved": "https://registry.npmjs.org/@jridgewell/trace-mapping/-/trace-mapping-0.3.31.tgz",
      "integrity": "sha512-zzNR+SdQSDJzc8joaeP8QQoCQr8NuYx2dIIytl1QeBEZHJ9uW6hebsrYgbz8hJwUQao3TWCMtmfV8Nu1twOLAw==",
      "dev": true,
      "license": "MIT",
      "dependencies": {
        "@jridgewell/resolve-uri": "^3.1.0",
        "@jridgewell/sourcemap-codec": "^1.4.14"
      }
```

```
    },
    "node_modules/@oxc-project/types": {
      "version": "0.154.0",
      "resolved": "https://registry.npmjs.org/@oxc-project/types/-/types-0.154.0.tgz",
      "integrity": "sha512-KYOUGQFlLWR+s4QMV2Q9ko38TZm7EdO87Qm7rvZLqk/webse/cDjtyxKhg/47l0byCbs/k46LT8qc4PKjAikzA==",
      "dev": true,
      "license": "MIT",
      "funding": {
        "url": "https://github.com/sponsors/oxc-project"
      }
    },
    "node_modules/@radix-ui/primitive": {
      "version": "1.2.0",
      "resolved": "https://registry.npmjs.org/@radix-ui/primitive/-/primitive-1.2.0.tgz",
      "integrity": "sha512-KABY+VMIRPJL+Vyzv/335FEhXXD/xDv8BMb1kl48/aXJZMH0LtHCTx5ga5RnxaEP3nZHtmTLf1P9vanmFX46bw==",
      "license": "MIT"
    },
    "node_modules/@radix-ui/react-checkbox": {
      "version": "1.4.1",
      "resolved": "https://registry.npmjs.org/@radix-ui/react-checkbox/-/react-checkbox-1.4.1.tgz",
      "integrity": "sha512-KWtwhh+98ML3seZ9vO9yRY2OwaQG90dCiDAxjpSNY2AaZ3Hik3B0dsk6m0ILywo/no3A9/SozadyPMNweVT8yw==",
      "license": "MIT",
      "dependencies": {
        "@radix-ui/primitive": "1.2.0",
        "@radix-ui/react-compose-refs": "1.1.5",
        "@radix-ui/react-context": "1.3.0",
        "@radix-ui/react-presence": "1.1.11",
        "@radix-ui/react-primitive": "2.2.0",
        "@radix-ui/react-use-controllable-state": "1.3.0",
        "@radix-ui/react-use-size": "1.1.5"
      },
      "peerDependencies": {
        "@types/react": "*",
        "@types/react-dom": "*",
        "react": "^16.8 || ^17.0 || ^18.0 || ^19.0 || ^19.0.0-rc",
        "react-dom": "^16.8 || ^17.0 || ^18.0 || ^19.0 || ^19.0.0-rc"
      },
      "peerDependenciesMeta": {
        "@types/react": {
          "optional": true
        },
        "@types/react-dom": {
          "optional": true
        }
      }
    },
    "node_modules/@radix-ui/react-compose-refs": {
      "version": "1.1.5",
      "resolved": "https://registry.npmjs.org/@radix-ui/react-compose-refs/-/react-compose-refs-1.1.5.tgz",
      "integrity": "sha512-+48PbAAbq3didjJxa+OaWY2ZwgAKsNiRGyeHKszblZMQ+kcpd9pAaT11cMkGEie0vsOi3QdeTE6d5Fe3Gn61kA==",
      "license": "MIT",
      "peerDependencies": {
        "@types/react": "*",
        "react": "^16.8 || ^17.0 || ^18.0 || ^19.0 || ^19.0.0-rc"
      },
      "peerDependenciesMeta": {
        "@types/react": {
          "optional": true
        }
      }
    },
    "node_modules/@radix-ui/react-context": {
      "version": "1.3.0",
      "resolved": "https://registry.npmjs.org/@radix-ui/react-context/-/react-context-1.3.0.tgz",
      "integrity": "sha512-v5AYEocMISkbJ+1fTXzZpiFv7NRr3D2WiYbLIKf+FkmJ8VkP6d503eV2n34MFussHXY1pcoq3yfJiQH77dc4Mg==",
      "license": "MIT",
      "peerDependencies": {
        "@types/react": "*",
        "react": "^16.8 || ^17.0 || ^18.0 || ^19.0 || ^19.0.0-rc"
      },
      "peerDependenciesMeta": {
        "@types/react": {
          "optional": true
        }
      }
    },
    "node_modules/@radix-ui/react-dialog": {
      "version": "1.3.1",
      "resolved": "https://registry.npmjs.org/@radix-ui/react-dialog/-/react-dialog-1.3.1.tgz",
      "integrity": "sha512-+0E4qvVTwjAWra9sEhJ+9BTsvHE00zkUuNw1VGh7S+Gc13dfYk+S1PVQdchWDj+XYHhAai7Z7IpzXVDCGsDplg==",
      "license": "MIT",
```

```
    "dependencies": {
      "@radix-ui/primitive": "1.2.0",
      "@radix-ui/react-compose-refs": "1.1.5",
      "@radix-ui/react-context": "1.3.0",
      "@radix-ui/react-dismissable-layer": "1.2.1",
      "@radix-ui/react-focus-guards": "1.2.0",
      "@radix-ui/react-focus-scope": "1.3.1",
      "@radix-ui/react-id": "1.1.4",
      "@radix-ui/react-portal": "1.2.0",
      "@radix-ui/react-presence": "1.1.11",
      "@radix-ui/react-primitive": "2.2.0",
      "@radix-ui/react-slot": "1.5.0",
      "@radix-ui/react-use-controllable-state": "1.3.0",
      "@radix-ui/react-use-layout-effect": "1.1.4",
      "aria-hidden": "^1.2.4",
      "react-remove-scroll": "^2.7.2"
    },
    "peerDependencies": {
      "@types/react": "*",
      "@types/react-dom": "*",
      "react": "^16.8 || ^17.0 || ^18.0 || ^19.0 || ^19.0.0-rc",
      "react-dom": "^16.8 || ^17.0 || ^18.0 || ^19.0 || ^19.0.0-rc"
    },
    "peerDependenciesMeta": {
      "@types/react": {
        "optional": true
      },
      "@types/react-dom": {
        "optional": true
      }
    }
  },
  "node_modules/@radix-ui/react-dismissable-layer": {
    "version": "1.2.1",
    "resolved": "https://registry.npmjs.org/@radix-ui/react-dismissable-layer/-/react-dismissable-layer-1.2.1.tgz
    "integrity": "sha512-KIfDcAsx+oVylFZ4xryVKusJUrLLhTQmfnJW4kwk4Km5myvhHCrj04hnWWUC166+xD4DHdH8tQGylwYX1h6+Pg==
    "license": "MIT",
    "dependencies": {
      "@radix-ui/primitive": "1.2.0",
      "@radix-ui/react-compose-refs": "1.1.5",
      "@radix-ui/react-primitive": "2.2.0",
      "@radix-ui/react-use-callback-ref": "1.1.5",
      "@radix-ui/react-use-effect-event": "0.0.5"
    },
    "peerDependencies": {
      "@types/react": "*",
      "@types/react-dom": "*",
      "react": "^16.8 || ^17.0 || ^18.0 || ^19.0 || ^19.0.0-rc",
      "react-dom": "^16.8 || ^17.0 || ^18.0 || ^19.0 || ^19.0.0-rc"
    },
    "peerDependenciesMeta": {
      "@types/react": {
        "optional": true
      },
      "@types/react-dom": {
        "optional": true
      }
    }
  },
  "node_modules/@radix-ui/react-focus-guards": {
    "version": "1.2.0",
    "resolved": "https://registry.npmjs.org/@radix-ui/react-focus-guards/-/react-focus-guards-1.2.0.tgz",
    "integrity": "sha512-MPm5R0iRGUDrDnPNxmLBkv+X7pN4XKzt+MbWJEuJQsH3NFH4omrbpXpucyYCCKTSt+na/ZxGhEWQrWTZ0285cA==
    "license": "MIT",
    "peerDependencies": {
      "@types/react": "*",
      "react": "^16.8 || ^17.0 || ^18.0 || ^19.0 || ^19.0.0-rc"
    },
    "peerDependenciesMeta": {
      "@types/react": {
        "optional": true
      }
    }
  },
  "node_modules/@radix-ui/react-focus-scope": {
    "version": "1.3.1",
    "resolved": "https://registry.npmjs.org/@radix-ui/react-focus-scope/-/react-focus-scope-1.3.1.tgz",
    "integrity": "sha512-ugeMhbXt4y5S2T1GnIqbWDKEN962PDwnX1fN0eKOOgf5f63Dh2mn8F1FUySlgW0iF6GiVsRF32DzuDIWTUyQJg==
    "license": "MIT",
    "dependencies": {
      "@radix-ui/react-compose-refs": "1.1.5",
```

```
        "@radix-ui/react-primitive": "2.2.0",
        "@radix-ui/react-use-callback-ref": "1.1.5"
      },
      "peerDependencies": {
        "@types/react": "*",
        "@types/react-dom": "*",
        "react": "^16.8 || ^17.0 || ^18.0 || ^19.0 || ^19.0.0-rc",
        "react-dom": "^16.8 || ^17.0 || ^18.0 || ^19.0 || ^19.0.0-rc"
      },
      "peerDependenciesMeta": {
        "@types/react": {
          "optional": true
        },
        "@types/react-dom": {
          "optional": true
        }
      }
    },
    "node_modules/@radix-ui/react-id": {
      "version": "1.1.4",
      "resolved": "https://registry.npmjs.org/@radix-ui/react-id/-/react-id-1.1.4.tgz",
      "integrity": "sha512-TMQp2llA+RYn7JcjnrMnz7wN4pcVttPZnRZo52PLQsoLVKzNlVwUeHmfePgTgRluXFvlD3GD5g5MOVVTJCO0qA==",
      "license": "MIT",
      "dependencies": {
        "@radix-ui/react-use-layout-effect": "1.1.4"
      },
      "peerDependencies": {
        "@types/react": "*",
        "react": "^16.8 || ^17.0 || ^18.0 || ^19.0 || ^19.0.0-rc"
      },
      "peerDependenciesMeta": {
        "@types/react": {
          "optional": true
        }
      }
    },
    "node_modules/@radix-ui/react-portal": {
      "version": "1.2.0",
      "resolved": "https://registry.npmjs.org/@radix-ui/react-portal/-/react-portal-1.2.0.tgz",
      "integrity": "sha512-StX7xXnaRU41VvFtMm9zlhVGz8XF6GmWWTXftkQaY+tqVkbs/R9UmAp5mLzHHapk5hM9RMZQvO/3usyIP/g42g==",
      "license": "MIT",
      "dependencies": {
        "@radix-ui/react-primitive": "2.2.0",
        "@radix-ui/react-use-layout-effect": "1.1.4"
      },
      "peerDependencies": {
        "@types/react": "*",
        "@types/react-dom": "*",
        "react": "^16.8 || ^17.0 || ^18.0 || ^19.0 || ^19.0.0-rc",
        "react-dom": "^16.8 || ^17.0 || ^18.0 || ^19.0 || ^19.0.0-rc"
      },
      "peerDependenciesMeta": {
        "@types/react": {
          "optional": true
        },
        "@types/react-dom": {
          "optional": true
        }
      }
    },
    "node_modules/@radix-ui/react-presence": {
      "version": "1.1.11",
      "resolved": "https://registry.npmjs.org/@radix-ui/react-presence/-/react-presence-1.1.11.tgz",
      "integrity": "sha512-Z7/atlkab36Z8hm+V8zYc79r0W+tiOB1o0tun1By94JyadkekLQmtEAnBSP9XKXBNQsStoStS4+gX10JpS5akA==",
      "license": "MIT",
      "dependencies": {
        "@radix-ui/react-use-layout-effect": "1.1.4"
      },
      "peerDependencies": {
        "@types/react": "*",
        "@types/react-dom": "*",
        "react": "^16.8 || ^17.0 || ^18.0 || ^19.0 || ^19.0.0-rc",
        "react-dom": "^16.8 || ^17.0 || ^18.0 || ^19.0 || ^19.0.0-rc"
      },
      "peerDependenciesMeta": {
        "@types/react": {
          "optional": true
        },
        "@types/react-dom": {
          "optional": true
        }
```

```
    }
  },
  "node_modules/@radix-ui/react-primitive": {
    "version": "2.2.0",
    "resolved": "https://registry.npmjs.org/@radix-ui/react-primitive/-/react-primitive-2.2.0.tgz",
    "integrity": "sha512-HCTSPMNqv55Qk0IX4geJbpyXazmqulcimwuyjxTkKi29v+QZbG2Zho9BnbBq4YS2PF+KlNb2CXoLz66uUmblkg==
    "license": "MIT",
    "dependencies": {
      "@radix-ui/react-slot": "1.5.0"
    },
    "peerDependencies": {
      "@types/react": "*",
      "@types/react-dom": "*",
      "react": "^16.8 || ^17.0 || ^18.0 || ^19.0 || ^19.0.0-rc",
      "react-dom": "^16.8 || ^17.0 || ^18.0 || ^19.0 || ^19.0.0-rc"
    },
    "peerDependenciesMeta": {
      "@types/react": {
        "optional": true
      },
      "@types/react-dom": {
        "optional": true
      }
    }
  },
  "node_modules/@radix-ui/react-slot": {
    "version": "1.5.0",
    "resolved": "https://registry.npmjs.org/@radix-ui/react-slot/-/react-slot-1.5.0.tgz",
    "integrity": "sha512-tyYd9ddPXAysAbdbD9eYxgwpCSv6f3PncqVSNKQFSR5lcJVLz3cb/pANDoYrLiHBpXv7skortyUgGUWsYuPPFQ==
    "license": "MIT",
    "dependencies": {
      "@radix-ui/react-compose-refs": "1.1.5"
    },
    "peerDependencies": {
      "@types/react": "*",
      "react": "^16.8 || ^17.0 || ^18.0 || ^19.0 || ^19.0.0-rc"
    },
    "peerDependenciesMeta": {
      "@types/react": {
        "optional": true
      }
    }
  },
  "node_modules/@radix-ui/react-switch": {
    "version": "1.4.1",
    "resolved": "https://registry.npmjs.org/@radix-ui/react-switch/-/react-switch-1.4.1.tgz",
    "integrity": "sha512-NpBGwc40rY02ZmSvuyeKk0Bvc8ZsNeTMi4qHvJ+ZH4EiYCv0zIXEgdCW4bVdzgIUeP9xxbLJSxKOUfqITYNmkA==
    "license": "MIT",
    "dependencies": {
      "@radix-ui/primitive": "1.2.0",
      "@radix-ui/react-compose-refs": "1.1.5",
      "@radix-ui/react-context": "1.3.0",
      "@radix-ui/react-primitive": "2.2.0",
      "@radix-ui/react-use-controllable-state": "1.3.0",
      "@radix-ui/react-use-size": "1.1.5"
    },
    "peerDependencies": {
      "@types/react": "*",
      "@types/react-dom": "*",
      "react": "^16.8 || ^17.0 || ^18.0 || ^19.0 || ^19.0.0-rc",
      "react-dom": "^16.8 || ^17.0 || ^18.0 || ^19.0 || ^19.0.0-rc"
    },
    "peerDependenciesMeta": {
      "@types/react": {
        "optional": true
      },
      "@types/react-dom": {
        "optional": true
      }
    }
  },
  "node_modules/@radix-ui/react-use-callback-ref": {
    "version": "1.1.5",
    "resolved": "https://registry.npmjs.org/@radix-ui/react-use-callback-ref/-/react-use-callback-ref-1.1.5.tgz",
    "integrity": "sha512-Y5GBf4NKeADoXI1geiMlMuMoURT3k9MizzzKhGb/m55H94aGigZ01PIpkvsO6lML13BA6XYAXSJ6gza7vTn5nw==
    "license": "MIT",
    "dependencies": {
      "@radix-ui/react-use-layout-effect": "1.1.4"
    },
    "peerDependencies": {
      "@types/react": "*",
```

```
        "react": "^16.8 || ^17.0 || ^18.0 || ^19.0 || ^19.0.0-rc"
      },
      "peerDependenciesMeta": {
        "@types/react": {
          "optional": true
        }
      }
    },
    "node_modules/@radix-ui/react-use-controllable-state": {
      "version": "1.3.0",
      "resolved": "https://registry.npmjs.org/@radix-ui/react-use-controllable-state/-/react-use-controllable-state
      "integrity": "sha512-TAcBI7bw2ljYCbv4+zuTSd6zICu8pRt6SDN2vJ/Z06K2MXh6I9WYFe/A9ovlFDtR5HVHGm5iDxDoABm/++dbKg==
      "license": "MIT",
      "dependencies": {
        "@radix-ui/primitive": "1.2.0",
        "@radix-ui/react-use-effect-event": "0.0.5",
        "@radix-ui/react-use-layout-effect": "1.1.4"
      },
      "peerDependencies": {
        "@types/react": "*",
        "react": "^16.8 || ^17.0 || ^18.0 || ^19.0 || ^19.0.0-rc"
      },
      "peerDependenciesMeta": {
        "@types/react": {
          "optional": true
        }
      }
    },
    "node_modules/@radix-ui/react-use-effect-event": {
      "version": "0.0.5",
      "resolved": "https://registry.npmjs.org/@radix-ui/react-use-effect-event/-/react-use-effect-event-0.0.5.tgz",
      "integrity": "sha512-7cshFL8HGS/7HEiHH+9kL9HBwp2sa9yX18Knwek6KYWmXwM7pegMgta2AXMQKI+rq3JnfSj9x8wYqFMTdG1Jgg==
      "license": "MIT",
      "dependencies": {
        "@radix-ui/react-use-layout-effect": "1.1.4"
      },
      "peerDependencies": {
        "@types/react": "*",
        "react": "^16.8 || ^17.0 || ^18.0 || ^19.0 || ^19.0.0-rc"
      },
      "peerDependenciesMeta": {
        "@types/react": {
          "optional": true
        }
      }
    },
    "node_modules/@radix-ui/react-use-layout-effect": {
      "version": "1.1.4",
      "resolved": "https://registry.npmjs.org/@radix-ui/react-use-layout-effect/-/react-use-layout-effect-1.1.4.tgz
      "integrity": "sha512-K20DkRkUwDnxEYMBPcg3Y6voLkEy5p5QQmszZgLngKKiC7dzBR/aEuK3w1qlx2JWDUNH6FluahYdgR3BP+QbYw==
      "license": "MIT",
      "peerDependencies": {
        "@types/react": "*",
        "react": "^16.8 || ^17.0 || ^18.0 || ^19.0 || ^19.0.0-rc"
      },
      "peerDependenciesMeta": {
        "@types/react": {
          "optional": true
        }
      }
    },
    "node_modules/@radix-ui/react-use-size": {
      "version": "1.1.5",
      "resolved": "https://registry.npmjs.org/@radix-ui/react-use-size/-/react-use-size-1.1.5.tgz",
      "integrity": "sha512-V1McDQkMGzgivwqdu7u96APs7oi0Jvj9LTzgq3WWrDZqxWdAqU9yZnZQqk5OizGFR8badUQwZsrlao7MOlWYOA==
      "license": "MIT",
      "dependencies": {
        "@radix-ui/react-use-layout-effect": "1.1.4"
      },
      "peerDependencies": {
        "@types/react": "*",
        "react": "^16.8 || ^17.0 || ^18.0 || ^19.0 || ^19.0.0-rc"
      },
      "peerDependenciesMeta": {
        "@types/react": {
          "optional": true
        }
      }
    },
    "node_modules/@rolldown/binding-android-arm-eabi": {
      "version": "1.2.14",
```

```
    "resolved": "https://registry.npmjs.org/@rolldown/binding-android-arm-eabi/-/binding-android-arm-eabi-1.2.14.
    "integrity": "sha512-aWR+XKH9+rW7m5fWq/5360J3mHycrx/o6xZM2DQFdJnTMdyP7/WzxPjhtLbVWdKo2y612/4U1bWqb3HQhiF7vg==
    "cpu": [
      "arm"
    ],
    "dev": true,
    "license": "MIT",
    "optional": true,
    "os": [
      "android"
    ],
    "engines": {
      "node": "^20.19.0 || >=22.12.0"
    }
  },
  "node_modules/@rolldown/binding-android-arm64": {
    "version": "1.2.14",
    "resolved": "https://registry.npmjs.org/@rolldown/binding-android-arm64/-/binding-android-arm64-1.2.14.tgz",
    "integrity": "sha512-QiVxHofl6A8lQU7WAtOUY4QMVZXohxwz7WJJoeh8NBEUyKfIkMRKhYyq8az/1RypNiIXzNTtiS6KwHz0erxYRQ==
    "cpu": [
      "arm64"
    ],
    "dev": true,
    "license": "MIT",
    "optional": true,
    "os": [
      "android"
    ],
    "engines": {
      "node": "^20.19.0 || >=22.12.0"
    }
  },
  "node_modules/@rolldown/binding-darwin-arm64": {
    "version": "1.2.14",
    "resolved": "https://registry.npmjs.org/@rolldown/binding-darwin-arm64/-/binding-darwin-arm64-1.2.14.tgz",
    "integrity": "sha512-lTQOzHuBIooh3jIr5XINQkjPGEuGy+Dsy0meXDr6Sjty0b99kYgGh4uBC/8mJX1T0kC8d6S0aPP1Y+bHkh6aBw==
    "cpu": [
      "arm64"
    ],
    "dev": true,
    "license": "MIT",
    "optional": true,
    "os": [
      "darwin"
    ],
    "engines": {
      "node": "^20.19.0 || >=22.12.0"
    }
  },
  "node_modules/@rolldown/binding-darwin-x64": {
    "version": "1.2.14",
    "resolved": "https://registry.npmjs.org/@rolldown/binding-darwin-x64/-/binding-darwin-x64-1.2.14.tgz",
    "integrity": "sha512-hyMKEGatjmBYCs/Q4sbIcL/GqpFEqsX3wc+HYVQ/85A4rxc1o7rPm4DUI4GV4k/h0ITddwFSGpqQunI14GXjTA==
    "cpu": [
      "x64"
    ],
    "dev": true,
    "license": "MIT",
    "optional": true,
    "os": [
      "darwin"
    ],
    "engines": {
      "node": "^20.19.0 || >=22.12.0"
    }
  },
  "node_modules/@rolldown/binding-freebsd-x64": {
    "version": "1.2.14",
    "resolved": "https://registry.npmjs.org/@rolldown/binding-freebsd-x64/-/binding-freebsd-x64-1.2.14.tgz",
    "integrity": "sha512-u371GbXoVXrEgP20PwzoGNOdAOqAMhzo19JzzY+V4YmmnC+DTOoqdbMu+O+54emM59Mik/UdrtWgcuEDKWRPKA==
    "cpu": [
      "x64"
    ],
    "dev": true,
    "license": "MIT",
    "optional": true,
    "os": [
      "freebsd"
    ],
    "engines": {
      "node": "^20.19.0 || >=22.12.0"
```

```
    }
  },
  "node_modules/@rolldown/binding-linux-arm-gnueabihf": {
    "version": "1.2.14",
    "resolved": "https://registry.npmjs.org/@rolldown/binding-linux-arm-gnueabihf/-/binding-linux-arm-gnueabihf-1
    "integrity": "sha512-BqwKsdZQf6EqVWr8fv2MrDYzAvOZ7+NYFSJESRGs87fkseEhs0TU9TXgRJTkZoRRkxTizyEg1LKUXfU3/78uqg==
    "cpu": [
      "arm"
    ],
    "dev": true,
    "license": "MIT",
    "optional": true,
    "os": [
      "linux"
    ],
    "engines": {
      "node": "^20.19.0 || >=22.12.0"
    }
  },
  "node_modules/@rolldown/binding-linux-arm64-gnu": {
    "version": "1.2.14",
    "resolved": "https://registry.npmjs.org/@rolldown/binding-linux-arm64-gnu/-/binding-linux-arm64-gnu-1.2.14.tg
    "integrity": "sha512-SD9kY8M009x/7s57Z1dgUVlP5+uYBgKQK0Tkr1WIWngrtUJmRCW1RJFMY7QDla2khXhmg2i5Io7MUjcmZNZ/KQ==
    "cpu": [
      "arm64"
    ],
    "dev": true,
    "libc": [
      "glibc"
    ],
    "license": "MIT",
    "optional": true,
    "os": [
      "linux"
    ],
    "engines": {
      "node": "^20.19.0 || >=22.12.0"
    }
  },
  "node_modules/@rolldown/binding-linux-arm64-musl": {
    "version": "1.2.14",
    "resolved": "https://registry.npmjs.org/@rolldown/binding-linux-arm64-musl/-/binding-linux-arm64-musl-1.2.14.
    "integrity": "sha512-BJ2CL19M6uuWesMgnqJzgxoI+N+eV7b0A9O9vLV42y+gitC41fNa8KElau1tHVzuLWX5GzEuxMPhAO0tQXQMkg==
    "cpu": [
      "arm64"
    ],
    "dev": true,
    "libc": [
      "musl"
    ],
    "license": "MIT",
    "optional": true,
    "os": [
      "linux"
    ],
    "engines": {
      "node": "^20.19.0 || >=22.12.0"
    }
  },
  "node_modules/@rolldown/binding-linux-ppc64-gnu": {
    "version": "1.2.14",
    "resolved": "https://registry.npmjs.org/@rolldown/binding-linux-ppc64-gnu/-/binding-linux-ppc64-gnu-1.2.14.tg
    "integrity": "sha512-4+Kl8daPV8NDHaD7mfCcc1pRM+Qg7ab8DyMm5FG5WoZgv4h2i3KFN1CybYBNbQqmuYm7ftJLvmMI1eHYJ22S/Q==
    "cpu": [
      "ppc64"
    ],
    "dev": true,
    "libc": [
      "glibc"
    ],
    "license": "MIT",
    "optional": true,
    "os": [
      "linux"
    ],
    "engines": {
      "node": "^20.19.0 || >=22.12.0"
    }
  },
  "node_modules/@rolldown/binding-linux-s390x-gnu": {
    "version": "1.2.14",
```

```
      "resolved": "https://registry.npmjs.org/@rolldown/binding-linux-s390x-gnu/-/binding-linux-s390x-gnu-1.2.14.tg
      "integrity": "sha512-V/h8ePq1fKDrmtFMz6xcCN3DKvuvMRrwwD1q0PkBeeo4DpK64biaKvqWGVxqCeYKqeRk7gE7/iKPxLCn08O97A==
      "cpu": [
        "s390x"
      ],
      "dev": true,
      "libc": [
        "glibc"
      ],
      "license": "MIT",
      "optional": true,
      "os": [
        "linux"
      ],
      "engines": {
        "node": "^20.19.0 || >=22.12.0"
      }
    },
    "node_modules/@rolldown/binding-linux-x64-gnu": {
      "version": "1.2.14",
      "resolved": "https://registry.npmjs.org/@rolldown/binding-linux-x64-gnu/-/binding-linux-x64-gnu-1.2.14.tgz",
      "integrity": "sha512-WxalXzgrLVpKC93xfpaJ3gCXUWzeCr+FRCbDVD2mUAy4L6Vo3lNVz0epUEUpxPWJkLNYUwM4OSIikv36OJ9mLg==
      "cpu": [
        "x64"
      ],
      "dev": true,
      "libc": [
        "glibc"
      ],
      "license": "MIT",
      "optional": true,
      "os": [
        "linux"
      ],
      "engines": {
        "node": "^20.19.0 || >=22.12.0"
      }
    },
    "node_modules/@rolldown/binding-linux-x64-musl": {
      "version": "1.2.14",
      "resolved": "https://registry.npmjs.org/@rolldown/binding-linux-x64-musl/-/binding-linux-x64-musl-1.2.14.tgz"
      "integrity": "sha512-3G3tnAmTpdk9jO3GQtyHXqeFD2SlecfTws/Y3M2mmj9nMBwwuLT4kur8sZKeu7ENUHSpVO3cIsm5A52LEWWwlg==
      "cpu": [
        "x64"
      ],
      "dev": true,
      "libc": [
        "musl"
      ],
      "license": "MIT",
      "optional": true,
      "os": [
        "linux"
      ],
      "engines": {
        "node": "^20.19.0 || >=22.12.0"
      }
    },
    "node_modules/@rolldown/binding-openharmony-arm64": {
      "version": "1.2.14",
      "resolved": "https://registry.npmjs.org/@rolldown/binding-openharmony-arm64/-/binding-openharmony-arm64-1.2.1
      "integrity": "sha512-qyr5XiNGxm2ytx17vvtcJ9nXn6v1gENETi503bJx3OGwZ1tSonj7BosxbMa/xeAfSl5iS9X6KjEWYXLu6v1L7Q==
      "cpu": [
        "arm64"
      ],
      "dev": true,
      "license": "MIT",
      "optional": true,
      "os": [
        "openharmony"
      ],
      "engines": {
        "node": "^20.19.0 || >=22.12.0"
      }
    },
    "node_modules/@rolldown/binding-win32-arm64-msvc": {
      "version": "1.2.14",
      "resolved": "https://registry.npmjs.org/@rolldown/binding-win32-arm64-msvc/-/binding-win32-arm64-msvc-1.2.14.
      "integrity": "sha512-oA4o5o0S2yB199YyYXDzKUv1Z56Rc+mgOjwm7Z/vJ9Z8igiDPYvoOuDyo6g7AK/ZaF09nPhDKVnGBcYHO11GXA==
      "cpu": [
        "arm64"
```

```
    ],
    "dev": true,
    "license": "MIT",
    "optional": true,
    "os": [
      "win32"
    ],
    "engines": {
      "node": "^20.19.0 || >=22.12.0"
    }
  },
  "node_modules/@rolldown/binding-win32-x64-msvc": {
    "version": "1.2.14",
    "resolved": "https://registry.npmjs.org/@rolldown/binding-win32-x64-msvc/-/binding-win32-x64-msvc-1.2.14.tgz"
    "integrity": "sha512-9mE94bf2GZUaR/fUSXCMpBoWkctu421Mi0ORpm4zqfbkjKep7RxzPFa5etcGs5h+2KApoWBOA/hAJa/7saGgEQ==
    "cpu": [
      "x64"
    ],
    "dev": true,
    "license": "MIT",
    "optional": true,
    "os": [
      "win32"
    ],
    "engines": {
      "node": "^20.19.0 || >=22.12.0"
    }
  },
  "node_modules/@rolldown/pluginutils": {
    "version": "1.0.1",
    "resolved": "https://registry.npmjs.org/@rolldown/pluginutils/-/pluginutils-1.0.1.tgz",
    "integrity": "sha512-2j9bGt5Jh8hj+vPtgzPtl72j0yRxHAyumoo6TNfAjsLB04UtpSvPbPcDcBMxz7n+9CYB0c1GxQFxYRg2jimqGw==
    "dev": true,
    "license": "MIT"
  },
  "node_modules/@tailwindcss/node": {
    "version": "4.3.3",
    "resolved": "https://registry.npmjs.org/@tailwindcss/node/-/node-4.3.3.tgz",
    "integrity": "sha512-/T8IKEsf9VTU6tLjgC7+sv2mOPtQxzE2jMw7u4Tt40Tx+QSZxpzh95/H6cMKoja9XuW7iMdLJYBB0o9G1CaAgg==
    "dev": true,
    "license": "MIT",
    "dependencies": {
      "@jridgewell/remapping": "^2.3.5",
      "enhanced-resolve": "^5.24.1",
      "jiti": "^2.7.0",
      "lightningcss": "1.32.0",
      "magic-string": "^0.30.21",
      "source-map-js": "^1.2.1",
      "tailwindcss": "4.3.3"
    }
  },
  "node_modules/@tailwindcss/node/node_modules/lightningcss": {
    "version": "1.32.0",
    "resolved": "https://registry.npmjs.org/lightningcss/-/lightningcss-1.32.0.tgz",
    "integrity": "sha512-NXYBzinNrblfraPGyrbPoD19C1h9lfI/1mzgWYvXUTe414Gz/X1FD2XBZSZM7rRTrMA8JL3OtAaGifrIKhQ5yQ==
    "dev": true,
    "license": "MPL-2.0",
    "dependencies": {
      "detect-libc": "^2.0.3"
    },
    "engines": {
      "node": ">= 12.0.0"
    },
    "funding": {
      "type": "opencollective",
      "url": "https://opencollective.com/parcel"
    },
    "optionalDependencies": {
      "lightningcss-android-arm64": "1.32.0",
      "lightningcss-darwin-arm64": "1.32.0",
      "lightningcss-darwin-x64": "1.32.0",
      "lightningcss-freebsd-x64": "1.32.0",
      "lightningcss-linux-arm-gnueabihf": "1.32.0",
      "lightningcss-linux-arm64-gnu": "1.32.0",
      "lightningcss-linux-arm64-musl": "1.32.0",
      "lightningcss-linux-x64-gnu": "1.32.0",
      "lightningcss-linux-x64-musl": "1.32.0",
      "lightningcss-win32-arm64-msvc": "1.32.0",
      "lightningcss-win32-x64-msvc": "1.32.0"
    }
  },
```

```
    "node_modules/@tailwindcss/node/node_modules/lightningcss-android-arm64": {
      "version": "1.32.0",
      "resolved": "https://registry.npmjs.org/lightningcss-android-arm64/-/lightningcss-android-arm64-1.32.0.tgz",
      "integrity": "sha512-YK7/ClTt4kAK0vo6w3X+Pnm0D2cf2vPHbhOXdoNti1Ga0al1P4TBZhwjATvjNwLEBCnKvjJc2jQgHXH0NEwlAg==
      "cpu": [
        "arm64"
      ],
      "dev": true,
      "license": "MPL-2.0",
      "optional": true,
      "os": [
        "android"
      ],
      "engines": {
        "node": ">= 12.0.0"
      },
      "funding": {
        "type": "opencollective",
        "url": "https://opencollective.com/parcel"
      }
    },
    "node_modules/@tailwindcss/node/node_modules/lightningcss-darwin-arm64": {
      "version": "1.32.0",
      "resolved": "https://registry.npmjs.org/lightningcss-darwin-arm64/-/lightningcss-darwin-arm64-1.32.0.tgz",
      "integrity": "sha512-RzeG9Ju5bag2Bv1/lwlVJvBE3q6TtXskdZLLCyfg5pt+HLz9BqlICO7LZM7VHNTTn/5PRhHFBSjk5lc4cmscPQ==
      "cpu": [
        "arm64"
      ],
      "dev": true,
      "license": "MPL-2.0",
      "optional": true,
      "os": [
        "darwin"
      ],
      "engines": {
        "node": ">= 12.0.0"
      },
      "funding": {
        "type": "opencollective",
        "url": "https://opencollective.com/parcel"
      }
    },
    "node_modules/@tailwindcss/node/node_modules/lightningcss-darwin-x64": {
      "version": "1.32.0",
      "resolved": "https://registry.npmjs.org/lightningcss-darwin-x64/-/lightningcss-darwin-x64-1.32.0.tgz",
      "integrity": "sha512-U+QsBp2m/s2wqpUYT/6wnlagdZbtZdndSmut/NJqlCcMLTWp5muCrID+K5UJ6jqD2BFshejCYXniPDbNh73V8w==
      "cpu": [
        "x64"
      ],
      "dev": true,
      "license": "MPL-2.0",
      "optional": true,
      "os": [
        "darwin"
      ],
      "engines": {
        "node": ">= 12.0.0"
      },
      "funding": {
        "type": "opencollective",
        "url": "https://opencollective.com/parcel"
      }
    },
    "node_modules/@tailwindcss/node/node_modules/lightningcss-freebsd-x64": {
      "version": "1.32.0",
      "resolved": "https://registry.npmjs.org/lightningcss-freebsd-x64/-/lightningcss-freebsd-x64-1.32.0.tgz",
      "integrity": "sha512-JCTigedEksZk3tHTTthnMdVfGf61Fky8Ji2E4YjUTEQX14xiy/lTzXnu1vwiZe3bYe0q+SpsSH/CTeDXK6WHig==
      "cpu": [
        "x64"
      ],
      "dev": true,
      "license": "MPL-2.0",
      "optional": true,
      "os": [
        "freebsd"
      ],
      "engines": {
        "node": ">= 12.0.0"
      },
      "funding": {
        "type": "opencollective",
```

```
        "url": "https://opencollective.com/parcel"
      }
    },
    "node_modules/@tailwindcss/node/node_modules/lightningcss-linux-arm-gnueabihf": {
      "version": "1.32.0",
      "resolved": "https://registry.npmjs.org/lightningcss-linux-arm-gnueabihf/-/lightningcss-linux-arm-gnueabihf-1
      "integrity": "sha512-x6rnnpRa2GL0zQOkt6rts3YDPzduLpWvwAF6EMhXFVZXD4tPrBkEFqzGowzCsIWsPjqSK+tyNEODUBXeeVHSkw==
      "cpu": [
        "arm"
      ],
      "dev": true,
      "license": "MPL-2.0",
      "optional": true,
      "os": [
        "linux"
      ],
      "engines": {
        "node": ">= 12.0.0"
      },
      "funding": {
        "type": "opencollective",
        "url": "https://opencollective.com/parcel"
      }
    },
    "node_modules/@tailwindcss/node/node_modules/lightningcss-linux-arm64-gnu": {
      "version": "1.32.0",
      "resolved": "https://registry.npmjs.org/lightningcss-linux-arm64-gnu/-/lightningcss-linux-arm64-gnu-1.32.0.tg
      "integrity": "sha512-0nnMyoyOLRJXfbMOilaSRcLH3Jw5z9HDNGfT/gwCPgaDjnx0i8w7vBzFLFR1f6CMLKF8gVbebmkUN3fa/kQJpQ==
      "cpu": [
        "arm64"
      ],
      "dev": true,
      "libc": [
        "glibc"
      ],
      "license": "MPL-2.0",
      "optional": true,
      "os": [
        "linux"
      ],
      "engines": {
        "node": ">= 12.0.0"
      },
      "funding": {
        "type": "opencollective",
        "url": "https://opencollective.com/parcel"
      }
    },
    "node_modules/@tailwindcss/node/node_modules/lightningcss-linux-arm64-musl": {
      "version": "1.32.0",
      "resolved": "https://registry.npmjs.org/lightningcss-linux-arm64-musl/-/lightningcss-linux-arm64-musl-1.32.0.
      "integrity": "sha512-UpQkoenr4UJEzgVIYpI80lDFvRmPVg6oqboNHfoH4CQIfNA+HOrZ7Mo7KZP02dC6LjghPQJeBsvXhJod/wnIBg==
      "cpu": [
        "arm64"
      ],
      "dev": true,
      "libc": [
        "musl"
      ],
      "license": "MPL-2.0",
      "optional": true,
      "os": [
        "linux"
      ],
      "engines": {
        "node": ">= 12.0.0"
      },
      "funding": {
        "type": "opencollective",
        "url": "https://opencollective.com/parcel"
      }
    },
    "node_modules/@tailwindcss/node/node_modules/lightningcss-linux-x64-gnu": {
      "version": "1.32.0",
      "resolved": "https://registry.npmjs.org/lightningcss-linux-x64-gnu/-/lightningcss-linux-x64-gnu-1.32.0.tgz",
      "integrity": "sha512-V7Qr52IhZmdKPVr+Vtw8o+WLsQJYCTd8loIfpDaMRWGUZfBOYEJeyJIkqGIDMZPwPx24pUMfwSxxI8phr/MbOA==
      "cpu": [
        "x64"
      ],
      "dev": true,
      "libc": [
```

```
        "glibc"
      ],
      "license": "MPL-2.0",
      "optional": true,
      "os": [
        "linux"
      ],
      "engines": {
        "node": ">= 12.0.0"
      },
      "funding": {
        "type": "opencollective",
        "url": "https://opencollective.com/parcel"
      }
    },
    "node_modules/@tailwindcss/node/node_modules/lightningcss-linux-x64-musl": {
      "version": "1.32.0",
      "resolved": "https://registry.npmjs.org/lightningcss-linux-x64-musl/-/lightningcss-linux-x64-musl-1.32.0.tgz"
      "integrity": "sha512-bYcLp+Vb0awsiXg/80uCRezCYHNg1/l3mt0gzHnWV9XP1W5sKa5/TCdGWaR/zBM2PeF/HbsQv/j2URNOiVuxWg==
      "cpu": [
        "x64"
      ],
      "dev": true,
      "libc": [
        "musl"
      ],
      "license": "MPL-2.0",
      "optional": true,
      "os": [
        "linux"
      ],
      "engines": {
        "node": ">= 12.0.0"
      },
      "funding": {
        "type": "opencollective",
        "url": "https://opencollective.com/parcel"
      }
    },
    "node_modules/@tailwindcss/node/node_modules/lightningcss-win32-arm64-msvc": {
      "version": "1.32.0",
      "resolved": "https://registry.npmjs.org/lightningcss-win32-arm64-msvc/-/lightningcss-win32-arm64-msvc-1.32.0.
      "integrity": "sha512-8SbC8BR40pS6baCM8sbtYDSwEVQd4JlFTOlaD3gWGHfThTcABnNDBda6eTZeqbofalIJhFx0qKzgHJmcPTnGdw==
      "cpu": [
        "arm64"
      ],
      "dev": true,
      "license": "MPL-2.0",
      "optional": true,
      "os": [
        "win32"
      ],
      "engines": {
        "node": ">= 12.0.0"
      },
      "funding": {
        "type": "opencollective",
        "url": "https://opencollective.com/parcel"
      }
    },
    "node_modules/@tailwindcss/node/node_modules/lightningcss-win32-x64-msvc": {
      "version": "1.32.0",
      "resolved": "https://registry.npmjs.org/lightningcss-win32-x64-msvc/-/lightningcss-win32-x64-msvc-1.32.0.tgz"
      "integrity": "sha512-Amq9B/SoZYdDi1kFrojnoqPLxYhQ4Wo5XiL8EVJrVsB8ARoC1PWW6VGtT0WKCemjy8aC+louJnjS7U18x3b06Q==
      "cpu": [
        "x64"
      ],
      "dev": true,
      "license": "MPL-2.0",
      "optional": true,
      "os": [
        "win32"
      ],
      "engines": {
        "node": ">= 12.0.0"
      },
      "funding": {
        "type": "opencollective",
        "url": "https://opencollective.com/parcel"
      }
    },
```

```
    "node_modules/@tailwindcss/oxide": {
      "version": "4.3.3",
      "resolved": "https://registry.npmjs.org/@tailwindcss/oxide/-/oxide-4.3.3.tgz",
      "integrity": "sha512-krXjAikiaFSPaK/FkAQT5UTx3VormQaiZ5hBFlJZ9UFQGB/rwg1MZIhHAG9smMQRTdyJxP6Qt5MwMtdyU5FWrA==",
      "dev": true,
      "license": "MIT",
      "engines": {
        "node": ">= 20"
      },
      "optionalDependencies": {
        "@tailwindcss/oxide-android-arm64": "4.3.3",
        "@tailwindcss/oxide-darwin-arm64": "4.3.3",
        "@tailwindcss/oxide-darwin-x64": "4.3.3",
        "@tailwindcss/oxide-freebsd-x64": "4.3.3",
        "@tailwindcss/oxide-linux-arm-gnueabihf": "4.3.3",
        "@tailwindcss/oxide-linux-arm64-gnu": "4.3.3",
        "@tailwindcss/oxide-linux-arm64-musl": "4.3.3",
        "@tailwindcss/oxide-linux-x64-gnu": "4.3.3",
        "@tailwindcss/oxide-linux-x64-musl": "4.3.3",
        "@tailwindcss/oxide-wasm32-wasi": "4.3.3",
        "@tailwindcss/oxide-win32-arm64-msvc": "4.3.3",
        "@tailwindcss/oxide-win32-x64-msvc": "4.3.3"
      }
    },
    "node_modules/@tailwindcss/oxide-android-arm64": {
      "version": "4.3.3",
      "resolved": "https://registry.npmjs.org/@tailwindcss/oxide-android-arm64/-/oxide-android-arm64-4.3.3.tgz",
      "integrity": "sha512-Y85A2gmPSkl5Ve5qR86GL4HT509cFqQh1aes9p3sSkyTPwt0Pppf3GkwGe4JPACcRYjgJIEhQgM6dBClnr0NYw==",
      "cpu": [
        "arm64"
      ],
      "dev": true,
      "license": "MIT",
      "optional": true,
      "os": [
        "android"
      ],
      "engines": {
        "node": ">= 20"
      }
    },
    "node_modules/@tailwindcss/oxide-darwin-arm64": {
      "version": "4.3.3",
      "resolved": "https://registry.npmjs.org/@tailwindcss/oxide-darwin-arm64/-/oxide-darwin-arm64-4.3.3.tgz",
      "integrity": "sha512-BiaWatpBcERQFDlOjRDpIVXuFK5PJez5SA4JMg6VYZdBYU+qKfV/vqjcIs+IYmtitf1xYQZTwXvU/8y4lfZUGw==",
      "cpu": [
        "arm64"
      ],
      "dev": true,
      "license": "MIT",
      "optional": true,
      "os": [
        "darwin"
      ],
      "engines": {
        "node": ">= 20"
      }
    },
    "node_modules/@tailwindcss/oxide-darwin-x64": {
      "version": "4.3.3",
      "resolved": "https://registry.npmjs.org/@tailwindcss/oxide-darwin-x64/-/oxide-darwin-x64-4.3.3.tgz",
      "integrity": "sha512-fAeUqfV5ndhxRwai8cXGzdLvul9utWOmeTkv69unv4ZXixjn61Z+p9lCWdwOwA3TYboG3BwdVuN/RDjhBRl0mw==",
      "cpu": [
        "x64"
      ],
      "dev": true,
      "license": "MIT",
      "optional": true,
      "os": [
        "darwin"
      ],
      "engines": {
        "node": ">= 20"
      }
    },
    "node_modules/@tailwindcss/oxide-freebsd-x64": {
      "version": "4.3.3",
      "resolved": "https://registry.npmjs.org/@tailwindcss/oxide-freebsd-x64/-/oxide-freebsd-x64-4.3.3.tgz",
      "integrity": "sha512-iyf5bV6+wnAlflVeEy7R25dupxTNECZN5QMI0qNT6eT+EgaGdZcKhGkr5SdoaWiLJ3spLqIY9VCeSGrwmtg4kw==",
      "cpu": [
        "x64"
```

```
      ],
      "dev": true,
      "license": "MIT",
      "optional": true,
      "os": [
        "freebsd"
      ],
      "engines": {
        "node": ">= 20"
      }
    },
    "node_modules/@tailwindcss/oxide-linux-arm-gnueabihf": {
      "version": "4.3.3",
      "resolved": "https://registry.npmjs.org/@tailwindcss/oxide-linux-arm-gnueabihf/-/oxide-linux-arm-gnueabihf-4.
      "integrity": "sha512-aAYUprJAJQWWbRrPvtjdroZ56Md+JM8pMiopS6xGEwDfLhqj+2ver2p4nU4Mb3CRqcMmNBjo8KkUgcxhkzVQGQ==
      "cpu": [
        "arm"
      ],
      "dev": true,
      "license": "MIT",
      "optional": true,
      "os": [
        "linux"
      ],
      "engines": {
        "node": ">= 20"
      }
    },
    "node_modules/@tailwindcss/oxide-linux-arm64-gnu": {
      "version": "4.3.3",
      "resolved": "https://registry.npmjs.org/@tailwindcss/oxide-linux-arm64-gnu/-/oxide-linux-arm64-gnu-4.3.3.tgz"
      "integrity": "sha512-nDxldcEENOxZRzC2uu9jrutZdAAQtb+8WWDCSnWL1zvBk1+FN+x6MtDViPB5AJMfttVCUhehGWus3XBPgatM/w==
      "cpu": [
        "arm64"
      ],
      "dev": true,
      "libc": [
        "glibc"
      ],
      "license": "MIT",
      "optional": true,
      "os": [
        "linux"
      ],
      "engines": {
        "node": ">= 20"
      }
    },
    "node_modules/@tailwindcss/oxide-linux-arm64-musl": {
      "version": "4.3.3",
      "resolved": "https://registry.npmjs.org/@tailwindcss/oxide-linux-arm64-musl/-/oxide-linux-arm64-musl-4.3.3.tg
      "integrity": "sha512-Md44bD6veX/PC5iyF8cDVnw4HBIANZepRZZ7a8DQOvkfo5WUBwcp6iAuCUz23u+4SUkhJlD3eL7hNdW8ezd/kA==
      "cpu": [
        "arm64"
      ],
      "dev": true,
      "libc": [
        "musl"
      ],
      "license": "MIT",
      "optional": true,
      "os": [
        "linux"
      ],
      "engines": {
        "node": ">= 20"
      }
    },
    "node_modules/@tailwindcss/oxide-linux-x64-gnu": {
      "version": "4.3.3",
      "resolved": "https://registry.npmjs.org/@tailwindcss/oxide-linux-x64-gnu/-/oxide-linux-x64-gnu-4.3.3.tgz",
      "integrity": "sha512-tx7us1muwOKAKWao2v/GaafFeQboE6aj88vC6ziN2NCGcRm8gWUhwjzg+YdVB1e4boAtdtma4L43onunI6NS4w==
      "cpu": [
        "x64"
      ],
      "dev": true,
      "libc": [
        "glibc"
      ],
      "license": "MIT",
      "optional": true,
```

```
      "os": [
        "linux"
      ],
      "engines": {
        "node": ">= 20"
      }
    },
    "node_modules/@tailwindcss/oxide-linux-x64-musl": {
      "version": "4.3.3",
      "resolved": "https://registry.npmjs.org/@tailwindcss/oxide-linux-x64-musl/-/oxide-linux-x64-musl-4.3.3.tgz",
      "integrity": "sha512-SJxX60smvHgasZoBy11dX6YRjXJFovwWBoedhbQPOBzgFWBHGB+TVPWB9BxzR7TTxU8FQZAI2AyiNCMzFm8Img==
      "cpu": [
        "x64"
      ],
      "dev": true,
      "libc": [
        "musl"
      ],
      "license": "MIT",
      "optional": true,
      "os": [
        "linux"
      ],
      "engines": {
        "node": ">= 20"
      }
    },
    "node_modules/@tailwindcss/oxide-wasm32-wasi": {
      "version": "4.3.3",
      "resolved": "https://registry.npmjs.org/@tailwindcss/oxide-wasm32-wasi/-/oxide-wasm32-wasi-4.3.3.tgz",
      "integrity": "sha512-jx1+rPhY/5Ympkktd656HBWEBLxP7dH06losBLjjf5vgCODXvi9KhtftWcMIwTFIDqBr7cRnQkdLnAG+IOlGvQ==
      "bundleDependencies": [
        "@napi-rs/wasm-runtime",
        "@emnapi/core",
        "@emnapi/runtime",
        "@tybys/wasm-util",
        "@emnapi/wasi-threads",
        "tslib"
      ],
      "cpu": [
        "wasm32"
      ],
      "dev": true,
      "license": "MIT",
      "optional": true,
      "dependencies": {
        "@emnapi/core": "^1.11.1",
        "@emnapi/runtime": "^1.11.1",
        "@emnapi/wasi-threads": "^1.2.2",
        "@napi-rs/wasm-runtime": "^1.1.4",
        "@tybys/wasm-util": "^0.10.2",
        "tslib": "^2.8.1"
      },
      "engines": {
        "node": ">=14.0.0"
      }
    },
    "node_modules/@tailwindcss/oxide-win32-arm64-msvc": {
      "version": "4.3.3",
      "resolved": "https://registry.npmjs.org/@tailwindcss/oxide-win32-arm64-msvc/-/oxide-win32-arm64-msvc-4.3.3.tg
      "integrity": "sha512-3rc292Ca2ceK6Ulcc/bAVnTs/3nDtoPhyEKlgPv+yQJQi/JS/AMJlqzxvlDacL1nekbrcf6bTqp/jV4qgnPxNQ==
      "cpu": [
        "arm64"
      ],
      "dev": true,
      "license": "MIT",
      "optional": true,
      "os": [
        "win32"
      ],
      "engines": {
        "node": ">= 20"
      }
    },
    "node_modules/@tailwindcss/oxide-win32-x64-msvc": {
      "version": "4.3.3",
      "resolved": "https://registry.npmjs.org/@tailwindcss/oxide-win32-x64-msvc/-/oxide-win32-x64-msvc-4.3.3.tgz",
      "integrity": "sha512-yJ0pwIVc/nYeGoV02WtsN8KYyLQv7kyI2wDnkezyJlGGjkd4QLwDGAwl47YpPJeuI0M0ObaXGSPjvWDPeTPggw==
      "cpu": [
        "x64"
      ],
```

```
    "dev": true,
    "license": "MIT",
    "optional": true,
    "os": [
      "win32"
    ],
    "engines": {
      "node": ">= 20"
    }
  },
  "node_modules/@tailwindcss/vite": {
    "version": "4.3.3",
    "resolved": "https://registry.npmjs.org/@tailwindcss/vite/-/vite-4.3.3.tgz",
    "integrity": "sha512-yYU8cogLeSh/ms2jh8Fj7jaba/EWa7Ja6GoUqYZaraEuCI5YS6ms6ObZgjjedm+jm6XZjdNRWBpPP6Z86oOxcw==
    "dev": true,
    "license": "MIT",
    "dependencies": {
      "@tailwindcss/node": "4.3.3",
      "@tailwindcss/oxide": "4.3.3",
      "tailwindcss": "4.3.3"
    },
    "peerDependencies": {
      "vite": "^5.2.0 || ^6 || ^7 || ^8"
    }
  },
  "node_modules/@tauri-apps/api": {
    "version": "2.12.4",
    "resolved": "https://registry.npmjs.org/@tauri-apps/api/-/api-2.12.4.tgz",
    "integrity": "sha512-pVmfis+4zT8H0Qhp3xPZx9Ju7kpzvA6rr/PSJPyuwfvucTQ8sVt61NYU9KMkK703UFlYadFmjKA4HhybOtN0gg==
    "license": "Apache-2.0 OR MIT",
    "funding": {
      "type": "opencollective",
      "url": "https://opencollective.com/tauri"
    }
  },
  "node_modules/@tauri-apps/cli": {
    "version": "2.12.3",
    "resolved": "https://registry.npmjs.org/@tauri-apps/cli/-/cli-2.12.3.tgz",
    "integrity": "sha512-f7/LsY74SVb1ChmOPw1ajOpxii0GSzDAgmWHRci8JUYuuai04rXsSbFobpmB0sP2DdlvMD/B5ZotEn8GOGMRUg==
    "dev": true,
    "license": "Apache-2.0 OR MIT",
    "bin": {
      "tauri": "tauri.js"
    },
    "engines": {
      "node": ">= 10"
    },
    "funding": {
      "type": "opencollective",
      "url": "https://opencollective.com/tauri"
    },
    "optionalDependencies": {
      "@tauri-apps/cli-darwin-arm64": "2.12.3",
      "@tauri-apps/cli-darwin-x64": "2.12.3",
      "@tauri-apps/cli-linux-arm-gnueabihf": "2.12.3",
      "@tauri-apps/cli-linux-arm64-gnu": "2.12.3",
      "@tauri-apps/cli-linux-arm64-musl": "2.12.3",
      "@tauri-apps/cli-linux-riscv64-gnu": "2.12.3",
      "@tauri-apps/cli-linux-x64-gnu": "2.12.3",
      "@tauri-apps/cli-linux-x64-musl": "2.12.3",
      "@tauri-apps/cli-win32-arm64-msvc": "2.12.3",
      "@tauri-apps/cli-win32-ia32-msvc": "2.12.3",
      "@tauri-apps/cli-win32-x64-msvc": "2.12.3"
    }
  },
  "node_modules/@tauri-apps/cli-darwin-arm64": {
    "version": "2.12.3",
    "resolved": "https://registry.npmjs.org/@tauri-apps/cli-darwin-arm64/-/cli-darwin-arm64-2.12.3.tgz",
    "integrity": "sha512-xmVNoJOOKzKLj7GLHXmXLimRby9M42aBIJa0sB80N7o24eKV5JiVmToKTRLVH9yhL05GZ/B6rSSOmbzNFJwBAA==
    "cpu": [
      "arm64"
    ],
    "dev": true,
    "license": "Apache-2.0 OR MIT",
    "optional": true,
    "os": [
      "darwin"
    ],
    "engines": {
      "node": ">= 10"
    }
```

```
    },
    "node_modules/@tauri-apps/cli-darwin-x64": {
      "version": "2.12.3",
      "resolved": "https://registry.npmjs.org/@tauri-apps/cli-darwin-x64/-/cli-darwin-x64-2.12.3.tgz",
      "integrity": "sha512-URd+0usfmUQQyb5kNPiKt2OT8gp7oGU7QR+qOppB6e35mpVBFFVNhWc9oWb3p0u71fDJ09DpF4T6m9xYxoIB8g==
      "cpu": [
        "x64"
      ],
      "dev": true,
      "license": "Apache-2.0 OR MIT",
      "optional": true,
      "os": [
        "darwin"
      ],
      "engines": {
        "node": ">= 10"
      }
    },
    "node_modules/@tauri-apps/cli-linux-arm-gnueabihf": {
      "version": "2.12.3",
      "resolved": "https://registry.npmjs.org/@tauri-apps/cli-linux-arm-gnueabihf/-/cli-linux-arm-gnueabihf-2.12.3.
      "integrity": "sha512-0kwUVx2LbmOoTRlwF1oDww7th4/NSluv4ZBQ6KRZsFKg4g0TlTcIiJ0VehqkQYUeC9xIT1Mk6XtF52mI155VSQ==
      "cpu": [
        "arm"
      ],
      "dev": true,
      "license": "Apache-2.0 OR MIT",
      "optional": true,
      "os": [
        "linux"
      ],
      "engines": {
        "node": ">= 10"
      }
    },
    "node_modules/@tauri-apps/cli-linux-arm64-gnu": {
      "version": "2.12.3",
      "resolved": "https://registry.npmjs.org/@tauri-apps/cli-linux-arm64-gnu/-/cli-linux-arm64-gnu-2.12.3.tgz",
      "integrity": "sha512-gKSGDx6fx+HBLQmG6guChFdisbrCSdx9Yli+j5teOa64gm1CeM+C6NLru5Pj3ZkkEep05BmCFjxvX+cjqAycZQ==
      "cpu": [
        "arm64"
      ],
      "dev": true,
      "libc": [
        "glibc"
      ],
      "license": "Apache-2.0 OR MIT",
      "optional": true,
      "os": [
        "linux"
      ],
      "engines": {
        "node": ">= 10"
      }
    },
    "node_modules/@tauri-apps/cli-linux-arm64-musl": {
      "version": "2.12.3",
      "resolved": "https://registry.npmjs.org/@tauri-apps/cli-linux-arm64-musl/-/cli-linux-arm64-musl-2.12.3.tgz",
      "integrity": "sha512-Yr59qMy/gcvAfBuFdCGlAmGiLsYWMFDbsP4bAI6iNBzcJTGrYWZGeiQhGDo29MQwfF/NUBqyM2qljXu5tZ6wjQ==
      "cpu": [
        "arm64"
      ],
      "dev": true,
      "libc": [
        "musl"
      ],
      "license": "Apache-2.0 OR MIT",
      "optional": true,
      "os": [
        "linux"
      ],
      "engines": {
        "node": ">= 10"
      }
    },
    "node_modules/@tauri-apps/cli-linux-riscv64-gnu": {
      "version": "2.12.3",
      "resolved": "https://registry.npmjs.org/@tauri-apps/cli-linux-riscv64-gnu/-/cli-linux-riscv64-gnu-2.12.3.tgz"
      "integrity": "sha512-jKr0/REBMnLKC0OwPQZkyge0mKDaNZ0b/AbfGwVyCgFfwS730EVLfVDo3nt7MUu6jJaytRq08+xSj5qfy+U1+Q==
      "cpu": [
        "riscv64"
```

```
    ],
    "dev": true,
    "libc": [
      "glibc"
    ],
    "license": "Apache-2.0 OR MIT",
    "optional": true,
    "os": [
      "linux"
    ],
    "engines": {
      "node": ">= 10"
    }
  },
  "node_modules/@tauri-apps/cli-linux-x64-gnu": {
    "version": "2.12.3",
    "resolved": "https://registry.npmjs.org/@tauri-apps/cli-linux-x64-gnu/-/cli-linux-x64-gnu-2.12.3.tgz",
    "integrity": "sha512-gTkEqJAGCMROGanxHnzaJzQ+/rXl39HWVg0/hDODS1wDWBGqoceqGC6Qm1+mQbyT11xnsB8mKu/gyVID/YpFIw==
    "cpu": [
      "x64"
    ],
    "dev": true,
    "libc": [
      "glibc"
    ],
    "license": "Apache-2.0 OR MIT",
    "optional": true,
    "os": [
      "linux"
    ],
    "engines": {
      "node": ">= 10"
    }
  },
  "node_modules/@tauri-apps/cli-linux-x64-musl": {
    "version": "2.12.3",
    "resolved": "https://registry.npmjs.org/@tauri-apps/cli-linux-x64-musl/-/cli-linux-x64-musl-2.12.3.tgz",
    "integrity": "sha512-T2dTxL1svRym71fZtaW4pZYXbthbfFsEJr1NeOUg/p7laWXZbUt/8DMSZf8recu9f7+1F/Lv00HtzsEu6vDO9w==
    "cpu": [
      "x64"
    ],
    "dev": true,
    "libc": [
      "musl"
    ],
    "license": "Apache-2.0 OR MIT",
    "optional": true,
    "os": [
      "linux"
    ],
    "engines": {
      "node": ">= 10"
    }
  },
  "node_modules/@tauri-apps/cli-win32-arm64-msvc": {
    "version": "2.12.3",
    "resolved": "https://registry.npmjs.org/@tauri-apps/cli-win32-arm64-msvc/-/cli-win32-arm64-msvc-2.12.3.tgz",
    "integrity": "sha512-eoiQwpEZWbpsVHcM9BAzqqe4TCHszvr3rsM7pUQ4ofLK0lF1i1d/jX0Qo5DYMqcrUtwQuDdDuOCbcT0Izf1VwQ==
    "cpu": [
      "arm64"
    ],
    "dev": true,
    "license": "Apache-2.0 OR MIT",
    "optional": true,
    "os": [
      "win32"
    ],
    "engines": {
      "node": ">= 10"
    }
  },
  "node_modules/@tauri-apps/cli-win32-ia32-msvc": {
    "version": "2.12.3",
    "resolved": "https://registry.npmjs.org/@tauri-apps/cli-win32-ia32-msvc/-/cli-win32-ia32-msvc-2.12.3.tgz",
    "integrity": "sha512-kE+KUg6Dbbkgvcw0m99wJVIToFQzJqpMBAXah74WqxaLzssNwSTUccrHp6+QVzMhjQP330tvekFmnQF+0NbE6Q==
    "cpu": [
      "ia32"
    ],
    "dev": true,
    "license": "Apache-2.0 OR MIT",
    "optional": true,
```

```
      "os": [
        "win32"
      ],
      "engines": {
        "node": ">= 10"
      }
    },
    "node_modules/@tauri-apps/cli-win32-x64-msvc": {
      "version": "2.12.3",
      "resolved": "https://registry.npmjs.org/@tauri-apps/cli-win32-x64-msvc/-/cli-win32-x64-msvc-2.12.3.tgz",
      "integrity": "sha512-L7wndWAgX2mLW7alswpL3d1R0P9FN2WYBgHaQkAYEBxHHGkY4vFX9CjcRQ1LAxDAMIJxrY7/aDziFJeChS84NQ==
      "cpu": [
        "x64"
      ],
      "dev": true,
      "license": "Apache-2.0 OR MIT",
      "optional": true,
      "os": [
        "win32"
      ],
      "engines": {
        "node": ">= 10"
      }
    },
    "node_modules/@tauri-apps/plugin-dialog": {
      "version": "2.8.3",
      "resolved": "https://registry.npmjs.org/@tauri-apps/plugin-dialog/-/plugin-dialog-2.8.3.tgz",
      "integrity": "sha512-Hd/yBfk2R5v2MFrz/0VArSXeh8xKLLXGunqSiTtcHKn1zNZwaKujuA0VSwUvNfwC4hDoF1PveS+gBDNe3nHspw==
      "license": "MIT OR Apache-2.0",
      "dependencies": {
        "@tauri-apps/api": "^2.12.0"
      }
    },
    "node_modules/@tauri-apps/plugin-opener": {
      "version": "2.7.2",
      "resolved": "https://registry.npmjs.org/@tauri-apps/plugin-opener/-/plugin-opener-2.7.2.tgz",
      "integrity": "sha512-LyybP1VSzTMQiaFYcsbAse47KpivlyXdLZMQzGLEnkgQacGESnpjAfFoQ6h5sqWgAdZDH9szYjPzHMpv0Sz+TQ==
      "license": "MIT OR Apache-2.0",
      "dependencies": {
        "@tauri-apps/api": "^2.12.0"
      }
    },
    "node_modules/@types/node": {
      "version": "26.6.5",
      "resolved": "https://registry.npmjs.org/@types/node/-/node-26.6.5.tgz",
      "integrity": "sha512-uMzsv9stDdofIZBx4UGh4Z9ZgXnGC9seRDscilBcTHAeOFk67MZg/k9bWVfO+bk4qZmG+l52hRnLwUiH2LnJTg==
      "license": "MIT",
      "dependencies": {
        "undici-types": "~8.9.0"
      }
    },
    "node_modules/@types/react": {
      "version": "19.3.0",
      "resolved": "https://registry.npmjs.org/@types/react/-/react-19.3.0.tgz",
      "integrity": "sha512-N0rFCuH9YoxG9/m61l9MfpJKfmLOVU0em7ipIz6TRgSSkvReLB9vL85GB+yr8Bs5leqpvg96JSwF4ZS1s4viQg==
      "devOptional": true,
      "license": "MIT",
      "dependencies": {
        "csstype": "^3.2.2"
      }
    },
    "node_modules/@types/react-dom": {
      "version": "19.3.0",
      "resolved": "https://registry.npmjs.org/@types/react-dom/-/react-dom-19.3.0.tgz",
      "integrity": "sha512-ZI7bU42mZXXKHn/qNLEw2IrbiINU7X5+vfgdixBHkCNpYWXjKgfQ/P+uyGb5CjOLB9UcnTeg3rylQtV2hym44Q==
      "devOptional": true,
      "license": "MIT",
      "peerDependencies": {
        "@types/react": "^19.3.0"
      }
    },
    "node_modules/@vitejs/plugin-react": {
      "version": "6.1.2",
      "resolved": "https://registry.npmjs.org/@vitejs/plugin-react/-/plugin-react-6.1.2.tgz",
      "integrity": "sha512-fhJNGUdscQa4HkI0xFxwonWyhnVReCPDbXI7FH7jmzpnVCrFQI7PRrhWecO263610vOrs9tr2Y4xcf8uAdFxbw==
      "dev": true,
      "license": "MIT",
      "dependencies": {
        "@rolldown/pluginutils": "^1.0.1"
      },
      "engines": {
```

```
        "node": "^20.19.0 || >=22.12.0"
      },
      "peerDependencies": {
        "@rolldown/plugin-babel": "^0.1.7 || ^0.2.0",
        "babel-plugin-react-compiler": "^1.0.0",
        "oxc-transform-react": "^0.152.0",
        "vite": "^8.0.0"
      },
      "peerDependenciesMeta": {
        "@rolldown/plugin-babel": {
          "optional": true
        },
        "babel-plugin-react-compiler": {
          "optional": true
        },
        "oxc-transform-react": {
          "optional": true
        }
      }
    },
    "node_modules/aria-hidden": {
      "version": "1.2.6",
      "resolved": "https://registry.npmjs.org/aria-hidden/-/aria-hidden-1.2.6.tgz",
      "integrity": "sha512-ik3ZgC9dY/lYVVM++OISsaYDeg1tb0VtP5uL3ouh1koGOaUMDPpbFIei4JkFimWUFPn90sbMNMXQAIVOlnYKJA==
      "license": "MIT",
      "dependencies": {
        "tslib": "^2.0.0"
      },
      "engines": {
        "node": ">=10"
      }
    },
    "node_modules/class-variance-authority": {
      "version": "0.7.1",
      "resolved": "https://registry.npmjs.org/class-variance-authority/-/class-variance-authority-0.7.1.tgz",
      "integrity": "sha512-Ka+9Trutv7G8M6WT6SeiRWz792K5qEqIGEGzXKhAE6xOWAY6pPH8U+9IY3oCMv6kqTmLsv7Xh/2w2RigkePMsg==
      "license": "Apache-2.0",
      "dependencies": {
        "clsx": "^2.1.1"
      },
      "funding": {
        "url": "https://polar.sh/cva"
      }
    },
    "node_modules/clsx": {
      "version": "2.1.1",
      "resolved": "https://registry.npmjs.org/clsx/-/clsx-2.1.1.tgz",
      "integrity": "sha512-eYm0QWBtUrBWZWG0d386OGAw16Z995PiOVo2B7bjWSbHedGl5e0ZWaq65kOGgUSNesEIDkB9ISbTg/JK9dhCZA==
      "license": "MIT",
      "engines": {
        "node": ">=6"
      }
    },
    "node_modules/csstype": {
      "version": "3.2.3",
      "resolved": "https://registry.npmjs.org/csstype/-/csstype-3.2.3.tgz",
      "integrity": "sha512-z1HGKcYy2xA8AGQfwrn0PAy+PB7X/GSj3UVJW9qKyn43xWa+gl5nXmU4qqLMRzWVLFC8KusUX8T/0kCiOYpAIQ==
      "devOptional": true,
      "license": "MIT"
    },
    "node_modules/detect-libc": {
      "version": "2.1.2",
      "resolved": "https://registry.npmjs.org/detect-libc/-/detect-libc-2.1.2.tgz",
      "integrity": "sha512-Btj2BOOO83o3WyH59e8MgXsxEQVcarkUOpEYrubB0urwnN10yQ364rsiByU11nZlqWYZm05i/of7io4mzihBtQ==
      "dev": true,
      "license": "Apache-2.0",
      "engines": {
        "node": ">=8"
      }
    },
    "node_modules/detect-node-es": {
      "version": "1.1.0",
      "resolved": "https://registry.npmjs.org/detect-node-es/-/detect-node-es-1.1.0.tgz",
      "integrity": "sha512-ypdmJU/TbBby2Dxibuv7ZLW3Bs1QEmM7nHjEANfohJLvE0XVujisn1qPJcZxg+qDucsr+bP6fLD1rPS3AhJ7EQ==
      "license": "MIT"
    },
    "node_modules/enhanced-resolve": {
      "version": "5.26.0",
      "resolved": "https://registry.npmjs.org/enhanced-resolve/-/enhanced-resolve-5.26.0.tgz",
      "integrity": "sha512-9vhedylFonb2YGogzUKX6+Ja72gOJbN1QHAqdrvqLwhdl/QWbKopzoUC9EbQNVsAns/bx/4uyqalrQAoy1IByw==
      "dev": true,
```

```
      "license": "MIT",
      "dependencies": {
        "graceful-fs": "^4.2.4",
        "tapable": "^2.3.3"
      },
      "engines": {
        "node": ">=10.13.0"
      }
    },
    "node_modules/fdir": {
      "version": "6.5.0",
      "resolved": "https://registry.npmjs.org/fdir/-/fdir-6.5.0.tgz",
      "integrity": "sha512-tIbYtZbucOs0BRGqPJkshJUYdL+SDH7dVM8gjy+ERp3WAUjLEFJE+02kanyHtwjWOnwrKYBiwAmM0p4kLJAnXg==",
      "dev": true,
      "license": "MIT",
      "engines": {
        "node": ">=12.0.0"
      },
      "peerDependencies": {
        "picomatch": "^3 || ^4"
      },
      "peerDependenciesMeta": {
        "picomatch": {
          "optional": true
        }
      }
    },
    "node_modules/fsevents": {
      "version": "2.3.3",
      "resolved": "https://registry.npmjs.org/fsevents/-/fsevents-2.3.3.tgz",
      "integrity": "sha512-5xoDfX+fL7faATnagmWPpbFtwh/R77WmMMqqHGS65C3vvB0YHrgF+B1YmZ3441tMj5n63k0212XNoJwzlhffQw==",
      "dev": true,
      "hasInstallScript": true,
      "license": "MIT",
      "optional": true,
      "os": [
        "darwin"
      ],
      "engines": {
        "node": "^8.16.0 || ^10.6.0 || >=11.0.0"
      }
    },
    "node_modules/get-nonce": {
      "version": "1.0.1",
      "resolved": "https://registry.npmjs.org/get-nonce/-/get-nonce-1.0.1.tgz",
      "integrity": "sha512-FJhYRoDaiatfEkUK8HKlicmu/3SGFD51q3itKDGoSTysQJBnfOcxU5GxnhE1E6soB76MbT0MBtnKJuXyAx+96Q==",
      "license": "MIT",
      "engines": {
        "node": ">=6"
      }
    },
    "node_modules/graceful-fs": {
      "version": "4.2.11",
      "resolved": "https://registry.npmjs.org/graceful-fs/-/graceful-fs-4.2.11.tgz",
      "integrity": "sha512-RbJ5/jmFcNNCcDV5o9eTnBLJ/HszWV0P73bc+Ff4nS/rJj+YaS6IGyiOL0VoBYX+l1Wrl3k63h/KrH+nhJ0XvQ==",
      "dev": true,
      "license": "ISC"
    },
    "node_modules/jiti": {
      "version": "2.7.0",
      "resolved": "https://registry.npmjs.org/jiti/-/jiti-2.7.0.tgz",
      "integrity": "sha512-AC/7JofJvZGrrneWNaEnJeOLUx+JlGt7tNa0wZiRPT4MY1wmfKjt2+6O2p2uz2+skll8OZZmJMNqeke7kKbNgQ==",
      "dev": true,
      "license": "MIT",
      "bin": {
        "jiti": "lib/jiti-cli.mjs"
      }
    },
    "node_modules/lightningcss": {
      "version": "1.33.0",
      "resolved": "https://registry.npmjs.org/lightningcss/-/lightningcss-1.33.0.tgz",
      "integrity": "sha512-WkUDrojuJs0xkgGf2udWxa3yGBRxPtxUkB79i6aCZLRgc7PM8fZe9TosfPDcvEpQZbuFASnHYmRLBLUbmLOIIA==",
      "dev": true,
      "license": "MPL-2.0",
      "dependencies": {
        "detect-libc": "^2.0.3"
      },
      "engines": {
        "node": ">= 12.0.0"
      },
      "funding": {
```

```
        "type": "opencollective",
        "url": "https://opencollective.com/parcel"
      },
      "optionalDependencies": {
        "lightningcss-android-arm64": "1.33.0",
        "lightningcss-darwin-arm64": "1.33.0",
        "lightningcss-darwin-x64": "1.33.0",
        "lightningcss-freebsd-x64": "1.33.0",
        "lightningcss-linux-arm-gnueabihf": "1.33.0",
        "lightningcss-linux-arm64-gnu": "1.33.0",
        "lightningcss-linux-arm64-musl": "1.33.0",
        "lightningcss-linux-x64-gnu": "1.33.0",
        "lightningcss-linux-x64-musl": "1.33.0",
        "lightningcss-win32-arm64-msvc": "1.33.0",
        "lightningcss-win32-x64-msvc": "1.33.0"
      }
    },
    "node_modules/lightningcss-android-arm64": {
      "version": "1.33.0",
      "resolved": "https://registry.npmjs.org/lightningcss-android-arm64/-/lightningcss-android-arm64-1.33.0.tgz",
      "integrity": "sha512-gEpRTalKdosp4Bb8qWtc2iOgE5SeIHlpS1up9bFq2wAyYhl1UdTObYiHe98zEM9SQvSoqQZ1IQD0JNpg3Ml5pg==
      "cpu": [
        "arm64"
      ],
      "dev": true,
      "license": "MPL-2.0",
      "optional": true,
      "os": [
        "android"
      ],
      "engines": {
        "node": ">= 12.0.0"
      },
      "funding": {
        "type": "opencollective",
        "url": "https://opencollective.com/parcel"
      }
    },
    "node_modules/lightningcss-darwin-arm64": {
      "version": "1.33.0",
      "resolved": "https://registry.npmjs.org/lightningcss-darwin-arm64/-/lightningcss-darwin-arm64-1.33.0.tgz",
      "integrity": "sha512-Sciaz8eenNTKn9b3t7+xr0ipTp9YxKQY4npwQ3mrRuL0BAVHBLyZxofhaKBAVtzmtRZ/zTyo0/to4B1uWG/Djg==
      "cpu": [
        "arm64"
      ],
      "dev": true,
      "license": "MPL-2.0",
      "optional": true,
      "os": [
        "darwin"
      ],
      "engines": {
        "node": ">= 12.0.0"
      },
      "funding": {
        "type": "opencollective",
        "url": "https://opencollective.com/parcel"
      }
    },
    "node_modules/lightningcss-darwin-x64": {
      "version": "1.33.0",
      "resolved": "https://registry.npmjs.org/lightningcss-darwin-x64/-/lightningcss-darwin-x64-1.33.0.tgz",
      "integrity": "sha512-Z5UPAxzrjlWNNyGy6i65cJzzvgJ5D3T6wMvs+gWpY9d7qRhANrxqAp6LhxIgZhWEw18RfJTGcRxjuLIBr+m8XQ==
      "cpu": [
        "x64"
      ],
      "dev": true,
      "license": "MPL-2.0",
      "optional": true,
      "os": [
        "darwin"
      ],
      "engines": {
        "node": ">= 12.0.0"
      },
      "funding": {
        "type": "opencollective",
        "url": "https://opencollective.com/parcel"
      }
    },
    "node_modules/lightningcss-freebsd-x64": {
```

```
      "version": "1.33.0",
      "resolved": "https://registry.npmjs.org/lightningcss-freebsd-x64/-/lightningcss-freebsd-x64-1.33.0.tgz",
      "integrity": "sha512-QQM/Ti/hQajJwCY+RiWuCZ9sdtI/XQk7nDK5vC8kkdwixezOlDgvDx7+RT+QjK6FcFT4MpsuoBnHIo/O3StRRg==
      "cpu": [
        "x64"
      ],
      "dev": true,
      "license": "MPL-2.0",
      "optional": true,
      "os": [
        "freebsd"
      ],
      "engines": {
        "node": ">= 12.0.0"
      },
      "funding": {
        "type": "opencollective",
        "url": "https://opencollective.com/parcel"
      }
    },
    "node_modules/lightningcss-linux-arm-gnueabihf": {
      "version": "1.33.0",
      "resolved": "https://registry.npmjs.org/lightningcss-linux-arm-gnueabihf/-/lightningcss-linux-arm-gnueabihf-1
      "integrity": "sha512-N7FVBe6iS24MlM6R/4RBTxGhQheZGs7tiQ9U32UtF75NzP5Q7xWPRqLBCKxlRQRk3rY1jCIPLzx7WzOhuUIRLQ==
      "cpu": [
        "arm"
      ],
      "dev": true,
      "license": "MPL-2.0",
      "optional": true,
      "os": [
        "linux"
      ],
      "engines": {
        "node": ">= 12.0.0"
      },
      "funding": {
        "type": "opencollective",
        "url": "https://opencollective.com/parcel"
      }
    },
    "node_modules/lightningcss-linux-arm64-gnu": {
      "version": "1.33.0",
      "resolved": "https://registry.npmjs.org/lightningcss-linux-arm64-gnu/-/lightningcss-linux-arm64-gnu-1.33.0.tg
      "integrity": "sha512-j2v/itmy4HlNxlc6voKXYgBqNi0Ng2LShg4z7GufpEgs05P+2suBVyi9I6YHq5uoVFx9ETin3eCEhLVyXGQnKg==
      "cpu": [
        "arm64"
      ],
      "dev": true,
      "libc": [
        "glibc"
      ],
      "license": "MPL-2.0",
      "optional": true,
      "os": [
        "linux"
      ],
      "engines": {
        "node": ">= 12.0.0"
      },
      "funding": {
        "type": "opencollective",
        "url": "https://opencollective.com/parcel"
      }
    },
    "node_modules/lightningcss-linux-arm64-musl": {
      "version": "1.33.0",
      "resolved": "https://registry.npmjs.org/lightningcss-linux-arm64-musl/-/lightningcss-linux-arm64-musl-1.33.0.
      "integrity": "sha512-yiO5ROMuYQgXbC60yjZU5CYSFZGKXL0HFATXt9mHJn1+zW55oCtMI9NfcVhYLMFDL7gV7oBPon/EmMMGg2OvtQ==
      "cpu": [
        "arm64"
      ],
      "dev": true,
      "libc": [
        "musl"
      ],
      "license": "MPL-2.0",
      "optional": true,
      "os": [
        "linux"
      ],
```

```
    "engines": {
      "node": ">= 12.0.0"
    },
    "funding": {
      "type": "opencollective",
      "url": "https://opencollective.com/parcel"
    }
  },
  "node_modules/lightningcss-linux-x64-gnu": {
    "version": "1.33.0",
    "resolved": "https://registry.npmjs.org/lightningcss-linux-x64-gnu/-/lightningcss-linux-x64-gnu-1.33.0.tgz",
    "integrity": "sha512-ar+Ju7LmcN0Jo4FpL4hpFybwNG9/3A/Br5KW2n2jyODg3MEZXaDYADdemoNS+BDNfMgKvylJLj4S5tyRActuAg==
    "cpu": [
      "x64"
    ],
    "dev": true,
    "libc": [
      "glibc"
    ],
    "license": "MPL-2.0",
    "optional": true,
    "os": [
      "linux"
    ],
    "engines": {
      "node": ">= 12.0.0"
    },
    "funding": {
      "type": "opencollective",
      "url": "https://opencollective.com/parcel"
    }
  },
  "node_modules/lightningcss-linux-x64-musl": {
    "version": "1.33.0",
    "resolved": "https://registry.npmjs.org/lightningcss-linux-x64-musl/-/lightningcss-linux-x64-musl-1.33.0.tgz"
    "integrity": "sha512-RYiYbkokw0trfKqqzfF55lginwEPrD3OJDfTuJzFs1MK6iFnDenaz1fqLLtX4ITG3OktJQXOeTaw1awrBAlZPw==
    "cpu": [
      "x64"
    ],
    "dev": true,
    "libc": [
      "musl"
    ],
    "license": "MPL-2.0",
    "optional": true,
    "os": [
      "linux"
    ],
    "engines": {
      "node": ">= 12.0.0"
    },
    "funding": {
      "type": "opencollective",
      "url": "https://opencollective.com/parcel"
    }
  },
  "node_modules/lightningcss-win32-arm64-msvc": {
    "version": "1.33.0",
    "resolved": "https://registry.npmjs.org/lightningcss-win32-arm64-msvc/-/lightningcss-win32-arm64-msvc-1.33.0.
    "integrity": "sha512-1K+MPfLSFVpphzpdbfkhlWk6wBrTObBzS2T6db10PNOZgR9GoVsAWzwNyuhUYYbTp23j+4RrncfujZ4uAzXvwA==
    "cpu": [
      "arm64"
    ],
    "dev": true,
    "license": "MPL-2.0",
    "optional": true,
    "os": [
      "win32"
    ],
    "engines": {
      "node": ">= 12.0.0"
    },
    "funding": {
      "type": "opencollective",
      "url": "https://opencollective.com/parcel"
    }
  },
  "node_modules/lightningcss-win32-x64-msvc": {
    "version": "1.33.0",
    "resolved": "https://registry.npmjs.org/lightningcss-win32-x64-msvc/-/lightningcss-win32-x64-msvc-1.33.0.tgz"
    "integrity": "sha512-OlEICDx/Xl0FqSp4bry8zFnCvGpig3Gl4gCquvYwHuqJKEC1+n9NgDniFvqHGmMv1ZkqDJrDqKKSykTDX+ehuA==
```

```
    "cpu": [
      "x64"
    ],
    "dev": true,
    "license": "MPL-2.0",
    "optional": true,
    "os": [
      "win32"
    ],
    "engines": {
      "node": ">= 12.0.0"
    },
    "funding": {
      "type": "opencollective",
      "url": "https://opencollective.com/parcel"
    }
  },
  "node_modules/lucide-react": {
    "version": "1.59.0",
    "resolved": "https://registry.npmjs.org/lucide-react/-/lucide-react-1.59.0.tgz",
    "integrity": "sha512-5qgMyyCPU6OvnKpLS2t693+ZtiqA8oaSweWoUows0BLFKFf6V75m4+CptpmohZHpD5IuOVIBXHBBiv2vpLJmtw==
    "license": "ISC",
    "peerDependencies": {
      "@types/react": "*",
      "react": "^16.5.1 || ^17.0.0 || ^18.0.0 || ^19.0.0"
    },
    "peerDependenciesMeta": {
      "@types/react": {
        "optional": true
      }
    }
  },
  "node_modules/magic-string": {
    "version": "0.30.21",
    "resolved": "https://registry.npmjs.org/magic-string/-/magic-string-0.30.21.tgz",
    "integrity": "sha512-vd2F4YUyEXKGcLHoq+TEyCjxueSeHnFxyyjNp80yg0XV4vUhnDer/lvvlqM/arB5bXQN5K2/3oinyCRyx8T2CQ==
    "dev": true,
    "license": "MIT",
    "dependencies": {
      "@jridgewell/sourcemap-codec": "^1.5.5"
    }
  },
  "node_modules/nanoid": {
    "version": "3.3.20",
    "resolved": "https://registry.npmjs.org/nanoid/-/nanoid-3.3.20.tgz",
    "integrity": "sha512-uKdg2G3GNCKQn9byYOpxbGqrT2fGO5KRt5J/8b3pok8rT6qxGWF6hxMyJiEYtAf+FVyYuD9hRaDqX5uPFYJ4ZQ==
    "dev": true,
    "funding": [
      {
        "type": "github",
        "url": "https://github.com/sponsors/ai"
      }
    ],
    "license": "MIT",
    "bin": {
      "nanoid": "bin/nanoid.cjs"
    },
    "engines": {
      "node": "^10 || ^12 || ^13.7 || ^14 || >=15.0.1"
    }
  },
  "node_modules/picocolors": {
    "version": "1.1.1",
    "resolved": "https://registry.npmjs.org/picocolors/-/picocolors-1.1.1.tgz",
    "integrity": "sha512-xceH2snhtb5M9liqDsmEw56le376mTZkEX/jEb/RxNFyegNul7eNslCXP9FDj/Lcu0X8KEyMceP2ntpaHrDEVA==
    "dev": true,
    "license": "ISC"
  },
  "node_modules/picomatch": {
    "version": "4.0.7",
    "resolved": "https://registry.npmjs.org/picomatch/-/picomatch-4.0.7.tgz",
    "integrity": "sha512-qcJu88Q2IWqJsDD529JKMdwGm/dvInW4HvQnRwiH9JtihJvzGOscDtHE3x1pBKeUOTysQ8kVmLnJ2kJu7yhcGA==
    "dev": true,
    "license": "MIT",
    "engines": {
      "node": ">=12"
    },
    "funding": {
      "url": "https://github.com/sponsors/jonschlinkert"
    }
  },
```

```
    "node_modules/postcss": {
      "version": "8.5.30",
      "resolved": "https://registry.npmjs.org/postcss/-/postcss-8.5.30.tgz",
      "integrity": "sha512-zkd+e9S1AQHhmaBKye9zlFHWjOwVgqXl1q3ECYy8561K7qxR2cREf/STLskulBFd78k6AOFeA+ff1TtEzk9bAA==",
      "dev": true,
      "funding": [
        {
          "type": "opencollective",
          "url": "https://opencollective.com/postcss/"
        },
        {
          "type": "tidelift",
          "url": "https://tidelift.com/funding/github/npm/postcss"
        },
        {
          "type": "github",
          "url": "https://github.com/sponsors/ai"
        }
      ],
      "license": "MIT",
      "dependencies": {
        "nanoid": "^3.3.20",
        "picocolors": "^1.1.1",
        "source-map-js": "^1.2.2"
      },
      "engines": {
        "node": "^10 || ^12 || >=14"
      }
    },
    "node_modules/react": {
      "version": "19.3.1",
      "resolved": "https://registry.npmjs.org/react/-/react-19.3.1.tgz",
      "integrity": "sha512-QNhWdt7nrgVWWQG58QuGsAR3jv3Hbe4mb4vz7w2csnHavciZJgda1CPNaldF6eVxv90ud3jUXpKlHL69gO38yw==",
      "license": "MIT",
      "engines": {
        "node": ">=0.10.0"
      }
    },
    "node_modules/react-dom": {
      "version": "19.3.1",
      "resolved": "https://registry.npmjs.org/react-dom/-/react-dom-19.3.1.tgz",
      "integrity": "sha512-Y0bARz53lhEC1NMCASs0/j+faB/zqt3R8hpvg1e8+61ZVJ4UL0UdC4cBbXfZMcIuhrfgeILTLe+ZeBCavQPtKQ==",
      "license": "MIT",
      "dependencies": {
        "scheduler": "^0.28.0"
      },
      "peerDependencies": {
        "react": "^19.3.1"
      }
    },
    "node_modules/react-remove-scroll": {
      "version": "2.7.2",
      "resolved": "https://registry.npmjs.org/react-remove-scroll/-/react-remove-scroll-2.7.2.tgz",
      "integrity": "sha512-Iqb9NjCCTt6Hf+vOdNIZGdTiH1QSqr27H/Ek9sv/a97gfueI/5h1s3yRi1nngzMUaOOToin5dI1dXKdXiF+u0Q==",
      "license": "MIT",
      "dependencies": {
        "react-remove-scroll-bar": "^2.3.7",
        "react-style-singleton": "^2.2.3",
        "tslib": "^2.1.0",
        "use-callback-ref": "^1.3.3",
        "use-sidecar": "^1.1.3"
      },
      "engines": {
        "node": ">=10"
      },
      "peerDependencies": {
        "@types/react": "*",
        "react": "^16.8.0 || ^17.0.0 || ^18.0.0 || ^19.0.0 || ^19.0.0-rc"
      },
      "peerDependenciesMeta": {
        "@types/react": {
          "optional": true
        }
      }
    },
    "node_modules/react-remove-scroll-bar": {
      "version": "2.3.8",
      "resolved": "https://registry.npmjs.org/react-remove-scroll-bar/-/react-remove-scroll-bar-2.3.8.tgz",
      "integrity": "sha512-9r+yi9+mgU33AKcj6IbT9oRCO78WriSj6t/cF8DWBZJ9aOGPOTEDvdUDz1FwKim7QXWwmHqtdHnRJfhAxEG46Q==",
      "license": "MIT",
      "dependencies": {
```

```
        "react-style-singleton": "^2.2.2",
        "tslib": "^2.0.0"
      },
      "engines": {
        "node": ">=10"
      },
      "peerDependencies": {
        "@types/react": "*",
        "react": "^16.8.0 || ^17.0.0 || ^18.0.0 || ^19.0.0"
      },
      "peerDependenciesMeta": {
        "@types/react": {
          "optional": true
        }
      }
    },
    "node_modules/react-style-singleton": {
      "version": "2.2.3",
      "resolved": "https://registry.npmjs.org/react-style-singleton/-/react-style-singleton-2.2.3.tgz",
      "integrity": "sha512-b6jSvxvVnyptAiLjbkWLE/lOnR4lfTtDAl+eUC7RZy+QQWc6wRzIV2CE6xBuMmDxc2qIihtDCZD5NPOFl7fRBQ==
      "license": "MIT",
      "dependencies": {
        "get-nonce": "^1.0.0",
        "tslib": "^2.0.0"
      },
      "engines": {
        "node": ">=10"
      },
      "peerDependencies": {
        "@types/react": "*",
        "react": "^16.8.0 || ^17.0.0 || ^18.0.0 || ^19.0.0 || ^19.0.0-rc"
      },
      "peerDependenciesMeta": {
        "@types/react": {
          "optional": true
        }
      }
    },
    "node_modules/rolldown": {
      "version": "1.2.14",
      "resolved": "https://registry.npmjs.org/rolldown/-/rolldown-1.2.14.tgz",
      "integrity": "sha512-eTBTTqMR6uHKLgcUqpJP8ntzDI6V4LYA8negAMBEI7gkgVvOdrx6VsvS2Ym+83KhOPdLCHWJu0w7UQFJZhHKNw==
      "dev": true,
      "license": "MIT",
      "dependencies": {
        "@oxc-project/types": "=0.154.0",
        "@rolldown/pluginutils": "^1.0.0"
      },
      "bin": {
        "rolldown": "bin/cli.mjs"
      },
      "engines": {
        "node": "^20.19.0 || >=22.12.0"
      },
      "optionalDependencies": {
        "@rolldown/binding-android-arm-eabi": "1.2.14",
        "@rolldown/binding-android-arm64": "1.2.14",
        "@rolldown/binding-darwin-arm64": "1.2.14",
        "@rolldown/binding-darwin-x64": "1.2.14",
        "@rolldown/binding-freebsd-x64": "1.2.14",
        "@rolldown/binding-linux-arm-gnueabihf": "1.2.14",
        "@rolldown/binding-linux-arm64-gnu": "1.2.14",
        "@rolldown/binding-linux-arm64-musl": "1.2.14",
        "@rolldown/binding-linux-ppc64-gnu": "1.2.14",
        "@rolldown/binding-linux-s390x-gnu": "1.2.14",
        "@rolldown/binding-linux-x64-gnu": "1.2.14",
        "@rolldown/binding-linux-x64-musl": "1.2.14",
        "@rolldown/binding-openharmony-arm64": "1.2.14",
        "@rolldown/binding-win32-arm64-msvc": "1.2.14",
        "@rolldown/binding-win32-x64-msvc": "1.2.14"
      }
    },
    "node_modules/scheduler": {
      "version": "0.28.0",
      "resolved": "https://registry.npmjs.org/scheduler/-/scheduler-0.28.0.tgz",
      "integrity": "sha512-juorfCmIkIw8tT+p5BXSm6PJjQF/ycEYmKyzURCIt/RaZIhL+PulbQ9Yu2z1HdOJDdqDTlxA1+xKBmHXJsczAw==
      "license": "MIT"
    },
    "node_modules/source-map-js": {
      "version": "1.2.2",
      "resolved": "https://registry.npmjs.org/source-map-js/-/source-map-js-1.2.2.tgz",
```

```
      "integrity": "sha512-KGj/8Y43x35aZVDtt+J4mK1hoLGHULMYfSkODJNQjNDC3oW1PqPoxMwo0pLUsWM/UEGzON/NxeHywEfNXNP3Vw==",
      "dev": true,
      "license": "BSD-3-Clause",
      "engines": {
        "node": ">=0.10.0"
      }
    },
    "node_modules/tailwind-merge": {
      "version": "2.6.1",
      "resolved": "https://registry.npmjs.org/tailwind-merge/-/tailwind-merge-2.6.1.tgz",
      "integrity": "sha512-Oo6tHdpZsGpkKG88HJ8RR1rg/RdnEkQEfMoEk2x1XRI3F1AxeU+ijRXpiVUF4UbLfcxxRGw6TbUINKYdWVsQTQ==",
      "license": "MIT",
      "funding": {
        "type": "github",
        "url": "https://github.com/sponsors/dcastil"
      }
    },
    "node_modules/tailwindcss": {
      "version": "4.3.3",
      "resolved": "https://registry.npmjs.org/tailwindcss/-/tailwindcss-4.3.3.tgz",
      "integrity": "sha512-gOhV3P7ufE62QDGg1zVaTgCR+EtPv92k2nIhVcVKcLmxT1sUBsQGhnZj175j+MqRt4zLF7ic+sCYjfhxMxj7YQ==",
      "dev": true,
      "license": "MIT"
    },
    "node_modules/tapable": {
      "version": "2.3.3",
      "resolved": "https://registry.npmjs.org/tapable/-/tapable-2.3.3.tgz",
      "integrity": "sha512-uxc/zpqFg6x7C8vOE7lh6Lbda8eEL9zmVm/PLeTPBRhh1xCgdWaQ+J1CUieGpIfm2HdtsUpRv+HshiasBMcc6A==",
      "dev": true,
      "license": "MIT",
      "engines": {
        "node": ">=6"
      },
      "funding": {
        "type": "opencollective",
        "url": "https://opencollective.com/webpack"
      }
    },
    "node_modules/tinyglobby": {
      "version": "0.2.17",
      "resolved": "https://registry.npmjs.org/tinyglobby/-/tinyglobby-0.2.17.tgz",
      "integrity": "sha512-wXR/dYpcqKmfWpEdZjiKJOwCNFndD0DMnrW/cYjVGttEkBfVgcLFHoNrlj47mjOVic9yyNu65alsgF4NQyTa2g==",
      "dev": true,
      "license": "MIT",
      "dependencies": {
        "fdir": "^6.5.0",
        "picomatch": "^4.0.4"
      },
      "engines": {
        "node": ">=12.0.0"
      },
      "funding": {
        "url": "https://github.com/sponsors/SuperchupuDev"
      }
    },
    "node_modules/tslib": {
      "version": "2.8.1",
      "resolved": "https://registry.npmjs.org/tslib/-/tslib-2.8.1.tgz",
      "integrity": "sha512-oJFu94HQb+KVduSUQL7wnpmqnfmLsOA/nAh6b6EH0wCEoK0/mPeXU6c3wKDV83MkOuHPRHtSXKKU99IBazS/2w==",
      "license": "0BSD"
    },
    "node_modules/tw-animate-css": {
      "version": "1.4.0",
      "resolved": "https://registry.npmjs.org/tw-animate-css/-/tw-animate-css-1.4.0.tgz",
      "integrity": "sha512-7bziOlRqH0hJx80h/3mbicLW7o8qLsH5+RaLR2t+OHM3D0JlWGODQKQ4cxbK7WlvmUxpcj6Kgu6EKqjrGFe3QQ==",
      "dev": true,
      "license": "MIT",
      "funding": {
        "url": "https://github.com/sponsors/Wombosvideo"
      }
    },
    "node_modules/typescript": {
      "version": "6.0.3",
      "resolved": "https://registry.npmjs.org/typescript/-/typescript-6.0.3.tgz",
      "integrity": "sha512-y2TvuxSZPDyQakkFRPZHKFm+KKVqIisdg9/CZwm9ftvKXLP8NRWj38/ODjNbr43SsoXqNuAisEf1GdCxqWcdBw==",
      "dev": true,
      "license": "Apache-2.0",
      "bin": {
        "tsc": "bin/tsc",
        "tsserver": "bin/tsserver"
      },
```

```
    "engines": {
      "node": ">=14.17"
    }
  },
  "node_modules/undici-types": {
    "version": "8.9.0",
    "resolved": "https://registry.npmjs.org/undici-types/-/undici-types-8.9.0.tgz",
    "integrity": "sha512-KTDyRTYX8sWmKXAikPHHSyc63CRPETMctyjKFupcC6OBLXT3xsN0e9aF7m+mIXutFWpUXuedtowG7iLOzp0kQg==",
    "license": "MIT"
  },
  "node_modules/use-callback-ref": {
    "version": "1.3.3",
    "resolved": "https://registry.npmjs.org/use-callback-ref/-/use-callback-ref-1.3.3.tgz",
    "integrity": "sha512-jQL3lRnocaFtu3V00JToYz/4QkNWswxijDaCVNZRiRTO3HQDLsdu1ZtmIUvV4yPp+rvWm5j0y0TG/S61cuijTg==",
    "license": "MIT",
    "dependencies": {
      "tslib": "^2.0.0"
    },
    "engines": {
      "node": ">=10"
    },
    "peerDependencies": {
      "@types/react": "*",
      "react": "^16.8.0 || ^17.0.0 || ^18.0.0 || ^19.0.0 || ^19.0.0-rc"
    },
    "peerDependenciesMeta": {
      "@types/react": {
        "optional": true
      }
    }
  },
  "node_modules/use-sidecar": {
    "version": "1.1.3",
    "resolved": "https://registry.npmjs.org/use-sidecar/-/use-sidecar-1.1.3.tgz",
    "integrity": "sha512-Fedw0aZvkhynoPYlA5WXrMCAMm+nSWdZt6lzJQ7Ok8S6Q+VsHmHpRWndVRJ8Be0ZbkfPc5LRYH+5XrzXcEeLRQ==",
    "license": "MIT",
    "dependencies": {
      "detect-node-es": "^1.1.0",
      "tslib": "^2.0.0"
    },
    "engines": {
      "node": ">=10"
    },
    "peerDependencies": {
      "@types/react": "*",
      "react": "^16.8.0 || ^17.0.0 || ^18.0.0 || ^19.0.0 || ^19.0.0-rc"
    },
    "peerDependenciesMeta": {
      "@types/react": {
        "optional": true
      }
    }
  },
  "node_modules/vite": {
    "version": "8.3.4",
    "resolved": "https://registry.npmjs.org/vite/-/vite-8.3.4.tgz",
    "integrity": "sha512-IftLE8phJhdNRIGNEV4JCCvfNScoZQVfcXaN8TQropWGJtOHcu+iAB9pHcuGvmEb/kddw0LBe/jS8ztdC6xdiQ==",
    "dev": true,
    "license": "MIT",
    "dependencies": {
      "lightningcss": "^1.33.0",
      "picomatch": "^4.0.7",
      "postcss": "^8.5.29",
      "rolldown": "~1.2.12",
      "tinyglobby": "^0.2.17"
    },
    "bin": {
      "vite": "bin/vite.js"
    },
    "engines": {
      "node": "^20.19.0 || >=22.12.0"
    },
    "funding": {
      "url": "https://github.com/vitejs/vite?sponsor=1"
    },
    "optionalDependencies": {
      "fsevents": "~2.3.3"
    },
    "peerDependencies": {
      "@types/node": "^20.19.0 || >=22.12.0",
      "@vitejs/devtools": "^0.7.1",
```

```
        "esbuild": "^0.27.0 || ^0.28.0",
        "jiti": ">=1.21.0",
        "less": "^4.0.0",
        "sass": "^1.70.0",
        "sass-embedded": "^1.70.0",
        "stylus": ">=0.54.8",
        "sugarss": "^5.0.0",
        "terser": "^5.16.0",
        "tsx": "^4.8.1",
        "yaml": "^2.4.2"
      },
      "peerDependenciesMeta": {
        "@types/node": {
          "optional": true
        },
        "@vitejs/devtools": {
          "optional": true
        },
        "esbuild": {
          "optional": true
        },
        "jiti": {
          "optional": true
        },
        "less": {
          "optional": true
        },
        "sass": {
          "optional": true
        },
        "sass-embedded": {
          "optional": true
        },
        "stylus": {
          "optional": true
        },
        "sugarss": {
          "optional": true
        },
        "terser": {
          "optional": true
        },
        "tsx": {
          "optional": true
        },
        "yaml": {
          "optional": true
        }
      }
    }
  }
}
```

## package.json

F:\Tools\CodeZipper\package.json

```
{
  "name": "codezipper",
  "private": true,
  "version": "0.1.0",
  "type": "module",
  "scripts": {
    "dev": "vite",
    "build": "tsc && vite build",
    "preview": "vite preview",
    "tauri": "tauri"
  },
  "dependencies": {
    "@radix-ui/react-checkbox": "^1.1.2",
    "@radix-ui/react-dialog": "^1.1.2",
    "@radix-ui/react-slot": "^1.1.0",
    "@radix-ui/react-switch": "^1.1.1",
    "@tauri-apps/api": "^2",
    "@tauri-apps/plugin-dialog": "^2.8.3",
    "@tauri-apps/plugin-opener": "^2",
    "@types/node": "^26.6.5",
    "class-variance-authority": "^0.7.1",
    "clsx": "^2.1.1",
    "lucide-react": "^1.59.0",
    "react": "^19.1.0",
```

```
    "react-dom": "^19.1.0",
    "tailwind-merge": "^2.5.5"
  },
  "devDependencies": {
    "@tailwindcss/vite": "^4.0.0",
    "@tauri-apps/cli": "^2",
    "@types/react": "^19.1.8",
    "@types/react-dom": "^19.1.6",
    "@vitejs/plugin-react": "^6.0.2",
    "tailwindcss": "^4.0.0",
    "tw-animate-css": "^1.2.5",
    "typescript": "~6.0.3",
    "vite": "^8.0.16"
  }
}
```

## README.md

F:\Tools\CodeZipper\README.md

```
# Tauri + React + Typescript

This template should help get you started developing with Tauri, React and Typescript in Vite.

## Recommended IDE Setup

- [VS Code](https://code.visualstudio.com/) + [Tauri](https://marketplace.visualstudio.com/items?itemName=tauri-app
```

## App.tsx

F:\Tools\CodeZipper\src\App.tsx

```
import { TitleBar } from "./components/TitleBar";
import { CodeZipper } from "./pages/CodeZipper";

export default function App() {
  return (
    <div className="flex h-screen w-screen flex-col overflow-hidden bg-background text-foreground">
      <TitleBar />
      <main className="min-h-0 flex-1 overflow-hidden">
        <CodeZipper />
      </main>
    </div>
  );
}
```

## FileTreeTable.tsx

F:\Tools\CodeZipper\src\components\FileTreeTable.tsx

```
import { useMemo, useState } from "react";
import {
    ChevronRight,
    ChevronDown,
    Check,
    Minus,
    File as FileIcon,
    Folder,
    FolderOpen,
} from "lucide-react";
import { cn } from "@/lib/utils";
import { buildTree, collectFiles, flattenTree, type TreeNode } from "@/lib/tree";
import { formatSize, type FileEntry } from "@/types";

type Props = {
    files: FileEntry[];
    selected: Set<string>;
    onSelectionChange: (next: Set<string>) => void;
};

/** Plain-button checkbox — guaranteed to fire onClick, no Radix involved. */
function TreeCheckbox({
    state,
    onToggle,
    label,
}: {
    state: boolean | "indeterminate";
    onToggle: () => void;
    label: string;
}) {
    return (
        <button
```

```
            type="button"
            role="checkbox"
            aria-checked={state === "indeterminate" ? "mixed" : state}
            aria-label={label}
            onClick={(e) => {
                e.preventDefault();
                e.stopPropagation();
                onToggle();
            }}
            className={cn(
                "flex size-4 shrink-0 items-center justify-center rounded-lg border shadow-sm transition-colors out
                "focus-visible:ring-2 focus-visible:ring-ring/50",
                state === false
                    ? "border-input bg-transparent hover:border-ring"
                    : "border-primary bg-primary text-primary-foreground"
            )}
        >
            {state === true && <Check className="size-3" strokeWidth={3} />}
            {state === "indeterminate" && <Minus className="size-3" strokeWidth={3} />}
        </button>
    );
}

export function FileTreeTable({ files, selected, onSelectionChange }: Props) {
    const tree = useMemo(() => buildTree(files), [files]);
    // Empty = all folders expanded by default. We only track what the user CLOSED.
    const [collapsed, setCollapsed] = useState<Set<string>>(new Set());

    const rows = useMemo(() => flattenTree(tree, collapsed), [tree, collapsed]);

    const toggleCollapsed = (path: string) => {
        setCollapsed((prev) => {
            const next = new Set(prev);
            if (next.has(path)) next.delete(path);
            else next.add(path);
            return next;
        });
    };

    const toggleFile = (path: string) => {
        const next = new Set(selected);
        if (next.has(path)) next.delete(path);
        else next.add(path);
        onSelectionChange(next);
    };

    const toggleFolder = (node: TreeNode) => {
        const descendants = collectFiles(node);
        const allSelected =
            descendants.length > 0 && descendants.every((p) => selected.has(p));
        const next = new Set(selected);
        if (allSelected) descendants.forEach((p) => next.delete(p));
        else descendants.forEach((p) => next.add(p));
        onSelectionChange(next);
    };

    const folderState = (node: TreeNode): boolean | "indeterminate" => {
        const descendants = collectFiles(node);
        if (descendants.length === 0) return false;
        const count = descendants.filter((p) => selected.has(p)).length;
        if (count === 0) return false;
        if (count === descendants.length) return true;
        return "indeterminate";
    };

    if (files.length === 0) {
        return (
            <div className="flex h-full flex-col items-center justify-center gap-3 rounded-lg border border-dashed
                <Folder className="size-10 opacity-50" />
                <div className="text-center">
                    <p className="text-sm font-medium text-foreground">No files yet</p>
                    <p className="text-xs">Add files or scan a folder to get started.</p>
                </div>
            </div>
        );
    }

    return (
        <div className="flex h-full flex-col overflow-hidden rounded-lg border bg-card">
            <div className="flex shrink-0 items-center gap-3 border-b bg-muted/40 px-4 py-2 text-xs font-medium upp
                <span className="w-4" />
```

```
                <span className="w-4" />
                <span className="flex-1">Name</span>
                <span className="w-20 text-right">Size</span>
            </div>

            <div className="flex-1 overflow-auto">
                {rows.map((node) => {
                    const indent = node.depth * 16;
                    const hasChildren = node.isFolder && node.children.length > 0;
                    const isOpen = !collapsed.has(node.path);
                    const state: boolean | "indeterminate" = node.isFolder
                        ? folderState(node)
                        : selected.has(node.path);

                    return (
                        <div
                            key={node.path}
                            className={cn(
                                "group flex items-center gap-2 border-b border-border/50 px-4 py-1.5 text-sm transi
                                node.depth % 2 === 1 && "bg-muted/20",
                                "hover:bg-accent/60"
                            )}
                        >
                            <div style={{ paddingLeft: indent }} className="flex items-center">
                                {hasChildren ? (
                                    <button
                                        type="button"
                                        onClick={() => toggleCollapsed(node.path)}
                                        className="grid size-5 place-items-center rounded hover:bg-accent"
                                        tabIndex={-1}
                                    >
                                        {isOpen ? (
                                            <ChevronDown className="size-3.5 text-muted-foreground" />
                                        ) : (
                                            <ChevronRight className="size-3.5 text-muted-foreground" />
                                        )}
                                    </button>
                                ) : (
                                    <span className="size-5" />
                                )}
                            </div>

                            <TreeCheckbox
                                state={state}
                                onToggle={() =>
                                    node.isFolder ? toggleFolder(node) : toggleFile(node.path)
                                }
                                label={`${node.isFolder ? "Folder" : "File"} ${node.name}`}
                            />

                            <div className="flex min-w-0 flex-1 items-center gap-2">
                                {node.isFolder ? (
                                    isOpen ? (
                                        <FolderOpen className="size-4 shrink-0 text-amber-500" />
                                    ) : (
                                        <Folder className="size-4 shrink-0 text-amber-500" />
                                    )
                                ) : (
                                    <FileIcon className="size-4 shrink-0 text-muted-foreground" />
                                )}
                                <span className={cn("truncate", node.isFolder && "font-medium")}>
                                    {node.name}
                                </span>
                            </div>

                            <span className="w-20 shrink-0 text-right text-xs tabular-nums text-muted-foreground">
                                {node.isFolder ? "" : formatSize(node.size)}
                            </span>
                        </div>
                    );
                })}
            </div>
        </div>
    );
}
```

## SettingsDialog.tsx

F:\Tools\CodeZipper\src\components\SettingsDialog.tsx

```tsx
import { RecommendedScanSettings, ScanSettings } from "@/types";
import { invoke } from "@tauri-apps/api/core";
import { RotateCcw, X } from "lucide-react";
import { useEffect, useState } from "react";
import { Dialog, DialogContent, DialogDescription, DialogFooter, DialogHeader, DialogTitle } from "./ui/dialog";
import { Switch } from "./ui/switch";
import { Button } from "./ui/button";

type Props = {
    open: boolean;
    onOpenChange: (open: boolean) => void;
    settings: ScanSettings;
    onSave: (next: ScanSettings) => void;
    onReset: () => void;
};

function normalizeExt(v: string) {
    return v.trim().replace(/^\.+/, "").toLowerCase();
}

function ChipInput({ values, onChange, placeholder, mode, helperText }: {
    values: string[];
    onChange: (next: string[]) => void;
    placeholder?: string;
    mode: "folder" | "extension";
    helperText?: string;
}) {
    const [draft, setDraft] = useState("");

    const commit = (raw: string) => {
        const parts = raw
            .split(/[,\n]/)
            .map((p) => (mode === "extension" ? normalizeExt(p) : p.trim()))
            .filter(Boolean);
        if (parts.length === 0) return;
        const next = [...values];
        for (const p of parts) {
            if (!next.some((v) => v.toLowerCase() === p.toLowerCase())) next.push(p);
        }
        onChange(next);
        setDraft("");
    };

    return (
        <div className="rounded-md border bg-muted/30 p-2">
            <div className="flex flex-wrap items-center gap-1.5">
                {values.map((v) => (
                    <span
                        key={v}
                        className="inline-flex items-center gap-1 rounded-sm bg-secondary px-2 py-0.5 text-xs text-
                    >
                        {v}
                        <button
                            type="button"
                            onClick={() => onChange(values.filter((x) => x !== v))}
                            className="hover:text-destructive"
                        >
                            <X className="size-3" />
                        </button>
                    </span>
                ))}


                <input
                    value={draft}
                    onChange={(e) => setDraft(e.target.value)}
                    onKeyDown={(e) => {
                        if (e.key === "Enter" || e.key === ",") {
                            e.preventDefault();
                            commit(draft);
                        } else if (e.key === "Backspace" && !draft && values.length) {
                            onChange(values.slice(0, -1));
                        }
                    }}
                    onPaste={(e) => {
                        const text = e.clipboardData.getData("text");
                        if (/[,\n]/.test(text)) {
                            e.preventDefault();
```

```
                            commit(text);
                        }
                    }}
                    onBlur={() => draft && commit(draft)}
                    placeholder={values.length === 0 ? placeholder : ""}
                    className="min-w-[140px] flex-1 bg-transparent px-1 py-0.5 text-sm outline-none"
                />
            </div>

            {helperText && (
                <p className="mt-1 px-1 text-[11px] text-muted-foreground">{helperText}</p>
            )}
        </div>
    )
}

export function SettingsDialog({
    open,
    onOpenChange,
    settings,
    onSave,
    onReset
}: Props) {
    const [draft, setDraft] = useState<ScanSettings>(settings);
    const [recommended, setRecommended] = useState<RecommendedScanSettings>({
        folders: [],
        extensions: [],
    });

    useEffect(() => {
        if (open) setDraft(settings);
    }, [open, settings]);

    useEffect(() => {
        invoke<RecommendedScanSettings>("get_recommended_scan_settings")
            .then(setRecommended)
            .catch(() => { });
    }, []);

    return (
        <Dialog open={open} onOpenChange={onOpenChange}>
            <DialogContent className="max-h-[85vh] max-w-2xl overflow-hidden p-0">
                <div className="flex max-h-[85vh] flex-col">
                    <DialogHeader className="border-b px-6 py-4">
                        <DialogTitle>CodeZipper settings</DialogTitle>
                        <DialogDescription>
                            Applied to folder scans. Existing file queue is not affected.
                        </DialogDescription>
                    </DialogHeader>

                    <div className="min-h-0 flex-1 space-y-6 overflow-y-auto px-6 py-4">
                        {/* Excluded folders */}
                        <section className="space-y-3">
                            <div className="flex items-center justify-between">
                                <div>
                                    <h3 className="text-sm font-medium">Excluded folders</h3>
                                    <p className="text-xs text-muted-foreground">
                                        Skipped during directory traversal.
                                    </p>
                                </div>

                                <Switch
                                    checked={draft.useRecommendedFolders}
                                    onCheckedChange={v =>
                                        setDraft(d => ({ ...d, useRecommendedFolders: v }))
                                    }
                                />
                            </div>

                            {draft.useRecommendedFolders && recommended.folders.length > 0 && (
                                <div className="flex flex-wrap gap-1.5 rounded-md border bg-muted/20 p-2">
                                    {recommended.folders.map((f) => (
                                        <span
                                            key={f}
                                            className="rounded-sm bg-secondary px-2 py-0.5 font-mono text-[11px]"
                                        >
                                            {f}
                                        </span>
                                    ))}
                                </div>
                            )}
```

```
                        <ChipInput
                            mode="folder"
                            values={draft.extraExcludedFolders}
                            onChange={(v) =>
                                setDraft((d) => ({ ...d, extraExcludedFolders: v }))
                            }
                            placeholder="Add folder name — e.g. coverage, .terraform"
                            helperText="Press Enter or comma to add. Wildcards like *.egg-info are supported."
                        />
                    </section>

                    {/* Included extensions */}
                    <section className="space-y-3">
                        <div className="flex items-center justify-between">
                            <div>
                                <h3 className="text-sm font-medium">Included file types</h3>
                                <p className="text-xs text-muted-foreground">
                                    Only files with these extensions will be queued.
                                </p>
                            </div>

                            <Switch
                                checked={draft.useRecommendedExtensions}
                                onCheckedChange={(v) =>
                                    setDraft((d) => ({ ...d, useRecommendedExtensions: v }))
                                }
                            />
                        </div>

                        {draft.useRecommendedExtensions && recommended.extensions.length > 0 && (
                            <div className="flex flex-wrap gap-1.5 rounded-md border bg-muted/20 p-2">
                                {recommended.extensions.map((e) => (
                                    <span
                                        key={e}
                                        className="rounded-sm bg-secondary px-2 py-0.5 font-mono text-[11px]"
                                    >
                                        .{e}
                                    </span>
                                ))}
                            </div>
                        )}

                        <ChipInput
                            mode="extension"
                            values={draft.extraIncludedExtensions}
                            onChange={(v) =>
                                setDraft((d) => ({ ...d, extraIncludedExtensions: v }))
                            }
                            placeholder="Add extension — e.g. ex, exs, pas"
                            helperText="Case-insensitive. Leading dots are stripped automatically."
                        />
                    </section>
                </div>

                <DialogFooter className="items-center border-t px-6 py-3 sm:justify-between">
                    <Button
                        variant="ghost"
                        onClick={() =>
                            setDraft({
                                useRecommendedFolders: true,
                                useRecommendedExtensions: true,
                                extraExcludedFolders: [],
                                extraIncludedExtensions: [],
                            })
                        }
                    >
                        <RotateCcw className="size-4" />
                        Reset
                    </Button>

                    <div className="flex gap-2">
                        <Button variant="ghost" onClick={() => onOpenChange(false)}>
                            Cancel
                        </Button>
                        <Button
                            onClick={() => {
                                onSave(draft);
                                onOpenChange(false);
                                onReset; // no-op, kept for API compat
                            }}
```

```
                            >
                                Save
                            </Button>
                        </div>
                    </DialogFooter>
                </div>
            </DialogContent>
        </Dialog>
    )
}
```

## SuccessDialog.tsx

F:\Tools\CodeZipper\src\components\SuccessDialog.tsx

```tsx
import { revealItemInDir } from "@tauri-apps/plugin-opener";
import { Dialog, DialogContent, DialogDescription, DialogFooter, DialogHeader, DialogTitle } from "./ui/dialog";
import { CheckCircle2, FolderOpen } from "lucide-react";
import { Button } from "./ui/button";

type Props = {
    open: boolean;
    onOpenChange: (open: boolean) => void;
    outputPath: string;
};

export function SuccessDialog({ open, onOpenChange, outputPath }: Props) {
    const reveal = async () => {
        try {
            await revealItemInDir(outputPath);
            onOpenChange(false);
        } catch (e) {
            console.error("Failed to reveal output:", e);
        }
    };

    return (
        <Dialog open={open} onOpenChange={onOpenChange}>
            <DialogContent>
                <DialogHeader>
                    <div className="mb-2 flex size-12 items-center justify-center rounded-full bg-primary/10 text-p
                        <CheckCircle2 className="size-6" />
                    </div>
                    <DialogTitle>Export complete</DialogTitle>
                    <DialogDescription className="break-all">{outputPath}</DialogDescription>
                </DialogHeader>
                <DialogFooter>
                    <Button variant="outline" onClick={() => onOpenChange(false)}>
                        Close
                    </Button>
                    <Button onClick={reveal}>
                        <FolderOpen className="size-4" />
                        Go to folder
                    </Button>
                </DialogFooter>
            </DialogContent>
        </Dialog>
    )
}
```

## TitleBar.tsx

F:\Tools\CodeZipper\src\components\TitleBar.tsx

```tsx
import { useTheme } from "@/hooks/useTheme";
import { getCurrentWindow } from "@tauri-apps/api/window"
import { Minus, Monitor, Moon, Square, Sun, X } from "lucide-react";
import { Button } from "./ui/button";

const win = getCurrentWindow();

export function TitleBar() {
    const { mode, cycle } = useTheme();
    const Icon = mode === "light" ? Sun : mode === "dark" ? Moon : Monitor;

    return (
        <header data-tauri-drag-region className="flex h-12 shrink-0 items-center justify-between border-b bg-trans
            <div className="flex items-center gap-2 pl-1">
                <span className="text-sm font-semibold tracking-tight">Code Zipper</span>
            </div>

```

```
            <div className="flex items-center gap-0.5">
                <Button variant="ghost" size="icon" onClick={cycle} className="size-8" title={`Theme: ${mode}`}>
                    <Icon className="size-4" />
                </Button>
                <Button variant="ghost" size="icon" onClick={() => win.minimize()} className="size-8">
                    <Minus className="size-4" />
                </Button>
                <Button variant="ghost" size="icon" onClick={() => win.toggleMaximize()} className="size-8">
                    <Square className="size-3.5" />
                </Button>
                <Button
                    variant="ghost"
                    size="icon"
                    onClick={() => win.close()}
                    className="size-8 text-destructive hover:bg-destructive/10 hover:text-destructive"
                >
                    <X className="size-4" />
                </Button>
            </div>
        </header>
    )
}
```

## button.tsx

F:\Tools\CodeZipper\src\components\ui\button.tsx

```
import * as React from "react";
import { Slot } from "@radix-ui/react-slot";
import { cva, type VariantProps } from "class-variance-authority";
import { cn } from "@/lib/utils";

const buttonVariants = cva(
  "inline-flex items-center justify-center gap-2 whitespace-nowrap rounded-md text-sm font-medium transition-all di
  {
    variants: {
      variant: {
        default: "bg-primary text-primary-foreground shadow-xs hover:bg-primary/90",
        destructive:
          "bg-destructive text-destructive-foreground shadow-xs hover:bg-destructive/90",
        outline:
          "border bg-background shadow-xs hover:bg-accent hover:text-accent-foreground",
        secondary:
          "bg-secondary text-secondary-foreground shadow-xs hover:bg-secondary/80",
        ghost: "hover:bg-accent hover:text-accent-foreground",
        link: "text-primary underline-offset-4 hover:underline",
      },
      size: {
        default: "h-9 px-4 py-2 has-[>svg]:px-3",
        sm: "h-8 rounded-md gap-1.5 px-3 has-[>svg]:px-2.5",
        lg: "h-10 rounded-md px-6",
        icon: "size-9",
      },
    },
    defaultVariants: { variant: "default", size: "default" },
  }
);

function Button({
  className,
  variant,
  size,
  asChild = false,
  ...props
}: React.ComponentProps<"button"> &
  VariantProps<typeof buttonVariants> & { asChild?: boolean }) {
  const Comp = asChild ? Slot : "button";
  return (
    <Comp className={cn(buttonVariants({ variant, size, className }))} {...props} />
  );
}

export { Button, buttonVariants };
```

## checkbox.tsx

F:\Tools\CodeZipper\src\components\ui\checkbox.tsx

```tsx
import * as React from "react";
import * as CheckboxPrimitive from "@radix-ui/react-checkbox";
import { CheckIcon, MinusIcon } from "lucide-react";
import { cn } from "@/lib/utils";

function Checkbox({
  className,
  ...props
}: React.ComponentProps<typeof CheckboxPrimitive.Root>) {
  return (
    <CheckboxPrimitive.Root
      className={cn(
        "peer size-4 shrink-0 rounded-[4px] border shadow-xs transition-shadow outline-none focus-visible:border-ri
        "data-[state=checked]:bg-primary data-[state=checked]:text-primary-foreground data-[state=checked]:border-p
        "data-[state=indeterminate]:bg-primary data-[state=indeterminate]:text-primary-foreground data-[state=indet
        className
      )}
      {...props}
    >
      <CheckboxPrimitive.Indicator className="flex items-center justify-center text-current">
        {props.checked === "indeterminate" ? (
          <MinusIcon className="size-3.5" strokeWidth={3} />
        ) : (
          <CheckIcon className="size-3.5" strokeWidth={3} />
        )}
      </CheckboxPrimitive.Indicator>
    </CheckboxPrimitive.Root>
  );
}

export { Checkbox };
```

## dialog.tsx

F:\Tools\CodeZipper\src\components\ui\dialog.tsx

```tsx
import * as React from "react";
import * as DialogPrimitive from "@radix-ui/react-dialog";
import { XIcon } from "lucide-react";
import { cn } from "@/lib/utils";

const Dialog = DialogPrimitive.Root;
const DialogTrigger = DialogPrimitive.Trigger;
const DialogPortal = DialogPrimitive.Portal;
const DialogClose = DialogPrimitive.Close;

function DialogOverlay({
  className,
  ...props
}: React.ComponentProps<typeof DialogPrimitive.Overlay>) {
  return (
    <DialogPrimitive.Overlay
      className={cn(
        "fixed inset-0 z-50 bg-black/60 backdrop-blur-sm",
        "data-[state=open]:animate-in data-[state=closed]:animate-out",
        "data-[state=closed]:fade-out-0 data-[state=open]:fade-in-0",
        className
      )}
      {...props}
    />
  );
}

function DialogContent({
  className,
  children,
  ...props
}: React.ComponentProps<typeof DialogPrimitive.Content>) {
  return (
    <DialogPortal>
      <DialogOverlay />
      <DialogPrimitive.Content
        className={cn(
          "bg-background fixed top-[50%] left-[50%] z-50 grid w-full max-w-[calc(100%-2rem)] translate-x-[-50%] tra
          "data-[state=open]:animate-in data-[state=closed]:animate-out",
          "data-[state=closed]:fade-out-0 data-[state=open]:fade-in-0",
          "data-[state=closed]:zoom-out-95 data-[state=open]:zoom-in-95",
          className
```

```
        )}
        {...props}
      >
        {children}
        <DialogPrimitive.Close className="ring-offset-background focus:ring-ring absolute top-4 right-4 rounded-xs
          <XIcon className="size-4" />
          <span className="sr-only">Close</span>
        </DialogPrimitive.Close>
      </DialogPrimitive.Content>
    </DialogPortal>
  );
}

function DialogHeader({ className, ...props }: React.ComponentProps<"div">) {
  return <div className={cn("flex flex-col gap-1.5 text-left", className)} {...props} />;
}

function DialogFooter({ className, ...props }: React.ComponentProps<"div">) {
  return (
    <div
      className={cn("flex flex-col-reverse gap-2 sm:flex-row sm:justify-end", className)}
      {...props}
    />
  );
}

function DialogTitle({
  className,
  ...props
}: React.ComponentProps<typeof DialogPrimitive.Title>) {
  return (
    <DialogPrimitive.Title
      className={cn("text-lg leading-none font-semibold", className)}
      {...props}
    />
  );
}

function DialogDescription({
  className,
  ...props
}: React.ComponentProps<typeof DialogPrimitive.Description>) {
  return (
    <DialogPrimitive.Description
      className={cn("text-muted-foreground text-sm", className)}
      {...props}
    />
  );
}

export {
  Dialog,
  DialogClose,
  DialogContent,
  DialogDescription,
  DialogFooter,
  DialogHeader,
  DialogTitle,
  DialogTrigger,
};
```

## input.tsx

F:\Tools\CodeZipper\src\components\ui\input.tsx

```
import * as React from "react";
import { cn } from "@/lib/utils";

function Input({ className, type, ...props }: React.ComponentProps<"input">) {
  return (
    <input
      type={type}
      className={cn(
        "file:text-foreground placeholder:text-muted-foreground selection:bg-primary selection:text-primary-foregro
        "focus-visible:border-ring focus-visible:ring-ring/50 focus-visible:ring-[3px]",
        className
      )}
      {...props}
    />
  );
}
```

```

export { Input };
```

## switch.tsx

F:\Tools\CodeZipper\src\components\ui\switch.tsx

```
import * as React from "react";
import * as SwitchPrimitive from "@radix-ui/react-switch";
import { cn } from "@/lib/utils";

function Switch({
  className,
  ...props
}: React.ComponentProps<typeof SwitchPrimitive.Root>) {
  return (
    <SwitchPrimitive.Root
      className={cn(
        "peer data-[state=checked]:bg-primary data-[state=unchecked]:bg-input focus-visible:ring-ring/50 inline-fle
        className
      )}
      {...props}
    >
      <SwitchPrimitive.Thumb className="bg-background pointer-events-none block size-4 rounded-full shadow-sm ring-
    </SwitchPrimitive.Root>
  );
}

export { Switch };
```

## useSettings.ts

F:\Tools\CodeZipper\src\hooks\useSettings.ts

```
import { DEFAULT_SCAN_SETTINGS, ScanSettings } from "@/types";
import { useEffect, useState } from "react";

const STORAGE_KEY = "codezipper.scanSettings";

function load(): ScanSettings {
    try {
        const raw = localStorage.getItem(STORAGE_KEY);
        if (!raw) return DEFAULT_SCAN_SETTINGS;

        const parsed = JSON.parse(raw) as Partial<ScanSettings>;
        return {...DEFAULT_SCAN_SETTINGS, ...parsed};
    } catch {
        return DEFAULT_SCAN_SETTINGS;
    }
}

export function useSettings() {
    const [settings, setSettings] = useState<ScanSettings>(load);

    useEffect(() => {
        localStorage.setItem(STORAGE_KEY, JSON.stringify(settings));
    }, [settings]);

    const reset = () => setSettings(DEFAULT_SCAN_SETTINGS);
    return {settings, setSettings, reset};
}
```

## useTheme.ts

F:\Tools\CodeZipper\src\hooks\useTheme.ts

```
import { useCallback, useEffect, useState } from "react";


export type ThemeMode = "light" | "dark" | "system"
const STORAGE_KEY = "codezipper.theme";

export function useTheme() {
    const [mode, setMode] = useState<ThemeMode>(() => {
        if (typeof window === "undefined") return "system";
        return (localStorage.getItem(STORAGE_KEY) as ThemeMode | null) ?? "system";
    });

    useEffect(() => {
        const root = document.documentElement;
        const mql = window.matchMedia('(prefers-color-scheme: dark)');

```

```
        const apply = () => {
            const isDark = mode === "dark" || (mode === "system" && mql.matches);
            root.classList.toggle("dark", isDark);
            root.style.colorScheme = isDark ? "dark" : "light";
        }

        apply();
        localStorage.setItem(STORAGE_KEY, mode);

        if (mode === "system") {
            mql.addEventListener("change", apply);
            return () => mql.removeEventListener("change", apply);
        }
    }, [mode]);

    const cycle = useCallback(() => {
        setMode(m => (m === "light" ? "dark" : m === "dark" ? "system" : "light"));
    }, []);

    return { mode, setMode, cycle };
}
```

## index.css

F:\Tools\CodeZipper\src\index.css

```
@import 'tailwindcss';
@import 'tw-animate-css';

@custom-variant dark (&:where(.dark, .dark *));

:root {
  --radius: 0.625rem;
  --background: oklch(1 0 0);
  --foreground: oklch(0.145 0 0);
  --card: oklch(1 0 0);
  --card-foreground: oklch(0.145 0 0);
  --popover: oklch(1 0 0);
  --popover-foreground: oklch(0.145 0 0);
  --primary: oklch(0.205 0 0);
  --primary-foreground: oklch(0.985 0 0);
  --secondary: oklch(0.97 0 0);
  --secondary-foreground: oklch(0.205 0 0);
  --muted: oklch(0.97 0 0);
  --muted-foreground: oklch(0.556 0 0);
  --accent: oklch(0.97 0 0);
  --accent-foreground: oklch(0.205 0 0);
  --destructive: oklch(0.577 0.245 27.325);
  --destructive-foreground: oklch(0.985 0 0);
  --border: oklch(0.922 0 0);
  --input: oklch(0.922 0 0);
  --ring: oklch(0.708 0 0);
}

.dark {
  --background: oklch(14.479% 0.00002 271.152 / 0.63);
  --foreground: oklch(0.985 0 0);
  --card: oklch(0.205 0 0);
  --card-foreground: oklch(0.985 0 0);
  --popover: oklch(0.205 0 0);
  --popover-foreground: oklch(0.985 0 0);
  --primary: oklch(0.922 0 0);
  --primary-foreground: oklch(0.205 0 0);
  --secondary: oklch(0.269 0 0);
  --secondary-foreground: oklch(0.985 0 0);
  --muted: oklch(0.269 0 0);
  --muted-foreground: oklch(0.708 0 0);
  --accent: oklch(0.269 0 0);
  --accent-foreground: oklch(0.985 0 0);
  --destructive: oklch(0.704 0.191 22.216);
  --destructive-foreground: oklch(0.985 0 0);
  --border: oklch(1 0 0 / 10%);
  --input: oklch(1 0 0 / 15%);
  --ring: oklch(0.556 0 0);
}

@theme inline {
  --color-background: var(--background);
  --color-foreground: var(--foreground);
  --color-card: var(--card);
  --color-card-foreground: var(--card-foreground);
```

```
  --color-popover: var(--popover);
  --color-popover-foreground: var(--popover-foreground);
  --color-primary: var(--primary);
  --color-primary-foreground: var(--primary-foreground);
  --color-secondary: var(--secondary);
  --color-secondary-foreground: var(--secondary-foreground);
  --color-muted: var(--muted);
  --color-muted-foreground: var(--muted-foreground);
  --color-accent: var(--accent);
  --color-accent-foreground: var(--accent-foreground);
  --color-destructive: var(--destructive);
  --color-destructive-foreground: var(--destructive-foreground);
  --color-border: var(--border);
  --color-input: var(--input);
  --color-ring: var(--ring);
  --radius-sm: calc(var(--radius) - 4px);
  --radius-md: calc(var(--radius) - 2px);
  --radius-lg: var(--radius);
  --radius-xl: calc(var(--radius) + 4px);
}

@layer base {
  * {
    @apply border-border outline-ring/50;
  }

  html,
  body,
  #root {
    height: 100%;
  }

  body {
    @apply bg-background text-foreground;
    margin: 0;
    overflow: hidden;
    font-family: 'Inter', system-ui, -apple-system, sans-serif;
    -webkit-font-smoothing: antialiased;
  }
}
```

## tree.ts

F:\Tools\CodeZipper\src\lib\tree.ts

```ts
import type { FileEntry } from "@/types";

export type TreeNode = {
    id: string;
    name: string;
    path: string;
    isFolder: boolean;
    size: number;
    depth: number;
    children: TreeNode[];
};

const toPosix = (p: string) => p.replace(/\\/g, "/");

/** Longest common ancestor **directory** of a set of paths. */
export function getCommonRoot(paths: string[]): string {
    if (paths.length === 0) return "";
    const split = paths.map((p) => toPosix(p).split("/"));
    const first = split[0];
    let common = 0;
    for (let i = 0; i < first.length; i++) {
        if (split.every((s) => s[i] === first[i])) common = i + 1;
        else break;
    }
    // Never include the filename in the common root
    if (common === first.length) common -= 1;
    return first.slice(0, common).join("/");
}

export function buildTree(files: FileEntry[]): TreeNode[] {
    if (files.length === 0) return [];

    const common = getCommonRoot(files.map((f) => f.path));
    const folderMap = new Map<string, TreeNode>();
    const roots: TreeNode[] = [];

```

```
    for (const file of files) {
        const norm = toPosix(file.path);
        const rel = norm.substring(common.length).replace(/^\//, "");
        const parts = rel.split("/").filter(Boolean);
        if (parts.length === 0) continue;

        let currentPath = common;
        let level = roots;
        let depth = 0;

        for (let i = 0; i < parts.length; i++) {
            const part = parts[i];
            const isLast = i === parts.length - 1;
            currentPath = currentPath ? `${currentPath}/${part}` : part;

            if (isLast) {
                level.push({
                    id: file.path,        // original path  matches `selected` set
                    name: part,
                    path: file.path,      // original path  matches `selected` set
                    isFolder: false,
                    size: file.size,
                    depth,
                    children: [],
                });
            } else {
                let folder = folderMap.get(currentPath);
                if (!folder) {
                    folder = {
                        id: currentPath,
                        name: part,
                        path: currentPath,  // normalized, only used for expand/collapse
                        isFolder: true,
                        size: 0,
                        depth,
                        children: [],
                    };
                    folderMap.set(currentPath, folder);
                    level.push(folder);
                }
                level = folder.children;
            }
            depth++;
        }
    }

    const sort = (nodes: TreeNode[]) => {
        nodes.sort((a, b) => {
            if (a.isFolder !== b.isFolder) return a.isFolder ? -1 : 1;
            return a.name.localeCompare(b.name);
        });
        nodes.forEach((n) => sort(n.children));
    };
    sort(roots);

    return roots;
}

/** Flatten tree for rendering. `collapsed` is a set of folder paths — empty means all expanded. */
export function flattenTree(nodes: TreeNode[], collapsed: Set<string>): TreeNode[] {
    const out: TreeNode[] = [];
    const walk = (list: TreeNode[]) => {
        for (const n of list) {
            out.push(n);
            if (n.isFolder && !collapsed.has(n.path)) walk(n.children);
        }
    };
    walk(nodes);
    return out;
}

export function collectFiles(node: TreeNode): string[] {
    if (!node.isFolder) return [node.path];
    return node.children.flatMap(collectFiles);
}
```

## utils.ts

F:\Tools\CodeZipper\src\lib\utils.ts

```ts
import { clsx, type ClassValue } from "clsx";
import { twMerge } from "tailwind-merge";

export function cn(...inputs: ClassValue[]) {
    return twMerge(clsx(inputs));
}
```

## main.tsx

F:\Tools\CodeZipper\src\main.tsx

```tsx
import React from "react";
import ReactDOM from "react-dom/client";
import App from "./App";
import "./index.css";

ReactDOM.createRoot(document.getElementById("root") as HTMLElement).render(
  <React.StrictMode>
    <App />
  </React.StrictMode>,
);
```

## CodeZipper.tsx

F:\Tools\CodeZipper\src\pages\CodeZipper.tsx

```tsx
import { invoke } from "@tauri-apps/api/core";
import { open, save } from "@tauri-apps/plugin-dialog";
import { desktopDir, join } from "@tauri-apps/api/path";
import { useCallback, useState } from "react";
import { useSettings } from "@/hooks/useSettings";
import { FileEntry } from "@/types";
import { Button } from "@/components/ui/button";
import { FilePlus2, FolderPlus, Play, Settings2, Trash2 } from "lucide-react";
import { FileTreeTable } from "@/components/FileTreeTable";
import { Input } from "@/components/ui/input";
import { SettingsDialog } from "@/components/SettingsDialog";
import { SuccessDialog } from "@/components/SuccessDialog";

function baseName(p: string): string {
    const parts = p.split(/[/\\]/).filter(Boolean);
    return parts[parts.length - 1] || "";
}

async function suggestOutputPath(sourceName: string): Promise<string> {
    const name = sourceName || "codezipper";
    const now = new Date();
    const pad = (n: number) => String(n).padStart(2, "0");
    const stamp = `${now.getFullYear()}-${pad(now.getMonth() + 1)}-${pad(
        now.getDate()
    )}_${pad(now.getHours())}-${pad(now.getMinutes())}`;
    const file = `${name}_${stamp}.pdf`;
    try {
        const desktop = await desktopDir();
        return await join(desktop, file);
    } catch {
        return file;
    }
}

export function CodeZipper() {
    const [files, setFiles] = useState<FileEntry[]>([]);
    const [selected, setSelected] = useState<Set<string>>(new Set());
    const [sourceName, setSourceName] = useState("");
    const [outputPath, setOutputPath] = useState("");
    const [busy, setBusy] = useState(false);
    const [scanning, setScanning] = useState(false);
    const [error, setError] = useState<string | null>(null);
    const [settingsOpen, setSettingsOpen] = useState(false);
    const [successOpen, setSuccessOpen] = useState(false);

    const { settings, setSettings, reset } = useSettings();

    const mergeFiles = useCallback((incoming: FileEntry[]) => {

        setFiles((prev) => {
            const seen = new Set(prev.map((f) => f.path));
            const merged = [...prev];
```

```
            for (const e of incoming) {
                if (!seen.has(e.path)) {
                    merged.push(e);
                    seen.add(e.path);
                }
            }
            return merged;
        });

        setSelected((prev) => {
            const next = new Set(prev);
            for (const e of incoming) next.add(e.path);
            return next;
        });
    }, []);

    const addFiles = async () => {
        setError(null);
        try {
            const picked = await open({ multiple: true, title: "Select source files" });
            if (!picked) return;
            const paths = Array.isArray(picked) ? picked : [picked];
            const entries: FileEntry[] = [];
            for (const p of paths) {
                const fe = await invoke<FileEntry | null>("file_entry", { path: p });
                if (fe) entries.push(fe);
            }
            mergeFiles(entries);

            if (!sourceName && entries.length > 0) {
                const name = baseName(entries[0].path.replace(/[/\\][^/\\]+$/, ""));
                const finalName = name || "codezipper";
                setSourceName(finalName);
                setOutputPath(await suggestOutputPath(finalName));
            }
        } catch (e) {
            setError(String(e));
        }
    };

    const addFolder = async () => {
        setError(null);
        setScanning(true);
        try {
            const picked = await open({ directory: true, title: "Select source folder" });
            if (!picked || Array.isArray(picked)) return;
            const entries = await invoke<FileEntry[]>("scan_folder", {
                root: picked,
                options: {
                    useRecommendedFolders: settings.useRecommendedFolders,
                    useRecommendedExtensions: settings.useRecommendedExtensions,
                    extraExcludedFolders: settings.extraExcludedFolders,
                    extraIncludedExtensions: settings.extraIncludedExtensions,
                },
            });
            mergeFiles(entries);

            const name = baseName(picked) || "codezipper";
            setSourceName(name);
            setOutputPath(await suggestOutputPath(name));
        } catch (e) {
            setError(String(e));
        } finally {
            setScanning(false);
        }
    };

    const clearAll = () => {
        setFiles([]);
        setSelected(new Set());
        setSourceName("");
        setOutputPath("");
        setError(null);
    };

    const browseOutput = async () => {
        const path = await save({
            title: "Save PDF as",
            defaultPath: outputPath || "codezipper.pdf",
            filters: [{ name: "PDF document", extensions: ["pdf"] }],
        });
```

```
        if (path) setOutputPath(path);
    };

    const runExport = async () => {
        setError(null);
        const toExport = files.filter((f) => selected.has(f.path));
        if (toExport.length === 0) {
            setError("Select at least one file to export.");
            return;
        }
        let target = outputPath.trim();
        if (!target) {
            target = await suggestOutputPath(sourceName || "codezipper");
            setOutputPath(target);
        }
        if (!target.toLowerCase().endsWith(".pdf")) target += ".pdf";

        setBusy(true);
        try {
            await invoke("generate_pdf_cmd", {
                output: target,
                files: toExport.map((f) => f.path),
            });
            setOutputPath(target);
            setSuccessOpen(true);
        } catch (e) {
            setError(String(e));
        } finally {
            setBusy(false);
        }
    };

    const disabled = busy || files.length === 0;

    return (
        <div className="flex h-full flex-col gap-3 p-5">
            {/* Toolbar */}
            <div className="flex items-center gap-2">
                <Button variant="outline" onClick={addFiles} disabled={scanning}>
                    <FilePlus2 className="size-4" />
                    Add files
                </Button>
                <Button variant="outline" onClick={addFolder} disabled={scanning}>
                    <FolderPlus className="size-4" />
                    {scanning ? "Scanning…" : "Add folder"}
                </Button>

                <span className="ml-2 text-xs text-muted-foreground">
                    {selected.size} of {files.length} file{files.length === 1 ? "" : "s"} selected
                </span>

                <div className="ml-auto flex items-center gap-1">
                    <Button
                        variant="ghost"
                        size="icon"
                        onClick={() => setSettingsOpen(true)}
                        title="Scan settings"
                    >
                        <Settings2 className="size-4" />
                    </Button>
                    <Button
                        variant="ghost"
                        size="icon"
                        onClick={clearAll}
                        disabled={files.length === 0}
                        title="Clear queue"
                    >
                        <Trash2 className="size-4" />
                    </Button>
                </div>
            </div>

            {/* File tree */}
            <div className="min-h-0 flex-1">
                <FileTreeTable
                    files={files}
                    selected={selected}
                    onSelectionChange={setSelected}
                />
            </div>

```

```
            {/* Output */}
            <div className="flex items-center gap-2">
                <span className="shrink-0 text-sm font-medium text-muted-foreground">Output</span>
                <Input
                    value={outputPath}
                    onChange={(e) => setOutputPath(e.target.value)}
                    placeholder="Auto-filled from the scanned folder — or click Browse"
                    className="flex-1"
                />
                <Button variant="outline" onClick={browseOutput}>
                    Browse
                </Button>
                <Button onClick={runExport} disabled={disabled}>
                    <Play className="size-4" />
                    {busy ? "Exporting…" : "Export"}
                </Button>
            </div>

            {error && (
                <div className="rounded-md border border-destructive/30 bg-destructive/10 px-3 py-2 text-sm text-de
                    {error}
                </div>
            )}

            <SettingsDialog
                open={settingsOpen}
                onOpenChange={setSettingsOpen}
                settings={settings}
                onSave={setSettings}
                onReset={reset}
            />
            <SuccessDialog
                open={successOpen}
                onOpenChange={setSuccessOpen}
                outputPath={outputPath}
            />
        </div>
    )
}
```

## types.ts

F:\Tools\CodeZipper\src\types.ts

```
export type FileEntry = {
    path: string;
    name: string;
    size: number;
};

export type ScanSettings = {
    useRecommendedFolders: boolean;
    useRecommendedExtensions: boolean;
    extraExcludedFolders: string[];
    extraIncludedExtensions: string[];
};

export type RecommendedScanSettings = {
    folders: string[];
    extensions: string[];
};

export const DEFAULT_SCAN_SETTINGS: ScanSettings = {
    useRecommendedFolders: true,
    useRecommendedExtensions: true,
    extraExcludedFolders: [],
    extraIncludedExtensions: [],
};

export function formatSize(bytes: number): string {
    if (bytes < 1024) return `${bytes} B`;
    if (bytes < 1024 * 1024) return `${(bytes / 1024).toFixed(1)} KB`;
    return `${(bytes / (1024 * 1024)).toFixed(1)} MB`;
}
```

## vite-env.d.ts

F:\Tools\CodeZipper\src\vite-env.d.ts

```
1  /// <reference types="vite/client" />
```

## build.rs

F:\Tools\CodeZipper\src-tauri\build.rs

```
1  fn main() {
2      tauri_build::build()
3  }
```

## default.json

F:\Tools\CodeZipper\src-tauri\capabilities\default.json

```
1  {
2    "$schema": "../gen/schemas/desktop-schema.json",
3    "identifier": "default",
4    "description": "Capability for the main window",
5    "windows": ["main"],
6    "permissions": [
7      "core:default",
8      "opener:default",
9      "core:window:allow-start-dragging",
10     "core:window:allow-minimize",
11     "core:window:allow-toggle-maximize",
12     "core:window:allow-close",
13     "core:window:allow-is-maximized",
14     "dialog:default",
15     "dialog:allow-open",
16     "dialog:allow-save"
17   ]
18 }
```

## Cargo.toml

F:\Tools\CodeZipper\src-tauri\Cargo.toml

```
1  [package]
2  name = "codezipper"
3  version = "0.1.0"
4  description = "A Tauri App"
5  authors = ["you"]
6  edition = "2024"
7
8  # See more keys and their definitions at https://doc.rust-lang.org/cargo/reference/manifest.html
9
10 [lib]
11 # The `_lib` suffix may seem redundant but it is necessary
12 # to make the lib name unique and wouldn't conflict with the bin name.
13 # This seems to be only an issue on Windows, see https://github.com/rust-lang/cargo/issues/8519
14 name = "codezipper_lib"
15 crate-type = ["staticlib", "cdylib", "rlib"]
16
17 [build-dependencies]
18 tauri-build = { version = "2", features = [] }
19
20 [dependencies]
21 tauri = { version = "2", features = [] }
22 tauri-plugin-opener = "2"
23 tauri-plugin-dialog = "2"
24 serde = { version = "1", features = ["derive"] }
25 serde_json = "1"
26 walkdir = "2"
27 printpdf = "0.7"
28
29
30 # Read the optimization guideline for more details: https://tauri.app/concept/size/#cargo-configuration
31 [profile.release]
32 codegen-units = 1
33 lto = true
34 opt-level = 3
35 panic = "abort"
36 strip = true
```

## acl-manifests.json

F:\Tools\CodeZipper\src-tauri\gen\schemas\acl-manifests.json

```
{"core":{"default_permission":{"identifier":"default","description":"Default core plugins set.","permissions":["cor
```

## capabilities.json

F:\Tools\CodeZipper\src-tauri\gen\schemas\capabilities.json

```
{"default":{"identifier":"default","description":"Capability for the main window","local":true,"windows":["main"],"
```

## desktop-schema.json

F:\Tools\CodeZipper\src-tauri\gen\schemas\desktop-schema.json

```
{
  "$schema": "http://json-schema.org/draft-07/schema#",
  "title": "CapabilityFile",
  "description": "Capability formats accepted in a capability file.",
  "anyOf": [
    {
      "description": "A single capability.",
      "allOf": [
        {
          "$ref": "#/definitions/Capability"
        }
      ]
    },
    {
      "description": "A list of capabilities.",
      "type": "array",
      "items": {
        "$ref": "#/definitions/Capability"
      }
    },
    {
      "description": "A list of capabilities.",
      "type": "object",
      "required": [
        "capabilities"
      ],
      "properties": {
        "capabilities": {
          "description": "The list of capabilities.",
          "type": "array",
          "items": {
            "$ref": "#/definitions/Capability"
          }
        }
      }
    }
  ],
  "definitions": {
    "Capability": {
      "description": "A grouping and boundary mechanism developers can use to isolate access to the IPC layer.\n\nI
      "type": "object",
      "required": [
        "identifier",
        "permissions"
      ],
      "properties": {
        "identifier": {
          "description": "Identifier of the capability.\n\n## Example\n\n`main-user-files-write`",
          "type": "string"
        },
        "description": {
          "description": "Description of what the capability is intended to allow on associated windows.\n\nIt shou
          "default": "",
          "type": "string"
        },
        "remote": {
          "description": "Configure remote URLs that can use the capability permissions.\n\nThis setting is optiona
          "anyOf": [
            {
              "$ref": "#/definitions/CapabilityRemote"
            },
            {
              "type": "null"
            }
          ]
        },
```

```
        "local": {
          "description": "Whether this capability is enabled for local app URLs or not. Defaults to `true`.",
          "default": true,
          "type": "boolean"
        },
        "windows": {
          "description": "List of windows that are affected by this capability. Can be a glob pattern.\n\nIf a wind
          "type": "array",
          "items": {
            "type": "string"
          }
        },
        "webviews": {
          "description": "List of webviews that are affected by this capability. Can be a glob pattern.\n\nThe capa
          "type": "array",
          "items": {
            "type": "string"
          }
        },
        "permissions": {
          "description": "List of permissions attached to this capability.\n\nMust include the plugin name as prefi
          "type": "array",
          "items": {
            "$ref": "#/definitions/PermissionEntry"
          },
          "uniqueItems": true
        },
        "platforms": {
          "description": "Limit which target platforms this capability applies to.\n\nBy default all platforms are
          "type": [
            "array",
            "null"
          ],
          "items": {
            "$ref": "#/definitions/Target"
          }
        }
      }
    },
    "CapabilityRemote": {
      "description": "Configuration for remote URLs that are associated with the capability.",
      "type": "object",
      "required": [
        "urls"
      ],
      "properties": {
        "urls": {
          "description": "Remote domains this capability refers to using the [URLPattern standard](https://urlpatte
          "type": "array",
          "items": {
            "type": "string"
          }
        }
      }
    },
    "PermissionEntry": {
      "description": "An entry for a permission value in a [`Capability`] can be either a raw permission [`Identifi
      "anyOf": [
        {
          "description": "Reference a permission or permission set by identifier.",
          "allOf": [
            {
              "$ref": "#/definitions/Identifier"
            }
          ]
        },
        {
          "description": "Reference a permission or permission set by identifier and extends its scope.",
          "type": "object",
          "allOf": [
            {
              "if": {
                "properties": {
                  "identifier": {
                    "anyOf": [
                      {
                        "description": "This permission set allows opening `mailto:`, `tel:`, `https://` and `http:
                        "type": "string",
                        "const": "opener:default",
                        "markdownDescription": "This permission set allows opening `mailto:`, `tel:`, `https://` an
                      },
```

```
                    {
                      "description": "This enables opening `mailto:`, `tel:`, `https://` and `http://` urls using
                      "type": "string",
                      "const": "opener:allow-default-urls",
                      "markdownDescription": "This enables opening `mailto:`, `tel:`, `https://` and `http://` ur
                    },
                    {
                      "description": "Enables the open_path command without any pre-configured scope.",
                      "type": "string",
                      "const": "opener:allow-open-path",
                      "markdownDescription": "Enables the open_path command without any pre-configured scope."
                    },
                    {
                      "description": "Enables the open_url command without any pre-configured scope.",
                      "type": "string",
                      "const": "opener:allow-open-url",
                      "markdownDescription": "Enables the open_url command without any pre-configured scope."
                    },
                    {
                      "description": "Enables the reveal_item_in_dir command without any pre-configured scope.",
                      "type": "string",
                      "const": "opener:allow-reveal-item-in-dir",
                      "markdownDescription": "Enables the reveal_item_in_dir command without any pre-configured s
                    },
                    {
                      "description": "Denies the open_path command without any pre-configured scope.",
                      "type": "string",
                      "const": "opener:deny-open-path",
                      "markdownDescription": "Denies the open_path command without any pre-configured scope."
                    },
                    {
                      "description": "Denies the open_url command without any pre-configured scope.",
                      "type": "string",
                      "const": "opener:deny-open-url",
                      "markdownDescription": "Denies the open_url command without any pre-configured scope."
                    },
                    {
                      "description": "Denies the reveal_item_in_dir command without any pre-configured scope.",
                      "type": "string",
                      "const": "opener:deny-reveal-item-in-dir",
                      "markdownDescription": "Denies the reveal_item_in_dir command without any pre-configured sc
                    }
                  ]
                }
              }
            },
            "then": {
              "properties": {
                "allow": {
                  "items": {
                    "title": "OpenerScopeEntry",
                    "description": "Opener scope entry.",
                    "anyOf": [
                      {
                        "type": "object",
                        "required": [
                          "url"
                        ],
                        "properties": {
                          "app": {
                            "description": "An application to open this url with, for example: firefox.",
                            "allOf": [
                              {
                                "$ref": "#/definitions/Application"
                              }
                            ]
                          },
                          "url": {
                            "description": "A URL that can be opened by the webview when using the Opener APIs.\n
                            "type": "string"
                          }
                        }
                      },
                      {
                        "type": "object",
                        "required": [
                          "path"
                        ],
                        "properties": {
                          "app": {
                            "description": "An application to open this path with, for example: xdg-open.",
```

```
                            "allOf": [
                              {
                                "$ref": "#/definitions/Application"
                              }
                            ]
                          },
                          "path": {
                            "description": "A path that can be opened by the webview when using the Opener APIs.\
                            "type": "string"
                          }
                        }
                      }
                    ]
                  }
                },
                "deny": {
                  "items": {
                    "title": "OpenerScopeEntry",
                    "description": "Opener scope entry.",
                    "anyOf": [
                      {
                        "type": "object",
                        "required": [
                          "url"
                        ],
                        "properties": {
                          "app": {
                            "description": "An application to open this url with, for example: firefox.",
                            "allOf": [
                              {
                                "$ref": "#/definitions/Application"
                              }
                            ]
                          },
                          "url": {
                            "description": "A URL that can be opened by the webview when using the Opener APIs.\n
                            "type": "string"
                          }
                        }
                      },
                      {
                        "type": "object",
                        "required": [
                          "path"
                        ],
                        "properties": {
                          "app": {
                            "description": "An application to open this path with, for example: xdg-open.",
                            "allOf": [
                              {
                                "$ref": "#/definitions/Application"
                              }
                            ]
                          },
                          "path": {
                            "description": "A path that can be opened by the webview when using the Opener APIs.\
                            "type": "string"
                          }
                        }
                      }
                    ]
                  }
                }
              }
            },
            "properties": {
              "identifier": {
                "description": "Identifier of the permission or permission set.",
                "allOf": [
                  {
                    "$ref": "#/definitions/Identifier"
                  }
                ]
              }
            }
          },
          {
            "properties": {
              "identifier": {
                "description": "Identifier of the permission or permission set.",
                "allOf": [
```

```
                    {
                      "$ref": "#/definitions/Identifier"
                    }
                  ]
                },
                "allow": {
                  "description": "Data that defines what is allowed by the scope.",
                  "type": [
                    "array",
                    "null"
                  ],
                  "items": {
                    "$ref": "#/definitions/Value"
                  }
                },
                "deny": {
                  "description": "Data that defines what is denied by the scope. This should be prioritized by vali
                  "type": [
                    "array",
                    "null"
                  ],
                  "items": {
                    "$ref": "#/definitions/Value"
                  }
                }
              }
            }
          ],
          "required": [
            "identifier"
          ]
        }
      ]
    },
    "Identifier": {
      "description": "Permission identifier",
      "oneOf": [
        {
          "description": "Default core plugins set.\n#### This default permission set includes:\n\n- `core:path:def
          "type": "string",
          "const": "core:default",
          "markdownDescription": "Default core plugins set.\n#### This default permission set includes:\n\n- `core:
        },
        {
          "description": "Default permissions for the plugin.\n#### This default permission set includes:\n\n- `all
          "type": "string",
          "const": "core:app:default",
          "markdownDescription": "Default permissions for the plugin.\n#### This default permission set includes:\n
        },
        {
          "description": "Enables the app_hide command without any pre-configured scope.",
          "type": "string",
          "const": "core:app:allow-app-hide",
          "markdownDescription": "Enables the app_hide command without any pre-configured scope."
        },
        {
          "description": "Enables the app_show command without any pre-configured scope.",
          "type": "string",
          "const": "core:app:allow-app-show",
          "markdownDescription": "Enables the app_show command without any pre-configured scope."
        },
        {
          "description": "Enables the bundle_type command without any pre-configured scope.",
          "type": "string",
          "const": "core:app:allow-bundle-type",
          "markdownDescription": "Enables the bundle_type command without any pre-configured scope."
        },
        {
          "description": "Enables the default_window_icon command without any pre-configured scope.",
          "type": "string",
          "const": "core:app:allow-default-window-icon",
          "markdownDescription": "Enables the default_window_icon command without any pre-configured scope."
        },
        {
          "description": "Enables the exit command without any pre-configured scope.",
          "type": "string",
          "const": "core:app:allow-exit",
          "markdownDescription": "Enables the exit command without any pre-configured scope."
        },
        {
          "description": "Enables the fetch_data_store_identifiers command without any pre-configured scope.",
```

```
      "type": "string",
      "const": "core:app:allow-fetch-data-store-identifiers",
      "markdownDescription": "Enables the fetch_data_store_identifiers command without any pre-configured scope"
    },
    {
      "description": "Enables the identifier command without any pre-configured scope.",
      "type": "string",
      "const": "core:app:allow-identifier",
      "markdownDescription": "Enables the identifier command without any pre-configured scope."
    },
    {
      "description": "Enables the name command without any pre-configured scope.",
      "type": "string",
      "const": "core:app:allow-name",
      "markdownDescription": "Enables the name command without any pre-configured scope."
    },
    {
      "description": "Enables the register_listener command without any pre-configured scope.",
      "type": "string",
      "const": "core:app:allow-register-listener",
      "markdownDescription": "Enables the register_listener command without any pre-configured scope."
    },
    {
      "description": "Enables the remove_data_store command without any pre-configured scope.",
      "type": "string",
      "const": "core:app:allow-remove-data-store",
      "markdownDescription": "Enables the remove_data_store command without any pre-configured scope."
    },
    {
      "description": "Enables the remove_listener command without any pre-configured scope.",
      "type": "string",
      "const": "core:app:allow-remove-listener",
      "markdownDescription": "Enables the remove_listener command without any pre-configured scope."
    },
    {
      "description": "Enables the set_app_theme command without any pre-configured scope.",
      "type": "string",
      "const": "core:app:allow-set-app-theme",
      "markdownDescription": "Enables the set_app_theme command without any pre-configured scope."
    },
    {
      "description": "Enables the set_dock_visibility command without any pre-configured scope.",
      "type": "string",
      "const": "core:app:allow-set-dock-visibility",
      "markdownDescription": "Enables the set_dock_visibility command without any pre-configured scope."
    },
    {
      "description": "Enables the supports_multiple_windows command without any pre-configured scope.",
      "type": "string",
      "const": "core:app:allow-supports-multiple-windows",
      "markdownDescription": "Enables the supports_multiple_windows command without any pre-configured scope."
    },
    {
      "description": "Enables the tauri_version command without any pre-configured scope.",
      "type": "string",
      "const": "core:app:allow-tauri-version",
      "markdownDescription": "Enables the tauri_version command without any pre-configured scope."
    },
    {
      "description": "Enables the version command without any pre-configured scope.",
      "type": "string",
      "const": "core:app:allow-version",
      "markdownDescription": "Enables the version command without any pre-configured scope."
    },
    {
      "description": "Denies the app_hide command without any pre-configured scope.",
      "type": "string",
      "const": "core:app:deny-app-hide",
      "markdownDescription": "Denies the app_hide command without any pre-configured scope."
    },
    {
      "description": "Denies the app_show command without any pre-configured scope.",
      "type": "string",
      "const": "core:app:deny-app-show",
      "markdownDescription": "Denies the app_show command without any pre-configured scope."
    },
    {
      "description": "Denies the bundle_type command without any pre-configured scope.",
      "type": "string",
      "const": "core:app:deny-bundle-type",
      "markdownDescription": "Denies the bundle_type command without any pre-configured scope."
```

```
        },
        {
          "description": "Denies the default_window_icon command without any pre-configured scope.",
          "type": "string",
          "const": "core:app:deny-default-window-icon",
          "markdownDescription": "Denies the default_window_icon command without any pre-configured scope."
        },
        {
          "description": "Denies the exit command without any pre-configured scope.",
          "type": "string",
          "const": "core:app:deny-exit",
          "markdownDescription": "Denies the exit command without any pre-configured scope."
        },
        {
          "description": "Denies the fetch_data_store_identifiers command without any pre-configured scope.",
          "type": "string",
          "const": "core:app:deny-fetch-data-store-identifiers",
          "markdownDescription": "Denies the fetch_data_store_identifiers command without any pre-configured scope.
        },
        {
          "description": "Denies the identifier command without any pre-configured scope.",
          "type": "string",
          "const": "core:app:deny-identifier",
          "markdownDescription": "Denies the identifier command without any pre-configured scope."
        },
        {
          "description": "Denies the name command without any pre-configured scope.",
          "type": "string",
          "const": "core:app:deny-name",
          "markdownDescription": "Denies the name command without any pre-configured scope."
        },
        {
          "description": "Denies the register_listener command without any pre-configured scope.",
          "type": "string",
          "const": "core:app:deny-register-listener",
          "markdownDescription": "Denies the register_listener command without any pre-configured scope."
        },
        {
          "description": "Denies the remove_data_store command without any pre-configured scope.",
          "type": "string",
          "const": "core:app:deny-remove-data-store",
          "markdownDescription": "Denies the remove_data_store command without any pre-configured scope."
        },
        {
          "description": "Denies the remove_listener command without any pre-configured scope.",
          "type": "string",
          "const": "core:app:deny-remove-listener",
          "markdownDescription": "Denies the remove_listener command without any pre-configured scope."
        },
        {
          "description": "Denies the set_app_theme command without any pre-configured scope.",
          "type": "string",
          "const": "core:app:deny-set-app-theme",
          "markdownDescription": "Denies the set_app_theme command without any pre-configured scope."
        },
        {
          "description": "Denies the set_dock_visibility command without any pre-configured scope.",
          "type": "string",
          "const": "core:app:deny-set-dock-visibility",
          "markdownDescription": "Denies the set_dock_visibility command without any pre-configured scope."
        },
        {
          "description": "Denies the supports_multiple_windows command without any pre-configured scope.",
          "type": "string",
          "const": "core:app:deny-supports-multiple-windows",
          "markdownDescription": "Denies the supports_multiple_windows command without any pre-configured scope."
        },
        {
          "description": "Denies the tauri_version command without any pre-configured scope.",
          "type": "string",
          "const": "core:app:deny-tauri-version",
          "markdownDescription": "Denies the tauri_version command without any pre-configured scope."
        },
        {
          "description": "Denies the version command without any pre-configured scope.",
          "type": "string",
          "const": "core:app:deny-version",
          "markdownDescription": "Denies the version command without any pre-configured scope."
        },
        {
          "description": "Default permissions for the plugin, which enables all commands.\n#### This default permis
```

```
      "type": "string",
      "const": "core:event:default",
      "markdownDescription": "Default permissions for the plugin, which enables all commands.\n#### This defaul
    },
    {
      "description": "Enables the emit command without any pre-configured scope.",
      "type": "string",
      "const": "core:event:allow-emit",
      "markdownDescription": "Enables the emit command without any pre-configured scope."
    },
    {
      "description": "Enables the emit_to command without any pre-configured scope.",
      "type": "string",
      "const": "core:event:allow-emit-to",
      "markdownDescription": "Enables the emit_to command without any pre-configured scope."
    },
    {
      "description": "Enables the listen command without any pre-configured scope.",
      "type": "string",
      "const": "core:event:allow-listen",
      "markdownDescription": "Enables the listen command without any pre-configured scope."
    },
    {
      "description": "Enables the unlisten command without any pre-configured scope.",
      "type": "string",
      "const": "core:event:allow-unlisten",
      "markdownDescription": "Enables the unlisten command without any pre-configured scope."
    },
    {
      "description": "Denies the emit command without any pre-configured scope.",
      "type": "string",
      "const": "core:event:deny-emit",
      "markdownDescription": "Denies the emit command without any pre-configured scope."
    },
    {
      "description": "Denies the emit_to command without any pre-configured scope.",
      "type": "string",
      "const": "core:event:deny-emit-to",
      "markdownDescription": "Denies the emit_to command without any pre-configured scope."
    },
    {
      "description": "Denies the listen command without any pre-configured scope.",
      "type": "string",
      "const": "core:event:deny-listen",
      "markdownDescription": "Denies the listen command without any pre-configured scope."
    },
    {
      "description": "Denies the unlisten command without any pre-configured scope.",
      "type": "string",
      "const": "core:event:deny-unlisten",
      "markdownDescription": "Denies the unlisten command without any pre-configured scope."
    },
    {
      "description": "Default permissions for the plugin, which enables all commands.\n#### This default permis
      "type": "string",
      "const": "core:image:default",
      "markdownDescription": "Default permissions for the plugin, which enables all commands.\n#### This defaul
    },
    {
      "description": "Enables the from_bytes command without any pre-configured scope.",
      "type": "string",
      "const": "core:image:allow-from-bytes",
      "markdownDescription": "Enables the from_bytes command without any pre-configured scope."
    },
    {
      "description": "Enables the from_path command without any pre-configured scope.",
      "type": "string",
      "const": "core:image:allow-from-path",
      "markdownDescription": "Enables the from_path command without any pre-configured scope."
    },
    {
      "description": "Enables the new command without any pre-configured scope.",
      "type": "string",
      "const": "core:image:allow-new",
      "markdownDescription": "Enables the new command without any pre-configured scope."
    },
    {
      "description": "Enables the rgba command without any pre-configured scope.",
      "type": "string",
      "const": "core:image:allow-rgba",
      "markdownDescription": "Enables the rgba command without any pre-configured scope."
```

```
        },
        {
          "description": "Enables the size command without any pre-configured scope.",
          "type": "string",
          "const": "core:image:allow-size",
          "markdownDescription": "Enables the size command without any pre-configured scope."
        },
        {
          "description": "Denies the from_bytes command without any pre-configured scope.",
          "type": "string",
          "const": "core:image:deny-from-bytes",
          "markdownDescription": "Denies the from_bytes command without any pre-configured scope."
        },
        {
          "description": "Denies the from_path command without any pre-configured scope.",
          "type": "string",
          "const": "core:image:deny-from-path",
          "markdownDescription": "Denies the from_path command without any pre-configured scope."
        },
        {
          "description": "Denies the new command without any pre-configured scope.",
          "type": "string",
          "const": "core:image:deny-new",
          "markdownDescription": "Denies the new command without any pre-configured scope."
        },
        {
          "description": "Denies the rgba command without any pre-configured scope.",
          "type": "string",
          "const": "core:image:deny-rgba",
          "markdownDescription": "Denies the rgba command without any pre-configured scope."
        },
        {
          "description": "Denies the size command without any pre-configured scope.",
          "type": "string",
          "const": "core:image:deny-size",
          "markdownDescription": "Denies the size command without any pre-configured scope."
        },
        {
          "description": "Default permissions for the plugin, which enables all commands.\n#### This default permis
          "type": "string",
          "const": "core:menu:default",
          "markdownDescription": "Default permissions for the plugin, which enables all commands.\n#### This defaul
        },
        {
          "description": "Enables the append command without any pre-configured scope.",
          "type": "string",
          "const": "core:menu:allow-append",
          "markdownDescription": "Enables the append command without any pre-configured scope."
        },
        {
          "description": "Enables the create_default command without any pre-configured scope.",
          "type": "string",
          "const": "core:menu:allow-create-default",
          "markdownDescription": "Enables the create_default command without any pre-configured scope."
        },
        {
          "description": "Enables the get command without any pre-configured scope.",
          "type": "string",
          "const": "core:menu:allow-get",
          "markdownDescription": "Enables the get command without any pre-configured scope."
        },
        {
          "description": "Enables the insert command without any pre-configured scope.",
          "type": "string",
          "const": "core:menu:allow-insert",
          "markdownDescription": "Enables the insert command without any pre-configured scope."
        },
        {
          "description": "Enables the is_checked command without any pre-configured scope.",
          "type": "string",
          "const": "core:menu:allow-is-checked",
          "markdownDescription": "Enables the is_checked command without any pre-configured scope."
        },
        {
          "description": "Enables the is_enabled command without any pre-configured scope.",
          "type": "string",
          "const": "core:menu:allow-is-enabled",
          "markdownDescription": "Enables the is_enabled command without any pre-configured scope."
        },
        {
          "description": "Enables the items command without any pre-configured scope.",
```

```
        "type": "string",
        "const": "core:menu:allow-items",
        "markdownDescription": "Enables the items command without any pre-configured scope."
      },
      {
        "description": "Enables the new command without any pre-configured scope.",
        "type": "string",
        "const": "core:menu:allow-new",
        "markdownDescription": "Enables the new command without any pre-configured scope."
      },
      {
        "description": "Enables the popup command without any pre-configured scope.",
        "type": "string",
        "const": "core:menu:allow-popup",
        "markdownDescription": "Enables the popup command without any pre-configured scope."
      },
      {
        "description": "Enables the prepend command without any pre-configured scope.",
        "type": "string",
        "const": "core:menu:allow-prepend",
        "markdownDescription": "Enables the prepend command without any pre-configured scope."
      },
      {
        "description": "Enables the remove command without any pre-configured scope.",
        "type": "string",
        "const": "core:menu:allow-remove",
        "markdownDescription": "Enables the remove command without any pre-configured scope."
      },
      {
        "description": "Enables the remove_at command without any pre-configured scope.",
        "type": "string",
        "const": "core:menu:allow-remove-at",
        "markdownDescription": "Enables the remove_at command without any pre-configured scope."
      },
      {
        "description": "Enables the set_accelerator command without any pre-configured scope.",
        "type": "string",
        "const": "core:menu:allow-set-accelerator",
        "markdownDescription": "Enables the set_accelerator command without any pre-configured scope."
      },
      {
        "description": "Enables the set_as_app_menu command without any pre-configured scope.",
        "type": "string",
        "const": "core:menu:allow-set-as-app-menu",
        "markdownDescription": "Enables the set_as_app_menu command without any pre-configured scope."
      },
      {
        "description": "Enables the set_as_help_menu_for_nsapp command without any pre-configured scope.",
        "type": "string",
        "const": "core:menu:allow-set-as-help-menu-for-nsapp",
        "markdownDescription": "Enables the set_as_help_menu_for_nsapp command without any pre-configured scope."
      },
      {
        "description": "Enables the set_as_window_menu command without any pre-configured scope.",
        "type": "string",
        "const": "core:menu:allow-set-as-window-menu",
        "markdownDescription": "Enables the set_as_window_menu command without any pre-configured scope."
      },
      {
        "description": "Enables the set_as_windows_menu_for_nsapp command without any pre-configured scope.",
        "type": "string",
        "const": "core:menu:allow-set-as-windows-menu-for-nsapp",
        "markdownDescription": "Enables the set_as_windows_menu_for_nsapp command without any pre-configured scop
      },
      {
        "description": "Enables the set_checked command without any pre-configured scope.",
        "type": "string",
        "const": "core:menu:allow-set-checked",
        "markdownDescription": "Enables the set_checked command without any pre-configured scope."
      },
      {
        "description": "Enables the set_enabled command without any pre-configured scope.",
        "type": "string",
        "const": "core:menu:allow-set-enabled",
        "markdownDescription": "Enables the set_enabled command without any pre-configured scope."
      },
      {
        "description": "Enables the set_icon command without any pre-configured scope.",
        "type": "string",
        "const": "core:menu:allow-set-icon",
        "markdownDescription": "Enables the set_icon command without any pre-configured scope."
```

```
      },
      {
        "description": "Enables the set_text command without any pre-configured scope.",
        "type": "string",
        "const": "core:menu:allow-set-text",
        "markdownDescription": "Enables the set_text command without any pre-configured scope."
      },
      {
        "description": "Enables the text command without any pre-configured scope.",
        "type": "string",
        "const": "core:menu:allow-text",
        "markdownDescription": "Enables the text command without any pre-configured scope."
      },
      {
        "description": "Denies the append command without any pre-configured scope.",
        "type": "string",
        "const": "core:menu:deny-append",
        "markdownDescription": "Denies the append command without any pre-configured scope."
      },
      {
        "description": "Denies the create_default command without any pre-configured scope.",
        "type": "string",
        "const": "core:menu:deny-create-default",
        "markdownDescription": "Denies the create_default command without any pre-configured scope."
      },
      {
        "description": "Denies the get command without any pre-configured scope.",
        "type": "string",
        "const": "core:menu:deny-get",
        "markdownDescription": "Denies the get command without any pre-configured scope."
      },
      {
        "description": "Denies the insert command without any pre-configured scope.",
        "type": "string",
        "const": "core:menu:deny-insert",
        "markdownDescription": "Denies the insert command without any pre-configured scope."
      },
      {
        "description": "Denies the is_checked command without any pre-configured scope.",
        "type": "string",
        "const": "core:menu:deny-is-checked",
        "markdownDescription": "Denies the is_checked command without any pre-configured scope."
      },
      {
        "description": "Denies the is_enabled command without any pre-configured scope.",
        "type": "string",
        "const": "core:menu:deny-is-enabled",
        "markdownDescription": "Denies the is_enabled command without any pre-configured scope."
      },
      {
        "description": "Denies the items command without any pre-configured scope.",
        "type": "string",
        "const": "core:menu:deny-items",
        "markdownDescription": "Denies the items command without any pre-configured scope."
      },
      {
        "description": "Denies the new command without any pre-configured scope.",
        "type": "string",
        "const": "core:menu:deny-new",
        "markdownDescription": "Denies the new command without any pre-configured scope."
      },
      {
        "description": "Denies the popup command without any pre-configured scope.",
        "type": "string",
        "const": "core:menu:deny-popup",
        "markdownDescription": "Denies the popup command without any pre-configured scope."
      },
      {
        "description": "Denies the prepend command without any pre-configured scope.",
        "type": "string",
        "const": "core:menu:deny-prepend",
        "markdownDescription": "Denies the prepend command without any pre-configured scope."
      },
      {
        "description": "Denies the remove command without any pre-configured scope.",
        "type": "string",
        "const": "core:menu:deny-remove",
        "markdownDescription": "Denies the remove command without any pre-configured scope."
      },
      {
        "description": "Denies the remove_at command without any pre-configured scope.",
```

```
      "type": "string",
      "const": "core:menu:deny-remove-at",
      "markdownDescription": "Denies the remove_at command without any pre-configured scope."
    },
    {
      "description": "Denies the set_accelerator command without any pre-configured scope.",
      "type": "string",
      "const": "core:menu:deny-set-accelerator",
      "markdownDescription": "Denies the set_accelerator command without any pre-configured scope."
    },
    {
      "description": "Denies the set_as_app_menu command without any pre-configured scope.",
      "type": "string",
      "const": "core:menu:deny-set-as-app-menu",
      "markdownDescription": "Denies the set_as_app_menu command without any pre-configured scope."
    },
    {
      "description": "Denies the set_as_help_menu_for_nsapp command without any pre-configured scope.",
      "type": "string",
      "const": "core:menu:deny-set-as-help-menu-for-nsapp",
      "markdownDescription": "Denies the set_as_help_menu_for_nsapp command without any pre-configured scope."
    },
    {
      "description": "Denies the set_as_window_menu command without any pre-configured scope.",
      "type": "string",
      "const": "core:menu:deny-set-as-window-menu",
      "markdownDescription": "Denies the set_as_window_menu command without any pre-configured scope."
    },
    {
      "description": "Denies the set_as_windows_menu_for_nsapp command without any pre-configured scope.",
      "type": "string",
      "const": "core:menu:deny-set-as-windows-menu-for-nsapp",
      "markdownDescription": "Denies the set_as_windows_menu_for_nsapp command without any pre-configured scope
    },
    {
      "description": "Denies the set_checked command without any pre-configured scope.",
      "type": "string",
      "const": "core:menu:deny-set-checked",
      "markdownDescription": "Denies the set_checked command without any pre-configured scope."
    },
    {
      "description": "Denies the set_enabled command without any pre-configured scope.",
      "type": "string",
      "const": "core:menu:deny-set-enabled",
      "markdownDescription": "Denies the set_enabled command without any pre-configured scope."
    },
    {
      "description": "Denies the set_icon command without any pre-configured scope.",
      "type": "string",
      "const": "core:menu:deny-set-icon",
      "markdownDescription": "Denies the set_icon command without any pre-configured scope."
    },
    {
      "description": "Denies the set_text command without any pre-configured scope.",
      "type": "string",
      "const": "core:menu:deny-set-text",
      "markdownDescription": "Denies the set_text command without any pre-configured scope."
    },
    {
      "description": "Denies the text command without any pre-configured scope.",
      "type": "string",
      "const": "core:menu:deny-text",
      "markdownDescription": "Denies the text command without any pre-configured scope."
    },
    {
      "description": "Default permissions for the plugin, which enables all commands.\n#### This default permis
      "type": "string",
      "const": "core:path:default",
      "markdownDescription": "Default permissions for the plugin, which enables all commands.\n#### This defaul
    },
    {
      "description": "Enables the basename command without any pre-configured scope.",
      "type": "string",
      "const": "core:path:allow-basename",
      "markdownDescription": "Enables the basename command without any pre-configured scope."
    },
    {
      "description": "Enables the dirname command without any pre-configured scope.",
      "type": "string",
      "const": "core:path:allow-dirname",
      "markdownDescription": "Enables the dirname command without any pre-configured scope."
```

```
      },
      {
        "description": "Enables the extname command without any pre-configured scope.",
        "type": "string",
        "const": "core:path:allow-extname",
        "markdownDescription": "Enables the extname command without any pre-configured scope."
      },
      {
        "description": "Enables the is_absolute command without any pre-configured scope.",
        "type": "string",
        "const": "core:path:allow-is-absolute",
        "markdownDescription": "Enables the is_absolute command without any pre-configured scope."
      },
      {
        "description": "Enables the join command without any pre-configured scope.",
        "type": "string",
        "const": "core:path:allow-join",
        "markdownDescription": "Enables the join command without any pre-configured scope."
      },
      {
        "description": "Enables the normalize command without any pre-configured scope.",
        "type": "string",
        "const": "core:path:allow-normalize",
        "markdownDescription": "Enables the normalize command without any pre-configured scope."
      },
      {
        "description": "Enables the resolve command without any pre-configured scope.",
        "type": "string",
        "const": "core:path:allow-resolve",
        "markdownDescription": "Enables the resolve command without any pre-configured scope."
      },
      {
        "description": "Enables the resolve_directory command without any pre-configured scope.",
        "type": "string",
        "const": "core:path:allow-resolve-directory",
        "markdownDescription": "Enables the resolve_directory command without any pre-configured scope."
      },
      {
        "description": "Denies the basename command without any pre-configured scope.",
        "type": "string",
        "const": "core:path:deny-basename",
        "markdownDescription": "Denies the basename command without any pre-configured scope."
      },
      {
        "description": "Denies the dirname command without any pre-configured scope.",
        "type": "string",
        "const": "core:path:deny-dirname",
        "markdownDescription": "Denies the dirname command without any pre-configured scope."
      },
      {
        "description": "Denies the extname command without any pre-configured scope.",
        "type": "string",
        "const": "core:path:deny-extname",
        "markdownDescription": "Denies the extname command without any pre-configured scope."
      },
      {
        "description": "Denies the is_absolute command without any pre-configured scope.",
        "type": "string",
        "const": "core:path:deny-is-absolute",
        "markdownDescription": "Denies the is_absolute command without any pre-configured scope."
      },
      {
        "description": "Denies the join command without any pre-configured scope.",
        "type": "string",
        "const": "core:path:deny-join",
        "markdownDescription": "Denies the join command without any pre-configured scope."
      },
      {
        "description": "Denies the normalize command without any pre-configured scope.",
        "type": "string",
        "const": "core:path:deny-normalize",
        "markdownDescription": "Denies the normalize command without any pre-configured scope."
      },
      {
        "description": "Denies the resolve command without any pre-configured scope.",
        "type": "string",
        "const": "core:path:deny-resolve",
        "markdownDescription": "Denies the resolve command without any pre-configured scope."
      },
      {
        "description": "Denies the resolve_directory command without any pre-configured scope.",
```

```
      "type": "string",
      "const": "core:path:deny-resolve-directory",
      "markdownDescription": "Denies the resolve_directory command without any pre-configured scope."
    },
    {
      "description": "Default permissions for the plugin, which enables all commands.\n#### This default permis
      "type": "string",
      "const": "core:resources:default",
      "markdownDescription": "Default permissions for the plugin, which enables all commands.\n#### This defaul
    },
    {
      "description": "Enables the close command without any pre-configured scope.",
      "type": "string",
      "const": "core:resources:allow-close",
      "markdownDescription": "Enables the close command without any pre-configured scope."
    },
    {
      "description": "Denies the close command without any pre-configured scope.",
      "type": "string",
      "const": "core:resources:deny-close",
      "markdownDescription": "Denies the close command without any pre-configured scope."
    },
    {
      "description": "Default permissions for the plugin, which enables all commands.\n#### This default permis
      "type": "string",
      "const": "core:tray:default",
      "markdownDescription": "Default permissions for the plugin, which enables all commands.\n#### This defaul
    },
    {
      "description": "Enables the get_by_id command without any pre-configured scope.",
      "type": "string",
      "const": "core:tray:allow-get-by-id",
      "markdownDescription": "Enables the get_by_id command without any pre-configured scope."
    },
    {
      "description": "Enables the new command without any pre-configured scope.",
      "type": "string",
      "const": "core:tray:allow-new",
      "markdownDescription": "Enables the new command without any pre-configured scope."
    },
    {
      "description": "Enables the remove_by_id command without any pre-configured scope.",
      "type": "string",
      "const": "core:tray:allow-remove-by-id",
      "markdownDescription": "Enables the remove_by_id command without any pre-configured scope."
    },
    {
      "description": "Enables the set_icon command without any pre-configured scope.",
      "type": "string",
      "const": "core:tray:allow-set-icon",
      "markdownDescription": "Enables the set_icon command without any pre-configured scope."
    },
    {
      "description": "Enables the set_icon_as_template command without any pre-configured scope.",
      "type": "string",
      "const": "core:tray:allow-set-icon-as-template",
      "markdownDescription": "Enables the set_icon_as_template command without any pre-configured scope."
    },
    {
      "description": "Enables the set_icon_with_as_template command without any pre-configured scope.",
      "type": "string",
      "const": "core:tray:allow-set-icon-with-as-template",
      "markdownDescription": "Enables the set_icon_with_as_template command without any pre-configured scope."
    },
    {
      "description": "Enables the set_menu command without any pre-configured scope.",
      "type": "string",
      "const": "core:tray:allow-set-menu",
      "markdownDescription": "Enables the set_menu command without any pre-configured scope."
    },
    {
      "description": "Enables the set_show_menu_on_left_click command without any pre-configured scope.",
      "type": "string",
      "const": "core:tray:allow-set-show-menu-on-left-click",
      "markdownDescription": "Enables the set_show_menu_on_left_click command without any pre-configured scope.
    },
    {
      "description": "Enables the set_temp_dir_path command without any pre-configured scope.",
      "type": "string",
      "const": "core:tray:allow-set-temp-dir-path",
      "markdownDescription": "Enables the set_temp_dir_path command without any pre-configured scope."
```

```
    },
    {
      "description": "Enables the set_title command without any pre-configured scope.",
      "type": "string",
      "const": "core:tray:allow-set-title",
      "markdownDescription": "Enables the set_title command without any pre-configured scope."
    },
    {
      "description": "Enables the set_tooltip command without any pre-configured scope.",
      "type": "string",
      "const": "core:tray:allow-set-tooltip",
      "markdownDescription": "Enables the set_tooltip command without any pre-configured scope."
    },
    {
      "description": "Enables the set_visible command without any pre-configured scope.",
      "type": "string",
      "const": "core:tray:allow-set-visible",
      "markdownDescription": "Enables the set_visible command without any pre-configured scope."
    },
    {
      "description": "Denies the get_by_id command without any pre-configured scope.",
      "type": "string",
      "const": "core:tray:deny-get-by-id",
      "markdownDescription": "Denies the get_by_id command without any pre-configured scope."
    },
    {
      "description": "Denies the new command without any pre-configured scope.",
      "type": "string",
      "const": "core:tray:deny-new",
      "markdownDescription": "Denies the new command without any pre-configured scope."
    },
    {
      "description": "Denies the remove_by_id command without any pre-configured scope.",
      "type": "string",
      "const": "core:tray:deny-remove-by-id",
      "markdownDescription": "Denies the remove_by_id command without any pre-configured scope."
    },
    {
      "description": "Denies the set_icon command without any pre-configured scope.",
      "type": "string",
      "const": "core:tray:deny-set-icon",
      "markdownDescription": "Denies the set_icon command without any pre-configured scope."
    },
    {
      "description": "Denies the set_icon_as_template command without any pre-configured scope.",
      "type": "string",
      "const": "core:tray:deny-set-icon-as-template",
      "markdownDescription": "Denies the set_icon_as_template command without any pre-configured scope."
    },
    {
      "description": "Denies the set_icon_with_as_template command without any pre-configured scope.",
      "type": "string",
      "const": "core:tray:deny-set-icon-with-as-template",
      "markdownDescription": "Denies the set_icon_with_as_template command without any pre-configured scope."
    },
    {
      "description": "Denies the set_menu command without any pre-configured scope.",
      "type": "string",
      "const": "core:tray:deny-set-menu",
      "markdownDescription": "Denies the set_menu command without any pre-configured scope."
    },
    {
      "description": "Denies the set_show_menu_on_left_click command without any pre-configured scope.",
      "type": "string",
      "const": "core:tray:deny-set-show-menu-on-left-click",
      "markdownDescription": "Denies the set_show_menu_on_left_click command without any pre-configured scope."
    },
    {
      "description": "Denies the set_temp_dir_path command without any pre-configured scope.",
      "type": "string",
      "const": "core:tray:deny-set-temp-dir-path",
      "markdownDescription": "Denies the set_temp_dir_path command without any pre-configured scope."
    },
    {
      "description": "Denies the set_title command without any pre-configured scope.",
      "type": "string",
      "const": "core:tray:deny-set-title",
      "markdownDescription": "Denies the set_title command without any pre-configured scope."
    },
    {
      "description": "Denies the set_tooltip command without any pre-configured scope.",
```

```
      "type": "string",
      "const": "core:tray:deny-set-tooltip",
      "markdownDescription": "Denies the set_tooltip command without any pre-configured scope."
    },
    {
      "description": "Denies the set_visible command without any pre-configured scope.",
      "type": "string",
      "const": "core:tray:deny-set-visible",
      "markdownDescription": "Denies the set_visible command without any pre-configured scope."
    },
    {
      "description": "Default permissions for the plugin.\n#### This default permission set includes:\n\n- `all
      "type": "string",
      "const": "core:webview:default",
      "markdownDescription": "Default permissions for the plugin.\n#### This default permission set includes:\n
    },
    {
      "description": "Enables the clear_all_browsing_data command without any pre-configured scope.",
      "type": "string",
      "const": "core:webview:allow-clear-all-browsing-data",
      "markdownDescription": "Enables the clear_all_browsing_data command without any pre-configured scope."
    },
    {
      "description": "Enables the create_webview command without any pre-configured scope.",
      "type": "string",
      "const": "core:webview:allow-create-webview",
      "markdownDescription": "Enables the create_webview command without any pre-configured scope."
    },
    {
      "description": "Enables the create_webview_window command without any pre-configured scope.",
      "type": "string",
      "const": "core:webview:allow-create-webview-window",
      "markdownDescription": "Enables the create_webview_window command without any pre-configured scope."
    },
    {
      "description": "Enables the get_all_webviews command without any pre-configured scope.",
      "type": "string",
      "const": "core:webview:allow-get-all-webviews",
      "markdownDescription": "Enables the get_all_webviews command without any pre-configured scope."
    },
    {
      "description": "Enables the internal_toggle_devtools command without any pre-configured scope.",
      "type": "string",
      "const": "core:webview:allow-internal-toggle-devtools",
      "markdownDescription": "Enables the internal_toggle_devtools command without any pre-configured scope."
    },
    {
      "description": "Enables the print command without any pre-configured scope.",
      "type": "string",
      "const": "core:webview:allow-print",
      "markdownDescription": "Enables the print command without any pre-configured scope."
    },
    {
      "description": "Enables the reparent command without any pre-configured scope.",
      "type": "string",
      "const": "core:webview:allow-reparent",
      "markdownDescription": "Enables the reparent command without any pre-configured scope."
    },
    {
      "description": "Enables the set_webview_auto_resize command without any pre-configured scope.",
      "type": "string",
      "const": "core:webview:allow-set-webview-auto-resize",
      "markdownDescription": "Enables the set_webview_auto_resize command without any pre-configured scope."
    },
    {
      "description": "Enables the set_webview_background_color command without any pre-configured scope.",
      "type": "string",
      "const": "core:webview:allow-set-webview-background-color",
      "markdownDescription": "Enables the set_webview_background_color command without any pre-configured scope
    },
    {
      "description": "Enables the set_webview_focus command without any pre-configured scope.",
      "type": "string",
      "const": "core:webview:allow-set-webview-focus",
      "markdownDescription": "Enables the set_webview_focus command without any pre-configured scope."
    },
    {
      "description": "Enables the set_webview_position command without any pre-configured scope.",
      "type": "string",
      "const": "core:webview:allow-set-webview-position",
      "markdownDescription": "Enables the set_webview_position command without any pre-configured scope."
```

```
      },
      {
        "description": "Enables the set_webview_size command without any pre-configured scope.",
        "type": "string",
        "const": "core:webview:allow-set-webview-size",
        "markdownDescription": "Enables the set_webview_size command without any pre-configured scope."
      },
      {
        "description": "Enables the set_webview_zoom command without any pre-configured scope.",
        "type": "string",
        "const": "core:webview:allow-set-webview-zoom",
        "markdownDescription": "Enables the set_webview_zoom command without any pre-configured scope."
      },
      {
        "description": "Enables the webview_close command without any pre-configured scope.",
        "type": "string",
        "const": "core:webview:allow-webview-close",
        "markdownDescription": "Enables the webview_close command without any pre-configured scope."
      },
      {
        "description": "Enables the webview_hide command without any pre-configured scope.",
        "type": "string",
        "const": "core:webview:allow-webview-hide",
        "markdownDescription": "Enables the webview_hide command without any pre-configured scope."
      },
      {
        "description": "Enables the webview_position command without any pre-configured scope.",
        "type": "string",
        "const": "core:webview:allow-webview-position",
        "markdownDescription": "Enables the webview_position command without any pre-configured scope."
      },
      {
        "description": "Enables the webview_show command without any pre-configured scope.",
        "type": "string",
        "const": "core:webview:allow-webview-show",
        "markdownDescription": "Enables the webview_show command without any pre-configured scope."
      },
      {
        "description": "Enables the webview_size command without any pre-configured scope.",
        "type": "string",
        "const": "core:webview:allow-webview-size",
        "markdownDescription": "Enables the webview_size command without any pre-configured scope."
      },
      {
        "description": "Denies the clear_all_browsing_data command without any pre-configured scope.",
        "type": "string",
        "const": "core:webview:deny-clear-all-browsing-data",
        "markdownDescription": "Denies the clear_all_browsing_data command without any pre-configured scope."
      },
      {
        "description": "Denies the create_webview command without any pre-configured scope.",
        "type": "string",
        "const": "core:webview:deny-create-webview",
        "markdownDescription": "Denies the create_webview command without any pre-configured scope."
      },
      {
        "description": "Denies the create_webview_window command without any pre-configured scope.",
        "type": "string",
        "const": "core:webview:deny-create-webview-window",
        "markdownDescription": "Denies the create_webview_window command without any pre-configured scope."
      },
      {
        "description": "Denies the get_all_webviews command without any pre-configured scope.",
        "type": "string",
        "const": "core:webview:deny-get-all-webviews",
        "markdownDescription": "Denies the get_all_webviews command without any pre-configured scope."
      },
      {
        "description": "Denies the internal_toggle_devtools command without any pre-configured scope.",
        "type": "string",
        "const": "core:webview:deny-internal-toggle-devtools",
        "markdownDescription": "Denies the internal_toggle_devtools command without any pre-configured scope."
      },
      {
        "description": "Denies the print command without any pre-configured scope.",
        "type": "string",
        "const": "core:webview:deny-print",
        "markdownDescription": "Denies the print command without any pre-configured scope."
      },
      {
        "description": "Denies the reparent command without any pre-configured scope.",
```

```
      "type": "string",
      "const": "core:webview:deny-reparent",
      "markdownDescription": "Denies the reparent command without any pre-configured scope."
    },
    {
      "description": "Denies the set_webview_auto_resize command without any pre-configured scope.",
      "type": "string",
      "const": "core:webview:deny-set-webview-auto-resize",
      "markdownDescription": "Denies the set_webview_auto_resize command without any pre-configured scope."
    },
    {
      "description": "Denies the set_webview_background_color command without any pre-configured scope.",
      "type": "string",
      "const": "core:webview:deny-set-webview-background-color",
      "markdownDescription": "Denies the set_webview_background_color command without any pre-configured scope.
    },
    {
      "description": "Denies the set_webview_focus command without any pre-configured scope.",
      "type": "string",
      "const": "core:webview:deny-set-webview-focus",
      "markdownDescription": "Denies the set_webview_focus command without any pre-configured scope."
    },
    {
      "description": "Denies the set_webview_position command without any pre-configured scope.",
      "type": "string",
      "const": "core:webview:deny-set-webview-position",
      "markdownDescription": "Denies the set_webview_position command without any pre-configured scope."
    },
    {
      "description": "Denies the set_webview_size command without any pre-configured scope.",
      "type": "string",
      "const": "core:webview:deny-set-webview-size",
      "markdownDescription": "Denies the set_webview_size command without any pre-configured scope."
    },
    {
      "description": "Denies the set_webview_zoom command without any pre-configured scope.",
      "type": "string",
      "const": "core:webview:deny-set-webview-zoom",
      "markdownDescription": "Denies the set_webview_zoom command without any pre-configured scope."
    },
    {
      "description": "Denies the webview_close command without any pre-configured scope.",
      "type": "string",
      "const": "core:webview:deny-webview-close",
      "markdownDescription": "Denies the webview_close command without any pre-configured scope."
    },
    {
      "description": "Denies the webview_hide command without any pre-configured scope.",
      "type": "string",
      "const": "core:webview:deny-webview-hide",
      "markdownDescription": "Denies the webview_hide command without any pre-configured scope."
    },
    {
      "description": "Denies the webview_position command without any pre-configured scope.",
      "type": "string",
      "const": "core:webview:deny-webview-position",
      "markdownDescription": "Denies the webview_position command without any pre-configured scope."
    },
    {
      "description": "Denies the webview_show command without any pre-configured scope.",
      "type": "string",
      "const": "core:webview:deny-webview-show",
      "markdownDescription": "Denies the webview_show command without any pre-configured scope."
    },
    {
      "description": "Denies the webview_size command without any pre-configured scope.",
      "type": "string",
      "const": "core:webview:deny-webview-size",
      "markdownDescription": "Denies the webview_size command without any pre-configured scope."
    },
    {
      "description": "Default permissions for the plugin.\n#### This default permission set includes:\n\n- `all
      "type": "string",
      "const": "core:window:default",
      "markdownDescription": "Default permissions for the plugin.\n#### This default permission set includes:\n
    },
    {
      "description": "Enables the activity_name command without any pre-configured scope.",
      "type": "string",
      "const": "core:window:allow-activity-name",
      "markdownDescription": "Enables the activity_name command without any pre-configured scope."
```

```
      },
      {
        "description": "Enables the available_monitors command without any pre-configured scope.",
        "type": "string",
        "const": "core:window:allow-available-monitors",
        "markdownDescription": "Enables the available_monitors command without any pre-configured scope."
      },
      {
        "description": "Enables the center command without any pre-configured scope.",
        "type": "string",
        "const": "core:window:allow-center",
        "markdownDescription": "Enables the center command without any pre-configured scope."
      },
      {
        "description": "Enables the close command without any pre-configured scope.",
        "type": "string",
        "const": "core:window:allow-close",
        "markdownDescription": "Enables the close command without any pre-configured scope."
      },
      {
        "description": "Enables the create command without any pre-configured scope.",
        "type": "string",
        "const": "core:window:allow-create",
        "markdownDescription": "Enables the create command without any pre-configured scope."
      },
      {
        "description": "Enables the current_monitor command without any pre-configured scope.",
        "type": "string",
        "const": "core:window:allow-current-monitor",
        "markdownDescription": "Enables the current_monitor command without any pre-configured scope."
      },
      {
        "description": "Enables the cursor_position command without any pre-configured scope.",
        "type": "string",
        "const": "core:window:allow-cursor-position",
        "markdownDescription": "Enables the cursor_position command without any pre-configured scope."
      },
      {
        "description": "Enables the destroy command without any pre-configured scope.",
        "type": "string",
        "const": "core:window:allow-destroy",
        "markdownDescription": "Enables the destroy command without any pre-configured scope."
      },
      {
        "description": "Enables the get_all_windows command without any pre-configured scope.",
        "type": "string",
        "const": "core:window:allow-get-all-windows",
        "markdownDescription": "Enables the get_all_windows command without any pre-configured scope."
      },
      {
        "description": "Enables the hide command without any pre-configured scope.",
        "type": "string",
        "const": "core:window:allow-hide",
        "markdownDescription": "Enables the hide command without any pre-configured scope."
      },
      {
        "description": "Enables the inner_position command without any pre-configured scope.",
        "type": "string",
        "const": "core:window:allow-inner-position",
        "markdownDescription": "Enables the inner_position command without any pre-configured scope."
      },
      {
        "description": "Enables the inner_size command without any pre-configured scope.",
        "type": "string",
        "const": "core:window:allow-inner-size",
        "markdownDescription": "Enables the inner_size command without any pre-configured scope."
      },
      {
        "description": "Enables the internal_toggle_maximize command without any pre-configured scope.",
        "type": "string",
        "const": "core:window:allow-internal-toggle-maximize",
        "markdownDescription": "Enables the internal_toggle_maximize command without any pre-configured scope."
      },
      {
        "description": "Enables the is_always_on_top command without any pre-configured scope.",
        "type": "string",
        "const": "core:window:allow-is-always-on-top",
        "markdownDescription": "Enables the is_always_on_top command without any pre-configured scope."
      },
      {
        "description": "Enables the is_closable command without any pre-configured scope.",
```

```
      "type": "string",
      "const": "core:window:allow-is-closable",
      "markdownDescription": "Enables the is_closable command without any pre-configured scope."
    },
    {
      "description": "Enables the is_decorated command without any pre-configured scope.",
      "type": "string",
      "const": "core:window:allow-is-decorated",
      "markdownDescription": "Enables the is_decorated command without any pre-configured scope."
    },
    {
      "description": "Enables the is_enabled command without any pre-configured scope.",
      "type": "string",
      "const": "core:window:allow-is-enabled",
      "markdownDescription": "Enables the is_enabled command without any pre-configured scope."
    },
    {
      "description": "Enables the is_focused command without any pre-configured scope.",
      "type": "string",
      "const": "core:window:allow-is-focused",
      "markdownDescription": "Enables the is_focused command without any pre-configured scope."
    },
    {
      "description": "Enables the is_fullscreen command without any pre-configured scope.",
      "type": "string",
      "const": "core:window:allow-is-fullscreen",
      "markdownDescription": "Enables the is_fullscreen command without any pre-configured scope."
    },
    {
      "description": "Enables the is_maximizable command without any pre-configured scope.",
      "type": "string",
      "const": "core:window:allow-is-maximizable",
      "markdownDescription": "Enables the is_maximizable command without any pre-configured scope."
    },
    {
      "description": "Enables the is_maximized command without any pre-configured scope.",
      "type": "string",
      "const": "core:window:allow-is-maximized",
      "markdownDescription": "Enables the is_maximized command without any pre-configured scope."
    },
    {
      "description": "Enables the is_minimizable command without any pre-configured scope.",
      "type": "string",
      "const": "core:window:allow-is-minimizable",
      "markdownDescription": "Enables the is_minimizable command without any pre-configured scope."
    },
    {
      "description": "Enables the is_minimized command without any pre-configured scope.",
      "type": "string",
      "const": "core:window:allow-is-minimized",
      "markdownDescription": "Enables the is_minimized command without any pre-configured scope."
    },
    {
      "description": "Enables the is_resizable command without any pre-configured scope.",
      "type": "string",
      "const": "core:window:allow-is-resizable",
      "markdownDescription": "Enables the is_resizable command without any pre-configured scope."
    },
    {
      "description": "Enables the is_visible command without any pre-configured scope.",
      "type": "string",
      "const": "core:window:allow-is-visible",
      "markdownDescription": "Enables the is_visible command without any pre-configured scope."
    },
    {
      "description": "Enables the maximize command without any pre-configured scope.",
      "type": "string",
      "const": "core:window:allow-maximize",
      "markdownDescription": "Enables the maximize command without any pre-configured scope."
    },
    {
      "description": "Enables the minimize command without any pre-configured scope.",
      "type": "string",
      "const": "core:window:allow-minimize",
      "markdownDescription": "Enables the minimize command without any pre-configured scope."
    },
    {
      "description": "Enables the monitor_from_point command without any pre-configured scope.",
      "type": "string",
      "const": "core:window:allow-monitor-from-point",
      "markdownDescription": "Enables the monitor_from_point command without any pre-configured scope."
```

```
      },
      {
        "description": "Enables the outer_position command without any pre-configured scope.",
        "type": "string",
        "const": "core:window:allow-outer-position",
        "markdownDescription": "Enables the outer_position command without any pre-configured scope."
      },
      {
        "description": "Enables the outer_size command without any pre-configured scope.",
        "type": "string",
        "const": "core:window:allow-outer-size",
        "markdownDescription": "Enables the outer_size command without any pre-configured scope."
      },
      {
        "description": "Enables the primary_monitor command without any pre-configured scope.",
        "type": "string",
        "const": "core:window:allow-primary-monitor",
        "markdownDescription": "Enables the primary_monitor command without any pre-configured scope."
      },
      {
        "description": "Enables the request_user_attention command without any pre-configured scope.",
        "type": "string",
        "const": "core:window:allow-request-user-attention",
        "markdownDescription": "Enables the request_user_attention command without any pre-configured scope."
      },
      {
        "description": "Enables the scale_factor command without any pre-configured scope.",
        "type": "string",
        "const": "core:window:allow-scale-factor",
        "markdownDescription": "Enables the scale_factor command without any pre-configured scope."
      },
      {
        "description": "Enables the scene_identifier command without any pre-configured scope.",
        "type": "string",
        "const": "core:window:allow-scene-identifier",
        "markdownDescription": "Enables the scene_identifier command without any pre-configured scope."
      },
      {
        "description": "Enables the set_always_on_bottom command without any pre-configured scope.",
        "type": "string",
        "const": "core:window:allow-set-always-on-bottom",
        "markdownDescription": "Enables the set_always_on_bottom command without any pre-configured scope."
      },
      {
        "description": "Enables the set_always_on_top command without any pre-configured scope.",
        "type": "string",
        "const": "core:window:allow-set-always-on-top",
        "markdownDescription": "Enables the set_always_on_top command without any pre-configured scope."
      },
      {
        "description": "Enables the set_background_color command without any pre-configured scope.",
        "type": "string",
        "const": "core:window:allow-set-background-color",
        "markdownDescription": "Enables the set_background_color command without any pre-configured scope."
      },
      {
        "description": "Enables the set_badge_count command without any pre-configured scope.",
        "type": "string",
        "const": "core:window:allow-set-badge-count",
        "markdownDescription": "Enables the set_badge_count command without any pre-configured scope."
      },
      {
        "description": "Enables the set_badge_label command without any pre-configured scope.",
        "type": "string",
        "const": "core:window:allow-set-badge-label",
        "markdownDescription": "Enables the set_badge_label command without any pre-configured scope."
      },
      {
        "description": "Enables the set_closable command without any pre-configured scope.",
        "type": "string",
        "const": "core:window:allow-set-closable",
        "markdownDescription": "Enables the set_closable command without any pre-configured scope."
      },
      {
        "description": "Enables the set_content_protected command without any pre-configured scope.",
        "type": "string",
        "const": "core:window:allow-set-content-protected",
        "markdownDescription": "Enables the set_content_protected command without any pre-configured scope."
      },
      {
        "description": "Enables the set_cursor_grab command without any pre-configured scope.",
```

```
      "type": "string",
      "const": "core:window:allow-set-cursor-grab",
      "markdownDescription": "Enables the set_cursor_grab command without any pre-configured scope."
    },
    {
      "description": "Enables the set_cursor_icon command without any pre-configured scope.",
      "type": "string",
      "const": "core:window:allow-set-cursor-icon",
      "markdownDescription": "Enables the set_cursor_icon command without any pre-configured scope."
    },
    {
      "description": "Enables the set_cursor_position command without any pre-configured scope.",
      "type": "string",
      "const": "core:window:allow-set-cursor-position",
      "markdownDescription": "Enables the set_cursor_position command without any pre-configured scope."
    },
    {
      "description": "Enables the set_cursor_visible command without any pre-configured scope.",
      "type": "string",
      "const": "core:window:allow-set-cursor-visible",
      "markdownDescription": "Enables the set_cursor_visible command without any pre-configured scope."
    },
    {
      "description": "Enables the set_decorations command without any pre-configured scope.",
      "type": "string",
      "const": "core:window:allow-set-decorations",
      "markdownDescription": "Enables the set_decorations command without any pre-configured scope."
    },
    {
      "description": "Enables the set_effects command without any pre-configured scope.",
      "type": "string",
      "const": "core:window:allow-set-effects",
      "markdownDescription": "Enables the set_effects command without any pre-configured scope."
    },
    {
      "description": "Enables the set_enabled command without any pre-configured scope.",
      "type": "string",
      "const": "core:window:allow-set-enabled",
      "markdownDescription": "Enables the set_enabled command without any pre-configured scope."
    },
    {
      "description": "Enables the set_focus command without any pre-configured scope.",
      "type": "string",
      "const": "core:window:allow-set-focus",
      "markdownDescription": "Enables the set_focus command without any pre-configured scope."
    },
    {
      "description": "Enables the set_focusable command without any pre-configured scope.",
      "type": "string",
      "const": "core:window:allow-set-focusable",
      "markdownDescription": "Enables the set_focusable command without any pre-configured scope."
    },
    {
      "description": "Enables the set_fullscreen command without any pre-configured scope.",
      "type": "string",
      "const": "core:window:allow-set-fullscreen",
      "markdownDescription": "Enables the set_fullscreen command without any pre-configured scope."
    },
    {
      "description": "Enables the set_fullscreen_on_monitor command without any pre-configured scope.",
      "type": "string",
      "const": "core:window:allow-set-fullscreen-on-monitor",
      "markdownDescription": "Enables the set_fullscreen_on_monitor command without any pre-configured scope."
    },
    {
      "description": "Enables the set_icon command without any pre-configured scope.",
      "type": "string",
      "const": "core:window:allow-set-icon",
      "markdownDescription": "Enables the set_icon command without any pre-configured scope."
    },
    {
      "description": "Enables the set_ignore_cursor_events command without any pre-configured scope.",
      "type": "string",
      "const": "core:window:allow-set-ignore-cursor-events",
      "markdownDescription": "Enables the set_ignore_cursor_events command without any pre-configured scope."
    },
    {
      "description": "Enables the set_max_size command without any pre-configured scope.",
      "type": "string",
      "const": "core:window:allow-set-max-size",
      "markdownDescription": "Enables the set_max_size command without any pre-configured scope."
```

```
        },
        {
          "description": "Enables the set_maximizable command without any pre-configured scope.",
          "type": "string",
          "const": "core:window:allow-set-maximizable",
          "markdownDescription": "Enables the set_maximizable command without any pre-configured scope."
        },
        {
          "description": "Enables the set_min_size command without any pre-configured scope.",
          "type": "string",
          "const": "core:window:allow-set-min-size",
          "markdownDescription": "Enables the set_min_size command without any pre-configured scope."
        },
        {
          "description": "Enables the set_minimizable command without any pre-configured scope.",
          "type": "string",
          "const": "core:window:allow-set-minimizable",
          "markdownDescription": "Enables the set_minimizable command without any pre-configured scope."
        },
        {
          "description": "Enables the set_overlay_icon command without any pre-configured scope.",
          "type": "string",
          "const": "core:window:allow-set-overlay-icon",
          "markdownDescription": "Enables the set_overlay_icon command without any pre-configured scope."
        },
        {
          "description": "Enables the set_position command without any pre-configured scope.",
          "type": "string",
          "const": "core:window:allow-set-position",
          "markdownDescription": "Enables the set_position command without any pre-configured scope."
        },
        {
          "description": "Enables the set_progress_bar command without any pre-configured scope.",
          "type": "string",
          "const": "core:window:allow-set-progress-bar",
          "markdownDescription": "Enables the set_progress_bar command without any pre-configured scope."
        },
        {
          "description": "Enables the set_resizable command without any pre-configured scope.",
          "type": "string",
          "const": "core:window:allow-set-resizable",
          "markdownDescription": "Enables the set_resizable command without any pre-configured scope."
        },
        {
          "description": "Enables the set_shadow command without any pre-configured scope.",
          "type": "string",
          "const": "core:window:allow-set-shadow",
          "markdownDescription": "Enables the set_shadow command without any pre-configured scope."
        },
        {
          "description": "Enables the set_simple_fullscreen command without any pre-configured scope.",
          "type": "string",
          "const": "core:window:allow-set-simple-fullscreen",
          "markdownDescription": "Enables the set_simple_fullscreen command without any pre-configured scope."
        },
        {
          "description": "Enables the set_size command without any pre-configured scope.",
          "type": "string",
          "const": "core:window:allow-set-size",
          "markdownDescription": "Enables the set_size command without any pre-configured scope."
        },
        {
          "description": "Enables the set_size_constraints command without any pre-configured scope.",
          "type": "string",
          "const": "core:window:allow-set-size-constraints",
          "markdownDescription": "Enables the set_size_constraints command without any pre-configured scope."
        },
        {
          "description": "Enables the set_skip_taskbar command without any pre-configured scope.",
          "type": "string",
          "const": "core:window:allow-set-skip-taskbar",
          "markdownDescription": "Enables the set_skip_taskbar command without any pre-configured scope."
        },
        {
          "description": "Enables the set_theme command without any pre-configured scope.",
          "type": "string",
          "const": "core:window:allow-set-theme",
          "markdownDescription": "Enables the set_theme command without any pre-configured scope."
        },
        {
          "description": "Enables the set_title command without any pre-configured scope.",
```

```
      "type": "string",
      "const": "core:window:allow-set-title",
      "markdownDescription": "Enables the set_title command without any pre-configured scope."
    },
    {
      "description": "Enables the set_title_bar_style command without any pre-configured scope.",
      "type": "string",
      "const": "core:window:allow-set-title-bar-style",
      "markdownDescription": "Enables the set_title_bar_style command without any pre-configured scope."
    },
    {
      "description": "Enables the set_visible_on_all_workspaces command without any pre-configured scope.",
      "type": "string",
      "const": "core:window:allow-set-visible-on-all-workspaces",
      "markdownDescription": "Enables the set_visible_on_all_workspaces command without any pre-configured scop
    },
    {
      "description": "Enables the show command without any pre-configured scope.",
      "type": "string",
      "const": "core:window:allow-show",
      "markdownDescription": "Enables the show command without any pre-configured scope."
    },
    {
      "description": "Enables the start_dragging command without any pre-configured scope.",
      "type": "string",
      "const": "core:window:allow-start-dragging",
      "markdownDescription": "Enables the start_dragging command without any pre-configured scope."
    },
    {
      "description": "Enables the start_resize_dragging command without any pre-configured scope.",
      "type": "string",
      "const": "core:window:allow-start-resize-dragging",
      "markdownDescription": "Enables the start_resize_dragging command without any pre-configured scope."
    },
    {
      "description": "Enables the theme command without any pre-configured scope.",
      "type": "string",
      "const": "core:window:allow-theme",
      "markdownDescription": "Enables the theme command without any pre-configured scope."
    },
    {
      "description": "Enables the title command without any pre-configured scope.",
      "type": "string",
      "const": "core:window:allow-title",
      "markdownDescription": "Enables the title command without any pre-configured scope."
    },
    {
      "description": "Enables the toggle_maximize command without any pre-configured scope.",
      "type": "string",
      "const": "core:window:allow-toggle-maximize",
      "markdownDescription": "Enables the toggle_maximize command without any pre-configured scope."
    },
    {
      "description": "Enables the unmaximize command without any pre-configured scope.",
      "type": "string",
      "const": "core:window:allow-unmaximize",
      "markdownDescription": "Enables the unmaximize command without any pre-configured scope."
    },
    {
      "description": "Enables the unminimize command without any pre-configured scope.",
      "type": "string",
      "const": "core:window:allow-unminimize",
      "markdownDescription": "Enables the unminimize command without any pre-configured scope."
    },
    {
      "description": "Denies the activity_name command without any pre-configured scope.",
      "type": "string",
      "const": "core:window:deny-activity-name",
      "markdownDescription": "Denies the activity_name command without any pre-configured scope."
    },
    {
      "description": "Denies the available_monitors command without any pre-configured scope.",
      "type": "string",
      "const": "core:window:deny-available-monitors",
      "markdownDescription": "Denies the available_monitors command without any pre-configured scope."
    },
    {
      "description": "Denies the center command without any pre-configured scope.",
      "type": "string",
      "const": "core:window:deny-center",
      "markdownDescription": "Denies the center command without any pre-configured scope."
```

```
      },
      {
        "description": "Denies the close command without any pre-configured scope.",
        "type": "string",
        "const": "core:window:deny-close",
        "markdownDescription": "Denies the close command without any pre-configured scope."
      },
      {
        "description": "Denies the create command without any pre-configured scope.",
        "type": "string",
        "const": "core:window:deny-create",
        "markdownDescription": "Denies the create command without any pre-configured scope."
      },
      {
        "description": "Denies the current_monitor command without any pre-configured scope.",
        "type": "string",
        "const": "core:window:deny-current-monitor",
        "markdownDescription": "Denies the current_monitor command without any pre-configured scope."
      },
      {
        "description": "Denies the cursor_position command without any pre-configured scope.",
        "type": "string",
        "const": "core:window:deny-cursor-position",
        "markdownDescription": "Denies the cursor_position command without any pre-configured scope."
      },
      {
        "description": "Denies the destroy command without any pre-configured scope.",
        "type": "string",
        "const": "core:window:deny-destroy",
        "markdownDescription": "Denies the destroy command without any pre-configured scope."
      },
      {
        "description": "Denies the get_all_windows command without any pre-configured scope.",
        "type": "string",
        "const": "core:window:deny-get-all-windows",
        "markdownDescription": "Denies the get_all_windows command without any pre-configured scope."
      },
      {
        "description": "Denies the hide command without any pre-configured scope.",
        "type": "string",
        "const": "core:window:deny-hide",
        "markdownDescription": "Denies the hide command without any pre-configured scope."
      },
      {
        "description": "Denies the inner_position command without any pre-configured scope.",
        "type": "string",
        "const": "core:window:deny-inner-position",
        "markdownDescription": "Denies the inner_position command without any pre-configured scope."
      },
      {
        "description": "Denies the inner_size command without any pre-configured scope.",
        "type": "string",
        "const": "core:window:deny-inner-size",
        "markdownDescription": "Denies the inner_size command without any pre-configured scope."
      },
      {
        "description": "Denies the internal_toggle_maximize command without any pre-configured scope.",
        "type": "string",
        "const": "core:window:deny-internal-toggle-maximize",
        "markdownDescription": "Denies the internal_toggle_maximize command without any pre-configured scope."
      },
      {
        "description": "Denies the is_always_on_top command without any pre-configured scope.",
        "type": "string",
        "const": "core:window:deny-is-always-on-top",
        "markdownDescription": "Denies the is_always_on_top command without any pre-configured scope."
      },
      {
        "description": "Denies the is_closable command without any pre-configured scope.",
        "type": "string",
        "const": "core:window:deny-is-closable",
        "markdownDescription": "Denies the is_closable command without any pre-configured scope."
      },
      {
        "description": "Denies the is_decorated command without any pre-configured scope.",
        "type": "string",
        "const": "core:window:deny-is-decorated",
        "markdownDescription": "Denies the is_decorated command without any pre-configured scope."
      },
      {
        "description": "Denies the is_enabled command without any pre-configured scope.",
```

```
      "type": "string",
      "const": "core:window:deny-is-enabled",
      "markdownDescription": "Denies the is_enabled command without any pre-configured scope."
    },
    {
      "description": "Denies the is_focused command without any pre-configured scope.",
      "type": "string",
      "const": "core:window:deny-is-focused",
      "markdownDescription": "Denies the is_focused command without any pre-configured scope."
    },
    {
      "description": "Denies the is_fullscreen command without any pre-configured scope.",
      "type": "string",
      "const": "core:window:deny-is-fullscreen",
      "markdownDescription": "Denies the is_fullscreen command without any pre-configured scope."
    },
    {
      "description": "Denies the is_maximizable command without any pre-configured scope.",
      "type": "string",
      "const": "core:window:deny-is-maximizable",
      "markdownDescription": "Denies the is_maximizable command without any pre-configured scope."
    },
    {
      "description": "Denies the is_maximized command without any pre-configured scope.",
      "type": "string",
      "const": "core:window:deny-is-maximized",
      "markdownDescription": "Denies the is_maximized command without any pre-configured scope."
    },
    {
      "description": "Denies the is_minimizable command without any pre-configured scope.",
      "type": "string",
      "const": "core:window:deny-is-minimizable",
      "markdownDescription": "Denies the is_minimizable command without any pre-configured scope."
    },
    {
      "description": "Denies the is_minimized command without any pre-configured scope.",
      "type": "string",
      "const": "core:window:deny-is-minimized",
      "markdownDescription": "Denies the is_minimized command without any pre-configured scope."
    },
    {
      "description": "Denies the is_resizable command without any pre-configured scope.",
      "type": "string",
      "const": "core:window:deny-is-resizable",
      "markdownDescription": "Denies the is_resizable command without any pre-configured scope."
    },
    {
      "description": "Denies the is_visible command without any pre-configured scope.",
      "type": "string",
      "const": "core:window:deny-is-visible",
      "markdownDescription": "Denies the is_visible command without any pre-configured scope."
    },
    {
      "description": "Denies the maximize command without any pre-configured scope.",
      "type": "string",
      "const": "core:window:deny-maximize",
      "markdownDescription": "Denies the maximize command without any pre-configured scope."
    },
    {
      "description": "Denies the minimize command without any pre-configured scope.",
      "type": "string",
      "const": "core:window:deny-minimize",
      "markdownDescription": "Denies the minimize command without any pre-configured scope."
    },
    {
      "description": "Denies the monitor_from_point command without any pre-configured scope.",
      "type": "string",
      "const": "core:window:deny-monitor-from-point",
      "markdownDescription": "Denies the monitor_from_point command without any pre-configured scope."
    },
    {
      "description": "Denies the outer_position command without any pre-configured scope.",
      "type": "string",
      "const": "core:window:deny-outer-position",
      "markdownDescription": "Denies the outer_position command without any pre-configured scope."
    },
    {
      "description": "Denies the outer_size command without any pre-configured scope.",
      "type": "string",
      "const": "core:window:deny-outer-size",
      "markdownDescription": "Denies the outer_size command without any pre-configured scope."
```

```
        },
        {
          "description": "Denies the primary_monitor command without any pre-configured scope.",
          "type": "string",
          "const": "core:window:deny-primary-monitor",
          "markdownDescription": "Denies the primary_monitor command without any pre-configured scope."
        },
        {
          "description": "Denies the request_user_attention command without any pre-configured scope.",
          "type": "string",
          "const": "core:window:deny-request-user-attention",
          "markdownDescription": "Denies the request_user_attention command without any pre-configured scope."
        },
        {
          "description": "Denies the scale_factor command without any pre-configured scope.",
          "type": "string",
          "const": "core:window:deny-scale-factor",
          "markdownDescription": "Denies the scale_factor command without any pre-configured scope."
        },
        {
          "description": "Denies the scene_identifier command without any pre-configured scope.",
          "type": "string",
          "const": "core:window:deny-scene-identifier",
          "markdownDescription": "Denies the scene_identifier command without any pre-configured scope."
        },
        {
          "description": "Denies the set_always_on_bottom command without any pre-configured scope.",
          "type": "string",
          "const": "core:window:deny-set-always-on-bottom",
          "markdownDescription": "Denies the set_always_on_bottom command without any pre-configured scope."
        },
        {
          "description": "Denies the set_always_on_top command without any pre-configured scope.",
          "type": "string",
          "const": "core:window:deny-set-always-on-top",
          "markdownDescription": "Denies the set_always_on_top command without any pre-configured scope."
        },
        {
          "description": "Denies the set_background_color command without any pre-configured scope.",
          "type": "string",
          "const": "core:window:deny-set-background-color",
          "markdownDescription": "Denies the set_background_color command without any pre-configured scope."
        },
        {
          "description": "Denies the set_badge_count command without any pre-configured scope.",
          "type": "string",
          "const": "core:window:deny-set-badge-count",
          "markdownDescription": "Denies the set_badge_count command without any pre-configured scope."
        },
        {
          "description": "Denies the set_badge_label command without any pre-configured scope.",
          "type": "string",
          "const": "core:window:deny-set-badge-label",
          "markdownDescription": "Denies the set_badge_label command without any pre-configured scope."
        },
        {
          "description": "Denies the set_closable command without any pre-configured scope.",
          "type": "string",
          "const": "core:window:deny-set-closable",
          "markdownDescription": "Denies the set_closable command without any pre-configured scope."
        },
        {
          "description": "Denies the set_content_protected command without any pre-configured scope.",
          "type": "string",
          "const": "core:window:deny-set-content-protected",
          "markdownDescription": "Denies the set_content_protected command without any pre-configured scope."
        },
        {
          "description": "Denies the set_cursor_grab command without any pre-configured scope.",
          "type": "string",
          "const": "core:window:deny-set-cursor-grab",
          "markdownDescription": "Denies the set_cursor_grab command without any pre-configured scope."
        },
        {
          "description": "Denies the set_cursor_icon command without any pre-configured scope.",
          "type": "string",
          "const": "core:window:deny-set-cursor-icon",
          "markdownDescription": "Denies the set_cursor_icon command without any pre-configured scope."
        },
        {
          "description": "Denies the set_cursor_position command without any pre-configured scope.",
```

```
      "type": "string",
      "const": "core:window:deny-set-cursor-position",
      "markdownDescription": "Denies the set_cursor_position command without any pre-configured scope."
    },
    {
      "description": "Denies the set_cursor_visible command without any pre-configured scope.",
      "type": "string",
      "const": "core:window:deny-set-cursor-visible",
      "markdownDescription": "Denies the set_cursor_visible command without any pre-configured scope."
    },
    {
      "description": "Denies the set_decorations command without any pre-configured scope.",
      "type": "string",
      "const": "core:window:deny-set-decorations",
      "markdownDescription": "Denies the set_decorations command without any pre-configured scope."
    },
    {
      "description": "Denies the set_effects command without any pre-configured scope.",
      "type": "string",
      "const": "core:window:deny-set-effects",
      "markdownDescription": "Denies the set_effects command without any pre-configured scope."
    },
    {
      "description": "Denies the set_enabled command without any pre-configured scope.",
      "type": "string",
      "const": "core:window:deny-set-enabled",
      "markdownDescription": "Denies the set_enabled command without any pre-configured scope."
    },
    {
      "description": "Denies the set_focus command without any pre-configured scope.",
      "type": "string",
      "const": "core:window:deny-set-focus",
      "markdownDescription": "Denies the set_focus command without any pre-configured scope."
    },
    {
      "description": "Denies the set_focusable command without any pre-configured scope.",
      "type": "string",
      "const": "core:window:deny-set-focusable",
      "markdownDescription": "Denies the set_focusable command without any pre-configured scope."
    },
    {
      "description": "Denies the set_fullscreen command without any pre-configured scope.",
      "type": "string",
      "const": "core:window:deny-set-fullscreen",
      "markdownDescription": "Denies the set_fullscreen command without any pre-configured scope."
    },
    {
      "description": "Denies the set_fullscreen_on_monitor command without any pre-configured scope.",
      "type": "string",
      "const": "core:window:deny-set-fullscreen-on-monitor",
      "markdownDescription": "Denies the set_fullscreen_on_monitor command without any pre-configured scope."
    },
    {
      "description": "Denies the set_icon command without any pre-configured scope.",
      "type": "string",
      "const": "core:window:deny-set-icon",
      "markdownDescription": "Denies the set_icon command without any pre-configured scope."
    },
    {
      "description": "Denies the set_ignore_cursor_events command without any pre-configured scope.",
      "type": "string",
      "const": "core:window:deny-set-ignore-cursor-events",
      "markdownDescription": "Denies the set_ignore_cursor_events command without any pre-configured scope."
    },
    {
      "description": "Denies the set_max_size command without any pre-configured scope.",
      "type": "string",
      "const": "core:window:deny-set-max-size",
      "markdownDescription": "Denies the set_max_size command without any pre-configured scope."
    },
    {
      "description": "Denies the set_maximizable command without any pre-configured scope.",
      "type": "string",
      "const": "core:window:deny-set-maximizable",
      "markdownDescription": "Denies the set_maximizable command without any pre-configured scope."
    },
    {
      "description": "Denies the set_min_size command without any pre-configured scope.",
      "type": "string",
      "const": "core:window:deny-set-min-size",
      "markdownDescription": "Denies the set_min_size command without any pre-configured scope."
```

```
      },
      {
        "description": "Denies the set_minimizable command without any pre-configured scope.",
        "type": "string",
        "const": "core:window:deny-set-minimizable",
        "markdownDescription": "Denies the set_minimizable command without any pre-configured scope."
      },
      {
        "description": "Denies the set_overlay_icon command without any pre-configured scope.",
        "type": "string",
        "const": "core:window:deny-set-overlay-icon",
        "markdownDescription": "Denies the set_overlay_icon command without any pre-configured scope."
      },
      {
        "description": "Denies the set_position command without any pre-configured scope.",
        "type": "string",
        "const": "core:window:deny-set-position",
        "markdownDescription": "Denies the set_position command without any pre-configured scope."
      },
      {
        "description": "Denies the set_progress_bar command without any pre-configured scope.",
        "type": "string",
        "const": "core:window:deny-set-progress-bar",
        "markdownDescription": "Denies the set_progress_bar command without any pre-configured scope."
      },
      {
        "description": "Denies the set_resizable command without any pre-configured scope.",
        "type": "string",
        "const": "core:window:deny-set-resizable",
        "markdownDescription": "Denies the set_resizable command without any pre-configured scope."
      },
      {
        "description": "Denies the set_shadow command without any pre-configured scope.",
        "type": "string",
        "const": "core:window:deny-set-shadow",
        "markdownDescription": "Denies the set_shadow command without any pre-configured scope."
      },
      {
        "description": "Denies the set_simple_fullscreen command without any pre-configured scope.",
        "type": "string",
        "const": "core:window:deny-set-simple-fullscreen",
        "markdownDescription": "Denies the set_simple_fullscreen command without any pre-configured scope."
      },
      {
        "description": "Denies the set_size command without any pre-configured scope.",
        "type": "string",
        "const": "core:window:deny-set-size",
        "markdownDescription": "Denies the set_size command without any pre-configured scope."
      },
      {
        "description": "Denies the set_size_constraints command without any pre-configured scope.",
        "type": "string",
        "const": "core:window:deny-set-size-constraints",
        "markdownDescription": "Denies the set_size_constraints command without any pre-configured scope."
      },
      {
        "description": "Denies the set_skip_taskbar command without any pre-configured scope.",
        "type": "string",
        "const": "core:window:deny-set-skip-taskbar",
        "markdownDescription": "Denies the set_skip_taskbar command without any pre-configured scope."
      },
      {
        "description": "Denies the set_theme command without any pre-configured scope.",
        "type": "string",
        "const": "core:window:deny-set-theme",
        "markdownDescription": "Denies the set_theme command without any pre-configured scope."
      },
      {
        "description": "Denies the set_title command without any pre-configured scope.",
        "type": "string",
        "const": "core:window:deny-set-title",
        "markdownDescription": "Denies the set_title command without any pre-configured scope."
      },
      {
        "description": "Denies the set_title_bar_style command without any pre-configured scope.",
        "type": "string",
        "const": "core:window:deny-set-title-bar-style",
        "markdownDescription": "Denies the set_title_bar_style command without any pre-configured scope."
      },
      {
        "description": "Denies the set_visible_on_all_workspaces command without any pre-configured scope.",
```

```
      "type": "string",
      "const": "core:window:deny-set-visible-on-all-workspaces",
      "markdownDescription": "Denies the set_visible_on_all_workspaces command without any pre-configured scope
    },
    {
      "description": "Denies the show command without any pre-configured scope.",
      "type": "string",
      "const": "core:window:deny-show",
      "markdownDescription": "Denies the show command without any pre-configured scope."
    },
    {
      "description": "Denies the start_dragging command without any pre-configured scope.",
      "type": "string",
      "const": "core:window:deny-start-dragging",
      "markdownDescription": "Denies the start_dragging command without any pre-configured scope."
    },
    {
      "description": "Denies the start_resize_dragging command without any pre-configured scope.",
      "type": "string",
      "const": "core:window:deny-start-resize-dragging",
      "markdownDescription": "Denies the start_resize_dragging command without any pre-configured scope."
    },
    {
      "description": "Denies the theme command without any pre-configured scope.",
      "type": "string",
      "const": "core:window:deny-theme",
      "markdownDescription": "Denies the theme command without any pre-configured scope."
    },
    {
      "description": "Denies the title command without any pre-configured scope.",
      "type": "string",
      "const": "core:window:deny-title",
      "markdownDescription": "Denies the title command without any pre-configured scope."
    },
    {
      "description": "Denies the toggle_maximize command without any pre-configured scope.",
      "type": "string",
      "const": "core:window:deny-toggle-maximize",
      "markdownDescription": "Denies the toggle_maximize command without any pre-configured scope."
    },
    {
      "description": "Denies the unmaximize command without any pre-configured scope.",
      "type": "string",
      "const": "core:window:deny-unmaximize",
      "markdownDescription": "Denies the unmaximize command without any pre-configured scope."
    },
    {
      "description": "Denies the unminimize command without any pre-configured scope.",
      "type": "string",
      "const": "core:window:deny-unminimize",
      "markdownDescription": "Denies the unminimize command without any pre-configured scope."
    },
    {
      "description": "This permission set configures the types of dialogs\navailable from the dialog plugin.\n\
      "type": "string",
      "const": "dialog:default",
      "markdownDescription": "This permission set configures the types of dialogs\navailable from the dialog pl
    },
    {
      "description": "Enables the ask command without any pre-configured scope. (**DEPRECATED**: This is now an
      "type": "string",
      "const": "dialog:allow-ask",
      "markdownDescription": "Enables the ask command without any pre-configured scope. (**DEPRECATED**: This i
    },
    {
      "description": "Enables the confirm command without any pre-configured scope. (**DEPRECATED**: This is no
      "type": "string",
      "const": "dialog:allow-confirm",
      "markdownDescription": "Enables the confirm command without any pre-configured scope. (**DEPRECATED**: Th
    },
    {
      "description": "Enables the message command without any pre-configured scope.",
      "type": "string",
      "const": "dialog:allow-message",
      "markdownDescription": "Enables the message command without any pre-configured scope."
    },
    {
      "description": "Enables the open command without any pre-configured scope.",
      "type": "string",
      "const": "dialog:allow-open",
      "markdownDescription": "Enables the open command without any pre-configured scope."
```

```
      },
      {
        "description": "Enables the save command without any pre-configured scope.",
        "type": "string",
        "const": "dialog:allow-save",
        "markdownDescription": "Enables the save command without any pre-configured scope."
      },
      {
        "description": "Denies the ask command without any pre-configured scope. (**DEPRECATED**: This is now an
        "type": "string",
        "const": "dialog:deny-ask",
        "markdownDescription": "Denies the ask command without any pre-configured scope. (**DEPRECATED**: This is
      },
      {
        "description": "Denies the confirm command without any pre-configured scope. (**DEPRECATED**: This is now
        "type": "string",
        "const": "dialog:deny-confirm",
        "markdownDescription": "Denies the confirm command without any pre-configured scope. (**DEPRECATED**: Thi
      },
      {
        "description": "Denies the message command without any pre-configured scope.",
        "type": "string",
        "const": "dialog:deny-message",
        "markdownDescription": "Denies the message command without any pre-configured scope."
      },
      {
        "description": "Denies the open command without any pre-configured scope.",
        "type": "string",
        "const": "dialog:deny-open",
        "markdownDescription": "Denies the open command without any pre-configured scope."
      },
      {
        "description": "Denies the save command without any pre-configured scope.",
        "type": "string",
        "const": "dialog:deny-save",
        "markdownDescription": "Denies the save command without any pre-configured scope."
      },
      {
        "description": "This permission set allows opening `mailto:`, `tel:`, `https://` and `http://` urls using
        "type": "string",
        "const": "opener:default",
        "markdownDescription": "This permission set allows opening `mailto:`, `tel:`, `https://` and `http://` ur
      },
      {
        "description": "This enables opening `mailto:`, `tel:`, `https://` and `http://` urls using their default
        "type": "string",
        "const": "opener:allow-default-urls",
        "markdownDescription": "This enables opening `mailto:`, `tel:`, `https://` and `http://` urls using their
      },
      {
        "description": "Enables the open_path command without any pre-configured scope.",
        "type": "string",
        "const": "opener:allow-open-path",
        "markdownDescription": "Enables the open_path command without any pre-configured scope."
      },
      {
        "description": "Enables the open_url command without any pre-configured scope.",
        "type": "string",
        "const": "opener:allow-open-url",
        "markdownDescription": "Enables the open_url command without any pre-configured scope."
      },
      {
        "description": "Enables the reveal_item_in_dir command without any pre-configured scope.",
        "type": "string",
        "const": "opener:allow-reveal-item-in-dir",
        "markdownDescription": "Enables the reveal_item_in_dir command without any pre-configured scope."
      },
      {
        "description": "Denies the open_path command without any pre-configured scope.",
        "type": "string",
        "const": "opener:deny-open-path",
        "markdownDescription": "Denies the open_path command without any pre-configured scope."
      },
      {
        "description": "Denies the open_url command without any pre-configured scope.",
        "type": "string",
        "const": "opener:deny-open-url",
        "markdownDescription": "Denies the open_url command without any pre-configured scope."
      },
      {
        "description": "Denies the reveal_item_in_dir command without any pre-configured scope.",
```

```
          "type": "string",
          "const": "opener:deny-reveal-item-in-dir",
          "markdownDescription": "Denies the reveal_item_in_dir command without any pre-configured scope."
        }
      ]
    },
    "Value": {
      "description": "All supported ACL values.",
      "anyOf": [
        {
          "description": "Represents a null JSON value.",
          "type": "null"
        },
        {
          "description": "Represents a [`bool`].",
          "type": "boolean"
        },
        {
          "description": "Represents a valid ACL [`Number`].",
          "allOf": [
            {
              "$ref": "#/definitions/Number"
            }
          ]
        },
        {
          "description": "Represents a [`String`].",
          "type": "string"
        },
        {
          "description": "Represents a list of other [`Value`]s.",
          "type": "array",
          "items": {
            "$ref": "#/definitions/Value"
          }
        },
        {
          "description": "Represents a map of [`String`] keys to [`Value`]s.",
          "type": "object",
          "additionalProperties": {
            "$ref": "#/definitions/Value"
          }
        }
      ]
    },
    "Number": {
      "description": "A valid ACL number.",
      "anyOf": [
        {
          "description": "Represents an [`i64`].",
          "type": "integer",
          "format": "int64"
        },
        {
          "description": "Represents a [`f64`].",
          "type": "number",
          "format": "double"
        }
      ]
    },
    "Target": {
      "description": "Platform target.",
      "oneOf": [
        {
          "description": "MacOS.",
          "type": "string",
          "enum": [
            "macOS"
          ]
        },
        {
          "description": "Windows.",
          "type": "string",
          "enum": [
            "windows"
          ]
        },
        {
          "description": "Linux.",
          "type": "string",
          "enum": [
```

```
              "linux"
            ]
          },
          {
            "description": "Android.",
            "type": "string",
            "enum": [
              "android"
            ]
          },
          {
            "description": "iOS.",
            "type": "string",
            "enum": [
              "iOS"
            ]
          }
        ]
      },
      "Application": {
        "description": "Opener scope application.",
        "anyOf": [
          {
            "description": "Open in default application.",
            "type": "null"
          },
          {
            "description": "If true, allow open with any application.",
            "type": "boolean"
          },
          {
            "description": "Allow specific application to open with.",
            "type": "string"
          }
        ]
      }
    }
}
```

## windows-schema.json

F:\Tools\CodeZipper\src-tauri\gen\schemas\windows-schema.json

```
{
  "$schema": "http://json-schema.org/draft-07/schema#",
  "title": "CapabilityFile",
  "description": "Capability formats accepted in a capability file.",
  "anyOf": [
    {
      "description": "A single capability.",
      "allOf": [
        {
          "$ref": "#/definitions/Capability"
        }
      ]
    },
    {
      "description": "A list of capabilities.",
      "type": "array",
      "items": {
        "$ref": "#/definitions/Capability"
      }
    },
    {
      "description": "A list of capabilities.",
      "type": "object",
      "required": [
        "capabilities"
      ],
      "properties": {
        "capabilities": {
          "description": "The list of capabilities.",
          "type": "array",
          "items": {
            "$ref": "#/definitions/Capability"
          }
        }
      }
    }
  ],
  "definitions": {
```

```
  "Capability": {
    "description": "A grouping and boundary mechanism developers can use to isolate access to the IPC layer.\n\nI
    "type": "object",
    "required": [
      "identifier",
      "permissions"
    ],
    "properties": {
      "identifier": {
        "description": "Identifier of the capability.\n\n## Example\n\n`main-user-files-write`",
        "type": "string"
      },
      "description": {
        "description": "Description of what the capability is intended to allow on associated windows.\n\nIt shou
        "default": "",
        "type": "string"
      },
      "remote": {
        "description": "Configure remote URLs that can use the capability permissions.\n\nThis setting is optiona
        "anyOf": [
          {
            "$ref": "#/definitions/CapabilityRemote"
          },
          {
            "type": "null"
          }
        ]
      },
      "local": {
        "description": "Whether this capability is enabled for local app URLs or not. Defaults to `true`.",
        "default": true,
        "type": "boolean"
      },
      "windows": {
        "description": "List of windows that are affected by this capability. Can be a glob pattern.\n\nIf a wind
        "type": "array",
        "items": {
          "type": "string"
        }
      },
      "webviews": {
        "description": "List of webviews that are affected by this capability. Can be a glob pattern.\n\nThe capa
        "type": "array",
        "items": {
          "type": "string"
        }
      },
      "permissions": {
        "description": "List of permissions attached to this capability.\n\nMust include the plugin name as prefi
        "type": "array",
        "items": {
          "$ref": "#/definitions/PermissionEntry"
        },
        "uniqueItems": true
      },
      "platforms": {
        "description": "Limit which target platforms this capability applies to.\n\nBy default all platforms are
        "type": [
          "array",
          "null"
        ],
        "items": {
          "$ref": "#/definitions/Target"
        }
      }
    }
  },
  "CapabilityRemote": {
    "description": "Configuration for remote URLs that are associated with the capability.",
    "type": "object",
    "required": [
      "urls"
    ],
    "properties": {
      "urls": {
        "description": "Remote domains this capability refers to using the [URLPattern standard](https://urlpatte
        "type": "array",
        "items": {
          "type": "string"
        }
      }
```

```
    }
  },
  "PermissionEntry": {
    "description": "An entry for a permission value in a [`Capability`] can be either a raw permission [`Identifi
    "anyOf": [
      {
        "description": "Reference a permission or permission set by identifier.",
        "allOf": [
          {
            "$ref": "#/definitions/Identifier"
          }
        ]
      },
      {
        "description": "Reference a permission or permission set by identifier and extends its scope.",
        "type": "object",
        "allOf": [
          {
            "if": {
              "properties": {
                "identifier": {
                  "anyOf": [
                    {
                      "description": "This permission set allows opening `mailto:`, `tel:`, `https://` and `http:
                      "type": "string",
                      "const": "opener:default",
                      "markdownDescription": "This permission set allows opening `mailto:`, `tel:`, `https://` an
                    },
                    {
                      "description": "This enables opening `mailto:`, `tel:`, `https://` and `http://` urls using
                      "type": "string",
                      "const": "opener:allow-default-urls",
                      "markdownDescription": "This enables opening `mailto:`, `tel:`, `https://` and `http://` ur
                    },
                    {
                      "description": "Enables the open_path command without any pre-configured scope.",
                      "type": "string",
                      "const": "opener:allow-open-path",
                      "markdownDescription": "Enables the open_path command without any pre-configured scope."
                    },
                    {
                      "description": "Enables the open_url command without any pre-configured scope.",
                      "type": "string",
                      "const": "opener:allow-open-url",
                      "markdownDescription": "Enables the open_url command without any pre-configured scope."
                    },
                    {
                      "description": "Enables the reveal_item_in_dir command without any pre-configured scope.",
                      "type": "string",
                      "const": "opener:allow-reveal-item-in-dir",
                      "markdownDescription": "Enables the reveal_item_in_dir command without any pre-configured s
                    },
                    {
                      "description": "Denies the open_path command without any pre-configured scope.",
                      "type": "string",
                      "const": "opener:deny-open-path",
                      "markdownDescription": "Denies the open_path command without any pre-configured scope."
                    },
                    {
                      "description": "Denies the open_url command without any pre-configured scope.",
                      "type": "string",
                      "const": "opener:deny-open-url",
                      "markdownDescription": "Denies the open_url command without any pre-configured scope."
                    },
                    {
                      "description": "Denies the reveal_item_in_dir command without any pre-configured scope.",
                      "type": "string",
                      "const": "opener:deny-reveal-item-in-dir",
                      "markdownDescription": "Denies the reveal_item_in_dir command without any pre-configured sc
                    }
                  ]
                }
              }
            },
            "then": {
              "properties": {
                "allow": {
                  "items": {
                    "title": "OpenerScopeEntry",
                    "description": "Opener scope entry.",
                    "anyOf": [
```

```
                    {
                      "type": "object",
                      "required": [
                        "url"
                      ],
                      "properties": {
                        "app": {
                          "description": "An application to open this url with, for example: firefox.",
                          "allOf": [
                            {
                              "$ref": "#/definitions/Application"
                            }
                          ]
                        },
                        "url": {
                          "description": "A URL that can be opened by the webview when using the Opener APIs.\n
                          "type": "string"
                        }
                      }
                    },
                    {
                      "type": "object",
                      "required": [
                        "path"
                      ],
                      "properties": {
                        "app": {
                          "description": "An application to open this path with, for example: xdg-open.",
                          "allOf": [
                            {
                              "$ref": "#/definitions/Application"
                            }
                          ]
                        },
                        "path": {
                          "description": "A path that can be opened by the webview when using the Opener APIs.\
                          "type": "string"
                        }
                      }
                    }
                  ]
                }
              },
              "deny": {
                "items": {
                  "title": "OpenerScopeEntry",
                  "description": "Opener scope entry.",
                  "anyOf": [
                    {
                      "type": "object",
                      "required": [
                        "url"
                      ],
                      "properties": {
                        "app": {
                          "description": "An application to open this url with, for example: firefox.",
                          "allOf": [
                            {
                              "$ref": "#/definitions/Application"
                            }
                          ]
                        },
                        "url": {
                          "description": "A URL that can be opened by the webview when using the Opener APIs.\n
                          "type": "string"
                        }
                      }
                    },
                    {
                      "type": "object",
                      "required": [
                        "path"
                      ],
                      "properties": {
                        "app": {
                          "description": "An application to open this path with, for example: xdg-open.",
                          "allOf": [
                            {
                              "$ref": "#/definitions/Application"
                            }
                          ]
```

```
                          },
                          "path": {
                            "description": "A path that can be opened by the webview when using the Opener APIs.\
                            "type": "string"
                          }
                        }
                      }
                    ]
                  }
                }
              }
            },
            "properties": {
              "identifier": {
                "description": "Identifier of the permission or permission set.",
                "allOf": [
                  {
                    "$ref": "#/definitions/Identifier"
                  }
                ]
              }
            }
          },
          {
            "properties": {
              "identifier": {
                "description": "Identifier of the permission or permission set.",
                "allOf": [
                  {
                    "$ref": "#/definitions/Identifier"
                  }
                ]
              },
              "allow": {
                "description": "Data that defines what is allowed by the scope.",
                "type": [
                  "array",
                  "null"
                ],
                "items": {
                  "$ref": "#/definitions/Value"
                }
              },
              "deny": {
                "description": "Data that defines what is denied by the scope. This should be prioritized by vali
                "type": [
                  "array",
                  "null"
                ],
                "items": {
                  "$ref": "#/definitions/Value"
                }
              }
            }
          }
        ],
        "required": [
          "identifier"
        ]
      }
    ]
  },
  "Identifier": {
    "description": "Permission identifier",
    "oneOf": [
      {
        "description": "Default core plugins set.\n#### This default permission set includes:\n\n- `core:path:def
        "type": "string",
        "const": "core:default",
        "markdownDescription": "Default core plugins set.\n#### This default permission set includes:\n\n- `core:
      },
      {
        "description": "Default permissions for the plugin.\n#### This default permission set includes:\n\n- `all
        "type": "string",
        "const": "core:app:default",
        "markdownDescription": "Default permissions for the plugin.\n#### This default permission set includes:\n
      },
      {
        "description": "Enables the app_hide command without any pre-configured scope.",
        "type": "string",
        "const": "core:app:allow-app-hide",
```

```
      "markdownDescription": "Enables the app_hide command without any pre-configured scope."
    },
    {
      "description": "Enables the app_show command without any pre-configured scope.",
      "type": "string",
      "const": "core:app:allow-app-show",
      "markdownDescription": "Enables the app_show command without any pre-configured scope."
    },
    {
      "description": "Enables the bundle_type command without any pre-configured scope.",
      "type": "string",
      "const": "core:app:allow-bundle-type",
      "markdownDescription": "Enables the bundle_type command without any pre-configured scope."
    },
    {
      "description": "Enables the default_window_icon command without any pre-configured scope.",
      "type": "string",
      "const": "core:app:allow-default-window-icon",
      "markdownDescription": "Enables the default_window_icon command without any pre-configured scope."
    },
    {
      "description": "Enables the exit command without any pre-configured scope.",
      "type": "string",
      "const": "core:app:allow-exit",
      "markdownDescription": "Enables the exit command without any pre-configured scope."
    },
    {
      "description": "Enables the fetch_data_store_identifiers command without any pre-configured scope.",
      "type": "string",
      "const": "core:app:allow-fetch-data-store-identifiers",
      "markdownDescription": "Enables the fetch_data_store_identifiers command without any pre-configured scope
    },
    {
      "description": "Enables the identifier command without any pre-configured scope.",
      "type": "string",
      "const": "core:app:allow-identifier",
      "markdownDescription": "Enables the identifier command without any pre-configured scope."
    },
    {
      "description": "Enables the name command without any pre-configured scope.",
      "type": "string",
      "const": "core:app:allow-name",
      "markdownDescription": "Enables the name command without any pre-configured scope."
    },
    {
      "description": "Enables the register_listener command without any pre-configured scope.",
      "type": "string",
      "const": "core:app:allow-register-listener",
      "markdownDescription": "Enables the register_listener command without any pre-configured scope."
    },
    {
      "description": "Enables the remove_data_store command without any pre-configured scope.",
      "type": "string",
      "const": "core:app:allow-remove-data-store",
      "markdownDescription": "Enables the remove_data_store command without any pre-configured scope."
    },
    {
      "description": "Enables the remove_listener command without any pre-configured scope.",
      "type": "string",
      "const": "core:app:allow-remove-listener",
      "markdownDescription": "Enables the remove_listener command without any pre-configured scope."
    },
    {
      "description": "Enables the set_app_theme command without any pre-configured scope.",
      "type": "string",
      "const": "core:app:allow-set-app-theme",
      "markdownDescription": "Enables the set_app_theme command without any pre-configured scope."
    },
    {
      "description": "Enables the set_dock_visibility command without any pre-configured scope.",
      "type": "string",
      "const": "core:app:allow-set-dock-visibility",
      "markdownDescription": "Enables the set_dock_visibility command without any pre-configured scope."
    },
    {
      "description": "Enables the supports_multiple_windows command without any pre-configured scope.",
      "type": "string",
      "const": "core:app:allow-supports-multiple-windows",
      "markdownDescription": "Enables the supports_multiple_windows command without any pre-configured scope."
    },
    {
```

```
      "description": "Enables the tauri_version command without any pre-configured scope.",
      "type": "string",
      "const": "core:app:allow-tauri-version",
      "markdownDescription": "Enables the tauri_version command without any pre-configured scope."
    },
    {
      "description": "Enables the version command without any pre-configured scope.",
      "type": "string",
      "const": "core:app:allow-version",
      "markdownDescription": "Enables the version command without any pre-configured scope."
    },
    {
      "description": "Denies the app_hide command without any pre-configured scope.",
      "type": "string",
      "const": "core:app:deny-app-hide",
      "markdownDescription": "Denies the app_hide command without any pre-configured scope."
    },
    {
      "description": "Denies the app_show command without any pre-configured scope.",
      "type": "string",
      "const": "core:app:deny-app-show",
      "markdownDescription": "Denies the app_show command without any pre-configured scope."
    },
    {
      "description": "Denies the bundle_type command without any pre-configured scope.",
      "type": "string",
      "const": "core:app:deny-bundle-type",
      "markdownDescription": "Denies the bundle_type command without any pre-configured scope."
    },
    {
      "description": "Denies the default_window_icon command without any pre-configured scope.",
      "type": "string",
      "const": "core:app:deny-default-window-icon",
      "markdownDescription": "Denies the default_window_icon command without any pre-configured scope."
    },
    {
      "description": "Denies the exit command without any pre-configured scope.",
      "type": "string",
      "const": "core:app:deny-exit",
      "markdownDescription": "Denies the exit command without any pre-configured scope."
    },
    {
      "description": "Denies the fetch_data_store_identifiers command without any pre-configured scope.",
      "type": "string",
      "const": "core:app:deny-fetch-data-store-identifiers",
      "markdownDescription": "Denies the fetch_data_store_identifiers command without any pre-configured scope.
    },
    {
      "description": "Denies the identifier command without any pre-configured scope.",
      "type": "string",
      "const": "core:app:deny-identifier",
      "markdownDescription": "Denies the identifier command without any pre-configured scope."
    },
    {
      "description": "Denies the name command without any pre-configured scope.",
      "type": "string",
      "const": "core:app:deny-name",
      "markdownDescription": "Denies the name command without any pre-configured scope."
    },
    {
      "description": "Denies the register_listener command without any pre-configured scope.",
      "type": "string",
      "const": "core:app:deny-register-listener",
      "markdownDescription": "Denies the register_listener command without any pre-configured scope."
    },
    {
      "description": "Denies the remove_data_store command without any pre-configured scope.",
      "type": "string",
      "const": "core:app:deny-remove-data-store",
      "markdownDescription": "Denies the remove_data_store command without any pre-configured scope."
    },
    {
      "description": "Denies the remove_listener command without any pre-configured scope.",
      "type": "string",
      "const": "core:app:deny-remove-listener",
      "markdownDescription": "Denies the remove_listener command without any pre-configured scope."
    },
    {
      "description": "Denies the set_app_theme command without any pre-configured scope.",
      "type": "string",
      "const": "core:app:deny-set-app-theme",
```

```
      "markdownDescription": "Denies the set_app_theme command without any pre-configured scope."
    },
    {
      "description": "Denies the set_dock_visibility command without any pre-configured scope.",
      "type": "string",
      "const": "core:app:deny-set-dock-visibility",
      "markdownDescription": "Denies the set_dock_visibility command without any pre-configured scope."
    },
    {
      "description": "Denies the supports_multiple_windows command without any pre-configured scope.",
      "type": "string",
      "const": "core:app:deny-supports-multiple-windows",
      "markdownDescription": "Denies the supports_multiple_windows command without any pre-configured scope."
    },
    {
      "description": "Denies the tauri_version command without any pre-configured scope.",
      "type": "string",
      "const": "core:app:deny-tauri-version",
      "markdownDescription": "Denies the tauri_version command without any pre-configured scope."
    },
    {
      "description": "Denies the version command without any pre-configured scope.",
      "type": "string",
      "const": "core:app:deny-version",
      "markdownDescription": "Denies the version command without any pre-configured scope."
    },
    {
      "description": "Default permissions for the plugin, which enables all commands.\n#### This default permis
      "type": "string",
      "const": "core:event:default",
      "markdownDescription": "Default permissions for the plugin, which enables all commands.\n#### This defaul
    },
    {
      "description": "Enables the emit command without any pre-configured scope.",
      "type": "string",
      "const": "core:event:allow-emit",
      "markdownDescription": "Enables the emit command without any pre-configured scope."
    },
    {
      "description": "Enables the emit_to command without any pre-configured scope.",
      "type": "string",
      "const": "core:event:allow-emit-to",
      "markdownDescription": "Enables the emit_to command without any pre-configured scope."
    },
    {
      "description": "Enables the listen command without any pre-configured scope.",
      "type": "string",
      "const": "core:event:allow-listen",
      "markdownDescription": "Enables the listen command without any pre-configured scope."
    },
    {
      "description": "Enables the unlisten command without any pre-configured scope.",
      "type": "string",
      "const": "core:event:allow-unlisten",
      "markdownDescription": "Enables the unlisten command without any pre-configured scope."
    },
    {
      "description": "Denies the emit command without any pre-configured scope.",
      "type": "string",
      "const": "core:event:deny-emit",
      "markdownDescription": "Denies the emit command without any pre-configured scope."
    },
    {
      "description": "Denies the emit_to command without any pre-configured scope.",
      "type": "string",
      "const": "core:event:deny-emit-to",
      "markdownDescription": "Denies the emit_to command without any pre-configured scope."
    },
    {
      "description": "Denies the listen command without any pre-configured scope.",
      "type": "string",
      "const": "core:event:deny-listen",
      "markdownDescription": "Denies the listen command without any pre-configured scope."
    },
    {
      "description": "Denies the unlisten command without any pre-configured scope.",
      "type": "string",
      "const": "core:event:deny-unlisten",
      "markdownDescription": "Denies the unlisten command without any pre-configured scope."
    },
    {
```

```
      "description": "Default permissions for the plugin, which enables all commands.\n#### This default permis
      "type": "string",
      "const": "core:image:default",
      "markdownDescription": "Default permissions for the plugin, which enables all commands.\n#### This defaul
    },
    {
      "description": "Enables the from_bytes command without any pre-configured scope.",
      "type": "string",
      "const": "core:image:allow-from-bytes",
      "markdownDescription": "Enables the from_bytes command without any pre-configured scope."
    },
    {
      "description": "Enables the from_path command without any pre-configured scope.",
      "type": "string",
      "const": "core:image:allow-from-path",
      "markdownDescription": "Enables the from_path command without any pre-configured scope."
    },
    {
      "description": "Enables the new command without any pre-configured scope.",
      "type": "string",
      "const": "core:image:allow-new",
      "markdownDescription": "Enables the new command without any pre-configured scope."
    },
    {
      "description": "Enables the rgba command without any pre-configured scope.",
      "type": "string",
      "const": "core:image:allow-rgba",
      "markdownDescription": "Enables the rgba command without any pre-configured scope."
    },
    {
      "description": "Enables the size command without any pre-configured scope.",
      "type": "string",
      "const": "core:image:allow-size",
      "markdownDescription": "Enables the size command without any pre-configured scope."
    },
    {
      "description": "Denies the from_bytes command without any pre-configured scope.",
      "type": "string",
      "const": "core:image:deny-from-bytes",
      "markdownDescription": "Denies the from_bytes command without any pre-configured scope."
    },
    {
      "description": "Denies the from_path command without any pre-configured scope.",
      "type": "string",
      "const": "core:image:deny-from-path",
      "markdownDescription": "Denies the from_path command without any pre-configured scope."
    },
    {
      "description": "Denies the new command without any pre-configured scope.",
      "type": "string",
      "const": "core:image:deny-new",
      "markdownDescription": "Denies the new command without any pre-configured scope."
    },
    {
      "description": "Denies the rgba command without any pre-configured scope.",
      "type": "string",
      "const": "core:image:deny-rgba",
      "markdownDescription": "Denies the rgba command without any pre-configured scope."
    },
    {
      "description": "Denies the size command without any pre-configured scope.",
      "type": "string",
      "const": "core:image:deny-size",
      "markdownDescription": "Denies the size command without any pre-configured scope."
    },
    {
      "description": "Default permissions for the plugin, which enables all commands.\n#### This default permis
      "type": "string",
      "const": "core:menu:default",
      "markdownDescription": "Default permissions for the plugin, which enables all commands.\n#### This defaul
    },
    {
      "description": "Enables the append command without any pre-configured scope.",
      "type": "string",
      "const": "core:menu:allow-append",
      "markdownDescription": "Enables the append command without any pre-configured scope."
    },
    {
      "description": "Enables the create_default command without any pre-configured scope.",
      "type": "string",
      "const": "core:menu:allow-create-default",
```

```
        "markdownDescription": "Enables the create_default command without any pre-configured scope."
      },
      {
        "description": "Enables the get command without any pre-configured scope.",
        "type": "string",
        "const": "core:menu:allow-get",
        "markdownDescription": "Enables the get command without any pre-configured scope."
      },
      {
        "description": "Enables the insert command without any pre-configured scope.",
        "type": "string",
        "const": "core:menu:allow-insert",
        "markdownDescription": "Enables the insert command without any pre-configured scope."
      },
      {
        "description": "Enables the is_checked command without any pre-configured scope.",
        "type": "string",
        "const": "core:menu:allow-is-checked",
        "markdownDescription": "Enables the is_checked command without any pre-configured scope."
      },
      {
        "description": "Enables the is_enabled command without any pre-configured scope.",
        "type": "string",
        "const": "core:menu:allow-is-enabled",
        "markdownDescription": "Enables the is_enabled command without any pre-configured scope."
      },
      {
        "description": "Enables the items command without any pre-configured scope.",
        "type": "string",
        "const": "core:menu:allow-items",
        "markdownDescription": "Enables the items command without any pre-configured scope."
      },
      {
        "description": "Enables the new command without any pre-configured scope.",
        "type": "string",
        "const": "core:menu:allow-new",
        "markdownDescription": "Enables the new command without any pre-configured scope."
      },
      {
        "description": "Enables the popup command without any pre-configured scope.",
        "type": "string",
        "const": "core:menu:allow-popup",
        "markdownDescription": "Enables the popup command without any pre-configured scope."
      },
      {
        "description": "Enables the prepend command without any pre-configured scope.",
        "type": "string",
        "const": "core:menu:allow-prepend",
        "markdownDescription": "Enables the prepend command without any pre-configured scope."
      },
      {
        "description": "Enables the remove command without any pre-configured scope.",
        "type": "string",
        "const": "core:menu:allow-remove",
        "markdownDescription": "Enables the remove command without any pre-configured scope."
      },
      {
        "description": "Enables the remove_at command without any pre-configured scope.",
        "type": "string",
        "const": "core:menu:allow-remove-at",
        "markdownDescription": "Enables the remove_at command without any pre-configured scope."
      },
      {
        "description": "Enables the set_accelerator command without any pre-configured scope.",
        "type": "string",
        "const": "core:menu:allow-set-accelerator",
        "markdownDescription": "Enables the set_accelerator command without any pre-configured scope."
      },
      {
        "description": "Enables the set_as_app_menu command without any pre-configured scope.",
        "type": "string",
        "const": "core:menu:allow-set-as-app-menu",
        "markdownDescription": "Enables the set_as_app_menu command without any pre-configured scope."
      },
      {
        "description": "Enables the set_as_help_menu_for_nsapp command without any pre-configured scope.",
        "type": "string",
        "const": "core:menu:allow-set-as-help-menu-for-nsapp",
        "markdownDescription": "Enables the set_as_help_menu_for_nsapp command without any pre-configured scope."
      },
      {
```

```
      "description": "Enables the set_as_window_menu command without any pre-configured scope.",
      "type": "string",
      "const": "core:menu:allow-set-as-window-menu",
      "markdownDescription": "Enables the set_as_window_menu command without any pre-configured scope."
    },
    {
      "description": "Enables the set_as_windows_menu_for_nsapp command without any pre-configured scope.",
      "type": "string",
      "const": "core:menu:allow-set-as-windows-menu-for-nsapp",
      "markdownDescription": "Enables the set_as_windows_menu_for_nsapp command without any pre-configured scop
    },
    {
      "description": "Enables the set_checked command without any pre-configured scope.",
      "type": "string",
      "const": "core:menu:allow-set-checked",
      "markdownDescription": "Enables the set_checked command without any pre-configured scope."
    },
    {
      "description": "Enables the set_enabled command without any pre-configured scope.",
      "type": "string",
      "const": "core:menu:allow-set-enabled",
      "markdownDescription": "Enables the set_enabled command without any pre-configured scope."
    },
    {
      "description": "Enables the set_icon command without any pre-configured scope.",
      "type": "string",
      "const": "core:menu:allow-set-icon",
      "markdownDescription": "Enables the set_icon command without any pre-configured scope."
    },
    {
      "description": "Enables the set_text command without any pre-configured scope.",
      "type": "string",
      "const": "core:menu:allow-set-text",
      "markdownDescription": "Enables the set_text command without any pre-configured scope."
    },
    {
      "description": "Enables the text command without any pre-configured scope.",
      "type": "string",
      "const": "core:menu:allow-text",
      "markdownDescription": "Enables the text command without any pre-configured scope."
    },
    {
      "description": "Denies the append command without any pre-configured scope.",
      "type": "string",
      "const": "core:menu:deny-append",
      "markdownDescription": "Denies the append command without any pre-configured scope."
    },
    {
      "description": "Denies the create_default command without any pre-configured scope.",
      "type": "string",
      "const": "core:menu:deny-create-default",
      "markdownDescription": "Denies the create_default command without any pre-configured scope."
    },
    {
      "description": "Denies the get command without any pre-configured scope.",
      "type": "string",
      "const": "core:menu:deny-get",
      "markdownDescription": "Denies the get command without any pre-configured scope."
    },
    {
      "description": "Denies the insert command without any pre-configured scope.",
      "type": "string",
      "const": "core:menu:deny-insert",
      "markdownDescription": "Denies the insert command without any pre-configured scope."
    },
    {
      "description": "Denies the is_checked command without any pre-configured scope.",
      "type": "string",
      "const": "core:menu:deny-is-checked",
      "markdownDescription": "Denies the is_checked command without any pre-configured scope."
    },
    {
      "description": "Denies the is_enabled command without any pre-configured scope.",
      "type": "string",
      "const": "core:menu:deny-is-enabled",
      "markdownDescription": "Denies the is_enabled command without any pre-configured scope."
    },
    {
      "description": "Denies the items command without any pre-configured scope.",
      "type": "string",
      "const": "core:menu:deny-items",
```

```
      "markdownDescription": "Denies the items command without any pre-configured scope."
    },
    {
      "description": "Denies the new command without any pre-configured scope.",
      "type": "string",
      "const": "core:menu:deny-new",
      "markdownDescription": "Denies the new command without any pre-configured scope."
    },
    {
      "description": "Denies the popup command without any pre-configured scope.",
      "type": "string",
      "const": "core:menu:deny-popup",
      "markdownDescription": "Denies the popup command without any pre-configured scope."
    },
    {
      "description": "Denies the prepend command without any pre-configured scope.",
      "type": "string",
      "const": "core:menu:deny-prepend",
      "markdownDescription": "Denies the prepend command without any pre-configured scope."
    },
    {
      "description": "Denies the remove command without any pre-configured scope.",
      "type": "string",
      "const": "core:menu:deny-remove",
      "markdownDescription": "Denies the remove command without any pre-configured scope."
    },
    {
      "description": "Denies the remove_at command without any pre-configured scope.",
      "type": "string",
      "const": "core:menu:deny-remove-at",
      "markdownDescription": "Denies the remove_at command without any pre-configured scope."
    },
    {
      "description": "Denies the set_accelerator command without any pre-configured scope.",
      "type": "string",
      "const": "core:menu:deny-set-accelerator",
      "markdownDescription": "Denies the set_accelerator command without any pre-configured scope."
    },
    {
      "description": "Denies the set_as_app_menu command without any pre-configured scope.",
      "type": "string",
      "const": "core:menu:deny-set-as-app-menu",
      "markdownDescription": "Denies the set_as_app_menu command without any pre-configured scope."
    },
    {
      "description": "Denies the set_as_help_menu_for_nsapp command without any pre-configured scope.",
      "type": "string",
      "const": "core:menu:deny-set-as-help-menu-for-nsapp",
      "markdownDescription": "Denies the set_as_help_menu_for_nsapp command without any pre-configured scope."
    },
    {
      "description": "Denies the set_as_window_menu command without any pre-configured scope.",
      "type": "string",
      "const": "core:menu:deny-set-as-window-menu",
      "markdownDescription": "Denies the set_as_window_menu command without any pre-configured scope."
    },
    {
      "description": "Denies the set_as_windows_menu_for_nsapp command without any pre-configured scope.",
      "type": "string",
      "const": "core:menu:deny-set-as-windows-menu-for-nsapp",
      "markdownDescription": "Denies the set_as_windows_menu_for_nsapp command without any pre-configured scope
    },
    {
      "description": "Denies the set_checked command without any pre-configured scope.",
      "type": "string",
      "const": "core:menu:deny-set-checked",
      "markdownDescription": "Denies the set_checked command without any pre-configured scope."
    },
    {
      "description": "Denies the set_enabled command without any pre-configured scope.",
      "type": "string",
      "const": "core:menu:deny-set-enabled",
      "markdownDescription": "Denies the set_enabled command without any pre-configured scope."
    },
    {
      "description": "Denies the set_icon command without any pre-configured scope.",
      "type": "string",
      "const": "core:menu:deny-set-icon",
      "markdownDescription": "Denies the set_icon command without any pre-configured scope."
    },
    {
```

```
      "description": "Denies the set_text command without any pre-configured scope.",
      "type": "string",
      "const": "core:menu:deny-set-text",
      "markdownDescription": "Denies the set_text command without any pre-configured scope."
    },
    {
      "description": "Denies the text command without any pre-configured scope.",
      "type": "string",
      "const": "core:menu:deny-text",
      "markdownDescription": "Denies the text command without any pre-configured scope."
    },
    {
      "description": "Default permissions for the plugin, which enables all commands.\n#### This default permis
      "type": "string",
      "const": "core:path:default",
      "markdownDescription": "Default permissions for the plugin, which enables all commands.\n#### This defaul
    },
    {
      "description": "Enables the basename command without any pre-configured scope.",
      "type": "string",
      "const": "core:path:allow-basename",
      "markdownDescription": "Enables the basename command without any pre-configured scope."
    },
    {
      "description": "Enables the dirname command without any pre-configured scope.",
      "type": "string",
      "const": "core:path:allow-dirname",
      "markdownDescription": "Enables the dirname command without any pre-configured scope."
    },
    {
      "description": "Enables the extname command without any pre-configured scope.",
      "type": "string",
      "const": "core:path:allow-extname",
      "markdownDescription": "Enables the extname command without any pre-configured scope."
    },
    {
      "description": "Enables the is_absolute command without any pre-configured scope.",
      "type": "string",
      "const": "core:path:allow-is-absolute",
      "markdownDescription": "Enables the is_absolute command without any pre-configured scope."
    },
    {
      "description": "Enables the join command without any pre-configured scope.",
      "type": "string",
      "const": "core:path:allow-join",
      "markdownDescription": "Enables the join command without any pre-configured scope."
    },
    {
      "description": "Enables the normalize command without any pre-configured scope.",
      "type": "string",
      "const": "core:path:allow-normalize",
      "markdownDescription": "Enables the normalize command without any pre-configured scope."
    },
    {
      "description": "Enables the resolve command without any pre-configured scope.",
      "type": "string",
      "const": "core:path:allow-resolve",
      "markdownDescription": "Enables the resolve command without any pre-configured scope."
    },
    {
      "description": "Enables the resolve_directory command without any pre-configured scope.",
      "type": "string",
      "const": "core:path:allow-resolve-directory",
      "markdownDescription": "Enables the resolve_directory command without any pre-configured scope."
    },
    {
      "description": "Denies the basename command without any pre-configured scope.",
      "type": "string",
      "const": "core:path:deny-basename",
      "markdownDescription": "Denies the basename command without any pre-configured scope."
    },
    {
      "description": "Denies the dirname command without any pre-configured scope.",
      "type": "string",
      "const": "core:path:deny-dirname",
      "markdownDescription": "Denies the dirname command without any pre-configured scope."
    },
    {
      "description": "Denies the extname command without any pre-configured scope.",
      "type": "string",
      "const": "core:path:deny-extname",
```

```
      "markdownDescription": "Denies the extname command without any pre-configured scope."
    },
    {
      "description": "Denies the is_absolute command without any pre-configured scope.",
      "type": "string",
      "const": "core:path:deny-is-absolute",
      "markdownDescription": "Denies the is_absolute command without any pre-configured scope."
    },
    {
      "description": "Denies the join command without any pre-configured scope.",
      "type": "string",
      "const": "core:path:deny-join",
      "markdownDescription": "Denies the join command without any pre-configured scope."
    },
    {
      "description": "Denies the normalize command without any pre-configured scope.",
      "type": "string",
      "const": "core:path:deny-normalize",
      "markdownDescription": "Denies the normalize command without any pre-configured scope."
    },
    {
      "description": "Denies the resolve command without any pre-configured scope.",
      "type": "string",
      "const": "core:path:deny-resolve",
      "markdownDescription": "Denies the resolve command without any pre-configured scope."
    },
    {
      "description": "Denies the resolve_directory command without any pre-configured scope.",
      "type": "string",
      "const": "core:path:deny-resolve-directory",
      "markdownDescription": "Denies the resolve_directory command without any pre-configured scope."
    },
    {
      "description": "Default permissions for the plugin, which enables all commands.\n#### This default permis
      "type": "string",
      "const": "core:resources:default",
      "markdownDescription": "Default permissions for the plugin, which enables all commands.\n#### This defaul
    },
    {
      "description": "Enables the close command without any pre-configured scope.",
      "type": "string",
      "const": "core:resources:allow-close",
      "markdownDescription": "Enables the close command without any pre-configured scope."
    },
    {
      "description": "Denies the close command without any pre-configured scope.",
      "type": "string",
      "const": "core:resources:deny-close",
      "markdownDescription": "Denies the close command without any pre-configured scope."
    },
    {
      "description": "Default permissions for the plugin, which enables all commands.\n#### This default permis
      "type": "string",
      "const": "core:tray:default",
      "markdownDescription": "Default permissions for the plugin, which enables all commands.\n#### This defaul
    },
    {
      "description": "Enables the get_by_id command without any pre-configured scope.",
      "type": "string",
      "const": "core:tray:allow-get-by-id",
      "markdownDescription": "Enables the get_by_id command without any pre-configured scope."
    },
    {
      "description": "Enables the new command without any pre-configured scope.",
      "type": "string",
      "const": "core:tray:allow-new",
      "markdownDescription": "Enables the new command without any pre-configured scope."
    },
    {
      "description": "Enables the remove_by_id command without any pre-configured scope.",
      "type": "string",
      "const": "core:tray:allow-remove-by-id",
      "markdownDescription": "Enables the remove_by_id command without any pre-configured scope."
    },
    {
      "description": "Enables the set_icon command without any pre-configured scope.",
      "type": "string",
      "const": "core:tray:allow-set-icon",
      "markdownDescription": "Enables the set_icon command without any pre-configured scope."
    },
    {
```

```
      "description": "Enables the set_icon_as_template command without any pre-configured scope.",
      "type": "string",
      "const": "core:tray:allow-set-icon-as-template",
      "markdownDescription": "Enables the set_icon_as_template command without any pre-configured scope."
    },
    {
      "description": "Enables the set_icon_with_as_template command without any pre-configured scope.",
      "type": "string",
      "const": "core:tray:allow-set-icon-with-as-template",
      "markdownDescription": "Enables the set_icon_with_as_template command without any pre-configured scope."
    },
    {
      "description": "Enables the set_menu command without any pre-configured scope.",
      "type": "string",
      "const": "core:tray:allow-set-menu",
      "markdownDescription": "Enables the set_menu command without any pre-configured scope."
    },
    {
      "description": "Enables the set_show_menu_on_left_click command without any pre-configured scope.",
      "type": "string",
      "const": "core:tray:allow-set-show-menu-on-left-click",
      "markdownDescription": "Enables the set_show_menu_on_left_click command without any pre-configured scope.
    },
    {
      "description": "Enables the set_temp_dir_path command without any pre-configured scope.",
      "type": "string",
      "const": "core:tray:allow-set-temp-dir-path",
      "markdownDescription": "Enables the set_temp_dir_path command without any pre-configured scope."
    },
    {
      "description": "Enables the set_title command without any pre-configured scope.",
      "type": "string",
      "const": "core:tray:allow-set-title",
      "markdownDescription": "Enables the set_title command without any pre-configured scope."
    },
    {
      "description": "Enables the set_tooltip command without any pre-configured scope.",
      "type": "string",
      "const": "core:tray:allow-set-tooltip",
      "markdownDescription": "Enables the set_tooltip command without any pre-configured scope."
    },
    {
      "description": "Enables the set_visible command without any pre-configured scope.",
      "type": "string",
      "const": "core:tray:allow-set-visible",
      "markdownDescription": "Enables the set_visible command without any pre-configured scope."
    },
    {
      "description": "Denies the get_by_id command without any pre-configured scope.",
      "type": "string",
      "const": "core:tray:deny-get-by-id",
      "markdownDescription": "Denies the get_by_id command without any pre-configured scope."
    },
    {
      "description": "Denies the new command without any pre-configured scope.",
      "type": "string",
      "const": "core:tray:deny-new",
      "markdownDescription": "Denies the new command without any pre-configured scope."
    },
    {
      "description": "Denies the remove_by_id command without any pre-configured scope.",
      "type": "string",
      "const": "core:tray:deny-remove-by-id",
      "markdownDescription": "Denies the remove_by_id command without any pre-configured scope."
    },
    {
      "description": "Denies the set_icon command without any pre-configured scope.",
      "type": "string",
      "const": "core:tray:deny-set-icon",
      "markdownDescription": "Denies the set_icon command without any pre-configured scope."
    },
    {
      "description": "Denies the set_icon_as_template command without any pre-configured scope.",
      "type": "string",
      "const": "core:tray:deny-set-icon-as-template",
      "markdownDescription": "Denies the set_icon_as_template command without any pre-configured scope."
    },
    {
      "description": "Denies the set_icon_with_as_template command without any pre-configured scope.",
      "type": "string",
      "const": "core:tray:deny-set-icon-with-as-template",
```

```
      "markdownDescription": "Denies the set_icon_with_as_template command without any pre-configured scope."
    },
    {
      "description": "Denies the set_menu command without any pre-configured scope.",
      "type": "string",
      "const": "core:tray:deny-set-menu",
      "markdownDescription": "Denies the set_menu command without any pre-configured scope."
    },
    {
      "description": "Denies the set_show_menu_on_left_click command without any pre-configured scope.",
      "type": "string",
      "const": "core:tray:deny-set-show-menu-on-left-click",
      "markdownDescription": "Denies the set_show_menu_on_left_click command without any pre-configured scope."
    },
    {
      "description": "Denies the set_temp_dir_path command without any pre-configured scope.",
      "type": "string",
      "const": "core:tray:deny-set-temp-dir-path",
      "markdownDescription": "Denies the set_temp_dir_path command without any pre-configured scope."
    },
    {
      "description": "Denies the set_title command without any pre-configured scope.",
      "type": "string",
      "const": "core:tray:deny-set-title",
      "markdownDescription": "Denies the set_title command without any pre-configured scope."
    },
    {
      "description": "Denies the set_tooltip command without any pre-configured scope.",
      "type": "string",
      "const": "core:tray:deny-set-tooltip",
      "markdownDescription": "Denies the set_tooltip command without any pre-configured scope."
    },
    {
      "description": "Denies the set_visible command without any pre-configured scope.",
      "type": "string",
      "const": "core:tray:deny-set-visible",
      "markdownDescription": "Denies the set_visible command without any pre-configured scope."
    },
    {
      "description": "Default permissions for the plugin.\n#### This default permission set includes:\n\n- `all
      "type": "string",
      "const": "core:webview:default",
      "markdownDescription": "Default permissions for the plugin.\n#### This default permission set includes:\n
    },
    {
      "description": "Enables the clear_all_browsing_data command without any pre-configured scope.",
      "type": "string",
      "const": "core:webview:allow-clear-all-browsing-data",
      "markdownDescription": "Enables the clear_all_browsing_data command without any pre-configured scope."
    },
    {
      "description": "Enables the create_webview command without any pre-configured scope.",
      "type": "string",
      "const": "core:webview:allow-create-webview",
      "markdownDescription": "Enables the create_webview command without any pre-configured scope."
    },
    {
      "description": "Enables the create_webview_window command without any pre-configured scope.",
      "type": "string",
      "const": "core:webview:allow-create-webview-window",
      "markdownDescription": "Enables the create_webview_window command without any pre-configured scope."
    },
    {
      "description": "Enables the get_all_webviews command without any pre-configured scope.",
      "type": "string",
      "const": "core:webview:allow-get-all-webviews",
      "markdownDescription": "Enables the get_all_webviews command without any pre-configured scope."
    },
    {
      "description": "Enables the internal_toggle_devtools command without any pre-configured scope.",
      "type": "string",
      "const": "core:webview:allow-internal-toggle-devtools",
      "markdownDescription": "Enables the internal_toggle_devtools command without any pre-configured scope."
    },
    {
      "description": "Enables the print command without any pre-configured scope.",
      "type": "string",
      "const": "core:webview:allow-print",
      "markdownDescription": "Enables the print command without any pre-configured scope."
    },
    {
```

```
      "description": "Enables the reparent command without any pre-configured scope.",
      "type": "string",
      "const": "core:webview:allow-reparent",
      "markdownDescription": "Enables the reparent command without any pre-configured scope."
    },
    {
      "description": "Enables the set_webview_auto_resize command without any pre-configured scope.",
      "type": "string",
      "const": "core:webview:allow-set-webview-auto-resize",
      "markdownDescription": "Enables the set_webview_auto_resize command without any pre-configured scope."
    },
    {
      "description": "Enables the set_webview_background_color command without any pre-configured scope.",
      "type": "string",
      "const": "core:webview:allow-set-webview-background-color",
      "markdownDescription": "Enables the set_webview_background_color command without any pre-configured scope
    },
    {
      "description": "Enables the set_webview_focus command without any pre-configured scope.",
      "type": "string",
      "const": "core:webview:allow-set-webview-focus",
      "markdownDescription": "Enables the set_webview_focus command without any pre-configured scope."
    },
    {
      "description": "Enables the set_webview_position command without any pre-configured scope.",
      "type": "string",
      "const": "core:webview:allow-set-webview-position",
      "markdownDescription": "Enables the set_webview_position command without any pre-configured scope."
    },
    {
      "description": "Enables the set_webview_size command without any pre-configured scope.",
      "type": "string",
      "const": "core:webview:allow-set-webview-size",
      "markdownDescription": "Enables the set_webview_size command without any pre-configured scope."
    },
    {
      "description": "Enables the set_webview_zoom command without any pre-configured scope.",
      "type": "string",
      "const": "core:webview:allow-set-webview-zoom",
      "markdownDescription": "Enables the set_webview_zoom command without any pre-configured scope."
    },
    {
      "description": "Enables the webview_close command without any pre-configured scope.",
      "type": "string",
      "const": "core:webview:allow-webview-close",
      "markdownDescription": "Enables the webview_close command without any pre-configured scope."
    },
    {
      "description": "Enables the webview_hide command without any pre-configured scope.",
      "type": "string",
      "const": "core:webview:allow-webview-hide",
      "markdownDescription": "Enables the webview_hide command without any pre-configured scope."
    },
    {
      "description": "Enables the webview_position command without any pre-configured scope.",
      "type": "string",
      "const": "core:webview:allow-webview-position",
      "markdownDescription": "Enables the webview_position command without any pre-configured scope."
    },
    {
      "description": "Enables the webview_show command without any pre-configured scope.",
      "type": "string",
      "const": "core:webview:allow-webview-show",
      "markdownDescription": "Enables the webview_show command without any pre-configured scope."
    },
    {
      "description": "Enables the webview_size command without any pre-configured scope.",
      "type": "string",
      "const": "core:webview:allow-webview-size",
      "markdownDescription": "Enables the webview_size command without any pre-configured scope."
    },
    {
      "description": "Denies the clear_all_browsing_data command without any pre-configured scope.",
      "type": "string",
      "const": "core:webview:deny-clear-all-browsing-data",
      "markdownDescription": "Denies the clear_all_browsing_data command without any pre-configured scope."
    },
    {
      "description": "Denies the create_webview command without any pre-configured scope.",
      "type": "string",
      "const": "core:webview:deny-create-webview",
```

```
      "markdownDescription": "Denies the create_webview command without any pre-configured scope."
    },
    {
      "description": "Denies the create_webview_window command without any pre-configured scope.",
      "type": "string",
      "const": "core:webview:deny-create-webview-window",
      "markdownDescription": "Denies the create_webview_window command without any pre-configured scope."
    },
    {
      "description": "Denies the get_all_webviews command without any pre-configured scope.",
      "type": "string",
      "const": "core:webview:deny-get-all-webviews",
      "markdownDescription": "Denies the get_all_webviews command without any pre-configured scope."
    },
    {
      "description": "Denies the internal_toggle_devtools command without any pre-configured scope.",
      "type": "string",
      "const": "core:webview:deny-internal-toggle-devtools",
      "markdownDescription": "Denies the internal_toggle_devtools command without any pre-configured scope."
    },
    {
      "description": "Denies the print command without any pre-configured scope.",
      "type": "string",
      "const": "core:webview:deny-print",
      "markdownDescription": "Denies the print command without any pre-configured scope."
    },
    {
      "description": "Denies the reparent command without any pre-configured scope.",
      "type": "string",
      "const": "core:webview:deny-reparent",
      "markdownDescription": "Denies the reparent command without any pre-configured scope."
    },
    {
      "description": "Denies the set_webview_auto_resize command without any pre-configured scope.",
      "type": "string",
      "const": "core:webview:deny-set-webview-auto-resize",
      "markdownDescription": "Denies the set_webview_auto_resize command without any pre-configured scope."
    },
    {
      "description": "Denies the set_webview_background_color command without any pre-configured scope.",
      "type": "string",
      "const": "core:webview:deny-set-webview-background-color",
      "markdownDescription": "Denies the set_webview_background_color command without any pre-configured scope.
    },
    {
      "description": "Denies the set_webview_focus command without any pre-configured scope.",
      "type": "string",
      "const": "core:webview:deny-set-webview-focus",
      "markdownDescription": "Denies the set_webview_focus command without any pre-configured scope."
    },
    {
      "description": "Denies the set_webview_position command without any pre-configured scope.",
      "type": "string",
      "const": "core:webview:deny-set-webview-position",
      "markdownDescription": "Denies the set_webview_position command without any pre-configured scope."
    },
    {
      "description": "Denies the set_webview_size command without any pre-configured scope.",
      "type": "string",
      "const": "core:webview:deny-set-webview-size",
      "markdownDescription": "Denies the set_webview_size command without any pre-configured scope."
    },
    {
      "description": "Denies the set_webview_zoom command without any pre-configured scope.",
      "type": "string",
      "const": "core:webview:deny-set-webview-zoom",
      "markdownDescription": "Denies the set_webview_zoom command without any pre-configured scope."
    },
    {
      "description": "Denies the webview_close command without any pre-configured scope.",
      "type": "string",
      "const": "core:webview:deny-webview-close",
      "markdownDescription": "Denies the webview_close command without any pre-configured scope."
    },
    {
      "description": "Denies the webview_hide command without any pre-configured scope.",
      "type": "string",
      "const": "core:webview:deny-webview-hide",
      "markdownDescription": "Denies the webview_hide command without any pre-configured scope."
    },
    {
```

```
      "description": "Denies the webview_position command without any pre-configured scope.",
      "type": "string",
      "const": "core:webview:deny-webview-position",
      "markdownDescription": "Denies the webview_position command without any pre-configured scope."
    },
    {
      "description": "Denies the webview_show command without any pre-configured scope.",
      "type": "string",
      "const": "core:webview:deny-webview-show",
      "markdownDescription": "Denies the webview_show command without any pre-configured scope."
    },
    {
      "description": "Denies the webview_size command without any pre-configured scope.",
      "type": "string",
      "const": "core:webview:deny-webview-size",
      "markdownDescription": "Denies the webview_size command without any pre-configured scope."
    },
    {
      "description": "Default permissions for the plugin.\n#### This default permission set includes:\n\n- `all
      "type": "string",
      "const": "core:window:default",
      "markdownDescription": "Default permissions for the plugin.\n#### This default permission set includes:\n
    },
    {
      "description": "Enables the activity_name command without any pre-configured scope.",
      "type": "string",
      "const": "core:window:allow-activity-name",
      "markdownDescription": "Enables the activity_name command without any pre-configured scope."
    },
    {
      "description": "Enables the available_monitors command without any pre-configured scope.",
      "type": "string",
      "const": "core:window:allow-available-monitors",
      "markdownDescription": "Enables the available_monitors command without any pre-configured scope."
    },
    {
      "description": "Enables the center command without any pre-configured scope.",
      "type": "string",
      "const": "core:window:allow-center",
      "markdownDescription": "Enables the center command without any pre-configured scope."
    },
    {
      "description": "Enables the close command without any pre-configured scope.",
      "type": "string",
      "const": "core:window:allow-close",
      "markdownDescription": "Enables the close command without any pre-configured scope."
    },
    {
      "description": "Enables the create command without any pre-configured scope.",
      "type": "string",
      "const": "core:window:allow-create",
      "markdownDescription": "Enables the create command without any pre-configured scope."
    },
    {
      "description": "Enables the current_monitor command without any pre-configured scope.",
      "type": "string",
      "const": "core:window:allow-current-monitor",
      "markdownDescription": "Enables the current_monitor command without any pre-configured scope."
    },
    {
      "description": "Enables the cursor_position command without any pre-configured scope.",
      "type": "string",
      "const": "core:window:allow-cursor-position",
      "markdownDescription": "Enables the cursor_position command without any pre-configured scope."
    },
    {
      "description": "Enables the destroy command without any pre-configured scope.",
      "type": "string",
      "const": "core:window:allow-destroy",
      "markdownDescription": "Enables the destroy command without any pre-configured scope."
    },
    {
      "description": "Enables the get_all_windows command without any pre-configured scope.",
      "type": "string",
      "const": "core:window:allow-get-all-windows",
      "markdownDescription": "Enables the get_all_windows command without any pre-configured scope."
    },
    {
      "description": "Enables the hide command without any pre-configured scope.",
      "type": "string",
      "const": "core:window:allow-hide",
```

```
      "markdownDescription": "Enables the hide command without any pre-configured scope."
    },
    {
      "description": "Enables the inner_position command without any pre-configured scope.",
      "type": "string",
      "const": "core:window:allow-inner-position",
      "markdownDescription": "Enables the inner_position command without any pre-configured scope."
    },
    {
      "description": "Enables the inner_size command without any pre-configured scope.",
      "type": "string",
      "const": "core:window:allow-inner-size",
      "markdownDescription": "Enables the inner_size command without any pre-configured scope."
    },
    {
      "description": "Enables the internal_toggle_maximize command without any pre-configured scope.",
      "type": "string",
      "const": "core:window:allow-internal-toggle-maximize",
      "markdownDescription": "Enables the internal_toggle_maximize command without any pre-configured scope."
    },
    {
      "description": "Enables the is_always_on_top command without any pre-configured scope.",
      "type": "string",
      "const": "core:window:allow-is-always-on-top",
      "markdownDescription": "Enables the is_always_on_top command without any pre-configured scope."
    },
    {
      "description": "Enables the is_closable command without any pre-configured scope.",
      "type": "string",
      "const": "core:window:allow-is-closable",
      "markdownDescription": "Enables the is_closable command without any pre-configured scope."
    },
    {
      "description": "Enables the is_decorated command without any pre-configured scope.",
      "type": "string",
      "const": "core:window:allow-is-decorated",
      "markdownDescription": "Enables the is_decorated command without any pre-configured scope."
    },
    {
      "description": "Enables the is_enabled command without any pre-configured scope.",
      "type": "string",
      "const": "core:window:allow-is-enabled",
      "markdownDescription": "Enables the is_enabled command without any pre-configured scope."
    },
    {
      "description": "Enables the is_focused command without any pre-configured scope.",
      "type": "string",
      "const": "core:window:allow-is-focused",
      "markdownDescription": "Enables the is_focused command without any pre-configured scope."
    },
    {
      "description": "Enables the is_fullscreen command without any pre-configured scope.",
      "type": "string",
      "const": "core:window:allow-is-fullscreen",
      "markdownDescription": "Enables the is_fullscreen command without any pre-configured scope."
    },
    {
      "description": "Enables the is_maximizable command without any pre-configured scope.",
      "type": "string",
      "const": "core:window:allow-is-maximizable",
      "markdownDescription": "Enables the is_maximizable command without any pre-configured scope."
    },
    {
      "description": "Enables the is_maximized command without any pre-configured scope.",
      "type": "string",
      "const": "core:window:allow-is-maximized",
      "markdownDescription": "Enables the is_maximized command without any pre-configured scope."
    },
    {
      "description": "Enables the is_minimizable command without any pre-configured scope.",
      "type": "string",
      "const": "core:window:allow-is-minimizable",
      "markdownDescription": "Enables the is_minimizable command without any pre-configured scope."
    },
    {
      "description": "Enables the is_minimized command without any pre-configured scope.",
      "type": "string",
      "const": "core:window:allow-is-minimized",
      "markdownDescription": "Enables the is_minimized command without any pre-configured scope."
    },
    {
```

```
      "description": "Enables the is_resizable command without any pre-configured scope.",
      "type": "string",
      "const": "core:window:allow-is-resizable",
      "markdownDescription": "Enables the is_resizable command without any pre-configured scope."
    },
    {
      "description": "Enables the is_visible command without any pre-configured scope.",
      "type": "string",
      "const": "core:window:allow-is-visible",
      "markdownDescription": "Enables the is_visible command without any pre-configured scope."
    },
    {
      "description": "Enables the maximize command without any pre-configured scope.",
      "type": "string",
      "const": "core:window:allow-maximize",
      "markdownDescription": "Enables the maximize command without any pre-configured scope."
    },
    {
      "description": "Enables the minimize command without any pre-configured scope.",
      "type": "string",
      "const": "core:window:allow-minimize",
      "markdownDescription": "Enables the minimize command without any pre-configured scope."
    },
    {
      "description": "Enables the monitor_from_point command without any pre-configured scope.",
      "type": "string",
      "const": "core:window:allow-monitor-from-point",
      "markdownDescription": "Enables the monitor_from_point command without any pre-configured scope."
    },
    {
      "description": "Enables the outer_position command without any pre-configured scope.",
      "type": "string",
      "const": "core:window:allow-outer-position",
      "markdownDescription": "Enables the outer_position command without any pre-configured scope."
    },
    {
      "description": "Enables the outer_size command without any pre-configured scope.",
      "type": "string",
      "const": "core:window:allow-outer-size",
      "markdownDescription": "Enables the outer_size command without any pre-configured scope."
    },
    {
      "description": "Enables the primary_monitor command without any pre-configured scope.",
      "type": "string",
      "const": "core:window:allow-primary-monitor",
      "markdownDescription": "Enables the primary_monitor command without any pre-configured scope."
    },
    {
      "description": "Enables the request_user_attention command without any pre-configured scope.",
      "type": "string",
      "const": "core:window:allow-request-user-attention",
      "markdownDescription": "Enables the request_user_attention command without any pre-configured scope."
    },
    {
      "description": "Enables the scale_factor command without any pre-configured scope.",
      "type": "string",
      "const": "core:window:allow-scale-factor",
      "markdownDescription": "Enables the scale_factor command without any pre-configured scope."
    },
    {
      "description": "Enables the scene_identifier command without any pre-configured scope.",
      "type": "string",
      "const": "core:window:allow-scene-identifier",
      "markdownDescription": "Enables the scene_identifier command without any pre-configured scope."
    },
    {
      "description": "Enables the set_always_on_bottom command without any pre-configured scope.",
      "type": "string",
      "const": "core:window:allow-set-always-on-bottom",
      "markdownDescription": "Enables the set_always_on_bottom command without any pre-configured scope."
    },
    {
      "description": "Enables the set_always_on_top command without any pre-configured scope.",
      "type": "string",
      "const": "core:window:allow-set-always-on-top",
      "markdownDescription": "Enables the set_always_on_top command without any pre-configured scope."
    },
    {
      "description": "Enables the set_background_color command without any pre-configured scope.",
      "type": "string",
      "const": "core:window:allow-set-background-color",
```

```
      "markdownDescription": "Enables the set_background_color command without any pre-configured scope."
    },
    {
      "description": "Enables the set_badge_count command without any pre-configured scope.",
      "type": "string",
      "const": "core:window:allow-set-badge-count",
      "markdownDescription": "Enables the set_badge_count command without any pre-configured scope."
    },
    {
      "description": "Enables the set_badge_label command without any pre-configured scope.",
      "type": "string",
      "const": "core:window:allow-set-badge-label",
      "markdownDescription": "Enables the set_badge_label command without any pre-configured scope."
    },
    {
      "description": "Enables the set_closable command without any pre-configured scope.",
      "type": "string",
      "const": "core:window:allow-set-closable",
      "markdownDescription": "Enables the set_closable command without any pre-configured scope."
    },
    {
      "description": "Enables the set_content_protected command without any pre-configured scope.",
      "type": "string",
      "const": "core:window:allow-set-content-protected",
      "markdownDescription": "Enables the set_content_protected command without any pre-configured scope."
    },
    {
      "description": "Enables the set_cursor_grab command without any pre-configured scope.",
      "type": "string",
      "const": "core:window:allow-set-cursor-grab",
      "markdownDescription": "Enables the set_cursor_grab command without any pre-configured scope."
    },
    {
      "description": "Enables the set_cursor_icon command without any pre-configured scope.",
      "type": "string",
      "const": "core:window:allow-set-cursor-icon",
      "markdownDescription": "Enables the set_cursor_icon command without any pre-configured scope."
    },
    {
      "description": "Enables the set_cursor_position command without any pre-configured scope.",
      "type": "string",
      "const": "core:window:allow-set-cursor-position",
      "markdownDescription": "Enables the set_cursor_position command without any pre-configured scope."
    },
    {
      "description": "Enables the set_cursor_visible command without any pre-configured scope.",
      "type": "string",
      "const": "core:window:allow-set-cursor-visible",
      "markdownDescription": "Enables the set_cursor_visible command without any pre-configured scope."
    },
    {
      "description": "Enables the set_decorations command without any pre-configured scope.",
      "type": "string",
      "const": "core:window:allow-set-decorations",
      "markdownDescription": "Enables the set_decorations command without any pre-configured scope."
    },
    {
      "description": "Enables the set_effects command without any pre-configured scope.",
      "type": "string",
      "const": "core:window:allow-set-effects",
      "markdownDescription": "Enables the set_effects command without any pre-configured scope."
    },
    {
      "description": "Enables the set_enabled command without any pre-configured scope.",
      "type": "string",
      "const": "core:window:allow-set-enabled",
      "markdownDescription": "Enables the set_enabled command without any pre-configured scope."
    },
    {
      "description": "Enables the set_focus command without any pre-configured scope.",
      "type": "string",
      "const": "core:window:allow-set-focus",
      "markdownDescription": "Enables the set_focus command without any pre-configured scope."
    },
    {
      "description": "Enables the set_focusable command without any pre-configured scope.",
      "type": "string",
      "const": "core:window:allow-set-focusable",
      "markdownDescription": "Enables the set_focusable command without any pre-configured scope."
    },
    {
```

```
      "description": "Enables the set_fullscreen command without any pre-configured scope.",
      "type": "string",
      "const": "core:window:allow-set-fullscreen",
      "markdownDescription": "Enables the set_fullscreen command without any pre-configured scope."
    },
    {
      "description": "Enables the set_fullscreen_on_monitor command without any pre-configured scope.",
      "type": "string",
      "const": "core:window:allow-set-fullscreen-on-monitor",
      "markdownDescription": "Enables the set_fullscreen_on_monitor command without any pre-configured scope."
    },
    {
      "description": "Enables the set_icon command without any pre-configured scope.",
      "type": "string",
      "const": "core:window:allow-set-icon",
      "markdownDescription": "Enables the set_icon command without any pre-configured scope."
    },
    {
      "description": "Enables the set_ignore_cursor_events command without any pre-configured scope.",
      "type": "string",
      "const": "core:window:allow-set-ignore-cursor-events",
      "markdownDescription": "Enables the set_ignore_cursor_events command without any pre-configured scope."
    },
    {
      "description": "Enables the set_max_size command without any pre-configured scope.",
      "type": "string",
      "const": "core:window:allow-set-max-size",
      "markdownDescription": "Enables the set_max_size command without any pre-configured scope."
    },
    {
      "description": "Enables the set_maximizable command without any pre-configured scope.",
      "type": "string",
      "const": "core:window:allow-set-maximizable",
      "markdownDescription": "Enables the set_maximizable command without any pre-configured scope."
    },
    {
      "description": "Enables the set_min_size command without any pre-configured scope.",
      "type": "string",
      "const": "core:window:allow-set-min-size",
      "markdownDescription": "Enables the set_min_size command without any pre-configured scope."
    },
    {
      "description": "Enables the set_minimizable command without any pre-configured scope.",
      "type": "string",
      "const": "core:window:allow-set-minimizable",
      "markdownDescription": "Enables the set_minimizable command without any pre-configured scope."
    },
    {
      "description": "Enables the set_overlay_icon command without any pre-configured scope.",
      "type": "string",
      "const": "core:window:allow-set-overlay-icon",
      "markdownDescription": "Enables the set_overlay_icon command without any pre-configured scope."
    },
    {
      "description": "Enables the set_position command without any pre-configured scope.",
      "type": "string",
      "const": "core:window:allow-set-position",
      "markdownDescription": "Enables the set_position command without any pre-configured scope."
    },
    {
      "description": "Enables the set_progress_bar command without any pre-configured scope.",
      "type": "string",
      "const": "core:window:allow-set-progress-bar",
      "markdownDescription": "Enables the set_progress_bar command without any pre-configured scope."
    },
    {
      "description": "Enables the set_resizable command without any pre-configured scope.",
      "type": "string",
      "const": "core:window:allow-set-resizable",
      "markdownDescription": "Enables the set_resizable command without any pre-configured scope."
    },
    {
      "description": "Enables the set_shadow command without any pre-configured scope.",
      "type": "string",
      "const": "core:window:allow-set-shadow",
      "markdownDescription": "Enables the set_shadow command without any pre-configured scope."
    },
    {
      "description": "Enables the set_simple_fullscreen command without any pre-configured scope.",
      "type": "string",
      "const": "core:window:allow-set-simple-fullscreen",
```

```
      "markdownDescription": "Enables the set_simple_fullscreen command without any pre-configured scope."
    },
    {
      "description": "Enables the set_size command without any pre-configured scope.",
      "type": "string",
      "const": "core:window:allow-set-size",
      "markdownDescription": "Enables the set_size command without any pre-configured scope."
    },
    {
      "description": "Enables the set_size_constraints command without any pre-configured scope.",
      "type": "string",
      "const": "core:window:allow-set-size-constraints",
      "markdownDescription": "Enables the set_size_constraints command without any pre-configured scope."
    },
    {
      "description": "Enables the set_skip_taskbar command without any pre-configured scope.",
      "type": "string",
      "const": "core:window:allow-set-skip-taskbar",
      "markdownDescription": "Enables the set_skip_taskbar command without any pre-configured scope."
    },
    {
      "description": "Enables the set_theme command without any pre-configured scope.",
      "type": "string",
      "const": "core:window:allow-set-theme",
      "markdownDescription": "Enables the set_theme command without any pre-configured scope."
    },
    {
      "description": "Enables the set_title command without any pre-configured scope.",
      "type": "string",
      "const": "core:window:allow-set-title",
      "markdownDescription": "Enables the set_title command without any pre-configured scope."
    },
    {
      "description": "Enables the set_title_bar_style command without any pre-configured scope.",
      "type": "string",
      "const": "core:window:allow-set-title-bar-style",
      "markdownDescription": "Enables the set_title_bar_style command without any pre-configured scope."
    },
    {
      "description": "Enables the set_visible_on_all_workspaces command without any pre-configured scope.",
      "type": "string",
      "const": "core:window:allow-set-visible-on-all-workspaces",
      "markdownDescription": "Enables the set_visible_on_all_workspaces command without any pre-configured scop
    },
    {
      "description": "Enables the show command without any pre-configured scope.",
      "type": "string",
      "const": "core:window:allow-show",
      "markdownDescription": "Enables the show command without any pre-configured scope."
    },
    {
      "description": "Enables the start_dragging command without any pre-configured scope.",
      "type": "string",
      "const": "core:window:allow-start-dragging",
      "markdownDescription": "Enables the start_dragging command without any pre-configured scope."
    },
    {
      "description": "Enables the start_resize_dragging command without any pre-configured scope.",
      "type": "string",
      "const": "core:window:allow-start-resize-dragging",
      "markdownDescription": "Enables the start_resize_dragging command without any pre-configured scope."
    },
    {
      "description": "Enables the theme command without any pre-configured scope.",
      "type": "string",
      "const": "core:window:allow-theme",
      "markdownDescription": "Enables the theme command without any pre-configured scope."
    },
    {
      "description": "Enables the title command without any pre-configured scope.",
      "type": "string",
      "const": "core:window:allow-title",
      "markdownDescription": "Enables the title command without any pre-configured scope."
    },
    {
      "description": "Enables the toggle_maximize command without any pre-configured scope.",
      "type": "string",
      "const": "core:window:allow-toggle-maximize",
      "markdownDescription": "Enables the toggle_maximize command without any pre-configured scope."
    },
    {
```

```
      "description": "Enables the unmaximize command without any pre-configured scope.",
      "type": "string",
      "const": "core:window:allow-unmaximize",
      "markdownDescription": "Enables the unmaximize command without any pre-configured scope."
    },
    {
      "description": "Enables the unminimize command without any pre-configured scope.",
      "type": "string",
      "const": "core:window:allow-unminimize",
      "markdownDescription": "Enables the unminimize command without any pre-configured scope."
    },
    {
      "description": "Denies the activity_name command without any pre-configured scope.",
      "type": "string",
      "const": "core:window:deny-activity-name",
      "markdownDescription": "Denies the activity_name command without any pre-configured scope."
    },
    {
      "description": "Denies the available_monitors command without any pre-configured scope.",
      "type": "string",
      "const": "core:window:deny-available-monitors",
      "markdownDescription": "Denies the available_monitors command without any pre-configured scope."
    },
    {
      "description": "Denies the center command without any pre-configured scope.",
      "type": "string",
      "const": "core:window:deny-center",
      "markdownDescription": "Denies the center command without any pre-configured scope."
    },
    {
      "description": "Denies the close command without any pre-configured scope.",
      "type": "string",
      "const": "core:window:deny-close",
      "markdownDescription": "Denies the close command without any pre-configured scope."
    },
    {
      "description": "Denies the create command without any pre-configured scope.",
      "type": "string",
      "const": "core:window:deny-create",
      "markdownDescription": "Denies the create command without any pre-configured scope."
    },
    {
      "description": "Denies the current_monitor command without any pre-configured scope.",
      "type": "string",
      "const": "core:window:deny-current-monitor",
      "markdownDescription": "Denies the current_monitor command without any pre-configured scope."
    },
    {
      "description": "Denies the cursor_position command without any pre-configured scope.",
      "type": "string",
      "const": "core:window:deny-cursor-position",
      "markdownDescription": "Denies the cursor_position command without any pre-configured scope."
    },
    {
      "description": "Denies the destroy command without any pre-configured scope.",
      "type": "string",
      "const": "core:window:deny-destroy",
      "markdownDescription": "Denies the destroy command without any pre-configured scope."
    },
    {
      "description": "Denies the get_all_windows command without any pre-configured scope.",
      "type": "string",
      "const": "core:window:deny-get-all-windows",
      "markdownDescription": "Denies the get_all_windows command without any pre-configured scope."
    },
    {
      "description": "Denies the hide command without any pre-configured scope.",
      "type": "string",
      "const": "core:window:deny-hide",
      "markdownDescription": "Denies the hide command without any pre-configured scope."
    },
    {
      "description": "Denies the inner_position command without any pre-configured scope.",
      "type": "string",
      "const": "core:window:deny-inner-position",
      "markdownDescription": "Denies the inner_position command without any pre-configured scope."
    },
    {
      "description": "Denies the inner_size command without any pre-configured scope.",
      "type": "string",
      "const": "core:window:deny-inner-size",
```

```
      "markdownDescription": "Denies the inner_size command without any pre-configured scope."
    },
    {
      "description": "Denies the internal_toggle_maximize command without any pre-configured scope.",
      "type": "string",
      "const": "core:window:deny-internal-toggle-maximize",
      "markdownDescription": "Denies the internal_toggle_maximize command without any pre-configured scope."
    },
    {
      "description": "Denies the is_always_on_top command without any pre-configured scope.",
      "type": "string",
      "const": "core:window:deny-is-always-on-top",
      "markdownDescription": "Denies the is_always_on_top command without any pre-configured scope."
    },
    {
      "description": "Denies the is_closable command without any pre-configured scope.",
      "type": "string",
      "const": "core:window:deny-is-closable",
      "markdownDescription": "Denies the is_closable command without any pre-configured scope."
    },
    {
      "description": "Denies the is_decorated command without any pre-configured scope.",
      "type": "string",
      "const": "core:window:deny-is-decorated",
      "markdownDescription": "Denies the is_decorated command without any pre-configured scope."
    },
    {
      "description": "Denies the is_enabled command without any pre-configured scope.",
      "type": "string",
      "const": "core:window:deny-is-enabled",
      "markdownDescription": "Denies the is_enabled command without any pre-configured scope."
    },
    {
      "description": "Denies the is_focused command without any pre-configured scope.",
      "type": "string",
      "const": "core:window:deny-is-focused",
      "markdownDescription": "Denies the is_focused command without any pre-configured scope."
    },
    {
      "description": "Denies the is_fullscreen command without any pre-configured scope.",
      "type": "string",
      "const": "core:window:deny-is-fullscreen",
      "markdownDescription": "Denies the is_fullscreen command without any pre-configured scope."
    },
    {
      "description": "Denies the is_maximizable command without any pre-configured scope.",
      "type": "string",
      "const": "core:window:deny-is-maximizable",
      "markdownDescription": "Denies the is_maximizable command without any pre-configured scope."
    },
    {
      "description": "Denies the is_maximized command without any pre-configured scope.",
      "type": "string",
      "const": "core:window:deny-is-maximized",
      "markdownDescription": "Denies the is_maximized command without any pre-configured scope."
    },
    {
      "description": "Denies the is_minimizable command without any pre-configured scope.",
      "type": "string",
      "const": "core:window:deny-is-minimizable",
      "markdownDescription": "Denies the is_minimizable command without any pre-configured scope."
    },
    {
      "description": "Denies the is_minimized command without any pre-configured scope.",
      "type": "string",
      "const": "core:window:deny-is-minimized",
      "markdownDescription": "Denies the is_minimized command without any pre-configured scope."
    },
    {
      "description": "Denies the is_resizable command without any pre-configured scope.",
      "type": "string",
      "const": "core:window:deny-is-resizable",
      "markdownDescription": "Denies the is_resizable command without any pre-configured scope."
    },
    {
      "description": "Denies the is_visible command without any pre-configured scope.",
      "type": "string",
      "const": "core:window:deny-is-visible",
      "markdownDescription": "Denies the is_visible command without any pre-configured scope."
    },
    {
```

```
            "description": "Denies the maximize command without any pre-configured scope.",
            "type": "string",
            "const": "core:window:deny-maximize",
            "markdownDescription": "Denies the maximize command without any pre-configured scope."
          },
          {
            "description": "Denies the minimize command without any pre-configured scope.",
            "type": "string",
            "const": "core:window:deny-minimize",
            "markdownDescription": "Denies the minimize command without any pre-configured scope."
          },
          {
            "description": "Denies the monitor_from_point command without any pre-configured scope.",
            "type": "string",
            "const": "core:window:deny-monitor-from-point",
            "markdownDescription": "Denies the monitor_from_point command without any pre-configured scope."
          },
          {
            "description": "Denies the outer_position command without any pre-configured scope.",
            "type": "string",
            "const": "core:window:deny-outer-position",
            "markdownDescription": "Denies the outer_position command without any pre-configured scope."
          },
          {
            "description": "Denies the outer_size command without any pre-configured scope.",
            "type": "string",
            "const": "core:window:deny-outer-size",
            "markdownDescription": "Denies the outer_size command without any pre-configured scope."
          },
          {
            "description": "Denies the primary_monitor command without any pre-configured scope.",
            "type": "string",
            "const": "core:window:deny-primary-monitor",
            "markdownDescription": "Denies the primary_monitor command without any pre-configured scope."
          },
          {
            "description": "Denies the request_user_attention command without any pre-configured scope.",
            "type": "string",
            "const": "core:window:deny-request-user-attention",
            "markdownDescription": "Denies the request_user_attention command without any pre-configured scope."
          },
          {
            "description": "Denies the scale_factor command without any pre-configured scope.",
            "type": "string",
            "const": "core:window:deny-scale-factor",
            "markdownDescription": "Denies the scale_factor command without any pre-configured scope."
          },
          {
            "description": "Denies the scene_identifier command without any pre-configured scope.",
            "type": "string",
            "const": "core:window:deny-scene-identifier",
            "markdownDescription": "Denies the scene_identifier command without any pre-configured scope."
          },
          {
            "description": "Denies the set_always_on_bottom command without any pre-configured scope.",
            "type": "string",
            "const": "core:window:deny-set-always-on-bottom",
            "markdownDescription": "Denies the set_always_on_bottom command without any pre-configured scope."
          },
          {
            "description": "Denies the set_always_on_top command without any pre-configured scope.",
            "type": "string",
            "const": "core:window:deny-set-always-on-top",
            "markdownDescription": "Denies the set_always_on_top command without any pre-configured scope."
          },
          {
            "description": "Denies the set_background_color command without any pre-configured scope.",
            "type": "string",
            "const": "core:window:deny-set-background-color",
            "markdownDescription": "Denies the set_background_color command without any pre-configured scope."
          },
          {
            "description": "Denies the set_badge_count command without any pre-configured scope.",
            "type": "string",
            "const": "core:window:deny-set-badge-count",
            "markdownDescription": "Denies the set_badge_count command without any pre-configured scope."
          },
          {
            "description": "Denies the set_badge_label command without any pre-configured scope.",
            "type": "string",
            "const": "core:window:deny-set-badge-label",
```

```
      "markdownDescription": "Denies the set_badge_label command without any pre-configured scope."
    },
    {
      "description": "Denies the set_closable command without any pre-configured scope.",
      "type": "string",
      "const": "core:window:deny-set-closable",
      "markdownDescription": "Denies the set_closable command without any pre-configured scope."
    },
    {
      "description": "Denies the set_content_protected command without any pre-configured scope.",
      "type": "string",
      "const": "core:window:deny-set-content-protected",
      "markdownDescription": "Denies the set_content_protected command without any pre-configured scope."
    },
    {
      "description": "Denies the set_cursor_grab command without any pre-configured scope.",
      "type": "string",
      "const": "core:window:deny-set-cursor-grab",
      "markdownDescription": "Denies the set_cursor_grab command without any pre-configured scope."
    },
    {
      "description": "Denies the set_cursor_icon command without any pre-configured scope.",
      "type": "string",
      "const": "core:window:deny-set-cursor-icon",
      "markdownDescription": "Denies the set_cursor_icon command without any pre-configured scope."
    },
    {
      "description": "Denies the set_cursor_position command without any pre-configured scope.",
      "type": "string",
      "const": "core:window:deny-set-cursor-position",
      "markdownDescription": "Denies the set_cursor_position command without any pre-configured scope."
    },
    {
      "description": "Denies the set_cursor_visible command without any pre-configured scope.",
      "type": "string",
      "const": "core:window:deny-set-cursor-visible",
      "markdownDescription": "Denies the set_cursor_visible command without any pre-configured scope."
    },
    {
      "description": "Denies the set_decorations command without any pre-configured scope.",
      "type": "string",
      "const": "core:window:deny-set-decorations",
      "markdownDescription": "Denies the set_decorations command without any pre-configured scope."
    },
    {
      "description": "Denies the set_effects command without any pre-configured scope.",
      "type": "string",
      "const": "core:window:deny-set-effects",
      "markdownDescription": "Denies the set_effects command without any pre-configured scope."
    },
    {
      "description": "Denies the set_enabled command without any pre-configured scope.",
      "type": "string",
      "const": "core:window:deny-set-enabled",
      "markdownDescription": "Denies the set_enabled command without any pre-configured scope."
    },
    {
      "description": "Denies the set_focus command without any pre-configured scope.",
      "type": "string",
      "const": "core:window:deny-set-focus",
      "markdownDescription": "Denies the set_focus command without any pre-configured scope."
    },
    {
      "description": "Denies the set_focusable command without any pre-configured scope.",
      "type": "string",
      "const": "core:window:deny-set-focusable",
      "markdownDescription": "Denies the set_focusable command without any pre-configured scope."
    },
    {
      "description": "Denies the set_fullscreen command without any pre-configured scope.",
      "type": "string",
      "const": "core:window:deny-set-fullscreen",
      "markdownDescription": "Denies the set_fullscreen command without any pre-configured scope."
    },
    {
      "description": "Denies the set_fullscreen_on_monitor command without any pre-configured scope.",
      "type": "string",
      "const": "core:window:deny-set-fullscreen-on-monitor",
      "markdownDescription": "Denies the set_fullscreen_on_monitor command without any pre-configured scope."
    },
    {
```

```
      "description": "Denies the set_icon command without any pre-configured scope.",
      "type": "string",
      "const": "core:window:deny-set-icon",
      "markdownDescription": "Denies the set_icon command without any pre-configured scope."
    },
    {
      "description": "Denies the set_ignore_cursor_events command without any pre-configured scope.",
      "type": "string",
      "const": "core:window:deny-set-ignore-cursor-events",
      "markdownDescription": "Denies the set_ignore_cursor_events command without any pre-configured scope."
    },
    {
      "description": "Denies the set_max_size command without any pre-configured scope.",
      "type": "string",
      "const": "core:window:deny-set-max-size",
      "markdownDescription": "Denies the set_max_size command without any pre-configured scope."
    },
    {
      "description": "Denies the set_maximizable command without any pre-configured scope.",
      "type": "string",
      "const": "core:window:deny-set-maximizable",
      "markdownDescription": "Denies the set_maximizable command without any pre-configured scope."
    },
    {
      "description": "Denies the set_min_size command without any pre-configured scope.",
      "type": "string",
      "const": "core:window:deny-set-min-size",
      "markdownDescription": "Denies the set_min_size command without any pre-configured scope."
    },
    {
      "description": "Denies the set_minimizable command without any pre-configured scope.",
      "type": "string",
      "const": "core:window:deny-set-minimizable",
      "markdownDescription": "Denies the set_minimizable command without any pre-configured scope."
    },
    {
      "description": "Denies the set_overlay_icon command without any pre-configured scope.",
      "type": "string",
      "const": "core:window:deny-set-overlay-icon",
      "markdownDescription": "Denies the set_overlay_icon command without any pre-configured scope."
    },
    {
      "description": "Denies the set_position command without any pre-configured scope.",
      "type": "string",
      "const": "core:window:deny-set-position",
      "markdownDescription": "Denies the set_position command without any pre-configured scope."
    },
    {
      "description": "Denies the set_progress_bar command without any pre-configured scope.",
      "type": "string",
      "const": "core:window:deny-set-progress-bar",
      "markdownDescription": "Denies the set_progress_bar command without any pre-configured scope."
    },
    {
      "description": "Denies the set_resizable command without any pre-configured scope.",
      "type": "string",
      "const": "core:window:deny-set-resizable",
      "markdownDescription": "Denies the set_resizable command without any pre-configured scope."
    },
    {
      "description": "Denies the set_shadow command without any pre-configured scope.",
      "type": "string",
      "const": "core:window:deny-set-shadow",
      "markdownDescription": "Denies the set_shadow command without any pre-configured scope."
    },
    {
      "description": "Denies the set_simple_fullscreen command without any pre-configured scope.",
      "type": "string",
      "const": "core:window:deny-set-simple-fullscreen",
      "markdownDescription": "Denies the set_simple_fullscreen command without any pre-configured scope."
    },
    {
      "description": "Denies the set_size command without any pre-configured scope.",
      "type": "string",
      "const": "core:window:deny-set-size",
      "markdownDescription": "Denies the set_size command without any pre-configured scope."
    },
    {
      "description": "Denies the set_size_constraints command without any pre-configured scope.",
      "type": "string",
      "const": "core:window:deny-set-size-constraints",
```

```
      "markdownDescription": "Denies the set_size_constraints command without any pre-configured scope."
    },
    {
      "description": "Denies the set_skip_taskbar command without any pre-configured scope.",
      "type": "string",
      "const": "core:window:deny-set-skip-taskbar",
      "markdownDescription": "Denies the set_skip_taskbar command without any pre-configured scope."
    },
    {
      "description": "Denies the set_theme command without any pre-configured scope.",
      "type": "string",
      "const": "core:window:deny-set-theme",
      "markdownDescription": "Denies the set_theme command without any pre-configured scope."
    },
    {
      "description": "Denies the set_title command without any pre-configured scope.",
      "type": "string",
      "const": "core:window:deny-set-title",
      "markdownDescription": "Denies the set_title command without any pre-configured scope."
    },
    {
      "description": "Denies the set_title_bar_style command without any pre-configured scope.",
      "type": "string",
      "const": "core:window:deny-set-title-bar-style",
      "markdownDescription": "Denies the set_title_bar_style command without any pre-configured scope."
    },
    {
      "description": "Denies the set_visible_on_all_workspaces command without any pre-configured scope.",
      "type": "string",
      "const": "core:window:deny-set-visible-on-all-workspaces",
      "markdownDescription": "Denies the set_visible_on_all_workspaces command without any pre-configured scope
    },
    {
      "description": "Denies the show command without any pre-configured scope.",
      "type": "string",
      "const": "core:window:deny-show",
      "markdownDescription": "Denies the show command without any pre-configured scope."
    },
    {
      "description": "Denies the start_dragging command without any pre-configured scope.",
      "type": "string",
      "const": "core:window:deny-start-dragging",
      "markdownDescription": "Denies the start_dragging command without any pre-configured scope."
    },
    {
      "description": "Denies the start_resize_dragging command without any pre-configured scope.",
      "type": "string",
      "const": "core:window:deny-start-resize-dragging",
      "markdownDescription": "Denies the start_resize_dragging command without any pre-configured scope."
    },
    {
      "description": "Denies the theme command without any pre-configured scope.",
      "type": "string",
      "const": "core:window:deny-theme",
      "markdownDescription": "Denies the theme command without any pre-configured scope."
    },
    {
      "description": "Denies the title command without any pre-configured scope.",
      "type": "string",
      "const": "core:window:deny-title",
      "markdownDescription": "Denies the title command without any pre-configured scope."
    },
    {
      "description": "Denies the toggle_maximize command without any pre-configured scope.",
      "type": "string",
      "const": "core:window:deny-toggle-maximize",
      "markdownDescription": "Denies the toggle_maximize command without any pre-configured scope."
    },
    {
      "description": "Denies the unmaximize command without any pre-configured scope.",
      "type": "string",
      "const": "core:window:deny-unmaximize",
      "markdownDescription": "Denies the unmaximize command without any pre-configured scope."
    },
    {
      "description": "Denies the unminimize command without any pre-configured scope.",
      "type": "string",
      "const": "core:window:deny-unminimize",
      "markdownDescription": "Denies the unminimize command without any pre-configured scope."
    },
    {
```

```
      "description": "This permission set configures the types of dialogs\navailable from the dialog plugin.\n\
      "type": "string",
      "const": "dialog:default",
      "markdownDescription": "This permission set configures the types of dialogs\navailable from the dialog pl
    },
    {
      "description": "Enables the ask command without any pre-configured scope. (**DEPRECATED**: This is now an
      "type": "string",
      "const": "dialog:allow-ask",
      "markdownDescription": "Enables the ask command without any pre-configured scope. (**DEPRECATED**: This i
    },
    {
      "description": "Enables the confirm command without any pre-configured scope. (**DEPRECATED**: This is no
      "type": "string",
      "const": "dialog:allow-confirm",
      "markdownDescription": "Enables the confirm command without any pre-configured scope. (**DEPRECATED**: Th
    },
    {
      "description": "Enables the message command without any pre-configured scope.",
      "type": "string",
      "const": "dialog:allow-message",
      "markdownDescription": "Enables the message command without any pre-configured scope."
    },
    {
      "description": "Enables the open command without any pre-configured scope.",
      "type": "string",
      "const": "dialog:allow-open",
      "markdownDescription": "Enables the open command without any pre-configured scope."
    },
    {
      "description": "Enables the save command without any pre-configured scope.",
      "type": "string",
      "const": "dialog:allow-save",
      "markdownDescription": "Enables the save command without any pre-configured scope."
    },
    {
      "description": "Denies the ask command without any pre-configured scope. (**DEPRECATED**: This is now an
      "type": "string",
      "const": "dialog:deny-ask",
      "markdownDescription": "Denies the ask command without any pre-configured scope. (**DEPRECATED**: This is
    },
    {
      "description": "Denies the confirm command without any pre-configured scope. (**DEPRECATED**: This is now
      "type": "string",
      "const": "dialog:deny-confirm",
      "markdownDescription": "Denies the confirm command without any pre-configured scope. (**DEPRECATED**: Thi
    },
    {
      "description": "Denies the message command without any pre-configured scope.",
      "type": "string",
      "const": "dialog:deny-message",
      "markdownDescription": "Denies the message command without any pre-configured scope."
    },
    {
      "description": "Denies the open command without any pre-configured scope.",
      "type": "string",
      "const": "dialog:deny-open",
      "markdownDescription": "Denies the open command without any pre-configured scope."
    },
    {
      "description": "Denies the save command without any pre-configured scope.",
      "type": "string",
      "const": "dialog:deny-save",
      "markdownDescription": "Denies the save command without any pre-configured scope."
    },
    {
      "description": "This permission set allows opening `mailto:`, `tel:`, `https://` and `http://` urls using
      "type": "string",
      "const": "opener:default",
      "markdownDescription": "This permission set allows opening `mailto:`, `tel:`, `https://` and `http://` ur
    },
    {
      "description": "This enables opening `mailto:`, `tel:`, `https://` and `http://` urls using their default
      "type": "string",
      "const": "opener:allow-default-urls",
      "markdownDescription": "This enables opening `mailto:`, `tel:`, `https://` and `http://` urls using their
    },
    {
      "description": "Enables the open_path command without any pre-configured scope.",
      "type": "string",
      "const": "opener:allow-open-path",
```

```
          "markdownDescription": "Enables the open_path command without any pre-configured scope."
        },
        {
          "description": "Enables the open_url command without any pre-configured scope.",
          "type": "string",
          "const": "opener:allow-open-url",
          "markdownDescription": "Enables the open_url command without any pre-configured scope."
        },
        {
          "description": "Enables the reveal_item_in_dir command without any pre-configured scope.",
          "type": "string",
          "const": "opener:allow-reveal-item-in-dir",
          "markdownDescription": "Enables the reveal_item_in_dir command without any pre-configured scope."
        },
        {
          "description": "Denies the open_path command without any pre-configured scope.",
          "type": "string",
          "const": "opener:deny-open-path",
          "markdownDescription": "Denies the open_path command without any pre-configured scope."
        },
        {
          "description": "Denies the open_url command without any pre-configured scope.",
          "type": "string",
          "const": "opener:deny-open-url",
          "markdownDescription": "Denies the open_url command without any pre-configured scope."
        },
        {
          "description": "Denies the reveal_item_in_dir command without any pre-configured scope.",
          "type": "string",
          "const": "opener:deny-reveal-item-in-dir",
          "markdownDescription": "Denies the reveal_item_in_dir command without any pre-configured scope."
        }
      ]
    },
    "Value": {
      "description": "All supported ACL values.",
      "anyOf": [
        {
          "description": "Represents a null JSON value.",
          "type": "null"
        },
        {
          "description": "Represents a [`bool`].",
          "type": "boolean"
        },
        {
          "description": "Represents a valid ACL [`Number`].",
          "allOf": [
            {
              "$ref": "#/definitions/Number"
            }
          ]
        },
        {
          "description": "Represents a [`String`].",
          "type": "string"
        },
        {
          "description": "Represents a list of other [`Value`]s.",
          "type": "array",
          "items": {
            "$ref": "#/definitions/Value"
          }
        },
        {
          "description": "Represents a map of [`String`] keys to [`Value`]s.",
          "type": "object",
          "additionalProperties": {
            "$ref": "#/definitions/Value"
          }
        }
      ]
    },
    "Number": {
      "description": "A valid ACL number.",
      "anyOf": [
        {
          "description": "Represents an [`i64`].",
          "type": "integer",
          "format": "int64"
        },
```

```
        {
          "description": "Represents a [`f64`].",
          "type": "number",
          "format": "double"
        }
      ]
    },
    "Target": {
      "description": "Platform target.",
      "oneOf": [
        {
          "description": "MacOS.",
          "type": "string",
          "enum": [
            "macOS"
          ]
        },
        {
          "description": "Windows.",
          "type": "string",
          "enum": [
            "windows"
          ]
        },
        {
          "description": "Linux.",
          "type": "string",
          "enum": [
            "linux"
          ]
        },
        {
          "description": "Android.",
          "type": "string",
          "enum": [
            "android"
          ]
        },
        {
          "description": "iOS.",
          "type": "string",
          "enum": [
            "iOS"
          ]
        }
      ]
    },
    "Application": {
      "description": "Opener scope application.",
      "anyOf": [
        {
          "description": "Open in default application.",
          "type": "null"
        },
        {
          "description": "If true, allow open with any application.",
          "type": "boolean"
        },
        {
          "description": "Allow specific application to open with.",
          "type": "string"
        }
      ]
    }
  }
}
```

## lib.rs

F:\Tools\CodeZipper\src-tauri\src\lib.rs

```
// Learn more about Tauri commands at https://tauri.app/develop/calling-rust/
mod scanner;
mod pdf;

#[cfg_attr(mobile, tauri::mobile_entry_point)]
pub fn run() {
    tauri::Builder::default()
        .plugin(tauri_plugin_opener::init())
        .plugin(tauri_plugin_dialog::init())
        .invoke_handler(tauri::generate_handler![
```

```
            scanner::scan_folder,
            scanner::file_entry,
            scanner::get_recommended_scan_settings,
            pdf::generate_pdf_cmd
        ])
        .run(tauri::generate_context!())
        .expect("error while running tauri application");
}
```

## main.rs

F:\Tools\CodeZipper\src-tauri\src\main.rs

```
// Prevents additional console window on Windows in release, DO NOT REMOVE!!
#![cfg_attr(not(debug_assertions), windows_subsystem = "windows")]

fn main() {
    codezipper_lib::run()
}
```

## pdf.rs

F:\Tools\CodeZipper\src-tauri\src\pdf.rs

```
use printpdf::*;
use std::fs::File;
use std::io::BufWriter;

const PAGE_W: f32 = 210.0;   // A4 mm
const PAGE_H: f32 = 297.0;
const LEFT:   f32 = 15.0;
const RIGHT:  f32 = 195.0;
const BOTTOM: f32 = 20.0;
const LINE_H: f32 = 3.2;

/// Generate a single PDF containing every file with line numbers.
pub fn generate_pdf(output: &str, files: &[String]) -> Result<(), String> {
    let (doc, first_page, first_layer) =
        PdfDocument::new("Djangi Toolbox", Mm(PAGE_W), Mm(PAGE_H), "Content");

    let mono   = doc.add_builtin_font(BuiltinFont::Courier).map_err(|e| e.to_string())?;
    let bold   = doc.add_builtin_font(BuiltinFont::CourierBold).map_err(|e| e.to_string())?;

    let mut layer = doc.get_page(first_page).get_layer(first_layer);
    let mut y = PAGE_H - 20.0;

    // --- Header ---
    layer.use_text("DJANGI TOOLBOX", 14.0, Mm(LEFT), Mm(y), &bold);
    y -= 5.0;
    let subtitle = format!(
        "// SOURCE CODE EXPORT  •  {} file(s)",
        files.len()
    );
    layer.use_text(&subtitle, 7.0, Mm(LEFT), Mm(y), &mono);
    y -= 10.0;

    for path in files {
        let content = match std::fs::read_to_string(path) {
            Ok(c) => c,
            Err(e) => format!("// (unreadable: {e})"),
        };
        let name = std::path::Path::new(path)
            .file_name()
            .map(|s| s.to_string_lossy().to_string())
            .unwrap_or_else(|| path.clone());

        // New page if the header won't fit
        if y < BOTTOM + 20.0 {
            let (p, l) = doc.add_page(Mm(PAGE_W), Mm(PAGE_H), "Content");
            layer = doc.get_page(p).get_layer(l);
            y = PAGE_H - 20.0;
        }

        // File header block
        layer.use_text(&name, 10.0, Mm(LEFT), Mm(y), &bold);
        y -= 4.0;
        layer.use_text(path, 6.0, Mm(LEFT), Mm(y), &mono);
        y -= 6.0;

        for (i, line) in content.lines().enumerate() {
            if y < BOTTOM {
```

```
                let (p, l) = doc.add_page(Mm(PAGE_W), Mm(PAGE_H), "Content");
                layer = doc.get_page(p).get_layer(l);
                y = PAGE_H - 20.0;
            }
            // Truncate — Courier 6pt is ~3.4pt/char  ~110 chars fit
            let truncated: String = line.chars().take(115).collect();
            let text = format!("{:>4}  {}", i + 1, truncated);
            layer.use_text(&text, 6.0, Mm(LEFT), Mm(y), &mono);
            y -= LINE_H;
        }
        y -= 5.0;
    }

    // Avoid "unused" warnings in case truncation is refactored later
    let _ = RIGHT;

    let file = File::create(output).map_err(|e| e.to_string())?;
    doc.save(&mut BufWriter::new(file)).map_err(|e| e.to_string())?;
    Ok(())
}

#[tauri::command]
pub fn generate_pdf_cmd(output: String, files: Vec<String>) -> Result<(), String> {
    generate_pdf(&output, &files)
}
```

## scanner.rs

F:\Tools\CodeZipper\src-tauri\src\scanner.rs

```
use serde::{Deserialize, Serialize};
use std::path::Path;
use walkdir::WalkDir;

// ---------------------------------------------------------------------------
// Models
// ---------------------------------------------------------------------------

#[derive(Serialize, Clone)]
pub struct FileEntry {
    pub path: String,
    pub name: String,
    pub size: u64,
}

#[derive(Deserialize, Default)]
#[serde(rename_all = "camelCase")]
pub struct ScanOptions {
    #[serde(default)]
    pub use_recommended_folders: bool,
    #[serde(default)]
    pub use_recommended_extensions: bool,
    #[serde(default)]
    pub extra_excluded_folders: Vec<String>,
    #[serde(default)]
    pub extra_included_extensions: Vec<String>,
}

#[derive(Serialize)]
#[serde(rename_all = "camelCase")]
pub struct RecommendedScanSettings {
    pub folders: Vec<String>,
    pub extensions: Vec<String>,
}

// ---------------------------------------------------------------------------
// Recommended lists (single source of truth)
// ---------------------------------------------------------------------------

const RECOMMENDED_FOLDERS: &[&str] = &[
    // Build output / caches
    "bin",
    "obj",
    "dist",
    "build",
    "out",
    "target",
    "coverage",
    ".cache",
    ".parcel-cache",
    ".turbo",
```

```
    ".next",
    ".nuxt",
    ".svelte-kit",
    "release",
    "debug",
    // Version control / IDE
    ".git",
    ".svn",
    ".hg",
    ".vs",
    ".vscode",
    ".idea",
    // Package managers
    "node_modules",
    "packages",
    "vendor",
    ".pnpm-store",
    ".yarn",
    // Python
    "__pycache__",
    ".pytest_cache",
    ".mypy_cache",
    ".ruff_cache",
    "venv",
    ".venv",
    "env",
    ".tox",
    "site-packages",
    "*.egg-info",
    // JVM
    ".gradle",
    ".mvn",
    "*.iml",
    // Misc
    "*.log",
    ".terraform",
    ".serverless",
    "tmp",
    "temp",
];

const RECOMMENDED_EXTENSIONS: &[&str] = &[
    // .NET / XAML
    "cs",
    "xaml",
    "axaml",
    "fs",
    "fsx",
    "vb",
    "csproj",
    "fsproj",
    "vbproj",
    "sln",
    "props",
    "targets",
    // Web
    "html",
    "htm",
    "css",
    "scss",
    "sass",
    "less",
    "js",
    "jsx",
    "mjs",
    "cjs",
    "ts",
    "tsx",
    "mts",
    "cts",
    "vue",
    "svelte",
    "astro",
    // Other languages
    "java",
    "kt",
    "kts",
    "scala",
    "go",
    "rs",
    "c",
```

```
    "cpp",
    "cc",
    "cxx",
    "h",
    "hpp",
    "hh",
    "py",
    "rb",
    "php",
    "pl",
    "lua",
    "dart",
    "swift",
    "m",
    "mm",
    // Shell
    "sh",
    "bash",
    "zsh",
    "fish",
    "ps1",
    "psm1",
    "bat",
    "cmd",
    // Config / data
    "json",
    "jsonc",
    "json5",
    "yaml",
    "yml",
    "toml",
    "ini",
    "config",
    "xml",
    "env",
    "properties",
    "gradle",
    // Docs
    "md",
    "mdx",
    "rst",
    "txt",
    "adoc",
    // Data / query
    "sql",
    "prisma",
    "graphql",
    "gql",
    "proto",
    // Templates
    "hbs",
    "handlebars",
    "ejs",
    "pug",
    "mustache",
    "liquid",
    "jinja",
    "jinja2",
];

// ---------------------------------------------------------------------------
// Helpers
// ---------------------------------------------------------------------------

fn normalize_ext(s: &str) -> String {
    s.trim().trim_start_matches('.').to_lowercase()
}

fn entry_for(path: &Path) -> Option<FileEntry> {
    let meta = std::fs::metadata(path).ok()?;
    Some(FileEntry {
        path: path.to_string_lossy().to_string(),
        name: path.file_name()?.to_string_lossy().to_string(),
        size: meta.len(),
    })
}

fn build_skip_list(opts: &ScanOptions) -> Vec<String> {
    let mut out: Vec<String> = Vec::new();
    if opts.use_recommended_folders {
        out.extend(RECOMMENDED_FOLDERS.iter().map(|s| s.to_string()));
```

```
    }
    out.extend(
        opts.extra_excluded_folders
            .iter()
            .map(|s| s.trim().to_string())
            .filter(|s| !s.is_empty()),
    );
    out.iter().map(|s| s.to_lowercase()).collect()
}

fn build_ext_list(opts: &ScanOptions) -> Vec<String> {
    let mut out: Vec<String> = Vec::new();
    if opts.use_recommended_extensions {
        out.extend(RECOMMENDED_EXTENSIONS.iter().map(|s| s.to_string()));
    }
    out.extend(
        opts.extra_included_extensions
            .iter()
            .map(|s| normalize_ext(s))
            .filter(|s| !s.is_empty()),
    );
    out
}

// ---------------------------------------------------------------------------
// Commands
// ---------------------------------------------------------------------------

#[tauri::command]
pub fn get_recommended_scan_settings() -> RecommendedScanSettings {
    RecommendedScanSettings {
        folders: RECOMMENDED_FOLDERS.iter().map(|s| s.to_string()).collect(),
        extensions: RECOMMENDED_EXTENSIONS
            .iter()
            .map(|s| s.to_string())
            .collect(),
    }
}

#[tauri::command]
pub fn scan_folder(root: String, options: Option<ScanOptions>) -> Vec<FileEntry> {
    let opts = options.unwrap_or(ScanOptions {
        use_recommended_folders: true,
        use_recommended_extensions: true,
        ..Default::default()
    });

    let skip = build_skip_list(&opts);
    let exts = build_ext_list(&opts);

    let mut out = Vec::new();

    for entry in WalkDir::new(&root).into_iter().filter_entry(|e| {
        if !e.file_type().is_dir() {
            return true;
        }
        let name = e.file_name().to_string_lossy().to_lowercase();
        !skip.iter().any(|s| {
            // Support simple glob patterns like "*.egg-info"
            if let Some(suffix) = s.strip_prefix('*') {
                name.ends_with(suffix)
            } else {
                name == *s
            }
        })
    }) {
        let Ok(e) = entry else { continue };
        if !e.file_type().is_file() {
            continue;
        }

        let ext = e
            .path()
            .extension()
            .and_then(|s| s.to_str())
            .map(normalize_ext)
            .unwrap_or_default();

        if !exts.iter().any(|c| c == &ext) {
            continue;
        }
```

```
295
296         if let Some(fe) = entry_for(e.path()) {
297             out.push(fe);
298         }
299     }
300
301     out
302 }
303
304 #[tauri::command]
305 pub fn file_entry(path: String) -> Option<FileEntry> {
306     entry_for(Path::new(&path))
307 }
```

## tauri.conf.json

F:\Tools\CodeZipper\src-tauri\tauri.conf.json

```
1  {
2    "$schema": "https://schema.tauri.app/config/2",
3    "productName": "codezipper",
4    "version": "0.1.0",
5    "identifier": "com.aljawi.codezipper",
6    "build": {
7      "beforeDevCommand": "npm run dev",
8      "devUrl": "http://localhost:1420",
9      "beforeBuildCommand": "npm run build",
10     "frontendDist": "../dist"
11   },
12   "app": {
13     "windows": [
14       {
15         "title": "codezipper",
16         "width": 1200,
17         "height": 800,
18         "minWidth": 900,
19         "minHeight": 640,
20         "decorations": false,
21         "transparent": true,
22         "center": true,
23         "resizable": true,
24         "shadow": true,
25         "windowEffects": {
26           "effects": [
27             "mica"
28           ],
29           "state": "active",
30           "radius": 12
31         }
32       }
33     ],
34     "security": {
35       "csp": null
36     }
37   },
38   "bundle": {
39     "active": true,
40     "targets": "all",
41     "icon": [
42       "icons/32x32.png",
43       "icons/128x128.png",
44       "icons/128x128@2x.png",
45       "icons/icon.icns",
46       "icons/icon.ico"
47     ]
48   }
49 }
```

## tsconfig.json

F:\Tools\CodeZipper\tsconfig.json

```
1  {
2    "compilerOptions": {
3      "target": "ES2022",
4      "useDefineForClassFields": true,
5      "lib": [
6        "ES2020",
7        "DOM",
8        "DOM.Iterable"
9      ],
```

```
    "module": "ESNext",
    "skipLibCheck": true,

    /* Bundler mode */
    "moduleResolution": "bundler",
    "allowImportingTsExtensions": true,
    "resolveJsonModule": true,
    "isolatedModules": true,
    "noEmit": true,
    "jsx": "react-jsx",

    /* Linting */
    "strict": true,
    "noUnusedLocals": true,
    "noUnusedParameters": true,
    "noFallthroughCasesInSwitch": true,

    /* alias */
    "paths": {
      "@/*": [
        "./src/*"
      ]
    }
  },
  "include": [
    "src"
  ],
  "references": [
    {
      "path": "./tsconfig.node.json"
    }
  ]
}
```

## tsconfig.node.json

F:\Tools\CodeZipper\tsconfig.node.json

```
{
  "compilerOptions": {
    "composite": true,
    "skipLibCheck": true,
    "module": "ESNext",
    "moduleResolution": "bundler",
    "allowSyntheticDefaultImports": true
  },
  "include": ["vite.config.ts"]
}
```

## vite.config.ts

F:\Tools\CodeZipper\vite.config.ts

```
import { defineConfig } from "vite";
import react from "@vitejs/plugin-react";
import tailwindcss from "@tailwindcss/vite";
import path from "node:path";
import process from "node:process";
const host = process.env.TAURI_DEV_HOST;

// https://vite.dev/config/
export default defineConfig(() => ({
  plugins: [react(), tailwindcss()],
  resolve: {
    alias: {
      "@": path.resolve(__dirname, "./src"),
    },
  },
  // Vite options tailored for Tauri development and only applied in `tauri dev` or `tauri build`
  //
  // 1. prevent Vite from obscuring rust errors
  clearScreen: false,
  // 2. tauri expects a fixed port, fail if that port is not available
  server: {
    port: 1420,
    strictPort: true,
    host: host || false,
    hmr: host
      ? {
          protocol: "ws",
          host,
```

```
          port: 1421,
        }
      : undefined,
    watch: {
      // 3. tell Vite to ignore watching `src-tauri`
      ignored: ["**/src-tauri/**"],
    },
  },
}));
```