

Cisco Catalyst Switch Initialization & Management

Command Line Interface (CLI) Verification and Device Storage Report

Part 1: Connect to the Device Using a Console Connection

Step 1: Out-of-Band Terminal Link Emulation

A standard rollover console wire was connected between Laptop0 and the Catalyst switch infrastructure platform to open direct asynchronous line control options independent of current data plane routing availability.





Figure 1.1: Initializing Terminal Line Session Prompt

Step 2: User EXEC Character Mapping Shell

Executed fundamental diagnostic lookups and context-sensitive help parsing parameters within the basic shell hierarchy level.



Wireless Security	
	WPA2 Personal ▼
	AES ▼
	MyPassPhrase1
	3600
	Disabled ▼
	Disabled ▼

Figure 1.2: Context-Sensitive User Shell Command Reference

Step 3: Privilege Boundary Scaling Analysis

Advanced system authorization context parameters to administrative Privileged EXEC mode using the enable macro statement check.





Figure 1.3: Elevating Security Clearance Context Commands

Part 2: Copy Configuration Information to the Device

Step 1 & 2: Global Management Submodes Configuration

Navigated terminal execution focus into global operational memory layers (configure terminal) and established unique host platform identification string markers.



The screenshot shows a dialog box titled "WPA2-Personal Needed for Connection". The dialog has a light gray header bar with the title. Below the header, there is a text area that reads: "This wireless network has WPA2-Personal enabled. To connect to this network, enter the required passphrase in the appropriate field below. Then click the **Connect** button." Below this text, there are two input fields. The first is labeled "Security" and has a dropdown menu showing "WPA2-Personal". To the right of this field is a text label: "Please select the wireless security method used by your existing wireless network." The second input field is labeled "Pre-shared Key" and contains the text "MyPassPhrase!1". To the right of this field is a text label: "Please enter a Pre-shared Key that is 8 to 63 characters in length." At the bottom of the dialog, there is a green bar with two buttons: "Cancel" and "Connect". To the right of the "Connect" button, the word "Active" is partially visible. At the very bottom of the screen, there is a black status bar with white text that reads: "Wireless-N Notebook Adapter Wireless Network Monitor v1.0 Model No. WPC300N".

Figure 2.1: Assigning Device Hostname via Global Space

Step 3: Hardening Access Line Interconnections

Isolated line console zero subconfiguration fields to deploy line credential checking parameters across terminal attachment actions.

WPA2-Personal Needed for Connection

This wireless network has WPA2-Personal enabled. To connect to this network, enter the required passphrase in the appropriate field below. Then click the **Connect** button.

Security

WPA2-Personal

Please select the wireless security method used by your existing wireless network.

Pre-shared Key

MyPassPhrase1!

Please enter a Pre-shared Key that is 8 to 63 characters in length.

Figure 2.2: Securing Line Console Interface Target Paths

Step 4: Operational State Verification Checks

Exited out-of-band context limits completely to prompt standard access challenges and check system defensive parameter operations.



Figure 2.3: Operational Line Console Challenge Sequence

Part 3: Save the Updated Configuration to the Device

Step 1: Display Active Live Volatile Configuration Parameters

Audited active functional elements running directly inside live volatile RAM operational memory banks.




Figure 3.1: Active Running RAM Buffer Registry State

Step 2: Serializing Modifications to Persistent Storage blocks

Committed live variables safely down into permanent non-volatile memory arrays (NVRAM) via memory synchronization transactions to handle system power cycles securely.



Figure 3.2: NVRAM Serialization File Commit Status

Part 4: Laboratory Assessment Validation Records

Step 1: Structural Component Performance Metrics Overview

Inspected specific scoring nodes inside the assessment suite to verify all target line changes and password criteria mapped successfully.



Figure 4.1: Individual Criteria Allocation Results Card

Step 2: Activity Completion Index Validation Certificate

Final lab completion output audit confirming absolute task objective integration with an explicit 100% metrics completion record profile.



Figure 4.2: Comprehensive Activity Progress Summary Block