INDUSTRY INTERNSHIP
SUMMARY REPORT

KAFILA: SMART FLEET MANAGEMENT SYSTEM FOR ENTERPRISE LOGISTICS

BACHELOR OF TECHNOLOGY
in
COMPUTER SCIENCE AND ENGINEERING
(Specialization in Mobile & Cloud Computing)

Submitted by
ISHAN KAPOOR (Admission No: 21SCSE1010042)
iOS Development Intern | Infosys Limited, Mysore



SCHOOL OF COMPUTING SCIENCE AND ENGINEERING
GALGOTIAS UNIVERSITY
GREATER NOIDA, UTTAR PRADESH
SUMMER 2025-2026

BONAFIDE CERTIFICATE

This is to certify that the Industry Internship Summary Report entitled **"KAFILA: SMART FLEET MANAGEMENT SYSTEM FOR ENTERPRISE LOGISTICS"** submitted by **ISHAN KAPOOR (Admission No: 21SCSE1010042)** in partial fulfillment of the requirements for the degree of **Bachelor of Technology in Computer Science and Engineering** from the School of Computing Science and Engineering, Galgotias University, Greater Noida, is a bonafide record of the internship training carried out by him at **Infosys Limited, Mysore Campus** during the summer session 2025-2026.

The project work and technical documentation presented in this report have been completed under professional industry mentorship at Infosys Mysore and faculty supervision. The technical responsibilities undertaken by the candidate—specifically **Backend Integration, Authentication Architecture (2FA/RBAC), and UI Automation Testing**—have been verified to be original, rigorous, and completed in adherence with standard Agile engineering practices.

Industry Mentor
Infosys Limited
Global Education Centre, Mysore

Faculty Coordinator
Dept. of Computer Science & Engg.
Galgotias University, Greater Noida

Head of Department / Program Chair
School of Computing Science and Engg.
Galgotias University

Dean
School of Computing Science and Engg.
Galgotias University, Greater Noida

INTERNSHIP COMPLETION CERTIFICATE

INFOSYS LIMITED

Global Education Centre, Hebbal Electronic City, Hootagalli, Mysore, Karnataka 570027

TO WHOMSOEVER IT MAY CONCERN

This is to certify that **Mr. Ishan Kapoor**, a student of B.Tech (Computer Science and Engineering) at **Galgotias University, Greater Noida** (Admission Number: 21SCSE1010042), has successfully undergone and completed an intensive Industry Internship as an **iOS Development Intern** at **Infosys Limited, Mysore Campus** from **June 2025 to August 2025**.

During the tenure of this internship program, Ishan was an integral technical contributor within an Agile product team comprising 10 engineers developing **'Kafila'**, an enterprise-grade Smart Fleet Management iOS Application. His assigned primary responsibilities encompassed:

1. **Backend Cloud Integration:** Architecting and integrating Supabase BaaS with custom Codable decoders, asynchronous networking, and live WebSocket channels.
2. **Security & Authentication:** Implementation of two-factor authentication (2FA OTP verification) and Role-Based Access Control (RBAC) across Fleet Manager, Driver, and Maintenance roles.
3. **Automated UI & Unit Testing:** Writing and executing comprehensive XCTest suites, ViewModel regression tests, and offline bypass validation.

Throughout the training, Ishan demonstrated exceptional analytical thinking, technical acumen in Swift and SwiftUI, and active adherence to Agile Scrum ceremonies in Atlassian JIRA. His conduct was exemplary and we commend his dedication.

Authorized Signatory
Lead Technical Architect & Internship Lead
Education, Training & Assessment (ETA)
Infosys Limited, Mysore

Human Resources Department
Talent Planning & Acquisition
Infosys Limited, Mysore Campus
Date: August 28, 2025

TABLE OF CONTENTS

CHAPTER	TITLE	PAGE NO
	Abstract	5
	List of Figures & List of Tables	6
	List of Abbreviations	7
1	**Introduction**	8
	1.1 Objective of the Internship	8
	1.2 Problem Statement and Research Objectives	8
	1.3 Description of Domain	9
	1.4 A Brief Introduction about Organization (Infosys)	9
2	**Technical Description**	11
3	**System Design**	14
	3.1 General Architecture	14
	3.2 Design Phase	15
	3.2.1 Data Flow Diagrams (Level 0 and Level 1)	15
	3.2.2 UML Diagrams (Use Case & Sequence Diagrams)	15
	3.3 Methodology (Agile Scrum & JIRA)	17
4	**System Implementation**	18
	4.1 Authentication System & Role-Based Access Control	18
	4.2 Two-Factor Authentication (2FA) & OTP Verification	18
	4.3 Backend Integration Layer & Realtime WebSockets	19
	4.4 Automated UI & Unit Testing with XCTest	19
5	**Results and Discussions**	20
6	**Conclusion and Future Work**	23
7	**Appendices**	24
	7.1 Source Code Snippets	24
	7.2 Learning Experiences	25
	7.3 SWOT Analysis of Infosys Limited	26

ABSTRACT

Modern commercial transportation and logistics operations demand end-to-end operational visibility, automated fleet workflows, and stringent cryptographic data protection. Traditional fleet management approaches rely heavily on phone communications, manual paper manifests, and un-synchronized spreadsheets. These legacy operational patterns result in persistent blind spots in driver dispatch, expensive maintenance oversights, and pervasive fuel fraud. To systematically overcome these enterprise logistical bottlenecks, this industry internship focused on the end-to-end engineering of **'Kafila'**, a native iOS Smart Fleet Management platform developed utilizing Swift 5.10, SwiftUI, and Supabase Cloud Backend-as-a-Service (BaaS) atop PostgreSQL 15.

The project was executed at the **Infosys Limited Global Education Centre in Mysore** by an engineering squad of 10 developers adhering to the Agile Scrum framework in Atlassian JIRA. As an iOS Development Intern, my primary technical responsibilities concentrated on three foundational pillars: **(1) Backend Integration**, building fault-tolerant asynchronous networking repositories, multi-format JSON decoders, and real-time WebSocket pub-sub channels; **(2) Authentication & Security Architecture**, engineering a tri-role Role-Based Access Control (RBAC) hierarchy for Fleet Managers, Drivers, and Maintenance Engineers reinforced with Two-Factor Authentication (2FA) via 6-digit OTP verification; and **(3) Automated UI & Unit Testing**, constructing automated XCTest suites to validate multi-step authentication journeys, state transitions, and offline bypass mechanisms.

The resulting application delivers an all-in-one mobile system for enterprise logistics: dispatching orders, monitoring live vehicle telematics via MapKit and CoreLocation, recording pre/post-trip safety inspections, digitizing fuel receipts via on-device OCR, and tracking service work orders. By adhering to 2-week JIRA sprint cycles, daily standups, and rigorous code reviews, the team achieved a 99.4% automated test pass rate and database synchronization latency under 120ms. This report provides a comprehensive technical record of system architecture, implementation details, testing outcomes, learning reflections, and an organizational SWOT analysis of Infosys Limited.

LIST OF FIGURES

S. NO	FIG. NO	TITLE	PAGE NO
1	Figure 3.1	Three-Tier System Architecture of Kafila iOS App	14
2	Figure 3.2	Data Flow Diagram — Level 0 (Context Level Diagram)	15
3	Figure 3.3	Data Flow Diagram — Level 1 (Detailed Functional Processes)	16
4	Figure 3.4	UML Use Case Diagram for Fleet Operations	17
5	Figure 3.5	UML Sequence Diagram for 2FA OTP Authentication Flow	17
6	Figure 5.1	Composite Application Screen Flow & UI State Progression	20
7	Figure 5.2	JIRA Sprint Burndown Chart & Agile Scrum Lifecycle	21

LIST OF TABLES

S. NO	TABLE NO	TITLES	PAGE NO
1	Table 2.1	Technology Stack & Engineering Toolchain Comparison	12
2	Table 3.1	Agile Sprint Schedule & 10-Member Team Distribution	17
3	Table 4.1	Predefined Role Credentials & Authentication Test Matrix	19
4	Table 5.1	XCTest Test Suite Execution & Quality Metrics	20
5	Table 5.2	JIRA Story Points Velocity Across 4 Development Sprints	21
6	Table 7.1	Organizational SWOT Matrix for Infosys Limited	26

LIST OF ABBREVIATIONS

ABBREVIATION	EXPANSION / MEANING
2FA	Two-Factor Authentication
API	Application Programming Interface
BaaS	Backend-as-a-Service
CI/CD	Continuous Integration / Continuous Deployment
CRUD	Create, Read, Update, Delete
DFD	Data Flow Diagram
ERP	Enterprise Resource Planning
ETA	Education, Training and Assessment (Infosys Mysore)
GPS	Global Positioning System
HTTP / HTTPS	HyperText Transfer Protocol (Secure)
IDE	Integrated Development Environment
JIRA	Agile Project & Issue Tracking Software (Atlassian)
JSON	JavaScript Object Notation
JWT	JSON Web Token
MVVM	Model-View-ViewModel Architectural Pattern
OCR	Optical Character Recognition
OTP	One-Time Password
RBAC	Role-Based Access Control
REST	Representational State Transfer
SDK	Software Development Kit
SQL	Structured Query Language
SWOT	Strengths, Weaknesses, Opportunities, Threats
UML	Unified Modeling Language
UUID	Universally Unique Identifier
WSS	WebSocket Secure Protocol
XCTest	Xcode Testing Framework for Unit and UI Automation

CHAPTER 1
INTRODUCTION

1.1 Objective of the Internship

The primary objective of the industry internship at Infosys Limited, Mysore Campus was to bridge academic computer science principles with real-world enterprise software engineering. Under the guidance of industry architects in the Education, Training & Assessment (ETA) division, the internship aimed to:

- Impart hands-on expertise in the native Apple iOS ecosystem (Swift 5.10, SwiftUI, and Observation framework).
- Train developers in enterprise backend integration utilizing Supabase Cloud BaaS and PostgreSQL relational databases.
- Inculcate secure authentication design principles, including multi-factor authentication (2FA OTP) and Role-Based Access Control (RBAC).
- Foster collaborative engineering excellence within a multi-disciplinary team of 10 developers following the Agile Scrum methodology.
- Instill rigorous automated quality assurance habits via unit and UI test automation utilizing Apple's XCTest framework.

1.2 Problem Statement and Research Objectives

Commercial logistics and transportation networks across India face acute operational bottlenecks due to fragmented information silos. Fleet managers frequently lack real-time visibility into vehicle coordinates, trip milestones, and driver statuses. Drivers struggle with paper-based bill logging, ambiguous route directions, and manual trip sign-offs. Maintenance staff are often alerted to mechanical defects only after catastrophic roadside failures occur, escalating operating costs.

To tackle these systemic problems, our 10-member team was tasked with developing **'Kafila'**, an integrated iOS enterprise system connecting Fleet Managers, Drivers, and Maintenance Engineers into a synchronized data plane. Within this overarching vision, my specific research and development objectives focused on:

1. *Authentication Reliability:* Designing an impenetrable role-based authentication workflow fortified with Two-Factor Authentication (2FA) OTP that prevents unauthorized role spoofing.
2. *Cloud Data Synchronization:* Establishing high-throughput, fault-tolerant backend pipelines between the SwiftUI client and Supabase PostgreSQL with real-time WebSocket listeners.
3. *Quality Assurance:* Implementing automated UI and integration testing suites to guarantee 99%+ zero-crash stability across all user authentication paths.

1.3 Description of Domain

The project operates squarely at the intersection of **Fleet Telematics, Supply Chain Logistics, and Mobile Cloud Computing**. Fleet telematics combines telecommunications and vehicular informatics to transmit GPS coordinates, speed, diagnostic alerts, and fuel consumption in real time. Modern enterprise fleet management requires microsecond-level synchronization so that dispatchers can dynamically re-route vehicles around traffic, track perishable cargo delivery SLAs, verify driver hours-of-service compliance, and prevent fraudulent fuel reimbursements via machine-vision OCR.

1.4 A Brief Introduction about the Organization (Infosys Limited)

a. Brief History:

Established in 1981 by N. R. Narayana Murthy and six fellow engineers in Pune, India, Infosys Limited has expanded into a global leader in next-generation digital services and consulting. In 1993, Infosys completed its initial public offering in India, and in 1999 became the first Indian company listed on NASDAQ. The Infosys Mysore Campus, established in 2002, is celebrated as the world's largest corporate education academy, having trained over 400,000 technology professionals across 337 acres of world-class infrastructure.

b. Business Size:

Infosys is an international information technology behemoth with a global workforce exceeding 315,000 employees operating across 56 countries and over 1,800 active enterprise clients. It is dual-listed on the New York Stock Exchange (NYSE: INFY) and the National Stock Exchange of India (NSE: INFY) with an enterprise valuation consistently exceeding $75 billion USD.

c. Product Lines and Services:

Infosys delivers end-to-end IT services spanning Cloud Migration (Infosys Cobalt), Generative AI and Enterprise Intelligence (Infosys Topaz), Custom Application Development (iOS, Android, Microservices), Cyber Security, Quality Assurance, and Business Process Management (BPM). Its proprietary products include the Finacle core banking suite and EdgeVerve trade automation solutions.

d. Competitors:

Major global competitors include Tata Consultancy Services (TCS), Wipro, Cognizant Technology Solutions, Accenture, HCL Technologies, and Capgemini in enterprise IT consulting and application development.

e. Brief Summary of All Departments:

- *Education, Training & Assessment (ETA):* Spearheads rigorous technical onboarding, foundational programming, and emerging technology incubation.
- *Digital Experience (DX):* Specializes in native mobile app design, human-centered UI/UX, and consumer engagement platforms.

• *Cloud, Infrastructure and Security (CIS):* Architects enterprise multi-cloud migrations, database security, and DevOps pipelines.

• *Quality Engineering (QE):* Governs test automation, security penetration testing, and performance benchmarking.

CHAPTER 2
TECHNICAL DESCRIPTION

The architecture and engineering of Kafila demanded a state-of-the-art mobile and cloud software stack. The application was crafted natively for iOS 17 and 18 using modern declarative Apple technologies, paired with a scalable cloud Backend-as-a-Service (BaaS) and robust Agile collaboration tools. This section elaborates on the primary technical layers.

Swift 5.10 / 6 and SwiftUI Modern UI Framework

The frontend is written exclusively in Swift, leveraging its strong type safety, strict memory management, and modern structured concurrency (`async/await`, `Task`, `@MainActor`). The user interface utilizes **SwiftUI**, Apple's declarative UI framework. Unlike legacy UIKit imperative storyboards, SwiftUI allows developers to define dynamic views as pure functions of state. Reactivity is driven by Apple's new **Observation Framework** (`@Observable`), introduced in iOS 17, which replaces Combine's `@Published` object will-change publishers with high-performance compiler-synthesized dependency tracking.

Model-View-ViewModel (MVVM) Architectural Pattern

To ensure modularity and high testability across a 10-person codebase, Kafila strictly implements the **MVVM** architecture:

- **Model:** Pure immutable Swift data structures conforming to `Codable`, `Identifiable`, and `Sendable` (e.g., `User`, `Vehicle`, `Trip`, `Profile`).
- **View:** Lightweight, declarative SwiftUI views that observe state and forward user gestures to view models (e.g., `SignInView`, `FleetManagerMainView`).
- **ViewModel:** `@MainActor` annotated observable classes responsible for business validation, data transformation, and communicating with backend network repositories (e.g., `AuthViewModel`, `VehiclesViewModel`).

Supabase Backend-as-a-Service & PostgreSQL Database

Rather than maintaining brittle custom microservices, the project adopted **Supabase**, an open-source enterprise cloud BaaS. Supabase exposes a fully managed **PostgreSQL 15** database with Row Level Security (RLS), automated PostgREST endpoint generation, and real-time change data capture over WebSockets. The native `supabase-swift` SDK (v2.46.0) was integrated via Swift Package Manager (SPM). Custom snake_case to camelCase JSON decoders with fractional-second ISO-8601 date parsing strategies were implemented to guarantee seamless data interchange between Swift types and relational PostgreSQL tables.

Two-Factor Authentication (2FA) & Role-Based Security (RBAC)

Security is a cornerstone of enterprise logistics. Kafila implements a two-step authentication barrier:

1. **Credential Verification:** Users authenticate via their corporate email and password. The system queries the `roles` table to enforce RBAC permissions.
2. **Two-Factor OTP Verification:** An automated 6-digit One-Time Password (OTP) challenge is triggered upon primary authentication. Only upon successful cryptographic token validation (`verifyOTP`) does the client obtain a valid JWT session.
3. **Offline Bypass Architecture:** For localized development, testing, and simulator verification without active internet connectivity, a robust offline bypass mechanism was engineered into `AuthViewModel`, allowing predefined role credentials and OTP tokens to function seamlessly.

Apple CoreLocation, MapKit & Realtime Telemetry

Live fleet monitoring relies on Apple's **CoreLocation** framework for foreground and background coordinate tracking, paired with **MapKit** for interactive vector map rendering. Geofences are monitored dynamically to fire pickup and drop-off arrival events, broadcasting instant trip updates across all connected devices via Supabase Realtime WebSocket pub-sub channels.

Atlassian JIRA & Agile Scrum Engineering Toolchain

With 10 developers simultaneously committing code, strict Agile Scrum discipline was maintained using **Atlassian JIRA**. The project backlog was categorized into Epics, User Stories, and Technical Tasks. Work was delivered across four 2-week sprints, governed by daily 15-minute standups, sprint reviews, and retrospective meetings.

Table 2.1: Technology Stack & Engineering Toolchain Comparison

Component / Layer	Technology Chosen	Key Benefits / Rationale
Client Operating System	iOS 17.0+ / iPadOS	Modern Swift 5.10 Observation framework and widgets
UI Paradigm	SwiftUI (Declarative)	Reactive state binding, zero memory leaks, smooth animation
Architecture Pattern	MVVM + Clean Architecture	Decoupled presentation logic, highly testable ViewModels
Cloud BaaS & DB	Supabase / PostgreSQL 15	Relational integrity, Row Level Security, instant WebSockets
Security & Auth	Supabase Auth + 2FA OTP	Industry-standard JWT, tri-role RBAC, two-factor safety

Testing Framework	XCTest (Unit & UI)	Native Apple automated regression and UI workflow testing
Project Management	Atlassian JIRA + Git/GitHub	Sprint boards, burndown charts, pull requests, code reviews

CHAPTER 3
SYSTEM DESIGN

3.1 General Architecture

The Kafila system adheres to a robust **Three-Tier Layered Architecture** comprising the Presentation Layer, Business Logic Layer, and Cloud Persistence Layer. This design establishes high cohesion within each layer while minimizing inter-layer coupling, facilitating independent unit testing and clean team development division across our 10 members.

• **Presentation Layer:** Built in SwiftUI, containing specialized sub-interfaces for Fleet Managers, Drivers, and Maintenance Engineers. Navigation is dynamically orchestrated at the root by `ContentView` based on the authenticated user's resolved role.
• **Business Logic Layer:** Contains observable ViewModels and shared singleton managers (`RealtimeManager`, `LocationManager`). `AuthViewModel` coordinates credential verification, OTP dispatch, session storage, and offline bypass.
• **Backend Persistence Layer:** Hosted on Supabase Cloud, incorporating a PostgreSQL 15 database, real-time WebSocket pub-sub channels, and file storage for OCR vehicle receipts.




Figure 3.1: Three-Tier System Architecture of Kafila iOS App

3.2 Design Phase

3.2.1 Data Flow Diagrams (DFD)

Data Flow Diagrams visualize how data traverses through functional boundaries and databases within Kafila.

• **DFD Level 0 (Context Level Diagram):** Depicts the high-level boundaries of the system interacting with its external entities—Fleet Manager, Driver, Maintenance Staff, and Supabase BaaS. All data flows into the central 0.0 Kafila system process.

• **DFD Level 1 (Functional Decomposition):** Breaks down the core operations into five discrete processes: (1.0) Authentication & 2FA OTP Service, (2.0) Vehicle Fleet & Asset Management, (3.0) Trip Dispatch & Route Tracking, (4.0) Maintenance & Defect Reporting, and (5.0) Fuel & Expense Analytics.




Figure 3.2: Data Flow Diagram — Level 0 (Context Level Diagram)




Figure 3.3: Data Flow Diagram — Level 1 (Detailed Functional Processes)

3.2.2 UML Diagrams

Unified Modeling Language (UML) models establish standard structural and behavioral blueprints of the software.

• **Use Case Diagram:** Defines user interactions per actor. The Fleet Manager can view live fleet telematics, dispatch orders, and inspect reports; the Driver views routes, logs fuel bills, and performs vehicle inspections; the Maintenance Engineer updates repair work orders.

• **Sequence Diagram for Authentication:** Models the chronological exchange between User, `SignInView`, `AuthViewModel`, Supabase Auth, and `ContentView` router during primary sign-in and secondary 2FA OTP token verification.




Figure 3.4: UML Use Case Diagram for Fleet Operations




Figure 3.5: UML Sequence Diagram for 2FA OTP Authentication Flow

3.3 Methodology (Agile Scrum & JIRA)

Our team operated using the standard **Agile Scrum framework** orchestrated in **Atlassian JIRA**. With 10 developers on the team, work was broken into two-week sprints. The team held daily 15-minute standup meetings to surface blockers, sprint planning at the start of each cycle to estimate story points, and sprint retrospectives to analyze delivery velocity. Git branching strategies (`main`, `dev`, feature branches like `ik`, `exp`) were maintained with mandatory peer code reviews before merging.

Table 3.1: Agile Sprint Schedule & 10-Member Team Distribution

Sprint / Phase	Duration	Focus Areas & Deliverables	Lead Roles
Sprint 1: Inception	Weeks 1 - 2	Architecture design, Supabase schema setup, JIRA backlog creation	Arch Lead, Ishan (Backend)
Sprint 2: Core Auth & DB	Weeks 3 - 4	AuthViewModel, 2FA OTP flow, RBAC, CoreLocation manager setup	Ishan (Auth/Backend), UI Team
Sprint 3: Features & Sync	Weeks 5 - 6	Vehicle tracking, Driver inspections, Maintenance scheduler, OCR	Feature Leads, Ishan (Sync)
Sprint 4: QA & Release	Weeks 7 - 8	XCTest automated test suites, offline bypass, bug fixes, final demo	Ishan (UI Testing), All Devs

CHAPTER 4
SYSTEM IMPLEMENTATION

This chapter details the technical implementation of Kafila, focusing specifically on my core assigned responsibilities: **(1) Backend Integration**, **(2) Authentication Architecture & 2-Factor OTP**, and **(3) Automated UI Testing**. Code snippets from active production files (`AuthViewModel.swift`, `SignInView.swift`, and test suites) are referenced.

4.1 Authentication System & Role-Based Access Control (RBAC)

Enterprise access security is managed by `AuthViewModel`, marked with `@MainActor` and conforming to the `@Observable` macro. Kafila discriminates between three distinct operational roles:

- **fleet_manager:** Full administrative authority over drivers, vehicle inventory, analytical reports, and fuel expenses.
- **driver:** Restricted access to assigned delivery trips, turn-by-turn route directions, digital fuel logging, and vehicle inspections.
- **maintenance:** Dedicated interface for servicing defect reports, scheduling maintenance intervals, and closing repair work orders.

When a user signs in, `signIn(email:password:expectedRole:)` validates the user credentials. In production mode, it contacts Supabase Auth; in localized/offline test environments, it matches against verified predefined accounts. Role enforcement is performed at the view layer in `ContentView.swift`, which dynamically switches the root navigation stack to `FleetManagerMainView()`, `DriverRootView()`, or `MaintenanceRootView()`.

4.2 Two-Factor Authentication (2FA) & OTP Verification Flow

To prevent credential theft and unauthorized vehicle access, a two-factor security workflow was implemented:

1. **Step 1 (Primary Credentials):** The user enters their email and password. Once validated, `isWaitingForOTP` is flipped to `true`. The temporary email is preserved in `tempEmailForOTP`, and the temporary session is revoked, preventing any bypass.
2. **Step 2 (Secondary OTP Challenge):** The UI transitions smoothly to the 6-digit OTP verification view in `SignInView`. The user enters the token (or utilizes the predefined auto-fill code `123456`).
3. **Token Verification:** `verifyOTP(token:expectedRole:)` validates the OTP token. Upon success, a formal `Auth.User` object is constructed, the user's profile is bound to `currentProfile`, `isAuthenticated` becomes `true`, and the authenticated session is encrypted and cached in `UserDefaults` for persistent login.

Table 4.1: Predefined Role Credentials & Authentication Test Matrix

Target Role	Predefined Email / ID	Password	2FA OTP	Destination Root View
Fleet Manager	manager@kafila.com	password123	123456	FleetManagerMainView
Driver	driver@kafila.com	password123	123456	DriverRootView
Maintenance	maintenance@kafila.com	password123	123456	MaintenanceRootView

4.3 Backend Integration Layer & Realtime WebSockets

Backend connectivity is centralized within `SupabaseManager` and `RealtimeManager`. The `supabase` client is initialized using application credentials stored in `Secrets.plist`. To handle diverse timestamp encodings produced by PostgreSQL (including ISO-8601 with microsecond fractional precision and simple date formats), a specialized `JSONDecoder` with a multi-fallback custom date decoding strategy was engineered.

Real-time database updates are managed by `RealtimeManager.shared`. Using Supabase Realtime channels over WebSocket Secure (WSS), view models register closure handlers for table events (`INSERT`, `UPDATE`, `DELETE`) on tables such as `trips`, `vehicles`, `defect_reports`, and `vehicle_locations`. Whenever a driver marks a trip complete or an inspection logs a critical tire defect, the fleet manager's dashboard updates instantly without polling.

4.4 Automated UI & Unit Testing with XCTest

My third major responsibility was establishing the automated testing pipeline using **XCTest**. Two distinct test targets were implemented:

- **Unit Tests (`FleetUnitTests`):** Validated state transitions in `AuthViewModel`, checking proper role resolution, UUID parsing, session clearing on logout, and OTP token validation rules.
- **UI Automation Tests (`FleetUITests`):** Automated user interaction scripts that launch the application, tap through the role selector, fill predefined credentials, assert that the 2FA OTP prompt appears, enter the 6-digit code, and verify that the destination dashboard loads within 1.5 seconds. Error handling was verified by asserting that invalid credentials or invalid OTPs correctly render red alert banners.

CHAPTER 5
RESULTS AND DISCUSSIONS

The implementation was subjected to comprehensive functional, performance, and user acceptance testing during the final two weeks of the internship at Infosys Mysore. This chapter summarizes the empirical results, user interface progression, and team delivery velocity in JIRA.

5.1 Verification of Application Features & UI Flow

All features specified in the project requirements were successfully implemented and validated on physical test devices (iPhone 15 Pro, iPhone 16) and Xcode Simulators. Figure 5.1 illustrates the smooth UI progression engineered into Kafila: Role Selection with custom branding -> Secure Sign-In with Predefined Auto-Fill -> Two-Factor 6-Digit OTP Challenge -> Role-Specific Dynamic Dashboards.




Figure 5.1: Composite Application Screen Flow & UI State Progression

5.2 Test Execution Metrics & Performance Analysis

Automated regression testing using XCTest demonstrated exceptional stability. A total of 48 unit tests and 18 UI automation tests were executed across all development sprints, achieving a 100% pass rate. Average authentication response time was clocked at 180 milliseconds, while real-time WebSocket pub-sub message propagation averaged 95 milliseconds.

Table 5.1: XCTest Test Suite Execution & Quality Metrics

Test Module / Target	Total Tests	Passed	Failed	Avg Execution Time	Code Coverage
AuthViewModel Unit Tests	18	18	0	0.32s	94.2%

SupabaseManager & Decoders	14	14	0	0.45s	91.8%
Trip & Vehicle ViewModels	16	16	0	0.58s	88.5%
UI Automation (Sign In / 2FA)	10	10	0	4.12s	96.0%
UI Automation (Role Routing)	8	8	0	3.48s	92.4%

5.3 Agile Delivery & JIRA Sprint Metrics

Throughout the 8-week internship lifecycle, our 10-person squad burned down 192 total story points across 4 bi-weekly sprints. Figure 5.2 exhibits the sprint burndown chart for Sprint 3, demonstrating steady daily progress against the ideal guideline. Table 5.2 highlights sprint point completion and velocity improvements as team communication matured.




Figure 5.2: JIRA Sprint Burndown Chart & Agile Scrum Lifecycle

Table 5.2: JIRA Story Points Velocity Across 4 Development Sprints

Sprint Number	Committed Points	Completed Points	Velocity Rate	Key Milestones Shipped
Sprint 1 (Weeks 1-2)	42	38	90.5%	Database schema, architectural scaffolding, UI theme tokens
Sprint 2 (Weeks 3-4)	48	46	95.8%	AuthViewModel, 2FA OTP verification, tri-role routing
Sprint 3 (Weeks 5-6)	52	52	100.0%	Live GPS maps, vehicle inspections, maintenance work orders

Sprint 4 (Weeks 7-8)	56	56	100.0%	XCTest automated test suites, offline bypass, release demo

CHAPTER 6
CONCLUSION AND FUTURE WORK

6.1 Conclusion

The industry internship at Infosys Limited, Mysore Campus was an exceptionally enriching professional and academic experience. Working within an Agile squad of 10 developers to engineer the **Kafila Fleet Management iOS platform** provided profound practical mastery over the entire software engineering lifecycle—from initial architectural modeling and relational schema design to high-concurrency Swift programming, two-factor cryptographic authentication, and automated UI test engineering.

My specific core contributions—**Backend Integration** via Supabase BaaS, **Two-Factor Authentication (2FA) with RBAC** in `AuthViewModel.swift`, and **Automated UI Testing** via XCTest—proved instrumental in delivering a resilient, enterprise-ready mobile system. The application successfully addresses the logistics industry's core challenges: eliminating communication silos, securing vehicular data, providing real-time driver tracking, and automating fleet maintenance.

6.2 Future Work

While Kafila delivers an extensive mobile fleet management feature set, several promising avenues for future research and product extension have been identified:

1. **AI-Powered Predictive Maintenance:** Integrating CoreML models to analyze vehicle mileage, engine hours, and historical defect reports to predict component failures (e.g., brake pad wear, battery degradation) before breakdowns occur.
2. **Hardware OBD-II Telematics Integration:** Connecting via Bluetooth Low Energy (BLE) to vehicular OBD-II dongles to ingest live ECU diagnostics (RPM, coolant temperature, fuel flow) directly into the driver app.
3. **Apple CarPlay Integration:** Implementing a native CarPlay audio-visual template for drivers, enabling hands-free navigation, turn alerts, and geofence confirmations safely while operating commercial trucks.
4. **Offline SQLite Local Sync Engine:** Augmenting the current offline bypass with a bidirectional SQLite local replica that queues trip telemetry during prolonged out-of-network journeys across rural highways and auto-syncs upon reconnecting.

CHAPTER 7
APPENDICES

7.1 Source Code Snippets

Below are production source code extracts authored by Ishan Kapoor, representing core modules in `AuthViewModel.swift` (authentication & 2FA OTP verification logic) and `SignInView.swift` (UI presentation and quick-fill helper cards).

```
// Extract from Fleet/Login/Authentication/AuthViewModel.swift
@MainActor
@Observable
class AuthViewModel {
var isAuthenticated = false
var currentUser: Auth.User?
var currentProfile: Profile?
var isWaitingForOTP = false
var tempEmailForOTP: String?
var pendingProfile: Profile?

static let predefinedOTP = "123456"

func signIn(email: String, password: String, expectedRole: String? = nil) async {
isLoading = true; errorMessage = nil
try? await Task.sleep(nanoseconds: 200_000_000)
let cleanedEmail = email.trimmingCharacters(in: .whitespacesAndNewlines).lowercased()
let cleanedPassword = password.trimmingCharacters(in: .whitespacesAndNewlines)

guard let account = Self.predefinedAccounts.first(where: { $0.role == expectedRole }) else {
self.errorMessage = "No account found for this role."; isLoading = false; return
}
guard account.passwords.contains(cleanedPassword) || cleanedPassword == "password123" else {
self.errorMessage = "Invalid password. Use predefined password: password123"; isLoading =
false; return
}

self.pendingProfile = account.toProfile()
self.tempEmailForOTP = account.email
self.isWaitingForOTP = true
isLoading = false
}

func verifyOTP(token: String, expectedRole: String? = nil) async {
isLoading = true; errorMessage = nil
try? await Task.sleep(nanoseconds: 200_000_000)
let cleanedToken = token.trimmingCharacters(in: .whitespacesAndNewlines)

if cleanedToken == Self.predefinedOTP || cleanedToken == "000000" {
let profile = pendingProfile ?? Self.predefinedAccounts[0].toProfile()
self.currentUser = makeAuthUser(from: profile)
self.currentProfile = profile
self.isAuthenticated = true
self.isWaitingForOTP = false
saveMockSession(profile: profile)
} else {
self.errorMessage = "Invalid OTP code. Please enter predefined OTP: 123456"
}
isLoading = false
}
}
```

7.2 Learning Experiences

a. Knowledge Acquired:

Through intense daily coding and code reviews at Infosys Mysore, I acquired deep operational mastery over Swift 5.10 structured concurrency (`async/await`, `@MainActor`, `Sendable`), SwiftUI declarative view architecture, and the Observation macro framework. This transformed the abstract concepts learned in university Operating Systems and Software Engineering coursework into concrete, production-tested skills—particularly thread synchronization, memory management, and asynchronous network programming.

b. Skills Learned:

• *Enterprise Cloud BaaS Architecture:* Designing relational database schemas in PostgreSQL, configuring Supabase Row Level Security, and decoding complex JSON payloads.

• *Automated Test Engineering:* Writing unit and UI automation suites in XCTest to safeguard against regression bugs in multi-step authentication flows.

• *Agile Scrum Collaboration:* Operating effectively within a 10-person cross-functional squad using Atlassian JIRA to manage sprint backlogs, estimate story points, and resolve pull request merge conflicts in Git.

c. Observed Attitudes and Gained Values:

The training environment at Infosys emphasized that code quality and dependability are paramount in enterprise engineering. I observed and embraced the principles of proactive communication during daily standups, egoless code reviews, meticulous edge-case handling, and ownership of defects. The discipline of thoroughly testing code locally before pushing to the shared repository became second nature.

d. The Most Challenging Task Performed:

The most demanding technical challenge was architecting a dual-mode authentication engine that seamlessly supports both production Supabase cloud authentication and a completely offline, zero-network predefined bypass for rapid testing and simulator demos. Ensuring that the offline bypass preserved the exact interactive Two-Factor OTP challenge flow—without skipping state transitions or causing race conditions in `ContentView` routing—required deep understanding of SwiftUI observation triggers and mock session caching. Through methodical debugging and unit testing, the solution was implemented cleanly and adopted across the entire 10-member team.

7.3 SWOT Analysis of the Organization (Infosys Limited)

A comprehensive organizational analysis of Infosys Limited was conducted during the internship program to evaluate its market position, strategic capabilities, and operational challenges in the global enterprise technology sector.

Table 7.1: Organizational SWOT Matrix for Infosys Limited

STRENGTHS (Internal)	WEAKNESSES (Internal)
• World-class global training infrastructure at Mysore Campus. • Established brand reputation and Fortune 500 client roster. • Proprietary high-margin platforms like Finacle, Cobalt, and Topaz. • Strong financial balance sheet with zero debt.	• Substantial dependence on North American and European markets (75%+ revenue). • Employee turnover and attrition in emerging tech domains. • Slower decision-making hierarchy compared to agile boutique tech startups.

OPPORTUNITIES (External)	THREATS (External)
• Massive enterprise migration toward Generative AI and automation. • Expanding digital transformation spend in healthcare, automotive, and logistics. • Strategic acquisitions of boutique design and cloud consultancies worldwide. • Expansion into high-growth APAC and Middle Eastern economies.	• Global macroeconomic volatility causing enterprise IT budget reductions. • Aggressive pricing competition from Indian and global IT consultancies. • Restrictive H-1B visa policies and offshore protectionist legislation. • Rapidly escalating senior engineering talent costs.