

## NAME

**cbsd jls** -- List jails on local node or other nodes of the farm.

## SYNOPSIS

**cbsd jls** [**alljails**=1] [**shownode**=1] [**node**=<node-name>] [**header**=0]  
[**display**=jid,jname,ip4\_addr,host\_hostname,path,status] [**--help**]

## DESCRIPTION

The **cbsd jls** command lists all jails on the local node or other nodes added to the farm.

The options are as follows:

**alljails=1**

List jails from the whole farm (from all registered nodes).

**shownode=1**

When used with alljails option, lists the node name on which the jail resides.

**node**=<node-name>

Lists jails only from one particular node specified via node-name argument.

**header=0**

Omits header display, when listing nodes.

**display**=jid,jname,ip4\_addr,host\_hostname,path,status

The outputted fields can be changed through the display option.

**--help** Show simple usage instructions.

When there are no arguments specified defaults are taken from \$workdir/etc/defaults/jls.conf. These can be modified by changing the \$workdir/etc/jls.conf file leaving the default file intact for future reference.

## ENVIRONMENT

### FILES

\$workdir/etc/defaults/jls.conf

\$workdir/etc/jls.conf

## EXIT STATUS

The **cbsd jls** utility exits 0 on success, and >0 if an error occurs.

## EXAMPLES

List all jails on a single node:

**cbsd jls**

JNAME	JID	IP4_ADDR	HOST_HOSTNAME	PATH	STATUS
jail1	0	10.0.0.2/16	jail1.my.domain	/usr/jails/jails/jail1	Off
jail2	0	10.0.0.3/16	jail2.my.domain	/usr/jails/jails/jail2	Off
jail3	1	10.0.0.4/16	jail3.my.domain	/usr/jails/jails/jail3	On

List all jails on a the whole farm:

**cbsd jls alljails=1**

JNAME	JID	IP4_ADDR	HOST_HOSTNAME	PATH	STATUS
jail1	0	10.0.0.2/16	jail1.my.domain	/usr/jails/jails/jail1	Off
jail2	0	10.0.0.3/16	jail2.my.domain	/usr/jails/jails/jail2	Off
jail3	1	10.0.0.4/16	jail3.my.domain	/usr/jails/jails/jail3	On
jail1	0	10.0.1.2/16	jail1.my.domain	/usr/jails/jails/jail1	Off
jail2	0	10.0.1.3/16	jail2.my.domain	/usr/jails/jails/jail2	Off
jail3	1	10.0.1.4/16	jail3.my.domain	/usr/jails/jails/jail3	On

List all jails on the farm with node names shown:

**cbsd jls alljails=1 shownode=1**

NODENAME	JNAME	JID	IP4_ADDR	HOST_HOSTNAME	PATH
master	jail1	0	10.0.0.2/16	jail1.my.domain	/usr/jails/jails/jail1
master	jail2	0	10.0.0.3/16	jail2.my.domain	/usr/jails/jails/jail2
master	jail3	1	10.0.0.4/16	jail3.my.domain	/usr/jails/jails/jail3
slave	jail1	0	10.0.1.2/16	jail1.my.domain	/usr/jails/jails/jail1
slave	jail2	0	10.0.1.3/16	jail2.my.domain	/usr/jails/jails/jail2
slave	jail3	1	10.0.1.4/16	jail3.my.domain	/usr/jails/jails/jail3

## SEE ALSO

cbsd-jregister(8)

**AUTHORS**

Oleg Ginzburg <*olevole@olevole.ru*>