

THE ncML SPECS GROUP

ncML-G

and

ncML-G_{ML} Ver. 0.3.1

AN EXTENSION OF ncML FOR ENABLING
INTEROPERABILITY WITH GIS

SCHEMA DOCUMENTATION



When netCDF meets GIS Community

Editor: Stefano Nativi

January 2005

UNIDATA / UCAR

University of Florence

Italian National Research Council /IMAA

Send comments to nativi@ucar.edu (nativi@imaa.cnr.it)

INDEX

INDEX.....	2
XML SCHEMAS DOCUMENTATION.....	3
Documentation of geoCoordinateSystem schema version 0.3.1	3
geoCoordinateSystem schema source	16
Documentation of coverageGeoCoordSystem schema version 0.3.1	18
coverageGeoCoordSystem schema source	44
REFERENCES	46

OBJECTIVES

The main object of the GIS extension model for ncML is to facilitate the interoperability between the Earth Sciences and the GIS Communities.

Such interoperability is essential to support interoperability: between the Earth Sciences Community and the Society.

The present extension introduces a set of optional elements which are useful to describe a netCDF dataset according to geo-spatial models introduced by international committee for standardization.

These elements are based on the following international standardization initiatives: OGC OpenGIS and ISO TC211.

The ncML-G expected result is to ease the import of netCDF dataset from GIS tools.

The ncML-G_{ML} schema was conceived to explicitly formalize the introduced solution to harmonize Earth Sciences and GIS data models (i.e. ncML-G). NcML-G_{ML} must consist of two parts (or views):

- a multidimensional array model for ES community realm;
- a feature/coverage model for GIS community realm;

OVERVIEW

See the separated documentation

XML SCHEMAS DOCUMENTATION

Documentation of geoCoordinateSystem schema version 0.3.1

Schema **geoCoordinateSystem.xsd** version 0.3.1

Elements

geoCoordinateSystem
geoRefCoordinateSystem
spatialExtent
temporalExtent
verticalExtent

Complex types

_DatasetGeoDomainExtent
_DatasetGeoDomainLocation
_GeoCoordinateSystemType
_GeoRefCoordinateSystemType
_TemporalExtent
_VerticalExtent

schema location: <http://www.unidata.ucar.edu/schemas/netcdf-cs.xsd>
targetNamespace: <http://www.ucar.edu/schemas/netcdf>

Elements

coordinateAxis
coordinateAxisBoundary
coordinateSystem

Complex types

CoordinateAxisBoundaryType
CoordinateAxisType
CoordinateSystemType

The ncML specs group


coordinateTransform **CoordinateTransformType**
NetcdfType (r)
VariableType (r)

schema location: <http://www.unidata.ucar.edu/schemas/netcdf.xsd>
targetNamespace: <http://www.ucar.edu/schemas/netcdf>

Elements Complex types
attribute **AttributeType**
dimension **DimensionType**
netcdf **NetcdfType**
values **ValuesType**
variable **VariableType**

element **geoCoordinateSystem**

diagram



namespace <http://www.ucar.edu/schemas/netcdf>

type **nc:_GeoCoordinateSystemType**

children **coordinateAxisRef nc:coordinateTransform coordinateTransformRef geoDomainExtent**


attributes	Name	Type	Use	Default	Fixed	Annotation
	name	xsd:token	required			
annotation	documentation	Dataset coordinate system whose domain is characterized by a geographic description. Such geographic description of the domain is generally useful for catalog service				

source `<xsd:element name="geoCoordinateSystem" type="nc:_GeoCoordinateSystemType" substitutionGroup="nc:coordinateSystem">`
`<xsd:annotation>`
`<xsd:documentation>Dataset coordinate system whose domain is characterized by a geographic description.`
`Such geographic description of the domain is generally useful for catalog service</xsd:documentation>`
`</xsd:annotation>`
`</xsd:element>`

The ncML specs group

element **geoRefCoordinateSystem**

diagram



namespace <http://www.ucar.edu/schemas/netcdf>

type **nc:_GeoRefCoordinateSystemType**

children **coordinateAxisRef nc:coordinateTransform coordinateTransformRef geoDomainExtent geoDomainLocation**

attributes	Name	Type	Use	Default	Fixed	Annotation
	name	xsd:token	required			

annotation Dataset coordinate system whose domain is fully localized according to a spatial reference system. A localized domain is generally characterized by a geographic description, as well.

source `<xsd:element name="geoRefCoordinateSystem" type="nc:_GeoRefCoordinateSystemType" substitutionGroup="nc:geoCoordinateSystem">`

`<xsd:annotation>`

`<xsd:documentation>Dataset coordinate system whose domain is fully localized according to a spatial reference system.`


`A localized domain is generally characterized by a geographic description, as well.</xsd:documentation>`

`</xsd:annotation>`

`</xsd:element>`

element **spatialExtent**

diagram



namespace <http://www.ucar.edu/schemas/netcdf>

type **gml:BoundingShapeType**


children **gml:Envelope gml:Polygon gml:Solid gml:null**

The ncML specs group

used by	complexType	_DatasetGeoDomainExtent				
attributes	Name	Type	Use	Default	Fixed	Annotation
	type	string			simple	
	xlink:href	anyURI	optional			
	xlink:role	anyURI	optional			
	xlink:arcrole	anyURI	optional			
	xlink:title	string	optional			
	xlink:show	string	optional			
	xlink:actuate	string	optional			
	gml:remoteSchema	anyURI	optional			
source	<xsd:element name="spatialExtent" type="gml:BoundingShapeType"/>					

element **temporalExtent**

diagram



namespace <http://www.ucar.edu/schemas/netcdf>

type **nc:_TemporalExtent**


children **gml:_TPrimitive**

used by complexType **_DatasetGeoDomainExtent**

source <xsd:element name="temporalExtent" type="nc:_TemporalExtent"/>

element **verticalExtent**

diagram



namespace <http://www.ucar.edu/schemas/netcdf>

type **nc:_VerticalExtent**

children **gml:pos gml:coordinates**


used by complexType **_DatasetGeoDomainExtent**

attributes	Name	Type	Use	Default	Fixed	Annotation
	srsName	xsd:anyURI	optional			
source	<xsd:element name="verticalExtent" type="nc:_VerticalExtent"/>					

The ncML specs group

complexType **_DatasetGeoDomainExtent**

diagram



namespace <http://www.ucar.edu/schemas/netcdf>


children **nc:spatialExtent nc:verticalExtent nc:temporalExtent**

used by element **_GeoCoordinateSystemType/geoDomainExtent**

attributes	Name	Type	Use	Default	Fixed	Annotation
	description	xsd:string	optional			
source	<pre> <xsd:complexType name="_DatasetGeoDomainExtent" abstract="false"> <xsd:sequence> <xsd:element ref="nc:spatialExtent" maxOccurs="unbounded"/> <xsd:element ref="nc:verticalExtent" minOccurs="0" maxOccurs="unbounded"/> <xsd:element ref="nc:temporalExtent" minOccurs="0" maxOccurs="unbounded"/> </xsd:sequence> <xsd:attribute name="description" type="xsd:string" use="optional"/> </xsd:complexType> </pre>					

complexType **_DatasetGeoDomainLocation**

diagram



namespace <http://www.ucar.edu/schemas/netcdf>

children **gml:_CoordinateReferenceSystem**

used by element **_GeoRefCoordinateSystemType/geoDomainLocation**

```

<xsd:complexType name="_DatasetGeoDomainLocation">
  <xsd:sequence>
    <xsd:element ref="gml:_CoordinateReferenceSystem"/>
  </xsd:sequence>


```

The ncML specs group

</xsd:complexType>

complexType _GeoCoordinateSystemType

diagram



namespace <http://www.ucar.edu/schemas/netcdf>

type extension of `nc:CoordinateSystemType`

children `coordinateAxisRef` `nc:coordinateTransform` `coordinateTransformRef` `geoDomainExtent`


used by element `geoCoordinateSystem`
complexType `_GeoRefCoordinateSystemType`

attributes	Name	Type	Use	Default	Fixed	Annotation
	name	xsd:token	required			
annotation	documentation	It is an extension of the ncML-CS CoordinateSystemType				

```
<xsd:complexType name="_GeoCoordinateSystemType">
  <xsd:annotation>
    <xsd:documentation>It is an extension of the ncML-CS CoordinateSystemType</xsd:documentation>
  </xsd:annotation>
  <xsd:complexContent>
    <xsd:extension base="nc:CoordinateSystemType">
      <xsd:sequence minOccurs="0">
        <xsd:element name="geoDomainExtent" type="nc:_DatasetGeoDomainExtent">
          <xsd:annotation>
            <xsd:documentation>Geographic Extension of the coordinate system Domain</xsd:documentation>
          </xsd:annotation>
        </xsd:element>
      </xsd:sequence>
    </xsd:extension>
  </xsd:complexContent>
</xsd:complexType>
```

element _GeoCoordinateSystemType/geoDomainExtent

diagram



namespace <http://www.ucar.edu/schemas/netcdf>

type `nc:_DatasetGeoDomainExtent`

children `nc:spatialExtent` `nc:verticalExtent` `nc:temporalExtent`


The ncML specs group

attributes	Name	Type	Use	Default	Fixed	Annotation
	description	xsd:string	optional			
annotation	documentation	Geographic Extension of the coordinate system Domain				

source `<xsd:element name="geoDomainExtent" type="nc:_DatasetGeoDomainExtent">`
`<xsd:annotation>`
`<xsd:documentation>Geographic Extension of the coordinate system Domain</xsd:documentation>`
`</xsd:annotation>`
`</xsd:element>`

complexType **_GeoRefCoordinateSystemType**

diagram



namespace <http://www.ucar.edu/schemas/netcdf>

type extension of **nc:_GeoCoordinateSystemType**

children **coordinateAxisRef nc:coordinateTransform coordinateTransformRef geoDomainExtent geoDomainLocation**

used by element **geoRefCoordinateSystem**


attributes	Name	Type	Use	Default	Fixed	Annotation
	name	xsd:token	required			
annotation	documentation	Geo-referenced Coordinate System type				

source `<xsd:complexType name="_GeoRefCoordinateSystemType">`
`<xsd:annotation>`
`<xsd:documentation>Geo-referenced Coordinate System type</xsd:documentation>`
`</xsd:annotation>`
`<xsd:complexContent>`
`<xsd:extension base="nc:_GeoCoordinateSystemType">`
`<xsd:sequence minOccurs="0">`
`<xsd:element name="geoDomainLocation" type="nc:_DatasetGeoDomainLocation">`
`<xsd:annotation>`
`<xsd:documentation>Geographic Localization of the coordinate system Domain</xsd:documentation>`
`</xsd:annotation>`
`</xsd:element>`
`</xsd:sequence>`
`</xsd:extension>`
`</xsd:complexContent>`
`</xsd:complexType>`

The ncML specs group

element **_GeoRefCoordinateSystemType/geoDomainLocation**

diagram



namespace <http://www.ucar.edu/schemas/netcdf>

type **nc:_DatasetGeoDomainLocation**

children **gml:_CoordinateReferenceSystem**


annotation documentation Geographic Localization of the coordinate system Domain

source

```
<xsd:element name="geoDomainLocation" type="nc:_DatasetGeoDomainLocation">
  <xsd:annotation>
    <xsd:documentation>Geographic Localization of the coordinate system Domain</xsd:documentation>
  </xsd:annotation>
</xsd:element>
```

complexType **_TemporalExtent**

diagram



namespace <http://www.ucar.edu/schemas/netcdf>

children **gml:TPrimitive**

used by element **temporalExtent**

source


```
<xsd:complexType name="_TemporalExtent" abstract="false">
```

The ncML specs group

```
<xsd:sequence>
  <xsd:element ref="gml:_TPrimitive"/>
</xsd:sequence>
</xsd:complexType>
```

complexType **_VerticalExtent**

diagram



namespace <http://www.ucar.edu/schemas/netcdf>

children **gml:pos gml:coordinates**

used by element **vertical Extent**


attributes	Name	Type	Use	Default	Fixed	Annotation
	srsName	xsd:anyURI	optional			

source

```
<xsd:complexType name="_VerticalExtent" abstract="false">
  <xsd:choice>
    <xsd:element ref="gml:pos"/>
    <xsd:element ref="gml:coordinates"/>
  </xsd:choice>
  <xsd:attribute name="srsName" type="xsd:anyURI" use="optional"/>
</xsd:complexType>
```

element **nc:coordinateAxis**

diagram



namespace <http://www.ucar.edu/schemas/netcdf>

type **nc:CoordinateAxisType**

children **nc:attribute nc:values**


attributes	Name	Type	Use	Default	Fixed	Annotation
	name	xsd:token	required			
	shape	xsd:token	optional			
	type	nc:DataType	required			
	units	xsd:token	required			
	axisType	nc:AxisType	optional			
	positive	nc:PositiveValue	optional			
	boundaryRef	xsd:token	optional			

source

```
<xsd:element name="coordinateAxis" type="nc:CoordinateAxisType" substitutionGroup="nc:variable"/>
```

element **nc:coordinateAxisBoundary**

diagram




namespace <http://www.ucar.edu/schemas/netcdf>

The ncML specs group

type	nc:CoordinateAxisBoundaryType					
children	nc:attribute nc:values					
attributes	Name	Type	Use	Default	Fixed	Annotation
	name	xsd:token	required			
	shape	xsd:token	optional			
	type	nc:DataType	required			
source	<pre><xsd:element name="coordinateAxisBoundary" type="nc:CoordinateAxisBoundaryType" substitutionGroup="nc:variable"/></pre>					

element nc:coordinateSystem

diagram




namespace <http://www.ucar.edu/schemas/netcdf>

type **nc:CoordinateSystemType**

children	coordinateAxisRef nc:coordinateTransform coordinateTransformRef					
attributes	Name	Type	Use	Default	Fixed	Annotation
	name	xsd:token	required			
source	<pre><xsd:element name="coordinateSystem" type="nc:CoordinateSystemType"/></pre>					

element nc:coordinateTransform

diagram



namespace <http://www.ucar.edu/schemas/netcdf>

type **nc:CoordinateTransformType**


children **parameter**

The ncML specs group

used by	complexType	nc:CoordinateSystemType				
attributes	Name	Type	Use	Default	Fixed	Annotation
	name	xsd:token	required			
	authority	xsd:token	required			
	transformType	nc:TransformType	optional			
source	<code><xsd:element name="coordinateTransform" type="nc:CoordinateTransformType"/></code>					

complexType **nc:CoordinateAxisBoundaryType**

diagram



namespace <http://www.ucar.edu/schemas/netcdf>

type extension of **nc:VariableType**


children **nc:attribute nc:values**

used by element **nc:coordinateAxisBoundary**

attributes	Name	Type	Use	Default	Fixed	Annotation
	name	xsd:token	required			
	shape	xsd:token	optional			
	type	nc:DataType	required			
source	<pre> <xsd:complexType name="CoordinateAxisBoundaryType"> <xsd:complexContent> <xsd:extension base="nc:VariableType"/> </xsd:complexContent> </xsd:complexType> </pre>					

complexType **nc:CoordinateAxisType**

diagram



namespace <http://www.ucar.edu/schemas/netcdf>

type extension of **nc:VariableType**

children **nc:attribute nc:values**

used by element **nc:coordinateAxis**

attributes	Name	Type	Use	Default	Fixed	Annotation
	name	xsd:token	required			
	shape	xsd:token	optional			
	type	nc:DataType	required			
	units	xsd:token	required			
	axisType	nc:AxisType	optional			
	positive	nc:PositiveValue	optional			
	boundaryRef	xsd:token	optional			
source	<pre> <xsd:complexType name="CoordinateAxisType"> <xsd:complexContent> <xsd:extension base="nc:VariableType"> <xsd:attribute name="units" type="xsd:token" use="required"/> <xsd:attribute name="axisType" type="nc:AxisType" use="optional"/> </xsd:extension> </xsd:complexContent> </xsd:complexType> </pre>					

The ncML specs group


```

<xsd:attribute name="positive" type="nc:PositiveValue" use="optional"/>
<xsd:attribute name="boundaryRef" type="xsd:token" use="optional"/>
</xsd:extension>
</xsd:complexContent>
</xsd:complexType>

```

complexType nc:CoordinateSystemType

diagram



namespace <http://www.ucar.edu/schemas/netcdf>

children **coordinateAxisRef nc:coordinateTransform coordinateTransformRef**

used by
 element **nc:coordinateSystem**
 complexType **_GeoCoordinateSystemType**

attributes	Name	Type	Use	Default	Fixed	Annotation
	name	xsd:token	required			

source

```

<xsd:complexType name="CoordinateSystemType">
  <xsd:sequence>
    <xsd:element name="coordinateAxisRef" maxOccurs="unbounded">
      <xsd:complexType>
        <xsd:attribute name="ref" type="xsd:string"/>
      </xsd:complexType>
    </xsd:element>
    <xsd:choice minOccurs="0" maxOccurs="unbounded">
      <xsd:element ref="nc:coordinateTransform"/>
      <xsd:element name="coordinateTransformRef">
        <xsd:complexType>
          <xsd:attribute name="ref" type="xsd:token"/>
        </xsd:complexType>
      </xsd:element>
    </xsd:choice>
    <!-- coordinate axis references -->
    <!-- set of coordinateTransform or coordinateTransform references -->
  </xsd:sequence>
  <xsd:attribute name="name" type="xsd:token" use="required"/>
</xsd:complexType>

```

element nc:CoordinateSystemType/coordinateAxisRef

diagram



namespace <http://www.ucar.edu/schemas/netcdf>

attributes	Name	Type	Use	Default	Fixed	Annotation
	ref	xsd:string				

source


```

<xsd:element name="coordinateAxisRef" maxOccurs="unbounded">
  <xsd:complexType>
    <xsd:attribute name="ref" type="xsd:string"/>
  </xsd:complexType>
</xsd:element>

```

element nc:CoordinateSystemType/coordinateTransformRef

diagram



namespace <http://www.ucar.edu/schemas/netcdf>


attributes	Name	Type	Use	Default	Fixed	Annotation
	ref	xsd:token				

The ncML specs group

```
source <xsd:element name="coordinateTransformRef">
  <xsd:complexType>
    <xsd:attribute name="ref" type="xsd:token"/>
  </xsd:complexType>
</xsd:element>
```

complexType **nc:CoordinateTransformType**

diagram



namespace <http://www.ucar.edu/schemas/netcdf>

children **parameter**


used by element **nc:coordinateTransform**

attributes	Name	Type	Use	Default	Fixed	Annotation
	name	xsd:token	required			
	authority	xsd:token	required			
	transformType	nc:TransformType	optional			

```
source <xsd:complexType name="CoordinateTransformType">
  <xsd:choice minOccurs="0" maxOccurs="unbounded">
    <xsd:element name="parameter" type="nc:AttributeType"/>
  </xsd:choice>
  <xsd:attribute name="name" type="xsd:token" use="required"/>
  <xsd:attribute name="authority" type="xsd:token" use="required"/>
  <xsd:attribute name="transformType" type="nc:TransformType" use="optional"/>
</xsd:complexType>
```

element **nc:CoordinateTransformType/parameter**

diagram



namespace <http://www.ucar.edu/schemas/netcdf>

type **nc:AttributeType**


attributes	Name	Type	Use	Default	Fixed	Annotation
	name	xsd:token	required			
	type	nc:DataType	required			
	value	xsd:string	optional			
	separator	xsd:string				

```
source <xsd:element name="parameter" type="nc:AttributeType"/>
```

The ncML specs group

redefinition of complexType **NetcdfType**

diagram



type extension of **nc:NetcdfType**

children **nc:dimension nc:variable nc:attribute nc:coordinateSystem nc:coordinateTransform**

used by element **nc:netcdf**

attributes	Name	Type	Use	Default	Fixed	Annotation
	id	xsd:token	optional			
	uri	xsd:anyURI	optional			

```

source <xsd:complexType name="NetcdfType">
  <xsd:complexContent>
    <xsd:extension base="nc:NetcdfType">
      <xsd:choice minOccurs="0" maxOccurs="unbounded">
        <xsd:element ref="nc:coordinateSystem"/>
        <xsd:element ref="nc:coordinateTransform"/>
      </xsd:choice>
    </xsd:extension>
  </xsd:complexContent>
</xsd:complexType>

```

geoCoordinateSystem schema source

```

<?xml version="1.0" encoding="UTF-8" ?>
<!--

```

edited with XMLSPY v5 rel. 4 U (<http://www.xmlspy.com>) by Stefano Nativi (UCAR Unidata)


```
-->
<xsd:schema targetNamespace="http://www.ucar.edu/schemas/netcdf"
  xmlns:nc="http://www.ucar.edu/schemas/netcdf"
  xmlns:fgdc="http://www.fgdc.gov/metadata/standards" xmlns:gml="http://www.opengis.net/gml"
  xmlns:xsd="http://www.w3.org/2001/XMLSchema" elementFormDefault="qualified">
<xsd:annotation>
<xsd:documentation>
  <appinfo source="urn:ncML:specification:schema-
    xsd:geoCoordinateSystem:v0.3.1">geoCoordinateSystem.xsd</appinfo>
  <documentation xml:lang="en">Metadata for unreferenced or referenced geo coordinate systems
    characterizing a ncML dataset. An extension to the ncML core metadata in order to formalise netCDF
    metadata useful for GIS interoperability NcML Group, editor S. Nativi Creation: Boulder, Aug 2003; Update:
    Florence, Dec 2004;</documentation>
  </xsd:documentation>
</xsd:annotation>
<xsd:import namespace="http://www.ucar.edu/schemas/netcdf"
  schemaLocation="http://www.unidata.ucar.edu/schemas/netcdf-cs.xsd" />
<xsd:import namespace="http://www.opengis.net/gml"
  schemaLocation="C:\Nativi\Geomatics\STANDARDS\OpenGIS\GML NWIP\GML3\gml3.0\base\feature.xsd"
  />
<xsd:import namespace="http://www.opengis.net/gml"
  schemaLocation="C:\Nativi\Geomatics\STANDARDS\OpenGIS\GML
  NWIP\GML3\gml3.0\base\temporal.xsd" />
<xsd:import namespace="http://www.opengis.net/gml"
  schemaLocation="C:\Nativi\Geomatics\STANDARDS\OpenGIS\GML
  NWIP\GML3\gml3.0\base\coordinateReferenceSystems.xsd" />
<!--
===== Elements =====
-->
<xsd:element name="geoCoordinateSystem" type="nc:_GeoCoordinateSystemType"
  substitutionGroup="nc:coordinateSystem">
<xsd:annotation>
  <xsd:documentation>Dataset coordinate system whose domain is characterized by a geographic description.
    Such geographic description of the domain is generally useful for catalog service</xsd:documentation>
  </xsd:annotation>
</xsd:element>
<xsd:element name="geoRefCoordinateSystem" type="nc:_GeoRefCoordinateSystemType"
  substitutionGroup="nc:geoCoordinateSystem">
<xsd:annotation>
  <xsd:documentation>Dataset coordinate system whose domain is fully localized according to a spatial
    reference system. A localized domain is generally characterized by a geographic description, as
    well.</xsd:documentation>
  </xsd:annotation>
</xsd:element>
<!--
===== Complex type =====
-->
<xsd:complexType name="_GeoRefCoordinateSystemType">
<xsd:annotation>
  <xsd:documentation>Geo-referenced Coordinate System type</xsd:documentation>
  </xsd:annotation>
<xsd:complexContent>
  <xsd:extension base="nc:_GeoCoordinateSystemType">
  <xsd:sequence minOccurs="0">
  <xsd:element name="geoDomainLocation" type="nc:_DatasetGeoDomainLocation">
  <xsd:annotation>
    <xsd:documentation>Geographic Localization of the coordinate system Domain</xsd:documentation>
    </xsd:annotation>
  </xsd:element>
  </xsd:sequence>
  </xsd:extension>
  </xsd:complexContent>
  </xsd:complexType>
<xsd:complexType name="_GeoCoordinateSystemType">
<xsd:annotation>
  <xsd:documentation>It is an extension of the ncML-CS CoordinateSystemType</xsd:documentation>
  </xsd:annotation>
<xsd:complexContent>
  <xsd:extension base="nc:CoordinateSystemType">
  <xsd:sequence minOccurs="0">
```

```
<xsd:element name="geoDomainExtent" type="nc:_DatasetGeoDomainExtent">
<xsd:annotation>
  <xsd:documentation>Geographic Extension of the coordinate system Domain</xsd:documentation>
</xsd:annotation>
</xsd:element>
</xsd:sequence>
</xsd:extension>
</xsd:complexContent>
</xsd:complexType>
<xsd:complexType name="_DatasetGeoDomainExtent" abstract="false">
<xsd:sequence>
  <xsd:element ref="nc:spatialExtent" maxOccurs="unbounded" />
  <xsd:element ref="nc:verticalExtent" minOccurs="0" maxOccurs="unbounded" />
  <xsd:element ref="nc:temporalExtent" minOccurs="0" maxOccurs="unbounded" />
</xsd:sequence>
  <xsd:attribute name="description" type="xsd:string" use="optional" />
</xsd:complexType>
<xsd:complexType name="_DatasetGeoDomainLocation">
<xsd:sequence>
  <xsd:element ref="gml:_CoordinateReferenceSystem" />
</xsd:sequence>
</xsd:complexType>
<xsd:complexType name="_TemporalExtent" abstract="false">
<xsd:sequence>
  <xsd:element ref="gml:TPrimitive" />
</xsd:sequence>
</xsd:complexType>
<xsd:complexType name="_VerticalExtent" abstract="false">
<xsd:choice>
  <xsd:element ref="gml:pos" />
  <xsd:element ref="gml:coordinates" />
</xsd:choice>
  <xsd:attribute name="srsName" type="xsd:anyURI" use="optional" />
</xsd:complexType>
<!--
===== GML based elements =====
-->
<xsd:element name="verticalExtent" type="nc:_VerticalExtent" />
<xsd:element name="temporalExtent" type="nc:_TemporalExtent" />
<xsd:element name="spatialExtent" type="gml:BoundingShapeType" />
</xsd:schema>
```

Documentation of coverageGeoCoordSystem schema version 0.3.1

Schema coverageGeoCoordSystem.xsd

schema location: C:\Nativi\PAPER\GIM\schemas\coverageGeoCoordSystem.xsd
 targetNamespace: http://www.ucar.edu/schemas/netcdf

Elements	Complex types
coverageGeoCoordSystem	_CoverageGeoCoordSystem
coverageGeoRefCoordSystem	_CoverageGeoRefCoordSystem
grid	_GridCoverageType
gridCoverage	_RectifiedGridCoverageType
netcdfCoverages	
rangeInfo	
rectifiedGrid	
rectifiedGridCoverage	
variableRef	

schema location: C:\Nativi\PAPER\GIM\schemas\GeoCoordinateSystem.xsd
 targetNamespace: http://www.ucar.edu/schemas/netcdf

The ncML specs group

Elements


geoCoordinateSystem
geoRefCoordinateSystem
spatialExtent
temporalExtent
verticalExtent

Complex types

_DatasetGeoDomainExtent
_DatasetGeoDomainLocation
_GeoCoordinateSystemType
_GeoRefCoordinateSystemType
_TemporalExtent
_VerticalExtent

element **coverageGeoCoordSystem**

diagram



namespace <http://www.ucar.edu/schemas/netcdf>

type **nc:_CoverageGeoCoordSystem**

children **coordinateAxisRef** **nc:coordinateTransform** **coordinateTransformRef** **geoDomainExtent** **nc:variableRef** **gridCoverage**


used by element **netcdfCoverages**

attributes	Name	Type	Use	Default	Fixed	Annotation
	name	xsd:token	required			
annotation	documentation	Extent and geometry information which characterizes the Coverage coordinate system				

The ncML specs group

element **coverageGeoRefCoordSystem**

diagram



namespace <http://www.ucar.edu/schemas/netcdf>

type **nc:_CoverageGeoRefCoordSystem**


children **coordinateAxisRef** **nc:coordinateTransform** **coordinateTransformRef** **geoDomainExtent** **geoDomainLocation** **nc:variableRef** **nc:gridCoverage**

attributes	Name	Type	Use	Default	Fixed	Annotation
annotation	documentation	xsd:token	required			Extent, referenced location and geometry information which characterizes the Coverage coordinate system

The ncML specs group

element **grid**

diagram



namespace <http://www.ucar.edu/schemas/netcdf>

type **gml:GridType**

children **gml:metaDataProperty gml:description gml:name limits axisName**


used by complexType **_GridCoverageType**

attributes	Name	Type	Use	Default	Fixed	Annotation
	gml:id	ID	optional			
	gid	string	optional			documentation For backward compatibility with GML2. This identifier is superseded by gml:id inherited from AbstractGMLType.
	srsName	anyURI	optional			
	dimension	positiveInteger	required			
annotation	documentation	Coverage geometry information: describes the matrix dimension axes. These axes are pointed by the CoordinateAxisRef elements				

The ncML specs group

element **gridCoverage**

diagram



namespace <http://www.ucar.edu/schemas/netcdf>

type **nc:_GridCoverageType**


children **nc:grid nc:rangeInfo**

used by complexType **_CoverageGeoRefCoordSystem**

annotation documentation Grid dimensions stem from geo coordinate system axes. Grid extent depends on dataset dimensions.

element **netcdfCoverages**

diagram



namespace <http://www.ucar.edu/schemas/netcdf>

type extension of **nc:NetcdfType**

children **nc:dimension nc:variable nc:attribute nc:coverageGeoCoordSystem**


attributes	Name id	Type xsd:token	Use optional	Default	Fixed	Annotation

The ncML specs group

uri `xsd:anyURI` optional
 annotation documentation NetCDF dataset containing one or more Coverages

element **rangeInfo**

diagram




namespace `http://www.ucar.edu/schemas/netcdf`

children **rangeSet coverageFunction**

used by complexTypes **_GridCoverageType _RectifiedGridCoverageType**

element **rangeInfo/rangeSet**

diagram




namespace `http://www.ucar.edu/schemas/netcdf`

type **gml:RangeSetType**

children **gml:ValueCollection gml:DataBlock gml:File**

element **rangeInfo/coverageFunction**

diagram



namespace `http://www.ucar.edu/schemas/netcdf`


type **gml:CoverageFunctionType**

children **gml:MappingRule gml:GridFunction**

The ncML specs group

element **rectifiedGrid**

diagram



namespace <http://www.ucar.edu/schemas/netcdf>

type **gml:RectifiedGridType**


children **gml:metaDataProperty gml:description gml:name limits axisName origin offsetVectors**

used by complexType **_RectifiedGridCoverageType**

attributes	Name	Type	Use	Default	Fixed	Annotation
	gml:id	ID	optional			
	gid	string	optional			documentation For backward compatibility with GML2. This identifier is superseded by gml:id inherited from AbstractGMLType.
	srsName	anyURI	optional			
	dimension	positiveInteger	required			

element **rectifiedGridCoverage**

diagram



namespace <http://www.ucar.edu/schemas/netcdf>

type **nc:_RectifiedGridCoverageType**

children **nc:rectifiedGrid nc:rangeInfo**

The ncML specs group

element **variableRef**

diagram




namespace <http://www.ucar.edu/schemas/netcdf>

used by complexTypes **_CoverageGeoCoordSystem** **_CoverageGeoRefCoordSystem**

attributes	Name	Type	Use	Default	Fixed	Annotation
	ref	xsd:string				
annotation	documentation	Reference to netCDF variables whose values are the coverage matrix counts				

complexType **_CoverageGeoCoordSystem**

diagram



namespace <http://www.ucar.edu/schemas/netcdf>

type extension of **nc:_GeoCoordinateSystemType**

children **coordinateAxisRef** **nc:coordinateTransform** **coordinateTransformRef** **geoDomainExtent** **nc:variableRef** **gridCoverage**


used by element **coverageGeoCoordSystem**

attributes	Name	Type	Use	Default	Fixed	Annotation
	name	xsd:token	required			
annotation	documentation	Coordinate System of a Coverage dataset. Dataset coordinate system whose domain is characterized by a geographic description. Such geographic description of the domain is generally useful for catalog service. Coverage dataset is characterized by Grid implicit geometry.				

The ncML specs group

element **_CoverageGeoCoordSystem/gridCoverage**

diagram



namespace <http://www.ucar.edu/schemas/netcdf>


type **nc:_GridCoverageType**

children **nc:grid nc:rangelInfo**

annotation documentation Grid dimensions stem from geo coordinate system axes.

complexType **_CoverageGeoRefCoordSystem**

diagram




namespace <http://www.ucar.edu/schemas/netcdf>

The ncML specs group

type	extension of nc:_GeoRefCoordinateSystemType					
children	coordinateAxisRef nc:coordinateTransform coordinateTransformRef geoDomainExtent geoDomainLocation nc:variableRef nc:gridCoverage					
used by	element	coverageGeoRefCoordSystem				
attributes	Name	Type	Use	Default	Fixed	Annotation
	name	xsd:token	required			

complexType **_GridCoverageType**

diagram




namespace <http://www.ucar.edu/schemas/netcdf>

children	nc:grid nc:rangelInfo					
used by	elements	gridCoverage _CoverageGeoCoordSystem/gridCoverage				
annotation	documentation	If geoCS is located, then grid element is sufficient. Otherwise, useful elements are the specialisations: rectified, referenceable and sparse grids.				

complexType **_RectifiedGridCoverageType**

diagram




namespace <http://www.ucar.edu/schemas/netcdf>

children	nc:rectifiedGrid nc:rangelInfo					
used by	element	rectifiedGridCoverage				

The ncML specs group

element **nc:geoCoordinateSystem**

diagram



namespace <http://www.ucar.edu/schemas/netcdf>

type **nc:_GeoCoordinateSystemType**


children **coordinateAxisRef nc:coordinateTransform coordinateTransformRef geoDomainExtent**

attributes	Name	Type	Use	Default	Fixed	Annotation
	name	xsd:token	required			
annotation	documentation	Dataset coordinate system whose domain is characterized by a geographic description. Such geographic description of the domain is generally useful for catalog service				

The ncML specs group

element **gml:_ImplicitGeometry**

diagram



namespace <http://www.opengis.net/gml>

type **gml:AbstractGeometryType**


children **gml:metaDataProperty gml:description gml:name**

attributes	Name	Type	Use	Default	Fixed	Annotation
	gml:id	ID	optional			
	gid	string	optional			document For backward compatibility with GML2. This identifier is superseded by gml:id inherited from AbstractGMLType.
	srsName	anyURI	optional			

The ncML specs group

element **gml:Grid**

diagram



namespace <http://www.opengis.net/gml>

type **gml:GridType**

children **gml:metaDataProperty gml:description gml:name limits axisName**


used by complexType **gml:GridDomainType**

attributes	Name	Type	Use	Default	Fixed	Annotation
	gml:id	ID	optional			
	gid	string	optional			documentation For backward compatibility with GML2. This identifier is superseded by gml:id inherited from AbstractGMLType.
	srsName	anyURI	optional			
	dimension	positiveInteger	required			

The ncML specs group

element **gml:RectifiedGrid**

diagram



namespace <http://www.opengis.net/gml>

type **gml:RectifiedGridType**


children **gml:metaDataProperty gml:description gml:name limits axisName origin offsetVectors**

used by complexType **gml:RectifiedGridDomainType**

attributes	Name	Type	Use	Default	Fixed	Annotation
	gml:id	ID	optional			documentation
	gid	string	optional			For backward compatibility with GML2. This identifier is superseded by gml:id inherited from AbstractGMLType.
	srsName	anyURI	optional			
	dimension	positiveInteger	required			

complexType **gml:GridEnvelopeType**

diagram



The ncML specs group

namespace <http://www.opengis.net/gml>

children **low high**

used by element **gml:GridLimitsType/GridEnvelope**

annotation documentation Provides grid coordinate values for the diametrically opposed corners of an envelope that bounds a section of grid. The value of a single coordinate is the number of offsets from the origin of the grid in the direction of a specific axis.

element **gml:GridEnvelopeType/low**



namespace <http://www.opengis.net/gml>

type **gml:integerList**

element **gml:GridEnvelopeType/high**



namespace <http://www.opengis.net/gml>

type **gml:integerList**

complexType **gml:GridLimitsType**




namespace <http://www.opengis.net/gml>

children **GridEnvelope**

used by element **gml:GridType/limits**

element **gml:GridLimitsType/GridEnvelope**



namespace <http://www.opengis.net/gml>


type **gml:GridEnvelopeType**

children **low high**

The ncML specs group

complexType **gml:GridType**

diagram



namespace <http://www.opengis.net/gml>

type extension of **gml:AbstractGeometryType**

children **gml:metaDataProperty** **gml:description** **gml:name** **limits** **axisName**

used by elements **gml:Grid** **grid**

complexType **gml:RectifiedGridType**


attributes	Name	Type	Use	Default	Fixed	Annotation
	gml:id	ID	optional			
	gid	string	optional			

annotation	srsName	dimension	documentation
	anyURI	positiveInteger	Implicitly defines an unrectified grid, which is a network composed of two or more sets of equally spaced parallel lines in which the members of each set intersect the members of the other sets at right angles.

documentation For backward compatibility with GML2. This identifier is superseded by gml:id inherited from AbstractGMLType.

element **gml:GridType/limits**

diagram




namespace <http://www.opengis.net/gml>

type **gml:GridLimitsType**

children **GridEnvelope**

The ncML specs group

element **gml:GridType/axisName**




namespace <http://www.opengis.net/gml>

type **xsd:string**

complexType **gml:RectifiedGridType**

diagram



namespace <http://www.opengis.net/gml>

type extension of **gml:GridType**

children **gml:metaDataProperty gml:description gml:name limits axisName origin offsetVectors**

used by elements **gml:RectifiedGrid rectifiedGrid**

attributes	Name	Type	Use	Default	Fixed	Annotation
	gml:id	ID	optional			
	gid	string	optional			


documentation
For backward compatibility with GML2. This identifier is superseded by gml:id inherited from AbstractGMLType.

annotation	srsName	anyURI	optional			
	dimension	positiveInteger	required			
	documentation	A rectified grid has an origin and vectors that define its post locations.				

The ncML specs group

element **gml:RectifiedGridType/origin**

diagram



namespace <http://www.opengis.net/gml>


type **gml:PointPropertyType**

children **gml:Point**

attributes	Name	Type	Use	Default	Fixed simple	Annotation
	type	string				
	xlink:href	anyURI	optional			
	xlink:role	anyURI	optional			
	xlink:arcrole	anyURI	optional			
	xlink:title	string	optional			
	xlink:show	string	optional			
	xlink:actuate	string	optional			
	gml:remoteSchema	anyURI	optional			

element **gml:RectifiedGridType/offsetVectors**

diagram



namespace <http://www.opengis.net/gml>

type **gml:MultiPointPropertyType**


children **gml:MultiPoint**

attributes	Name	Type	Use	Default	Fixed simple	Annotation
	type	string				
	xlink:href	anyURI	optional			
	xlink:role	anyURI	optional			
	xlink:arcrole	anyURI	optional			
	xlink:title	string	optional			
	xlink:show	string	optional			
	xlink:actuate	string	optional			
	gml:remoteSchema	anyURI	optional			

The ncML specs group

element **gml:_Coverage**

diagram



namespace <http://www.opengis.net/gml>

type **gml:AbstractCoverageType**


children **gml:metaDataProperty** **gml:description** **gml:name** **gml:boundedBy** **gml:location** **gml:domainSet** **gml:rangeSet** **gml:coverageFunction**

The ncML specs group

attributes	Name	Type	Use	Default	Fixed	Annotation
	gml:id	ID	optional			
	fid	string				appInfo deprecated docume deprecated in ntation GML version 3.0
	dimension	positiveInteger	optional			

element **gml:coverageFunction**

diagram



namespace <http://www.opengis.net/gml>


type **gml:CoverageFunctionType**

children **gml:MappingRule** **gml:GridFunction**

used by complexTypes **gml:AbstractCoverageType** **gml:GridCoverageType** **gml:MultiPointCoverageType**
gml:MultiSurfaceCoverageType **gml:RectifiedGridCoverageType**

element **gml:DataBlock**

diagram



namespace <http://www.opengis.net/gml>

type **gml:DataBlockType**

children **gml:tupletList** **gml:rangeParameters**

used by complexType **gml:RangeSetType**

element **gml:domainSet**

namespace <http://www.opengis.net/gml>

type **gml:DomainSetType**

children **gml:_Geometry** **gml:_TObject** **gml:_Feature**


used by complexType **gml:AbstractCoverageType**

attributes	Name	Type	Use	Default	Fixed	Annotation
	type	string			simple	
	xlink:href	anyURI	optional			
	xlink:role	anyURI	optional			
	xlink:arcrole	anyURI	optional			
	xlink:title	string	optional			
	xlink:show	string	optional			
	xlink:actuate	string	optional			
	gml:remoteSchema	anyURI	optional			

The ncML specs group

element **gml:File**

diagram



namespace <http://www.opengis.net/gml>


type **gml:FileType**

children **fileName fileStructure mimeType compression gml:rangeParameters**

used by complexType **gml:RangeSetType**

element **gml:GridCoverage**

diagram



namespace <http://www.opengis.net/gml>


type **gml:GridCoverageType**

children **gml:gridDomain gml:rangeSet gml:coverageFunction**

attributes	Name	Type	Use	Default	Fixed	Annotation
	gml:id	ID	optional			
	fid	string				
	dimension	positiveInteger	required			
						appInfo deprecated docume deprecated in ntation GML version 3.0

element **gml:gridDomain**

diagram



namespace <http://www.opengis.net/gml>

type **gml:GridDomainType**


children **gml:Grid**

The ncML specs group

used by	complexType	gml:GridCoverageType				
attributes	Name	Type	Use	Default	Fixed	Annotation
	type	string			simple	
	xlink:href	anyURI	optional			
	xlink:role	anyURI	optional			
	xlink:arcrole	anyURI	optional			
	xlink:title	string	optional			
	xlink:show	string	optional			
	xlink:actuate	string	optional			
	gml:remoteSchema	anyURI	optional			

element **gml:GridFunction**

diagram



namespace <http://www.opengis.net/gml>


type **gml:GridFunctionType**

children **sequenceRule startPoint**

used by complexType **gml:CoverageFunctionType**

element **gml:IndexMap**

diagram



namespace <http://www.opengis.net/gml>


type **gml:IndexMapType**

children **sequenceRule startPoint lookUpTable**

The ncML specs group

element **gml:MappingRule**

diagram



namespace <http://www.opengis.net/gml>

type **gml:StringOrRefType**


used by complexType **gml:CoverageFunctionType**

attributes	Name	Type	Use	Default	Fixed	Annotation
	gml:id	ID	optional			
	type	string			simple	
	xlink:href	anyURI	optional			
	xlink:role	anyURI	optional			
	xlink:arcrole	anyURI	optional			
	xlink:title	string	optional			
	xlink:show	string	optional			
	xlink:actuate	string	optional			
	gml:remoteSchema	anyURI	optional			

annotation documentation Description of a rule for associating members from the domainSet with members of the rangeSet.

element **gml:MultiPointCoverage**

diagram



namespace <http://www.opengis.net/gml>


type **gml:MultiPointCoverageType**

children **gml:multiPointDomain gml:rangeSet gml:coverageFunction**

attributes	Name	Type	Use	Default	Fixed	Annotation
	gml:id	ID	optional			
	fid	string				applInfo deprecated in GML version 3.0
	dimension	positiveInteger	required			

element **gml:multiPointDomain**

diagram



namespace <http://www.opengis.net/gml>

type **gml:MultiPointDomainType**

children **gml:MultiPoint**


used by complexType **gml:MultiPointCoverageType**

The ncML specs group

attributes	Name	Type	Use	Default	Fixed	Annotation
	type	string			simple	
	xlink:href	anyURI	optional			
	xlink:role	anyURI	optional			
	xlink:arcrole	anyURI	optional			
	xlink:title	string	optional			
	xlink:show	string	optional			
	xlink:actuate	string	optional			
	gml:remoteSchema	anyURI	optional			

element **gml:MultiSurfaceCoverage**

diagram



namespace <http://www.opengis.net/gml>

type **gml:MultiSurfaceCoverageType**

children **gml:multiSurfaceDomain gml:rangeSet gml:coverageFunction**

attributes	Name	Type	Use	Default	Fixed	Annotation
	gml:id	ID	optional			
	fid	string				applInfo deprecated in GML version 3.0
	dimension	positiveInteger	required			

element **gml:multiSurfaceDomain**

diagram



namespace <http://www.opengis.net/gml>

type **gml:MultiSurfaceDomainType**

children **gml:MultiSurface**


used by complexType **gml:MultiSurfaceCoverageType**

attributes	Name	Type	Use	Default	Fixed	Annotation
	type	string			simple	
	xlink:href	anyURI	optional			
	xlink:role	anyURI	optional			
	xlink:arcrole	anyURI	optional			
	xlink:title	string	optional			
	xlink:show	string	optional			
	xlink:actuate	string	optional			
	gml:remoteSchema	anyURI	optional			

The ncML specs group

element **gml:rangeParameters**

diagram



namespace <http://www.opengis.net/gml>


type **gml:RangeParametersType**

The ncML specs group

children	gml:_Value					
used by	complexTypees	gml:DataBlockType gml:FileType				
attributes	Name	Type	Use	Default	Fixed	Annotation
	type	string			simple	
	xlink:href	anyURI	optional			
	xlink:role	anyURI	optional			
	xlink:arcrole	anyURI	optional			
	xlink:title	string	optional			
	xlink:show	string	optional			
	xlink:actuate	string	optional			
	gml:remoteSchema	anyURI	optional			

element **gml:rangeSet**

diagram



namespace <http://www.opengis.net/gml>


type **gml:RangeSetType**

children **gml:ValueCollection gml:DataBlock gml:File**

used by complexTypes **gml:AbstractCoverageType gml:GridCoverageType gml:MultiPointCoverageType gml:MultiSurfaceCoverageType gml:RectifiedGridCoverageType**

element **gml:RectifiedGridCoverage**

diagram



namespace <http://www.opengis.net/gml>

type **gml:RectifiedGridCoverageType**


children **gml:rectifiedGridDomain gml:rangeSet gml:coverageFunction**

attributes	Name	Type	Use	Default	Fixed	Annotation
	gml:id	ID	optional			
	fid	string				appInfo deprecated in GML version 3.0
	dimension	positiveInteger	required			

The ncML specs group

element **gml:rectifiedGridDomain**

diagram



namespace <http://www.opengis.net/gml>

type **gml:RectifiedGridDomainType**


children **gml:RectifiedGrid**

used by complexType **gml:RectifiedGridCoverageType**

attributes	Name	Type	Use	Default	Fixed	Annotation
	type	string			simple	
	xlink:href	anyURI	optional			
	xlink:role	anyURI	optional			
	xlink:arcrole	anyURI	optional			
	xlink:title	string	optional			
	xlink:show	string	optional			
	xlink:actuate	string	optional			
	gml:remoteSchema	anyURI	optional			

element **gml:tupleList**

diagram



namespace <http://www.opengis.net/gml>

type **gml:CoordinatesType**

used by complexType **gml:DataBlockType**

attributes	Name	Type	Use	Default	Fixed	Annotation
	decimal	string				
	cs	string		.		
	ts	string		 		

coverageGeoCoordSystem schema source

```
<?xml version="1.0" encoding="UTF-8" ?>
- <!--
  edited with XMLSPY v5 rel. 4 U (http://www.xmlspy.com) by Stefano Nativi (UCAR Unidata)
-->
<xsd:schema targetNamespace="http://www.ucar.edu/schemas/netcdf"
  xmlns:xsd="http://www.w3.org/2001/XMLSchema" xmlns:gml="http://www.opengis.net/gml"
  xmlns:fgdc="http://www.fgdc.gov/metadata/standards"
  xmlns:nc="http://www.ucar.edu/schemas/netcdf" elementFormDefault="qualified">
  <xsd:annotation>
  <xsd:documentation>
    <appinfo source="urn:ncML:specification:schema-
      xsd:CoverageGeoCoordSystem:v0.3.1">coverageGeoCoordSystem.xsd</appinfo>
    <documentation xml:lang="en">Metadata for coverage associated to a referenced or unreferenced geo
      coordinate system. An extension to the ncML core metadata in order to formalise netCDF metadata useful
      for GIS interoperability NcML Group, editor S. Nativi Creation: Boulder, Aug 2003; Update: Florence, Dec
      2004; Update: Florence, Jan 2005;</documentation>
    </xsd:documentation>
  </xsd:annotation>
  </xsd:documentation>
  <xsd:import namespace="http://www.ucar.edu/schemas/netcdf"
    schemaLocation="C:\Nativi\PAPERI\GIM\schemas\GeoCoordinateSystem.xsd" />
```

The ncML specs group

```

<xsd:import namespace="http://www.opengis.net/gml"
  schemaLocation="C:\Nativi\Geomatics\STANDARDS\OpenGIS\GML NWIP\GML3\gml3.0\base\grids.xsd"
/>
<xsd:import namespace="http://www.opengis.net/gml"
  schemaLocation="C:\Nativi\Geomatics\STANDARDS\OpenGIS\GML
  NWIP\GML3\gml3.0\base\coverage.xsd" />
<!--
===== Complex Types defined =====
-->
<xsd:complexType name="_CoverageGeoCoordSystem">
<xsd:annotation>
  <xsd:documentation>Coordinate System of a Coverage dataset. Dataset coordinate system whose domain is
  characterized by a geographic description. Such geographic description of the domain is generally useful
  for catalog service. Coverage dataset is characterized by Grid implicit geometry.</xsd:documentation>
</xsd:annotation>
<xsd:complexContent>
<xsd:extension base="nc:_GeoCoordinateSystemType">
<xsd:sequence>
  <xsd:element ref="nc:variableRef" />
<xsd:element name="gridCoverage" type="nc:_GridCoverageType" minOccurs="0" maxOccurs="unbounded">
<xsd:annotation>
  <xsd:documentation>Grid dimensions stem from geo coordinate system axes.</xsd:documentation>
</xsd:annotation>
</xsd:element>
</xsd:sequence>
</xsd:extension>
</xsd:complexContent>
</xsd:complexType>
<xsd:complexType name="_GridCoverageType">
<xsd:annotation>
  <xsd:documentation>If geoCS is located, then grid element is sufficient. Otherwise, useful elements are the
  specialisations: rectified, referenceable and sparse grids.</xsd:documentation>
</xsd:annotation>
<xsd:sequence>
  <xsd:element ref="nc:grid" />
  <xsd:element ref="nc:rangeInfo" minOccurs="0" />
</xsd:sequence>
</xsd:complexType>
<xsd:complexType name="_CoverageGeoRefCoordSystem">
<xsd:complexContent>
<xsd:extension base="nc:_GeoRefCoordinateSystemType">
<xsd:sequence>
<xsd:annotation>
  <xsd:documentation>Whether geoDomainLocation is present, Coverage can be a rectified Grid. On the contrary,
  the appropriate elements is the generalization: Grid</xsd:documentation>
</xsd:annotation>
<xsd:element ref="nc:variableRef" maxOccurs="unbounded" />
<xsd:element ref="nc:gridCoverage" minOccurs="0" maxOccurs="unbounded" />
</xsd:sequence>
</xsd:extension>
</xsd:complexContent>
</xsd:complexType>
<xsd:complexType name="_RectifiedGridCoverageType">
<xsd:sequence>
  <xsd:element ref="nc:rectifiedGrid" />
  <xsd:element ref="nc:rangeInfo" minOccurs="0" />
</xsd:sequence>
</xsd:complexType>
<!--
===== Global Element defined
-->
<xsd:element name="netcdfCoverages" substitutionGroup="nc:netcdf">
<xsd:annotation>
  <xsd:documentation>NetCDF dataset containing one or more Coverages</xsd:documentation>
</xsd:annotation>
<xsd:complexType>
<xsd:complexContent>
<xsd:extension base="nc:NetcdfType">
<xsd:sequence>

```

```

<xsd:element ref="nc:coverageGeoCoordSystem" maxOccurs="unbounded" />
</xsd:sequence>
</xsd:extension>
</xsd:complexContent>
</xsd:complexType>
</xsd:element>
<xsd:element name="coverageGeoCoordSystem" type="nc:_CoverageGeoCoordSystem"
  substitutionGroup="nc:geoCoordinateSystem">
<xsd:annotation>
  <xsd:documentation>Extent and geometry information which characterizes the Coverage coordinate
    system</xsd:documentation>
</xsd:annotation>
</xsd:element>
<xsd:element name="coverageGeoRefCoordSystem" type="nc:_CoverageGeoRefCoordSystem"
  substitutionGroup="nc:coverageGeoCoordSystem">
<xsd:annotation>
  <xsd:documentation>Extent, referenced location and geometry information which characterizes the Coverage
    coordinate system</xsd:documentation>
</xsd:annotation>
</xsd:element>
<xsd:element name="rectifiedGridCoverage" type="nc:_RectifiedGridCoverageType"
  substitutionGroup="nc:gridCoverage" />
<xsd:element name="gridCoverage" type="nc:_GridCoverageType">
<xsd:annotation>
  <xsd:documentation>Grid dimensions stem from geo coordinate system axes. Grid extent depends on dataset
    dimensions.</xsd:documentation>
</xsd:annotation>
</xsd:element>
<xsd:element name="rangeInfo">
<xsd:complexType>
<xsd:sequence>
  <xsd:element name="rangeSet" type="gml:RangeSetType" />
  <xsd:element name="coverageFunction" type="gml:CoverageFunctionType" minOccurs="0" />
</xsd:sequence>
</xsd:complexType>
</xsd:element>
<xsd:element name="variableRef">
<xsd:annotation>
  <xsd:documentation>Reference to netCDF variables whose values are the coverage matrix
    counts</xsd:documentation>
</xsd:annotation>
</xsd:complexType>
<xsd:attribute name="ref" type="xsd:string" />
</xsd:element>
<!--
===== GML based elements =====
-->
<xsd:element name="grid" type="gml:GridType">
<xsd:annotation>
  <xsd:documentation>Coverage geometry information: describes the matrix dimension axes. These axes are
    pointed by the CoordianteAxisRef elements</xsd:documentation>
</xsd:annotation>
</xsd:element>
<xsd:element name="rectifiedGrid" type="gml:RectifiedGridType" />
</xsd:schema>

```

REFERENCES

- Caron. J., “NetCDF Java Library”, Unidata netCDF packages, available at <http://www.unidata.ucar.edu/packages/netcdf-java/>
- ISO 19107, “Geographic information — Spatial schema”, Reference number ISO 19107:2003(E), 2003.

The ncML specs group

- ISO/DIS 19108, “Geographic information — Temporal schema”, document N1001, 12 Oct 2000.
- ISO 19111, “Geographic information — Spatial Referencing by Coordinates”, Reference number ISO 19111:2003(E), 2003.
- ISO 19115, “Geographic information — Metadata” Reference number ISO 19115:2003(E), 2003.
- ISO 19115, “Extensions to ISO/TC 211 – 19115.3 Metadata to support Imagery and Gridded Data”, Document N233, 4 Aug 2000
- ISO 19123, “Schema for coverage geometry and functions”, document N1038, 18 Jan 2001
- S. Nativi, J. Caron, E. Davis and B. Domenico, “Design and implementation of netCDF Markup Language (NcML) and Its GML-based extension (NcML-GML)”, to be published on the Computers & Geosciences Journal, Elsevier Publication, for the Special Issue on the “Applications of XML in Geosciences”.
- Nativi, S., Blumenthal, B., Habermann, T., Hertzmann, D., Raskin, R., Caron, J., Domenico, B., Ho, Y., Weber, J., 2004. Differences among the data models used by the Geographic Information Systems and Atmospheric Science communities, Proceedings of American Meteorological Society – 20th Interactive Image Processing Systems Conference, Seattle (WA), Jan 2004.
- Open GIS Consortium Inc. “Abstract Specification - Topic6: The Coverage Type and its Subtypes ver. 4”, Document 99-106, 31 Mar 1999.
- Open GIS Consortium Inc. “Web Coverage Service (WCS), Version 1.0.0”, Document OGC 03-065r6, Aug 2003.
- Open GIS Consortium Inc. “Web Map Service Implementation Specification ver. 1.1.1”, Document OGC 01-068r3, 11 Jul 2002.
- Open GIS Consortium Inc. “OpenGIS® Geography Markup Language (GML) Implementation Specification version 3.0”, Document OGC 02 023r4, 29 Jan 2003.
- Unidata netCDF Group, “netCDF Usage”, Unidata software: netCDF, available at <http://my.unidata.ucar.edu/content/software/netcdf/usage.html>
- Unidata netCDF Group, “NetCDF Frequently asked questions”, Unidata software: netCDF, [http://available at http://my.unidata.ucar.edu/content/software/netcdf/faq.html#whatisit](http://my.unidata.ucar.edu/content/software/netcdf/faq.html#whatisit)
- NcML Specification Group, “NcML Overview”, Unidata NcML tutorial, available at www.unidata.ucar.edu/packages/netcdf/ncml/
- Unidata netCDF Group, “NetCDF Description Language”, Unidata software: netCDF, available at <http://www.unidata.ucar.edu/packages/netcdf/guidec/guidec-15.html#HEADING15-0>
- Unidata netCDF Group, “netCDF Conventions”, netCDF User's Guide, available at <http://www.unidata.ucar.edu/packages/netcdf/conventions.html>