QualityForge API

REST + WebSocket OpenAPI 3.0

□□□□	□□	□□	□□
API	1.0.0	operationId	2026-08-10

□□□□

docs/04-architecture/32-API .yaml OpenAPI 3.0.0 98 164 44 Schema YAML

0.

□□	□□
	QualityForge Core API
	/api/v1
	HTTPS + JSON multipart/form-data WSS
	kebab-case/ JSON camelCase
	32-API .yaml REST 34- .md 36-WebSocket .md
	164 operationId ID OpenAPI operationId

0.1

- 1
- 2
- 3
- 4
- 5 REST
- 6 Schema

- 7 WebSocket
- 8
- 9

1.

□□	□□
	URL /api/v1 v1
	application/json; charset=utf-8 multipart/form-data
	ISO 8601 / RFC 3339 UTC
	ID UUID ID
	requestId /Agent/ taskId runId traceId
	/ / /
	Content-Type 415 406

1.1

```
GET /api/v1/workspaces?page=1&pageSize=20 HTTP/1.1
Authorization: Bearer <access-token>
X-Request-ID: 7d3d5c7d-...
Accept: application/json
```

2.

		/	
BearerAuth	http	header: bearer	
ApiKeyAuth	apiKey	header: X-API-Key	CI/CD qf_live_xxx SHA-256
RunnerTokenAuth	apiKey	header: X-Runner-Token	Runner /

2.1

- Bearer JWT
- ApiKeyAuth CI/CD Scope

- RunnerTokenAuth Runner
- RBAC /Workspace
- Secret LLM Key Token

3.

3.1

```
{
  "code": "SUCCESS",
 "message": "    ",
  "timestamp": 1719234500000,
  "requestId": "req-544d9e96-dbbc-4c98-aae1-b6cbd3ae96dd"
}
```

> □□□□□□
>
> 32-API .yaml ResponseEnvelope data 37-API .md code/message/data YAML

	200 / 201 202 204 responses
	page/pageSize items page pageSize total
/	400
	POST Idempotency-Key / / 409
	version/If-Match 409
	202

4.

```
{
  "code": "RESOURCE_NOT_FOUND",
 "message": "    ",
  "timestamp": 1719234500000,
  "requestId": "req-544d9e96-dbbc-4c98-aae1-b6cbd3ae96dd"
}
```

HTTP		
400		
401	Token	

HTTP		
403		
404		ID/
409		
413/415	/	
422		
429	/	Retry-After
500/502/503/504		retryable=true

5. REST

OpenAPI ID “ operationId” YAML SDK
Schema 6

5.1 Workspace 17 operations

ID			/	/
API-WS-001	GET /workspaces		BearerAuth :	: : 200 ResponseEnvelope + object -
API-WS-002	POST /workspaces		BearerAuth :	: application/json: object : 200 ResponseEnvelope + object - (Saga)
API-WS-003	POST /workspaces/{id}/ai-scan	Swagger/OpenAPI AI	BearerAuth : path id (, string/uuid)	: application/json: object : 200 ResponseEnvelope + object - AI
API-WS-004	GET /workspaces/{id}		BearerAuth : path id (, string/uuid)	: : 200 ResponseEnvelope + object - OK 404
API-WS-005	PUT /workspaces/{id}		BearerAuth : path id (, string/uuid)	: application/json: Workspace : 200 ResponseEnvelope + object - 400 404
API-WS-006	DELETE /workspaces/{id}	Archived	BearerAuth : path id (, string/uuid)	: : 200 404
API-WS-007	GET /workspaces/{id}/ai-context	AI	BearerAuth : path id (, string/uuid)	: : 200 ResponseEnvelope + object - OK 404
API-WS-008	PUT /workspaces/{id}/ai-context	AI	BearerAuth : path id (, string/uuid)	: application/json: AIContext : 200 ResponseEnvelope + object - 400
API-WS-009	GET /workspaces/{id}/ai-scan/status	AI	BearerAuth : path id (, string/uuid)	: : 200 ResponseEnvelope + object - OK
API-WS-010	GET /workspaces/{id}/environments		BearerAuth : path id (, string/uuid)	: : 200 ResponseEnvelope + object - OK
API-WS-011	POST /workspaces/{id}/environments		BearerAuth : path id (, string/uuid)	: application/json: Environment : 200 ResponseEnvelope + object - 400
API-WS-012	GET /environments/{id}		BearerAuth : path id (, string/uuid)	: : 200 ResponseEnvelope + object - OK 404

ID			/	/
API-WS-013	PUT /environments/{id}		BearerAuth : path id (, string/uuid)	: application/json: Environment : 200 ResponseEnvelope + object - 404
API-WS-014	DELETE /environments/{id}		BearerAuth : path id (, string/uuid)	: : 200 404
API-WS-015	GET /workspaces/{id}/secrets		BearerAuth : path id (, string/uuid)	: : 200 ResponseEnvelope + object - OK
API-WS-016	POST /workspaces/{id}/secrets	/	BearerAuth : path id (, string/uuid)	: application/json: object : 200 ResponseEnvelope + object - 400
API-WS-017	DELETE /workspaces/{id}/secrets/{secretId}		BearerAuth : path id (, string/uuid) path secretId (, string/uuid)	: : 200 404

5.2 TestDesign 20 operations

ID			/	/
API-TD-001	POST /test-designs/{designId}/generate-cases	AI	BearerAuth : path designId (, string/uuid)	: application/json: object : 200 ResponseEnvelope + object -
API-TD-002	POST /test-designs/upload	multipart	BearerAuth :	: multipart/form-data: object : 200 ResponseEnvelope + object -
API-TD-003	GET /test-designs/requirements		BearerAuth : WorkspaceIdQuery PageParam PageSizeParam	: : 200 ResponseEnvelope + object - OK
API-TD-004	GET /test-designs/requirements/{id}		BearerAuth : path id (, string/uuid)	: : 200 ResponseEnvelope + object - OK 404
API-TD-005	DELETE /test-designs/requirements/{id}		BearerAuth : path id (, string/uuid)	: : 200
API-TD-006	POST /test-designs/{designId}/parse		BearerAuth : path designId (, string/uuid)	: : 202 ResponseEnvelope + object -
API-TD-007	GET /test-designs/plans		BearerAuth : WorkspaceIdQuery query	: : 200 ResponseEnvelope + object - OK

ID			/	/
			requirementDocumentId (, string/uuid) PageParam PageSizeParam	
API-TD-008	POST /test-designs/plans		BearerAuth :	: application/json: TestDesignPlan : 201 ResponseEnvelope + object -
API-TD-009	GET /test-designs/plans/{planId}		BearerAuth : path planId (, string/uuid)	: : 200 ResponseEnvelope + object - OK 404
API-TD-010	PUT /test-designs/plans/{planId}		BearerAuth : path planId (, string/uuid)	: application/json: TestDesignPlan : 200 ResponseEnvelope + object -
API-TD-011	GET /test-designs/cases		BearerAuth : WorkspaceIdQuery query scenarioId (, string/uuid) query status (, string{DRAFT, GENERATING, REVIEWING, APPROVED}) PageParam PageSizeParam	: : 200 ResponseEnvelope + object - OK
API-TD-012	PUT /test-designs/cases/{caseId}		BearerAuth : path caseId (, string/uuid)	: application/json: DesignTestCase : 200 ResponseEnvelope + object -
API-TD-013	DELETE /test-designs/cases/{caseId}		BearerAuth : path caseId (, string/uuid)	: : 200
API-TD-014	POST /test-designs/cases/batch-approve	DesignTestCase → TestCase	BearerAuth :	: application/json: object : 200 ResponseEnvelope + object - 409 ResponseEnvelope - ERR_DESIGN_APPLY_CONFLICT
API-TD-015	GET /test-designs/{designId}/ir	TestingIR	BearerAuth : path designId (, string/uuid)	: : 200 ResponseEnvelope + object - OK 404
API-TD-016	POST /test-designs/{designId}/ir/recompile	TestingIR	BearerAuth : path designId (, string/uuid)	: : 202 ResponseEnvelope + object - 404
API-TD-017	GET /test-designs/{designId}/rules	IR	BearerAuth : path designId (, string/uuid) query page (, integer) query	: : 200 ResponseEnvelope + object - OK 404

ID			/	/
			pageSize (, integer)	
API-TD-018	GET /reviews		BearerAuth : query status (, string{OPEN, RESOLVED, EXPIRED}) query assetType (, string) query severity (, string{forced, required, sample, info}) query page (, integer) query pageSize (, integer)	: : 200 ResponseEnvelope + object - OK
API-TD-019	POST /reviews		BearerAuth :	: application/json: ReviewTask : 201 ResponseEnvelope + object -
API-TD-020	PUT /reviews/{reviewId}/resolve		BearerAuth : path reviewId (, string)	: application/json: object : 200 ResponseEnvelope + object - 404

5.3 TestAsset 40 operations

ID			/	/
API-TA-001	POST /assets/locators/self-heal	UI AI	BearerAuth :	: application/json: object : 200 ResponseEnvelope + object -
API-TA-002	GET /assets/cases		BearerAuth : query workspaceId (, string/uuid)	: : 200 ResponseEnvelope + object -
API-TA-003	POST /assets/cases	AI	BearerAuth :	: application/json: object : 200 ResponseEnvelope + object -
API-TA-004	GET /assets/data-profiles		BearerAuth : query workspaceId (, string/uuid)	: : 200 ResponseEnvelope + object -
API-TA-005	POST /assets/data-profiles		BearerAuth :	: application/json: object : 200 ResponseEnvelope + object -
API-TA-006	GET /assets/cases/{caseId}		BearerAuth : path caseId (, string/uuid)	: : 200 ResponseEnvelope + object - OK 404
API-TA-007	PUT /assets/cases/{caseId}	( )	BearerAuth : path caseId (, string/uuid)	: application/json: TestCase : 200 ResponseEnvelope + object - 404
API-	DELETE /assets/cases/{caseId}	(Deprecated)	BearerAuth : path caseId (,	:

ID			/	/
TA-008			string/uuid)	: 200 404
API-TA-009	GET /assets/cases/{caseId}/versions		BearerAuth : path caseId (, string/uuid) PageParam PageSizeParam	: : 200 ResponseEnvelope + object - OK
API-TA-010	POST /assets/cases/deduplicate	AI	BearerAuth :	: application/json: object : 200 ResponseEnvelope + object -
API-TA-011	GET /assets/suites		BearerAuth : WorkspaceIdQuery PageParam PageSizeParam	: : 200 ResponseEnvelope + object - OK
API-TA-012	POST /assets/suites		BearerAuth :	: application/json: TestSuite : 200 ResponseEnvelope + object - 400
API-TA-013	GET /assets/suites/{id}		BearerAuth : path id (, string/uuid)	: : 200 ResponseEnvelope + object - OK 404
API-TA-014	PUT /assets/suites/{id}		BearerAuth : path id (, string/uuid)	: application/json: TestSuite : 200 ResponseEnvelope + object - 404
API-TA-015	DELETE /assets/suites/{id}		BearerAuth : path id (, string/uuid)	: : 200 404
API-TA-016	POST /assets/suites/{id}/cases		BearerAuth : path id (, string/uuid)	: application/json: object : 200
API-TA-017	DELETE /assets/suites/{id}/cases/{caseId}		BearerAuth : path id (, string/uuid) path caseId (, string/uuid)	: : 200 404
API-TA-018	GET /assets/locators		BearerAuth : WorkspaceIdQuery PageParam PageSizeParam	: : 200 ResponseEnvelope + object - OK
API-TA-019	POST /assets/locators		BearerAuth :	: application/json: Locator : 200 ResponseEnvelope + object - 400
API-TA-020	GET /assets/locators/{id}		BearerAuth : path id (, string/uuid)	: : 200 ResponseEnvelope + object - OK 404
API-TA-021	PUT /assets/locators/{id}		BearerAuth : path id (, string/uuid)	: application/json: Locator : 200 ResponseEnvelope + object - 404

ID			/	/
API-TA-022	DELETE /assets/locators/{id}		BearerAuth : path id (, string/uuid)	: : 200 404
API-TA-023	GET /assets/mocks	Mock	BearerAuth : WorkspaceIdQuery PageParam PageSizeParam	: : 200 ResponseEnvelope + object - OK
API-TA-024	POST /assets/mocks	Mock	BearerAuth :	: application/json: MockConfig : 200 ResponseEnvelope + object - 400
API-TA-025	GET /assets/mocks/{id}	Mock	BearerAuth : path id (, string/uuid)	: : 200 ResponseEnvelope + object - OK 404
API-TA-026	PUT /assets/mocks/{id}	Mock	BearerAuth : path id (, string/uuid)	: application/json: MockConfig : 200 ResponseEnvelope + object - 404
API-TA-027	DELETE /assets/mocks/{id}	Mock	BearerAuth : path id (, string/uuid)	: : 200 404
API-TA-028	GET /assets/contracts		BearerAuth : WorkspaceIdQuery PageParam PageSizeParam	: : 200 ResponseEnvelope + object - OK
API-TA-029	POST /assets/contracts	/	BearerAuth :	: application/json: APIContract : 200 ResponseEnvelope + object - 400
API-TA-030	GET /assets/contracts/{id}		BearerAuth : path id (, string/uuid)	: : 200 ResponseEnvelope + object - OK 404
API-TA-031	PUT /assets/contracts/{id}		BearerAuth : path id (, string/uuid)	: application/json: APIContract : 200 ResponseEnvelope + object - 404
API-TA-032	DELETE /assets/contracts/{id}		BearerAuth : path id (, string/uuid)	: : 200 404
API-TA-033	GET /assets/data-profiles/{id}		BearerAuth : path id (, string/uuid)	: : 200 ResponseEnvelope + object - OK 404
API-TA-034	PUT /assets/data-profiles/{id}		BearerAuth : path id (, string/uuid)	: application/json: TestDataProfile : 200 ResponseEnvelope + object - 404

ID			/	/
API-TA-035	DELETE /assets/data-profiles/{id}		BearerAuth : path id (, string/uuid)	: : 200 404
API-TA-036	POST /assets/data/synthesize	AI	BearerAuth :	: application/json: object : 200 ResponseEnvelope + object -
API-TA-037	GET /assets/cases/{caseId}/assertions		BearerAuth : path caseId (, string/uuid)	: : 200 ResponseEnvelope + object - OK 404
API-TA-038	POST /assets/cases/{caseId}/assertions		BearerAuth : path caseId (, string/uuid)	: application/json: Assertion : 201 ResponseEnvelope + object - 404
API-TA-039	PUT /assets/assertions/{assertionId}		BearerAuth : path assertionId (, string/uuid)	: application/json: Assertion : 200 ResponseEnvelope + object - 404
API-TA-040	DELETE /assets/assertions/{assertionId}		BearerAuth : path assertionId (, string/uuid)	: : 200 404

5.4 Execution 10 operations

ID			/	/
API-EX-001	POST /executions/tasks/run		BearerAuth :	: application/json: object : 200 ResponseEnvelope + object -
API-EX-002	GET /executions/plans		BearerAuth : WorkspaceIdQuery PageParam PageSizeParam	: : 200 ResponseEnvelope + object - OK
API-EX-003	POST /executions/plans		BearerAuth :	: application/json: ExecutionPlan : 200 ResponseEnvelope + object - 400
API-EX-004	GET /executions/plans/{id}		BearerAuth : path id (, string/uuid)	: : 200 ResponseEnvelope + object - OK 404
API-EX-005	PUT /executions/plans/{id}		BearerAuth : path id (, string/uuid)	: application/json: ExecutionPlan : 200 ResponseEnvelope + object - 404
API-EX-006	DELETE /executions/plans/{id}		BearerAuth : path id (, string/uuid)	: : 200 404

ID			/	/
API-EX-007	GET /executions/tasks	( )	BearerAuth : WorkspaceIdQuery PageParam PageSizeParam	: : 200 ResponseEnvelope + object - OK
API-EX-008	POST /executions/tasks/{taskId}/cancel	( )	BearerAuth : path taskId (, string/uuid)	: : 200
API-EX-009	GET /executions/tasks/{taskId}/results	( )	BearerAuth : path taskId (, string/uuid) PageParam PageSizeParam	: : 200 ResponseEnvelope + object - OK
API-EX-010	GET /executions/tasks/{taskId}/status	( )	BearerAuth : path taskId (, string/uuid)	: : 200 ResponseEnvelope + object - OK 404

5.5 QualityIntelligence 7 operations

ID			/	/
API-QI-001	POST /intelligence/analysis/trigger	AI RCA	BearerAuth :	: application/json: object : 200 ResponseEnvelope + object -
API-QI-002	GET /intelligence/reports	( )	BearerAuth : WorkspaceIdQuery PageParam PageSizeParam	: : 200 ResponseEnvelope + object - OK
API-QI-003	GET /intelligence/reports/{reportId}	( )	BearerAuth : path reportId (, string/uuid)	: : 200 ResponseEnvelope + object - OK 404
API-QI-004	GET /intelligence/reports/{reportId}/failures	( )	BearerAuth : path reportId (, string/uuid) PageParam PageSizeParam	: : 200 ResponseEnvelope + object - OK 404
API-QI-005	GET /intelligence/reports/{reportId}/coverage	(C-1)	BearerAuth : path reportId (, string/uuid)	: : 200 ResponseEnvelope + object - OK 404
API-QI-006	POST /intelligence/defects/export	/ Jira(L2)	BearerAuth :	: application/json: object : 200 ResponseEnvelope + object -
API-QI-007	PATCH /intelligence/failures/{id}/verify	AI (manualVerified,)	BearerAuth : path id (, string/uuid)	: application/json: object : 200 ResponseEnvelope + object -

5.6 Skill 8 operations

ID			/	/
API-SK-001	GET /skills		BearerAuth :	: : 200 ResponseEnvelope + object -
API-SK-002	POST /skills		BearerAuth :	: application/json: object : 200 ResponseEnvelope + object -
API-SK-003	POST /skills/{id}/deactivate		BearerAuth : path id (, string/uuid)	: : 200 ResponseEnvelope -
API-SK-004	POST /skills/{id}/activate		BearerAuth : path id (, string/uuid)	: : 200 ResponseEnvelope -
API-SK-005	GET /skills/{id}	Skill Manifest	BearerAuth : path id (, string/uuid)	: : 200 ResponseEnvelope + object - OK 404
API-SK-006	PUT /skills/{id}	Skill( )	BearerAuth : path id (, string/uuid)	: application/json: Skill : 200 ResponseEnvelope + object - 404
API-SK-007	DELETE /skills/{id}	Skill	BearerAuth : path id (, string/uuid)	: : 200 404
API-SK-008	POST /skills/{id}/invoke	Skill( )	BearerAuth : path id (, string/uuid)	: application/json: object : 200 ResponseEnvelope + object - 404

5.7 Agent 16 operations

ID			/	/
API-AG-001	GET /agents		BearerAuth :	: : 200 ResponseEnvelope + object -
API-AG-002	POST /agents		BearerAuth :	: application/json: object : 200 ResponseEnvelope + object -
API-AG-003	POST /agents/{id}/sessions		BearerAuth : path id (, string/uuid)	: application/json: object : 200 ResponseEnvelope + object -
API-AG-004	POST /agents/sessions/{sessionId}/step		BearerAuth : path sessionId (, string/uuid)	: application/json: object : 200 ResponseEnvelope + object - 404

ID			/	/
API-AG-005	GET /agents/sessions/{sessionId}/trace	(Trace)	BearerAuth : path sessionId (, string/uuid)	: : 200 ResponseEnvelope + object - Trace
API-AG-006	GET /agents/{id}	Agent	BearerAuth : path id (, string/uuid)	: : 200 ResponseEnvelope + object - OK 404
API-AG-007	PUT /agents/{id}	Agent( )	BearerAuth : path id (, string/uuid)	: application/json: Agent : 200 ResponseEnvelope + object - 404
API-AG-008	DELETE /agents/{id}	Agent	BearerAuth : path id (, string/uuid)	: : 200 404
API-AG-009	GET /agents/{id}/prompts	Prompt	BearerAuth : path id (, string/uuid) PageParam PageSizeParam	: : 200 ResponseEnvelope + object - OK
API-AG-010	POST /agents/{id}/prompts	Prompt	BearerAuth : path id (, string/uuid)	: application/json: AgentPromptVersion : 200 ResponseEnvelope + object - 400
API-AG-011	POST /agents/{id}/prompts/{versionId}/activate	Prompt	BearerAuth : path id (, string/uuid) path versionId (, string/uuid)	: : 200
API-AG-012	GET /agents/workflows		BearerAuth : WorkspaceIdQuery PageParam PageSizeParam	: : 200 ResponseEnvelope + object - OK
API-AG-013	POST /agents/workflows		BearerAuth :	: application/json: AgentWorkflow : 200 ResponseEnvelope + object - 400
API-AG-014	GET /agents/workflows/{id}		BearerAuth : path id (, string/uuid)	: : 200 ResponseEnvelope + object - OK 404
API-AG-015	PUT /agents/workflows/{id}		BearerAuth : path id (, string/uuid)	: application/json: AgentWorkflow : 200 ResponseEnvelope + object - 404
API-AG-016	DELETE /agents/workflows/{id}		BearerAuth : path id (, string/uuid)	: : 200 404

5.8 Knowledge 13 operations

ID			/	/
API-KN-001	GET /knowledge/entries		BearerAuth : query query (, string)	: : 200 ResponseEnvelope + object -
API-KN-002	POST /knowledge/entries		BearerAuth :	: application/json: object : 200 ResponseEnvelope + object -
API-KN-003	GET /knowledge/baselines		BearerAuth : query workspaceId (, string/uuid)	: : 200 ResponseEnvelope + object -
API-KN-004	POST /knowledge/baselines	Schema	BearerAuth :	: application/json: object : 200 ResponseEnvelope + object -
API-KN-005	GET /knowledge/entries/{id}		BearerAuth : path id (, string/uuid)	: : 200 ResponseEnvelope + object - OK 404
API-KN-006	PUT /knowledge/entries/{id}		BearerAuth : path id (, string/uuid)	: application/json: KnowledgeEntry : 200 ResponseEnvelope + object - 404
API-KN-007	DELETE /knowledge/entries/{id}		BearerAuth : path id (, string/uuid)	: : 200 404
API-KN-008	GET /knowledge/search	(RAG)	BearerAuth : query q (, string) WorkspaceIdQuery	: : 200 ResponseEnvelope + object - OK
API-KN-009	GET /knowledge/audit		BearerAuth : WorkspaceIdQuery PageParam PageSizeParam	: : 200 ResponseEnvelope + object - OK
API-KN-010	POST /knowledge/audit/{id}/approve	( )	BearerAuth : path id (, string/uuid)	: : 200
API-KN-011	GET /knowledge/baselines/{id}		BearerAuth : path id (, string/uuid)	: : 200 ResponseEnvelope + object - OK 404
API-KN-012	PUT /knowledge/baselines/{id}	( )	BearerAuth : path id (, string/uuid)	: application/json: BaselineItem : 200 ResponseEnvelope + object - 404
API-KN-013	DELETE /knowledge/baselines/{id}		BearerAuth : path id (, string/uuid)	: : 200 404

5.9 CICD 14 operations

ID			/	/
API-CI-001	GET /cicd/configs		BearerAuth :	: : 200 ResponseEnvelope + object -
API-CI-002	POST /cicd/configs		BearerAuth :	: application/json: object : 200 ResponseEnvelope + object -
API-CI-003	GET /cicd/runs		BearerAuth :	: : 200 ResponseEnvelope + object -
API-CI-004	GET /cicd/runs/{id}		BearerAuth : path id (, string/uuid)	: : 200 ResponseEnvelope + object -
API-CI-005	GET /cicd/configs/{id}		BearerAuth : path id (, string/uuid)	: : 200 ResponseEnvelope + object - OK 404
API-CI-006	PUT /cicd/configs/{id}		BearerAuth : path id (, string/uuid)	: application/json: PipelineConfig : 200 ResponseEnvelope + object - 404
API-CI-007	DELETE /cicd/configs/{id}		BearerAuth : path id (, string/uuid)	: : 200 404
API-CI-008	POST /cicd/webhooks/git	Git webhook	ApiKeyAuth :	: application/json: object : 200 ResponseEnvelope + object -
API-CI-009	POST /cicd/gates/check	( )	ApiKeyAuth :	: application/json: object : 200 ResponseEnvelope + object -
API-CI-010	GET /quality-gates		BearerAuth : WorkspaceIdQuery PageParam PageSizeParam	: : 200 ResponseEnvelope + object - OK
API-CI-011	POST /quality-gates		BearerAuth :	: application/json: QualityGate : 200 ResponseEnvelope + object - 400
API-CI-012	GET /quality-gates/{id}		BearerAuth : path id (, string/uuid)	: : 200 ResponseEnvelope + object - OK 404
API-CI-013	PUT /quality-gates/{id}		BearerAuth : path id (, string/uuid)	: application/json: QualityGate : 200 ResponseEnvelope + object - 404

ID			/	/
API-CI-014	DELETE /quality-gates/{id}		BearerAuth : path id (, string/uuid)	: : 200 404

5.10 PlatformSettings 19 operations

ID			/	/
API-PS-001	GET /settings/runners	(Runner)	BearerAuth :	: : 200 ResponseEnvelope + object -
API-PS-002	POST /settings/runners/register	Shell	BearerAuth :	: application/json: object : 200 ResponseEnvelope + object -
API-PS-003	POST /settings/runners/heartbeat	Online	BearerAuth :	: application/json: object : 200 ResponseEnvelope -
API-PS-004	GET /settings/llm	LLM	BearerAuth : PageParam PageSizeParam	: : 200 ResponseEnvelope + object - OK
API-PS-005	POST /settings/llm	LLM (Key)	BearerAuth :	: application/json: LlmConfig : 200 ResponseEnvelope + object - 400
API-PS-006	POST /settings/llm/ping	/	BearerAuth :	: application/json: object : 200 ResponseEnvelope + object -
API-PS-007	PUT /settings/llm/{id}	LLM	BearerAuth : path id (, string/uuid)	: application/json: LlmConfig : 200 ResponseEnvelope + object - 404
API-PS-008	DELETE /settings/llm/{id}	LLM	BearerAuth : path id (, string/uuid)	: : 200 404
API-PS-009	GET /settings/runners/{id}	Runner	BearerAuth : path id (, string/uuid)	: : 200 ResponseEnvelope + object - OK 404
API-PS-010	PUT /settings/runners/{id}	Runner( )	BearerAuth : path id (, string/uuid)	: application/json: RunnerNode : 200 ResponseEnvelope + object - 404
API-PS-011	DELETE /settings/runners/{id}	Runner	BearerAuth : path id (, string/uuid)	: : 200 404
API-PS-012	GET /settings/secrets		BearerAuth : PageParam	: : 200 ResponseEnvelope +

ID			/	/
			PageSizeParam	object - OK
API-PS-013	POST /settings/secrets	( )	BearerAuth :	: application/json: WorkspaceSecret : 200 ResponseEnvelope + object - 400
API-PS-014	DELETE /settings/secrets/{id}		BearerAuth : path id (, string/uuid)	: : 200 404
API-PS-015	GET /settings/users	(RBAC)	BearerAuth : PageParam PageSizeParam	: : 200 ResponseEnvelope + object - OK
API-PS-016	POST /settings/users		BearerAuth :	: application/json: User : 200 ResponseEnvelope + object - 400
API-PS-017	GET /settings/users/{id}		BearerAuth : path id (, string/uuid)	: : 200 ResponseEnvelope + object - OK 404
API-PS-018	PUT /settings/users/{id}	/	BearerAuth : path id (, string/uuid)	: application/json: User : 200 ResponseEnvelope + object - 404
API-PS-019	DELETE /settings/users/{id}		BearerAuth : path id (, string/uuid)	: : 200 404

6. Schema

OpenAPI components/schemas 44 required YAML Create/Update/Response

6.1 ResponseEnvelope

code	string	required	
message	string	required	
timestamp	integer/int64	required	
requestId	string	required	Trace ID

6.2 Workspace

id	string/uuid	-	
name	string	-	
description	string	-	
ownerId	string/uuid	-	
frontTechStack	string	-	
backTechStack	string	-	
dbType	string	-	
status	string{Active, Archived}	enum=Active,Archived	AI
scanStatus	string{Pending, Scanning, Ready, Error}	enum=Pending,Scanning,Ready,Error	AI / WorkspaceAIContext.scan_status
createdAt	string/date-time	-	

6.3 FailureAnalysis

id	string/uuid	-	
executionResultId	string/uuid	-	
failureCategory	string{ProductBug, ScriptIssue, EnvIssue, FlakyTest}	enum=ProductBug,ScriptIssue,EnvIssue,FlakyTest	
rootCauseDescription	string	-	
confidenceScore	number/float	-	
suggestedAction	string	-	
assignedDeveloperId	string/uuid	-	

6.4 Skill

id	string/uuid	-	
name	string	-	
version	string	-	
capabilityType	string	-	
status	string{Installing, Inactive, Active, Disabled, Error}	enum=Installing,Inactive,Active,Disabled,Error	
installedAt	string/date-time	-	

6.5 Agent

id	string/uuid	-	
name	string	-	

role	string	-	
systemPrompt	string	-	
temperature	number	-	
status	string{Draft, Inactive, Active, Running, Degraded, Retired}	enum=Draft,Inactive,Active,Running,Degraded,Retired	

6.6 AgentSession

id	string/uuid	-	
agentId	string/uuid	-	
workspaceId	string/uuid	-	
status	string{Running, Success, WaitingFeedback, Failed, Timeout}	enum=Running,Success,WaitingFeedback,Failed,Timeout	
userInstruction	string	-	
totalTokens	integer	-	
totalCost	number/float	-	

6.7 AgentTraceNode

id	string/uuid	-	
sessionId	string/uuid	-	
parentNodeId	string/uuid	-	
nodeType	string{DecisionSummary, ToolCall, UserInput, AgentMessage}	enum=DecisionSummary,ToolCall,UserInput,AgentMessage	

content	string	-	
toolName	string	-	
toolInput	string	-	
toolOutput	string	-	

6.8 KnowledgeEntry

id	string/uuid	-	
title	string	-	
content	string	-	
status	string{Draft, PendingReview, Published, Archived}	enum=Draft,PendingReview,Published,Archived	

6.9 BaselineItem

id	string/uuid	-	
workspaceId	string/uuid	-	
baselineKey	string	-	
baselineType	string{API_SCHEMA, UI_SCREENSHOT, PERFORMANCE_METRIC}	enum=API_SCHEMA,UI_SCREENSHOT,PERFORMANCE_METRIC	
content	string	-	
version	integer	-	

6.10 PipelineConfig

id	string/uuid	-	
name	string	-	
qualityGateId	string/uuid	-	

6.11 PipelineRun

id	string/uuid	-	
pipelineConfigId	string/uuid	-	
gitBranch	string	-	
gitCommitId	string	-	
gitAuthor	string	-	
gateStatus	string{Running, Passed, Warned, Blocked, Quarantined}	enum=Running,Passed,Warned,Blocked,Quarantined	

6.12 RunnerNode

id	string/uuid	-	
name	string	-	
ipAddress	string	-	
runnerToken	string	-	
osType	string	-	
status	string{OnlineIdle, OnlineBusy, Offline, HeartbeatLost}	enum=OnlineIdle,OnlineBusy, Offline,HeartbeatLost	

heartbeatTime	string/date-time	-	

6.13 TestCase

id	string/uuid	-	
workspaceId	string/uuid	-	
scenarioId	string/uuid	-	
apiContractId	string/uuid	-	
code	string	-	
title	string	-	
priority	string{P0, P1, P2, P3}	enum=P0,P1,P2,P3	
testType	string{API, UI, Performance, Security}	enum=API,UI,Performance,Security	
status	string{Draft, Reviewed, Deprecated}	enum=Draft,Reviewed,Deprecated	
generatedConfidence	number/float	minimum=0 maximum=1	AI B-2 DesignTestCase
createdAt	string/date-time	-	
updatedAt	string/date-time	-	

6.14 DesignTestCase

B-2 AI TestCase

id	string/uuid	-	
tenantId	string/uuid	-	
workspaceId	string/uuid	-	
scenarioId	string/uuid	-	

caseCode	string	-	TC-TEMP-001
title	string	-	
precondition	string	-	
steps	object	-	
testData	object	-	TestData
expectedResult	object	-	
priority	string{P0, P1, P2, P3}	default=P1 enum=P0,P1,P2,P3	AI
testType	string{API, UI, Performance, Security}	default=API enum=API,UI,Performance,Security	AI
apiContractId	string/uuid	-	
status	string{DRAFT, GENERATING, REVIEWING, APPROVED}	default=DRAFT enum=DRAFT,GENERATING,REVIEWING,APPROVED	
confidenceScore	number/float	minimum=0 maximum=1	AI TestCase.generatedConfidence
promotedTestCaseId	string/uuid	-	TestCase NULL
createdAt	string/date-time	-	
updatedAt	string/date-time	-	

6.15 TestDataProfile

id	string/uuid	-	
workspaceId	string/uuid	-	
profileName	string	-	
dataRows	string	-	
isMasked	boolean	-	

6.16 Environment

id	string/uuid	-	
tenantId	string/uuid	-	
workspaceId	string/uuid	-	
name	string	-	
baseUrl	string	-	
dbConnectionString	string	-	
redisHost	string	-	
extraConfigs	object	-	
status	string{Online, Offline}	enum=Online,Offline	

6.17 AIContext

id	string/uuid	-	
tenantId	string/uuid	-	
workspaceId	string/uuid	-	
systemPrompt	string	-	
businessContext	string	-	
namingConventions	string	-	
llmProvider	string	-	
llmModel	string	-	

6.18 TestPlan

id	string/uuid	-	
tenantId	string/uuid	-	
workspaceId	string/uuid	-	
name	string	-	
description	string	-	
status	string{Draft, Reviewed, Deprecated}	enum=Draft,Reviewed,Deprecated	
ownerId	string/uuid	-	
startDate	string/date	-	
endDate	string/date	-	

6.19 TestDesignPlan

AI TestPlan

id	string/uuid	-	
tenantId	string/uuid	-	
workspaceId	string/uuid	-	
requirementDocumentId	string/uuid	-	ID C-1
testPlanId	string/uuid	-	ID
scope	string	-	
strategy	string	-	
testTypes	string	-	API,UI,Performance
version	integer	default=1	
createdAt	string/date-time	-	

updatedAt	string/date-time	-	

6.20 TestScenario

id	string/uuid	-	
tenantId	string/uuid	-	
workspaceId	string/uuid	-	
testDesignPlanId	string/uuid	-	ID C-1 TestDesignPlan
name	string	-	
description	string	-	
flowSteps	string	-	

6.21 TestSuite

id	string/uuid	-	
tenantId	string/uuid	-	
workspaceId	string/uuid	-	
name	string	-	
description	string	-	
queryRules	string	-	

6.22 AutomationScript

id	string/uuid	-	

tenantId	string/uuid	-	
workspaceId	string/uuid	-	
testCaseId	string/uuid	-	
scriptLanguage	string	-	
codeContent	string	-	
gitRepoUrl	string	-	
gitFilePath	string	-	
version	string	-	

6.23 TestData

id	string/uuid	-	
tenantId	string/uuid	-	
workspaceId	string/uuid	-	
testCaseId	string/uuid	-	
name	string	-	
dataType	string{JSON, CSV, KeyValue}	enum=JSON,CSV,KeyValue	
dataSchema	string	-	
dataValues	string	-	

6.24 MockConfig

id	string/uuid	-	
tenantId	string/uuid	-	

workspaceId	string/uuid	-	
name	string	-	
requestMatchRules	string	-	
responseStatus	integer	-	
responseHeaders	string	-	
responseBody	string	-	
delayMs	integer	-	
isActive	boolean	-	

6.25 Locator

id	string/uuid	-	
tenantId	string/uuid	-	
workspaceId	string/uuid	-	
elementName	string	-	
pageName	string	-	
primarySelector	string	-	
backupSelectors	string	-	
score	number/float	-	
status	string{Verified, Decaying, Failed, Healed}	enum=Verified,Decaying,Failed,Healed	

6.26 APIContract

id	string/uuid	-	
tenantId	string/uuid	-	
workspaceId	string/uuid	-	
apiPath	string	-	
method	string{GET, POST, PUT, DELETE, PATCH}	enum=GET,POST,PUT,DELETE, PATCH	
headersSchema	string	-	
requestSchema	string	-	
responseSchema	string	-	
source	string	-	

6.27 ExecutionPlan

id	string/uuid	-	
tenantId	string/uuid	-	
workspaceId	string/uuid	-	
name	string	-	
environmentId	string/uuid	-	
scopeConfigs	string	-	
triggerType	string{Manual, Schedule, Webhook}	enum=Manual,Schedule,Webhook	
cronExpression	string	-	
parallelNum	integer	-	
runnerId	string/uuid	-	

6.28 ExecutionTask

id	string/uuid	-	
tenantId	string/uuid	-	
executionPlanId	string/uuid	-	
runnerId	string/uuid	-	
status	string{Pending, Running, Completed, Failed, Cancelled}	enum=Pending,Running,Completed,Failed,Cancelled	
totalCaseCount	integer	-	
successCaseCount	integer	-	
failedCaseCount	integer	-	
startTime	string/date-time	-	
endTime	string/date-time	-	

6.29 ExecutionResult

id	string/uuid	-	
tenantId	string/uuid	-	
executionTaskId	string/uuid	-	
testCaseId	string/uuid	-	
status	string{Passed, Failed, Skipped, Error}	enum=Passed,Failed,Skipped,Error	
durationMs	integer	-	
errorMessage	string	-	
errorStackTrace	string	-	
screenshots	string	-	

logs	string	-	
traces	string	-	

6.30 TestReport

id	string/uuid	-	
tenantId	string/uuid	-	
workspaceId	string/uuid	-	
executionTaskId	string/uuid	-	
title	string	-	
status	string{Pending, Analyzing, Completed, Failed}	enum=Pending,Analyzing,Completed,Failed	
totalCases	integer	-	
failedCases	integer	-	
flakyCases	integer	-	
passRate	number/float	-	
riskLevel	string{Low, Medium, High, Critical}	enum=Low,Medium,High,Critical	
aiSummary	string	-	
reportPath	string	-	

6.31 CoverageReport

C-2 coverage-analyzer Skill 12

id	string/uuid	-	

tenantId	string/uuid	-	
workspaceId	string/uuid	-	
testReportId	string/uuid	-	ID
overallVerdict	string{GATE_PASS, GATE_FAILURE}	enum=GATE_PASS,GATE_FAILURE	FAIL GATE_FAILURE
dimensions	object	-	assertion_id verdict PASS/(PASS+REPAIR+REJECT+UNVERIFIED) REJECT / / FAIL Strategy NOT_APPLICABLE
thresholdsUsed	object	-	+ Strategy
gateFailures	array<object>	-	gap/missing_count/missing_sample GATE_PASS
computedAt	string/date-time	-	

6.32 FailureCluster

id	string/uuid	-	
tenantId	string/uuid	-	
testReportId	string/uuid	-	
clusterName	string	-	
commonPattern	string	-	
caseCount	integer	-	
jiraIssueKey	string	-	

6.33 AgentWorkflow

id	string/uuid	-	

tenantId	string/uuid	-	
name	string	-	
description	string	-	
flowDefinition	string	-	
status	string{Active, Inactive}	enum=Active,Inactive	

6.34 QualityGate

id	string/uuid	-	
tenantId	string/uuid	-	
workspaceId	string/uuid	-	
name	string	-	
rulesConfig	string	-	
isActive	boolean	-	

6.35 SkillInvocation

id	string/uuid	-	
tenantId	string/uuid	-	
skillId	string/uuid	-	
executionTaskId	string/uuid	-	
callerAgentId	string/uuid	-	
inputPayload	string	-	
outputPayload	string	-	

status	string{Running, Success, Failed, Timeout}	enum=Running,Success,Failed,Timeout	
latencyMs	integer	-	
errorCode	string	-	

6.36 AgentPromptVersion

id	string/uuid	-	
tenantId	string/uuid	-	
agentId	string/uuid	-	
versionTag	string	-	
systemPrompt	string	-	
isActive	boolean	-	
updatedBy	string/uuid	-	

6.37 LlmConfig

apiKey apiKeyPlaintext

id	string/uuid	-	
tenantId	string/uuid	-	
provider	string{ANTHROPIC, OPENAI, DEEPSEEK, AZURE}	enum=ANTHROPIC,OPENAI,DEEPSEEK,AZURE	
modelName	string	-	
apiEndpoint	string	-	
weight	integer	default=1	

maxTpm	integer	default=100000	
status	string{ACTIVE, OFFLINE, BLOCKED}	enum=ACTIVE,OFFLINE,BLOCKED	
lastLatencyMs	integer	-	

6.38 User

id	string/uuid	-	
tenantId	string/uuid	-	
username	string	-	
email	string/email	-	
status	string{Active, Suspended, Inactive}	enum=Active,Suspended,Inactive	
roles	array<string{TenantAdmin, TestLead, TestEngineer}>	-	
createdAt	string/date-time	-	

6.39 WorkspaceSecret

secretValue

id	string/uuid	-	
tenantId	string/uuid	-	
workspaceId	string/uuid	-	
secretKey	string	-	
targetEnvId	string/uuid	-	
createdAt	string/date-time	-	

updatedAt	string/date-time	-	

6.40 RequirementDocument

id	string/uuid	-	
tenantId	string/uuid	-	
workspaceId	string/uuid	-	
title	string	-	
fileName	string	-	
status	string{Draft, Parsing, Completed, Failed}	enum=Draft,Parsing,Completed,Failed	
parsedElements	string	-	JSON
createdAt	string/date-time	-	

6.41 TestingIR

B-3 requirement-compiler

id	string/uuid	-	
tenantId	string/uuid	-	
workspaceId	string/uuid	-	
requirementDocumentId	string/uuid	-	ID
irVersion	string	-	IR 1.0.0
irContent	object	-	IR requirements/business_rules/entities/state_machines/interface_contracts/constraints
status	string{DRAFT, COMPILING, VALIDATED, FAILED}	enum=DRAFT,COMPILING,VALIDATED,FAILED	

compileVerdict	string{PASS, PASS_WITH_REVIEW, REJECT}	enum=PASS,PASS_WITH_REVIEW,REJECT	requirement-compiler
sourceTrace	string	-	
createdAt	string/date-time	-	
updatedAt	string/date-time	-	

6.42 BusinessRule

B-3 TestingIR

id	string/uuid	-	
tenantId	string/uuid	-	
workspaceId	string/uuid	-	
testingIrId	string/uuid	-	IR ID
ruleId	string	-	R-001
condition	string	-	
action	string	-	
source	string	-	PRD/API_SPEC
sourceTrace	string	-	PRD§3.2
confidence	number/float	minimum=0 maximum=1	AI
createdAt	string/date-time	-	
updatedAt	string/date-time	-	

6.43 Assertion

B-3 assertion-generator assertion-verifier

id	string/uuid	-	

tenantId	string/uuid	-	
workspaceId	string/uuid	-	
testCaseId	string/uuid	-	
designTestCaseId	string/uuid	-	
assertionId	string	-	AST-001
target	string	-	response.body.total
expression	string	-	eq/gt/lt/contains/exists
expected	string	-	
verificationStatus	string{VERIFIED, REJECTED, UNVERIFIED}	enum=VERIFIED,REJECTED,UNVERIFIED	assertion-verifier
sourceTrace	string	-	
createdAt	string/date-time	-	
updatedAt	string/date-time	-	

6.44 ReviewTask

B-3 hitl-gatekeeper

id	string/uuid	-	
tenantId	string/uuid	-	
workspaceId	string/uuid	-	
reviewId	string	-	RVW-<10hex>
severity	string{forced, required, sample, info}	enum=forced,required,sample,info	
status	string{OPEN, RESOLVED, EXPIRED}	enum=OPEN,RESOLVED,EXPIRED	
eventType	string{critical_path, contract_mutation, breaking_drift, healing_overrun, ambiguity_flag,	enum=critical_path,contract_mutation,breaking_drift,healing_overrun,ambiguity_flag,inference	

	inference}		
assetType	string{requirement, rule, scenario, case, assertion, locator, fixture, contract}	enum=requirement,rule,scenario,case,assertion,locator,fixture,contract	
assetId	string/uuid	-	ID
proposedAction	string	-	
confidence	number/float	minimum=0 maximum=1	
confidenceRationale	string	-	
blastRadius	object	-	affected_ir_elements + downstream_skills
diff	object	-	before/after
slaSeconds	integer	-	
resolution	string{approve, reject, modify}	enum=approve,reject,modify	
resolutionNote	string	-	
createdAt	string/date-time	-	
resolvedAt	string/date-time	-	

7. WebSocket

Execution /		Log / Progress / CaseResult / TaskStatus / Error	Pause / Resume / Cancel / Ack
AI	AI	Observation / Finding / Recommendation / Error	Ack / Stop
Agent Trace		NodeStarted / ToolCall / ToolResult / NodeFinished / SessionStatus	Ack / Cancel
Workspace	OpenAPI/	ScanProgress / ArtifactDiscovered / ScanCompleted / ScanFailed	Ack / Cancel

7.1

```
{
  "type": "Progress",
  "channel": "execution",
  "resourceId": "task-id",
  "seq": 42,
  "timestamp": "2026-08-10T10:00:00Z",
  "requestId": "...",
  "payload": { }
}
```

- Cookie Secret URL
- resourceId
- ping/pong lastSeq REST
- seq /
- Error

8.

	OpenAPI / operationId Schema
	Schema
	JWT/API Key/Runner Token Scope RLS Secret Webhook
/	

	/

9.

ID			
API-GAP-01	164 operationId	SDK	ID
API-GAP-02	Schema required		Create/Update/Response required
API-GAP-03	YAML data code/message/data		ResponseEnvelope 32/37
API-GAP-04	/ object	/	Page AsyncTask Schema
API-GAP-05	Markdown		ErrorCode
API-GAP-06	200 envelope 204	SDK	
API-GAP-07	2026-08-04 schema		YAML 44 Schema
API-GAP-08	RBAC		scope/permission
API-GAP-09	Webhook		timestamp nonce

□□□□□□

OpenAPI 10 operationId / / SDK

A.

- REST Schema docs/04-architecture/32-API .yaml
- docs/04-architecture/37-API .md
- RBAC RLS API Key Secret docs/04-architecture/34- .md
- docs/04-architecture/36-WebSocket .md

- docs/01-product/04- .md docs/04-architecture/33- Schema .md
- OpenAPI