

ONLINE MASTERS IN **DATA SCIENCE**

DSC 255 - MACHINE LEARNING FUNDAMENTALS

CROSS-VALIDATION

SANJOY DASGUPTA, PROFESSOR

UC San Diego

COMPUTER SCIENCE & ENGINEERING
HALICIOĞLU DATA SCIENCE INSTITUTE



K-nearest neighbor classification

Classify a point using the labels of its k -nearest neighbors among the training points.

| MNIST: | K | 1 | 3 | 5 | 7 | 9 | 11 |
|--------|----------------|------|------|------|------|------|------|
| | Test error (%) | 3.09 | 2.94 | 3.13 | 3.10 | 3.43 | 3.34 |

In real life, there's no test set. How to decide which k is best?

K-nearest neighbor classification

Classify a point using the labels of its k -nearest neighbors among the training points.

| MNIST: | K | 1 | 3 | 5 | 7 | 9 | 11 |
|--------|----------------|------|------|------|------|------|------|
| | Test error (%) | 3.09 | 2.94 | 3.13 | 3.10 | 3.43 | 3.34 |

In real life, there's no test set. How to decide which k is best?

1 Hold-out set:

- Let S be the training set.
- Choose a subset $V \subset S$ as a validation set.
- What fraction of V is misclassified by the k -nearest neighbors in $S \setminus V$?

K-nearest neighbor classification

Classify a point using the labels of its k -nearest neighbors among the training points.

| MNIST: | K | 1 | 3 | 5 | 7 | 9 | 11 |
|--------|----------------|------|------|------|------|------|------|
| | Test error (%) | 3.09 | 2.94 | 3.13 | 3.10 | 3.43 | 3.34 |

In real life, there's no test set. How to decide which k is best?

1 Hold-out set:

- Let S be the training set.
- Choose a subset $V \subset S$ as a *validation* set.
- What fraction of V is misclassified by the k -nearest neighbors in $S \setminus V$?

2 Leave-one-out cross-validation:

- For each point $x \in S$, find the k -nearest neighbors in $S \setminus \{x\}$.
- What fraction are misclassified?

How to estimate the error of k -NN for a particular k ?

10-fold cross-validation

- Divide the training set into 10 equal pieces.
- Training set (call it S): 60,000 points
- Call the pieces S_1, S_2, \dots, S_{10} : 6,000 points each.
- For each piece S_i :
 - Classify each point in S_i using k -NN with training set $S - S_i$
 - Let ϵ_i = fraction of S_i that is incorrectly classified
- Take the average of these 10 numbers:

$$\text{estimated error with } k\text{-NN} = \frac{\epsilon_1 + \dots + \epsilon_{10}}{10}$$