

HTML5 Div

Reemplaza los <div> con los elementos HTML5 apropiados

```
<div id="header">  
  <h1> Soy una cabecera de nivel 1</h1>  
</div>
```

```
<div id="footer">  
  <h3> UPV/EHU </h3>  
  <p> Curso 2013/14 </p>  
</div>
```

HTML5 Etiquetas de navegación

Reemplaza los <div> con las etiquetas HTML5 apropiadas

```
<div id="navigation">  
<ul>  
  <li>Home</li>  
  <li>About</li>  
  <li>Aircraft</li>  
  <li>Pilots</li>  
  <li>Apply</li>  
</ul>  
</div>
```

HTML5 Etiqueta <section>

Reemplaza los <div> con las etiquetas HTML5 apropiadas y actualiza los niveles de cabeceras a <h1> y <h2>

```
<div class="section">
  <h2>Navy Fighter Weapons School</h2>
  <h3>Maverick & Goose Crash and Burn</h3>
  <p>Aha, Jester's dead...</p>
</div>
```

HTML5 Etiqueta <article>

Añade las etiquetas <article> necesarias alrededor de los elementos de esta sección:

```
<section id="top-gun">
  <header>
    <h1>Navy School Updates</h1>
  </header>

  <h2>Maverick & Goose Crash and Burn</h2>
  <p>Aha, Jester's dead...</p>

  <h2>She's Lost That Lovin' Feelin'</h2>
  <p>I hate it when she does that...</p>
</section>
```

HTML5 Etiqueta <aside>

Reemplaza la etiqueta <p class="aside">
con el elemento HTML5 apropiado::

```
<section id="top-gun">
  <header>
    <h1>Navy School Updates</h1>
  </header>

  <article>
    <h2>Maverick & Goose Crash and Burn</h2>
    <p>Aha, Jester's dead...</p>
    <p class="aside">FACT: The airspeed velocity of an F14...</p>
  </article>
</section>
```

Ejemplo completo de refactorización a HTML5

Refactorizar el siguiente código usando los elementos HTML5 adecuados.

```
<!DOCTYPE html PUBLIC "-//W3C//DTD XHTML 1.0 Strict//EN"
"http://www.w3.org/TR/xhtml1/DTD/xhtml1-strict.dtd">
<html xmlns="http://www.w3.org/1999/xhtml"
      lang="en"
      xml:lang="en">
  <head>
    <meta charset="utf-8" />
    <title>Exercise 1</title>
    <link href="css/style.css" rel="stylesheet" />
  </head>
  <body>
<div id="header">
  <h1>Top Gun</h1>
  <h2> Navy Fighter Weapons School</h2>
</div>

<div id="navigation">
  <ul>
    <li>Home</li>
    <li>About</li>
    <li>Aircraft</li>
    <li>Pilots</li>
    <li>Apply</li>
  </ul>
</div>
```

```
<div id="section">
  <h2>Top Gun Aircraft</h2>
  <div class="article">
    <h3>The F14 Tomcat</h3>
    <p>Tower this is Ghost Rider requesting a flyby. Negative,
      Ghost Rider, the pattern is full.</p>
    <p class="aside">FACT: Son, your brain's writing checks your
      body can't cash...</p>
  </div>

  <div class="article">
    <h3>The MIG-28</h3>
    <p>
      You were in a 4g inverted dive with a MIG-28? Yes, ma'am. At
      what range?
    </p>
  </div>
</div>

<div id="footer">
  <h3>USS Enterprise</h3>
  <p>© 2011 United States Navy</p>
</div>
</body>
</html>
```

(II) Ejemplo completo de refactorización a HTML5

Refactorizar el siguiente código usando los elementos HTML5 adecuados.

```
<!DOCTYPE html PUBLIC "-//W3C//DTD HTML 4.01//EN"
"http://www.w3.org/TR/html4/strict.dtd">
<html>
  <head>
    <meta http-equiv="content-type" content="text/html; charset=UTF-8">
    <title>Head First Lounge</title>
    <link type="text/css" rel="stylesheet" href="lounge.css">
    <script type="text/javascript" src="lounge.js"></script>
  </head>
  <body>
    <h1>Welcome to Head First Lounge</h1>
    <p>
      
    </p>
    <p>
      Join us any evening for refreshing <a href="elixirs.html">elixirs</a>,
      conversation and maybe a game or two of Tap Tap Revolution.
      Wireless access is always provided; BYOWS (Bring Your Own Web Server).
    </p>
  </body>
</html>
```