```
No.     Time                        Source              Destination         Protocol Length Info
      1 2003-09-23 13:39:52.896793  192.168.1.102       192.168.1.104       SNMP     92     get-request
1.3.6.1.4.1.11.2.3.9.4.2.1.2.2.2.1.0
Frame 1: 92 bytes on wire (736 bits), 92 bytes captured (736 bits)
    Encapsulation type: Ethernet (1)
    Arrival Time: Sep 23, 2003 13:39:52.896793000 中国标准时间
    [Time shift for this packet: 0.000000000 seconds]
    Epoch Time: 1064295592.896793000 seconds
    [Time delta from previous captured frame: 0.000000000 seconds]
    [Time delta from previous displayed frame: 0.000000000 seconds]
    [Time since reference or first frame: 0.000000000 seconds]
    Frame Number: 1
    Frame Length: 92 bytes (736 bits)
    Capture Length: 92 bytes (736 bits)
    [Frame is marked: False]
    [Frame is ignored: False]
    [Protocols in frame: eth:ethertype:ip:udp:snmp]
    [Coloring Rule Name: UDP]
    [Coloring Rule String: udp]
Ethernet II, Src: Dell_4f:36:23 (00:08:74:4f:36:23), Dst: HewlettP_61:eb:ed (00:30:c1:61:eb:ed)
    Destination: HewlettP_61:eb:ed (00:30:c1:61:eb:ed)
        Address: HewlettP_61:eb:ed (00:30:c1:61:eb:ed)
        .... ..0. .... .... .... .... = LG bit: Globally unique address (factory default)
        .... ...0 .... .... .... .... = IG bit: Individual address (unicast)
    Source: Dell_4f:36:23 (00:08:74:4f:36:23)
        Address: Dell_4f:36:23 (00:08:74:4f:36:23)
        .... ..0. .... .... .... .... = LG bit: Globally unique address (factory default)
        .... ...0 .... .... .... .... = IG bit: Individual address (unicast)
    Type: IPv4 (0x0800)
Internet Protocol Version 4, Src: 192.168.1.102, Dst: 192.168.1.104
    0100 .... = Version: 4
    .... 0101 = Header Length: 20 bytes (5)
    Differentiated Services Field: 0x00 (DSCP: CS0, ECN: Not-ECT)
        0000 00.. = Differentiated Services Codepoint: Default (0)
        .... ..00 = Explicit Congestion Notification: Not ECN-Capable Transport (0)
    Total Length: 78
    Identification: 0x02fd (765)
    Flags: 0x0000
        0... .... .... .... = Reserved bit: Not set
        .0.. .... .... .... = Don't fragment: Not set
        ..0. .... .... .... = More fragments: Not set
        ...0 0000 0000 0000 = Fragment offset: 0
    Time to live: 128
    Protocol: UDP (17)
    Header checksum: 0x0000 [validation disabled]
    [Header checksum status: Unverified]
    Source: 192.168.1.102
    Destination: 192.168.1.104
User Datagram Protocol, Src Port: 4334, Dst Port: 161
    Source Port: 4334
    Destination Port: 161
    Length: 58
    Checksum: 0x65f8 [unverified]
    [Checksum Status: Unverified]
    [Stream index: 0]
Simple Network Management Protocol
    version: version-1 (0)
    community: public
    data: get-request (0)
        get-request
            request-id: 6395
            error-status: noError (0)
            error-index: 0
            variable-bindings: 1 item
                1.3.6.1.4.1.11.2.3.9.4.2.1.2.2.2.1.0: Value (Null)
                    Object Name: 1.3.6.1.4.1.11.2.3.9.4.2.1.2.2.2.1.0 (iso.3.6.1.4.1.11.2.3.9.4.2.1.2.2.2.1.0)
                    Value (Null)
No.     Time                        Source              Destination         Protocol Length Info
      2 2003-09-23 13:39:52.913753  192.168.1.104       192.168.1.102       SNMP     93     get-response
1.3.6.1.4.1.11.2.3.9.4.2.1.2.2.2.1.0
Frame 2: 93 bytes on wire (744 bits), 93 bytes captured (744 bits)
    Encapsulation type: Ethernet (1)
    Arrival Time: Sep 23, 2003 13:39:52.913753000 中国标准时间
    [Time shift for this packet: 0.000000000 seconds]
    Epoch Time: 1064295592.913753000 seconds
    [Time delta from previous captured frame: 0.016960000 seconds]
    [Time delta from previous displayed frame: 0.016960000 seconds]
```

[Time since reference or first frame: 0.016960000 seconds]
    Frame Number: 2
    Frame Length: 93 bytes (744 bits)
    Capture Length: 93 bytes (744 bits)
    [Frame is marked: False]
    [Frame is ignored: False]
    [Protocols in frame: eth:ethertype:ip:udp:snmp]
    [Coloring Rule Name: UDP]
    [Coloring Rule String: udp]
Ethernet II, Src: HewlettP_61:eb:ed (00:30:c1:61:eb:ed), Dst: Dell_4f:36:23 (00:08:74:4f:36:23)
    Destination: Dell_4f:36:23 (00:08:74:4f:36:23)
        Address: Dell_4f:36:23 (00:08:74:4f:36:23)
        .... ..0. .... = LG bit: Globally unique address (factory default)
        ....0 .... = IG bit: Individual address (unicast)
    Source: HewlettP_61:eb:ed (00:30:c1:61:eb:ed)
        Address: HewlettP_61:eb:ed (00:30:c1:61:eb:ed)
        .... ..0. .... = LG bit: Globally unique address (factory default)
        ....0 .... = IG bit: Individual address (unicast)
    Type: IPv4 (0x0800)
Internet Protocol Version 4, Src: 192.168.1.104, Dst: 192.168.1.102
    0100 .... = Version: 4
    .... 0101 = Header Length: 20 bytes (5)
    Differentiated Services Field: 0x00 (DSCP: CS0, ECN: Not-ECT)
        0000 00.. = Differentiated Services Codepoint: Default (0)
        .... ..00 = Explicit Congestion Notification: Not ECN-Capable Transport (0)
    Total Length: 79
    Identification: 0xeda2 (60834)
    Flags: 0x0000
        0... .... = Reserved bit: Not set
        .0.. .... = Don't fragment: Not set
        ..0. .... = More fragments: Not set
        ...0 0000 0000 0000 = Fragment offset: 0
    Time to live: 60
    Protocol: UDP (17)
    Header checksum: 0x0cdd [validation disabled]
    [Header checksum status: Unverified]
    Source: 192.168.1.104
    Destination: 192.168.1.102
User Datagram Protocol, Src Port: 161, Dst Port: 4334
    Source Port: 161
    Destination Port: 4334
    Length: 59
    Checksum: 0x53f2 [unverified]
    [Checksum Status: Unverified]
    [Stream index: 0]
Simple Network Management Protocol
    version: version-1 (0)
    community: public
    data: get-response (2)
        get-response
            request-id: 6395
            error-status: noError (0)
            error-index: 0
            variable-bindings: 1 item
                1.3.6.1.4.1.11.2.3.9.4.2.1.2.2.2.1.0: 10
                    Object Name: 1.3.6.1.4.1.11.2.3.9.4.2.1.2.2.2.1.0 (iso.3.6.1.4.1.11.2.3.9.4.2.1.2.2.2.1.0)
                    Value (OctetString): 10
No.   Time   Source   Destination   Protocol Length Info
    11 2003-09-23 13:39:55.913764   192.168.1.102   192.168.1.104   SNMP   92   get-request
1.3.6.1.4.1.11.2.3.9.4.2.1.2.2.2.1.0
Frame 11: 92 bytes on wire (736 bits), 92 bytes captured (736 bits)
    Encapsulation type: Ethernet (1)
    Arrival Time: Sep 23, 2003 13:39:55.913764000 中国标准时间
    [Time shift for this packet: 0.000000000 seconds]
    Epoch Time: 1064295595.913764000 seconds
    [Time delta from previous captured frame: 0.478716000 seconds]
    [Time delta from previous displayed frame: 3.000011000 seconds]
    [Time since reference or first frame: 3.016971000 seconds]
    Frame Number: 11
    Frame Length: 92 bytes (736 bits)
    Capture Length: 92 bytes (736 bits)
    [Frame is marked: False]
    [Frame is ignored: False]
    [Protocols in frame: eth:ethertype:ip:udp:snmp]
    [Coloring Rule Name: UDP]
    [Coloring Rule String: udp]
Ethernet II, Src: Dell_4f:36:23 (00:08:74:4f:36:23), Dst: HewlettP_61:eb:ed (00:30:c1:61:eb:ed)

```
    Destination: HewlettP_61:eb:ed (00:30:c1:61:eb:ed)
        Address: HewlettP_61:eb:ed (00:30:c1:61:eb:ed)
        .... ..0. .... .... .... .... = LG bit: Globally unique address (factory default)
        .... ...0 .... .... .... .... = IG bit: Individual address (unicast)
    Source: Dell_4f:36:23 (00:08:74:4f:36:23)
        Address: Dell_4f:36:23 (00:08:74:4f:36:23)
        .... ..0. .... .... .... .... = LG bit: Globally unique address (factory default)
        .... ...0 .... .... .... .... = IG bit: Individual address (unicast)
    Type: IPv4 (0x0800)
Internet Protocol Version 4, Src: 192.168.1.102, Dst: 192.168.1.104
    0100 .... = Version: 4
    .... 0101 = Header Length: 20 bytes (5)
    Differentiated Services Field: 0x00 (DSCP: CS0, ECN: Not-ECT)
        0000 00.. = Differentiated Services Codepoint: Default (0)
        .... ..00 = Explicit Congestion Notification: Not ECN-Capable Transport (0)
    Total Length: 78
    Identification: 0x0308 (776)
    Flags: 0x0000
        0... .... .... .... = Reserved bit: Not set
        .0.. .... .... .... = Don't fragment: Not set
        ..0. .... .... .... = More fragments: Not set
        ...0 0000 0000 0000 = Fragment offset: 0
    Time to live: 128
    Protocol: UDP (17)
    Header checksum: 0x0000 [validation disabled]
    [Header checksum status: Unverified]
    Source: 192.168.1.102
    Destination: 192.168.1.104
User Datagram Protocol, Src Port: 4336, Dst Port: 161
    Source Port: 4336
    Destination Port: 161
    Length: 58
    Checksum: 0x64f6 [unverified]
    [Checksum Status: Unverified]
    [Stream index: 1]
Simple Network Management Protocol
    version: version-1 (0)
    community: public
    data: get-request (0)
        get-request
            request-id: 6396
            error-status: noError (0)
            error-index: 0
            variable-bindings: 1 item
                1.3.6.1.4.1.11.2.3.9.4.2.1.2.2.2.1.0: Value (Null)
                    Object Name: 1.3.6.1.4.1.11.2.3.9.4.2.1.2.2.2.1.0 (iso.3.6.1.4.1.11.2.3.9.4.2.1.2.2.2.1.0)
                    Value (Null)
No.     Time                          Source              Destination          Protocol Length Info
    12 2003-09-23 13:39:55.930920     192.168.1.104        192.168.1.102         SNMP     93      get-response
1.3.6.1.4.1.11.2.3.9.4.2.1.2.2.2.1.0
Frame 12: 93 bytes on wire (744 bits), 93 bytes captured (744 bits)
    Encapsulation type: Ethernet (1)
    Arrival Time: Sep 23, 2003 13:39:55.930920000 中国标准时间
    [Time shift for this packet: 0.000000000 seconds]
    Epoch Time: 1064295595.930920000 seconds
    [Time delta from previous captured frame: 0.017156000 seconds]
    [Time delta from previous displayed frame: 0.017156000 seconds]
    [Time since reference or first frame: 3.034127000 seconds]
    Frame Number: 12
    Frame Length: 93 bytes (744 bits)
    Capture Length: 93 bytes (744 bits)
    [Frame is marked: False]
    [Frame is ignored: False]
    [Protocols in frame: eth:ethertype:ip:udp:snmp]
    [Coloring Rule Name: UDP]
    [Coloring Rule String: udp]
Ethernet II, Src: HewlettP_61:eb:ed (00:30:c1:61:eb:ed), Dst: Dell_4f:36:23 (00:08:74:4f:36:23)
    Destination: Dell_4f:36:23 (00:08:74:4f:36:23)
        Address: Dell_4f:36:23 (00:08:74:4f:36:23)
        .... ..0. .... .... .... .... = LG bit: Globally unique address (factory default)
        .... ...0 .... .... .... .... = IG bit: Individual address (unicast)
    Source: HewlettP_61:eb:ed (00:30:c1:61:eb:ed)
        Address: HewlettP_61:eb:ed (00:30:c1:61:eb:ed)
        .... ..0. .... .... .... .... = LG bit: Globally unique address (factory default)
        .... ...0 .... .... .... .... = IG bit: Individual address (unicast)
    Type: IPv4 (0x0800)
Internet Protocol Version 4, Src: 192.168.1.104, Dst: 192.168.1.102
```

```
    0100 .... = Version: 4
    .... 0101 = Header Length: 20 bytes (5)
    Differentiated Services Field: 0x00 (DSCP: CS0, ECN: Not-ECT)
        0000 00.. = Differentiated Services Codepoint: Default (0)
        .... ..00 = Explicit Congestion Notification: Not ECN-Capable Transport (0)
    Total Length: 79
    Identification: 0xeda3 (60835)
    Flags: 0x0000
        0... .... .... .... = Reserved bit: Not set
        .0.. .... .... .... = Don't fragment: Not set
        ..0. .... .... .... = More fragments: Not set
        ...0 0000 0000 0000 = Fragment offset: 0
    Time to live: 60
    Protocol: UDP (17)
    Header checksum: 0x0cdc [validation disabled]
    [Header checksum status: Unverified]
    Source: 192.168.1.104
    Destination: 192.168.1.102
User Datagram Protocol, Src Port: 161, Dst Port: 4336
    Source Port: 161
    Destination Port: 4336
    Length: 59
    Checksum: 0x52f0 [unverified]
    [Checksum Status: Unverified]
    [Stream index: 1]
Simple Network Management Protocol
    version: version-1 (0)
    community: public
    data: get-response (2)
        get-response
            request-id: 6396
            error-status: noError (0)
            error-index: 0
            variable-bindings: 1 item
                1.3.6.1.4.1.11.2.3.9.4.2.1.2.2.2.1.0: 10
                    Object Name: 1.3.6.1.4.1.11.2.3.9.4.2.1.2.2.2.1.0 (iso.3.6.1.4.1.11.2.3.9.4.2.1.2.2.2.1.0)
                    Value (OctetString): 10
No.    Time                          Source              Destination         Protocol Length Info
    13 2003-09-23 13:39:58.930512    192.168.1.102       192.168.1.104       SNMP     92      get-request
1.3.6.1.4.1.11.2.3.9.4.2.1.2.2.2.1.0
Frame 13: 92 bytes on wire (736 bits), 92 bytes captured (736 bits)
    Encapsulation type: Ethernet (1)
    Arrival Time: Sep 23, 2003 13:39:58.930512000 中国标准时间
    [Time shift for this packet: 0.000000000 seconds]
    Epoch Time: 1064295598.930512000 seconds
    [Time delta from previous captured frame: 2.999592000 seconds]
    [Time delta from previous displayed frame: 2.999592000 seconds]
    [Time since reference or first frame: 6.033719000 seconds]
    Frame Number: 13
    Frame Length: 92 bytes (736 bits)
    Capture Length: 92 bytes (736 bits)
    [Frame is marked: False]
    [Frame is ignored: False]
    [Protocols in frame: eth:ethertype:ip:udp:snmp]
    [Coloring Rule Name: UDP]
    [Coloring Rule String: udp]
Ethernet II, Src: Dell_4f:36:23 (00:08:74:4f:36:23), Dst: HewlettP_61:eb:ed (00:30:c1:61:eb:ed)
    Destination: HewlettP_61:eb:ed (00:30:c1:61:eb:ed)
        Address: HewlettP_61:eb:ed (00:30:c1:61:eb:ed)
        .... ..0. .... .... .... .... = LG bit: Globally unique address (factory default)
        .... ...0 .... .... .... .... = IG bit: Individual address (unicast)
    Source: Dell_4f:36:23 (00:08:74:4f:36:23)
        Address: Dell_4f:36:23 (00:08:74:4f:36:23)
        .... ..0. .... .... .... .... = LG bit: Globally unique address (factory default)
        .... ...0 .... .... .... .... = IG bit: Individual address (unicast)
    Type: IPv4 (0x0800)
Internet Protocol Version 4, Src: 192.168.1.102, Dst: 192.168.1.104
    0100 .... = Version: 4
    .... 0101 = Header Length: 20 bytes (5)
    Differentiated Services Field: 0x00 (DSCP: CS0, ECN: Not-ECT)
        0000 00.. = Differentiated Services Codepoint: Default (0)
        .... ..00 = Explicit Congestion Notification: Not ECN-Capable Transport (0)
    Total Length: 78
    Identification: 0x0309 (777)
    Flags: 0x0000
        0... .... .... .... = Reserved bit: Not set
        .0.. .... .... .... = Don't fragment: Not set
```

```
    ..0. .... .... .... = More fragments: Not set
    ...0 0000 0000 0000 = Fragment offset: 0
    Time to live: 128
    Protocol: UDP (17)
    Header checksum: 0x0000 [validation disabled]
    [Header checksum status: Unverified]
    Source: 192.168.1.102
    Destination: 192.168.1.104
User Datagram Protocol, Src Port: 4337, Dst Port: 161
    Source Port: 4337
    Destination Port: 161
    Length: 58
    Checksum: 0x63f5 [unverified]
    [Checksum Status: Unverified]
    [Stream index: 2]
Simple Network Management Protocol
    version: version-1 (0)
    community: public
    data: get-request (0)
        get-request
            request-id: 6397
            error-status: noError (0)
            error-index: 0
            variable-bindings: 1 item
                1.3.6.1.4.1.11.2.3.9.4.2.1.2.2.2.1.0: Value (Null)
                    Object Name: 1.3.6.1.4.1.11.2.3.9.4.2.1.2.2.2.1.0 (iso.3.6.1.4.1.11.2.3.9.4.2.1.2.2.2.1.0)
                    Value (Null)
No.     Time                        Source              Destination         Protocol Length Info
     14 2003-09-23 13:39:58.947601  192.168.1.104       192.168.1.102       SNMP      93    get-response
1.3.6.1.4.1.11.2.3.9.4.2.1.2.2.2.1.0
Frame 14: 93 bytes on wire (744 bits), 93 bytes captured (744 bits)
    Encapsulation type: Ethernet (1)
    Arrival Time: Sep 23, 2003 13:39:58.947601000 中国标准时间
    [Time shift for this packet: 0.000000000 seconds]
    Epoch Time: 1064295598.947601000 seconds
    [Time delta from previous captured frame: 0.017089000 seconds]
    [Time delta from previous displayed frame: 0.017089000 seconds]
    [Time since reference or first frame: 6.050808000 seconds]
    Frame Number: 14
    Frame Length: 93 bytes (744 bits)
    Capture Length: 93 bytes (744 bits)
    [Frame is marked: False]
    [Frame is ignored: False]
    [Protocols in frame: eth:ethertype:ip:udp:snmp]
    [Coloring Rule Name: UDP]
    [Coloring Rule String: udp]
Ethernet II, Src: HewlettP_61:eb:ed (00:30:c1:61:eb:ed), Dst: Dell_4f:36:23 (00:08:74:4f:36:23)
    Destination: Dell_4f:36:23 (00:08:74:4f:36:23)
        Address: Dell_4f:36:23 (00:08:74:4f:36:23)
        .... ..0. .... .... .... .... = LG bit: Globally unique address (factory default)
        .... ...0 .... .... .... .... = IG bit: Individual address (unicast)
    Source: HewlettP_61:eb:ed (00:30:c1:61:eb:ed)
        Address: HewlettP_61:eb:ed (00:30:c1:61:eb:ed)
        .... ..0. .... .... .... .... = LG bit: Globally unique address (factory default)
        .... ...0 .... .... .... .... = IG bit: Individual address (unicast)
    Type: IPv4 (0x0800)
Internet Protocol Version 4, Src: 192.168.1.104, Dst: 192.168.1.102
    0100 .... = Version: 4
    .... 0101 = Header Length: 20 bytes (5)
    Differentiated Services Field: 0x00 (DSCP: CS0, ECN: Not-ECT)
        0000 00.. = Differentiated Services Codepoint: Default (0)
        .... ..00 = Explicit Congestion Notification: Not ECN-Capable Transport (0)
    Total Length: 79
    Identification: 0xeda4 (60836)
    Flags: 0x0000
        0... .... .... .... = Reserved bit: Not set
        .0.. .... .... .... = Don't fragment: Not set
        ..0. .... .... .... = More fragments: Not set
        ...0 0000 0000 0000 = Fragment offset: 0
    Time to live: 60
    Protocol: UDP (17)
    Header checksum: 0x0cdb [validation disabled]
    [Header checksum status: Unverified]
    Source: 192.168.1.104
    Destination: 192.168.1.102
User Datagram Protocol, Src Port: 161, Dst Port: 4337
    Source Port: 161
```

```
    Destination Port: 4337
    Length: 59
    Checksum: 0x51ef [unverified]
    [Checksum Status: Unverified]
    [Stream index: 2]
Simple Network Management Protocol
    version: version-1 (0)
    community: public
    data: get-response (2)
        get-response
            request-id: 6397
            error-status: noError (0)
            error-index: 0
            variable-bindings: 1 item
                1.3.6.1.4.1.11.2.3.9.4.2.1.2.2.2.1.0: 10
                    Object Name: 1.3.6.1.4.1.11.2.3.9.4.2.1.2.2.2.1.0 (iso.3.6.1.4.1.11.2.3.9.4.2.1.2.2.2.1.0)
                    Value (OctetString): 10
No.     Time                        Source              Destination         Protocol Length Info
     15 2003-09-23 13:40:01.947256  192.168.1.102       192.168.1.104       SNMP     92     get-request
1.3.6.1.4.1.11.2.3.9.4.2.1.2.2.2.1.0
Frame 15: 92 bytes on wire (736 bits), 92 bytes captured (736 bits)
    Encapsulation type: Ethernet (1)
    Arrival Time: Sep 23, 2003 13:40:01.947256000 中国标准时间
    [Time shift for this packet: 0.000000000 seconds]
    Epoch Time: 1064295601.947256000 seconds
    [Time delta from previous captured frame: 2.999655000 seconds]
    [Time delta from previous displayed frame: 2.999655000 seconds]
    [Time since reference or first frame: 9.050463000 seconds]
    Frame Number: 15
    Frame Length: 92 bytes (736 bits)
    Capture Length: 92 bytes (736 bits)
    [Frame is marked: False]
    [Frame is ignored: False]
    [Protocols in frame: eth:ethertype:ip:udp:snmp]
    [Coloring Rule Name: UDP]
    [Coloring Rule String: udp]
Ethernet II, Src: Dell_4f:36:23 (00:08:74:4f:36:23), Dst: HewlettP_61:eb:ed (00:30:c1:61:eb:ed)
    Destination: HewlettP_61:eb:ed (00:30:c1:61:eb:ed)
        Address: HewlettP_61:eb:ed (00:30:c1:61:eb:ed)
        .... ..0. .... .... .... .... = LG bit: Globally unique address (factory default)
        .... ...0 .... .... .... .... = IG bit: Individual address (unicast)
    Source: Dell_4f:36:23 (00:08:74:4f:36:23)
        Address: Dell_4f:36:23 (00:08:74:4f:36:23)
        .... ..0. .... .... .... .... = LG bit: Globally unique address (factory default)
        .... ...0 .... .... .... .... = IG bit: Individual address (unicast)
    Type: IPv4 (0x0800)
Internet Protocol Version 4, Src: 192.168.1.102, Dst: 192.168.1.104
    0100 .... = Version: 4
    .... 0101 = Header Length: 20 bytes (5)
    Differentiated Services Field: 0x00 (DSCP: CS0, ECN: Not-ECT)
        0000 00.. = Differentiated Services Codepoint: Default (0)
        .... ..00 = Explicit Congestion Notification: Not ECN-Capable Transport (0)
    Total Length: 78
    Identification: 0x030a (778)
    Flags: 0x0000
        0... .... .... .... = Reserved bit: Not set
        .0.. .... .... .... = Don't fragment: Not set
        ..0. .... .... .... = More fragments: Not set
        ...0 0000 0000 0000 = Fragment offset: 0
    Time to live: 128
    Protocol: UDP (17)
    Header checksum: 0x0000 [validation disabled]
    [Header checksum status: Unverified]
    Source: 192.168.1.102
    Destination: 192.168.1.104
User Datagram Protocol, Src Port: 4338, Dst Port: 161
    Source Port: 4338
    Destination Port: 161
    Length: 58
    Checksum: 0x62f4 [unverified]
    [Checksum Status: Unverified]
    [Stream index: 3]
Simple Network Management Protocol
    version: version-1 (0)
    community: public
    data: get-request (0)
        get-request
```

```
                    request-id: 6398
                    error-status: noError (0)
                    error-index: 0
                    variable-bindings: 1 item
                        1.3.6.1.4.1.11.2.3.9.4.2.1.2.2.2.1.0: Value (Null)
                            Object Name: 1.3.6.1.4.1.11.2.3.9.4.2.1.2.2.2.1.0 (iso.3.6.1.4.1.11.2.3.9.4.2.1.2.2.2.1.0)
                            Value (Null)
No.     Time                           Source               Destination          Protocol Length Info
     16 2003-09-23 13:40:01.964285      192.168.1.104        192.168.1.102        SNMP     93       get-response
1.3.6.1.4.1.11.2.3.9.4.2.1.2.2.2.1.0
Frame 16: 93 bytes on wire (744 bits), 93 bytes captured (744 bits)
    Encapsulation type: Ethernet (1)
    Arrival Time: Sep 23, 2003 13:40:01.964285000 中国标准时间
    [Time shift for this packet: 0.000000000 seconds]
    Epoch Time: 1064295601.964285000 seconds
    [Time delta from previous captured frame: 0.017029000 seconds]
    [Time delta from previous displayed frame: 0.017029000 seconds]
    [Time since reference or first frame: 9.067492000 seconds]
    Frame Number: 16
    Frame Length: 93 bytes (744 bits)
    Capture Length: 93 bytes (744 bits)
    [Frame is marked: False]
    [Frame is ignored: False]
    [Protocols in frame: eth:ethertype:ip:udp:snmp]
    [Coloring Rule Name: UDP]
    [Coloring Rule String: udp]
Ethernet II, Src: HewlettP_61:eb:ed (00:30:c1:61:eb:ed), Dst: Dell_4f:36:23 (00:08:74:4f:36:23)
    Destination: Dell_4f:36:23 (00:08:74:4f:36:23)
        Address: Dell_4f:36:23 (00:08:74:4f:36:23)
        .... ..0. .... .... .... .... = LG bit: Globally unique address (factory default)
        .... ...0 .... .... .... .... = IG bit: Individual address (unicast)
    Source: HewlettP_61:eb:ed (00:30:c1:61:eb:ed)
        Address: HewlettP_61:eb:ed (00:30:c1:61:eb:ed)
        .... ..0. .... .... .... .... = LG bit: Globally unique address (factory default)
        .... ...0 .... .... .... .... = IG bit: Individual address (unicast)
    Type: IPv4 (0x0800)
Internet Protocol Version 4, Src: 192.168.1.104, Dst: 192.168.1.102
    0100 .... = Version: 4
    .... 0101 = Header Length: 20 bytes (5)
    Differentiated Services Field: 0x00 (DSCP: CS0, ECN: Not-ECT)
        0000 00.. = Differentiated Services Codepoint: Default (0)
        .... ..00 = Explicit Congestion Notification: Not ECN-Capable Transport (0)
    Total Length: 79
    Identification: 0xeda5 (60837)
    Flags: 0x0000
        0... .... .... .... = Reserved bit: Not set
        .0.. .... .... .... = Don't fragment: Not set
        ..0. .... .... .... = More fragments: Not set
        ...0 0000 0000 0000 = Fragment offset: 0
    Time to live: 60
    Protocol: UDP (17)
    Header checksum: 0x0cda [validation disabled]
    [Header checksum status: Unverified]
    Source: 192.168.1.104
    Destination: 192.168.1.102
User Datagram Protocol, Src Port: 161, Dst Port: 4338
    Source Port: 161
    Destination Port: 4338
    Length: 59
    Checksum: 0x50ee [unverified]
    [Checksum Status: Unverified]
    [Stream index: 3]
Simple Network Management Protocol
    version: version-1 (0)
    community: public
    data: get-response (2)
        get-response
            request-id: 6398
            error-status: noError (0)
            error-index: 0
            variable-bindings: 1 item
                1.3.6.1.4.1.11.2.3.9.4.2.1.2.2.2.1.0: 10
                    Object Name: 1.3.6.1.4.1.11.2.3.9.4.2.1.2.2.2.1.0 (iso.3.6.1.4.1.11.2.3.9.4.2.1.2.2.2.1.0)
                    Value (OctetString): 10
No.     Time                           Source               Destination          Protocol Length Info
     17 2003-09-23 13:40:04.964007      192.168.1.102        192.168.1.104        SNMP     92       get-request
1.3.6.1.4.1.11.2.3.9.4.2.1.2.2.2.1.0
```

```
Frame 17: 92 bytes on wire (736 bits), 92 bytes captured (736 bits)
    Encapsulation type: Ethernet (1)
    Arrival Time: Sep 23, 2003 13:40:04.964007000 中国标准时间
    [Time shift for this packet: 0.000000000 seconds]
    Epoch Time: 1064295604.964007000 seconds
    [Time delta from previous captured frame: 2.999722000 seconds]
    [Time delta from previous displayed frame: 2.999722000 seconds]
    [Time since reference or first frame: 12.067214000 seconds]
    Frame Number: 17
    Frame Length: 92 bytes (736 bits)
    Capture Length: 92 bytes (736 bits)
    [Frame is marked: False]
    [Frame is ignored: False]
    [Protocols in frame: eth:ethertype:ip:udp:snmp]
    [Coloring Rule Name: UDP]
    [Coloring Rule String: udp]
Ethernet II, Src: Dell_4f:36:23 (00:08:74:4f:36:23), Dst: HewlettP_61:eb:ed (00:30:c1:61:eb:ed)
    Destination: HewlettP_61:eb:ed (00:30:c1:61:eb:ed)
        Address: HewlettP_61:eb:ed (00:30:c1:61:eb:ed)
        .... ..0. .... .... .... .... = LG bit: Globally unique address (factory default)
        .... ...0 .... .... .... .... = IG bit: Individual address (unicast)
    Source: Dell_4f:36:23 (00:08:74:4f:36:23)
        Address: Dell_4f:36:23 (00:08:74:4f:36:23)
        .... ..0. .... .... .... .... = LG bit: Globally unique address (factory default)
        .... ...0 .... .... .... .... = IG bit: Individual address (unicast)
    Type: IPv4 (0x0800)
Internet Protocol Version 4, Src: 192.168.1.102, Dst: 192.168.1.104
    0100 .... = Version: 4
    .... 0101 = Header Length: 20 bytes (5)
    Differentiated Services Field: 0x00 (DSCP: CS0, ECN: Not-ECT)
        0000 00.. = Differentiated Services Codepoint: Default (0)
        .... ..00 = Explicit Congestion Notification: Not ECN-Capable Transport (0)
    Total Length: 78
    Identification: 0x030b (779)
    Flags: 0x0000
        0... .... .... .... = Reserved bit: Not set
        .0.. .... .... .... = Don't fragment: Not set
        ..0. .... .... .... = More fragments: Not set
        ...0 0000 0000 0000 = Fragment offset: 0
    Time to live: 128
    Protocol: UDP (17)
    Header checksum: 0x0000 [validation disabled]
    [Header checksum status: Unverified]
    Source: 192.168.1.102
    Destination: 192.168.1.104
User Datagram Protocol, Src Port: 4339, Dst Port: 161
    Source Port: 4339
    Destination Port: 161
    Length: 58
    Checksum: 0x61f3 [unverified]
    [Checksum Status: Unverified]
    [Stream index: 4]
Simple Network Management Protocol
    version: version-1 (0)
    community: public
    data: get-request (0)
        get-request
            request-id: 6399
            error-status: noError (0)
            error-index: 0
            variable-bindings: 1 item
                1.3.6.1.4.1.11.2.3.9.4.2.1.2.2.2.1.0: Value (Null)
                    Object Name: 1.3.6.1.4.1.11.2.3.9.4.2.1.2.2.2.1.0 (iso.3.6.1.4.1.11.2.3.9.4.2.1.2.2.2.1.0)
                    Value (Null)
No.     Time                          Source              Destination           Protocol Length Info
     18 2003-09-23 13:40:04.981940     192.168.1.104       192.168.1.102         SNMP     93      get-response
1.3.6.1.4.1.11.2.3.9.4.2.1.2.2.2.1.0
Frame 18: 93 bytes on wire (744 bits), 93 bytes captured (744 bits)
    Encapsulation type: Ethernet (1)
    Arrival Time: Sep 23, 2003 13:40:04.981940000 中国标准时间
    [Time shift for this packet: 0.000000000 seconds]
    Epoch Time: 1064295604.981940000 seconds
    [Time delta from previous captured frame: 0.017933000 seconds]
    [Time delta from previous displayed frame: 0.017933000 seconds]
    [Time since reference or first frame: 12.085147000 seconds]
    Frame Number: 18
    Frame Length: 93 bytes (744 bits)
```

```
    Capture Length: 93 bytes (744 bits)
    [Frame is marked: False]
    [Frame is ignored: False]
    [Protocols in frame: eth:ethertype:ip:udp:snmp]
    [Coloring Rule Name: UDP]
    [Coloring Rule String: udp]
Ethernet II, Src: HewlettP_61:eb:ed (00:30:c1:61:eb:ed), Dst: Dell_4f:36:23 (00:08:74:4f:36:23)
    Destination: Dell_4f:36:23 (00:08:74:4f:36:23)
        Address: Dell_4f:36:23 (00:08:74:4f:36:23)
        .... ..0. .... .... .... .... = LG bit: Globally unique address (factory default)
        .... ...0 .... .... .... .... = IG bit: Individual address (unicast)
    Source: HewlettP_61:eb:ed (00:30:c1:61:eb:ed)
        Address: HewlettP_61:eb:ed (00:30:c1:61:eb:ed)
        .... ..0. .... .... .... .... = LG bit: Globally unique address (factory default)
        .... ...0 .... .... .... .... = IG bit: Individual address (unicast)
    Type: IPv4 (0x0800)
Internet Protocol Version 4, Src: 192.168.1.104, Dst: 192.168.1.102
    0100 .... = Version: 4
    .... 0101 = Header Length: 20 bytes (5)
    Differentiated Services Field: 0x00 (DSCP: CS0, ECN: Not-ECT)
        0000 00.. = Differentiated Services Codepoint: Default (0)
        .... ..00 = Explicit Congestion Notification: Not ECN-Capable Transport (0)
    Total Length: 79
    Identification: 0xeda6 (60838)
    Flags: 0x0000
        0... .... .... .... = Reserved bit: Not set
        .0.. .... .... .... = Don't fragment: Not set
        ..0. .... .... .... = More fragments: Not set
        ...0 0000 0000 0000 = Fragment offset: 0
    Time to live: 60
    Protocol: UDP (17)
    Header checksum: 0x0cd9 [validation disabled]
    [Header checksum status: Unverified]
    Source: 192.168.1.104
    Destination: 192.168.1.102
User Datagram Protocol, Src Port: 161, Dst Port: 4339
    Source Port: 161
    Destination Port: 4339
    Length: 59
    Checksum: 0x4fed [unverified]
    [Checksum Status: Unverified]
    [Stream index: 4]
Simple Network Management Protocol
    version: version-1 (0)
    community: public
    data: get-response (2)
        get-response
            request-id: 6399
            error-status: noError (0)
            error-index: 0
            variable-bindings: 1 item
                1.3.6.1.4.1.11.2.3.9.4.2.1.2.2.2.1.0: 10
                    Object Name: 1.3.6.1.4.1.11.2.3.9.4.2.1.2.2.2.1.0 (iso.3.6.1.4.1.11.2.3.9.4.2.1.2.2.2.1.0)
                    Value (OctetString): 10
No.     Time                        Source          Destination       Protocol Length Info
    19 2003-09-23 13:40:05.217358    192.168.1.100     192.168.1.255     NBNS     92     Name query NB NOHO<20>
Frame 19: 92 bytes on wire (736 bits), 92 bytes captured (736 bits)
    Encapsulation type: Ethernet (1)
    Arrival Time: Sep 23, 2003 13:40:05.217358000 中国标准时间
    [Time shift for this packet: 0.000000000 seconds]
    Epoch Time: 1064295605.217358000 seconds
    [Time delta from previous captured frame: 0.235418000 seconds]
    [Time delta from previous displayed frame: 0.235418000 seconds]
    [Time since reference or first frame: 12.320565000 seconds]
    Frame Number: 19
    Frame Length: 92 bytes (736 bits)
    Capture Length: 92 bytes (736 bits)
    [Frame is marked: False]
    [Frame is ignored: False]
    [Protocols in frame: eth:ethertype:ip:udp:nbns]
    [Coloring Rule Name: SMB]
    [Coloring Rule String: smb || nbss || nbns || nbipx || ipxsap || netbios]
Ethernet II, Src: CnetTech_73:8d:ce (00:80:ad:73:8d:ce), Dst: Broadcast (ff:ff:ff:ff:ff:ff)
    Destination: Broadcast (ff:ff:ff:ff:ff:ff)
        Address: Broadcast (ff:ff:ff:ff:ff:ff)
        .... ..1. .... .... .... .... = LG bit: Locally administered address (this is NOT the factory default)
        .... ...1 .... .... .... .... = IG bit: Group address (multicast/broadcast)
```

```
    Source: CnetTech_73:8d:ce (00:80:ad:73:8d:ce)
        Address: CnetTech_73:8d:ce (00:80:ad:73:8d:ce)
        .... ..0. .... .... .... .... = LG bit: Globally unique address (factory default)
        .... ...0 .... .... .... .... = IG bit: Individual address (unicast)
    Type: IPv4 (0x0800)
Internet Protocol Version 4, Src: 192.168.1.100, Dst: 192.168.1.255
    0100 .... = Version: 4
    .... 0101 = Header Length: 20 bytes (5)
    Differentiated Services Field: 0x00 (DSCP: CS0, ECN: Not-ECT)
        0000 00.. = Differentiated Services Codepoint: Default (0)
        .... ..00 = Explicit Congestion Notification: Not ECN-Capable Transport (0)
    Total Length: 78
    Identification: 0xd9f8 (55800)
    Flags: 0x0000
        0... .... .... .... = Reserved bit: Not set
        .0.. .... .... .... = Don't fragment: Not set
        ..0. .... .... .... = More fragments: Not set
        ...0 0000 0000 0000 = Fragment offset: 0
    Time to live: 128
    Protocol: UDP (17)
    Header checksum: 0xdbf2 [validation disabled]
    [Header checksum status: Unverified]
    Source: 192.168.1.100
    Destination: 192.168.1.255
User Datagram Protocol, Src Port: 137, Dst Port: 137
    Source Port: 137
    Destination Port: 137
    Length: 58
    Checksum: 0x7853 [unverified]
    [Checksum Status: Unverified]
    [Stream index: 5]
NetBIOS Name Service
    Transaction ID: 0x97f2
    Flags: 0x0110, Opcode: Name query, Recursion desired, Broadcast
        0... .... .... .... = Response: Message is a query
        .000 0... .... .... = Opcode: Name query (0)
        .... ..0. .... .... = Truncated: Message is not truncated
        .... ...1 .... .... = Recursion desired: Do query recursively
        .... .... ...1 .... = Broadcast: Broadcast packet
    Questions: 1
    Answer RRs: 0
    Authority RRs: 0
    Additional RRs: 0
    Queries
        NOHO<20>: type NB, class IN
            Name: NOHO<20> (Server service)
            Type: NB (32)
            Class: IN (1)
No.     Time                            Source                Destination           Protocol Length Info
     20 2003-09-23 13:40:05.217393      192.168.1.102         192.168.1.100         NBNS     104    Name query response NB
192.168.1.102
Frame 20: 104 bytes on wire (832 bits), 104 bytes captured (832 bits)
    Encapsulation type: Ethernet (1)
    Arrival Time: Sep 23, 2003 13:40:05.217393000 中国标准时间
    [Time shift for this packet: 0.000000000 seconds]
    Epoch Time: 1064295605.217393000 seconds
    [Time delta from previous captured frame: 0.000035000 seconds]
    [Time delta from previous displayed frame: 0.000035000 seconds]
    [Time since reference or first frame: 12.320600000 seconds]
    Frame Number: 20
    Frame Length: 104 bytes (832 bits)
    Capture Length: 104 bytes (832 bits)
    [Frame is marked: False]
    [Frame is ignored: False]
    [Protocols in frame: eth:ethertype:ip:udp:nbns]
    [Coloring Rule Name: SMB]
    [Coloring Rule String: smb || nbss || nbns || nbipx || ipxsap || netbios]
Ethernet II, Src: Dell_4f:36:23 (00:08:74:4f:36:23), Dst: CnetTech_73:8d:ce (00:80:ad:73:8d:ce)
    Destination: CnetTech_73:8d:ce (00:80:ad:73:8d:ce)
        Address: CnetTech_73:8d:ce (00:80:ad:73:8d:ce)
        .... ..0. .... .... .... .... = LG bit: Globally unique address (factory default)
        .... ...0 .... .... .... .... = IG bit: Individual address (unicast)
    Source: Dell_4f:36:23 (00:08:74:4f:36:23)
        Address: Dell_4f:36:23 (00:08:74:4f:36:23)
        .... ..0. .... .... .... .... = LG bit: Globally unique address (factory default)
        .... ...0 .... .... .... .... = IG bit: Individual address (unicast)
    Type: IPv4 (0x0800)
```

```
Internet Protocol Version 4, Src: 192.168.1.102, Dst: 192.168.1.100
    0100 .... = Version: 4
    .... 0101 = Header Length: 20 bytes (5)
    Differentiated Services Field: 0x00 (DSCP: CS0, ECN: Not-ECT)
        0000 00.. = Differentiated Services Codepoint: Default (0)
        .... ..00 = Explicit Congestion Notification: Not ECN-Capable Transport (0)
    Total Length: 90
    Identification: 0x030c (780)
    Flags: 0x0000
        0... .... .... .... = Reserved bit: Not set
        .0.. .... .... .... = Don't fragment: Not set
        ..0. .... .... .... = More fragments: Not set
        ...0 0000 0000 0000 = Fragment offset: 0
    Time to live: 128
    Protocol: UDP (17)
    Header checksum: 0x0000 [validation disabled]
    [Header checksum status: Unverified]
    Source: 192.168.1.102
    Destination: 192.168.1.100
User Datagram Protocol, Src Port: 137, Dst Port: 137
    Source Port: 137
    Destination Port: 137
    Length: 70
    Checksum: 0x3eea [unverified]
    [Checksum Status: Unverified]
    [Stream index: 6]
NetBIOS Name Service
    Transaction ID: 0x97f2
    Flags: 0x8500, Response, Opcode: Name query, Authoritative, Recursion desired, Reply code: No error
        1... .... .... .... = Response: Message is a response
        .000 0... .... .... = Opcode: Name query (0)
        .... .1.. .... .... = Authoritative: Server is an authority for domain
        .... ..0. .... .... = Truncated: Message is not truncated
        .... ...1 .... .... = Recursion desired: Do query recursively
        .... .... 0... .... = Recursion available: Server can't do recursive queries
        .... .... ...0 .... = Broadcast: Not a broadcast packet
        .... .... .... 0000 = Reply code: No error (0)
    Questions: 0
    Answer RRs: 1
    Authority RRs: 0
    Additional RRs: 0
    Answers
        NOHO<20>: type NB, class IN
            Name: NOHO<20> (Server service)
            Type: NB (32)
            Class: IN (1)
            Time to live: 3 days, 11 hours, 20 minutes
            Data length: 6
            Name flags: 0x6000, ONT: Unknown (H-node, unique)
                0... .... .... .... = Name type: Unique name
                .11. .... .... .... = ONT: Unknown (3)
            Addr: 192.168.1.102
No.     Time                          Source              Destination           Protocol Length Info
    56 2003-09-23 13:40:07.981721    192.168.1.102       192.168.1.104         SNMP     92      get-request
1.3.6.1.4.1.11.2.3.9.4.2.1.2.2.2.1.0
Frame 56: 92 bytes on wire (736 bits), 92 bytes captured (736 bits)
    Encapsulation type: Ethernet (1)
    Arrival Time: Sep 23, 2003 13:40:07.981721000 中国标准时间
    [Time shift for this packet: 0.000000000 seconds]
    Epoch Time: 1064295607.981721000 seconds
    [Time delta from previous captured frame: 2.542284000 seconds]
    [Time delta from previous displayed frame: 2.764328000 seconds]
    [Time since reference or first frame: 15.084928000 seconds]
    Frame Number: 56
    Frame Length: 92 bytes (736 bits)
    Capture Length: 92 bytes (736 bits)
    [Frame is marked: False]
    [Frame is ignored: False]
    [Protocols in frame: eth:ethertype:ip:udp:snmp]
    [Coloring Rule Name: UDP]
    [Coloring Rule String: udp]
Ethernet II, Src: Dell_4f:36:23 (00:08:74:4f:36:23), Dst: HewlettP_61:eb:ed (00:30:c1:61:eb:ed)
    Destination: HewlettP_61:eb:ed (00:30:c1:61:eb:ed)
        Address: HewlettP_61:eb:ed (00:30:c1:61:eb:ed)
        .... ..0. .... .... .... .... = LG bit: Globally unique address (factory default)
        .... ...0 .... .... .... .... = IG bit: Individual address (unicast)
    Source: Dell_4f:36:23 (00:08:74:4f:36:23)
```

```
        Address: Dell_4f:36:23 (00:08:74:4f:36:23)
        .... ..0. .... .... .... .... = LG bit: Globally unique address (factory default)
        .... ...0 .... .... .... .... = IG bit: Individual address (unicast)
    Type: IPv4 (0x0800)
Internet Protocol Version 4, Src: 192.168.1.102, Dst: 192.168.1.104
    0100 .... = Version: 4
    .... 0101 = Header Length: 20 bytes (5)
    Differentiated Services Field: 0x00 (DSCP: CS0, ECN: Not-ECT)
        0000 00.. = Differentiated Services Codepoint: Default (0)
        .... ..00 = Explicit Congestion Notification: Not ECN-Capable Transport (0)
    Total Length: 78
    Identification: 0x031e (798)
    Flags: 0x0000
        0... .... .... .... = Reserved bit: Not set
        .0.. .... .... .... = Don't fragment: Not set
        ..0. .... .... .... = More fragments: Not set
        ...0 0000 0000 0000 = Fragment offset: 0
    Time to live: 128
    Protocol: UDP (17)
    Header checksum: 0x0000 [validation disabled]
    [Header checksum status: Unverified]
    Source: 192.168.1.102
    Destination: 192.168.1.104
User Datagram Protocol, Src Port: 4340, Dst Port: 161
    Source Port: 4340
    Destination Port: 161
    Length: 58
    Checksum: 0x60f2 [unverified]
    [Checksum Status: Unverified]
    [Stream index: 7]
Simple Network Management Protocol
    version: version-1 (0)
    community: public
    data: get-request (0)
        get-request
            request-id: 6400
            error-status: noError (0)
            error-index: 0
            variable-bindings: 1 item
                1.3.6.1.4.1.11.2.3.9.4.2.1.2.2.2.1.0: Value (Null)
                    Object Name: 1.3.6.1.4.1.11.2.3.9.4.2.1.2.2.2.1.0 (iso.3.6.1.4.1.11.2.3.9.4.2.1.2.2.2.1.0)
                    Value (Null)
No.    Time                         Source            Destination          Protocol Length Info
    57 2003-09-23 13:40:07.999107   192.168.1.104     192.168.1.102        SNMP     93      get-response
1.3.6.1.4.1.11.2.3.9.4.2.1.2.2.2.1.0
Frame 57: 93 bytes on wire (744 bits), 93 bytes captured (744 bits)
    Encapsulation type: Ethernet (1)
    Arrival Time: Sep 23, 2003 13:40:07.999107000 中国标准时间
    [Time shift for this packet: 0.000000000 seconds]
    Epoch Time: 1064295607.999107000 seconds
    [Time delta from previous captured frame: 0.017386000 seconds]
    [Time delta from previous displayed frame: 0.017386000 seconds]
    [Time since reference or first frame: 15.102314000 seconds]
    Frame Number: 57
    Frame Length: 93 bytes (744 bits)
    Capture Length: 93 bytes (744 bits)
    [Frame is marked: False]
    [Frame is ignored: False]
    [Protocols in frame: eth:ethertype:ip:udp:snmp]
    [Coloring Rule Name: UDP]
    [Coloring Rule String: udp]
Ethernet II, Src: HewlettP_61:eb:ed (00:30:c1:61:eb:ed), Dst: Dell_4f:36:23 (00:08:74:4f:36:23)
    Destination: Dell_4f:36:23 (00:08:74:4f:36:23)
        Address: Dell_4f:36:23 (00:08:74:4f:36:23)
        .... ..0. .... .... .... .... = LG bit: Globally unique address (factory default)
        .... ...0 .... .... .... .... = IG bit: Individual address (unicast)
    Source: HewlettP_61:eb:ed (00:30:c1:61:eb:ed)
        Address: HewlettP_61:eb:ed (00:30:c1:61:eb:ed)
        .... ..0. .... .... .... .... = LG bit: Globally unique address (factory default)
        .... ...0 .... .... .... .... = IG bit: Individual address (unicast)
    Type: IPv4 (0x0800)
Internet Protocol Version 4, Src: 192.168.1.104, Dst: 192.168.1.102
    0100 .... = Version: 4
    .... 0101 = Header Length: 20 bytes (5)
    Differentiated Services Field: 0x00 (DSCP: CS0, ECN: Not-ECT)
        0000 00.. = Differentiated Services Codepoint: Default (0)
        .... ..00 = Explicit Congestion Notification: Not ECN-Capable Transport (0)
```

```
    Total Length: 79
    Identification: 0xeda7 (60839)
    Flags: 0x0000
        0... .... .... .... = Reserved bit: Not set
        .0.. .... .... .... = Don't fragment: Not set
        ..0. .... .... .... = More fragments: Not set
        ...0 0000 0000 0000 = Fragment offset: 0
    Time to live: 60
    Protocol: UDP (17)
    Header checksum: 0x0cd8 [validation disabled]
    [Header checksum status: Unverified]
    Source: 192.168.1.104
    Destination: 192.168.1.102
User Datagram Protocol, Src Port: 161, Dst Port: 4340
    Source Port: 161
    Destination Port: 4340
    Length: 59
    Checksum: 0x4eec [unverified]
    [Checksum Status: Unverified]
    [Stream index: 7]
Simple Network Management Protocol
    version: version-1 (0)
    community: public
    data: get-response (2)
        get-response
            request-id: 6400
            error-status: noError (0)
            error-index: 0
            variable-bindings: 1 item
                1.3.6.1.4.1.11.2.3.9.4.2.1.2.2.2.1.0: 10
                    Object Name: 1.3.6.1.4.1.11.2.3.9.4.2.1.2.2.2.1.0 (iso.3.6.1.4.1.11.2.3.9.4.2.1.2.2.2.1.0)
                    Value (OctetString): 10
No.     Time                      Source              Destination         Protocol Length Info
     58 2003-09-23 13:40:10.753003   192.168.1.102       192.168.1.255       NBNS     92     Name query NB
WORKGROUP<1b>
Frame 58: 92 bytes on wire (736 bits), 92 bytes captured (736 bits)
    Encapsulation type: Ethernet (1)
    Arrival Time: Sep 23, 2003 13:40:10.753003000 中国标准时间
    [Time shift for this packet: 0.000000000 seconds]
    Epoch Time: 1064295610.753003000 seconds
    [Time delta from previous captured frame: 2.753896000 seconds]
    [Time delta from previous displayed frame: 2.753896000 seconds]
    [Time since reference or first frame: 17.856210000 seconds]
    Frame Number: 58
    Frame Length: 92 bytes (736 bits)
    Capture Length: 92 bytes (736 bits)
    [Frame is marked: False]
    [Frame is ignored: False]
    [Protocols in frame: eth:ethertype:ip:udp:nbns]
    [Coloring Rule Name: SMB]
    [Coloring Rule String: smb || nbss || nbns || nbipx || ipxsap || netbios]
Ethernet II, Src: Dell_4f:36:23 (00:08:74:4f:36:23), Dst: Broadcast (ff:ff:ff:ff:ff:ff)
    Destination: Broadcast (ff:ff:ff:ff:ff:ff)
        Address: Broadcast (ff:ff:ff:ff:ff:ff)
        .... ..1. .... .... .... .... = LG bit: Locally administered address (this is NOT the factory default)
        .... ...1 .... .... .... .... = IG bit: Group address (multicast/broadcast)
    Source: Dell_4f:36:23 (00:08:74:4f:36:23)
        Address: Dell_4f:36:23 (00:08:74:4f:36:23)
        .... ..0. .... .... .... .... = LG bit: Globally unique address (factory default)
        .... ...0 .... .... .... .... = IG bit: Individual address (unicast)
    Type: IPv4 (0x0800)
Internet Protocol Version 4, Src: 192.168.1.102, Dst: 192.168.1.255
    0100 .... = Version: 4
    .... 0101 = Header Length: 20 bytes (5)
    Differentiated Services Field: 0x00 (DSCP: CS0, ECN: Not-ECT)
        0000 00.. = Differentiated Services Codepoint: Default (0)
        .... ..00 = Explicit Congestion Notification: Not ECN-Capable Transport (0)
    Total Length: 78
    Identification: 0x031f (799)
    Flags: 0x0000
        0... .... .... .... = Reserved bit: Not set
        .0.. .... .... .... = Don't fragment: Not set
        ..0. .... .... .... = More fragments: Not set
        ...0 0000 0000 0000 = Fragment offset: 0
    Time to live: 128
    Protocol: UDP (17)
    Header checksum: 0xb2ca [validation disabled]
```

[Header checksum status: Unverified]
        Source: 192.168.1.102
        Destination: 192.168.1.255
User Datagram Protocol, Src Port: 137, Dst Port: 137
        Source Port: 137
        Destination Port: 137
        Length: 58
        Checksum: 0x6608 [unverified]
        [Checksum Status: Unverified]
        [Stream index: 8]
NetBIOS Name Service
        Transaction ID: 0x932d
        Flags: 0x0110, Opcode: Name query, Recursion desired, Broadcast
                0... .... = Response: Message is a query
                .000 0... .... = Opcode: Name query (0)
                .... ..0. .... = Truncated: Message is not truncated
                ....1 .... = Recursion desired: Do query recursively
                ....1 .... = Broadcast: Broadcast packet
        Questions: 1
        Answer RRs: 0
        Authority RRs: 0
        Additional RRs: 0
        Queries
                WORKGROUP<1b>: type NB, class IN
                        Name: WORKGROUP<1b> (Domain Master Browser)
                        Type: NB (32)
                        Class: IN (1)
No.   Time   Source   Destination   Protocol Length Info
     59 2003-09-23 13:40:10.999449   192.168.1.102   192.168.1.104   SNMP   92   get-request
1.3.6.1.4.1.11.2.3.9.4.2.1.2.2.2.1.0
Frame 59: 92 bytes on wire (736 bits), 92 bytes captured (736 bits)
        Encapsulation type: Ethernet (1)
        Arrival Time: Sep 23, 2003 13:40:10.999449000 中国标准时间
        [Time shift for this packet: 0.000000000 seconds]
        Epoch Time: 1064295610.999449000 seconds
        [Time delta from previous captured frame: 0.246446000 seconds]
        [Time delta from previous displayed frame: 0.246446000 seconds]
        [Time since reference or first frame: 18.102656000 seconds]
        Frame Number: 59
        Frame Length: 92 bytes (736 bits)
        Capture Length: 92 bytes (736 bits)
        [Frame is marked: False]
        [Frame is ignored: False]
        [Protocols in frame: eth:ethertype:ip:udp:snmp]
        [Coloring Rule Name: UDP]
        [Coloring Rule String: udp]
Ethernet II, Src: Dell_4f:36:23 (00:08:74:4f:36:23), Dst: HewlettP_61:eb:ed (00:30:c1:61:eb:ed)
        Destination: HewlettP_61:eb:ed (00:30:c1:61:eb:ed)
                Address: HewlettP_61:eb:ed (00:30:c1:61:eb:ed)
                .... ..0. .... = LG bit: Globally unique address (factory default)
                ....0 .... = IG bit: Individual address (unicast)
        Source: Dell_4f:36:23 (00:08:74:4f:36:23)
                Address: Dell_4f:36:23 (00:08:74:4f:36:23)
                .... ..0. .... = LG bit: Globally unique address (factory default)
                ....0 .... = IG bit: Individual address (unicast)
        Type: IPv4 (0x0800)
Internet Protocol Version 4, Src: 192.168.1.102, Dst: 192.168.1.104
        0100 .... = Version: 4
        .... 0101 = Header Length: 20 bytes (5)
        Differentiated Services Field: 0x00 (DSCP: CS0, ECN: Not-ECT)
                0000 00.. = Differentiated Services Codepoint: Default (0)
                .... ..00 = Explicit Congestion Notification: Not ECN-Capable Transport (0)
        Total Length: 78
        Identification: 0x0320 (800)
        Flags: 0x0000
                0... .... = Reserved bit: Not set
                .0.. .... = Don't fragment: Not set
                ..0. .... = More fragments: Not set
                ...0 0000 0000 0000 = Fragment offset: 0
        Time to live: 128
        Protocol: UDP (17)
        Header checksum: 0x0000 [validation disabled]
        [Header checksum status: Unverified]
        Source: 192.168.1.102
        Destination: 192.168.1.104
User Datagram Protocol, Src Port: 4341, Dst Port: 161
        Source Port: 4341

```
    Destination Port: 161
    Length: 58
    Checksum: 0x5ff1 [unverified]
    [Checksum Status: Unverified]
    [Stream index: 9]
Simple Network Management Protocol
    version: version-1 (0)
    community: public
    data: get-request (0)
        get-request
            request-id: 6401
            error-status: noError (0)
            error-index: 0
            variable-bindings: 1 item
                1.3.6.1.4.1.11.2.3.9.4.2.1.2.2.2.1.0: Value (Null)
                    Object Name: 1.3.6.1.4.1.11.2.3.9.4.2.1.2.2.2.1.0 (iso.3.6.1.4.1.11.2.3.9.4.2.1.2.2.2.1.0)
                    Value (Null)
No.    Time                          Source            Destination        Protocol Length Info
    60 2003-09-23 13:40:11.016762    192.168.1.104     192.168.1.102      SNMP     93     get-response
1.3.6.1.4.1.11.2.3.9.4.2.1.2.2.2.1.0
Frame 60: 93 bytes on wire (744 bits), 93 bytes captured (744 bits)
    Encapsulation type: Ethernet (1)
    Arrival Time: Sep 23, 2003 13:40:11.016762000 中国标准时间
    [Time shift for this packet: 0.000000000 seconds]
    Epoch Time: 1064295611.016762000 seconds
    [Time delta from previous captured frame: 0.017313000 seconds]
    [Time delta from previous displayed frame: 0.017313000 seconds]
    [Time since reference or first frame: 18.119969000 seconds]
    Frame Number: 60
    Frame Length: 93 bytes (744 bits)
    Capture Length: 93 bytes (744 bits)
    [Frame is marked: False]
    [Frame is ignored: False]
    [Protocols in frame: eth:ethertype:ip:udp:snmp]
    [Coloring Rule Name: UDP]
    [Coloring Rule String: udp]
Ethernet II, Src: HewlettP_61:eb:ed (00:30:c1:61:eb:ed), Dst: Dell_4f:36:23 (00:08:74:4f:36:23)
    Destination: Dell_4f:36:23 (00:08:74:4f:36:23)
        Address: Dell_4f:36:23 (00:08:74:4f:36:23)
        .... ..0. .... .... .... .... = LG bit: Globally unique address (factory default)
        .... ...0 .... .... .... .... = IG bit: Individual address (unicast)
    Source: HewlettP_61:eb:ed (00:30:c1:61:eb:ed)
        Address: HewlettP_61:eb:ed (00:30:c1:61:eb:ed)
        .... ..0. .... .... .... .... = LG bit: Globally unique address (factory default)
        .... ...0 .... .... .... .... = IG bit: Individual address (unicast)
    Type: IPv4 (0x0800)
Internet Protocol Version 4, Src: 192.168.1.104, Dst: 192.168.1.102
    0100 .... = Version: 4
    .... 0101 = Header Length: 20 bytes (5)
    Differentiated Services Field: 0x00 (DSCP: CS0, ECN: Not-ECT)
        0000 00.. = Differentiated Services Codepoint: Default (0)
        .... ..00 = Explicit Congestion Notification: Not ECN-Capable Transport (0)
    Total Length: 79
    Identification: 0xeda8 (60840)
    Flags: 0x0000
        0... .... .... .... = Reserved bit: Not set
        .0.. .... .... .... = Don't fragment: Not set
        ..0. .... .... .... = More fragments: Not set
        ...0 0000 0000 0000 = Fragment offset: 0
    Time to live: 60
    Protocol: UDP (17)
    Header checksum: 0x0cd7 [validation disabled]
    [Header checksum status: Unverified]
    Source: 192.168.1.104
    Destination: 192.168.1.102
User Datagram Protocol, Src Port: 161, Dst Port: 4341
    Source Port: 161
    Destination Port: 4341
    Length: 59
    Checksum: 0x4deb [unverified]
    [Checksum Status: Unverified]
    [Stream index: 9]
Simple Network Management Protocol
    version: version-1 (0)
    community: public
    data: get-response (2)
        get-response
```

```
                request-id: 6401
                error-status: noError (0)
                error-index: 0
                variable-bindings: 1 item
                    1.3.6.1.4.1.11.2.3.9.4.2.1.2.2.2.1.0: 10
                        Object Name: 1.3.6.1.4.1.11.2.3.9.4.2.1.2.2.2.1.0 (iso.3.6.1.4.1.11.2.3.9.4.2.1.2.2.2.1.0)
                        Value (OctetString): 10
No.    Time                          Source              Destination          Protocol Length Info
    69 2003-09-23 13:40:11.502246    192.168.1.102       192.168.1.255        NBNS     92      Name query NB
WORKGROUP<1b>
Frame 69: 92 bytes on wire (736 bits), 92 bytes captured (736 bits)
    Encapsulation type: Ethernet (1)
    Arrival Time: Sep 23, 2003 13:40:11.502246000 中国标准时间
    [Time shift for this packet: 0.000000000 seconds]
    Epoch Time: 1064295611.502246000 seconds
    [Time delta from previous captured frame: 0.063782000 seconds]
    [Time delta from previous displayed frame: 0.485484000 seconds]
    [Time since reference or first frame: 18.605453000 seconds]
    Frame Number: 69
    Frame Length: 92 bytes (736 bits)
    Capture Length: 92 bytes (736 bits)
    [Frame is marked: False]
    [Frame is ignored: False]
    [Protocols in frame: eth:ethertype:ip:udp:nbns]
    [Coloring Rule Name: SMB]
    [Coloring Rule String: smb || nbss || nbns || nbipx || ipxsap || netbios]
Ethernet II, Src: Dell_4f:36:23 (00:08:74:4f:36:23), Dst: Broadcast (ff:ff:ff:ff:ff:ff)
    Destination: Broadcast (ff:ff:ff:ff:ff:ff)
        Address: Broadcast (ff:ff:ff:ff:ff:ff)
        .... ..1. .... .... .... .... = LG bit: Locally administered address (this is NOT the factory default)
        .... ...1 .... .... .... .... = IG bit: Group address (multicast/broadcast)
    Source: Dell_4f:36:23 (00:08:74:4f:36:23)
        Address: Dell_4f:36:23 (00:08:74:4f:36:23)
        .... ..0. .... .... .... .... = LG bit: Globally unique address (factory default)
        .... ...0 .... .... .... .... = IG bit: Individual address (unicast)
    Type: IPv4 (0x0800)
Internet Protocol Version 4, Src: 192.168.1.102, Dst: 192.168.1.255
    0100 .... = Version: 4
    .... 0101 = Header Length: 20 bytes (5)
    Differentiated Services Field: 0x00 (DSCP: CS0, ECN: Not-ECT)
        0000 00.. = Differentiated Services Codepoint: Default (0)
        .... ..00 = Explicit Congestion Notification: Not ECN-Capable Transport (0)
    Total Length: 78
    Identification: 0x032b (811)
    Flags: 0x0000
        0... .... .... .... = Reserved bit: Not set
        .0.. .... .... .... = Don't fragment: Not set
        ..0. .... .... .... = More fragments: Not set
        ...0 0000 0000 0000 = Fragment offset: 0
    Time to live: 128
    Protocol: UDP (17)
    Header checksum: 0xb2be [validation disabled]
    [Header checksum status: Unverified]
    Source: 192.168.1.102
    Destination: 192.168.1.255
User Datagram Protocol, Src Port: 137, Dst Port: 137
    Source Port: 137
    Destination Port: 137
    Length: 58
    Checksum: 0x6608 [unverified]
    [Checksum Status: Unverified]
    [Stream index: 8]
NetBIOS Name Service
    Transaction ID: 0x932d
    Flags: 0x0110, Opcode: Name query, Recursion desired, Broadcast
        0... .... .... .... = Response: Message is a query
        .000 0... .... .... = Opcode: Name query (0)
        .... ..0. .... .... = Truncated: Message is not truncated
        .... ...1 .... .... = Recursion desired: Do query recursively
        .... .... ...1 .... = Broadcast: Broadcast packet
    Questions: 1
    Answer RRs: 0
    Authority RRs: 0
    Additional RRs: 0
    Queries
        WORKGROUP<1b>: type NB, class IN
            Name: WORKGROUP<1b> (Domain Master Browser)
```

```
                Type: NB (32)
                Class: IN (1)
No.      Time                              Source                Destination           Protocol Length Info
     71 2003-09-23 13:40:12.252279    192.168.1.102         192.168.1.255         NBNS     92      Name query NB
WORKGROUP<1b>
Frame 71: 92 bytes on wire (736 bits), 92 bytes captured (736 bits)
    Encapsulation type: Ethernet (1)
    Arrival Time: Sep 23, 2003 13:40:12.252279000 中国标准时间
    [Time shift for this packet: 0.000000000 seconds]
    Epoch Time: 1064295612.252279000 seconds
    [Time delta from previous captured frame: 0.702190000 seconds]
    [Time delta from previous displayed frame: 0.750033000 seconds]
    [Time since reference or first frame: 19.355486000 seconds]
    Frame Number: 71
    Frame Length: 92 bytes (736 bits)
    Capture Length: 92 bytes (736 bits)
    [Frame is marked: False]
    [Frame is ignored: False]
    [Protocols in frame: eth:ethertype:ip:udp:nbns]
    [Coloring Rule Name: SMB]
    [Coloring Rule String: smb || nbss || nbns || nbipx || ipxsap || netbios]
Ethernet II, Src: Dell_4f:36:23 (00:08:74:4f:36:23), Dst: Broadcast (ff:ff:ff:ff:ff:ff)
    Destination: Broadcast (ff:ff:ff:ff:ff:ff)
        Address: Broadcast (ff:ff:ff:ff:ff:ff)
        .... ..1. .... .... .... .... = LG bit: Locally administered address (this is NOT the factory default)
        .... ...1 .... .... .... .... = IG bit: Group address (multicast/broadcast)
    Source: Dell_4f:36:23 (00:08:74:4f:36:23)
        Address: Dell_4f:36:23 (00:08:74:4f:36:23)
        .... ..0. .... .... .... .... = LG bit: Globally unique address (factory default)
        .... ...0 .... .... .... .... = IG bit: Individual address (unicast)
    Type: IPv4 (0x0800)
Internet Protocol Version 4, Src: 192.168.1.102, Dst: 192.168.1.255
    0100 .... = Version: 4
    .... 0101 = Header Length: 20 bytes (5)
    Differentiated Services Field: 0x00 (DSCP: CS0, ECN: Not-ECT)
        0000 00.. = Differentiated Services Codepoint: Default (0)
        .... ..00 = Explicit Congestion Notification: Not ECN-Capable Transport (0)
    Total Length: 78
    Identification: 0x032d (813)
    Flags: 0x0000
        0... .... .... .... = Reserved bit: Not set
        .0.. .... .... .... = Don't fragment: Not set
        ..0. .... .... .... = More fragments: Not set
        ...0 0000 0000 0000 = Fragment offset: 0
    Time to live: 128
    Protocol: UDP (17)
    Header checksum: 0xb2bc [validation disabled]
    [Header checksum status: Unverified]
    Source: 192.168.1.102
    Destination: 192.168.1.255
User Datagram Protocol, Src Port: 137, Dst Port: 137
    Source Port: 137
    Destination Port: 137
    Length: 58
    Checksum: 0x6608 [unverified]
    [Checksum Status: Unverified]
    [Stream index: 8]
NetBIOS Name Service
    Transaction ID: 0x932d
    Flags: 0x0110, Opcode: Name query, Recursion desired, Broadcast
        0... .... .... .... = Response: Message is a query
        .000 0... .... .... = Opcode: Name query (0)
        .... ..0. .... .... = Truncated: Message is not truncated
        .... ...1 .... .... = Recursion desired: Do query recursively
        .... .... ...1 .... = Broadcast: Broadcast packet
    Questions: 1
    Answer RRs: 0
    Authority RRs: 0
    Additional RRs: 0
    Queries
        WORKGROUP<1b>: type NB, class IN
            Name: WORKGROUP<1b> (Domain Master Browser)
            Type: NB (32)
            Class: IN (1)
No.      Time                              Source                Destination           Protocol Length Info
     72 2003-09-23 13:40:14.017174    192.168.1.102         192.168.1.104         SNMP     92      get-request
1.3.6.1.4.1.11.2.3.9.4.2.1.2.2.2.1.0
```

```
Frame 72: 92 bytes on wire (736 bits), 92 bytes captured (736 bits)
    Encapsulation type: Ethernet (1)
    Arrival Time: Sep 23, 2003 13:40:14.017174000 中国标准时间
    [Time shift for this packet: 0.000000000 seconds]
    Epoch Time: 1064295614.017174000 seconds
    [Time delta from previous captured frame: 1.764895000 seconds]
    [Time delta from previous displayed frame: 1.764895000 seconds]
    [Time since reference or first frame: 21.120381000 seconds]
    Frame Number: 72
    Frame Length: 92 bytes (736 bits)
    Capture Length: 92 bytes (736 bits)
    [Frame is marked: False]
    [Frame is ignored: False]
    [Protocols in frame: eth:ethertype:ip:udp:snmp]
    [Coloring Rule Name: UDP]
    [Coloring Rule String: udp]
Ethernet II, Src: Dell_4f:36:23 (00:08:74:4f:36:23), Dst: HewlettP_61:eb:ed (00:30:c1:61:eb:ed)
    Destination: HewlettP_61:eb:ed (00:30:c1:61:eb:ed)
        Address: HewlettP_61:eb:ed (00:30:c1:61:eb:ed)
        .... ..0. .... .... .... .... = LG bit: Globally unique address (factory default)
        .... ...0 .... .... .... .... = IG bit: Individual address (unicast)
    Source: Dell_4f:36:23 (00:08:74:4f:36:23)
        Address: Dell_4f:36:23 (00:08:74:4f:36:23)
        .... ..0. .... .... .... .... = LG bit: Globally unique address (factory default)
        .... ...0 .... .... .... .... = IG bit: Individual address (unicast)
    Type: IPv4 (0x0800)
Internet Protocol Version 4, Src: 192.168.1.102, Dst: 192.168.1.104
    0100 .... = Version: 4
    .... 0101 = Header Length: 20 bytes (5)
    Differentiated Services Field: 0x00 (DSCP: CS0, ECN: Not-ECT)
        0000 00.. = Differentiated Services Codepoint: Default (0)
        .... ..00 = Explicit Congestion Notification: Not ECN-Capable Transport (0)
    Total Length: 78
    Identification: 0x032e (814)
    Flags: 0x0000
        0... .... .... .... = Reserved bit: Not set
        .0.. .... .... .... = Don't fragment: Not set
        ..0. .... .... .... = More fragments: Not set
        ...0 0000 0000 0000 = Fragment offset: 0
    Time to live: 128
    Protocol: UDP (17)
    Header checksum: 0x0000 [validation disabled]
    [Header checksum status: Unverified]
    Source: 192.168.1.102
    Destination: 192.168.1.104
User Datagram Protocol, Src Port: 4343, Dst Port: 161
    Source Port: 4343
    Destination Port: 161
    Length: 58
    Checksum: 0x5eef [unverified]
    [Checksum Status: Unverified]
    [Stream index: 10]
Simple Network Management Protocol
    version: version-1 (0)
    community: public
    data: get-request (0)
        get-request
            request-id: 6402
            error-status: noError (0)
            error-index: 0
            variable-bindings: 1 item
                1.3.6.1.4.1.11.2.3.9.4.2.1.2.2.2.1.0: Value (Null)
                    Object Name: 1.3.6.1.4.1.11.2.3.9.4.2.1.2.2.2.1.0 (iso.3.6.1.4.1.11.2.3.9.4.2.1.2.2.2.1.0)
                    Value (Null)
No.     Time                         Source              Destination            Protocol Length Info
    73 2003-09-23 13:40:14.034659    192.168.1.104       192.168.1.102          SNMP     93     get-response
1.3.6.1.4.1.11.2.3.9.4.2.1.2.2.2.1.0
Frame 73: 93 bytes on wire (744 bits), 93 bytes captured (744 bits)
    Encapsulation type: Ethernet (1)
    Arrival Time: Sep 23, 2003 13:40:14.034659000 中国标准时间
    [Time shift for this packet: 0.000000000 seconds]
    Epoch Time: 1064295614.034659000 seconds
    [Time delta from previous captured frame: 0.017485000 seconds]
    [Time delta from previous displayed frame: 0.017485000 seconds]
    [Time since reference or first frame: 21.137866000 seconds]
    Frame Number: 73
    Frame Length: 93 bytes (744 bits)
```

```
        Capture Length: 93 bytes (744 bits)
        [Frame is marked: False]
        [Frame is ignored: False]
        [Protocols in frame: eth:ethertype:ip:udp:snmp]
        [Coloring Rule Name: UDP]
        [Coloring Rule String: udp]
Ethernet II, Src: HewlettP_61:eb:ed (00:30:c1:61:eb:ed), Dst: Dell_4f:36:23 (00:08:74:4f:36:23)
    Destination: Dell_4f:36:23 (00:08:74:4f:36:23)
        Address: Dell_4f:36:23 (00:08:74:4f:36:23)
        .... ..0. .... .... .... .... = LG bit: Globally unique address (factory default)
        .... ...0 .... .... .... .... = IG bit: Individual address (unicast)
    Source: HewlettP_61:eb:ed (00:30:c1:61:eb:ed)
        Address: HewlettP_61:eb:ed (00:30:c1:61:eb:ed)
        .... ..0. .... .... .... .... = LG bit: Globally unique address (factory default)
        .... ...0 .... .... .... .... = IG bit: Individual address (unicast)
    Type: IPv4 (0x0800)
Internet Protocol Version 4, Src: 192.168.1.104, Dst: 192.168.1.102
    0100 .... = Version: 4
    .... 0101 = Header Length: 20 bytes (5)
    Differentiated Services Field: 0x00 (DSCP: CS0, ECN: Not-ECT)
        0000 00.. = Differentiated Services Codepoint: Default (0)
        .... ..00 = Explicit Congestion Notification: Not ECN-Capable Transport (0)
    Total Length: 79
    Identification: 0xeda9 (60841)
    Flags: 0x0000
        0... .... .... .... = Reserved bit: Not set
        .0.. .... .... .... = Don't fragment: Not set
        ..0. .... .... .... = More fragments: Not set
        ...0 0000 0000 0000 = Fragment offset: 0
    Time to live: 60
    Protocol: UDP (17)
    Header checksum: 0x0cd6 [validation disabled]
    [Header checksum status: Unverified]
    Source: 192.168.1.104
    Destination: 192.168.1.102
User Datagram Protocol, Src Port: 161, Dst Port: 4343
    Source Port: 161
    Destination Port: 4343
    Length: 59
    Checksum: 0x4ce9 [unverified]
    [Checksum Status: Unverified]
    [Stream index: 10]
Simple Network Management Protocol
    version: version-1 (0)
    community: public
    data: get-response (2)
        get-response
            request-id: 6402
            error-status: noError (0)
            error-index: 0
            variable-bindings: 1 item
                1.3.6.1.4.1.11.2.3.9.4.2.1.2.2.2.1.0: 10
                    Object Name: 1.3.6.1.4.1.11.2.3.9.4.2.1.2.2.2.1.0 (iso.3.6.1.4.1.11.2.3.9.4.2.1.2.2.2.1.0)
                    Value (OctetString): 10
```