4. Day Time Running Light System

A: WIRING DIAGRAM

Refer to "Headlight System" in the wiring diagram. <Ref. to WI-253, WIRING DIAGRAM, Headlight System.>

B: INSPECTION

1. DAYTIME RUNNING LIGHT SYSTEM CHECK

	Step	Check	Yes	No
1	CHECK BODY INTEGRATED UNIT. Read the DTC using Subaru Select Monitor. NOTE: For detailed procedures, refer to "PC application help for Subaru Select Monitor".	Is DTC displayed?	Perform the diagnosis according to DTC.	Go to step 2.
2	CHECK CURRENT DATA. Display the following items using Subaru Select Monitor. • «Parking Brake Switch Input» • «Shift position» • «Lighting II Switch Input»	Is the input signal normal?	Go to step 3.	Check the defective part.
3	CHECK RELAY. Check the daytime running light relay. <ref. and="" check="" fuse.="" inspection,="" li-5,="" relay="" relay,="" to=""></ref.>	Is the relay OK?	Go to step 4.	Replace the relay.
4	CHECK HARNESS. Check each harness.	Is harness normal?	Replace the body integrated unit. <ref. sl-78,<br="" to="">REMOVAL, Body Integrated Unit.></ref.>	Repair or replace the harness.

C: NOTE

For operation procedures of each component of the daytime running light system, refer to the respective section.

- Headlight Assembly: <Ref. to LI-23, Headlight Assembly.>
- Headlight bulb: <Ref. to LI-29, Headlight Bulb.>
- Combination switch (light): <Ref. to LI-18, Combination Switch (Light).>
- Daytime running resistor: <Ref. to LI-76, Day Time Running Resistor.>