

# Atmosphere Pro



## White Paper

V 1.0.1 @ December 2014

@Copyrights 2014 Async-IO.org

<b>Atmosphere Satellite .....</b>	<b>2</b>
How to install Satellite .....	3
Configuring Hazelcast.....	4
How replication works.....	4
AtmosphereResource Replication .....	6
AtmosphereResource Retrieval .....	7
Message Replication.....	8
Failing to deliver a message.....	9
<b>Atmosphere Tower Control.....</b>	<b>10</b>
Installing Tower Control .....	10
Starting Tower Control .....	11
<i>io.async.control.AsyncSupport</i> .....	13
<i>io.async.control.AtmosphereFramework</i> .....	14
<i>io.async.control.broadcaster</i> .....	15
<i>io.async.control.cache</i> .....	15
<i>io.async.control.config</i> .....	16
<i>io.async.control.factory</i> .....	16
<i>io.async.control.interceptors</i> .....	17
<i>io.async.control.resource</i> .....	17
<i>io.async.control.statistics</i> .....	18
<i>io.async.control.websocket</i> .....	18
<b>Atmosphere Postman .....</b>	<b>19</b>
How to install Postman.....	19
Installing the client side.....	20
<i>Callbacks</i> .....	20
<i>How it works</i> .....	20


## Atmosphere Satellite

Applications using Atmosphere Satellite gain the following superpowers:

- Elastic Scalability (just add more servers and they cluster auto magically, i.e. automatically)
- Super Speeds (in memory transaction speeds)
- High Availability
- Fault Tolerance
- Cloud Readiness
- 100% State Replication of AtmosphereResource, Broadcaster and BroadcasterCache
- Powered by Hazelcast 3.x ([www.hazelcast.org](http://www.hazelcast.org)): An In-Memory Data Grid

Atmosphere Satellite is easily able to handle this type of use case with in-memory performance, linear scalability as you add new nodes and reliability.

Satellite is small and gets transparently enabled by Atmosphere. Because of its design approach as well as Satellite's ability to automatically discover and cluster with peers, Satellite provides drop-in session clustering ability for any Atmosphere enabled server. It requires no additional investment in hardware and elastically scales as you add Atmosphere's application. This is a great way to ensure that Atmosphere's session state is maintained when you are clustering Atmosphere servers.



## How to install Satellite

To install Satellite, all you need to do is to add the following dependency in your pom.xml:

```
<dependency>

    <groupId>io.async</groupId>

    <artifactId>atmosphere-satellite</artifactId>

    <version>1.x</version>

</dependency>
```

Atmosphere will auto-detect the jar and will install Satellite automatically. Once installed, you should see in your log:

```
Sep 12, 2014 11:02:17 AM com.hazelcast.cluster.MulticastJoiner
INFO: [10.0.1.4]:5701 [dev]
Members [1] {
    Member [10.0.1.4]:5701 this
}

Sep 12, 2014 11:02:17 AM com.hazelcast.core.LifecycleService
INFO: [10.0.1.4]:5701 [dev] Address[10.0.1.4]:5701 is STARTED
11:02:17.098 INFO [main] i.a.s.Satellite [Satellite.java:81]
    Atmosphere Satellite e6ba40a1-29ab-493c-9295-30bcc7a2aaea
11:02:17.106 INFO [main] o.a.c.AtmosphereFramework [AtmosphereFramework.java:1906]
Auto detecting WebSocketHandler in /WEB-INF/classes/
```

When another Atmosphere Satellite instance is getting installed, the log for the first installation will show

```
Sep 12, 2014 11:14:31 AM com.hazelcast.cluster.ClusterService
INFO: [10.0.1.4]:5701 [dev]
Members [2] {
    Member [10.0.1.4]:5701 this
    Member [10.0.1.4]:5702
}
}
```

Addition and removal of Atmosphere Satellite are dynamic and will always be reflected in the log of each Atmosphere Satellite installation. You can also browse Satellite's MBeans using your favorite JMX client under the 'io.async.satellite' package.

### Configuring Hazelcast

You can configure Hazelcast by following the normal way, as recommended by the Hazelcast team

<http://hazelcast.org/docs/latest/manual/html/config.html>

By default, a Hazelcast instance named "AtmosphereSatellite" will be created. If your application already use a HazelcastInstance or want to create a new instance with a different name, just define in web/atmosphere.xml:

```
<init-param>

  <param-name>io.async.satellite.HazelcastSatelliteTransport.instanceName</ param-name >

  < param-value > <<name>> </ param-value >

</init-param>
```

If the HazelcastInstance name exists, it will be picked and if not, created. It is strongly recommended to configure Hazelcast instance via **hazelcast.xml**

### How replication works


A Satellite always publishes its state at the moment it changes. Changing states includes:

- **Broadcaster:** when a Broadcaster is created by one Satellite, a message will be sent to all others Satellites, asking them to create the Broadcaster. Hence all available Satellites will have the same set of created Broadcasters. The same will happen when a Broadcaster is destroyed from one of the Satellite, e.g. the removal will also be execute by all Atmosphere Satellite.
- **AtmosphereResource:** when an AtmosphereResource is created (when a users/browsers connects), a message will be sent to all others Satellites, asking them to register the AtmosphereResource's UUID with its associated broadcaster. When an AtmosphereResource gets registered with a Broadcaster, the AtmosphereResource becomes candidate for message caching. The same will happens when an AtmosphereResource gets removed.
- **BroadcasterCache:** BroadcasterCache are tightly coupled with Broadcaster. Hence, BroadcasterCache are getting created everytime a Broadcaster is. Every time a new AtmosphereResource is added to a Broadcaster, a message will be sent to all others Satellites, and the AtmosphereResource's UUID will be added to the list of active BroadcasterCache's.

## Broadcaster Replication

As noted, Broadcaster are getting replicated by following:


1. In a Satellite, a Broadcaster is getting created (#1)
2. The Satellite send a message to other Satellites (#2)
3. The Broadcaster is created in the other Satellite (#3)



### AtmosphereResource Replication

When a user/browser connect, an AtmosphereResource is always created. With Satellite, the UUID of that AtmosphereResource will be shared amongst the Satellites:

1. Browser connects
2. AtmosphereResource gets created
3. The Atmosphere's UUID is sent to all Satellites
4. The UUID is registered with BroadcasterCache. Registering UUID with BroadcasterCache means message will be cached for that resource unless once of the Satellite successfully deliver the message.



## AtmosphereResource Retrieval

It is possible to retrieve an AtmosphereResource located on another node by using the *AtmosphereResourceFactory.locate(uuid, Async)* API. Under the hood class *AtmosphereResourceFactory* will communicate with the remote Satellites and create a local “stub” for the remote AtmosphereResource if located.

```
factory.locate(message.getMessage(), new AtmosphereResourceFactory.Async() {  
    @Override  
    public void available(AtmosphereResource r) {  
        // Do something with the resource  
        r.write( "Hello World" );  
    }  
});
```

The operation of locating an AtmosphereResource is asynchronous, and it is left to the application developer to block in case the retrieval must be done synchronously:


```
final AtomicReference<AtmosphereResource> resource  
    = new AtomicReference<AtmosphereResource>();  
final CountDownLatch latch = new CountDownLatch(1);  
  
factory.locate(message.getMessage(), new AtmosphereResourceFactory.Async() {  
    @Override  
    public void available(AtmosphereResource r) {  
        resource.set(r);  
        latch.countDown();  
    }  
});  
latch.await();  
  
AtmosphereResource stub = resource.get();  
stub.write("Hello World");
```



## Message Replication


When a message is broadcasted in one Satellite, the message will be sent to all Satellites, which in turn will broadcast to their set of AtmosphereResources and cached for AtmosphereResource not located on that Satellite.

As soon as the message is successfully delivered in one Satellite, the information will be sent to all other Satellites so they can remove the message from their BroadcasterCache.



### Failing to deliver a message

If, for any reason the message is not delivered to the AtmosphereResource, the message will stay in all Satellite's BroadcasterCache so when the browser reconnects using its previous AtmosphereResource's UUID, the message will be pulled from the cache and send. Then all Satellites will be advised the message has been delivered and



## Atmosphere Tower Control

Atmosphere Tower Control is designed with ease of use and flexibility in mind and delivers unprecedented power to Atmosphere's Developers. Atmosphere Tower Control is a complete ecosystem for developers, offering a complete end to end solution for monitoring and debugging an Atmosphere application.

Tower Control offers the ability to completely configure Atmosphere, collect statistics, reload Atmosphere applications and hot swap an Atmosphere applications remotely.

### Installing Tower Control

To install Satellite, all you need to do is to add the following dependency in your pom.xml:

```
<dependency>
  <groupId>io.async</groupId>
  <artifactId>atmosphere-tower-control</artifactId>
  <version>1.x</version>
</dependency>
```

Atmosphere will auto-detect the jar and will install Tower Control automatically. Once installed, you should see in your log:

```
11:56:17.411 INFO [main] o.a.c.AnnotationHandler [AnnotationHandler.java:63] Found
Annotation in class io.async.control.TowerControlInterceptor being scanned: interface
org.atmosphere.config.service.AtmosphereInterceptorService
```

```
11:56:17.537 INFO [main] i.a.c.TowerControlInterceptor [TowerControlInterceptor.java:58]
```


*Atmosphere Tower Control*

```
11:56:17.538 INFO [main] o.a.c.AnnotationHandler [AnnotationHandler.java:63] Found
Annotation in class io.async.control.TowerControlListener being scanned: interface
org.atmosphere.config.service.BroadcasterListenerService
```

## Starting Tower Control


To start Tower Control, all you need to have is a tool supporting JMX. For example, both Java Mission Control(JMC) and jVisualVM supports JMX. Let's assume we will use JMC. To start JMC, just do:

```
% jmc
```



Next, select under the JVM Browser Tab, select the Java process, which started your Atmosphere Application. On the right side, select the MBean Tab. You should see

To make things simpler, type `io.async` in the Filter field, so we just see Tower Control Beans



All the Atmosphere's MBeans are grouped by type:

- **io.async.control:** Contains information about installed AsyncSupport and AtmosphereFramework classes.
- **io.async.control.broadcaster:** The current set of created Broadcaster with their associated state.
- **io.async.control.cache:** The current set of created BroadcasterCache with their associated state.
- **io.async.control.factory:** The BroadcasterFactory, AtmosphereResourceFactory and WebSocketProcessorFactory with their associated state.
- **io.async.control.interceptors:** The current set of installed AtmosphereInterceptor with their associated state.
- **io.async.control.resource:** The current set of connected clients, represented by their AtmosphereResource.
- **io.async.statistics:** Live statistic like number of connections, messages, transport used as well as Browser's used.
- **io.async.control.websocket:** Contains information about installed WebSocketProcessor

Let's explore them one by one and see what kind of information is available from those beans.


## `io.async.control.AsyncSupport`

### Attributes

Contains information about the server used and if websocket is supported or not.

### Operations:

No operation available



## Attributes

Contains information about how Atmosphere has been started and configured. Everything configured by default or via web/application.xml is getting reflected.

Operations:

You can reconfigure the AtmosphereFramework via the MBean's operations. For example, you can add `BroadcasterListener`, `init-params` etc. and then click on `reload` to reconfigure the AtmosphereFramework.

**MBean Tree**

Filter:

- io.async.control
- io.async.control.AsyncSupport
- io.async.control.Atmosphere
- io.async.control.broadcaster
- io.async.control.cache
- io.async.control.config
- io.async.control.configng
- io.async.control.interceptors
- io.async.control.resource
- io.async.control.statistics
- io.async.control.websocket

**MBean Features**

Attributes | Operations | Notifications | Metadata

Name	Value
AllowAllClassesScan	true
AnnotationPackages	java.util.LinkedList, size 1
AnnotationProcessor	org.atmosphere.cpr.DefaultAnnotationProcessor
AnnotationTypes	java.util.ArrayList, size 4
AsyncSupport	org.atmosphere.container.Jetty9AsyncSupportWithWebSocket
AsyncSupportListeners	java.util.ArrayList, size 1
AtmosphereDoXmlPath	/META-INF/atmosphere.xml
AtmosphereHandlers	java.util.HashMap, size 1
AtmosphereObjectFactory	org.atmosphere.cpr.AtmosphereFramework\$DefaultAtmosphereObjectFactory
BroadcasterCacheClassName	org.atmosphere.cache.UUIDBroadcasterCache
BroadcasterCacheListeners	java.util.ArrayList, size 0
BroadcasterCacheListener	java.util.ArrayList, size 0
BroadcasterClassName	org.atmosphere.cpr.DefaultBroadcaster
BroadcasterFactoryClassName	org.atmosphere.cpr.DefaultBroadcasterFactory
BroadcasterFilters	java.util.ArrayList, size 0
BroadcasterLifeCyclePolicy	NEVER
BroadcasterListeners	java.util.ArrayList, size 1
BroadcasterMappedToAtmosphereHandlers	java.util.HashMap, size 1
BroadcasterTypes	java.util.concurrent.ConcurrentLinkedQueue, size 7
DefaultInterceptors	java.util.ArrayList, size 11
EndpointMapper	org.atmosphere.util.DefaultEndpointMapper
ExcludedInterceptors	java.util.ArrayList, size 0
ExternalizeDestroy	false
FilterManipulators	java.util.ArrayList, size 1
HandlerClassPath	/WEB-INF/classes/
InitParams	java.util.HashMap, size 4
InterceptorMappedToAtmosphereHandlers	java.util.HashMap, size 1
Interceptors	java.util.ArrayList, size 14
IsAServletFilter	false
LibraryClassPath	/WEB-INF/lib/
MappingRegex	[a-zA-Z0-9-.*~@;\\?]+
ObjectFactoryType	java.util.concurrent.ConcurrentLinkedQueue, size 3
SharedThreadPools	true
UseBlockingImplementation	false
UseNativeImplementation	false
UseServlet30	true
UseStreamForFlushingComments	true
WebSocketEnabled	true
WebSocketProcessorClassName	org.atmosphere.websocket.DefaultWebSocketProcessor
WebSocketProtocolClassName	org.atmosphere.websocket.protocol.SimpleHttpProtocol


## io.async.control.broadcaster

### Attributes

Contains information about the current state of a Broadcaster. For example, the AtmosphereResource, the number of them, the installed BroadcasterListener, etc.

### Operations:

Several operations are available, like adding, on the fly, AtmosphereResource, broadcasting messages, resuming AtmosphereResources etc.



Name	Value
AtmosphereResourceCount	1
AtmosphereResources	java.util.ArrayList, size 1
BroadcasterListeners	java.util.ArrayList, size 2
destroyed	false
/chat	/chat
LifeCycleListeners	java.util.ArrayList, size 0
LifeCyclePolicy	NEVER
Messages	java.util.ArrayList, size 0
OutOfOrderBroadcastSupported	false
Policy	FIFO
Scope	APPLICATION
WriteQueues	java.util.concurrent.ConcurrentHashMap, size 0


## io.async.control.cache

### Attributes

Contains information about the current state of the BroadcasterCache like active AtmosphereResource, installed listeners etc.

### Operations:

Message can be added,excluded or deleted from the cache



Name	Value
ActiveClients	java.util.concurrent.ConcurrentHashMap, size 1
63422b69-c619-415b-ae09-58be3d2a3f74	1410280193577
BroadcasterCacheInspectors	java.util.ArrayList, size 0
BroadcasterCacheListeners	java.util.ArrayList, size 0
Messages	java.util.HashMap, size 0




## io.async.control.config

### Attributes

Contains information about the BroadcasterConfig likes Thread, Thread Pool, etc.

### Operations:

You can destroy or remove BroadcastFilter



The screenshot shows the JBoss JMX console. On the left, the 'MBean Tree' is filtered to 'io.async'. The 'io.async.control.config' MBean is selected. On the right, the 'MBean Features' tab is active, showing a table of attributes.

Name	Value
AsyncWriteServiceSize	20
BroadcastFilters	java.util.ArrayList, size 0
ExecutorServiceSize	0
HandleExecutors	false
ScheduledExecutorServiceSize	8


## io.async.control.factory

### Attributes

Contains information about the number of AtmosphereResource, Broadcaster and WebSocketProcessor

### Operations:

You add find AtmosphereResource based on their UUID



The screenshot shows the JBoss JMX console. On the left, the 'MBean Tree' is filtered to 'io.async'. The 'io.async.control.factory' MBean is selected. On the right, the 'MBean Features' tab is active, showing a table of attributes.

Name	Value
AtmosphereResources	java.util.ArrayList, size 1
[0]	63422b69-c619-415b-ae09-58be3d2a3f74
Count	1

## io.async.control.interceptors

### Attributes

Contains information about the installed AtmosphereInterceptors

### Operations:

For example, you can configure on the fly the SuspendTrackerInterceptor.

The screenshot shows the JBoss MBean console. On the left, the 'MBean Tree' lists various system MBeans. The 'io.async.control.interceptors' MBean is selected. On the right, the 'MBean Features' tab is active, showing the 'Operations' section. The operations listed are: addTrackedUUID : void, clear : void, and removeTrackedUUID : void. The 'Name', 'Value', and 'Description' columns are empty.

## io.async.control.resource

### Attributes

The list of current connected users, or AtmosphereResource.

### Operations:

You can close and or resume an existing AtmosphereResource

The screenshot shows the JBoss MBean console. On the left, the 'MBean Tree' lists various system MBeans. The 'io.async.control.resource' MBean is selected. On the right, the 'MBean Features' tab is active, showing the 'Attributes' section. The attributes listed are: AsyncWriter (java.util.ArrayList, size 2), AtmosphereHandler (org.atmosphere.config.managed.ManagedAtmosphereHandler), Attributes (java.util.HashMap, size 21), Broadcaster (/chat), Cancelled (false), Headers (java.util.HashMap, size 17), Listeners (java.util.ArrayList, size 5), QueryString, RequestDestroyed (false), ResponseDestroyed (false), Resumed (false), Serializer, Suspended (true), Transport (WEBSOCKET), UserAgent (Mozilla/5.0 (Macintosh; Intel Mac OS X 10\_9\_4) AppleWebKit/537.36 (KHTML, like Gecko) Chrome/37.4204388c-0df6-403d-92d5-519538001129), and Uuid (4204388c-0df6-403d-92d5-519538001129). The 'Update' column is empty.


## io.async.control.statistics

### Attributes

Collect statistics about the current number of connections, disconnected count, total received messages etc.

### Operations:

Enable/Disable statistics collection.



Name	Value
CapturingStatsOn	true
CleanDisconnect	0
CloseCount	0
DirtyDisconnect	0
JsonpCount	0
LongPollingCount	0
PollingMessageCount	0
SseCount	0
StreamingCount	0
TotalJsonpCount	0
TotalLongPollingCount	0
TotalMessageCount	1
TotalSseCount	0
TotalStreamingCount	0
TotalWebSocketCount	1
WebSocketCount	1
WebSocketMessageCount	14


## io.async.control.websocket

### Attributes

Information about how websockets are installed and configured

### Operations:

None



Name	Value	Update I
ByteBufferSize	2097152	Default
CharBufferSize	2097152	Default
ClosingTime	0	Default
Destroyable	false	Default
ExecuteAsync	false	Default
Mapper	org.atmosphere.util.DefaultEndpointMapper	Default
WebSocketHandlers	java.util.HashMap, size 0	Default
WildcardMapping	false	Default

## Atmosphere Postman

With Guaranteed Delivery, the Atmosphere Postman system uses a built-in data store to persist messages. Atmosphere Postman guarantees the client that when sending a message; the message will always be delivered to the server. In case of a failure, the message will be re-sent until it reaches the server. Postman guarantee client's messages delivery.

When combined with Atmosphere Satellite, when a websocket or fallback transport delivers a message, the send operation does not complete successfully until the message is safely stored in the sender's data store. Subsequently, the message is not deleted from one data store until it is successfully forwarded to and stored in the next data store. As a result, once a websocket or fallback transport successfully sends a message, it is also stored in memory on at least one Atmosphere Satellite until the message has been successfully delivered and acknowledged by the browser. **Installing Satellite and Postman guarantee 100% messages delivery, both from the browser and the server.**

### How to install Postman

To install Satellite, all you need to do is to add the following dependency in your pom.xml:

```
<dependency>
  <groupId>io.async</groupId>
  <artifactId>atmosphere-postman</artifactId>
  <version>1.0.0</version>
</dependency>
```

Atmosphere will auto-detect the jar and will install Tower Control automatically. Once installed, you should see in your log:

```
17:23:33.409 INFO [main] i.a.p.ClientAckInterceptor [ClientAckInterceptor.java:46]
    Atmosphere Postman : io.async.postman.ClientAckInterceptor

17:23:33.409 INFO [main] o.a.c.AtmosphereFramework [AtmosphereFramework.java:2362]
    Installed AtmosphereInterceptor io.async.postman.ClientAckInterceptor with priority
    AFTER_DEFAULT

17:23:33.409 INFO [main] i.a.p.ReloadAckInterceptor [ReloadAckInterceptor.java:64]
    Atmosphere Postman : io.async.postman.ReloadAckInterceptor
```

## Installing the client side

Client side, you need to add to you application's main page

```
<script type="text/javascript" language="javascript" src="atmosphere.js"></script>
<script type="text/javascript" language="javascript" src="atmosphere.postman.js"></script>
```

## Callbacks

You can trace and react using two client's side function

```
atmosphere.onAckSuccess = function(res) {
    console.log("onAckSuccess");
    console.log(res);
};

atmosphere.onAckFailed = function(req) {
    console.log("onAckFailed");
    console.log(req);
};
```

## How it works

If atmosphere.postman.js is loaded in client and ClientAckInterceptor is included in interceptor stack in server, when you sends a message using the `push` method, the followings will happen:

1. A JSON consisting of 'id' and 'message' is created and sent instead of the message.
2. At the same time, the timer handling ACK is set in client.
  - 3.1 If server receives it,
    - 4.1. ClientAckInterceptor parses that JSON, restore the message and send the ACK using the id.
    - 4.2. If the ACK is arrived in client, atmosphere.onAckSuccess will be executed with AtmosphereResponse.
  - 3.1 If server can't receive it,
    - 5.1 After AtmosphereRequest.ackInterval in ms or 5 seconds if it's not set, atmosphere.onAckFailed will be executed with AtmosphereRequest.
    - 5.2 At the same time, the original message is sent again then the situation goes to step 1.