Data Compression
Fall 2022
Part 3-Lecture 3
JPEG

Dr. Mona Soliman

IT Dept.

JPEG


JPEG Compression
Color Transform
Down-sampling
Forward DCT
Quantization
Encoding
JPEG-Compressed Image Data
Decoding
De-quantization
Inverse DCT
Up-sampling
Color Transform
Raw Image Data
JPEG Decompression

4-JPEG: ENCODING

1. DC encoding
2. ZigZag order
3. AC encoding

DC TERM OF DCT COEFFICIENTS

- The first element in each transformed block is the DC coefficient Term
- DC term is a measure of the average of spatial block values (e.g luminance)
- The changes in DC coefficients values of consecutive blocks is small
- The DC coefficients are coded separately from the AC ones.
- ***Differential encoding*** (DPCM) is applied on all DC coefficients

DIFFERENTIAL ENCODING OF DC TERMS



ZIGZAG SCAN OF DCT COEFFICIENTS

0	1	5	6	14	15	27	28
2	4	7	13	16	26	29	42
3	8	12	17	25	30	41	43
9	11	18	24	31	40	44	53
10	19	23	32	39	45	52	54
20	22	33	38	46	51	55	60
21	34	37	47	50	56	59	61
35	36	48	49	57	58	62	63

- Transform Coefficients
  - DC coefficient
  - AC coefficients



The DC coefficient and lower-frequency AC coefficients, both horizontal and vertical, are scanned first

HOW TO READ ZIGZAG ORDER?? EXAMPLE

ENCODING OF AC COEFFICIENTS

- The remaining 63 values in the vector are the AC coefficients

- Run Lenght Coding (RLE) followed by Entrpy Coding “Huffman” is applied on the AC coefficients.

- In RLE, AC coefficients are divided into pairs; each pair is made up of (*skip, value*) where skip is the number of zeros in the run and value is the next Non-Zero Value.

  {#-zeros-to-skip , next non-zero value}.

Encoding of AC Coefficients "Steps"

1. Read AC coefficients in Zigzag order
2. Apply Run Length Code (*Use category number from category table not number it self*)
3. Apply Huffman coding on output of Run Length Code
4. Coding using Huffman code and additional bits

RLE, CATEGORIES TABLE

Note: ***MSB of -ive "Additional Bits" is "0"***
MSB of +ive "additional Bits" is "1"



Category	AC coefficient values	Additional Bits
1	-1,1	0,1
2	-3,-2,2,3	00,01,10,11
3	-7...-4,4...7	000,001,010,011,100,101,110,111
4	15...-8,8...15	0000,0001,0010, 0011,.....
5	-31...-16,16...31	
6	-63...-32,32...63	
7	-127...-33,33...127	
8	-255...-128,128...255	
9	-511...-256,256...511	
10	-1023...-512,512...1023	

RLE- HUFFMAN ENCODING FOR JPEG

Example:

-2,0,0,2,0,0,3,2,0,1,0,0,-2,0,-1,0,0,1,0,0,-1,000000000.....0000

Apply RLE

Category number
Not number itself

-2,	0,0,2,	0,0,3,	2,	0,1,	0,0,-2,	0,-1,	0,0,1,	0,0,-1,	EOB
0/2	2/2	2/2	0/2	1/1	2/2	1/1	2/1	2/1	EOB

Apply Huffman on Descriptors

P(2/2)=3	P(2/2)=3	P(0/2, 2/1)=4	P(1/1,EOB,2/2)=6
P(0/2)=2	P(1/1,EOB)=3	P(2/2)=3	P(0/2,2/1)=4
P(2/1)=2	P(0/2)=2	P(1/1,EOB)=3	
P(1/1)=2	P(2/1)=2		
P(EOB)=1			

1
0
01
00
1
10
01
010
11
011

RLE- HUFFMAN ENCODING FOR JPEG

Encoding

Huffman Table

0/2	10
1/1	010
2/1	11
2/2	00
EOB	011



Compressed Size =37 Bits

RLE- HUFFMAN ENCODING FOR JPEG

Decoding



COMPRESSED/DECOMPRESSED IMAGE

Figure 2 – Peppers



Figure 3 – DCT of Peppers



Figure 4 – Quantized DCT of Peppers

Figure 6 – Quality 50 – 84% Zeros

Figure 7 – Quality 20 – 91% Zeros

Figure 8 – Quality 10 – 94% Zeros

JPEG ENCODING



The Encoder model of JPEG compression standard

JPEG DECODING