

# **Ontologies and the Semantic Web**

The Story So Far

# Semantic Web



THE  
SEMANTIC  
WEB

# Semantic Web

- According to **W3C**
  - “an evolving extension of the World Wide Web in which web content can be ... read and used by software agents, thus permitting them to find, share and integrate information more easily”
- Data will use uniform syntactic structure (**RDF**)
- **Ontologies** will provide
  - Schemas for data
  - Vocabulary for annotations
- Ultimate goal is to transform web into a platform for distributed applications and sharing (linking) of data

# What is an Ontology?

What is an Ontology?


# What is an Ontology?

A model of (some aspect of) the world

# What is an Ontology?

A model of (some aspect of) the world


- Introduces **vocabulary** relevant to domain, e.g.:
  - Anatomy



# What is an Ontology?

A model of (some aspect of) the world

- Introduces **vocabulary** relevant to domain, e.g.:
  - Anatomy
  - Cellular biology






# What is an Ontology?

A model of (some aspect of) the world

- Introduces **vocabulary** relevant to domain, e.g.:
  - Anatomy
  - Cellular biology
  - Aerospace






# What is an Ontology?

A model of (some aspect of) the world

- Introduces **vocabulary** relevant to domain, e.g.:

- Anatomy
- Cellular biology
- Aerospace
- Dogs



# What is an Ontology?

A model of (some aspect of) the world

- Introduces **vocabulary** relevant to domain, e.g.:

- Anatomy
- Cellular biology
- Aerospace
- Dogs
- Hotdogs
- ...




# What is an Ontology?

A model of (some aspect of) the world

- Introduces **vocabulary** relevant to domain
- Specifies **meaning** (semantics) of terms

Heart **is a** muscular organ that  
**is part of** the circulatory system



# What is an Ontology?


A model of (some aspect of) the world

- Introduces **vocabulary** relevant to domain
- Specifies **meaning** (semantics) of terms

Heart **is a** muscular organ that  
**is part of** the circulatory system

- **Formalised** using suitable logic

$$\forall x. [\text{Heart}(x) \rightarrow \text{MuscularOrgan}(x) \wedge \\ \exists y. [\text{isPartOf}(x, y) \wedge \\ \text{CirculatorySystem}(y)]]$$



# Web Ontology Language OWL (2)

- **W3C** recommendation(s)
- Motivated by **Semantic Web** activity
  - Requirement for standardised “web ontology language”
- Supported by **tools and infrastructure**
  - APIs (e.g., OWL API, Thea, OWLink)
  - Development environments (e.g., Protégé, Swoop, TopBraid Composer, Neon)
  - Reasoners & Information Systems (e.g., Pellet, Racer, HermiT, Quonto, ...)
- Based on **Description Logics** (SHOIN / SROIQ)



# Description Logics (DLs)

- Fragments of **first order logic** designed for KR
- Desirable computational properties
  - **Decidable** (essential)
  - Low complexity (desirable)
- Succinct and **variable free syntax**

$$\forall x. [\text{Heart}(x) \rightarrow \text{MuscularOrgan}(x) \wedge \\ \exists y. [\text{isPartOf}(x, y) \wedge \\ \text{CirculatorySystem}(y)]]$$

$$\text{Heart} \sqsubseteq \text{MuscularOrgan} \sqcap \\ \exists \text{isPartOf}. \text{CirculatorySystem}$$

# Description Logics (DLs)

DL **Knowledge Base** (KB) consists of two parts:

- Ontology (aka **TBox**) axioms define terminology (schema)

$\text{Heart} \sqsubseteq \text{MuscularOrgan} \sqcap \exists \text{isPartOf}.\text{CirculatorySystem}$   
 $\text{HeartDisease} \equiv \text{Disease} \sqcap \exists \text{affects}.\text{Heart}$   
 $\text{VascularDisease} \equiv \text{Disease} \sqcap \exists \text{affects} . (\exists \text{isPartOf}.\text{CirculatorySystem})$

- Ground facts (aka **ABox**) use the terminology (data)

$\text{John} : \text{Patient} \sqcap \exists \text{suffersFrom}.\text{HeartDisease}$



# Why Care About Semantics?



# Why Care About Semantics?

Why should I care about semantics?



# Why Care About Semantics?

Why should I care about semantics?



# Why Care About Semantics?

Why should I care about semantics?

Well, from a philosophical POV, we need to specify the relationship between statements in the logic and the existential phenomena they describe.



# Why Care About Semantics?

Why should I care about semantics?

Well, from a philosophical POV, we need to specify the relationship between statements in the logic and the existential phenomena they describe.

That's OK, but I don't get paid for philosophy.



# Why Care About Semantics?

Why should I care about semantics?

Well, from a philosophical POV, we need to specify the relationship between statements in the logic and the existential phenomena they describe.


That's OK, but I don't get paid for philosophy.

From a practical POV, in order to specify and test (ontology-based) information systems we need to precisely define their intended behaviour



# What are Ontologies Good For?

- Coherent **user-centric view** of domain
  - Help identify and resolve disagreements
- Ontology-based **Information Systems**
  - View of data that is independent of logical/physical schema
  - Answers reflect schema & data, e.g.:  
“Patients suffering from Vascular Disease”



Now... *that* should clear up a few things around here




# What are Ontologies Good For?

Heart  $\sqsubseteq$  MuscularOrgan  $\sqcap$   
     $\exists$ isPartOf.CirculatorySystem  
HeartDisease  $\equiv$  Disease  $\sqcap$   
     $\exists$ affects.Heart  
VascularDisease  $\equiv$  Disease  $\sqcap$   
     $\exists$ affects.( $\exists$ isPartOf.CirculatorySystem)  
  
John : Patient  $\sqcap$   
     $\exists$ suffersFrom.HeartDisease

# What are Ontologies Good For?

- Coherent **user-centric view** of domain
  - Help identify and resolve disagreements
- Ontology-based **Information Systems**
  - View of data that is independent of logical/physical schema
  - Answers reflect schema & data, e.g.:
    - “Patients suffering from Vascular Disease”
  - Query expansion/navigation/refinement
  - Incomplete and semi-structured data
  - Integration of heterogeneous sources



Now... *that* should clear up a few things around here

# Information-Based Decisions

**Increasingly critical** in many areas:

- In Healthcare industry, e.g., selecting patients for screening
  - Too much screening harms patients and wastes money
  - Too little screening costs lives



# Information-Based Decisions

**Increasingly critical** in many areas:

- In Oil and Gas industry, e.g., selecting production parameters
  - Better quality information could add €1B/year net value to Statoil production
  - Poorer quality information and analysis costs €6M/weekend!



# Information-Based Decisions

**Increasingly critical** in many areas:

- In IT industry, e.g., facilitating tech support
  - SAP deals with 80,000 queries/month at a cost of approx. €16M
  - SAP estimate 50% of support staff time spent searching for relevant information



# Healthcare

- UK NHS **£10 billion** “Connecting for Health” IT programme
- Key component is **Care Records Service** (CRS)
  - “Live, interactive patient record service accessible 24/7”
  - Patient **data distributed** across local centres in 5 regional clusters, and a national DB
  - **SNOMED-CT** ontology provides common **vocabulary** for data
    - Clinical data uses terms drawn from this ontology
    - The ontology defines more than 400,000 different terms!

# What About Scalability?

- Only **useful in practice** if we can deal with large ontologies and/or large data sets
- Unfortunately, many ontology languages are highly intractable
  - OWL 2 satisfiability is **2NEXPTIME-complete** w.r.t. schema
  - and **NP-Hard** w.r.t. data (upper bound open)
- Problem addressed in practice by
  - Algorithms that work well in **typical cases**
  - Highly **optimised implementations**
  - Use of tractable fragments (aka **profiles**)



# Tableau Reasoning Algorithms

Tableau Reasoning Algorithms

# Tableau Reasoning Algorithms

Standard technique based on (hyper-) **tableau**

- Reasoning tasks reducible to (un)**satisfiability**
  - E.g.,  $\text{KB} \models \text{HeartDisease} \vee \text{VascularDisease}$  iff  
 $\text{KB} \cup \{x:(\text{HeartDisease} \sqcap \neg \text{VascularDisease})\}$  is *not* satisfiable

# Tableau Reasoning Algorithms

Standard technique based on (hyper-) **tableau**

- Reasoning tasks reducible to (un)**satisfiability**
  - E.g.,  $\text{KB} \models \text{HeartDisease} \vee \text{VascularDisease}$  iff  
 $\text{KB} \cup \{x:(\text{HeartDisease} \wedge \neg \text{VascularDisease})\}$  is *not* satisfiable
- Algorithm tries to construct (an abstraction of) a model:

$x : \text{HeartDisease} \sqcap \neg \text{VascularDisease}$

# Tableau Reasoning Algorithms

Standard technique based on (hyper-) **tableau**

- Reasoning tasks reducible to (un)**satisfiability**
  - E.g.,  $\text{KB} \models \text{HeartDisease} \vee \text{VascularDisease}$  iff  
 $\text{KB} \cup \{x:(\text{HeartDisease} \wedge \neg \text{VascularDisease})\}$  is *not* satisfiable
- Algorithm tries to construct (an abstraction of) a model:

$x : \text{HeartDisease} \wedge \neg \text{VascularDisease}$

$x : \text{HeartDisease}$

# Tableau Reasoning Algorithms

Standard technique based on (hyper-) **tableau**

- Reasoning tasks reducible to (un)**satisfiability**
  - E.g.,  $\text{KB} \models \text{HeartDisease} \vee \text{VascularDisease}$  iff  
 $\text{KB} \models \{ \text{HeartDisease} \vee \text{VascularDisease} \}$  is *not* satisfiable
- Algorithm tries to construct (an abstraction of) a model:

$x : \text{HeartDisease} \sqcap \neg \text{VascularDisease}$

$x : \text{HeartDisease}$

$x : \text{Disease}$

$x : \exists \text{affects} . \text{Heart}$

# Tableau Reasoning Algorithms

Standard technique based on (hyper-) **tableau**

- Reasoning tasks reducible to (un)**satisfiability**
  - E.g.,  $\text{KB} \models \text{HeartDisease} \vee \text{VascularDisease}$  iff  
 $\text{KB} \wedge \{ \neg(\text{HeartDisease} \vee \text{VascularDisease}) \}$  is *not* satisfiable
- Algorithm tries to construct (an abstraction of) a model:

$x : \text{HeartDisease} \sqcap \neg \text{VascularDisease}$

$x : \text{HeartDisease}$

$x : \text{Disease}$

$x : \exists \text{affects} . \text{Heart}$

$(x, y) : \text{affects}$

$y : \text{Heart}$

# Tableau Reasoning Algorithms

Standard technique based on (hyper-) **tableau**

- Reasoning tasks reducible to (un)**satisfiability**
  - E.g.,  $\text{KB} \models \text{HeartDisease} \vee \text{VascularDisease}$  iff  
 $\text{KB} \cup \{x:(\text{HeartDisease} \wedge \neg \text{VascularDisease})\}$  is *not* satisfiable
- Algorithm tries to construct (an abstraction of) a model:

$x : \text{HeartDisease} \sqcap \neg \text{VascularDisease}$   
 $x : \text{HeartDisease}$   
 $x : \text{Disease}$   
 $x : \exists \text{affects} . \text{Heart}$   
 $(x, y) : \text{affects}$   
 $y : \text{Heart}$   
 $y : \text{MuscularOrgan}$   
 $y : \exists \text{isPartOf} . \text{CirculatorySystem}$



# Tableau Reasoning Algorithms

Standard technique based on (hyper-) **tableau**

- Reasoning tasks reducible to (un)**satisfiability**
  - E.g.,  $\text{KB} \models \text{HeartDisease} \vee \text{VascularDisease}$  iff  
 $\text{KB} \cup \{\neg(\text{HeartDisease} \vee \text{VascularDisease})\}$  is *not* satisfiable
- Algorithm tries to construct (an abstraction of) a model:

$x : \text{HeartDisease} \sqcap \neg \text{VascularDisease}$   
 $x : \text{HeartDisease}$   
 $x : \text{Disease}$   
 $x : \exists \text{affects} . \text{Heart}$   
 $(x, y) : \text{affects}$   
 $y : \text{Heart}$   
 $y : \text{MuscularOrgan}$   
 $y : \exists \text{isPartOf} . \text{CirculatorySystem}$   
 $(y, z) : \text{isPartOf}$   
 $z : \text{CirculatorySystem}$

# Tableau Reasoning Algorithms

Standard technique based on (hyper-) **tableau**

- Reasoning tasks reducible to (un)**satisfiability**
  - E.g.,  $\text{KB} \models \text{HeartDisease} \vee \text{VascularDisease}$  iff  
 $\text{KB} \cup \{\neg(\text{HeartDisease} \vee \text{VascularDisease})\}$  is *not* satisfiable
- Algorithm tries to construct (an abstraction of) a model:

$x : \text{HeartDisease} \sqcap \neg \text{VascularDisease} \quad x : \neg \text{VascularDisease}$   
 $x : \text{HeartDisease}$   
 $x : \text{Disease}$   
 $x : \exists \text{affects} . \text{Heart}$   
 $(x, y) : \text{affects}$   
 $y : \text{Heart}$   
 $y : \text{MuscularOrgan}$   
 $y : \exists \text{isPartOf} . \text{CirculatorySystem}$   
 $(y, z) : \text{isPartOf}$   
 $z : \text{CirculatorySystem}$

# Tableau Reasoning Algorithms

Standard technique based on (hyper-) **tableau**

- Reasoning tasks reducible to (un)satisfiability
  - E.g.,  $\text{KB} \models \text{HeartDisease} \vee \text{VascularDisease}$  iff  
 $\text{KB} \cup \{x : (\text{HeartDisease} \wedge \neg \text{VascularDisease})\}$  is *not* satisfiable
- Algorithm tries to construct (an abstraction of) a model:

$x : \text{HeartDisease} \sqcap \neg \text{VascularDisease}$	$x : \neg \text{VascularDisease}$
$x : \text{HeartDisease}$	$x : \neg \text{Disease} \sqcup$
$x : \text{Disease}$	$\neg \exists \text{affects} . (\exists \text{isPartOf} . \text{CirculatorySystem})$
$x : \exists \text{affects} . \text{Heart}$	
$(x, y) : \text{affects}$	
$y : \text{Heart}$	
$y : \text{MuscularOrgan}$	
$y : \exists \text{isPartOf} . \text{CirculatorySystem}$	
$(y, z) : \text{isPartOf}$	
$z : \text{CirculatorySystem}$	

# Tableau Reasoning Algorithms

Standard technique based on (hyper-) **tableau**

- Reasoning tasks reducible to (un)satisfiability
  - E.g.,  $\text{KB} \models \text{HeartDisease} \vee \text{VascularDisease}$  iff  
 $\text{KB} \sqcup \{x:(\text{HeartDisease} \sqcap \neg \text{VascularDisease})\}$  is *not* satisfiable
- Algorithm tries to construct (an abstraction of) a model:

$x : \text{HeartDisease} \sqcap \neg \text{VascularDisease}$	$x : \neg \text{VascularDisease}$
$x : \text{HeartDisease}$	$x : \neg \text{Disease} \sqcup$
$x : \text{Disease}$	$\neg \exists \text{affects} . (\exists \text{isPartOf} . \text{CirculatorySystem})$
$x : \exists \text{affects} . \text{Heart}$	$x : \neg \text{Disease}$
$(x, y) : \text{affects}$	
$y : \text{Heart}$	
$y : \text{MuscularOrgan}$	
$y : \exists \text{isPartOf} . \text{CirculatorySystem}$	
$(y, z) : \text{isPartOf}$	
$z : \text{CirculatorySystem}$	

# Tableau Reasoning Algorithms

Standard technique based on (hyper-) **tableau**

- Reasoning tasks reducible to (un)**satisfiability**
  - E.g.,  $\text{KB} \models \text{HeartDisease} \vee \text{VascularDisease}$  iff  
 $\text{KB} \sqcup \{x:(\text{HeartDisease} \sqcap \neg \text{VascularDisease})\}$  is *not* satisfiable
- Algorithm tries to construct (an abstraction of) a model:

$x : \text{HeartDisease} \sqcap \neg \text{VascularDisease}$	$x : \neg \text{VascularDisease}$
$x : \text{HeartDisease}$	$x : \neg \text{Disease} \sqcup$
$x : \text{Disease}$	$\neg \exists \text{affects} . (\exists \text{isPartOf} . \text{CirculatorySystem})$
$x : \exists \text{affects} . \text{Heart}$	$x : \neg \text{Disease}$
$(x, y) : \text{affects}$	
$y : \text{Heart}$	
$y : \text{MuscularOrgan}$	
$y : \exists \text{isPartOf} . \text{CirculatorySystem}$	
$(y, z) : \text{isPartOf}$	
$z : \text{CirculatorySystem}$	

# Tableau Reasoning Algorithms

Standard technique based on (hyper-) **tableau**

- Reasoning tasks reducible to (un)**satisfiability**
  - E.g.,  $\text{KB} \models \text{HeartDisease} \vee \text{VascularDisease}$  iff  
 $\text{KB} \sqcup \{x:(\text{HeartDisease} \sqcup \neg \text{VascularDisease})\}$  is *not* satisfiable
- Algorithm tries to construct (an abstraction of) a model

$x : \text{HeartDisease} \sqcap \neg \text{VascularDisease}$	$x : \neg \text{VascularDisease}$
$x : \text{HeartDisease}$	$x : \neg \text{Disease} \sqcup$
$x : \text{Disease}$	$\neg \exists \text{affects} . (\exists \text{isPartOf} . \text{CirculatorySystem})$
$x : \exists \text{affects} . \text{Heart}$	
$(x, y) : \text{affects}$	
$y : \text{Heart}$	
$y : \text{MuscularOrgan}$	
$y : \exists \text{isPartOf} . \text{CirculatorySystem}$	
$(y, z) : \text{isPartOf}$	
$z : \text{CirculatorySystem}$	

# Tableau Reasoning Algorithms

Standard technique based on (hyper-) **tableau**

- Reasoning tasks reducible to (un)**satisfiability**
  - E.g.,  $\text{KB} \models \text{HeartDisease} \vee \text{VascularDisease}$  iff  
 $\text{KB} \sqcup \{x:(\text{HeartDisease} \sqcap \neg \text{VascularDisease})\}$  is *not* satisfiable
- Algorithm tries to construct (an abstraction of) a model

$x : \text{HeartDisease} \sqcap \neg \text{VascularDisease}$	$x : \neg \text{VascularDisease}$
$x : \text{HeartDisease}$	$x : \neg \text{Disease} \sqcup$
$x : \text{Disease}$	$\neg \exists \text{affects} . (\exists \text{isPartOf} . \text{CirculatorySystem})$
$x : \exists \text{affects} . \text{Heart}$	$x : \neg \exists \text{affects} . (\exists \text{isPartOf} . \text{CirculatorySystem})$
$(x, y) : \text{affects}$	
$y : \text{Heart}$	
$y : \text{MuscularOrgan}$	
$y : \exists \text{isPartOf} . \text{CirculatorySystem}$	
$(y, z) : \text{isPartOf}$	
$z : \text{CirculatorySystem}$	

# Tableau Reasoning Algorithms

Standard technique based on (hyper-) **tableau**

- Reasoning tasks reducible to (un)satisfiability
  - E.g.,  $\text{KB} \models \text{HeartDisease} \vee \text{VascularDisease}$  iff  
 $\text{KB} \sqcup \{x:(\text{HeartDisease} \sqcap \neg \text{VascularDisease})\}$  is *not* satisfiable
- Algorithm tries to construct (an abstraction of) a model

$x : \text{HeartDisease} \sqcap \neg \text{VascularDisease}$	$x : \neg \text{VascularDisease}$
$x : \text{HeartDisease}$	$x : \neg \text{Disease} \sqcup$
$x : \text{Disease}$	$\neg \exists \text{affects}. (\exists \text{isPartOf}. \text{CirculatorySystem})$
$x : \exists \text{affects}. \text{Heart}$	$x : \neg \exists \text{affects}. (\exists \text{isPartOf}. \text{CirculatorySystem})$
$(x, y) : \text{affects}$	$x : \forall \text{affects}. (\forall \text{isPartOf}. \neg \text{CirculatorySystem})$
$y : \text{Heart}$	
$y : \text{MuscularOrgan}$	
$y : \exists \text{isPartOf}. \text{CirculatorySystem}$	
$(y, z) : \text{isPartOf}$	
$z : \text{CirculatorySystem}$	



# Tableau Reasoning Algorithms

Standard technique based on (hyper-) **tableau**

- Reasoning tasks reducible to (un)**satisfiability**
  - E.g.,  $\text{KB} \models \text{HeartDisease} \vee \text{VascularDisease}$  iff  
 $\text{KB} \sqcup \{x:(\text{HeartDisease} \sqcup \text{VascularDisease})\}$  is *not* satisfiable
- Algorithm tries to construct (an abstraction of) a model

$x : \text{HeartDisease} \sqcap \neg \text{VascularDisease}$   
 $x : \text{HeartDisease}$   
 $x : \text{Disease}$   
 $x : \exists \text{affects} . \text{Heart}$   
 $(x, y) : \text{affects}$   
 $y : \text{Heart}$   
 $y : \text{MuscularOrgan}$   
 $y : \exists \text{isPartOf} . \text{CirculatorySystem}$   
 $(y, z) : \text{isPartOf}$   
 $z : \text{CirculatorySystem}$

$x : \neg \text{VascularDisease}$   
 $x : \neg \text{Disease} \sqcup$   
 $\neg \exists \text{affects} . (\exists \text{isPartOf} . \text{CirculatorySystem})$   
 $x : \neg \exists \text{affects} . (\exists \text{isPartOf} . \text{CirculatorySystem})$   
 $x : \forall \text{affects} . (\forall \text{isPartOf} . \neg \text{CirculatorySystem})$   
 $y : \forall \text{isPartOf} . \neg \text{CirculatorySystem}$

# Tableau Reasoning Algorithms

Standard technique based on (hyper-) **tableau**

- Reasoning tasks reducible to (un)**satisfiability**
  - E.g.,  $\text{KB} \models \text{HeartDisease} \vee \text{VascularDisease}$  iff  
 $\text{KB} \sqcup \{x:(\text{HeartDisease} \sqcup \text{VascularDisease})\}$  is *not* satisfiable
- Algorithm tries to construct (an abstraction of) a model

$x : \text{HeartDisease} \sqcap \neg \text{VascularDisease}$   
 $x : \text{HeartDisease}$   
 $x : \text{Disease}$   
 $x : \exists \text{affects} . \text{Heart}$   
 $(x, y) : \text{affects}$   
 $y : \text{Heart}$   
 $y : \text{MuscularOrgan}$   
 $y : \exists \text{isPartOf} . \text{CirculatorySystem}$   
 $(y, z) : \text{isPartOf}$   
 $z : \text{CirculatorySystem}$

$x : \neg \text{VascularDisease}$   
 $x : \neg \text{Disease} \sqcup$   
 $\neg \exists \text{affects} . (\exists \text{isPartOf} . \text{CirculatorySystem})$   
 $x : \neg \exists \text{affects} . (\exists \text{isPartOf} . \text{CirculatorySystem})$   
 $x : \forall \text{affects} . (\forall \text{isPartOf} . \neg \text{CirculatorySystem})$   
 $y : \forall \text{isPartOf} . \neg \text{CirculatorySystem}$   
 $z : \neg \text{CirculatorySystem}$

# Tableau Reasoning Algorithms

Standard technique based on (hyper-) **tableau**

- Reasoning tasks reducible to (un)**satisfiability**
  - E.g.,  $\text{KB} \models \text{HeartDisease} \vee \text{VascularDisease}$  iff  
 $\text{KB} \sqcup \{x:(\text{HeartDisease} \sqcup \text{VascularDisease})\}$  is *not* satisfiable
- Algorithm tries to construct (an abstraction of) a model

$x : \text{HeartDisease} \sqcap \neg \text{VascularDisease}$   
 $x : \text{HeartDisease}$   
 $x : \text{Disease}$   
 $x : \exists \text{affects} . \text{Heart}$   
 $(x, y) : \text{affects}$   
 $y : \text{Heart}$   
 $y : \text{MuscularOrgan}$   
 $y : \exists \text{isPartOf} . \text{CirculatorySystem}$   
 $(y, z) : \text{isPartOf}$   
 $z : \text{CirculatorySystem}$

$x : \neg \text{VascularDisease}$   
 $x : \neg \text{Disease} \sqcup$   
 $\neg \exists \text{affects} . (\exists \text{isPartOf} . \text{CirculatorySystem})$   
 $x : \neg \exists \text{affects} . (\exists \text{isPartOf} . \text{CirculatorySystem})$   
 $x : \forall \text{affects} . (\forall \text{isPartOf} . \neg \text{CirculatorySystem})$   
 $y : \forall \text{isPartOf} . \neg \text{CirculatorySystem}$   
 $z : \neg \text{CirculatorySystem}$


# Highly Optimised Implementations

- Lazy unfolding
- Simplification and rewriting,  
e.g.,  $A \sqcap B \sqsubseteq C \longrightarrow A \sqsubseteq C \sqcup \neg B$
- HyperTableau (reduces non-determinism)
- Fast semi-decision procedures
- Search optimisations
- Reuse of previous computations
- Heuristics

**Not computationally optimal,  
but effective with many realistic ontologies**

# Scalability Issues

- Problems with very **large and/or cyclical ontologies**
  - Ontologies may define 10s/100s of thousands of terms
  - Potentially vast number ( $n^2$ ) of tests needed for classification
  - Each test can lead to construction of very large models



LeftSide  $\sqsubseteq \exists \text{hasComponent.}$ AorticValve  
LeftSide  $\sqsubseteq \exists \text{hasComponent.}$ MitralValve  
AorticValve  $\sqsubseteq \exists \text{hasConnection.}$ LeftVentricle  
MitralValve  $\sqsubseteq \exists \text{hasConnection.}$ LeftVentricle  
LeftVentricle  $\sqsubseteq \exists \text{isDivisionOf.}$ LeftSide

# Scalability Issues

- Problems with **large data sets** (ABoxes)
  - Main reasoning problem is (conjunctive) query answering, e.g., retrieve all patients suffering from vascular disease:  
 $Q(x) \leftarrow \text{Patient}(x) \wedge \text{suffersFrom}(x, y) \wedge \text{VascularDisease}(y)$
  - Decidability still open for OWL, although minor restrictions (on cycles in non-distinguished variables) restore decidability
  - Query answering reduced to standard decision problem, e.g., by checking for each individual  $x$  if  $\text{KB} \models Q(x)$
  - Model construction starts with *all* ground facts (data)
- Typical applications may use data sets with **10s/100s of millions** of individuals (or more)

# OWL 2 Profiles

- OWL recommendation now updated to **OWL 2**
- OWL 2 defines several **profiles** – fragments with desirable computational properties
  - **OWL 2 EL** targeted at very large ontologies
  - **OWL 2 QL** targeted at very large data sets

# OWL 2 EL

- A (near maximal) fragment of OWL 2 such that
  - Satisfiability checking is in PTime (**PTime-Complete**)
  - Data complexity of query answering also PTime-Complete
- Based on **EL** family of description logics
- Can exploit **saturation** based reasoning techniques
  - Computes complete classification in “one pass”
  - Computationally optimal (PTime for EL)
  - Can be extended to Horn fragment of OWL DL



# Saturation-based Technique (basics)

- Normalise ontology axioms to standard form:

$$A \sqsubseteq B \quad A \sqcap B \sqsubseteq C \quad A \sqsubseteq \exists R.B \quad \exists R.B \sqsubseteq C$$

- Saturate using inference rules:

$$\frac{A \sqsubseteq B \quad B \sqsubseteq C}{A \sqsubseteq C}$$

$$\frac{A \sqsubseteq B \quad A \sqsubseteq C \quad B \sqcap C \sqsubseteq D}{A \sqsubseteq D}$$

$$\frac{A \sqsubseteq \exists R.B \quad B \sqsubseteq C \quad \exists R.C \sqsubseteq D}{A \sqsubseteq D}$$

- Extension to Horn fragment requires (many) more rules

# Saturation-based Technique (basics)

Example:

$\text{OrganTransplant} \equiv \text{Transplant} \sqcap \exists \text{site}.\text{Organ}$

$\text{HeartTransplant} \equiv \text{Transplant} \sqcap \exists \text{site}.\text{Heart}$

$\text{Heart} \sqsubseteq \text{Organ}$

# Saturation-based Technique (basics)

Example:

$\text{OrganTransplant} \equiv \text{Transplant} \sqcap \exists \text{site}.\text{Organ}$

$\text{HeartTransplant} \equiv \text{Transplant} \sqcap \exists \text{site}.\text{Heart}$

$\text{Heart} \sqsubseteq \text{Organ}$

# Saturation-based Technique (basics)

Example:

$\text{OrganTransplant} \equiv \text{Transplant} \sqcap \exists \text{site}.\text{Organ}$

$\text{HeartTransplant} \equiv \text{Transplant} \sqcap \exists \text{site}.\text{Heart}$

$\text{Heart} \sqsubseteq \text{Organ}$

$\text{OrganTransplant} \sqsubseteq \text{Transplant}$

$\text{OrganTransplant} \sqsubseteq \exists \text{site}.\text{Organ}$

# Saturation-based Technique (basics)

Example:

$\text{OrganTransplant} \equiv \text{Transplant} \sqcap \exists \text{site}.\text{Organ}$

$\text{HeartTransplant} \equiv \text{Transplant} \sqcap \exists \text{site}.\text{Heart}$

$\text{Heart} \sqsubseteq \text{Organ}$

$\text{OrganTransplant} \sqsubseteq \text{Transplant}$

$\text{OrganTransplant} \sqsubseteq \exists \text{site}.\text{Organ}$

$\exists \text{site}.\text{Organ} \sqsubseteq \text{SO}$

$\text{Transplant} \sqcap \text{SO} \sqsubseteq \text{OrganTransplant}$

# Saturation-based Technique (basics)

Example:

$\text{OrganTransplant} \equiv \text{Transplant} \sqcap \exists \text{site}.\text{Organ}$

$\text{HeartTransplant} \equiv \text{Transplant} \sqcap \exists \text{site}.\text{Heart}$

$\text{Heart} \sqsubseteq \text{Organ}$

$\text{OrganTransplant} \sqsubseteq \text{Transplant}$

$\text{OrganTransplant} \sqsubseteq \exists \text{site}.\text{Organ}$

$\exists \text{site}.\text{Organ} \sqsubseteq \text{SO}$

$\text{Transplant} \sqcap \text{SO} \sqsubseteq \text{OrganTransplant}$

# Saturation-based Technique (basics)

Example:

$\text{OrganTransplant} \equiv \text{Transplant} \sqcap \exists \text{site}.\text{Organ}$

$\text{HeartTransplant} \equiv \text{Transplant} \sqcap \exists \text{site}.\text{Heart}$

$\text{Heart} \sqsubseteq \text{Organ}$

$\text{OrganTransplant} \sqsubseteq \text{Transplant}$

$\text{OrganTransplant} \sqsubseteq \exists \text{site}.\text{Organ}$

$\exists \text{site}.\text{Organ} \sqsubseteq \text{SO}$

$\text{Transplant} \sqcap \text{SO} \sqsubseteq \text{OrganTransplant}$

$\text{HeartTransplant} \sqsubseteq \text{Transplant}$

$\text{HeartTransplant} \sqsubseteq \exists \text{site}.\text{Heart}$

$\exists \text{site}.\text{Heart} \sqsubseteq \text{SH}$

$\text{Transplant} \sqcap \text{SH} \sqsubseteq \text{HeartTransplant}$

# Saturation-based Technique (basics)

Example:

$\text{OrganTransplant} \equiv \text{Transplant} \sqcap \exists \text{site}.\text{Organ}$

$\text{HeartTransplant} \equiv \text{Transplant} \sqcap \exists \text{site}.\text{Heart}$

$\text{Heart} \sqsubseteq \text{Organ}$

$\text{OrganTransplant} \sqsubseteq \text{Transplant}$

$\text{OrganTransplant} \sqsubseteq \exists \text{site}.\text{Organ}$

$\exists \text{site}.\text{Organ} \sqsubseteq \text{SO}$

$\text{Transplant} \sqcap \text{SO} \sqsubseteq \text{OrganTransplant}$

$\text{HeartTransplant} \sqsubseteq \text{Transplant}$

$\text{HeartTransplant} \sqsubseteq \exists \text{site}.\text{Heart}$

$\exists \text{site}.\text{Heart} \sqsubseteq \text{SH}$

$\text{Transplant} \sqcap \text{SH} \sqsubseteq \text{HeartTransplant}$



# Saturation-based Technique (basics)

Example:

$\text{OrganTransplant} \equiv \text{Transplant} \sqcap \exists \text{site}.\text{Organ}$

$\text{HeartTransplant} \equiv \text{Transplant} \sqcap \exists \text{site}.\text{Heart}$

$\text{Heart} \sqsubseteq \text{Organ}$

$\text{OrganTransplant} \sqsubseteq \text{Transplant}$

$\text{OrganTransplant} \sqsubseteq \exists \text{site}.\text{Organ}$

$\exists \text{site}.\text{Organ} \sqsubseteq \text{SO}$

$\text{Transplant} \sqcap \text{SO} \sqsubseteq \text{OrganTransplant}$

$\text{HeartTransplant} \sqsubseteq \text{Transplant}$

$\text{HeartTransplant} \sqsubseteq \exists \text{site}.\text{Heart}$

$\exists \text{site}.\text{Heart} \sqsubseteq \text{SH}$

$\text{Transplant} \sqcap \text{SH} \sqsubseteq \text{HeartTransplant}$

$\text{Heart} \sqsubseteq \text{Organ}$

# Saturation-based Technique (basics)

Example:

OrganTransplant  $\equiv$  Transplant  $\sqcap$   $\exists$ site.Organ  
HeartTransplant  $\equiv$  Transplant  $\sqcap$   $\exists$ site.Heart  
Heart  $\sqsubseteq$  Organ

$$\frac{A \sqsubseteq \exists R.B \quad B \sqsubseteq C \quad \exists R.C \sqsubseteq D}{A \sqsubseteq D}$$

OrganTransplant  $\sqsubseteq$  Transplant  
OrganTransplant  $\sqsubseteq$   $\exists$ site.Organ  
 $\exists$ site.Organ  $\sqsubseteq$  SO  
Transplant  $\sqcap$  SO  $\sqsubseteq$  OrganTransplant  
HeartTransplant  $\sqsubseteq$  Transplant  
HeartTransplant  $\sqsubseteq$   $\exists$ site.Heart  
 $\exists$ site.Heart  $\sqsubseteq$  SH  
Transplant  $\sqcap$  SH  $\sqsubseteq$  HeartTransplant  
Heart  $\sqsubseteq$  Organ

# Saturation-based Technique (basics)

Example:

$\text{OrganTransplant} \equiv \text{Transplant} \sqcap \exists \text{site}.\text{Organ}$   
 $\text{HeartTransplant} \equiv \text{Transplant} \sqcap \exists \text{site}.\text{Heart}$   
 $\text{Heart} \sqsubseteq \text{Organ}$

$$\frac{A \sqsubseteq \exists R.B \quad B \sqsubseteq C \quad \exists R.C \sqsubseteq D}{A \sqsubseteq D}$$

$\text{OrganTransplant} \sqsubseteq \text{Transplant}$   
 $\text{OrganTransplant} \sqsubseteq \exists \text{site}.\text{Organ}$   
 $\exists \text{site}.\text{Organ} \sqsubseteq \text{SO}$   
 $\text{Transplant} \sqcap \text{SO} \sqsubseteq \text{OrganTransplant}$   
 $\text{HeartTransplant} \sqsubseteq \text{Transplant}$   
 $\text{HeartTransplant} \sqsubseteq \exists \text{site}.\text{Heart}$   
 $\exists \text{site}.\text{Heart} \sqsubseteq \text{SH}$   
 $\text{Transplant} \sqcap \text{SH} \sqsubseteq \text{HeartTransplant}$   
 $\text{Heart} \sqsubseteq \text{Organ}$

$\text{HeartTransplant} \sqsubseteq \text{SO}$

# Saturation-based Technique (basics)

Example:

OrganTransplant  $\equiv$  Transplant  $\sqcap$   $\exists$ site.Organ  
HeartTransplant  $\equiv$  Transplant  $\sqcap$   $\exists$ site.Heart  
Heart  $\sqsubseteq$  Organ

$$\frac{A \sqsubseteq B \quad A \sqsubseteq C \quad B \sqcap C \sqsubseteq D}{A \sqsubseteq D}$$

OrganTransplant  $\sqsubseteq$  Transplant  
OrganTransplant  $\sqsubseteq$   $\exists$ site.Organ  
 $\exists$ site.Organ  $\sqsubseteq$  SO  
Transplant  $\sqcap$  SO  $\sqsubseteq$  OrganTransplant  
HeartTransplant  $\sqsubseteq$  Transplant  
HeartTransplant  $\sqsubseteq$   $\exists$ site.Heart  
 $\exists$ site.Heart  $\sqsubseteq$  SH  
Transplant  $\sqcap$  SH  $\sqsubseteq$  HeartTransplant  
Heart  $\sqsubseteq$  Organ

HeartTransplant  $\sqsubseteq$  SO

# Saturation-based Technique (basics)

Example:

$\text{OrganTransplant} \equiv \text{Transplant} \sqcap \exists \text{site}.\text{Organ}$   
 $\text{HeartTransplant} \equiv \text{Transplant} \sqcap \exists \text{site}.\text{Heart}$   
 $\text{Heart} \sqsubseteq \text{Organ}$

$$\frac{A \sqsubseteq B \quad A \sqsubseteq C \quad B \sqcap C \sqsubseteq D}{A \sqsubseteq D}$$

$\text{OrganTransplant} \sqsubseteq \text{Transplant}$   
 $\text{OrganTransplant} \sqsubseteq \exists \text{site}.\text{Organ}$   
 $\exists \text{site}.\text{Organ} \sqsubseteq \text{SO}$   
 $\text{Transplant} \sqcap \text{SO} \sqsubseteq \text{OrganTransplant}$   
 $\text{HeartTransplant} \sqsubseteq \text{Transplant}$   
 $\text{HeartTransplant} \sqsubseteq \exists \text{site}.\text{Heart}$   
 $\exists \text{site}.\text{Heart} \sqsubseteq \text{SH}$   
 $\text{Transplant} \sqcap \text{SH} \sqsubseteq \text{HeartTransplant}$   
 $\text{Heart} \sqsubseteq \text{Organ}$

$\text{HeartTransplant} \sqsubseteq \text{SO}$   
 $\text{HeartTransplant} \sqsubseteq \text{OrganTransplant}$

# Saturation-based Technique

Performance with large bio-medical ontologies:

	GO	NCI	Galen v.0	Galen v.7	SNOMED
Concepts:	20465	27652	2748	23136	389472
FACT++	15.24	6.05	465.35	—	650.37
HERMIT	199.52	169.47	45.72	—	—
PELLET	72.02	26.47	—	—	—
CEL	1.84	5.76	—	—	1185.70
CB	1.17	3.57	0.32	9.58	49.44
Speed-Up:	1.57X	1.61X	143X	$\infty$	13.15X

# OWL 2 QL

- A (near maximal) fragment of OWL 2 such that
  - Data complexity of conjunctive query answering in **AC<sup>0</sup>**
- Based on **DL-Lite** family of description logics
- Can exploit **query rewriting** based reasoning technique
  - Computationally optimal
  - Data storage and query evaluation can be delegated to standard RDBMS
  - Can be extended to more expressive languages (beyond AC<sup>0</sup>) by delegating query answering to a Datalog engine

# Query Rewriting Technique (basics)

- Given ontology  $O$  and query  $Q$ , use  $O$  to rewrite  $Q$  as  $Q^0$  s.t., for any set of ground facts  $A$ :
  - $\text{ans}(Q, O, A) = \text{ans}(Q^0, ;, A)$




# Query Rewriting Technique (basics)

- Given ontology  $O$  and query  $Q$ , use  $O$  to rewrite  $Q$  as  $Q^0$  s.t., for any set of ground facts  $A$ :
  - $\text{ans}(Q, O, A) = \text{ans}(Q^0, ;, A)$
- Use (GAV) mapping  $M$  to map  $Q^0$  to SQL query

# Query Rewriting Technique (basics)

- Given ontology  $O$  and query  $Q$ , use  $O$  to rewrite  $Q$  as  $Q^0$  s.t., for any set of ground facts  $A$ :
  - $\text{ans}(Q, O, A) = \text{ans}(Q^0, ;, A)$
- Use (GAV) mapping  $M$  to map  $Q^0$  to SQL query



# Query Rewriting Technique (basics)

- Given ontology  $O$  and query  $Q$ , use  $O$  to rewrite  $Q$  as  $Q^0$  s.t., for any set of ground facts  $A$ :
  - $\text{ans}(Q, O, A) = \text{ans}(Q^0, ;, A)$
- Use (GAV) mapping  $M$  to map  $Q^0$  to SQL query
- Resolution based query rewriting
  - **Clausify** ontology axioms
  - **Saturate** (clausified) ontology and query using resolution
  - **Prune** redundant query clauses

# Query Rewriting Technique (basics)

- Example:

Doctor  $\sqsubseteq \exists \text{treats}.\text{Patient}$   
Consultant  $\sqsubseteq \text{Doctor}$

$$Q(x) \leftarrow \text{treats}(x, y) \wedge \text{Patient}(y)$$

# Query Rewriting Technique (basics)

- Example:

Doctor  $\sqsubseteq \exists \text{treats.Patient}$

Consultant  $\sqsubseteq$  Doctor

$\text{treats}(x, f(x)) \leftarrow \text{Doctor}(x)$

$\text{Patient}(f(x)) \leftarrow \text{Doctor}(x)$

$\text{Doctor}(x) \leftarrow \text{Consultant}(x)$

$Q(x) \leftarrow \text{treats}(x, y) \wedge \text{Patient}(y)$

# Query Rewriting Technique (basics)

- Example:

Doctor  $\sqsubseteq \exists \text{treats.Patient}$

Consultant  $\sqsubseteq \text{Doctor}$

$\text{treats}(x, f(x)) \leftarrow \text{Doctor}(x)$

$\text{Patient}(f(x)) \leftarrow \text{Doctor}(x)$

$\text{Doctor}(x) \leftarrow \text{Consultant}(x)$

$Q(x) \leftarrow \text{treats}(x, y) \wedge \text{Patient}(y)$

# Query Rewriting Technique (basics)

- Example:

Doctor  $\sqsubseteq \exists \text{treats.Patient}$

Consultant  $\sqsubseteq \text{Doctor}$

$\text{treats}(x, f(x)) \leftarrow \text{Doctor}(x)$

$\text{Patient}(f(x)) \leftarrow \text{Doctor}(x)$

$\text{Doctor}(x) \leftarrow \text{Consultant}(x)$

$Q(x) \leftarrow \text{treats}(x, y) \wedge \text{Patient}(y)$

$Q(x) \leftarrow \text{Doctor}(x) \wedge \text{Patient}(f(x))$

# Query Rewriting Technique (basics)

- Example:

Doctor  $\sqsubseteq \exists \text{treats.Patient}$

Consultant  $\sqsubseteq \text{Doctor}$

$\text{treats}(x, f(x)) \leftarrow \text{Doctor}(x)$

$\text{Patient}(f(x)) \leftarrow \text{Doctor}(x)$

$\text{Doctor}(x) \leftarrow \text{Consultant}(x)$

$Q(x) \leftarrow \text{treats}(x, y) \wedge \text{Patient}(y)$

$Q(x) \leftarrow \text{Doctor}(x) \wedge \text{Patient}(f(x))$



# Query Rewriting Technique (basics)

- Example:

Doctor  $\sqsubseteq \exists \text{treats.Patient}$

Consultant  $\sqsubseteq \text{Doctor}$

$\text{treats}(x, f(x)) \leftarrow \text{Doctor}(x)$

$\text{Patient}(f(x)) \leftarrow \text{Doctor}(x)$

$\text{Doctor}(x) \leftarrow \text{Consultant}(x)$

$Q(x) \leftarrow \text{treats}(x, y) \wedge \text{Patient}(y)$

$Q(x) \leftarrow \text{Doctor}(x) \wedge \text{Patient}(f(x))$

$Q(x) \leftarrow \text{treats}(x, f(x)) \wedge \text{Doctor}(x)$

# Query Rewriting Technique (basics)

- Example:

Doctor  $\sqsubseteq \exists \text{treats.Patient}$

Consultant  $\sqsubseteq \text{Doctor}$

$\text{treats}(x, f(x)) \leftarrow \text{Doctor}(x)$

$\text{Patient}(f(x)) \leftarrow \text{Doctor}(x)$

$\text{Doctor}(x) \leftarrow \text{Consultant}(x)$

$Q(x) \leftarrow \text{treats}(x, y) \wedge \text{Patient}(y)$

$Q(x) \leftarrow \text{Doctor}(x) \wedge \text{Patient}(f(x))$

$Q(x) \leftarrow \text{treats}(x, f(x)) \wedge \text{Doctor}(x)$

# Query Rewriting Technique (basics)

- Example:

$\text{Doctor} \sqsubseteq \exists \text{treats}.\text{Patient}$

$\text{Consultant} \sqsubseteq \text{Doctor}$

$\text{treats}(x, f(x)) \leftarrow \text{Doctor}(x)$

$\text{Patient}(f(x)) \leftarrow \text{Doctor}(x)$

$\text{Doctor}(x) \leftarrow \text{Consultant}(x)$

$Q(x) \leftarrow \text{treats}(x, y) \wedge \text{Patient}(y)$

$Q(x) \leftarrow \text{Doctor}(x) \wedge \text{Patient}(f(x))$

$Q(x) \leftarrow \text{treats}(x, f(x)) \wedge \text{Doctor}(x)$

$Q(x) \leftarrow \text{Doctor}(x)$

# Query Rewriting Technique (basics)

- Example:

Doctor  $\sqsubseteq \exists \text{treats}.\text{Patient}$

Consultant  $\sqsubseteq \text{Doctor}$

$\text{treats}(x, f(x)) \leftarrow \text{Doctor}(x)$

$\text{Patient}(f(x)) \leftarrow \text{Doctor}(x)$

$\text{Doctor}(x) \leftarrow \text{Consultant}(x)$

$Q(x) \leftarrow \text{treats}(x, y) \wedge \text{Patient}(y)$

$Q(x) \leftarrow \text{Doctor}(x) \wedge \text{Patient}(f(x))$

$Q(x) \leftarrow \text{treats}(x, f(x)) \wedge \text{Doctor}(x)$

$Q(x) \leftarrow \text{Doctor}(x)$

# Query Rewriting Technique (basics)

- Example:

$\text{Doctor} \sqsubseteq \exists \text{treats}.\text{Patient}$

$\text{Consultant} \sqsubseteq \text{Doctor}$

$\text{treats}(x, f(x)) \leftarrow \text{Doctor}(x)$

$\text{Patient}(f(x)) \leftarrow \text{Doctor}(x)$

$\text{Doctor}(x) \leftarrow \text{Consultant}(x)$

$Q(x) \leftarrow \text{treats}(x, y) \wedge \text{Patient}(y)$

$Q(x) \leftarrow \text{Doctor}(x) \wedge \text{Patient}(f(x))$

$Q(x) \leftarrow \text{treats}(x, f(x)) \wedge \text{Doctor}(x)$

$Q(x) \leftarrow \text{Doctor}(x)$

$Q(x) \leftarrow \text{Consultant}(x)$

# Query Rewriting Technique (basics)

- Example:

Doctor  $\sqsubseteq \exists \text{treats.Patient}$

Consultant  $\sqsubseteq \text{Doctor}$

$\text{treats}(x, f(x)) \leftarrow \text{Doctor}(x)$

$\text{Patient}(f(x)) \leftarrow \text{Doctor}(x)$

$\text{Doctor}(x) \leftarrow \text{Consultant}(x)$

$Q(x) \leftarrow \text{treats}(x, y) \wedge \text{Patient}(y)$

$Q(x) \leftarrow \text{Doctor}(x) \wedge \text{Patient}(f(x))$

$Q(x) \leftarrow \text{treats}(x, f(x)) \wedge \text{Doctor}(x)$

$Q(x) \leftarrow \text{Doctor}(x)$

$Q(x) \leftarrow \text{Consultant}(x)$

# Query Rewriting Technique (basics)

- Example:

Doctor  $\sqsubseteq \exists \text{ treats.Patient}$

Consultant  $\sqsubseteq \text{Doctor}$

$\text{treats}(x, f(x)) \leftarrow \text{Doctor}(x)$

$\text{Patient}(f(x)) \leftarrow \text{Doctor}(x)$

$\text{Doctor}(x) \leftarrow \text{Consultant}(x)$

$Q(x) \leftarrow \text{treats}(x, y) \wedge \text{Patient}(y)$

~~$Q(x) \leftarrow \text{Doctor}(x) \wedge \text{Patient}(f(x))$~~

~~$Q(x) \leftarrow \text{treats}(x, f(x)) \wedge \text{Doctor}(x)$~~

$Q(x) \leftarrow \text{Doctor}(x)$

$Q(x) \leftarrow \text{Consultant}(x)$

# Query Rewriting Technique (basics)

- Example:

$\text{Doctor} \sqsubseteq \exists \text{treats}.\text{Patient}$

$\text{Consultant} \sqsubseteq \text{Doctor}$

$\text{treats}(x, f(x)) \leftarrow \text{Doctor}(x)$

$\text{Patient}(f(x)) \leftarrow \text{Doctor}(x)$

$\text{Doctor}(x) \leftarrow \text{Consultant}(x)$

$Q(x) \leftarrow \text{treats}(x, y) \wedge \text{Patient}(y)$

~~$Q(x) \leftarrow \text{Doctor}(x) \wedge \text{Patient}(f(x))$~~

~~$Q(x) \leftarrow \text{treats}(x, f(x)) \wedge \text{Doctor}(x)$~~

$Q(x) \leftarrow \text{Doctor}(x)$

$Q(x) \leftarrow \text{Consultant}(x)$

- For DL-Lite, result is a union of conjunctive queries

$Q(x) \leftarrow (\text{treats}(x, y) \wedge \text{Patient}(y)) \vee \text{Doctor}(x) \vee \text{Consultant}(x)$



# Query Rewriting Technique (basics)

- Data can be stored/left in **RDBMS**
- Relationship between ontology and DB defined by **mappings**, e.g.:

Doctor  $\mapsto$  SELECT Name FROM Doctor

Patient  $\mapsto$  SELECT Name FROM Patient

treats  $\mapsto$  SELECT DName, PName FROM Treats

# Query Rewriting Technique (basics)

- Data can be stored/left in **RDBMS**
- Relationship between ontology and DB defined by **mappings**, e.g.:

**Doctor**  $\mapsto$  SELECT Name FROM Doctor  
**Patient**  $\mapsto$  SELECT Name FROM Patient  
**treats**  $\mapsto$  SELECT DName, PName FROM Treats

- UCQ translated into **SQL query**:

$$Q(x) \leftarrow (\text{treats}(x, y) \wedge \text{Patient}(y)) \vee \text{Doctor}(x) \vee \text{Consultant}(x)$$

↓

SELECT Name FROM Doctor UNION  
SELECT DName FROM Treats, Patient WHERE PName=Name

# Problems & Research Challenges

- Combining best features of DLs & DBs
  - In particular, integrating OWA and CWA
- Hard to find a coherent semantic framework
  - Problems mainly due to existential quantifiers: should existentially implied objects be considered different?
    - Does a person owning a phone and an ipod own 2 things?
    - Does a person owning a phone and an iphone own 2 things?
    - Does a person owning a phone and a phone own 2 things?
- Interesting ideas emerging in DL & DB communities, e.g.:
  - *Calì et al. Datalog $\pm$ : a unified approach to ontologies and integrity constraints. ICDT 2009.*
  - *Motik et al. Bridging the gap between OWL and relational databases. WWW 2007.*

# Problems & Research Challenges

- Open questions w.r.t. query rewriting

# Problems & Research Challenges

- Open questions w.r.t. query rewriting
  - Currently only for very weak ontology languages

# Problems & Research Challenges

- Open questions w.r.t. query rewriting
  - Currently only for very weak ontology languages
  - Even for these languages, queries can get very large (order  $(|\mathcal{O}| \cdot |\mathcal{Q}|)^{|\mathcal{Q}|}$ ), and existing RDBMSs may behave poorly
    - Not clear if this will be a problem in practice, see, e.g., *Savo et al. MASTRO at Work: Experiences on Ontology-based Data Access. DL 2010.*

# Problems & Research Challenges

- Open questions w.r.t. query rewriting
  - Currently only for very weak ontology languages
  - Even for these languages, queries can get very large (order  $(|\mathcal{O}| \cdot |\mathcal{Q}|)^{|\mathcal{Q}|}$ ), and existing RDBMSs may behave poorly
    - Not clear if this will be a problem in practice, see, e.g., *Savo et al. MASTRO at Work: Experiences on Ontology-based Data Access. DL 2010.*
  - Larger fragments require (at least) Datalog engines and/or extension to technique (e.g., partial materialisation)
    - Promising new work in this area, see, e.g., *Lutz et al. Conjunctive Query Answering in the Description Logic EL Using a Relational Database System. IJCAI 2009.*

# Problems & Research Challenges

- Infrastructure



# Problems & Research Challenges

- Infrastructure
  - Standardised query language
    - SPARQL standard for RDF
    - Currently being extended for OWL, see [http://www.w3.org/2009/sparql/wiki/Main\\_Page](http://www.w3.org/2009/sparql/wiki/Main_Page)


# Problems & Research Challenges

- Infrastructure
  - Standardised query language
    - SPARQL standard for RDF
    - Currently being extended for OWL, see [http://www.w3.org/2009/sparql/wiki/Main\\_Page](http://www.w3.org/2009/sparql/wiki/Main_Page)
  - Privacy and information hiding
    - May want to keep parts of data/schema private
    - Difficulties compounded when information can be inferred, see, e.g., *Cuenca Grau et al. Privacy-preserving query answering in logic-based information systems. ECAI 2008.*

# Problems & Research Challenges

- Infrastructure
  - Standardised query language
    - SPARQL standard for RDF
    - Currently being extended for OWL, see [http://www.w3.org/2009/sparql/wiki/Main\\_Page](http://www.w3.org/2009/sparql/wiki/Main_Page)
  - Privacy and information hiding
    - May want to keep parts of data/schema private
    - Difficulties compounded when information can be inferred, see, e.g., *Cuenca Grau et al. Privacy-preserving query answering in logic-based information systems. ECAI 2008.*
  - ...

# Thank you for listening



FRAZZ: © Jeff Mallett/Dist. by United Feature Syndicate, Inc.

# Any questions?