1 Kubectl Kubernetes CheatSheet

KUBERNETES

Updated: October 14, 2018

- PDF Link: cheatsheet-kubernetes-A4.pdf, Category: kubernetes
- Blog URL: https://cheatsheet.dennyzhang.com/cheatsheet-kubernetes-A4

File me Issues or star this repo.

See more CheatSheets from Denny: #denny-cheatsheets

1.1 Common Commands

List everything kubectl get allall-namespaces	
List pods with nodes info kubectl get pod -o wide	
Validate yaml file with dry run kubectl createdry-runvalidate -f pod-dummy.yaml	
Start a temporary pod for testing kubectl runrm -i -timage=alpine test-\$RANDOM sh	
Run wget test temporarily kubectl runrm mytestimage=busybox -it	
Run curl test temporarily kubectl runrm mytestimage=yauritux/busybox-curl -it	
kubectl run shell command kubectl exec -it mytest ls -l /etc/hosts	
Get system conf via configmap kubectl -n kube-system get cm kubeadm-config -o yaml	
kubectl run instance with replicas kubectl run my-nginximage=nginxreplicas=2port=80	
Explain resource kubectl explain pods, kubectl explain svc	
Get all services kubectl get serviceall-namespaces	
Query healthcheck endpoint curl -L http://127.0.0.1:10250/healthz	
Open a bash terminal in a pod kubectl exec -it storage sh	
Check pod environment variables kubectl exec redis-master-ft9ex env	
Enable kubectl shell autocompletion echo "source <(kubectl completion bash)" »~/.bashrc, and rele	oad
Use minikube dockerd in your laptop eval \$(minikube docker-env), No need to push docker hub any mo	re
Get services sorted by name kubectl get services –sort-by=.metadata.name	
Get pods sorted by restart count kubectl get pods –sort-by='.status.containerStatuses[0].restartCount'	
Minikube minikube cheatsheet	
Docker docker cheatsheet	

1.2 Check Performance

Name	Command
Get node resource usage	kubectl top node
Get pod resource usage	kubectl top pod
Get resource usage for a given pod	kubectl top <podname>containers</podname>
List resource utilization for all containers	kubectl top podall-namespacescontainers=true

1.3 Resources Deletion

Name	Command
Delete pod	kubectl delete pod/ <pod-name> -n <my-namespace></my-namespace></pod-name>
Delete pods by labels	kubectl delete pod -l env=test
Delete deployments by labels	kubectl delete deployment -l app=wordpress
Delete all resources filtered by labels	kubectl delete pods, services -l name=myLabel
Delete resources under a namespace	kubectl -n my-ns delete po,svcall
Delete persist volumes by labels	kubectl delete pvc -l app=wordpress
Delete statefulset only (not pods)	<pre>kubectl delete sts/<stateful_set_name>cascade=false</stateful_set_name></pre>

1.4 Pod

Name	Command
List all pods	kubectl get pods
List pods for all namespace	kubectl get pods -all-namespaces
List all critical pods	kubectl get -n kube-system pods -a
List pods with more info	kubectl get pod -o wide, kubectl get pod/ <pod-name> -o yaml</pod-name>
Get pod info	kubectl describe pod/srv-mysql-server
List all pods with labels	kubectl get podsshow-labels
Get Pod initContainer status	<pre>kubectl get podtemplate '{{.status.initContainerStatuses}}' <pod-name></pod-name></pre>
kubectl run command	kubectl exec -it -n "\$ns" "\$podname" - sh -c "echo \$msg »/dev/err.log"
Kubernetes Yaml Examples	link: kubernetes yaml templates

1.5 Pod Advanced

Name	Command
Get pod by selector	podname=\$(kubectl get pods -n \$namespace -selector="app=syslog" -o jsonpath='{.items[*]
List pods and containers	kubectl get pods -o='custom-columns=PODS:.metadata.name,CONTAINERS:.spec.container
List pods, containers and images	kubectl get pods -o='custom-columns=PODS:.metadata.name,CONTAINERS:.spec.container

1.6 Label & Annontation

Name	Command
Filter pods by label	kubectl get pods -l owner=denny
Manually add label to a pod	kubectl label pods dummy-input owner=denny
Remove label	kubectl label pods dummy-input owner-
Manually add annonation to a pod	<pre>kubectl annotate pods dummy-input my-url=https://www.dennyzhang.com</pre>

1.7 Deployment & Scale

Name	Command
Scale out	kubectl scalereplicas=3 deployment/nginx-app
online rolling upgrade	kubectl rollout app-v1 app-v2image=img:v2
Roll backup	kubectl rollout app-v1 app-v2rollback
List rollout	kubectl get rs
Check update status	kubectl rollout status deployment/nginx-app
Check update history	kubectl rollout history deployment/nginx-app
Pause/Resume	kubectl rollout pause deployment/nginx-deployment, resume
Rollback to previous version	kubectl rollout undo deployment/nginx-deployment
Kubernetes Yaml Examples	link: kubernetes yaml templates, link: Pausing and Resuming a Deployment

1.8 Quota & Limits & Resource

Name	Command
List Resource Quota	kubectl get resourcequota
List Limit Range	kubectl get limitrange
Customize resource definition	kubectl set resources deployment nginx -c=nginxlimits=cpu=200m,memory=512Mi
Kubernetes Yaml Examples	link: kubernetes yaml templates

1.9 Service

Name	Command
List all services	kubectl get services
List service endpoints	kubectl get endpoints
Get service detail	kubectl get service nginx-service -o yaml
Get service cluster ip	kubectl get service nginx-service -o go-template='{{.spec.clusterIP}}'
Get service cluster port	kubectl get service nginx-service -o go-template='{{(index .spec.ports 0).port}}}'
Expose deployment as lb service	kubectl expose deployment/my-apptype=LoadBalancername=my-service
Expose service as lb service	kubectl expose service/wordpress-1-svctype=LoadBalancername=wordpress-lb
Kubernetes Yaml Examples	link: kubernetes yaml templates

1.10 StatefulSet

Name	Command
List statefulset	kubectl get sts
Delete statefulset only (not pods)	<pre>kubectl delete sts/<stateful_set_name>cascade=false</stateful_set_name></pre>
Scale statefulset	<pre>kubectl scale sts/<stateful_set_name>replicas=5</stateful_set_name></pre>
Kubernetes Yaml Examples	link: kubernetes yaml templates

1.11 Volumes & Volume Claims

Name	Command
Check the mounted volumes	kubectl exec storage ls /data
Check persist volume	kubectl describe pv/pv0001
List storage class	kubectl get storageclass
Copy files	<pre>kubectl cp /tmp/foo <namespace1>/<pod1>:/tmp/bar</pod1></namespace1></pre>
Kubernetes Yaml Examples	link: kubernetes yaml templates

1.12 Security

Name	Command
List certificates	kubectl get csr
Kubernetes Yaml Examples	link: kubernetes yaml templates

1.13 Extensiions

Name	Summary
List api group	kubectl api-versions
List all CRD	kubectl get crd

1.14 Components & Services

 $\bullet\,$ Services on Master Nodes

Name	Summary
kube-apiserver	exposes the Kubernetes API from master nodes
etcd	reliable data store for all k8s cluster data
kube-scheduler	schedule pods to run on selected nodes
kube-controller-manager	node controller, replication controller, endpoints controller, and service account & token controllers

• Services on Worker Nodes

Name	Summary
kubelet	makes sure that containers are running in a pod
kube-proxy	perform connection forwarding
Container Runtime	Kubernetes supported runtimes: Docker, rkt, runc and any OCI runtime-spec implementation.

 \bullet Addons: pods and services that implement cluster features

Name	Summary
DNS	serves DNS records for Kubernetes services
Web UI	a general purpose, web-based UI for Kubernetes clusters
Container Resource Monitoring	collect, store and serve container metrics
Cluster-level Logging	save container logs to a central log store with search/browsing interface

\bullet Tools

Name	Summary
kubectl	the command line util to talk to k8s cluster
kubeadm	the command to bootstrap the cluster
kubefed	the command line to control a Kubernetes Cluster Federation
Kubernetes Components	link: Kubernetes Components

1.15 Other Components

1.15.1 Log files

Name	Command
API Server.log= in master node	/var.log=/kube-apiserver.log
Scheduler.log=in master node	/var.log=/kube-scheduler.log
Controller.log= in master node	/var.log=/kube-controller-manager.log
Kubelet.log= in worker node	/var.log=/kubelet.log
Kube Proxy.log= in worker node	/var.log=/kubelet-proxy.log

1.15.2 Events & Metrics

Name	Command	
View all events	kubectl get eventsall-namespace	s

1.15.3 Namespace & Security

Name	Command
List authenticated contexts	kubectl config get-contexts
Switch context	kubectl config use-context <cluster-name></cluster-name>
Delete the specified context	<pre>kubectl config delete-context <cluster-name></cluster-name></pre>
List all namespaces defined	kubectl get namespaces
kubectl config file	~/.kube/config
Kubernetes Yaml Examples	link: kubernetes yaml templates

1.15.4 Network

Name	Command
Temporarily add a port-forwarding	kubectl port-forward redis-iz109 6379
Add port-forwaring for deployment	kubectl port-forward deployment/redis-master 6379:6379
Add port-forwaring for replicaset	kubectl port-forward rs/redis-master 6379:6379
Add port-forwaring for service	kubectl port-forward svc/redis-master 6379:6379
Get network policy	kubectl get NetworkPolicy

1.16 Basic

1.16.1 Key Concepts

Name	Summary
CNCF	Cloud Native Computing Foundation
CRI	Container Runtime Interface
CNI	Container Network Interface
CSI	Container Storage Interface

1.16.2 Kubernets Critical Files

Name	Comment
Config folder	/etc/kubernetes/
Certificate files	/etc/kubernetes/pki/
Credentials to API server	/etc/kubernetes/kubelet.conf
Superuser credentials	/etc/kubernetes/admin.conf
Kubernets working dir	/var/lib/kubelet/
Docker working dir	/var/lib/docker/
Etcd working dir	/var/lib/etcd/
Network cni	/etc/cni/net.d/
Docker container log	/var/log/containers/
Log files	/var/log/pods/
Env	export KUBECONFIG=/etc/kubernetes/admin.conf
Env	/etc/systemd/system/kubelet.service.d/10-kubeadm.conf

1.16.3 Check status

Name	Summary
List everything	kubectl get allall-namespaces
Get cluster info	kubectl cluster-info
Get configuration	kubectl config view
Get kubectl version	kubectl version
Get component status	kubectl get componentstatus
Similar to docker ps	kubectl get nodes
Similar to docker inspect	kubectl describe pod/nginx-app-413181-cn
Similar to docker logs	kubectl logs
Similar to docker exec	kubectl exec
Get services for current namespace	kubectl get svc
Get node status	kubectl describe node/ <node_name></node_name>

1.16.4 Kubernetes Developer Resources

Name	Summary
API Conventions	link: API Conventions

1.17 Misc scripts

• Tail pod log by label

• Get node hardware resource utilization

• Apply the configuration in manifest yaml and delete all the other configmaps that are not in the file.

kaubectl apply --prune -f manifest.yaml --all --prune-whitelist=core/v1/ConfigMap

1.18 More Resources

License: Code is licensed under MIT License.

https://kubernetes.io/docs/reference/kubectl/cheatsheet/

https://github.com/kubecamp/kubernetes_in_2_days

https://marc.xn--wckerlin-0za.ch/computer/kubernetes-on-ubuntu-16-04

https://codefresh.io/kubernetes-guides/kubernetes-cheat-sheet/