1 Kubectl Kubernetes CheatSheet

KUBERNETES

Updated: November 28, 2018

- PDF Link: cheatsheet-kubernetes-A4.pdf, Category: kubernetes
- Blog URL: https://cheatsheet.dennyzhang.com/cheatsheet-kubernetes-A4
- \bullet Related posts: Kubernetes Yaml, #denny-cheat sheets

File me Issues or star this repo.

1.1 Common Commands

Name	Command
Run curl test temporarily	kubectl runrm mytestimage=yauritux/busybox-curl -it
Run wget test temporarily	kubectl runrm mytestimage=busybox -it
List everything	kubectl get allall-namespaces
List pods with nodes info	kubectl get pod -o wide
Show nodes with labels	kubectl get nodesshow-labels
Validate yaml file with dry run	kubectl createdry-runvalidate -f pod-dummy.yaml
Start a temporary pod for testing	kubectl runrm -i -timage=alpine test-\$RANDOM sh
kubectl run shell command	kubectl exec -it mytest ls -l /etc/hosts
Get system conf via configmap	kubectl -n kube-system get cm kubeadm-config -o yaml
kubectl run instance with replicas	kubectl run my-nginximage=nginxreplicas=2port=80
Explain resource	kubectl explain pods, kubectl explain svc
Get all services	kubectl get serviceall-namespaces
Watch pods	kubectl get pods -n wordpresswatch
Query healthcheck endpoint	curl -L http://127.0.0.1:10250/healthz
Open a bash terminal in a pod	kubectl exec -it storage sh
Check pod environment variables	kubectl exec redis-master-ft9ex env
Enable kubectl shell autocompletion	echo "source <(kubectl completion bash)" »~/.bashrc, and reload
Use minikube dockerd in your laptop	eval \$(minikube docker-env), No need to push docker hub any more
Get services sorted by name	kubectl get services –sort-by=.metadata.name
Get pods sorted by restart count	$kubectl\ get\ pods\ -sort-by='.status.containerStatuses[0].restartCount'$
Reference	minikube cheatsheet, docker cheatsheet

1.2 Check Performance

Name	Command
Get node resource usage	kubectl top node
Get pod resource usage	kubectl top pod
Get resource usage for a given pod	kubectl top <podname>containers</podname>
List resource utilization for all containers	kubectl top podall-namespacescontainers=true

1.3 Resources Deletion

Name	Command
Delete pod	kubectl delete pod/ <pod-name> -n <my-namespace></my-namespace></pod-name>
Delete pod by force	<pre>kubectl delete pod/<pod-name>grace-period=0force</pod-name></pre>
Delete pods by labels	kubectl delete pod -l env=test
Delete deployments by labels	kubectl delete deployment -l app=wordpress
Delete all resources filtered by labels	kubectl delete pods, services -l name=myLabel
Delete resources under a namespace	kubectl -n my-ns delete po,svcall
Delete persist volumes by labels	kubectl delete pvc -l app=wordpress
Delete statefulset only (not pods)	<pre>kubectl delete sts/<stateful_set_name>cascade=false</stateful_set_name></pre>

1.4 Pod

Name	Command
List all pods	kubectl get pods
List pods for all namespace	kubectl get pods -all-namespaces
List all critical pods	kubectl get -n kube-system pods -a
List pods with more info	kubectl get pod -o wide, kubectl get pod/ <pod-name> -o yaml</pod-name>
Get pod info	kubectl describe pod/srv-mysql-server
List all pods with labels	kubectl get podsshow-labels
Get Pod initContainer status	<pre>kubectl get podtemplate '{{.status.initContainerStatuses}}' <pod-name></pod-name></pre>
kubectl run command	kubectl exec -it -n "\$ns" "\$podname" - sh -c "echo \$msg »/dev/err.log"
Kubernetes Yaml Examples	Link: kubernetes yaml templates

1.5 Pod Advanced

Name	Command
Watch pods	kubectl get pods -n wordpresswatch
Get pod by selector	podname=\$(kubectl get pods -n \$namespace -selector="app=syslog" -o jsonpath='{.items[*]
List pods and containers	kubectl get pods -o='custom-columns=PODS:.metadata.name,CONTAINERS:.spec.container
List pods, containers and images	$kubectl\ get\ pods\ -o='custom-columns=PODS:.metadata.name, CONTAINERS:.spec.containers and the contraction of the contractio$

1.6 Label & Annontation

Name	Command
Filter pods by label	kubectl get pods -l owner=denny
Manually add label to a pod	kubectl label pods dummy-input owner=denny
Remove label	kubectl label pods dummy-input owner-
Manually add annonation to a pod	kubectl annotate pods dummy-input my-url=https://www.dennyzhang.com

1.7 Deployment & Scale

Name	Command
Scale out	kubectl scalereplicas=3 deployment/nginx-app
online rolling upgrade	kubectl rollout app-v1 app-v2image=img:v2
Roll backup	kubectl rollout app-v1 app-v2rollback
List rollout	kubectl get rs
Check update status	kubectl rollout status deployment/nginx-app
Check update history	kubectl rollout history deployment/nginx-app
Pause/Resume	kubectl rollout pause deployment/nginx-deployment, resume
Rollback to previous version	kubectl rollout undo deployment/nginx-deployment
Kubernetes Yaml Examples	Link: kubernetes yaml templates, Link: Pausing and Resuming a Deployment

1.8 Quota & Limits & Resource

Name	Command
Customize resource definition	kubectl set resources deployment nginx -c=nginxlimits=cpu=200m,memory=512Mi
List Resource Quota	kubectl get resourcequota
List Limit Range	kubectl get limitrange
Customize resource definition	kubectl set resources deployment nginx -c=nginxlimits=cpu=200m,memory=512Mi
Kubernetes Yaml Examples	Link: kubernetes yaml templates

1.9 Service

Updated: November 28, 2018

Name	Command
List all services	kubectl get services
List service endpoints	kubectl get endpoints
Get service detail	kubectl get service nginx-service -o yaml
Get service cluster ip	kubectl get service nginx-service -o go-template='{{.spec.clusterIP}}'
Get service cluster port	kubectl get service nginx-service -o go-template='{{(index .spec.ports 0).port}}}'
Expose deployment as lb service	kubectl expose deployment/my-apptype=LoadBalancername=my-service
Expose service as lb service	kubectl expose service/wordpress-1-svctype=LoadBalancername=wordpress-lb
Kubernetes Yaml Examples	Link: kubernetes yaml templates

Updated: November 28, 2018

1.10 StatefulSet

Name	Command
List statefulset	kubectl get sts
Delete statefulset only (not pods)	<pre>kubectl delete sts/<stateful_set_name>cascade=false</stateful_set_name></pre>
Scale statefulset	<pre>kubectl scale sts/<stateful_set_name>replicas=5</stateful_set_name></pre>
Kubernetes Yaml Examples	Link: kubernetes yaml templates

1.11 Patch

Name	Command		
Patch service to loadbalancer	kubectl patch svc	"\$APP_INSTANCE_NAME-grafana" -p '{"spec":	{"type": "LoadBalan

1.12 Volumes & Volume Claims

Name	Command
Check the mounted volumes	kubectl exec storage ls /data
Check persist volume	kubectl describe pv/pv0001
List storage class	kubectl get storageclass
Copy files	<pre>kubectl cp /tmp/foo <namespace1>/<pod1>:/tmp/bar</pod1></namespace1></pre>
Kubernetes Yaml Examples	Link: kubernetes yaml templates

1.13 Node Maintenance

Name	Command
Mark node as unschedulable	kubectl cordon \$NDOE_NAME
Mark node as schedulable	kubectl uncordon \$NDOE_NAME
Drain node in preparation for maintenance	kubectl drain \$NODE NAME

1.14 Security

Name	Command
List certificates	kubectl get csr
Kubernetes Yaml Examples	Link: kubernetes yaml templates

1.15 Extensiions

Name	Summary
List api group	kubectl api-versions
List all CRD	kubectl get crd
List storageclass	kubectl get storageclass

1.16 Components & Services

1.16.1 Key Concepts

$_{ m Name}$	Summary
CNCF	Cloud Native Computing Foundation
CRI	Container Runtime Interface
CNI	Container Network Interface
CSI	Container Storage Interface

1.16.2 Services on Master Nodes

Name	Summary
kube-apiserver	exposes the Kubernetes API from master nodes
etcd	reliable data store for all k8s cluster data
kube-scheduler	schedule pods to run on selected nodes
kube-controller-manager	node controller, replication controller, endpoints controller, and service account & token controllers

Updated: November 28, 2018

1.16.3 Services on Worker Nodes

Name	Summary	
kubelet	makes sure that containers are running in a pod	
kube-proxy	perform connection forwarding	
Container Runtime	Kubernetes supported runtimes: Docker, rkt, runc and any OCI runtime-spec implementation.	

1.16.4 Addons: pods and services that implement cluster features

Name	Summary
DNS	serves DNS records for Kubernetes services
Web UI	a general purpose, web-based UI for Kubernetes clusters
Container Resource Monitoring	collect, store and serve container metrics
Cluster-level Logging	save container logs to a central log store with search/browsing interface

1.16.5 Tools

Name	Summary
kubectl	the command line util to talk to k8s cluster
kubeadm	the command to bootstrap the cluster
kubefed	the command line to control a Kubernetes Cluster Federation
Kubernetes Components	Link: Kubernetes Components

1.16.6 Kubernets Critical Files

Name	Comment
Config folder	/etc/kubernetes/
Certificate files	/etc/kubernetes/pki/
Credentials to API server	/etc/kubernetes/kubelet.conf
Superuser credentials	/etc/kubernetes/admin.conf
Kubernets working dir	/var/lib/kubelet/
Docker working dir	/var/lib/docker/
Etcd working dir	/var/lib/etcd/
Network cni	/etc/cni/net.d/
Docker container log	/var/log/containers/
Log files	/var/log/pods/
Env	export KUBECONFIG=/etc/kubernetes/admin.conf
Env	/etc/systemd/system/kubelet.service.d/10-kubeadm.conf

1.17 Other Components

1.17.1 Log files

Name	Command
API Server.log= in master node	/var.log=/kube-apiserver.log
Scheduler.log= in master node	/var.log=/kube-scheduler.log
Controller.log= in master node	/var.log=/kube-controller-manager.log
Kubelet.log= in worker node	/var.log=/kubelet.log
Kube Proxy.log= in worker node	/var.log=/kubelet-proxy.log

1.17.2 Events & Metrics

Name	Command
View all events	kubectl get eventsall-namespaces

1.17.3 Namespace & Security

Name	Command
List authenticated contexts	kubectl config get-contexts
Load context from config file	<pre>kubectl get cskubeconfig kube_config.yml</pre>
Switch context	<pre>kubectl config use-context <cluster-name></cluster-name></pre>
Delete the specified context	<pre>kubectl config delete-context <cluster-name></cluster-name></pre>
List all namespaces defined	kubectl get namespaces
kubectl config file	~/.kube/config
Kubernetes Yaml Examples	link: kubernetes yaml templates

1.17.4 Network

Name	Command
Temporarily add a port-forwarding	kubectl port-forward redis-iz109 6379
Add port-forwaring for deployment	kubectl port-forward deployment/redis-master 6379:6379
Add port-forwaring for replicaset	kubectl port-forward rs/redis-master 6379:6379
Add port-forwaring for service	kubectl port-forward svc/redis-master 6379:6379
Get network policy	kubectl get NetworkPolicy

1.18 More Resources

License: Code is licensed under MIT License.

https://kubernetes.io/docs/reference/kubectl/cheatsheet/

https://github.com/kubecamp/kubernetes_in_2_days

https://marc.xn--wckerlin-0za.ch/computer/kubernetes-on-ubuntu-16-04

https://codefresh.io/kubernetes-guides/kubernetes-cheat-sheet/

https://github.com/kubernetes/community/blob/master/contributors/devel/api-conventions.md

Updated: November 28, 2018