Path dependencies

Which crate uses which, read from Cargo.toml; the build stops on an upward edge

	a2a conformance	a2a-types	bus-mem	bus-api	bus-nats	a2a-mcp	a2a-audit	a2a workspace	a2a security	a2a-core	a2a-client	a2a-worker	driver a2a-http	driver-acp	gateway http	a2a-cli	a2a-tui	a2ad	deps
a2ad L5		●		●	●		●	●	●	●	●	●	●	●	●			·	12
a2a-tui L5		●		●	●		●		●	●	●						·		7
a2a-cli L5		●		●	●		●		●	●	●					·			7
gateway-http L4		●		●						●	●				·				4
driver-acp L4										●		●		·					2
driver-a2a-http L4		●										●	·						2
a2a-worker L3		●		●		●	●	●	●	●	●	·							8
a2a-client L3		●		●					●	●	·								4
a2a-core L2		●		●						·									2
a2a-security L2		●							·										1
a2a-workspace L2								·											0
a2a-audit L2		●					·												1
a2a-mcp L2						·													0
bus-nats L1		●		●	·														2
bus-api L1		●		·															1
bus-mem L1		●	·	●															2
a2a-types L0		·																	0
a2a-conformance test	·	●	●	●		●		●		●	●	●			●				9

Reading the grid

- Row uses column. Green: a lower layer. Amber: same layer (see the card on the right).
- Layers come from RFC-0001 sec 4.2; the dependency set is read from Cargo.toml.

Checks run at build time

- No dependency points up the stack; the build stops if one does.
- Same-layer edges: a2a-worker to a2a-client; bus-mem to bus-api; bus-nats to bus-api.