Crates by layer

Crates in the RFC-0001 layers, with line and test-attribute counts

L5 executables

a2ad
supervisor, broker, child hosts
9,068 lines, 149 test attributes
D-01 P-01

a2a-tui
operator terminal UI
4,624 lines, 80 test attributes

a2a-cli
command line (binary a2a)
3,727 lines, 45 test attributes

L4 drivers and gateway

gateway-http
HTTP ingress, TLS, agent cards
4,345 lines, 62 test attributes
G-01

driver-acp
ACP driver for omp and Claude Code
4,892 lines, 73 test attributes

driver-a2a-http
driver for an A2A HTTP backend
3,896 lines, 75 test attributes

L3 worker and client

a2a-worker
turn engine, approvals, delegation
12,368 lines, 140 test attributes

a2a-client
peer client, signing, envelopes
3,441 lines, 25 test attributes

L2 core libraries

a2a-core
tasks, approvals, budgets, envelopes
10,270 lines, 219 test attributes
R-01

a2a-security
identity, trust, redaction, cards
8,267 lines, 211 test attributes

a2a-workspace
workspace binding
4,182 lines, 56 test attributes

a2a-audit
hash-chained audit, spool, sinks
6,937 lines, 145 test attributes
A-01

a2a-mcp
MCP tool shim (a2abus-mcp-shim)
3,381 lines, 34 test attributes

L1 bus abstraction and bindings

bus-nats
NATS JetStream binding
4,361 lines, 55 test attributes

bus-api
Bus trait and message model
2,022 lines, 23 test attributes

bus-mem
in-memory bus for tests
2,403 lines, 12 test attributes

L0 shared types

a2a-types
A2A v1.0 types and ids
2,387 lines, 63 test attributes

Reading this page

- Bands are the RFC-0001 layers (sec 4.1). A crate may depend on its own or a lower band.
- Drawn from reading the code; the layer table is RFC-0001 sec 4.2.

Counts

- Lines: every .rs file under the crate, tests included. Test attributes: #[test] and #[x::test], scanned at build time (not the runtime pass count).
- 64 path dependencies in [dependencies] (dev-dependencies not drawn).

Exceptions

- Same-layer edges: a2a-worker to a2a-client; bus-mem to bus-api; bus-nats to bus-api.
- a2a-conformance is a test crate and sits outside the stack.