

2012-09-23
13:57:41

Real World OCaml

Jason Hickey, Anil Madhavapeddy, and Yaron Minsky

O'REILLY®
Beijing • Cambridge • Farnham • Köln • Sebastopol • Tokyo

2012-09-23

13:57:41

Real World OCaml

by Jason Hickey, Anil Madhavapeddy, and Yaron Minsky

Copyright © 2010 O'Reilly Media . All rights reserved.

Printed in the United States of America.

Published by O'Reilly Media, Inc., 1005 Gravenstein Highway North, Sebastopol, CA 95472.

O'Reilly books may be purchased for educational, business, or sales promotional use. Online editions are also available for most titles (<http://my.safaribooksonline.com>). For more information, contact our corporate/institutional sales department: (800) 998-9938 or corporate@oreilly.com.

Editor: Mike Loukides

Production Editor:

Copyeditor:

Proofreader: FIX ME!

Indexer:

Cover Designer:

Interior Designer: FIX ME!

Illustrator: Robert Romano

March 2013: First Edition.

Revision History for the First Edition:

YYYY-MM-DD First release

See <http://oreilly.com/catalog/errata.csp?isbn=9781449323912> for release details.

Nutshell Handbook, the Nutshell Handbook logo, and the O'Reilly logo are registered trademarks of O'Reilly Media, Inc. !!FILL THIS IN!! and related trade dress are trademarks of O'Reilly Media, Inc.

Many of the designations used by manufacturers and sellers to distinguish their products are claimed as trademarks. Where those designations appear in this book, and O'Reilly Media, Inc. was aware of a trademark claim, the designations have been printed in caps or initial caps.

While every precaution has been taken in the preparation of this book, the publisher and authors assume no responsibility for errors or omissions, or for damages resulting from the use of the information contained herein.

ISBN: 978-1-449-32391-2

[?]

1348423080

Table of Contents

Preface vii

1. Prologue 1

Why OCaml? 1

Why Core? 2

About the Authors 2

Jason Hickey 2

Anil Madhavapeddy 3

Yaron Minsky 3

2. A Guided Tour 5

OCaml as a calculator 5

Functions and Type Inference 7

Tuples, Lists, Options and Pattern-matching 9

Tuples 9

Lists 10

Options 14

Records and Variants 15

Imperative programming 16

Arrays 17

Mutable record fields 17

Refs 18

For and while loops 19

Where to go from here 19

3. Variables and Functions 21

Variables 21

Pattern matching and let 23

let/and bindings 24

Functions 24

Anonymous Functions 24

Multi-argument functions	26
Recursive functions	27
Prefix and Infix operators	28
Declaring functions with <code>function</code>	30
Labeled Arguments	31
Optional arguments	33
4. Lists, Options and Patterns	39
Example: pretty-printing a table	39
Computing the widths	40
Rendering the rows	40
Bringing it all together	41
5. Records and Variants	45
Records	45
Pattern matching	46
Field punning	47
Reusing field names	48
Functional updates	51
First-class fields	52
Variants	54
Example: terminal colors	54
Combining records and variants	58
Polymorphic variants	61
More advanced declarations	61
Polymorphic types	61
Recursive types	61
6. Error Handling	63
Error-aware return types	63
Encoding errors with <code>Result</code>	64
<code>Error</code> and <code>Or_error</code>	65
<code>bind</code> and other error-handling idioms	66
Exceptions	67
Exception handlers	69
Cleaning up in the presence of exceptions	69
Catching specific exceptions	70
Backtraces	71
Exceptions for control flow	72
From exceptions to error-aware types and back again	72
7. Files, Modules and Programs	73
Single File Programs	73

Multi-file programs and modules	76
Signatures and Abstract Types	77
More on modules and signatures	79
Concrete types in signatures	79
The <code>include</code> directive	80
Modules within a file	81
Opening modules	82
Common errors with modules	83
8. Functors and First-Class Modules	87
Functors	87
A trivial example	87
A bigger example: computing with intervals	89
Extending modules	97
First class modules	99
Another trivial example	100
Standard vs. first-class modules	102
A more complete example -- containers	104
Dynamically choosing a module	107
Example: A service bundle	108
9. Syntax Extensions	113
Serialization with s-expressions	113
Sexplib	115
Formatting of s-expressions	115
Sexp converters	115
Getting good error messages	118
Sexp-conversion directives	119
Bin_prot	120
Fieldslib	122
10. Object Oriented Programming	125
When to use objects	125
OCaml objects	126
Object Polymorphism	127
Classes	129
Class parameters and polymorphism	130
Object types	131
Immutable objects	134
Class types	135
Subtyping	137
Using more precise types to address subtyping problems	139
Using elided types to address subtyping problems	139

Narrowing	140
Binary methods	142
Private methods	144
Virtual classes and methods	146
Multiple inheritance	148
How names are resolved	148
Mixins	150
11. Concurrent Programming with Lwt	153
Timing and Thread Composition	154
Syntax Extensions	156
Cancellation	156
A simple TCP Echo Server	156
Onto an HTTP Server	156
Binding to the Github API	156
12. DocBook Playground	157
Cross reference example	158
13. Installation	159
Base Installation	159
MacOS X	159
Windows	159
Linux	159
Useful Libraries	159
Environment	159
Command Line	159
Editors	160

Preface

Conventions Used in This Book

The following typographical conventions are used in this book:

Italic

Indicates new terms, URLs, email addresses, filenames, and file extensions.

Constant width

Used for program listings, as well as within paragraphs to refer to program elements such as variable or function names, databases, data types, environment variables, statements, and keywords.

Constant width bold


Shows commands or other text that should be typed literally by the user.

Constant width italic

Shows text that should be replaced with user-supplied values or by values determined by context.



This icon signifies a tip, suggestion, or general note.



This icon indicates a warning or caution.

Using Code Examples


This book is here to help you get your job done. In general, you may use the code in this book in your programs and documentation. You do not need to contact us for permission unless you're reproducing a significant portion of the code. For example, writing a program that uses several chunks of code from this book does not require permission. Selling or distributing a CD-ROM of examples from O'Reilly books does

require permission. Answering a question by citing this book and quoting example code does not require permission. Incorporating a significant amount of example code from this book into your product's documentation does require permission.

We appreciate, but do not require, attribution. An attribution usually includes the title, author, publisher, and ISBN. For example: "*Book Title* by Some Author (O'Reilly). Copyright 2012 Some Copyright Holder, 978-0-596-xxxx-x."

If you feel your use of code examples falls outside fair use or the permission given above, feel free to contact us at permissions@oreilly.com.

Safari® Books Online

 Safari Books Online (www.safaribooksonline.com) is an on-demand digital library that delivers expert content in both book and video form from the world's leading authors in technology and business. Technology professionals, software developers, web designers, and business and creative professionals use Safari Books Online as their primary resource for research, problem solving, learning, and certification training.

Safari Books Online offers a range of product mixes and pricing programs for organizations, government agencies, and individuals. Subscribers have access to thousands of books, training videos, and prepublication manuscripts in one fully searchable database from publishers like O'Reilly Media, Prentice Hall Professional, Addison-Wesley Professional, Microsoft Press, Sams, Que, Peachpit Press, Focal Press, Cisco Press, John Wiley & Sons, Syngress, Morgan Kaufmann, IBM Redbooks, Packt, Adobe Press, FT Press, Apress, Manning, New Riders, McGraw-Hill, Jones & Bartlett, Course Technology, and dozens more. For more information about Safari Books Online, please visit us online.

How to Contact Us

Please address comments and questions concerning this book to the publisher:

O'Reilly Media, Inc.
1005 Gravenstein Highway North
Sebastopol, CA 95472
800-998-9938 (in the United States or Canada)
707-829-0515 (international or local)
707-829-0104 (fax)

We have a web page for this book, where we list errata, examples, and any additional information. You can access this page at:

<http://www.oreilly.com/catalog/<catalog page>>

Don't forget to update the `<url>` attribute, too.

2012-09-23

13:57:42

To comment or ask technical questions about this book, send email to:

bookquestions@oreilly.com

For more information about our books, courses, conferences, and news, see our website at *http://www.oreilly.com*.

Find us on Facebook: *http://facebook.com/oreilly*

Follow us on Twitter: *http://twitter.com/oreillymedia*

Watch us on YouTube: *http://www.youtube.com/oreillymedia*

2012-09-23

13:57:42

CHAPTER 1

Prologue

(yminsky: this is something of a placeholder. We need a real introduction that should talk, amongst other things, about what kinds of applications OCaml is good for and why one should want to learn it. Also, some coverage of who uses OCaml successfully now.)

Why OCaml?

Programming languages matter.

The programming languages that you use affect your productivity. They affect how reliable your software is, how efficient it is, how easy it is to read, to refactor, and to extend. And the programming languages you know and use can deeply affect how you think about programming and software design.

But not all ideas about how to design a programming language are created equal. Over the last 40 years, a few key language features have emerged that together form a kind of sweet-spot in language design. These features include:

- Garbage collection
- First-class and higher-order functions
- Static type-checking
- Parametric polymorphism
- Support for programming with immutable values
- Algebraic datatypes and pattern-matching
- Type inference

Some of these features you already know and love, and some are probably new to you. But as we hope to demonstrate over the course of this book, it turns out that there is something transformative about having them all together and able to interact with each other in a single language.

Despite their importance, these ideas have made only limited inroads into mainstream languages. And when they do arrive there, like higher-order functions in C# or parametric polymorphism in Java, it's typically in a limited and awkward form. The only languages that support these ideas well are statically-typed functional programming languages like OCaml, F#, Haskell, Scala and Standard-ML.

Among this worthy set of languages, OCaml stands apart because it manages to provide a great deal of power while remaining highly pragmatic, highly performant, and comparatively simple to use and understand. It is this that makes OCaml a great choice for programmers who want to step up to a better programming language, and at the same time want to get practical work done.

Why Core?

A language on its own isn't enough. You also need a rich set of libraries to base your applications on. A common source of frustration for those learning OCaml is that the standard library that ships with the OCaml compiler is not ideal. While it's well implemented, it covers only a small subset of the functionality you expect from a standard library, and the interfaces are idiosyncratic and inconsistent.

But all is not lost! There is an effective alternative to the OCaml standard library called Core. Jane Street, a company that has been using OCaml for nearly a decade, developed Core for its own internal use, but it was designed from the start with an eye towards being a general-purpose standard library. Core is also distributed with syntax-extensions which provide essential new functionality to OCaml; and there are additional libraries, like `Core_extended` and `Async`, that provide even more useful functionality.

We believe that Core makes OCaml a better tool, and that's why we'll present OCaml and Core together.

About the Authors

Jason Hickey

Jason Hickey is a Software Engineer at Google Inc. in Mountain View, California. He is part of the team that designs and develops the global computing infrastructure used to support Google services, including the software systems for managing and scheduling massively distributed computing resources.

Prior to joining Google, Jason was an Assistant Professor of Computer Science at Caltech, where his research was in reliable and fault-tolerant computing systems, including programming language design, formal methods, compilers, and new models of distributed computation. He obtained his PhD in Computer Science from Cornell University, where he studied programming languages. He is the author of the MetaPRL

system, a logical framework for design and analysis of large software systems; OMake, an advanced build system for large software projects. He is the author of the textbook, *An Introduction to Objective Caml* (unpublished).

Anil Madhavapeddy

Anil Madhavapeddy is a Senior Research Fellow at the University of Cambridge, based in the Systems Research Group. He was on the original team that developed the Xen hypervisor, and helped develop an industry-leading cloud management toolstack written entirely in OCaml. This XenServer product has been deployed on hundreds of thousands of physical hosts, and drives critical infrastructure for many Fortune 500 companies.

Prior to obtaining his PhD in 2006 from the University of Cambridge, Anil had a diverse background in industry at Network Appliance, NASA and Internet Vision. In addition to professional and academic activities, he is an active member of the open-source development community with the OpenBSD operating system, is co-chair of the Commercial Uses of Functional Programming workshop, and serves on the boards of startup companies such as Ashima Arts where OCaml is extensively used.

Yaron Minsky

Yaron Minsky heads the Technology group at Jane Street, a proprietary trading firm that is the largest industrial user of OCaml. He was responsible for introducing OCaml to the company and for managing the company's transition to using OCaml for all of its core infrastructure. Today, billions of dollars worth of securities transactions flow each day through those systems.

Yaron obtained his PhD in Computer Science from Cornell University, where he studied distributed systems. Yaron has lectured, blogged and written about OCaml for years, with articles published in Communications of the ACM and the Journal of Functional Programming. He chairs the steering committee of the Commercial Users of Functional Programming, and is a member of the steering committee for the International Conference on Functional Programming.

2012-09-23

13:57:42

CHAPTER 2

A Guided Tour

This chapter gives an overview of OCaml by walking through a series of small examples that cover most of the major features. This should give a sense of what OCaml can do, without going into too much detail about any particular topic.

We'll present this guided tour using the OCaml toplevel, an interactive shell that lets you type in expressions and evaluate them interactively. When you get to the point of running real programs, you'll want to leave the toplevel behind, but it's a great tool for getting to know the language.

You should have a working toplevel as you go through this chapter, so you can try out the examples as you go. There is a zero-configuration browser-based toplevel that you can use for this, which you can find here:

<http://realworldocaml.org/core-top>

Or you can install OCaml and Core on your computer directly. Instructions for this are found in Appendix {???}.

OCaml as a calculator

Let's spin up the toplevel and open the `Core.Std` module, which gives us access to Core's libraries, and then try out a few simple numerical calculations.

```
$ rlwrap ocaml
Objective Caml version 3.12.1

# open Core.Std;;
# 3 + 4;;
- : int = 7
# 8 / 3;;
- : int = 2
# 3.5 +. 6.;;
- : float = 9.5
```

```
# sqrt 9.;;
- : float = 3.
```

This looks a lot what you'd expect from any language, but there are a few differences that jump right out at you.

- We needed to type `;;` in order to tell the toplevel that it should evaluate an expression. This is a peculiarity of the toplevel that is not required in compiled code.
- After evaluating an expression, the toplevel spits out both the type of the result and the result itself.
- Function application in OCaml is syntactically unusual, in that function arguments are written out separated by spaces, rather than being demarcated by parentheses and commas.
- OCaml carefully distinguishes between `float`, the type for floating point numbers and `int`. The types have different literals (`6.` instead of `6`) and different infix operators (`+.` instead of `+`), and OCaml doesn't do any automated casting between the types. This can be a bit of a nuisance, but it has its benefits, since it prevents some classes of bugs that arise from confusion between the semantics of `int` and `float`.

We can also create variables to name the value of a given expression, using the `let` syntax.

```
# let x = 3 + 4;;
val x : int = 7
# let y = x + x;;
val y : int = 14
```

After a new variable is created, the toplevel tells us the name of the variable, in addition to its type and value.

The above examples are of top-level variables. We can introduce a *local* variable that exists only for the purpose of evaluating a single expression using `let` and `in`:

```
# let z = 3 in z + z;;
- : int = 6
# z;;
Characters 0-1:
  z;;
  ^
Error: Unbound value z
```

Note that `z` is a valid variable in the scope of the expression `z + z`, but that it doesn't exist thereafter.

We can also define multiple local variables using nested `let/in` expressions.

```
# let x = 3 in
  let y = 4 in
```



```
x * y ;;  
- : int = 12
```

Functions and Type Inference

The `let` syntax can also be used for creating functions:

```
# let square x = x * x ;;  
val square : int -> int = <fun>  
# square (square 2);;  
- : int = 16
```

Now that we're creating more interesting values, the types have gotten more interesting too. `int -> int` is a function type, in this case indicating a function that takes an `int` and returns an `int`. We can also write functions that take multiple arguments:

```
# let abs_diff x y =  
  abs (x - y) ;;  
val abs_diff : int -> int -> int = <fun>
```

and even functions that take other functions as arguments:

```
# let abs_change f x =  
  abs_diff (f x) x ;;  
val abs_change : (int -> int) -> int -> int = <fun>  
# abs_change square 10;;  
- : int = 90
```

This notation for multi-argument functions may be a little surprising at first, but we'll explain where it comes from when we get to function currying in Chapter 3. For the moment, think of the arrows as separating different arguments of the function, with the type after the final arrow being the return value of the function. Thus,

```
int -> int -> int
```

describes a function that takes two `int` arguments and returns an `int`, while

```
(int -> int) -> int -> int
```

describes a function of two arguments where the first argument is itself a function.

As the types we encounter get more complicated, you might ask yourself how OCaml is able to determine these types, given that we didn't write down any explicit type information. It turns out that OCaml is able to determine the type of a new expression using a technique called *type-inference*, by which it infers the type of a new expression based on what it already knows about the types of other related variables. For example, in `abs_change` above, the fact that `abs_diff` is already known to take two integer arguments lets the compiler infer that `x` is an `int` and that `f` returns an `int`.

Sometimes, there isn't enough information to fully determine the concrete type of a given value. Consider this function.

```
# let first_if_true test x y =
  if (test x) then x else y;;
```

`first_if_true` takes as its arguments a function `test`, and two values, `x` and `y`, where `x` is to be returned if `(test x)` evaluates to `true`, and `y` otherwise. So what's the type of `first_if_true`? There are no obvious clues such as arithmetic operators to tell you what the type of `x` and `y` are, which makes it seem like one could use this `first_if_true` on values of any type. Indeed, if we look at the type returned by the toplevel:

```
val first_if_true : ('a -> bool) -> 'a -> 'a -> 'a = <fun>
```

we see that rather than choose a single concrete type, OCaml has introduced a *type variable* `'a` to express that the type is generic. In particular, the type of the `test` argument is `('a -> bool)`, which means that `test` is a one-argument function whose return value is `bool`, and whose argument could be of any type `'a`. But, whatever type `'a` is, it has to be the same as the type of the other two arguments, `x` and `y`.

This genericity means that we can write:

```
# let long_string s = String.length s > 6;;
val long_string : string -> bool = <fun>
# first_if_true long_string "short" "loooooong";;
- : string = "loooooong"
```

And we can also write:

```
# let big_number x = x > 3;;
val big_number : int -> bool = <fun>
# first_if_true big_number 4 3;;
- : int = 4
```

But we can't mix and match two different concrete types for `'a` in the same use of `first_if_true`.

```
# first_if_true big_number "short" "loooooong";;
Characters 25-30:
  first_if_true big_number "short" "loooooong";;
                                ^^^^^^^
```

```
Error: This expression has type string but
      an expression was expected of type int
```

In this example, `big_number` requires that `'a` be of type `int`, whereas `"short"` and `"loooooong"` require that `'a` be of type `string`, and they can't all be right at the same time. This kind of genericity is called *parametric polymorphism*, and is very similar to generics in C# and Java.

Type errors vs exceptions

There's a big difference in OCaml (and really in any compiled language) between errors that are caught at compile time and those that are caught at run-time. It's better to catch errors as early as possible in the development process, and compilation time is best of all.

Working in the top-level somewhat obscures the difference between run-time and compile time errors, but that difference is still there. Generally, type errors, like this one:

```
# 3 + "potato";;
Characters 4-12:
  3 + "potato";;
    ^^^^^^^^
Error: This expression has type string but an expression was expected of type
      int
```

are compile-time errors, whereas an error that can't be caught by the type system, like division by zero, leads to a runtime exception.

```
# 3 / 0;;
Exception: Division_by_zero.
```

One important distinction is that type errors will stop you whether or not the offending code is ever actually executed. Thus, you get an error from typing in this code:

```
# if 3 < 4 then 0 else 3 + "potato";;
Characters 25-33:
  if 3 < 4 then 0 else 3 + "potato";;
                        ^^^^^^^^
Error: This expression has type string but an expression was expected of type
      int
```

but this code works fine.

```
# if 3 < 4 then 0 else 3 / 0;;
- : int = 0
```

Tuples, Lists, Options and Pattern-matching

Tuples

So far we've encountered a handful of basic types like `int`, `float` and `string` as well as function types like `string -> int`. But we haven't yet talked about any data structures. We'll start by looking at a particularly simple data structure, the tuple. You can create a tuple by joining values together with a comma:

```
# let tup = (3,"three");;
val tup : int * string = (3, "three")
```

The type `int * string` corresponds to the set of pairs of ints and strings. For the mathematically inclined, the `*` character is used because the space of all 2-tuples of type `t * s` corresponds to the Cartesian product of `t` and `s`.

You can extract the components of a tuple using OCaml's pattern-matching syntax. For example:

```
# let (x,y) = tup;;
val x : int = 3
val y : string = "three"
```

Here, the `(x,y)` on the left-hand side of the `let` is the pattern. This pattern lets us mint the new variables `x` and `y`, each bound to different components of the value being matched. Note that the same syntax is used both for constructing and for pattern-matching on tuples.

Here's an example of how you might use pattern matching in practice: a function for computing the distance between two points on the plane, where each point is represented as a pair of floats.

```
# let distance p1 p2 =
  let (x1,y1) = p1 in
  let (x2,y2) = p2 in
  sqrt ((x1 -. x2) ** 2. +. (y1 -. y2) ** 2.)
;;
val distance : float * float -> float * float -> float = <fun>
```

We can make this code more concise by doing the pattern matching on the arguments to the function directly.

```
# let distance (x1,y1) (x2,y2) =
  sqrt ((x1 -. x2) ** 2. +. (y1 -. y2) ** 2.)
;;
```

This is just a first taste of pattern matching. We'll see that pattern matching shows up in many contexts in OCaml, and turns out to be a surprisingly powerful and pervasive tool.

Lists

Where tuples let you combine a fixed number of items, potentially of different types, lists let you hold any number of items of the same type. For example:

```
# let languages = ["OCaml";"Perl";"C"];;
val languages : string list = ["OCaml"; "Perl"; "C"]
```

Note that you can't mix elements of different types on the same list, as we did with tuples.

```
# let numbers = [3;"four";5];;
Characters 17-23:
  let numbers = [3;"four";5];;
                ^^^^^^
```

```
Error: This expression has type string but an expression was expected of type
      int
```

In addition to constructing lists using brackets, we can use the operator `::` for adding elements to the front of a list.

```
# "French" :: "Spanish" :: languages;;
- : string list = ["French"; "Spanish"; "OCaml"; "Perl"; "C"]
```

Here, we're creating a new extended list, not changing the list we started with, as we can see.

```
# languages;;
- : string list = ["OCaml"; "Perl"; "C"]
```

The bracket notation for lists is really just syntactic sugar for `::`. Thus, the following declarations are all equivalent. Note that `[]` is used to represent the empty list.

```
# [1; 2; 3];;
- : int list = [1; 2; 3]
# 1 :: (2 :: (3 :: []));;
- : int list = [1; 2; 3]
# 1 :: 2 :: 3 :: [];;
- : int list = [1; 2; 3]
```

Thus, `::` and `[]`, which are examples of what are called *type-constructors*, are the basic building-blocks for lists.

Basic list patterns

The elements of a list can be accessed through pattern-matching. List patterns are fundamentally based on the two list constructors, `[]` and `::`. Here's a simple example.

```
# let (my_favorite :: the_rest) = languages ;;
val my_favorite : string = "OCaml"
val the_rest : string list = ["Perl"; "C"]
```

By pattern matching using `::`, we've broken off the first element of `languages` from the rest of the list. If you know Lisp or Scheme, what we've done is the equivalent of using `car` and `cdr` to break down a list.

If you tried the above example in the toplevel, you probably noticed that we omitted a warning generated by the compiler. Here's the full output:

```
# let (my_favorite :: the_rest) = languages ;;
Characters 5-28:
  let (my_favorite :: the_rest) = languages ;;
      ^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^
Warning 8: this pattern-matching is not exhaustive.
Here is an example of a value that is not matched:
[]
val my_favorite : string = "OCaml"
val the_rest : string list = ["Perl"; "C"]
```

The warning comes because the compiler can't be certain that the pattern match won't lead to a runtime error, and the warnings gives an example of the problem, the empty list, []. Indeed, if we try to use such a pattern-match on the empty list:

```
# let (my_favorite :: the_rest) = [];;
Characters 5-28:
  let (my_favorite :: the_rest) = [];;
      ^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^
Warning 8: this pattern-matching is not exhaustive.
Here is an example of a value that is not matched:
[]
Exception: (Match_failure "" 1 5).
```

we get a runtime error in addition to the compilation warning.

You can avoid these warnings, and more importantly make sure that your code actually handles all of the possible cases, by using a `match` statement. Here's an example:

```
# let my_favorite_language languages =
  match languages with
  | first :: the_rest -> first
  | [] -> "OCaml" (* A good default! *)
;;
val my_favorite_language : string list -> string = <fun>
# my_favorite_language ["English";"Spanish";"French"];
- : string = "English"
# my_favorite_language [];
- : string = "OCaml"
```

Recursive list functions

If we combine pattern matching with a recursive function call, we can do things like define a function for summing the elements of a list.

```
# let rec sum l =
  match l with
  | [] -> 0
  | hd :: tl -> hd + sum tl
;;
val sum : int list -> int
# sum [1;2;3;4;5];
- : int = 15
```

We had to add the `rec` keyword in the definition of `sum` to allow `sum` to refer to itself. We can introduce more complicated list patterns as well. Here's a function for destuttering a list, *i.e.*, for removing sequential duplicates.

```
# let rec destutter list =
  match list with
  | [] -> []
  | hd1 :: (hd2 :: tl) ->
    if hd1 = hd2 then destutter (hd2 :: tl)
    else hd1 :: destutter (hd2 :: tl)
;;
```

Actually, the code above has a problem. If you type it into the top-level, you'll see this error:

```
Warning 8: this pattern-matching is not exhaustive.
Here is an example of a value that is not matched:
_::[]
```

This is warning you that we've missed something, in particular that our code doesn't handle one-element lists. That's easy enough to fix by adding another case to the match:

```
# let rec destutter list =
  match list with
  | [] -> []
  | [hd] -> [hd]
  | hd1 :: (hd2 :: tl) ->
    if hd1 = hd2 then destutter (hd2 :: tl)
    else hd1 :: destutter (hd2 :: tl) ;;
val destutter : 'a list -> 'a list = <fun>
# destutter ["hey";"hey";"hey";"man!"];;
- : string list = ["hey"; "man!"]
```

Note that in the above, we used another variant of the list pattern, `[hd]`, to match a list with a single element. We can do this to match a list with any fixed number of elements, *e.g.*, `[x;y;z]` will match any list with exactly three elements, and will bind those elements to the variables `x`, `y` and `z`.

The List module

So far, we've built up all of our list functions using pattern matching and recursion. But in practice, this isn't usually necessary. Instead, you'll mostly use the rich collection of utility functions contained in Core's `List` module. For example:

```
# List.map ~f:String.length languages;;
- : int list = [5; 4; 1]
```

Here, we use the dot-notation to reference elements of the `List` and `String` module. `List.map` in particular is a function that takes a list and a function for transforming elements of that list (under the label `~f`. For now, you can ignore that bit of syntax, and

we'll learn more about it in chapter `{{{FUNCTIONS}}}`, and returns to us a new list with the transformed elements.

Options

Another common data structure in OCaml is the `option`. An `option` is used to express that a value that might or might not be present. For example,

```
# let divide x y =
  if y = 0 then None else Some (x/y) ;;
val divide : int -> int -> int option = <fun>
```

`Some` and `None` are type constructors, like `::` and `[]` for lists, which let you build optional values. You can think of an `option` as a specialized list that can only have zero or one element.

To get a value out of an option, we use pattern matching, as we did with tuples and lists. Consider the following simple function for printing a log entry given an optional time and a message. If no time is provided (*i.e.*, if the time is `None`), the current time is computed and used in its place.

```
# let print_log_entry maybe_time message =
  let time =
    match maybe_time with
    | Some x -> x
    | None -> Time.now ()
  in
  printf "%s: %s\n" (Time.to_string time) message ;;
val print_log_entry : Time.t option -> string -> unit
```

Here, we again use a `match` statement for handling the two possible states of an option. It's worth noting that we don't necessarily need to use an explicit `match` statement in this case. We can instead use some built in functions from the `Option` module, which, like the `List` module for lists, is a place where you can find a large collection of useful functions for working with options.

In this case, we can rewrite `print_log_entry` using `Option.value`, which either returns the content of an option if the option is `Some`, or a default value if the option is `None`.

```
# let print_log_entry maybe_time message =
  let time = Option.value ~default:(Time.now ()) maybe_time in
  printf "%s: %s\n" (Time.to_string time) message ;;
```

Options are important because they are the standard way in OCaml to encode a value that might not be there. This is different from most other languages, including Java and C#, where most if not all datatypes are *nullable*, meaning that, whatever their type is, any given value also contains the possibility of being a null value. In such languages, null is lurking everywhere.

In OCaml, however, nulls are explicit. A value of type `string * string` always actually contains two well-defined values of type `string`. If you want to allow, say, the first of those, to possibly be absent, then you need to change the type to something like `string option * string`. As we'll see, this explicitness allows the compiler to provide a great deal of help in making sure you're correctly handling the possibility of missing data.

Records and Variants

So far, we've only looked at data structures that were pre-defined in the language, like lists and tuples. But OCaml also allows us to define new datatypes. Here's a toy example of a datatype representing a point in 2-dimensional space:

```
# type point2d = { x : float; y : float };;
type point2d = { x : float; y : float; }
```

`point2d` is a *record* type, which you can think of as a tuple where the individual fields are named, rather than being defined positionally. Record types are easy enough to construct:

```
# let p = { x = 3.; y = -4. };;
val p : point2d = {x = 3.; y = -4.}
```

And we can get access to the contents of these types using pattern matching:

```
# let magnitude { x = x_pos; y = y_pos } = sqrt (x_pos ** 2. +. y_pos ** 2.);;
val magnitude : point2d -> float = <fun>
```

We can write the pattern match even more tersely, using what's called *field punning*. In particular, when the name of the field and the name of the variable coincide, we don't have to write them both down. Thus, the `magnitude` function can be rewritten as follows.

```
# let magnitude { x; y } = sqrt (x ** 2. +. y ** 2.);;
```

We can also use dot-notation for accessing record fields:

```
# let distance v1 v2 =
  magnitude { x = v1.x -. v2.x; y = v1.y -. v2.y };;
val distance : point2d -> point2d -> float = <fun>
```

And we can of course include our newly defined types as components in larger types, as in the following types, each of which is a description of a different geometric object.

```
# type circle_desc = { center: point2d; radius: float } ;;
# type rect_desc   = { lower_left: point2d; width: float; height: float } ;;
# type segment_desc = { endpoint1: point2d; endpoint2: point2d } ;;
```

Now, imagine that you want to combine multiple of these objects together, say as a description of a multi-object scene. You need some unified way of representing these objects together in a single type. One way of doing this is using a *variant* type:

```
# type scene_element =
  | Circle of circle_desc
  | Rect   of rect_desc
  | Segment of segment_desc
;;
```

The `|` character separates the different cases of the variant (the first `|` is optional), and each case has a tag, like `Circle`, `Rect` and `Scene`, to distinguish that case from the others. Here's how we might write a function for testing whether a point is in the interior of some element of a list of `scene_elements`.

```
# let is_inside_scene_element point scene_element =
  match scene_element with
  | Circle { center; radius } ->
    distance center point < radius
  | Rect { lower_left; width; height } ->
    point.x > lower_left.x && point.x < lower_left.x +. width
    && point.y > lower_left.y && point.y < lower_left.y +. height
  | Segment { endpoint1; endpoint2 } -> false
;;
val is_inside_scene_element : point2d -> scene_element -> bool = <fun>
# let is_inside_scene point scene =
  let point_is_inside_scene_element scene_element =
    is_inside_scene_element point scene_element
  in
  List.for_all scene ~f:point_is_inside_scene_element;;
val is_inside_shapes : point2d -> scene_element list -> bool = <fun>
```

You might at this point notice that the use of `match` here is reminiscent of how we used `match` with `option` and `list`. This is no accident: `option` and `list` are really just examples of variant types that happen to be important enough to be defined in the standard library (and in the case of lists, to have some special syntax).

Imperative programming

So far, we've only written so-called *pure* or *functional* code, meaning that we didn't write any code that modified a variable or value after its creation. This is a quite different style from *imperative* programming, where computations are structured as sequences of instructions that operate by modifying state as they go.

Functional code is the default in OCaml, with variable bindings and most data structures being immutable. But OCaml also has excellent support for imperative programming, including mutable data structures like arrays and hashtables and control-flow constructs like `for` and `while` loops.

Arrays

Perhaps the simplest mutable datastructure in OCaml is the array. Here's an example.

```
# let numbers = [| 1;2;3;4 |];;
val numbers : int array = [|1; 2; 3; 4|]
# numbers.(2) <- 4;;
- : unit = ()
# numbers;;
- : int array = [|1; 2; 4; 4|]
```

In the above, the `.(i)` syntax is used for referencing the element of an array, and the `<-` syntax is used for modifying an element of the array.

Arrays in OCaml are very similar to arrays in other languages like C: they are fixed width, indexing starts at 0, and accessing or modifying an array element is a constant-time operation. Arrays are more compact in terms of memory utilization than most other data structures in OCaml, including lists. OCaml uses three words per element of a list, but only one per element of an array.

Mutable record fields

The array is an important mutable datastructure, but it's not the only one. Records, which are immutable by default, can be declared with specific fields as being mutable. Here's a small example of a datastructure for storing a running statistical summary of a collection of numbers. Here's the basic data structure:

```
# type running_sum =
{ mutable sum: float;
  mutable sum_sq: float; (* sum of squares, for stdev *)
  mutable samples: int; } ;;
```

Here are some functions for computing means and standard deviations based on the `running_sum`.

```
# let mean rsum = rsum.sum /. float rsum.samples
let stdev rsum =
  sqrt (rsum.sum_sq /. float rsum.samples
        -. (rsum.sum /. float rsum.samples) ** 2.) ;;
val mean : running_sum -> float = <fun>
val stdev : running_sum -> float = <fun>
```

And finally, we can define functions for creating and modifying a `running_sum`. Note the use of single semi-colons to express a sequence of operations. When we were operating purely functionally, this wasn't necessary, but you start needing it when your code is acting by side-effect.

```
# let create () = { sum = 0.; sum_sq = 0.; samples = 0 }
let update rsum x =
```

```

    rsum.samples <- rsum.samples + 1;
    rsum.sum      <- rsum.sum      +. x;
    rsum.sum_sq   <- rsum.sum_sq   +. x *. x
  ;;
  val create : unit -> running_sum = <fun>
  val update : running_sum -> float -> unit = <fun>

```

A new and somewhat odd type has cropped up in this example: `unit`. What makes `unit` unusual is that there is only one value of type `unit`, which is written `()`. Because `unit` has only one inhabitant, a value of type `unit` can't convey any information.

If it doesn't convey any information, then what is `unit` good for? Most of the time, `unit` acts as a placeholder. Thus, we use `unit` for the return value of a function like `update` that operates by side effect rather than by returning a value, and for the argument to a function like `create` that doesn't require any information to be passed into it in order to run.

Here's an example of `create` and `update` in action.

```

# let rsum = create ();;
val rsum : running_sum = {sum = 0.; sum_sq = 0.; samples = 0}
# List.iter [1.;3.;2.;-7.;4.;5.] ~f:(fun x -> update rsum x);;
- : unit = ()
# mean rsum;;
- : float = 1.33333333333333326
# stdev rsum;;
- : float = 3.94405318873307698

```

Refs

We can declare a single mutable value by using a `ref`, which is a record type with a single mutable field that is defined in the standard library.

```

# let x = { contents = 0 };;
val x : int ref = {contents = 0}
# x.contents <- x.contents + 1;;
- : unit = ()
# x;;
- : int ref = {contents = 1}

```

There are a handful of useful functions and operators defined for refs to make them more convenient to work with.

```

# let x = ref 0 ;; (* create a ref, i.e., { contents = 0 } *)
val x : int ref = {contents = 0}
# !x ;;           (* get the contents of a ref, i.e., x.contents *)
- : int = 0
# x := !x + 1 ;;  (* assignment, i.e., x.contents <- ... *)
- : unit = ()
# incr x ;;       (* increment, i.e., x := !x + 1 *)
- : unit = ()

```

```
# !x ;;
- : int = 2
```

A ref is really just an example of a mutable record, but in practice, it's the standard way of dealing with a single mutable value in a computation.

For and while loops

Along with mutable data structures, OCaml gives you constructs like `while` and `for` loops for interacting with them. Here, for example, is a piece of imperative code for permuting an array. Here, we use the `Random` module as our source of randomness. (`Random` starts out with a deterministic seed, but you can call `Random.self_init` to get a new random seed chosen.)

```
# let permute ar =
  for i = 0 to Array.length ar - 2 do
    (* pick a j that is after i and before the end of the list *)
    let j = i + 1 + Random.int (Array.length ar - i - 1) in
    (* Swap i and j *)
    let tmp = ar.(i) in
    ar.(i) <- ar.(j);
    ar.(j) <- tmp
  done
;;
val permute : 'a array -> unit = <fun>
```

Note that the semi-colon after the first array assignment doesn't terminate the scope of the let-binding.

```
# let ar = Array.init 20 ~f:(fun i -> i);;
val ar : int array =
  [|0; 1; 2; 3; 4; 5; 6; 7; 8; 9; 10; 11; 12; 13; 14; 15; 16; 17; 18; 19|]
# permute ar;;
- : unit = ()
# ar;;
- : int array =
  [|14; 13; 1; 3; 2; 19; 17; 18; 9; 16; 15; 7; 12; 11; 4; 10; 0; 5; 6; 8|]
```

Where to go from here

That's it for our guided tour! There are plenty of features left to touch upon - we haven't shown you how to read from a file, as just one example - but the hope is that this has given you enough of a feel for the language that you have your bearings, and will be comfortable reading examples in the rest of the book.

2012-09-23

13:57:42

CHAPTER 3

Variables and Functions

Variables and functions are fundamental ideas that show up in virtually all programming languages. But while these are familiar topics, OCaml's variables and functions are different in subtle but important ways from what you may have seen elsewhere. Accordingly we're going to spend a some time diving into the details of how these concepts play out in OCaml.

Variables

At its simplest, a variable is an identifier whose meaning is bound to a particular value. In OCaml these bindings are often introduced using the `let` keyword. When typed in at the prompt of the interpreter, a `let` binding has the following syntax.

```
let <identifier> = <expr>
```

As we'll see when we get to the module system in chapter `MODULES`, this same syntax is used for top-level definitions in a module.

Every variable binding has a *scope*, which is the portion of the code that can access that binding. The scope of a top-level `let` binding is everything that follows it in the top-level session (or in the remainder of the module).

Here's a simple example.

```
# let x = 3;;  
val x : int = 3  
# let y = 4;;  
val y : int = 4  
# let z = x + y;;  
val z : int = 7
```

`let` can also be used to create a variable binding whose scope is limited to a particular expression, using the following syntax.

```
let <identifier> = <expr1> in <expr2>
```

This first evaluates *expr1* and then evaluates *expr2* with *identifier* bound to whatever value was produced by the evaluation of *expr1*. Here's how it looks in practice.

```
# let languages = "OCaml,Perl,C++,C";;
val languages : string = "OCaml,Perl,C++,C"
# let dashed_languages =
  let language_list = String.split languages ~on:', ' in
    String.concat ~sep:"- " language_list
  ;;
val dashed_languages : string = "OCaml-Perl-C++-C"
```

Note that the scope of `language_list` is just the expression `String.split languages ~on:', '`, and is not available at the top-level, as we can see if we try to access it now.

```
# language_list;;
Characters 0-13:
  language_list;;
^^^^^^^^^^^^^^
Error: Unbound value language_list
```

A let binding in an inner scope can *shadow*, or hide, the definition from an outer scope. So, for example, we could have written the `dashed_languages` example as follows:

```
# let languages = "OCaml,Perl,C++,C";;
val languages : string = "OCaml,Perl,C++,C"
# let dashed_languages =
  let languages = String.split languages ~on:', ' in
    String.concat ~sep:"- " languages
  ;;
val dashed_languages : Core.Std.String.t = "OCaml-Perl-C++-C"
```

This time, in the inner scope we called the list of strings `languages` instead of `language_list`, thus hiding the original definition of `languages`. But once the definition of `dashed_languages` is complete, the inner scope has closed and the original definition of `languages` reappears.

```
# languages;;
- : string = "OCaml,Perl,C++,C"
```

One common idiom is to use a series of nested `let/in` expressions to build up the components of a larger computation. Thus, we might write:

```
# let area_of_ring inner_radius outer_radius =
  let pi = acos (-1.) in
  let area_of_circle r = pi *. r *. r in
  area_of_circle outer_radius -. area_of_circle inner_radius
;;
```



```
# area_of_ring 1. 3.;;
- : float = 25.1327412287183449
```

It's important not to confuse this sequence of let bindings with the modification of a mutable variable. How would `area_of_ring` be different, for example, if we had instead written this purposefully confusing bit of code:

```
# let area_of_ring inner_radius outer_radius =
  let pi = acos (-1.) in
  let area_of_circle r = pi *. r *. r in
  let pi = 0. in
  area_of_circle outer_radius -. area_of_circle inner_radius
;;
```

Here, we redefined `pi` to be zero after the definition of `area_of_circle`. You might think that this would mean that the result of the computation would now be zero, but you'd be wrong. In fact, the behavior of the function is unchanged. That's because the original definition of `pi` wasn't changed, it was just shadowed, so that any subsequent reference to `pi` would see the new definition of `pi` as zero. But there is no later use of `pi`, so the binding doesn't make a difference. Indeed, if you type the example I gave above into the toplevel, OCaml will warn you that the definition is unused.

```
Characters 126-128:
```

```
  let pi = 0. in
    ^^
```

```
Warning 26: unused variable pi.
```

In OCaml, let bindings are immutable. As we'll see in chapter `{MUTABILITY}`, there are mutable values in OCaml, but no mutable variables.

Pattern matching and let

Another useful feature of let bindings is that they support the use of patterns on the left-hand side of the bind. Consider the following code, which uses `List.unzip`, a function for converting a list of pairs into a pair of lists.

```
# let (ints,strings) = List.unzip [(1,"one"); (2,"two"); (3,"three")]
val ints : int list = [1; 2; 3]
val strings : string list = ["one"; "two"; "three"]
```

This actually binds two variables, one for each element of the pair. Using a pattern in a let-binding makes the most sense for a pattern that is *irrefutable*, i.e., where any value of the type in question is guaranteed to match the pattern. Tuple and record patterns are irrefutable, but list patterns are not. Indeed, the following pattern match generates a warning because not all cases are covered.

```
# let (hd::tl) = [1;2;3];;
Characters 4-12:
  let (hd::tl) = [1;2;3];;
```

```

          ^^^^^^^^^
Warning 8: this pattern-matching is not exhaustive.
Here is an example of a value that is not matched:
[]

```

As a general matter, inexhaustive matches like the one above should be avoided.

let/and bindings

Another variant on the let binding is the use of **and** to join multiple variable definitions into a single declaration. For example, we can write:

```

# let x = 100 and y = 3.5;;
val x : int = 100
val y : float = 3.5

```

This can be useful when you want to create a number of new let bindings at once, without having each definition affect the next. So, if we wanted to create new bindings that swapped the values of *x* and *y*, we could write:

```

# let x = y and y = x ;;
val x : float = 3.5
val y : int = 100

```

This use-case doesn't come up that often. Most of the time that **and** comes into play, it's used to define multiple mutually recursive values, which we'll learn about later in the chapter.

Note that when doing a **let/and** style declaration, the order of execution of the right-hand side of the binds is undefined by the language definition, so one should not write code that relies on it.

Functions

OCaml being a functional language, it's no surprise that functions are an important and pervasive element of programming in OCaml. Indeed, we've seen functions pop up already in many of the examples we've looked at thus far. But while we've introduced the basics of functions, we're now going to cover them in more depth, starting from the foundations.

Anonymous Functions

We'll start by looking at the most basic form of OCaml function, the *anonymous* function. Anonymous functions are declared using the **fun** keyword, as follows.

```

# (fun x -> x + 1);;
- : int -> int = <fun>

```

Anonymous functions aren't named, but they can be used for many different purposes nonetheless. You can, for example, apply an anonymous function to an argument:

```
# (fun x -> x + 1) 7;;  
- : int = 8
```

Or pass it to another function.

```
# List.map ~f:(fun x -> x + 1) [1;2;3];;  
- : int list = [2; 3; 4]
```

Or even stuff them into a datastructure.

```
# let increments = [ (fun x -> x + 1); (fun x -> x + 2) ] ;;  
val increments : (int -> int) list = [<fun>; <fun>]  
# List.map ~f:(fun f -> f 5) increments;;  
- : int list = [6; 7]
```

It's worth stopping for a moment to puzzle this example out, since this kind of higher-order use of functions can be a bit obscure at first. The first thing to understand is the function `(fun f -> f 5)`, which takes a function as its argument and applies that function to the number 5. The invocation of `List.map` applies `(fun f -> f 5)` to the elements of the `increments` list (which are themselves functions) and returns the list containing the results of these function applications.

The key thing to understand is that functions are ordinary values in OCaml, and you can do everything with them that you'd do with an ordinary value, including passing them to and returning them from other functions and storing them in datastructures. We even name functions in the same way that we name other values, by using a `let` binding.

```
# let plusone = (fun x -> x + 1);;  
val plusone : int -> int = <fun>  
# plusone 3;;  
- : int = 4
```

Defining named functions is so common that there is some built-in syntactic sugar for it. Thus, we can write:

```
# let plusone x = x + 1;;  
val plusone : int -> int = <fun>
```

This is the most common and convenient way to declare a function, but syntactic niceties aside, the two styles of function definition are entirely equivalent.

let and fun

Functions and let bindings have a lot to do with each other. In some sense, you can think of the argument of a function as a variable being bound to its argument. Indeed, the following two expressions are nearly equivalent:

```
# (fun x -> x + 1) 7;;  
- : int = 8  
# let x = 7 in x + 1;;  
- : int = 8
```

This connection is important, and will come up more when programming in a monadic style, as we'll see in chapter `{ASYNC}`.

Multi-argument functions

OCaml of course also supports multi-argument functions. Here's an example that came up in chapter `{TOUR}`.

```
# let abs_diff x y = abs (x - y);;  
val abs_diff : int -> int -> int = <fun>  
# abs_diff 3 4;;  
- : int = 1
```

You may find the type signature of `abs_diff` with all of its arrows a little hard to parse. To understand what's going on, let's rewrite `abs_diff` in an equivalent form, using the `fun` keyword:

```
# let abs_diff =  
  (fun x -> (fun y -> abs (x - y)));;  
val abs_diff : int -> int -> int = <fun>
```

This rewrite makes it explicit that `abs_diff` is actually a function of one argument that returns another function of one argument, which itself returns the final computation. Because the functions are nested, the inner expression `abs (x - y)` has access to both `x`, which was captured by the first function application, and `y`, which was captured by the second one.

This style of function is called a *curried* function. (Currying is named after Haskell Curry, a famous logician who had a significant impact on the design and theory of programming languages.) The key to interpreting the type signature of a curried function is the observation that `->` is right-associative. The type signature of `abs_diff` can therefore be parenthesized as follows. This doesn't change the meaning of the signature, but it makes it easier to see how the currying fits in.

```
val abs_diff : int -> (int -> int)
```

Currying is more than just a theoretical curiosity. You can make use of currying to specialize a function by feeding in some of the arguments. Here's an example where we create a specialized version of `abs_diff` that measures the distance of a given number from 3.

```
# let dist_from_3 = abs_diff 3;;
val dist_from_3 : int -> int = <fun>
# dist_from_3 8;;
- : int = 5
# dist_from_3 (-1);;
- : int = 4
```

The practice of applying some of the arguments of a curried function to get a new function is called *partial application*.

Note that the `fun` keyword supports its own syntactic sugar for currying, so we could also have written `abs_diff` as follows.

```
# let abs_diff = (fun x y -> abs (x - y));;
```

You might worry that curried functions are terribly expensive, but this is not the case. In OCaml, there is no penalty for calling a curried function with all of its arguments. (Partial application, unsurprisingly, does have a small extra cost.)

Currying is not the only way of writing a multi-argument function in OCaml. It's also possible to use the different arms of a tuple as different arguments. So, we could write:

```
# let abs_diff (x,y) = abs (x - y)
val abs_diff : int * int -> int = <fun>
# abs_diff (3,4);;
- : int = 1
```

OCaml handles this calling convention efficiently as well. In particular it does not generally have to allocate a tuple just for the purpose of sending arguments to a tuple-style function.

There are small tradeoffs between these two approaches, but most of the time, one should stick to currying, since it's the default style in the OCaml world.

Recursive functions

In order to define a recursive function, you need to mark the `let` binding as recursive with the `rec` keyword, as shown in this example:

```
# let rec find_first_stutter = function
| [] | [_] ->
  (* only zero or one elements, so no repeats *)
  None
| x :: y :: tl ->
```

```

        if x = y then Some x else find_first_stutter (y::tl)
    val find_first_stutter : 'a list -> 'a option = <fun>

```

We can also define multiple mutually recursive values by using `let rec` and `and` together, as in this (gratuitously inefficient) example.

```

# let rec is_even x =
    if x = 0 then true else is_odd (x - 1)
  and is_odd x =
    if x = 0 then false else is_even (x - 1)
;;
val is_even : int -> bool = <fun>
val is_odd : int -> bool = <fun>
# List.map ~f:is_even [0;1;2;3;4;5];;
- : bool Core.Std.List.t = [true; false; true; false; true; false]
# List.map ~f:is_odd [0;1;2;3;4;5];;
- : bool Core.Std.List.t = [false; true; false; true; false; true]

```

Note that in the above example, we take advantage of the fact that the right hand side of the `||` is only evaluated if the left hand side evaluates to false.

Prefix and Infix operators

So far, we've seen examples of functions used in both prefix and infix style:

```

# Int.max 3 4;; (* prefix *)
- : int = 4
# 3 + 4;;      (* infix  *)
- : int = 7

```

You might not have thought of the second example as an ordinary function, but it very much is. Infix operators like `+` really only differ syntactically from other functions. In fact, if we put parenthesis around an infix operator, you can use it as an ordinary prefix function.

```

# (+) 3 4;;
- : int = 7
# List.map ~f:(+) 3 [4;5;6];;
- : int list = [7; 8; 9]

```

In the second expression above, we've partially applied `(+)` to gain a function that increments its single argument by 3, and then applied that to all the elements of a list.

A function is treated syntactically as an operator if the name of that function is chosen from one of a specialized set of identifiers. This set includes any identifier that is a sequence of characters from the following set

```
! $ % & * + - . / : < = > ? @ ^ | ~
```

or is one of a handful of pre-determined strings, including `mod`, the modulus operator, and `lsl`, for "logical shift left", a bit-shifting operation.

We can define (or redefine) the meaning of an operator as follows. Here's an example of a simple vector-addition operator on `int` pairs.

```
# let (+!) (x1,y1) (x2,y2) = (x1 + x2, y1 + y2)
val ( +! ) : int * int -> int * int -> int *int = <fun>
# (3,2) +! (-2,4);;
- : int * int = (1,6)
```

The syntactic role of an operator work is determined by its first character. This table describes how, and lists the operators from highest to lowest precedence.

First character	Usage
! ? ~	Prefix and unary
**	Infix, right associative
+ -	Infix, left associative
@ ^	Infix, right associative
= < > & \$	Infix, left associative

Here's an example of a very useful operator that's defined in Core, following these rules. Here's the definition:

```
# let (|!) x f = f x ;;
val ( |! ) : 'a -> ('a -> 'b) -> 'b = <fun>
```

It's not quite obvious at first what the purpose of this operator is: it just takes some value and a function, and applies the function to the value. But its utility is clearer when you see it in action. It works as a kind of sequencing operator, similar in spirit to using pipe in the UNIX shell. So, for example:

```
# let drop_zs string =
  String.to_list string
  |> List.filter ~f:(fun c -> c <> 'z')
  |> String.of_char_list
;;
val drop_zs : string -> string = <fun>
# drop_zs "lizkze UNIX zpipes wizth tzzypzzes";;
- : string = "like UNIX pipes with types"
```

Note that `|!` works here because it is left-associative. If it were right associative, it wouldn't be doing the right thing at all. Indeed, let's see what happens if we try using a right associative operator, like `(^!)`.

```
# let (^!) = (|!);;
val ( ^! ) : 'a -> ('a -> 'b) -> 'b = <fun>
```

```
# let drop_zs string =
  String.to_list string
  ^! List.filter ~f:(fun c -> c <> 'z')
  ^! String.of_char_list
;;
Characters 96-115:
^! String.of_char_list
^^^^^^^^^^^^^^^^^^^^
Error: This expression has type char list -> string
      but an expression was expected of type
      (char list -> char list) -> 'a'
```

The above type error is a little bewildering at first glance. What's going on is that, because `^!` is right associative, the operator is trying to feed the value `List.filter ~f:(fun c -> c <> 'z')` to the function `String.of_char_list`. But `String.of_char_list` expects a list of characters as its input, not a function.

The type error aside, this example highlights the importance of choosing the operator you use with care, particularly with respect to associativity.

Declaring functions with function

Another way to define a function is using the `function` keyword. Instead of having syntactic support for declaring curried functions, `function` has built-in pattern matching. Here's an example:

```
# let some_or_zero = function
  | Some x -> x
  | None -> 0
;;
val some_or_zero : int option -> int = <fun>
# List.map ~f:some_or_zero [Some 3; None; Some 4];;
- : int list = [3; 0; 4]
```

This is equivalent to combining a `fun` with `match`, as follows:

```
# let some_or_zero num_opt =
  match num_opt with
  | Some x -> x
  | None -> 0
;;
val some_or_zero : int option -> int = <fun>
```

We can also combine the different styles of function declaration together, as in the following example where we declare a two argument function with a pattern-match on the second argument.

```
# let some_or_default default = function
  | Some x -> x
  | None -> default
;;
```



```
# List.map ~f:(some_or_default 100) [Some 3; None; Some 4];;
- : int Core.Std.List.t = [3; 100; 4]
```

Also, note the use of partial application to generate the function passed to `List.map`

Labeled Arguments

Up until now, the different arguments to a function have been specified positionally, *i.e.*, by the order in which the arguments are passed to the function. OCaml also supports labeled arguments, which let you identify a function argument by name. Functions with labeled arguments can be declared by putting a tilde in front of the variable name in the definition of the function:

```
# let f ~foo:a ~bar:b = a + b
val f : foo:int -> bar:int -> int = <fun>
```

And the function can be called using the same convention:

```
# f ~foo:3 ~bar:10;;
- : int = 13
```

In addition, OCaml supports *label punning*, meaning that you get to drop the text after the `:` if the name of the label and the name of the variable being used are the same. Label punning works in both function declaration and function invocation, as shown in these examples:

```
# let f ~foo ~bar = foo + bar
val f : foo:int -> bar:int -> int = <fun>
# let foo = 3;;
# let bar = 4;;
# f ~foo ~bar;;
- : int = 7
```

Labeled arguments are useful in a few different cases:

- When defining a function with lots of arguments. Beyond a certain number, arguments are easier to remember by name than by position.
- When defining functions that have multiple arguments that might get confused with each other. This is most at issue when the arguments are of the same type. For example, consider this signature for a function for extracting a substring of another string.

```
val substring: string -> int -> int -> string
```

where the two ints are the starting position and length of the substring to extract. Labeled arguments can make this signature clearer:

```
val substring: string -> pos:int -> len:int -> string
```

This improves the readability of both the signature and of client code that makes use of `substring`, and makes it harder to accidentally swap the position and the length.

- When the meaning of a particular argument is unclear from the type alone. For example, consider a function for creating a hashtable where the first argument is the initial size of the table, and the second argument is a flag which, when true, indicates that the hashtable will reduce its size when the hashtable contains few elements. The following signature doesn't give you much of a hint as to the meaning of the arguments.

```
val create_hashtable : int -> bool -> ('a,'b) Hashtable.t
```

but with labeled arguments, we can make the intent much clearer.

```
val create_hashtable : init_size:int -> allow_shrinking:bool -> ('a,'b) Hashtable.t
```

- When you want flexibility on the order in which arguments are presented and the order of partial application. One common example is functions like `List.map` or `List.fold` which take a function as one of their arguments. When the function in question is big, it's often more readable to put the function last, *e.g.*:

```
# let rot13 s =
  String.map s ~f:(fun c ->
    if not (Char.is_alpha c) then c
    else
      let a_int = Char.to_int 'a' in
      let offset = Char.to_int (Char.lowercase c) - a_int in
      let c' = Char.of_int_exn ((offset + 13) mod 26 + a_int) in
      if Char.is_uppercase c then Char.uppercase c' else c'
  );;
val rot13 : string -> string = <fun>
# rot13 "Hello world!";;
- : string = "Uryyb jbeyq!"
# rot13 (rot13 "Hello world!");;
- : string = "Hello world!"
```

But despite the fact that we often want the argument `f` to go last, we sometimes want to partially apply that argument. In this example, we do so with `String.map`.

```
# List.map ~f:(String.map ~f:Char.uppercase)
[ "Hello"; "World" ];;
- : string list = ["HELLO"; "WORLD"]
```

Higher-order functions and labels

One surprising gotcha labeled arguments is that while order doesn't matter when calling a function with labeled arguments, it does matter in a higher-order context, *e.g.*, when passing a function with labeled arguments to another function. Here's an example.

```
# let apply_to_tuple f (first,second) = f ~first ~second;;
val apply_to_tuple : (first:'a -> second:'b -> 'c) -> 'a * 'b -> 'c = <fun>
```

Here, the definition of `apply_to_tuple` sets up the expectation that its first argument is a function with two labeled arguments, `first` and `second`, listed in that order. We could have defined `apply_to_tuple` differently to change the order in which the labeled arguments were listed.

```
# let apply_to_tuple f (first,second) = f ~second ~first;;
val apply_to_tuple : (second:'a -> first:'b -> 'c) -> 'b * 'a -> 'c = <fun>
```

It turns out this order of listing matters. In particular, if we define a function that has a different order

```
# let divide ~first ~second = first / second;;
val divide : first:int -> second:int -> int = <fun>
```

we'll find that it can't be passed in to `apply_to_tuple`.

```
# apply_to_tuple divide (3,4);;
Characters 15-21:
  apply_to_tuple divide (3,4);;
                ^^^^^^
Error: This expression has type first:int -> second:int -> int
      but an expression was expected of type second:'a -> first:'b -> 'c
```

But, if we go back to the original definition of `apply_to_tuple`, things will work smoothly.

```
# let apply_to_tuple f (first,second) = f ~first ~second;;
val apply_to_tuple : (first:'a -> second:'b -> 'c) -> 'a * 'b -> 'c = <fun>
# apply_to_tuple divide (3,4);;
- : int = 0
```

So, even though the order of labeled arguments usually doesn't matter, it will sometimes bite you in higher-ordered contexts, where you're doing things like passing functions as arguments to other functions.

Optional arguments

An optional argument is like a labeled argument that the caller can choose whether or not to provide. Optional arguments are passed in using the same syntax as labeled arguments, and, similarly to labeled arguments, optional arguments can be provided in any order.

Here's an example of a string concatenation function with an optional separator.

```
# let concat ?sep x y =
  let sep = match sep with None -> "" | Some x -> x in
```

```

    x ^ sep ^ y
;;
val concat : ?sep:string -> string -> string -> string = <fun>
# concat "foo" "bar";;      (* without the optional argument *)
- : string = "foobar"
# concat ~sep:"." "foo" "bar";;  (* with the optional argument *)
- : string = "foo:bar"

```

Here, `?` is used to mark the separator as optional. Note that, while the type of the optional argument is `string`, internally, the argument is received as a `string option`, where `None` indicates that the optional argument was not specified.

In the above example, we had a bit of code to substitute in the empty string when no argument was provided. This is a common enough pattern that there's an explicit syntax for doing this, which allows us to write `concat` even more tersely:

```

# let concat ?(sep="") x y = x ^ sep ^ y ;;
val concat : ?sep:string -> string -> string -> string = <fun>

```

Optional arguments are very useful, but they're also easy to abuse. The key advantage of optional arguments is that they let you write functions with complex options that users can ignore most of the time, only needing to think about them when they specifically want to invoke those options.

The downside is that it's easy for the caller of a function to not be aware that there is a choice to be made, leading them to pick the default behavior unknowingly, and sometimes wrongly. Optional arguments really only make sense when the extra concision of omitting the argument overwhelms the corresponding loss of explicitness.

This means that rarely used functions should not have optional arguments. A good rule of thumb for optional arguments is that you should never use an optional argument for internal functions of a module, only for functions that are exposed to users of a module.

Explicit passing of an optional argument

Sometimes you want to explicitly invoke an optional argument with a concrete option, where `None` indicates that the argument won't be passed in, and `Some` indicates it will. You can do that as follows:

```

# concat ?sep:None "foo" "bar";;
- : string = "foobar"

```

This is particularly useful when you want to pass through an optional argument from one function to another, leaving the choice of default to the second function. For example:

```

# let uppercase_concat ?sep a b = concat ?sep (String.uppercase a) b ;;
val uppercase_concat : ?sep:string -> string -> string -> string =
  <fun>

```

```
# uppercase_concat "foo" "bar";;
- : string = "F00bar"
# uppercase_concat "foo" "bar" ~sep:".";
- : string = "F00:bar"
```

Inference of labeled and optional arguments

(yminsky: *This is too abstract of an example.*)

One subtle aspect of labeled and optional arguments is how they are inferred by the type system. Consider the following example:

```
# let foo g x y = g ~x ~y ;;
val foo : (x:'a -> y:'b -> 'c) -> 'a -> 'b -> 'c = <fun>
```

In principle, it seems like the inferred type of `g` could have its labeled arguments listed in a different order, such as:

```
val foo : (y:'b -> x:'a -> 'c) -> 'a -> 'b -> 'c = <fun>
```

And it would be perfectly consistent for `g` to take an optional argument instead of a labeled one, which could lead to this type signature for `foo`:

```
val foo : (?x:'a -> y:'b -> 'c) -> 'a -> 'b -> 'c = <fun>
```

Since there are multiple plausible types to choose from, OCaml needs some heuristic for choosing between them. The heuristic the compiler uses is to prefer labels to options, and to choose the order of arguments that shows up in the source code.

Note that these heuristics might at different points in the source suggest different types. For example, here's a function whose argument `g` is a function that is used once with argument `~x` followed by `~y`, and once with argument `~y` followed by `~x`. The result of this is a compilation error.

```
# let bar g x y = g ~x ~y + g ~y ~x ;;
Characters 26-27:
  let bar g x y = g ~x ~y + g ~y ~x ;;
                        ^
```

```
Error: This function is applied to arguments
in an order different from other calls.
This is only allowed when the real type is known.
```

Note that if we provide an explicit type constraint for `g`, that constraint decides the question of what `g`'s type is, and the error disappears.

```
# let foo (g : ?y:'a -> x:'b -> int) x y =
  g ~x ~y + g ~y ~x ;;
val foo : (?y:'a -> x:'b -> int) -> 'b -> 'a -> int = <fun>
```

Optional arguments and partial application

Optional arguments can be tricky to think about in the presence of partial application. We can of course partially apply the optional argument itself:

```
# let colon_concat = concat ~sep:":";;
val colon_concat : string -> string -> string = <fun>
# colon_concat "a" "b";;
- : string = "a:b"
```

But what happens if we partially apply just the first argument?

```
# let prepend_pound = concat "# ";;
val prepend_pound : string -> string = <fun>
# prepend_pound "a BASH comment";;
- : string = "# a BASH comment"
```

Note that the optional argument `?sep` has now disappeared, or *erased*. So when does OCaml decide to erase an optional argument?

The rule is: an optional argument is erased as soon as the first positional argument defined *after* the optional argument is passed in. That explains the behavior of `prepend_pound` above. But if we had instead defined `concat` with the optional argument in the second position:

```
# let concat x ?(sep="") y = x ^ sep ^ y ;;
val concat : string -> ?sep:string -> string -> string = <fun>
```

then application of the first argument would not cause the optional argument to be erased.

```
# let prepend_pound = concat "# ";;
val prepend_pound : ?sep:string -> string -> string = <fun>
# prepend_pound "a BASH comment";;
- : string = "# a BASH comment"
# prepend_pound "a BASH comment" ~sep: "--- ";;
- : string = "# --- a BASH comment"
```

However, if all arguments to a function are presented at once, then erasure of optional arguments isn't applied until all of the arguments are passed in. This preserves our ability to pass in optional arguments anywhere on the argument list. Thus, we can write:

```
# concat "a" "b" ~sep:"=";;
- : string = "a=b"
```

An optional argument that doesn't have any following positional arguments can't be erased at all, which leads to a compiler warning.

```
# let concat x y ?(sep="") = x ^ sep ^ y ;;
Characters 15-38:
```

2012-09-23

13:57:42

```
let concat x y ?(sep="") = x ^ sep ^ y ;;
```

```
^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^
```

Warning 16: this optional argument cannot be erased.

```
val concat : string -> string -> ?sep:string -> string = <fun>
```

2012-09-23

13:57:42

CHAPTER 4

Lists, Options and Patterns

Example: pretty-printing a table

One common programming task is displaying tabular data. In this example, will go over the design of a simple library to do just that.

We'll start with the interface. The code will go in a new module called `Text_table` whose `.mli` contains just the following function:

```
(* [render headers rows] returns a string containing a formatted
   text table, using unix-style newlines as separators *)
val render
  : string list          (* header *)
  -> string list list    (* data *)
  -> string
```

If you invoke `render` as follows:

```
let () =
  print_string (Text_table.render
    ["language";"architect";"first release"]
    [ ["Lisp" ;"John McCarthy" ;"1958"] ;
      ["C"    ;"Dennis Ritchie" ;"1969"] ;
      ["ML"   ;"Robin Milner"  ;"1973"] ;
      ["OCaml";"Xavier Leroy"  ;"1996"] ;
    ])
  )
```

you'll get the following output:

language	architect	first release
Lisp	John McCarthy	1958
C	Dennis Ritchie	1969
ML	Robin Milner	1973
OCaml	Xavier Leroy	1996

Now that we know what `render` is supposed to do, let's dive into the implementation.

Computing the widths

To render the rows of the table, we'll first need the width of the widest entry in each column. The following function does just that.

```
let max_widths header rows =
  let to_lengths l = List.map ~f:String.length l in
  List.fold rows
    ~init:(to_lengths header)
    ~f:(fun acc row ->
      List.map2_exn ~f:Int.max acc (to_lengths row))
```

In the above we define a helper function, `to_lengths` which uses `List.map` and `String.length` to convert a list of strings to a list of string lengths. Then, starting with the lengths of the headers, we use `List.fold` to join in the lengths of the elements of each row by `max`'ing them together elementwise.

Note that this code will throw an exception if any of the rows has a different number of entries than the header. In particular, `List.map2_exn` throws an exception when its arguments have mismatched lengths.

Rendering the rows

Now we need to write the code to render a single row. There are really two different kinds of rows that need to be rendered; an ordinary row:

```
| Lisp      | John McCarthy | 1962      |
```

and a separator row:

```
|-----+-----+-----|
```

Let's start with the separator row, which we can generate as follows:

```
let render_separator widths =
  let pieces = List.map widths
    ~f:(fun w -> String.make (w + 2) '-')
  in
  "|" ^ String.concat ~sep:"+" pieces ^ "|"
```

We need the extra two-characters for each entry to account for the one character of padding on each side of a string in the table.

Performance of `String.concat` and `^`

In the above, we're using two different ways of concatenating strings, `String.concat`, which operates on lists of strings, and `^`, which is a pairwise operator. You should avoid `^` for joining long numbers of strings, since, it allocates a new string every time it runs. Thus, the following code:

```
let s = "." ^ "." ^ "." ^ "." ^ "." ^ "." ^ "." ^ "."
```

will allocate a string of length 2, 3, 4, 5, 6 and 7, whereas this code:

```
let s = String.concat [".";".";".";".";".";".";".";"."]
```

allocates one string of size 7, as well as a list of length 7. At these small sizes, the differences don't amount to much, but for assembling of large strings, it can be a serious performance issue.

We can write a very similar piece of code for rendering the data in an ordinary row.

```
let pad s length =
  if String.length s >= length then s
  else s ^ String.make (length - String.length s) ' '

let render_row row widths =
  let pieces = List.map2 row widths
  ~f:(fun s width -> " " ^ pad s width ^ " ")
  in
  "|" ^ String.concat ~sep:"|" pieces ^ "|"
```

You might note that `render_row` and `render_separator` share a bit of structure. We can improve the code a bit by factoring that repeated structure out:

```
let decorate_row ~sep row = "|" ^ String.concat ~sep row ^ "|"

let render_row widths row =
  decorate_row ~sep:"|"
  (List.map2_exn row widths ~f:(fun s w -> " " ^ pad s w ^ " "))

let render_separator widths =
  decorate_row ~sep:"+"
  (List.map widths ~f:(fun width -> String.make (width + 2) '-'))
```

Bringing it all together

And now we can write the function for rendering a full table.

```
let render_header rows =
  let widths = max_widths header rows in
  String.concat ~sep:"\n"
    (render_row widths header
     :: render_separator widths
     :: List.map rows ~f:(fun row -> render_row widths row)
    )
```

Now, let's think about how you might actually use this interface in practice. Usually, when you have data to render in a table, that data comes in the form of a list of objects of some sort, where you need to extract data from each record for each of the columns.

So, imagine that you start off with a record type for representing information about a given programming language:

```
type style =
  Object_oriented | Functional | Imperative | Logic

type prog_lang = { name: string;
                  architect: string;
                  year_released: int;
                  style: style list;
                  }
```

If we then wanted to render a table from a list of languages, we might write something like this:

```
let print_langs langs =
  let headers = ["name"; "architect"; "year released"] in
  let to_row lang =
    [lang.name; lang.architect; Int.to_string lang.year_released ]
  in
  print_string (Text_table.render headers (List.map ~f:to_row langs))
```

This is OK, but as you consider more complicated tables with more columns, it becomes easier to make the mistake of having a mismatch in between `headers` and `to_row`. Also, adding, removing and reordering columns becomes awkward, because changes need to be made in two places.

We can improve the table API by adding a type which is a first-class representative for a column. We'd add the following to the interface of `Text_table`:

```
(** An ['a column] is a specification of a column for rendering a table
   of values of type ['a] *)
type 'a column

(** [column_header to_entry] returns a new column given a header and a
    function for extracting the text entry from the data associated
    with a row *)
val column : string -> ('a -> string) -> 'a column

(** [column_render columns rows] Renders a table with the specified
    columns and rows *)
val column_render :
  'a column list -> 'a list -> string
```

Thus, the `column` functions creates a `column` from a header string and a function for extracting the text for that column associated with a given row. Implementing this interface is quite simple:

```
type 'a column = string * ('a -> string)
let column_header to_string = (header, to_string)
```

```
let column_render columns rows =  
  let header = List.map columns ~f:fst in  
  let rows = List.map rows ~f:(fun row ->  
    List.map columns ~f:(fun (_,to_string) -> to_string row))  
  in  
  render header rows
```

And we can rewrite `print_langs` to use this new interface as follows.

```
let columns =  
  [ Text_table.column "Name"      (fun x -> x.name);  
    Text_table.column "Architect" (fun x -> x.architect);  
    Text_table.column "Year Released"  
      (fun x -> Int.to_string x.year_released);  
  ]  
  
let print_langs langs =  
  print_string (Text_table.column_render columns langs)
```

The code is a bit longer, but it's also less error prone. In particular, several errors that might be made by the user are now ruled out by the type system. For example, it's no longer possible for the length of the header and the lengths of the rows to be mismatched.

The simple column-based interface described here is also a good starting for building a richer API. You could for example build specialized columns with different formatting and alignment rules, which is easier to do with this interface than with the original one based on passing in lists-of-lists.

2012-09-23

13:57:43

CHAPTER 5

Records and Variants

One of OCaml's best features is its concise and expressive system for declaring new datatypes. Two key elements of that system are *records* and *variants*, both of which we discussed briefly in chapter {{{GUIDEDTOUR}}}. In this chapter we'll cover records and variants in more depth, showing some of the more advanced features, as well as discuss how to use them effectively in your software designs.

Records

A record represents a collection of values stored together as one, where each component is identified by a different field name. The basic syntax for a record type declaration is as follows.

```
type <record-name> =  
  { <field-name> : <type-name> ;  
    <field-name> : <type-name> ;  
    ...  
  }
```

Here's a simple example, a `host_info` record that summarizes information about a given computer.

```
# type host_info =  
  { hostname   : string;  
    os_name    : string;  
    os_release : string;  
    cpu_arch   : string;  
  };;
```

We can construct a `host_info` just as easily. The following code uses the `Shell` module from `Core_extended` to dispatch commands to the shell to extract the information we need about the computer we're running on.

```
# open Core_extended.Std;;
```

```
# let my_host = { hostname = Shell.sh_one "hostname";
                  os_name   = Shell.sh_one "uname -s";
                  os_release = Shell.sh_one "uname -r";
                  cpu_arch  = Shell.sh_one "uname -p";
                };;
val my_host : host_info =
  {hostname = "Yarons-MacBook-Air.local"; os_name = "Darwin";
   os_release = "11.4.0"; cpu_arch = "i386"}
```

Once we have a record value in hand, we can extract elements from the record field using dot-notation.

```
# my_host.cpu_arch;;
- : string = "i386"
```

Pattern matching

Another way of getting information out of a record is by using a pattern match. In the following example, we use a pattern-match on the argument to a function.

```
# let host_info_to_string { hostname = h; os_name = os;
                           os_release = r; cpu_arch = c } =
    sprintf "%s (%s %s / %s)" h os r c;;
val host_info_to_string : host_info -> string = <fun>
# host_info_to_string my_host;;
- : string = "Yarons-MacBook-Air.local (Darwin 11.4.0 / i386)"
```

Notice that we didn't need a match statement because we used only a single pattern to match all possible records of type `host_info`. This works because record patterns are *irrefutable*, meaning that a single pattern is guaranteed to match any value of the type in question.

In other words, an irrefutable pattern is one where all of the requirements imposed by the pattern match are enforced by the type system, so that code that compiles will never have a runtime failure due to a failed match. This is in contrast to, say, lists, where it's easy to write a pattern match that fails at runtime. For example:

```
# let first_plus_second (x :: y :: _) = x + y;;
Characters 22-43:
    let first_plus_second (x :: y :: _) = x + y;;
                        ^^^^^^^^^^^^^^^^^^^^^^^^^
Warning 8: this pattern-matching is not exhaustive.
Here is an example of a value that is not matched:
[]
val first_plus_second : int list -> int = <fun>
# first_plus_second [5;3;6];;
- : int = 8
# first_plus_second [5];;
Exception: (Match_failure "" 1 22).
```


OCaml does offer an exhaustiveness check for record patterns, in particular, a warning for missing fields in a record pattern. With that warning turned on (which you can do in the toplevel by typing `#warnings "+9"`), the following code will complain about an inexhaustive match.

```
# let host_info_to_string
    { hostname = h; os_name = os; os_release = r } =
sprintf "%s (%s %s)" h os r;;
Characters 30-76:
    { hostname = h; os_name = os; os_release = r } =
    ^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^
```

Warning 9: the following labels are not bound in this record pattern:

cpu_arch

Either bind these labels explicitly or add `; _` to the pattern.

```
val host info to string : host info -> string = <fun>
```

Note that, unlike our previous example, ignoring this warning won't lead to a runtime error. The warning is nonetheless useful, because it gives you an opportunity to notice that there is some data that you're ignoring, which is often important.

We can disable the warning for a given pattern by explicitly acknowledging that we are ignoring extra fields by adding `_` to the pattern, as shown below.

```
# let host_info_to_string
  { hostname = h; os_name = os; os_release = r; _ } =
  sprintf "%s (%s %s)" h os r;;
val host_info_to_string : host_info -> string = <fun>
```

Field punning

When the name of a variable coincides with the name of a record field, OCaml provides some handy syntactic shortcuts. For example, the pattern in the following function binds all of the fields in question to variables of the same name. This is called *field punning*.

```
# let host_info_to_string { hostname; os_name; os_release; cpu_arch } =
  sprintf "%s (%s %s / %s)" hostname os_name os_release cpu_arch;;
val host_info_to_string : host_info -> string = <fun>
```

Field punning can also be used to construct a record. Consider the following code for generating a `host_info` record.

```
# let my_host =
  let hostname   = Shell.sh_one "hostname" in
  let os_name    = Shell.sh_one "uname -s" in
  let os_release = Shell.sh_one "uname -r" in
  let cpu_arch   = Shell.sh_one "uname -p" in
  { hostname; os_name; os_release; cpu_arch };;
val my_host : host info =
```

```
{hostname = "Yarons-MacBook-Air.local"; os_name = "Darwin";
  os_release = "11.4.0"; cpu_arch = "i386"}
```

In the above code, we defined variables corresponding to the record fields first, and then the record declaration itself simply listed the fields that needed to be included.

You can take advantage of both field punning and label punning when writing a function for constructing a record from labeled arguments, as shown below.

```
# let create_host_info ~hostname ~os_name ~os_release ~cpu_arch =
  let hostname = String.lowercase hostname in
  { hostname; os_name; os_release; cpu_arch };;
```

This is considerably more concise than what you would get without punning at all.

```
let create_host_info ~hostname:hostname ~os_name:os_name
  ~os_release:os_release ~cpu_arch:cpu_arch =
  let hostname = String.lowercase hostname in
  { hostname = hostname ; os_name = os_name;
    os_release = os_release; cpu_arch = cpu_arch };;
```

Together, labeled arguments, field names, and field and label punning, encourage a style where you carry names through your codebase, across different functions and modules. This is generally good practice, since it encourages consistent naming, which makes it easier for new people to navigate your source.

Reusing field names

Defining records with the same field names can be problematic. Let's consider a simple example: building types to represent the protocol used for a logging server. The following types represent messages a server might receive from a client.

Below, the `log_entry` message is used to deliver a log entry to the server for processing. The `logon` message is sent when a client initiates a connection, and includes the identity of the user connecting and credentials used for authentication. Finally, the `heartbeat` message is periodically sent by the client to demonstrate to the server that the client is alive and connected. All of these messages include a session id and the time the message was generated.

```
# type log_entry =
  { session_id: string;
    time: Time.t;
    important: bool;
    message: string;
  }
type heartbeat =
  { session_id: string;
    time: Time.t;
    status_message: string;
  }
```

```

type logon =
  { session_id: string;
    time: Time.t;
    user: string;
    credentials: string;
  }
;;

```

The fact that we reused field names will cause trouble when we try to construct a message.

```

# let create_log_entry ~session_id ~important message =
  { time = Time.now (); session_id; important; message }
;;
Characters 75-129:
  { time = Time.now (); session_id; important; message }
  ^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^
Error: The record field label important belongs to the type log_entry
      but is mixed here with labels of type logon

```

The problem is that the declaration of `logon` (and `heartbeat`) shadowed some of the fields of `log_entry`. As a result, the fields `time` and `session_id` are assumed to be fields of `logon`, and `important` and `message`, which were not shadowed, are assumed to be a field of `log_entry`. The compiler therefore complains that we're trying to construct a record with fields from two different record types.

There are two common solutions to this problem. The first is to add a prefix to each field name to make it unique. Thus, we could define `heartbeat` and `logon` as follows:

```

# type log_entry =
  { log_entry_session_id: string;
    log_entry_time: Time.t;
    log_entry_important: bool;
    log_entry_message: string;
  }
type heartbeat =
  { heartbeat_session_id: string;
    heartbeat_time: Time.t;
    heartbeat_status_message: string;
  }
type logon =
  { logon_session_id: string;
    logon_time: Time.t;
    logon_user: string;
    logon_credentials: string;
  }
;;

```

This eliminates the collisions and is simple enough to do. But it leaves you with awkwardly named record fields, and adds needless repetition and verbosity to your code.

Another approach is to mint a module for each type. This is actually a broadly useful idiom, providing for each type a namespace within which to put related values. Using this style we would write:

```
# module Log_entry = struct
  type t =
    { session_id: string;
      time: Time.t;
      important: bool;
      message: string;
    }
end
module Heartbeat = struct
  type t =
    { session_id: string;
      time: Time.t;
      status_message: string;
    }
end
module Logon = struct
  type t =
    { session_id: string;
      time: Time.t;
      user: string;
      credentials: string;
    }
end;;
```

Now, our heartbeat-creation function can be rendered as follows.

```
# let create_log_entry ~session_id ~important message =
  { Log_entry.time = Time.now (); Log_entry.session_id;
    Log_entry.important; Log_entry.message }
;;
val create_log_entry :
  session_id:string -> important:bool -> string -> Log_entry.t = <fun>
```

The module name `Log_entry` is required to qualify the fields, because this function is outside of the `Log_entry` module where the record was defined. OCaml only requires the module qualification for one record field, however, so we can write this more concisely.

```
# let create_log_entry ~session_id ~important message =
  { Log_entry.time = Time.now (); session_id; important; message }
;;
val create_log_entry :
  session_id:string -> important:bool -> string -> Log_entry.t = <fun>
```

For functions defined within the module where a given record is defined, the module qualification goes away entirely. And indeed, for things like constructors, defining it within the module is often the best solution.

Functional updates

Fairly often, you will find yourself wanting to create a new record that differs from an existing record in only a subset of the fields. For example, imagine our logging server had a record type for representing the state of a given client, including when the last heartbeat was received from that client. The following defines a type for representing this information, as well as a function for updating the client information when a new heartbeat arrives.

```
# type client_info =
  { addr: Unix.Inet_addr.t;
    port: int;
    user: string;
    credentials: string;
    last_heartbeat_time: Time.t;
  };;
# let register_heartbeat t hb =
  { addr = t.addr;
    port = t.port;
    user = t.user;
    credentials = t.credentials;
    last_heartbeat_time = hb.Heartbeat.time;
  };;
val register_heartbeat : client_info -> Heartbeat.t -> client_info = <fun>
```

This is fairly verbose, given that there's only one field that we actually want to change, and all the others are just being copied over from `t`. We can use OCaml's *functional update* syntax to do this more tersely. The syntax of a functional update is as follows.

```
{ <record-value> with <field> = <value>;
                  <field> = <value>;
                  ...
}
```

The purpose of the functional update is to create a new record based on an existing one, with a set of field changes layered on top.

Given this, we can rewrite `register_heartbeat` more concisely.

```
# let register_heartbeat t hb =
  { t with last_heartbeat_time = hb.Heartbeat.time };;
```

Functional updates make your code independent of the identity of the fields in the record that are not changing. This is often what you want, but it has downsides as well. In particular, if you change the definition of your record to have more fields, the type system will not prompt you to reconsider whether your update code should affect those fields. Consider what happens if we decided to add a field for the status message received on the last heartbeat.

```
# type client_info =
```

```
{ addr: Unix.Inet_addr.t;
  port: int;
  user: string;
  credentials: string;
  last_heartbeat_time: Time.t;
  last_heartbeat_status: string;
};;
```

The original implementation of `register_heartbeat` would now be invalid, and thus the compiler would warn us to think about how to handle this new field. But the version using a functional update continues to compile as is, even though it incorrectly ignores the new field. The correct thing to do would be to update the code as follows.

```
# let register_heartbeat t hb =
  { t with last_heartbeat_time = hb.Heartbeat.time;
        last_heartbeat_status = hb.Heartbeat.status_message;
  };;
```

The lesson here is that when you use a functional update, you should be confident that the full effect of the update will be registered by updating just the fields in question, even if the record changes later.

First-class fields

Consider the following function for extracting the usernames from a list of `Logon` messages.

```
# let get_users logons =
  List.map logons ~f:(fun x -> x.Logon.user);;
val get_hostnames : Logon.t list -> string list = <fun>
```

Here, we wrote a small function (`fun x -> x.Logon.user`) to access the `user` field. This kind of accessor function is a common enough pattern that that it would be convenient to generate them automatically. The `fieldslib` syntax extension that ships with `Core` does just that.

`fieldslib` is invoked by putting the `with fields` annotation at the end of the declaration of a record type. So, for example, we could have defined `Logon` as follows.

```
# module Logon = struct
  type t =
    { session_id: string;
      time: Time.t;
      user: string;
      credentials: string;
    }
  with fields
end;;
```

Given that definition, we can use the function `Logon.user` to extract the user field from a logon message.

```
# let get_users logons = List.map logons ~f:Logon.user;;
val get_users : Logon.t list -> string list = <fun>
```

In addition to generating field accessor functions, `fieldslib` also creates a sub-module called `Fields` that contains a first class representative of each field, in the form of a value of type `Field.t`. A `Field.t` bundles up the following functionality of a record field:

- The name of the field as a string
- The ability to extract the field
- The ability to do a functional update of that field
- The (optional) ability to set the record field, which is present only if the field is mutable. We'll talk more about mutable record fields in chapter `{{MUTABILITY}}`.

We can use these first class fields to do things like write a generic function for displaying a record field. The function `show_field` takes three arguments: the `Field.t`, a function for converting the contents of the field in question to a string, and the record type.

```
# let show_field field to_string record =
  sprintf "%s: %s" (Field.name field) (Field.get field record |> to_string);;
val show_field : ('a, 'b) Field.t -> ('b -> string) -> 'a -> string =
  <fun>
```

Here's an example of `show_field` in action.

```
# let logon = { Logon.
  session_id = "26685";
  time = Time.now ();
  user = "yminsky";
  credentials = "Xy2d9W"; }
;;
# show_field Logon.Fields.user Fn.id logon;;
- : string = "user: yminsky"
# show_field Logon.Fields.time Time.to_string logon;;
- : string = "time: 2012-06-26 18:44:13.807826"
```

`fieldslib` also provides higher-level operators, like `Fields.fold` and `Fields.iter`, which let you iterate over all the fields of a record. The following function uses `Logon.Fields.iter` and `show_field` to print out all the fields of a `Logon` record.

```
# let print_logon logon =
  let print to_string field =
    printf "%s\n" (show_field field to_string logon)
  in
  Logon.Fields.iter
    ~session_id:(print Fn.id)
```

```

    ~time:(print Time.to_string)
    ~user:(print Fn.id)
    ~credentials:(print Fn.id)
  ;;
val print_logon : Logon.t -> unit = <fun>
# print_logon logon;;
session_id: 26685
time: 2012-06-26 18:44:13.807826
user: yminsky
credentials: Xy2d9W
- : unit = ()

```

The advantage of using field iterators is that when the definition of `Logon` changes, `iter` will change along with it, prompting you to handle whatever new cases arise.

Field iterators are useful for a variety of tasks, from building validation functions to scaffolding the definition of a web-form based on a record type, all with a guarantee that you've exhaustively considered all elements of the field.

Variants

Variant types are used to represent multiple different possibilities, where each possibility is identified by a different *constructor*. The syntax of a variant type declaration is as follows.

```

type <variant-name> =
  | <Constructor1> [of <arg1> * .. * <argn>]?
  | <Constructor2> [of <arg1> * .. * <argn>]?
  ...

```

To give a better sense of why variants are useful, we'll walk through a concrete example of variants in action.

Example: terminal colors

Almost all terminals support a set of 8 basic colors, which we can represent with the following variant type.

```

# type basic_color =
  Black | Red | Green | Yellow | Blue | Magenta | Cyan | White;;

```

This is a particularly simple form of variant, in that the constructors don't have arguments. Such variants are very similar to the enumerations found in many languages, including C and Java.

We can construct instances of `basic_color` by simply writing out the constructors in question.


```
# [Black;Blue;Red];;
- : basic_color list = [Black; Blue; Red]
```

Pattern matching can be used to process a variant. Consider the following function which converts each `basic_color` to a corresponding integer. As we'll see, these integers will be used to compute escape codes for setting colors in the terminal.

```
# let basic_color_to_int = function
| Black -> 0 | Red    -> 1 | Green -> 2 | Yellow -> 3
| Blue  -> 4 | Magenta -> 5 | Cyan  -> 6 | White  -> 7 ;;
val basic_color_to_int : basic_color -> int = <fun>
```

Note that the exhaustiveness checking on pattern matches means that the compiler will warn us if we miss a case in the pattern match.

Using `basic_color_to_int`, we can now generate the escape codes to change the color of a given string.

```
# let color_by_number number text =
  sprintf "\027[38;5;%dm%s\027[0m" number text;;
  val color_by_number : int -> string -> string = <fun>
# let s = color_by_number (basic_color_to_int Blue) "Hello Blue World!";;
val s : string = "\027[38;5;4mHello Blue World!\027[0m"
# printf "%s\n" s;;
Hello Blue World!
- : unit = ()
```

On most terminals, that last line is printed in blue.

Full terminal colors

The simple enumeration of `basic_color` isn't enough to fully describe the set of colors that a modern terminal can display. `xterms` (and many other terminal programs) support 256 different colors, broken up into the following groups.

- The 8 basic colors, in regular and bold versions.
- A $6 \times 6 \times 6$ RGB color cube
- A 24-level grayscale ramp

We can represent this more complicated colorspace as a variant, but this time, the different constructors will have arguments, to describe the data available in each case.

```
# type weight = Regular | Bold
type color =
| Basic of basic_color * weight (* basic colors, regular and bold *)
| RGB   of int * int * int      (* 6x6x6 color cube *)
| Gray  of int                  (* 24 grayscale levels *)
;;
```

In order to compute the color code for a `color`, we use pattern matching to break down the `color` variant into the appropriate cases.

```
# let color_to_int = function
| Basic (basic_color,weight) ->
  let base = match weight with Bold -> 8 | Regular -> 0 in
  base + basic_color_to_int basic_color
| RGB (r,g,b) -> 16 + b + g * 6 + r * 36
| Gray i -> 232 + i ;;
val color_to_int : color -> int = <fun>
```

Catch-all cases and refactoring

OCaml's static checks can act as a form of refactoring tool, where the compiler warns you of places where your code needs to be adapted to changes made elsewhere. This shows up quite a bit when defining variant types.

Consider what would happen if we were to change the definition of `color` to the following.

```
# type color =
| Basic of basic_color      (* basic colors *)
| Bold  of basic_color      (* bold basic colors *)
| RGB   of int * int * int  (* 6x6x6 color cube *)
| Gray  of int              (* 24 grayscale levels *)
;;
```

Under this definition, `color_to_int` is wrong in two ways. First, the type of the contents of `Basic` have changed from having two arguments to having just one, and `color_to_int` still expects two.

```
# let color_to_int = function
| Basic (basic_color,weight) ->
  let base = match weight with Bold -> 8 | Regular -> 0 in
  base + basic_color_to_int basic_color
| RGB (r,g,b) -> 16 + b + g * 6 + r * 36
| Gray i -> 232 + i ;;
Characters 40-60:
Error: This pattern matches values of type 'a * 'b
      but a pattern was expected which matches values of type basic_color
```

Once we fix that, however, there's another problem, which is that we haven't handled the new `Bold` constructor.

```
# let color_to_int = function
| Basic basic_color -> basic_color_to_int basic_color
| RGB (r,g,b) -> 16 + b + g * 6 + r * 36
| Gray i -> 232 + i ;;
Characters 19-154:
Warning 8: this pattern-matching is not exhaustive.
Here is an example of a value that is not matched:
Bold
val color_to_int : color -> int = <fun>
```

Fixing this leads us to the correct implementation.

```
# let color_to_int = function
| Basic basic_color -> basic_color_to_int basic_color
| Bold basic_color -> 8 + basic_color_to_int basic_color
| RGB (r,g,b) -> 16 + b + g * 6 + r * 36
| Gray i -> 232 + i ;;
val color_to_int : color -> int = <fun>
```

Here, the type system has worked as a refactoring tool, identifying the places in our code that needed to be fixed. But for this refactoring to work well, there are some pitfalls you need to avoid in your code. In particular, you should avoid catch-all cases in pattern matches.

Imagine we wanted `color_to_int` to render the first 16 colors (the 8 `basic_colors` in regular and bold) in the expected way, but render everything else as white. We might have written the function as follows.

```
# let color_to_int = function
| Basic (basic_color,weight) ->
  let base = match weight with Bold -> 8 | Regular -> 0 in
  base + basic_color_to_int basic_color
| _ -> basic_color_to_int White;;
val color_to_int : color -> int = <fun>
```

But because the catch-all case encompasses all possibilities, the type system will no longer warn us that we have missed the new `Bold` case when we change the type to include it. To get the full power out of the static checks provided by the compiler, we need to be explicit about which cases are being handled by which branch of a pattern match, as we do below.

```
# let color_to_int = function
| Basic (basic_color,weight) ->
  let base = match weight with Bold -> 8 | Regular -> 0 in
  base + basic_color_to_int basic_color
| RGB _ | Gray _ -> basic_color_to_int White;;
val color_to_int : color -> int = <fun>
```

Using the above function, we can print text using the full set of available colors.

```
# let color_print color s =
  printf "%s\n" (color_by_number (color_to_int color) s);;
val color_print : color -> string -> unit = <fun>
# color_print (Basic (Red,Bold)) "A bold red!";;
A bold red!
- : unit = ()
# color_print (Gray 4) "A muted gray...";;
A muted gray...
- : unit = ()
```

Combining records and variants

Variants and records serve quite different purposes. Consider again the type `Log_entry.t` from section `[[REUSING FIELD NAMES]]`:

```
module Log_entry = struct
  type t =
    { session_id: string;
      time: Time.t;
      important: bool;
      message: string;
    }
end
```

This record type combines multiple pieces of data into one value. In particular, a single `Log_entry.t` has a *session_id* *and* a *time* *and* an *important* flag *and* a *message*. More generally, you can think of record types as acting as conjunctions. Variants, on the other hand, are disjunctions, letting you represent multiple possibilities. Consider the following variant type.

```
type client_message = | Logon of Logon.t
                     | Heartbeat of Heartbeat.t
                     | Log_entry of Log_entry.t
```

A `client_message` is a *Logon* *or* a *Heartbeat* *or* a *Log_entry*. If we want to write code that processes messages generically, rather than code specialized to a fixed message type, we need a type like `client_message` to unify the different message types into one overarching type.

Variants and records are most effective when used in concert, with variants used to represent true differences between different types, and records used to represent the parts that remain constant. As an example, consider the following function that takes a list of `client_messages` and returns all messages generated by a given user. The code in question is implemented by folding over the list of messages, where the accumulator is a pair of:

- the set of session identifiers for the user in question.
- the set of messages that have occurred under a session identifier known to be associated with a given user.

Here's the concrete code.

```
let messages_for_user user messages =
  let (user_messages, _) =
    List.fold messages ~init:([],String.Set.empty)
      ~f:(fun ((messages,user_sessions) as acc) message ->
        match message with
        | Logon m ->
          if m.Logon.user = user then
```

```

        (message::messages, Set.add user_sessions m.Logon.session_id)
      else acc
    | Heartbeat _ | Log_entry _ ->
      let session_id = match message with
        | Logon      m -> m.Logon.session_id
        | Heartbeat m -> m.Heartbeat.session_id
        | Log_entry m -> m.Log_entry.session_id
      in
      if Set.mem user_sessions session_id then
        (message::messages, user_sessions)
      else acc
    )
  in
  List.rev user_messages

```

There's one awkward bit about the code above, which is the calculation of the session ids. In particular, we have the following repetitive snippet of code:

```

let session_id = match message with
| Logon      m -> m.Logon.session_id
| Heartbeat m -> m.Heartbeat.session_id
| Log_entry m -> m.Log_entry.session_id
in

```

This code effectively computes the session id for each underlying message type. The repetition in this case isn't that bad, but would become problematic in larger and more complicated examples.

We can improve the code by refactoring our types to explicitly separate which parts are shared and which are common. The first step is to cut down the definitions of the per-message records to just contain the unique components of each message.

```

module Log_entry = struct
  type t = { important: bool;
            message: string;
            }
end

module Heartbeat = struct
  type t = { status_message: string; }
end

module Logon = struct
  type t = { user: string;
            credentials: string;
            }
end

```

We can then define a variant type that covers the different possible unique components.

```

type details =
| Logon of Logon.t

```

```
| Heartbeat of Heartbeat.t
| Log_entry of Log_entry.t
```

Separately, we need a record that contains the fields that are common across all messages.

```
module Common = struct
  type t = { session_id: string;
             time: Time.t;
           }
end
```

A full message can then be represented as a pair of a `Common.t` and a `details`. Using this, we can rewrite our example above as follows:

```
let messages_for_user user messages =
  let (user_messages, _) =
    List.fold messages ~init:([],String.Set.empty)
      ~f:(fun ((messages,user_sessions) as acc) ((common,details) as message) ->
        let session_id = common.Common.session_id in
        match details with
        | Logon m ->
          if m.Logon.user = user then
            (message::messages, Set.add user_sessions session_id)
          else acc
        | Heartbeat _ | Log_entry _ ->
          if Set.mem user_sessions session_id then
            (message::messages,user_sessions)
          else acc
      )
  in
  List.rev user_messages
```

Note that the more complex match statement for computing the session id has been replaced with the simple expression `common.Common.session_id`.

This basic design is good in another way: it allows us to essentially downcast to the specific message type once we know what it is, and then dispatch code to handle just that message type. In particular, while we use the type `Common.t * details` to represent an arbitrary message, we can use `Common.t * Logon.t` to represent a logon message. Thus, if we had functions for handling individual message types, we could write a dispatch function as follows.

```
let handle_message server_state (common,details) =
  match details with
  | Log_entry m -> handle_log_entry server_state (common,m)
  | Logon m -> handle_logon server_state (common,m)
  | Heartbeat m -> handle_heartbeat server_state (common,m)
```

And it's explicit at the type level that `handle_log_entry` sees only `Log_entry` messages, `handle_logon` sees only `Logon` messages, etc.

Polymorphic variants

More advanced declarations

Polymorphic types

Recursive types

2012-09-23

13:57:43

CHAPTER 6

Error Handling

Nobody likes dealing with errors. It's tedious, it's easy to get wrong, and it's usually just not as fun as planning out how your program is going to succeed. But error handling is important, and however much you don't like thinking about it, having your software fail due to poor error handling code is worse.

Thankfully, OCaml has powerful tools for handling errors reliably and with a minimum of pain. In this chapter we'll discuss some of the different approaches in OCaml to handling errors, and give some advice on how to design interfaces that help rather than hinder error handling.

We'll start by describing the two basic approaches for reporting errors in OCaml: error-aware return types and exceptions.

Error-aware return types

The best way in OCaml to signal an error is to include that error in your return value. Consider the type of the `find` function in the `list` module.

```
# List.find;;  
- : 'a list -> f:( 'a -> bool) -> 'a option
```

The `option` in the return type indicates that the function may not succeed in finding a suitable element, as you can see below.

```
# List.find [1;2;3] ~f:(fun x -> x >= 2) ;;  
- : int option = Some 2  
# List.find [1;2;3] ~f:(fun x -> x >= 10) ;;  
- : int option = None
```

Having errors be explicit in the return values of your functions tells the caller that there is an error that needs to be handled. The caller can then handle the error explicitly, either recovering from the error or propagating it onward.

The function `compute_bounds` below is an example of how you can handle errors in this style. The function takes a list and a comparison function, and returns upper and lower bounds for the list by finding the smallest and largest element on the list. `List.hd` and `List.last`, which return `None` when they encounter an empty list, are used to extract the largest and smallest element of the list.

```
# let compute_bounds ~cmp list =
  let sorted = List.sort ~cmp list in
  let smallest = List.hd sorted in
  let largest = List.last sorted in
  match smallest, largest with
  | None, _ | _, None -> None
  | Some x, Some y -> Some (x,y)
;;
val compute_bounds :
  cmp:('a -> 'a -> int) -> 'a list -> ('a * 'a) option = <fun>
```

The match statement is used to handle the error cases, propagating an error in `hd` or `last` into the return value of `compute_bounds`. On the other hand, in `find_mismatches` below, errors encountered during the computation do not propagate to the return value of the function. `find_mismatches` takes two hashtables as its arguments and tries to find keys that are stored in both. As such, a failure to find a key in one of the tables isn't really an error.

```
# let find_mismatches table1 table2 =
  Hashtbl.fold table1 ~init:[] ~f:(fun ~key ~data errors ->
    match Hashtbl.find table2 key with
    | Some data' when data' <> data -> key :: errors
    | _ -> errors
  )
;;
val find_mismatches :
  ('a, 'b) Hashtbl.t -> ('a, 'b) Hashtbl.t -> 'a list = <fun>
```

The use of options to encode errors underlines the fact that it's not clear whether a particular outcome, like not finding something on a list, is really an error, or just another valid outcome of your function. This turns out to be very context-dependent, and error-aware return types give you a uniform way of handling the result that works well for both situations.

Encoding errors with Result

Options aren't always a sufficiently expressive way to report errors. Specifically, when you encode an error as `None`, there's nowhere to say anything about the nature of the error.

`Result.t` is meant to address this deficiency. Here's the definition:

```
module Result : sig
```

```

type ('a,'b) t = | Ok of 'a
                | Error of 'b
end

```

A `Result.t` is essentially an option augmented with the ability to store other information in the error case. Like `Some` and `None` for options, the constructors `Ok` and `Error` are promoted to the top-level by `Core.Std`. As such, we can write:

```

# [ Ok 3; Error "abject failure"; Ok 4 ];;
[Ok 3; Error "abject failure"; Ok 4]
- : (int, string) Result.t list =
[Ok 3; Error "abject failure"; Ok 4]

```

without first opening the `Result` module.

Error and `Or_error`

`Result.t` gives you complete freedom to choose the type of value you use to represent errors, but it's often useful to standardize on an error type. Among other things, this makes it easier to write utility functions to automate common error handling patterns.

But which type to choose? Is it better to represent errors as strings? Or S-expressions? Or something else entirely?

Core's answer to this question is the `Error.t` type, which tries to forge a good compromise between efficiency, convenience and control over the presentation of errors.

It might not be obvious at first why efficiency is an issue at all. But generating error messages is an expensive business. An ASCII representation of a type can be quite time-consuming to construct, particularly if it includes expensive-to-convert numerical datatypes.

`Error` gets around this issue through laziness. In particular, an `Error.t` allows you to put off generation of the actual error string until you actually need, which means a lot of the time you never have to construct it at all. You can of course construct an error directly from a string:

```

# Error.of_string "something went wrong";;
- : Core.Std.Error.t = "something went wrong"

```

A more interesting construction message from a performance point of view is to construct an `Error.t` from a thunk:

```

# Error.of_thunk (fun () ->
  sprintf "something went wrong: %f" 32.3343);;
- : Core.Std.Error.t = "something went wrong: 32.334300"

```

In this case, we can benefit from the laziness of `Error`, since the thunk won't be called until the `Error.t` is converted to a string.

We can also create an `Error.t` based on an s-expression converter. This is probably the most common idiom in Core.

```
# Error.create "Something failed a long time ago" Time.epoch Time.sexp_of_t;;
- : Core.Std.Error.t =
  "Something failed a long time ago: (1969-12-31 19:00:00.000000)"
```

Here, the value `Time.epoch` is included in the error, but `Time.sexp_of_t`, which is used for converting the time to an s-expression, isn't run until the error is converted to a string. Using the `Sexplib` syntax-extension, which is discussed in more detail in chapter `{SYNTAX}`, we can inline create an s-expression converter for a collection of types, thus allowing us to register multiple pieces of data in an `Error.t`.

```
# Error.create "Something went terribly wrong"
  (3.5, ["a";"b";"c"],6034)
  <:sexp_of<float * string list * int>> ;;
- : Core.Std.Error.t = "Something went terribly wrong: (3.5(a b c)6034)"
```

Here, the declaration `<:sexp_of<float * string list * int>>` asks `Sexplib` to generate the sexp-converter for the tuple.

Error also has operations for transforming errors. For example, it's often useful to augment an error with some extra information about the context of the error, or to combine multiple errors together. `Error.of_list` and `Error.tag` fill these roles.

The type `'a Or_error.t` is just a shorthand for `('a,Error.t) Result.t`, and it is, after option, the most common way of returning errors in Core.

bind and other error-handling idioms

As you write more error handling code, you'll discover that certain patterns start to emerge. A number of these common patterns been codified in the interfaces of modules like `Option` and `Result`. One particularly useful one is built around the function `bind`, which is both an ordinary function and an infix operator `>>=`, both with the same type signature:

```
val (>>=) : 'a option -> ('a -> 'b option) -> 'b option
```

`bind` is a way of sequencing together error-producing functions so that that the first one to produce an error terminates the computation. In particular, `None >>= f` returns `None` without calling `f`, and `Some x >>= f` returns `f x`. We can use a nested sequence of these binds to express a multi-stage computation that can fail at any stage. Here's a rewrite `compute_bounds` in this style.

```
# let compute_bounds ~cmp list =
  let open Option.Monad_infix in
  let sorted = List.sort ~cmp list in
  List.hd sorted >>= (fun first ->
```

```
List.last sorted >>= (fun last ->
  Some (first,last)))
```

Note that we locally open the `Option.Monad_infix` module to get access to the infix operator `>>=`. The module is called `Monad_infix` because the bind operator is part of a sub-interface called `Monad`, which we'll talk about more in chapter `{{ASYNC}}`.

This is a bit easier to read if we write it with fewer parentheses and less indentation, as follows.

```
# let compute_bounds ~cmp list =
  let open Option.Monad_infix in
  let sorted = List.sort ~cmp list in
  List.hd sorted >>= fun first ->
  List.last sorted >>= fun last ->
  Some (first,last)
```

There are other useful idioms encoded in the functions in `Option`. Another example is `Option.both`, which takes two optional values and produces a new optional pair that is `None` if either of its arguments are `None`. Using `Option.both`, we can make `compute_bounds` even shorter.

```
# let compute_bounds ~cmp list =
  let sorted = List.sort ~cmp list in
  Option.both (List.hd sorted) (List.last sorted)
```

These error-handling functions are valuable because they let you express your error handling both explicitly and concisely. We've only discussed these functions in the context of the `Option` module, but similar functionality is available in both `Result` and `Or_error`.

Exceptions

Exceptions in OCaml are not that different from exceptions in many other languages, like Java, C# and Python. In all these cases, exceptions are a way to terminate a computation and report an error, while providing a mechanism to catch and handle (and possibly recover from) exceptions that are triggered by sub-computations.

We'll see an exception triggered in OCaml if, for example, we try to divide an integer by zero:

```
# 3 / 0;;
Exception: Division_by_zero.
```

And an exception can terminate a computation even if it happens nested a few levels deep in a computation.

```
# List.map ~f:(fun x -> 100 / x) [1;3;0;4];;
Exception: Division_by_zero.
```

In addition to built-in exceptions like `Divide_by_zero`, OCaml lets you define your own.

```
# exception Key_not_found of string;;
exception Key_not_found of string
# Key_not_found "a";;
- : exn = Key_not_found("a")
```

Here's an example of a function for looking up a key in an *association list*, *i.e.* a list of key/value pairs which uses this newly-defined exception:

```
# let rec find_exn alist key = match alist with
  | [] -> raise (Key_not_found key)
  | (key',data) :: tl -> if key = key' then data else find_exn tl key
;;
val find_exn : (string * 'a) list -> string -> 'a = <fun>
# let alist = [("a",1); ("b",2)];;
val alist : (string * int) list = [("a", 1); ("b", 2)]
# find_exn alist "a";;
- : int = 1
# find_exn alist "c";;
Exception: Key_not_found("c").
```

Note that we named the function `find_exn` to warn the user that the function routinely throws exceptions, a convention that is used heavily in Core.

In the above example, `raise` throws the exception, thus terminating the computation. The type of `raise` is a bit surprising when you first see it:

```
# raise;;
- : exn -> 'a = <fun>
```

Having the return type be an otherwise unused type variable `'a` suggests that `raise` could return a value of any type. That seems impossible, and it is. `raise` has this type because it never returns at all. This behavior isn't restricted to functions like `raise` that terminate by throwing exceptions. Here's another example of a function that doesn't return a value.

```
# let rec forever () = forever ();;
val forever : unit -> 'a = <fun>
```

`forever` doesn't return a value for a different reason: it is an infinite loop.

This all matters because it means that the return type of `raise` can be whatever it needs to be to fit in to the context it is called in. Thus, the type system will let us throw an exception anywhere in a program.

Declaring exceptions with `sexp`

OCaml can't always generate a useful textual representation of your exception, for example:

```
# exception Wrong_date of Date.t;;
exception Wrong_date of Date.t
# Wrong_date (Date.of_string "2011-02-23");;
- : exn = Wrong_date(_)
```

But if you declare the exception using `with sexp` (and the constituent types have `sexp` converters), we'll get something with more information.

```
# exception Wrong_date of Date.t with sexp;;
exception Wrong_date of Core.Std.Date.t
# Wrong_date (Date.of_string "2011-02-23");;
- : exn = (.Wrong_date 2011-02-23)
```

The period in front of `Wrong_date` is there because the representation generated by `with sexp` includes the full module path of the module where the exception in question is defined. This is quite useful in tracking down which precise exception is being reported. In this case, since we've declared the exception at the toplevel, that module path is trivial.

Exception handlers

So far, we've only seen exceptions fully terminate the execution of a computation. But often, we want a program to be able to respond to and recover from an exception. This is achieved through the use of *exception handlers*.

In OCaml, an exception handler is declared using a `try/with` statement. Here's the basic syntax.

```
try <expr> with
| <pat1> -> <expr1>
| <pat2> -> <expr2>
...
```

A `try/with` clause would first evaluate `<expr>`, and if that evaluation completes without returning an exception, then the value of the overall expression is the value of `<expr>`.

But if evaluating `<expr>` leads to an exception being thrown, then the exception will be fed to the pattern match statements following the `with`. If the exception matches a pattern, then the expression on the right hand side of that pattern will be evaluated. Otherwise, the original exception continues up the call stack, to be handled by the next outer exception handler, or terminate the program if there is none.

Cleaning up in the presence of exceptions

One headache with exceptions is that they can terminate your execution at unexpected places, leaving your program in an awkward state. Consider the following code snippet:

```
let load_config filename =
```

```

let inc = In_channel.create filename in
let config = Config.t_of_sexp (Sexp.input_sexp inc) in
In_channel.close inc;
config

```

The problem with this code is that the function that loads the s-expression and parses it into a `Config.t` might throw an exception if the config file in question is malformed. Unfortunately, that means that the `In_channel.t` that was opened will never be closed, leading to a file-descriptor leak.

We can fix this using Core's `protect` function. The basic purpose of `protect` is to ensure that the `finally` thunk will be called when `f` exits, whether it exited normally or with an exception. Here's how it could be used to fix `load_config`.

```

let load_config filename =
  let inc = In_channel.create filename in
  protect ~f:(fun () -> Config.t_of_sexp (Sexp.input_sexp inc))
    ~finally:(fun () -> In_channel.close inc)

```

Catching specific exceptions

OCaml's exception-handling system allows you to tune your error-recovery logic to the particular error that was thrown. For example, `List.find_exn` always throws `Not_found`. You can take advantage of this in your code, for example, let's define a function called `lookup_weight`, with the following signature:

```

(** [lookup_weight ~compute_weight alist key] Looks up a
    floating-point weight by applying [compute_weight] to the data
    associated with [key] by [alist]. If [key] is not found, then
    return 0.
*)
val lookup_weight :
  compute_weight:('data -> float) -> ('key * 'data) list -> 'key -> float

```

We can implement such a function using exceptions as follows:

```

# let lookup_weight ~compute_weight alist key =
  try
    let data = List.Assoc.find_exn alist key in
    compute_weight data
  with
    Not_found -> 0. ;;
val lookup_weight :
  compute_weight:('a -> float) -> ('b * 'a) list -> 'b -> float =
  <fun>

```

This implementation is more problematic than it looks. In particular, what happens if `compute_weight` itself throws an exception? Ideally, `lookup_weight` should propagate that exception on, but if the exception happens to be `Not_found`, then that's not what will happen:


```
# lookup_weight ~compute_weight:(fun _ -> raise Not_found)
  ["a",3; "b",4] "a" ;;
- : float = 0.
```

This kind of problem is hard to detect in advance, because the type system doesn't tell us what kinds of exceptions a given function might throw. Because of this kind of confusion, it's usually better to avoid catching specific exceptions. In this case, we can improve the code by catching the exception in a narrower scope.

```
# let lookup_weight ~compute_weight alist key =
  match
    try Some (List.Assoc.find_exn alist key) with
    | Not_found -> None
  with
  | None -> 0.
  | Some data -> compute_weight data ;;
```

At which point, it makes sense to simply use the non-exception throwing function, `List.Assoc.find`, instead.

Backtraces

A big part of the point of exceptions is to give useful debugging information. But at first glance, OCaml's exceptions can be less than informative. Consider the following simple program.

```
(* exn.ml *)

open Core.Std
exception Empty_list

let list_max = function
| [] -> raise Empty_list
| hd :: tl -> List.fold tl ~init:hd ~f:(Int.max)

let () =
  printf "%d\n" (list_max [1;2;3]);
  printf "%d\n" (list_max [])
```

If we build and run this program, we'll get a pretty uninformative error:

```
$ ./exn
3
Fatal error: exception Exn.Empty_list
```

The example in question is short enough that it's quite easy to see where the error came from. But in a complex program, simply knowing which exception was thrown is usually not enough information to figure out what went wrong.

We can get more information from OCaml if we turn on stack traces. This can be done by setting the `OCAMLRUNPARAM` environment variable, as shown:

```
exn $ export OCAMLRUNPARAM=b
exn $ ./exn
3
Fatal error: exception Exn.Empty_list
Raised at file "exn.ml", line 7, characters 16-26
Called from file "exn.ml", line 12, characters 17-28
```

Backtraces can also be obtained at runtime. In particular, `Exn.backtrace` will return the backtrace for the most recently thrown exception.

Exceptions for control flow

From exceptions to error-aware types and back again

Both exceptions and error-aware types are necessary parts of programming in OCaml. As such, you often need to move between these two worlds. Happily, Core comes with some useful helper functions to help you do just that. For example, given a piece of code that can throw an exception, you can capture that exception into an option as follows:

```
# let find alist key =
  Option.try_with (fun () -> find_exn alist key) ;;
val find : (string * 'a) list -> string -> 'a option = <fun>
# find ["a",1; "b",2] "c";;
- : int Core.Std.Option.t = None
# find ["a",1; "b",2] "b";;
- : int Core.Std.Option.t = Some 2
```

And `Result` and `Or_error` have similar `try_with` functions. So, we could write:

```
# let find alist key =
  Result.try_with (fun () -> find_exn alist key) ;;
val find : (string * 'a) list -> string -> ('a, exn) Result.t = <fun>
# find ["a",1; "b",2] "c";;
- : (int, exn) Result.t = Result.Error Key_not_found("c")
```

And then we can re-raise that exception:

```
# Result.ok_exn (find ["a",1; "b",2] "b");;
- : int = 2
# Result.ok_exn (find ["a",1; "b",2] "c");;
Exception: Key_not_found("c").
```

CHAPTER 7

Files, Modules and Programs

We've so far experienced OCaml only through the toplevel. As you move from exercises to real-world programs, you'll need to leave the toplevel behind and start building programs from files. Files are more than just a convenient way to store and manage your code; in OCaml, they also act as abstraction boundaries that divide your program into conceptual components.

In this chapter, we'll show you how to build an OCaml program from a collection of files, as well as the basics of working with modules and module signatures.

Single File Programs

We'll start with an example: a utility that reads lines from `stdin`, computing a frequency count of the lines that have been read in. At the end, the 10 lines with the highest frequency counts are written out. Here's a simple implementation, which we'll save as the file `freq.ml`. Note that we're using several functions from the `List.Assoc` module, which provides utility functions for interacting with association lists, *i.e.*, lists of key/value pairs.

```
(* freq.ml: basic implementation *)

open Core.Std

(* build_counts recursively builds up a mapping from lines to
   number of occurrences of that line. *)
let rec build_counts counts =
  match In_channel.input_line stdin with
  | None -> counts (* EOF, so return the counts accumulated so far *)
  | Some line ->
    (* get the number of times this line has been seen before,
       inferring 0 if the line doesn't show up in [counts] *)
    let count =
      match List.Assoc.find counts line with
      | None -> 0
      | Some x -> x
```

```

    in
    (* increment the count for line by 1, and recurse *)
    build_counts (List.Assoc.add counts line (count + 1))

let () =
  (* Compute the line counts *)
  let counts = build_counts [] in
  (* Sort the line counts in descending order of frequency *)
  let sorted_counts = List.sort ~cmp:(fun (_,x) (_,y) -> descending x y) counts in
  (* Print out the 10 highest frequency entries *)
  List.iter (List.take 10 sorted_counts) ~f:(fun (line,count) ->
    printf "%3d: %s\n" count line)

```

Where is the main function?

Unlike C, programs in OCaml do not have a unique `main` function. When an OCaml program is evaluated, all the statements in the implementation files are evaluated in order. These implementation files can contain arbitrary expressions, not just function definitions. In this example, the role of the `main` function is played by the expression `let () = process_lines []`, which kicks off the actions of the program. But really the entire file is evaluated at startup, and so in some sense the full codebase is one big `main` function.

If we weren't using `Core` or any other external libraries, we could build the executable like this:

```
ocamlc freq.ml -o freq
```

But in this case, this command will fail with the error `Unbound module Core`. We need a somewhat more complex invocation to get `Core` linked in:

```
ocamlfind ocamlc -linkpkg -thread -package core freq.ml -o freq
```

Here we're using `ocamlfind`, a tool which itself invokes other parts of the `ocaml` tool-chain (in this case, `ocamlc`) with the appropriate flags to link in particular libraries and packages. Here, `-package core` is asking `ocamlfind` to link in the `Core` library, `-linkpkg` is required to do the final linking in of packages for building a runnable executable, and `-thread` turns on threading support, which is required for `Core`.

While this works well enough for a one-file project, more complicated builds will require a tool to orchestrate the build. One great tool for this task is `ocamlbuild`, which is shipped with the OCaml compiler. We'll talk more about `ocamlbuild` in chapter `{{OCAMLBUILD}}`, but for now, we'll just walk through the steps required for this simple application. First, create a `_tags` file, containing the following lines.

```

true:package(core)
true:thread,annot,debugging

```

The purpose of the `_tags` file is to specify which compilation options are required for which files. In this case, we're telling `ocamlbuild` to link in the `core` package and to turn on threading, output of annotation files, and debugging support for all files (the pattern `true` matches every file in the project.)

We then create a build script `build.sh` that invokes `ocamlbuild`:

```
#!/usr/bin/env bash

TARGET=freq
ocamlbuild -use-ocamlfind $TARGET.byte && cp $TARGET.byte $TARGET
```

If you invoke `build.sh`, you'll get a bytecode executable. If we'd used a target of `unique.native` in `build.sh`, we would have gotten native-code instead.

Whichever way you build the application, you can now run it from the command-line. The following line extracts strings from the `ocamlpt` executable, and then reports the most frequently occurring ones.

```
$ strings `which ocamlpt` | ./freq
13: movq
10: cmpq
8: ", &
7: .globl
6: addq
6: leaq
5: ", $
5: .long
5: .quad
4: ", '
```

Byte-code vs native-code

OCaml ships with two compilers---the `ocamlc` byte-code compiler, and the `ocamlpt` native-code compiler. Programs compiled with `ocamlc` are interpreted by a virtual machine, while programs compiled with `ocamlpt` are compiled to native machine code to be run on a specific operating system and processor architecture.

Aside from performance, executables generated by the two compilers have nearly identical behavior. There are a few things to be aware of. First, the byte-code compiler can be used on more architectures, and has some better tool support; in particular, the OCaml debugger only works with byte-code. Also, the byte-code compiler compiles faster than the native code compiler.

As a general matter, production executables should usually be built using the native-code compiler, but it sometimes makes sense to use bytecode for development builds. And, of course, bytecode makes sense when targetting a platform not supported by the native code compiler.

Multi-file programs and modules

Source files in OCaml are tied into the module system, with each file compiling down into a module whose name is derived from the name of the file. We've encountered modules before, for example, when we used functions like `find` and `add` from the `List.Assoc` module. At it's simplest, you can think of a module as a collection of definitions that are stored within a namespace.

Let's consider how we can use modules to refactor the implementation of `freq.ml`. Remember that the variable `counts` contains an association list representing the counts of the lines seen so far. But updating an association list takes time linear in the length of the list, meaning that the time complexity of processing a file is quadratic in the number of distinct lines in the file.

We can fix this problem by replacing association lists with a more efficient datastructure. To do that, we'll first factor out the key functionality into a separate module with an explicit interface. We can consider alternative (and more efficient) implementations once we have a clear interface to program against.

We'll start by creating a file, `counter.ml`, that contains the logic for maintaining the association list used to describe the counts. The key function, called `touch`, updates the association list with the information that a given line should be added to the frequency counts.

```
(* counter.ml: first version *)

open Core.Std

let touch t s =
  let count =
    match List.Assoc.find t s with
    | None -> 0
    | Some x -> x
  in
  List.Assoc.add t s (count + 1)
```

We can now rewrite `freq.ml` to use `Counter`. Note that the resulting code can still be built with `build.sh`, since `ocamlbuild` will discover dependencies and realize that `counter.ml` needs to be compiled.

```
(* freq.ml: using Counter *)

open Core.Std

let rec build_counts counts =
  match In_channel.input_line stdin with
  | None -> counts
  | Some line -> build_counts (Counter.touch counts line)

let () =
```

```

let counts = build_counts [] in
let sorted_counts = List.sort counts
  ~cmp:(fun (_,x) (_,y) -> Int.descending x y)
in
List.iter (List.take sorted_counts 10)
  ~f:(fun (line,count) -> printf "%3d: %s\n" count line)

```

Signatures and Abstract Types

While we've pushed some of the logic to the `Counter` module, the code in `freq.ml` can still depend on the details of the implementation of `Counter`. Indeed, if you look at the invocation of `build_counts`:

```
let counts = build_counts [] in
```

you'll see that it depends on the fact that the empty set of frequency counts is represented as an empty list. We'd like to prevent this kind of dependency, so that we can change the implementation of `Counter` without needing to change client code like that in `freq.ml`.

The first step towards hiding the implementation details of `Counter` is to create an interface file, `counter.mli`, which controls how `counter` is accessed. Let's start by writing down a simple descriptive interface, *i.e.*, an interface that describes what's currently available in `Counter` without hiding anything. We'll use `val` declarations in the `mli`, which have the following syntax

```
val <identifier> : <type>
```

and are used to expose the existence of a given value in the module. Here's an interface that describes the current contents of `Counter`. We can save this as `counter.mli` and compile, and the program will build as before.

```

(* counter.mli: descriptive interface *)

val touch : (string * int) list -> string -> (string * int) list

```

To actually hide the fact that frequency counts are represented as association lists, we need to make the type of frequency counts *abstract*. A type is abstract if its name is exposed in the interface, but its definition is not. Here's an abstract interface for `Counter`:

```

(* counter.mli: abstract interface *)

open Core.Std

type t

val empty : t
val to_list : t -> (string * int) list
val touch : t -> string -> t

```

Note that we needed to add `empty` and `to_list` to `Counter`, since otherwise, there would be no way to create a `Counter.t` or get data out of one.

Here's a rewrite of `counter.ml` to match this signature.

```
(* counter.ml: implementation matching abstract interface *)

open Core.Std

type t = (string * int) list

let empty = []

let to_list x = x

let touch t s =
  let count =
    match List.Assoc.find t s with
    | None -> 0
    | Some x -> x
  in
  List.Assoc.add t s (count + 1)
```

If we now try to compile `freq.ml`, we'll get the following error:

```
File "freq.ml", line 11, characters 20-22:
Error: This expression has type 'a list
      but an expression was expected of type Counter.t
```

This is because `freq.ml` depends on the fact that frequency counts are represented as association lists, a fact that we've just hidden. We just need to fix the code to use `Counter.empty` instead of `[]` and `Counter.to_list` to get the association list out at the end for processing and printing.

Now we can turn to optimizing the implementation of `Counter`. Here's an alternate and far more efficient implementation, based on the `Map` datastructure in `Core`.

```
(* counter.ml: efficient version *)

open Core.Std

type t = (string,int) Map.t

let empty = Map.empty

let touch t s =
  let count =
    match Map.find t s with
    | None -> 0
    | Some x -> x
  in
  in
  Map.add t s (count + 1)
```



```
let to_list t = Map.to_alist t
```

More on modules and signatures

Concrete types in signatures

In our frequency-count example, the module `Counter` had an abstract type `Counter.t` for representing a collection of frequency counts. Sometimes, you'll want to make a type in your interface *concrete*, by including the type definition in the interface.

For example, imagine we wanted to add a function to `Counter` for returning the line with the median frequency count. If the number of lines is even, then there is no precise median, so the function would return the two lines before and after the median instead. We'll use a custom type to represent the fact that there are two possible possible return values. Here's a possible implementation.

```
type median = | Median of string
              | Before_and_after of string * string

let median t =
  let sorted_strings = List.sort (Map.to_alist t)
    ~cmp:(fun (_,x) (_,y) -> Int.descending x y)
  in
  let len = List.length sorted_strings in
  if len = 0 then failwith "median: empty frequency count";
  let nth n = List.nth_exn sorted_strings n in
  if len mod 2 = 1
  then Median (nth (len/2))
  else Before_and_after (nth (len/2) (len/2 + 1))
```

Now, to expose this usefully in the interface, we need to expose both the function and the type `median` with its definition. We'd do that by adding these lines to the `counter.mli`:

```
type median = | Median of string
              | Before_and_after of string * string

val get_median : t -> median
```

The decision of whether a given type should be abstract or concrete is an important one. Abstract types give you more control over how values are created and accessed, and makes it easier to enforce invariants beyond the what's enforced by the type itself; concrete types let you expose more detail and structure to client code in a lightweight way. The right choice depends very much on the context.

The include directive

OCaml provides a number of tools for manipulating modules. One particularly useful one is the `include` directive, which is used to include the contents of one module into another.

One natural application of `include` is to create one module which is an extension of another one. For example, imagine you wanted to build an extended version of the `List` module, where you've added some functionality not present in the module as distributed in `Core`. We can do this easily using `include`:

```
(* ext_list.ml: an extended list module *)

open Core.Std

(* The new function we're going to add *)
let rec intersperse list el =
  match list with
  | [] | [ _ ] -> list
  | x :: y :: tl -> x :: el :: intersperse (y::tl) el

(* The remainder of the list module *)
include List
```

Now, what about the interface of this new module? It turns out that `include` works on the signature language as well, so we can pull essentially the same trick to write an `mli` for this new module. The only trick is that we need to get our hands on the signature for the `list` module, which can be done using `module type of`.

```
(* ext_list.mli: an extended list module *)

open Core.Std

(* Include the interface of the list module from Core *)
include (module type of List)

(* Signature of function we're adding *)
val intersperse : 'a list -> 'a -> 'a list
```

And we can now use `Ext_list` as a replacement for `List`. If we want to use `Ext_list` in preference to `List` in our project, we can create a file of common definitions:

```
(* common.ml *)

module List = Ext_list
```

And if we then put `open Common` after `open Core.Std` at the top of each file in our project, then references to `List` will automatically go to `Ext_list` instead.

Modules within a file

Up until now, we've only considered modules that correspond to files, like `counter.ml`. But modules (and module signatures) can be nested inside other modules. As a simple example, consider a program that needs to deal with some class of identifier like a username. Rather than just keeping usernames as strings, you might want to mint an abstract type, so that the type-system will help you to not confuse usernames with other string data that is floating around your program.

Here's how you might create such a type, within a module:

```
open Core.Std

module Username : sig
  type t
  val of_string : string -> t
  val to_string : t -> string
end = struct
  type t = string
  let of_string x = x
  let to_string x = x
end
```

The basic structure of a module declaration like this is:

```
module <name> : <signature> = <implementation>
```

We could have written this slightly differently, by giving the signature its own top-level `module type` declaration, making it possible to in a lightweight way create multiple distinct types with the same underlying implementation.

```
module type ID = sig
  type t
  val of_string : string -> t
  val to_string : t -> string
end

module String_id = struct
  type t = string
  let of_string x = x
  let to_string x = x
end

module Username : ID = String_id
module Hostname : ID = String_id

(* Now the following buggy code won't compile *)
type session_info = {
  user: Username.t;
  host: Hostname.t;
  when_started: Time.t;
}
```

```
let sessions_have_same_user s1 s2 =
  s1.user = s2.user
```

We can also combine this with the use of the `include` directive to add some extra functionality to such a module. Thus, we could have rewritten the definition of `Hostname` above as follows to add a function `Hostname.mine` that returns the hostname of the present machine.

```
module Hostname : sig
  include ID
  val mine : unit -> t
end = struct
  include String_id
  let mine = Unix.gethostname
end
```

Opening modules

One useful primitive in OCaml's module language is the `open` directive. We've seen that already in the `open Core.Std` that has been at the top of our source files.

The basic purpose of `open` is to extend the namespaces that OCaml searches when trying to resolve an identifier. Roughly, if you open a module `M`, then every subsequent time you look for an identifier `foo`, the module system will look in `M` for a value named `foo`. This is true for all kinds of identifiers, including types, type constructors, values and modules.

`open` is essential when dealing with something like a standard library, but it's generally good style to keep opening of modules to a minimum. Opening a module is basically a tradeoff between terseness and explicitness - the more modules you open, the harder it is to look at an identifier and figure out where it's defined.

Here's some general advice on how to deal with opens.

- Opening modules at the top-level of a module should be done quite sparingly, and generally only with modules that have been specifically designed to be opened, like `Core.Std` or `Option.Monad_infix`.
- One alternative to local opens that makes your code terser without giving up on explicitness is to locally rebind the name of a module. So, instead of writing:

```
let print_median m =
  match m with
  | Counter.Median string -> printf "True median:\n  %s\n"
  | Counter.Before_and_after of before * after ->
    printf "Before and after median:\n  %s\n  %s\n" before after
```

you could write

```
let print_median m =
```

```

let module C = Counter in
match m with
| C.Median string -> printf "True median:\n  %s\n"
| C.Before_and_after of before * after ->
  printf "Before and after median:\n  %s\n  %s\n" before after

```

Because the module name `C` only exists for a short scope, it's easy to read and remember what `C` stands for. Rebinding modules to very short names at the top-level of your module is usually a mistake.

- If you do need to do an open, it's better to do a *local open*. There are two syntaxes for local opens. For example, you can write:

```

let average x y =
  let open Int64 in
  x + y / of_int 2

```

In the above, `of_int` and the infix operators are the ones from `Int64` module.

There's another even more lightweight syntax for local opens, which is particularly useful for small expressions:

```

let average x y =
  Int64.(x + y / of_int 2)

```

Common errors with modules

When OCaml compiles a program with an `ml` and an `mli`, it will complain if it detects a mismatch between the two. Here are some of the common errors you'll run into.

Type mismatches

The simplest kind of error is where the type specified in the signature does not match up with the type in the implementation of the module. As an example, if we replace the `val` declaration in `counter.mli` by swapping the types of the first two arguments:

```

val touch : string -> t -> t

```

and then try to compile `Counter` (by writing `ocamlbuild -use-ocamlfind counter.cmo`), we'll get the following error:

```

File "counter.ml", line 1, characters 0-1:
Error: The implementation counter.ml
does not match the interface counter.cmi:
Values do not match:
  val touch :
    ('a, int) Core.Std.Map.t -> 'a -> ('a, int) Core.Std.Map.t
is not included in
  val touch : string -> t -> t

```

This error message is a bit intimidating at first, and it takes a bit of thought to see where the first type, which is the type of `[touch]` in the implementation, doesn't match the second one, which is the type of `[touch]` in the interface. You need to recognize that `[t]` is in fact a `[Core.Std.Map.t]`, and the problem is that in the first type, the first argument is a map while the second is the key to that map, but the order is swapped in the second type.

Missing definitions

We might decide that we want a new function in `Counter` for pulling out the frequency count of a given string. We can update the `mli` by adding the following line.

```
val count : t -> string -> int
```

Now, if we try to compile without actually adding the implementation, we'll get this error:

```
File "counter.ml", line 1, characters 0-1:
Error: The implementation counter.ml
       does not match the interface counter.cmi:
       The field `count' is required but not provided
```

A missing type definition will lead to a similar error.

Type definition mismatches

Type definitions that show up in an `mli` need to match up with corresponding definitions in the `ml`. Consider again the example of the type `median`. The order of the declaration of variants matters to the OCaml compiler so, if the definition of `median` in the implementation lists those options in a different order:

```
type median = | Before_and_after of line * line
              | Median of line
```

that will lead to a compilation error:

```
File "counter.ml", line 1, characters 0-1:
Error: The implementation counter.ml
       does not match the interface counter.cmi:
       Type declarations do not match:
         type median = Before_and_after of string * string | Median of string
         is not included in
         type median = Median of string | Before_and_after of string * string
       Their first fields have different names, Before_and_after and Median.
```

Order is similarly important in other parts of the signature, including the order in which record fields are declared and the order of arguments (including labeled and optional arguments) to a function.

Cyclic dependencies

In most cases, OCaml doesn't allow circular dependencies, *i.e.*, a collection of definitions that all refer to each other. If you want to create such definitions, you typically have to mark them specially. For example, when defining a set of mutually recursive values, you need to define them using `let rec` rather than ordinary `let`.

The same is true at the module level. By default, circular dependencies between modules is not allowed, and indeed, circular dependencies among files is never allowed.

The simplest case of this is that a module can not directly refer to itself (although definitions within a module can refer to each other in the ordinary way). So, if we tried to add a reference to `Counter` from within `counter.ml`:

```
let singleton l = Counter.touch Counter.empty
```

then when we try to build, we'll get this error:

```
File "counter.ml", line 17, characters 18-31:  
Error: Unbound module Counter  
Command exited with code 2.
```

The problem manifests in a different way if we create circular references between files. We could create such a situation by adding a reference to `Freq` from `counter.ml`, *e.g.*, by adding the following line:

```
let build_counts = Freq.build_counts
```

In this case, `ocamlbuild` will notice the error and complain:

```
Circular dependencies: "freq.cmo" already seen in  
[ "counter.cmo"; "freq.cmo" ]
```

2012-09-23

13:57:44

CHAPTER 8

Functors and First-Class Modules

Up until now, we've seen modules play a limited role, serving as a mechanism for organizing code into units with specified interfaces. But OCaml's module system plays a bigger role in the language, acting as a powerful toolset for structuring large-scale systems. This chapter will introduce you to functors and first class modules, which greatly increase the power of the module system.

Functors

Functors are, roughly speaking, functions from modules to modules, and they can be used to solve a variety of code-structuring problems, including:

- *Dependency injection*, or making the implementations of some components of a system swappable. This is particularly useful when you want to mock up parts of your system for testing and simulation purposes.
- *Auto-extension of modules*. Sometimes, there is some functionality that you want to build in a standard way for different types, in each case based on a some piece of type-specific logic. For example, you might want to add a slew of comparison operators derived from a base comparison function. To do this by hand would require a lot of repetitive code for each type, but functors let you write this logic just once and apply it to many different types.
- *Instantiating modules with state*. Modules can contain mutable state, and that means that you'll occasionally want to have multiple instantiations of a particular module, each with its own separate and independent mutable state. Functors let you automate the construction of such modules.

A trivial example

We'll start by considering the simplest possible example: a functor for incrementing an integer.

More precisely, we'll create a functor that takes a module containing a single integer variable `x`, and returns a new module with `x` incremented by one. The first step is to define a module type which will describe the input and output of the functor.

```
# module type X_int = sig val x : int end;;
module type X_int = sig val x : int end
```

Now, we can use that module type to write the increment functor.

```
# module Increment (M:X_int) : X_int = struct
  let x = M.x + 1
end;;
module Increment : functor (M : X_int) -> X_int
```

One thing that immediately jumps out about functors is that they're considerably more heavyweight syntactically than ordinary functions. For one thing, functors require explicit type annotations, which ordinary functions do not. Here, we've specified the module type for both the input and output of the functor. Technically, only the type on the input is mandatory, although in practice, one often specifies both.

The following shows what happens when we omit the module type for the output of the functor.

```
# module Increment (M:X_int) = struct
  let x = M.x + 1
end;;
module Increment : functor (M : X_int) -> sig val x : int end
```

We can see that the inferred module type of the output is now written out explicitly, rather than being a reference to the named signature `X_int`.

Here's what `Increment` looks like in action.

```
# module Three = struct let x = 3 end;;
  module Three : sig val x : int end
# module Four = Increment(Three);;
module Four : sig val x : int end
# Four.x - Three.x;;
- : int = 1
```

In this case, we applied `Increment` to a module whose signature is exactly equal to `X_int`. But we can apply `Increment` to any module that satisfies `X_int`. So, for example, `Increment` can take as its input a module that has more fields than are contemplated in `X_int`, as shown below.

```
# module Three_and_more = struct
  let x = 3
  let y = "three"
end;;
module Three_and_more : sig val x : int val x_string : string end
```

```
# module Four = Increment(Three_and_more);;
module Four : sig val x : int end
```

A bigger example: computing with intervals

We'll now look at a more complex example, which will give us an opportunity to learn more about how functors work. In particular, we'll walk through the design of a library for computing with intervals. This library will be functorized over the type of the endpoints of the intervals and the ordering of those endpoints.

First we'll define a module type that captures the information we'll need about the endpoint type. This interface, which we'll call `Comparable`, contains just two things: a comparison function, and the type of the values to be compared.

```
# module type Comparable = sig
  type t
  val compare : t -> t -> int
end ;;
```

The comparison function follows the standard OCaml idiom for such functions, returning 0 if the two elements are equal, a positive number if the first element is larger than the second, and a negative number if the first element is smaller than the second. Thus, we could rewrite the standard comparison functions on top of `compare` as shown below.

```
compare x y < 0    (* x < y *)
compare x y = 0    (* x = y *)
compare x y > 0    (* x > y *)
```

Now that we have the `Comparable` interface, we can write the implementation of our interval module. In this module, we'll represent an interval with a variant type, which is either `Empty` or `Interval (x,y)`, where `x` and `y` are the bounds of the interval.

```
# module Make_interval(Endpoint : Comparable) = struct

  type t = | Interval of Endpoint.t * Endpoint.t
           | Empty

  let create low high =
    if Endpoint.compare low high > 0 then Empty
    else Interval (low,high)

  let is_empty = function
    | Empty -> true
    | Interval _ -> false

  let contains t x =
    match t with
    | Empty -> false
    | Interval (l,h) ->
```

```

Endpoint.compare x l >= 0 && Endpoint.compare x h <= 0

let intersect t1 t2 =
  let min x y = if Endpoint.compare x y <= 0 then x else y in
  let max x y = if Endpoint.compare x y >= 0 then x else y in
  match t1,t2 with
  | Empty, _ | _, Empty -> Empty
  | Interval (l1,h1), Interval (l2,h2) ->
    create (max l1 l2) (min h1 h2)

end ;;
module Make_interval :
  functor (Endpoint : Comparable) ->
    sig
      type t = Interval of Endpoint.t * Endpoint.t | Empty
      val create : Endpoint.t -> Endpoint.t -> t
      val contains : t -> Endpoint.t -> bool
      val intersect : t -> t -> t
    end
end

```

We can instantiate the functor by applying it to a module with the right signature. In the following, we provide the functor input as an anonymous module.

```

# module Int_interval =
  Make_interval(struct
    type t = int
    let compare = Int.compare
  end);;
module Int_interval :
  sig
    type t = Interval of int * int | Empty
    val create : int -> int -> t
    val contains : t -> int -> bool
    val intersect : t -> t -> t
  end
end

```

If we choose our interfaces to be aligned with the standards of our libraries, then we often don't have to construct a custom module for a given functor. In this case, for example, we can directly use the `Int` or `String` modules provided by Core.

```

# module Int_interval = Make_interval(Int) ;;
# module String_interval = Make_interval(String) ;;

```

This works because many modules in Core, including `Int` and `String`, satisfy an extended version of the `Comparable` signature described above. As a general matter, having standardized signatures is a good practice, both because a more uniform codebase is easier to navigate, and because it makes functors easier to use.

Now we can use the newly defined `Int_interval` module like any ordinary module.

```

# let i1 = Int_interval.create 3 8;;
val i1 : Int_interval.t = Int_interval.Interval (3, 8)
# let i2 = Int_interval.create 4 10;;

```

```

val i2 : Int_interval.t = Int_interval.Interval (4, 10)
# Int_interval.intersect i1 i2;;
- : Int_interval.t = Int_interval.Interval (4, 8)

```

This design gives us the freedom to use any comparison function we want for comparing the endpoints. We could, for example, create a type of int interval with the order of the comparison reversed, as follows:

```

# module Rev_int_interval =
  Make_interval(struct
    type t = int
    let compare x y = Int.compare y x
  end);;

```

The behavior of `Rev_int_interval` is of course different from `Int_interval`, as we can see below.

```

# let interval = Int_interval.create 4 3;;
val interval : Int_interval.t = Int_interval.Empty
# let rev_interval = Rev_int_interval.create 4 3;;
val rev_interval : Rev_int_interval.t = Rev_int_interval.Interval (4, 3)

```

Importantly, `Rev_int_interval.t` is a different type than `Int_interval.t`, even though its physical representation is the same. Indeed, the type system will prevent us from confusing them.

```

# Int_interval.contains rev_interval 3;;
Characters 22-34:
  Int_interval.contains rev_interval 3;;
                      ^^^^^^^^^^^^^
Error: This expression has type Rev_int_interval.t
      but an expression was expected of type
      Int_interval.t = Make_interval(Int).t

```

This is important, because confusing the two kinds of intervals would be a semantic error, and it's an easy one to make. The ability of functors to mint new types is a useful trick that comes up a lot.

Making the functor abstract

There's a problem with `Make_interval`. The code we wrote depends on the invariant that the upper bound of an interval is greater than its lower bound, but that invariant can be violated. The invariant is enforced by the `create` function, but because `Interval.t` is not abstract, we can bypass the `create` function.

```

# Int_interval.create 4 3;; (* going through create *)
- : Int_interval.t = Int_interval.Empty
# Int_interval.Interval (4,3);; (* bypassing create *)
- : Int_interval.t = Int_interval.Interval (4, 3)

```

To make `Int_interval.t` abstract, we need to apply an interface to the output of the `Make_interval`. Here's an explicit interface that we can use for that purpose.

```
# module type Interval_intf = sig
  type t
  type endpoint
  val create : endpoint -> endpoint -> t
  val is_empty : t -> bool
  val contains : t -> endpoint -> bool
  val intersect : t -> t -> t
end;;
```

This interface includes the type `endpoint` to represent the type of the endpoints of the interval. Given this interface, we can redo our definition of `Make_interval`, as follows. Notice that we added the type `endpoint` to the implementation of the module to make the implementation match `Interval_intf`.

```
# module Make_interval(Endpoint : Comparable) : Interval_intf = struct

  type endpoint = Endpoint.t
  type t = | Interval of Endpoint.t * Endpoint.t
          | Empty

  ....

  end ;;
module Make_interval : functor (Endpoint : Comparable) -> Interval_intf
```

Sharing constraints

The resulting module is abstract, but unfortunately, it's too abstract. In particular, we haven't exposed the type `endpoint`, which means that we can't even construct an interval anymore.

```
# module Int_interval = Make_interval(Int);;
module Int_interval : Interval_intf
# Int_interval.create 3 4;;
Characters 20-21:
  Int_interval.create 3 4;;
                      ^
Error: This expression has type int but an expression was expected of type
      Int_interval.endpoint
```

To fix this, we need to expose the fact that `endpoint` is equal to `Int.t` (or more generally, `Endpoint.t`, where `Endpoint` is the argument to the functor). One way of doing this is through a *sharing constraint*, which allows you to tell the compiler to expose the fact that a given type is equal to some other type. The syntax for a sharing constraint on a module type is as follows.

```
S with type t = s
```

where S is a module type, t is a type inside of S , and s is a different type. The result of this expression is a new signature that's been modified so that it exposes the fact that t is equal to s . We can use a sharing constraint to create a specialized version of `Interval_intf` for integer intervals.

```
# module type Int_interval_intf = Interval_intf with type endpoint = int;;
module type Int_interval_intf =
  sig
    type t
    type endpoint = int
    val create : endpoint -> endpoint -> t
    val is_empty : t -> bool
    val contains : t -> endpoint -> bool
    val intersect : t -> t -> t
  end
```

And we can also use it in the context of a functor, where the right-hand side of the sharing constraint is an element of the functor argument. Thus, we expose an equality between a type in the output of the functor (in this case, the type `endpoint`) and a type in its input (`Endpoint.t`).

```
# module Make_interval(Endpoint : Comparable)
  : Interval_intf with type endpoint = Endpoint.t = struct

  type endpoint = Endpoint.t
  type t = | Interval of Endpoint.t * Endpoint.t
          | Empty

  ...

end ;;
module Make_interval :
  functor (Endpoint : Comparable) ->
  sig
    type t
    type endpoint = Endpoint.t
    val create : endpoint -> endpoint -> t
    val is_empty : t -> bool
    val contains : t -> endpoint -> bool
    val intersect : t -> t -> t
  end
```

So now, the interface is as it was, except that `endpoint` is now known to be equal to `Endpoint.t`. As a result of that type equality, we can now do things like construct intervals again.

```
# let i = Int_interval.create 3 4;;
val i : Int_interval.t = <abstr>
# Int_interval.contains i 5;;
- : bool = false
```

Destructive substitution

Sharing constraints basically do the job, but the approach we used has some downsides. In particular, we've now been stuck with the useless type declaration of `endpoint` that clutters up both the interface and the implementation. A better solution would be to modify the `Interval_intf` signature by replacing `endpoint` with `Endpoint.t` everywhere it shows up, making `endpoint` unnecessary. We can do just this using what's called *destructive substitution*. Here's the basic syntax.

```
S with type t := s
```

where `S` is a signature, `t` is a type inside of `S`, and `s` is a different type. The following shows how we could use this with `Make_interval`.

Here's an example of what we get if we use destructive substitution to specialize the `Interval_intf` interface to integer intervals.

```
# module type Int_interval_intf = Interval_intf with type endpoint := int;;
module type Int_interval_intf =
  sig
    type t
    val create : int -> int -> t
    val is_empty : t -> bool
    val contains : t -> int -> bool
    val intersect : t -> t -> t
  end
```

There's now no mention of `endpoint`, all occurrences of that type having been replaced by `int`. As with sharing constraints, we can also use this in the context of a functor.

```
# module Make_interval(Endpoint : Comparable)
  : Interval_intf with type endpoint := Endpoint.t =
  struct

    type t = | Interval of Endpoint.t * Endpoint.t
             | Empty

    ....

  end ;;
module Make_interval :
  functor (Endpoint : Comparable) ->
  sig
    type t
    val create : Endpoint.t -> Endpoint.t -> t
    val is_empty : t -> bool
    val contains : t -> Endpoint.t -> bool
    val intersect : t -> t -> t
  end
```

The interface is precisely what we want, and we didn't need to define the `endpoint` type alias in the body of the module. If we instantiate this module, we'll see that it works

properly: we can construct new intervals, but `t` is abstract, and so we can't directly access the constructors and violate the invariants of the data structure.

```
# module Int_interval = Make_interval(Int);;
# Int_interval.create 3 4;;
- : Int_interval.t = <abstr>
# Int_interval.Interval (4,3);;
Characters 0-27:
  Int_interval.Interval (4,3);;
  ^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^
Error: Unbound constructor Int_interval.Interval
```

Using multiple interfaces

Another feature that we might want for our interval module is the ability to serialize the type, in particular, by converting to s-expressions. If we simply invoke the `sexp` plib macros by adding `with sexp` to the definition of `t`, though, we'll get an error:

```
# module Make_interval(Endpoint : Comparable)
  : Interval_intf with type endpoint := Endpoint.t = struct

  type t = | Interval of Endpoint.t * Endpoint.t
           | Empty
  with sexp

  ....

end ;;
Characters 120-123:
  type t = | Interval of Endpoint.t * Endpoint.t
                ^^^^^^^^^^^
Error: Unbound value Endpoint.t_of_sexp
```

The problem is that `with sexp` adds code for defining the s-expression converters, and that code assumes that `Endpoint` has the appropriate `sexp`-conversion functions for `Endpoint.t`. But all we know about `Endpoint` is that it satisfies the `Comparable` interface, which doesn't say anything about s-expressions.

Happily, Core comes with a built in interface for just this purpose called `Sexpable`, which is defined as follows:

```
module type Sexpable = sig
  type t = int
  val sexp_of_t : t -> Sexp.t
  val t_of_sexp : Sexp.t -> t
end
```

We can modify `Make_interval` to use the `Sexpable` interface, for both its input and its output. Note the use of destructive substitution to combine multiple signatures together. This is important because it stops the `type t`'s from the different signatures from interfering with each other.

Also note that we have been careful to override the sexp-converter here to ensure that the datastructures invariants are still maintained when reading in from an s-expression.

```
# module type Interval_intf_with_sexp = sig
  type t
  include Interval_intf with type t := t
  include Sexpable      with type t := t
end;;

# module Make_interval(Endpoint : sig
  type t
  include Comparable with type t := t
  include Sexpable   with type t := t
end) : Interval_intf_with_sexp with type endpoint := Endpoint.t =
struct

  type t = | Interval of Endpoint.t * Endpoint.t
          | Empty
  with sexp

  let create low high =
    ...

  (* put a wrapper round the autogenerated sexp_of_t to enforce
     the invariants of the datastructure *)
  let t_of_sexp sexp =
    match t_of_sexp sexp with
    | Empty -> Empty
    | Interval (x,y) -> create x y

  ....

end ;;

module Make_interval :
functor
  (Endpoint : sig
    type t
    val compare : t -> t -> int
    val sexp_of_t : t -> Sexplib.Sexp.t
    val t_of_sexp : Sexplib.Sexp.t -> t
  end) ->
sig
  type t
  val create : Endpoint.t -> Endpoint.t -> t
  val is_empty : t -> bool
  val contains : t -> Endpoint.t -> bool
  val intersect : t -> t -> t
  val sexp_of_t : t -> Sexplib.Sexp.t
  val t_of_sexp : Sexplib.Sexp.t -> t
end
```

And now, we can use that sexp-converter in the ordinary way:

```
# module Int = Make_interval(Int) ;;
# Int_interval.sexp_of_t (Int_interval.create 3 4);;
```

```
- : Sexplib.Sexp.t = (Interval 3 4)
# Int_interval.sexp_of_t (Int_interval.create 4 3);;
- : Sexplib.Sexp.t = Empty
```

Extending modules

One common use of functors is to generate type-specific functionality for a given module in a standardized way. We'll think about this in the context of an example of creating a simple data structure.

The following is a minimal interface for a functional queue. A functional queue is simple a functional version of a FIFO (first-in, first-out) queue. Being functional, operations on the queue return new queues, rather than modifying the queues that were passed in.

```
(* file: fqueue.mli *)

type 'a t
val empty : 'a t
val enqueue : 'a t -> 'a -> 'a t
(** [dequeue q] returns None if the [q] is empty *)
val dequeue : 'a t -> ('a * 'a t) option
val fold : 'a t -> init:'acc -> f:('acc -> 'a -> 'acc) -> 'acc
```

A standard trick for implementing functional queues efficiently is to maintain both an input and an output list, where the input list is ordered to make `enqueue` fast, and the output list is ordered to make `dequeue` fast. When the output list is empty, the input list is reversed and becomes the new output list. Thinking through why this is efficient is a worthwhile exercise, but we won't dwell on that here.

Here's a concrete implementation.

```
(* file: fqueue.ml *)

type 'a t = 'a list * 'a list

let empty = ([],[])

let enqueue (l1,l2) x = (x :: l1,l2)

let dequeue (in_list,out_list) =
  match out_list with
  | hd :: tl -> Some (hd, (in_list,tl))
  | [] ->
    match List.rev in_list with
    | [] -> None
    | hd::tl -> Some (hd, ([], tl))

let fold (in_list,out_list) ~init ~f =
  List.fold ~init:(List.fold ~init ~f out_list) ~f
    (List.rev in_list)
```

The code above works fine, but the interface it implements is unfortunately quite skeletal; there are lots of useful helper functions that one might want that aren't there. And implementing those helper functions can be something of a dull affair, since you need to implement essentially the same helper functions for multiple different data structures in essentially the same way.

As it happens, many of these helper functions can be derived mechanically from just the `fold` function we already implemented. Rather than write all of these helper functions by hand for every new container type, we can instead use a functor to write the code for these once and for all, basing them off of the `fold` function.

Let's create a new module, `Foldable`, that contains support for this. The first thing we'll need is a signature to describe a container that supports `fold`.

```
(* file: foldable.ml *)

module type S = sig
  type 'a t
  val fold : 'a t -> init:'acc -> f:('acc -> 'a -> 'acc) -> 'acc
end
```

We'll also need a signature for the helper functions we're going to generate. This just represents some of the helper functions we can derive from `fold`, but it's enough to give you a flavor of what you can do.

```
module type Extension = sig
  type 'a t
  val iter    : 'a t -> f:('a -> unit) -> unit
  val length : 'a t -> int
  val count  : 'a t -> f:('a -> bool) -> int
  val for_all : 'a t -> f:('a -> bool) -> bool
  val exists : 'a t -> f:('a -> bool) -> bool
end
```

Finally, we can define the functor itself.

```
module Extend(Container : S)
  : Extension with type 'a t := 'a C.t =
struct
  open Container

  let iter t ~f = fold t ~init:() ~f:(fun () a -> f a)
  let length t = fold t ~init:0 ~f:(fun acc _ -> acc + 1)
  let count t ~f = fold t ~init:0 ~f:(fun count x -> count + if f x then 1 else 0)

  exception Short_circuit

  let for_all c ~f =
    try iter c ~f:(fun x -> if not (f x) then raise Short_circuit); true
    with Short_circuit -> false
```

```

    let exists c ~f =
      try iter c ~f:(fun x -> if f x then raise Short_circuit); false
      with Short_circuit -> true
    end

```

Now we can apply this to `Fqueue`. First, we can extend the interface:

```

(* file: fqueue.mli, 2nd version *)

type 'a t
val empty : 'a t
val enqueue : 'a t -> 'a -> 'a t
val dequeue : 'a t -> ('a * 'a t) option
val fold : 'a t -> init:'acc -> f:('acc -> 'a -> 'acc) -> 'acc

include Foldable.Extension with type 'a t := 'a t

```

In order to apply the functor, we'll put the definition of `Fqueue` in a sub-module called `T`, and then call `Foldable.Extend` on `T`. Here's how that code would look.

```

module T = struct
  type 'a t = 'a list * 'a list

  ....

  let fold (in_list,out_list) ~init ~f =
    List.fold ~init:(List.fold ~init ~f out_list)
      ~f (List.rev in_list)

end
include T
include Foldable.Extend(T)

```

This pattern comes up quite a bit in `Core`. It's used to implement various standard bits of functionality, including:

- Comparison-based datastructures like maps and sets, based on the `Comparable` interface.
- Hash-based datastructures like hash sets and hash heaps.
- Support for so-called monadic libraries, like the ones discussed in {{{ERROR HANDLING}}} and {{{CONCURRENCY}}}. Here, the functor is used to provide a collection of standard helper functions based on the core `bind` and `return` operators.

First class modules

_(jyh: I'm going to start some new text on FCM. We might want another chapter, but let's see how it goes. I've kept Ron's original text below.)

OCaml provides several mechanisms for organizing your programs, including modules and functors, files and compilation units, and classes and objects. Files and compilation units (`.ml` and `.mli` files) are really just a simplified module system. Classes and objects are a different form of organization altogether (as we'll see in [\[Chapter 13\]](#)). Yet, in each of these cases, there is a clear separation between types and values -- values cannot contain types, and types cannot contain values. And since modules can contain types, modules can't be values.

(yminsky: Instead of saying that `ml` and `mli` files are a simplified module system, maybe say that they "provide a simple way of creating modules and interfaces", or some such? It's not like there's a simplified module system floating around)

(yminsky: consider dropping "Yet" in the above.)

Next, we'll relax this restriction with *first-class modules*. "First-class" means that modules can be passed around as ordinary values that can be created from and converted back to regular modules. This is a relatively recent addition to the OCaml language, and while it might seem trivial to say, it has profound consequences on the language. First-class modules are strictly more expressive than any other organization mechanism, including classes and objects. Once you use first-class modules, you'll never want to go back.

(yminsky: I wouldn't say they're strictly more expressive. For example, they don't give you a way of expressing subtyping relationships effectively, which objects do.)

This is not say that first-class modules should be used indiscriminately. When you pass modules as values, the reason is to support dynamic behavior, and this can have a negative impact on understandability. As we proceed, we'll compare first-class modules to other techniques, and suggest alternatives when it seems appropriate.

_(jyh: Original text You can think of OCaml as being broken up into two sub-language: a core language that is concerned with values and types, and a module language that is concerned with modules and module signatures. These sub-languages are stratified, in that modules can contain types and values, but ordinary values can't contain modules or module types. That means you can't do things like define a variable whose definition is a module, or a function that takes a module as an argument.

OCaml provides a way around this stratification in the form of *first-class modules*. First-class modules are ordinary values that can be created from and converted back to regular modules. As we'll see, letting modules into the core language makes it possible to use more flexible and dynamic module-oriented designs.)_

Another trivial example

Much as we did with functors, we'll start out with an utterly trivial example, to allow us to show the basic mechanics of first class modules with a minimum of fuss.

A first-class module is created by packaging up a module with a signature that it satisfies. The following defines a simple signature and a module that matches it.

```
# module type X_int = sig val x : int end;;
module type X_int = sig val x : int end
# module Three : X_int = struct let x = 3 end;;
module Three : X_int
# Three.x;;
- : int = 3
```

We can then create a first-class module using the `module` keyword.

```
# let three = (module Three : X_int);;
val three : (module X_int) = <module>
```

Note that the type of the first-class module, `(module X_int)`, is based on the name of the signature that we used in constructing it.

To get at the contents of `three`, we need to unpack it into a module again, which we can do using the `val` keyword.

```
# module New_three = (val three : X_int) ;;
module New_three : X_int
# New_three.x;;
- : int = 3
```

Using these conversions as building blocks, we can create tools for working with first-class modules in a natural way. The following shows the definition of two function, `to_int`, which converts a `(module X_int)` into an `int`. And `plus`, which adds two `(module X_int)`s.

```
# let to_int m =
  let module M = (val m : X_int) in
    M.x
;;
val to_int : (module X_int) -> int = <fun>
# let plus m1 m2 =
  (module struct
    let x = to_int m1 + to_int m2
  end : X_int)
;;
val plus : (module X_int) -> (module X_int) -> (module X_int) = <fun>
```

With these functions in hand, we can start operating on our `(module X_int)`'s in a more natural style, taking full advantage of the concision and simplicity of the core language.

```
# let six = plus three three;;
val six : (module X_int) = <module>
# to_int (List.fold ~init:six ~f:plus [three;three]);;
- : int = 12
```

Of course, all we've really done with this example is come up with a more cumbersome way of working with integers. Let's see what happens when we work with more complex abstract types.

Standard vs. first-class modules

(yminsky: I'm not in olve with the example. It feels in some sense too artificial, and that aside, when you get to the end of the example, you haven't really gotten any juice of first-class modules)

(yminsky: using "standard" in quotes seems a little awkward. Maybe just drop the quotes, and talk about standard or ordinary modules directly?)

Let's compare the style of "standard" modules to first-class modules, using a simple library of abstract geometric shapes. In a "standard" module definition, we would define the shapes using abstract data types, where there is a type `t` that defines the actual representation, and the module would include functions that operate on the values of type `t`. In the following code, the module type `Shape` defines the type of generic shape, and the modules `Rectangle` and `Line` implement some concrete shapes.

```
module type Shape = sig
  type t
  val area : t -> int
  val position : t -> int * int
end

module Rectangle = struct
  type t = { width : int; height : int; x : int; y : int }
  let make ~x ~y ~width ~height =
    { width = width; height = height; x = x; y = y }
  let area { width = width; height = height } = width * height
  let position { x = x; y = y } = (x, y)
end

module Line = struct
  type t = { dx : int; dy : int; x : int; y : int }
  let make ~x ~y ~dx ~dy = { dx = dx; dy = dy; x = x; y = y }
  let area _ = 0
  let position { x = x; y = y } = (x, y)
end
```

Next, if we want to define a generic shape that is either a rectangle or a line, we would probably use a variant type. The following module `Shapes` is entirely boilerplate. We define the variant type, then functions to perform a dynamic dispatch based on the type of object.

```
module Shapes = struct
  type t = [ `Rect of Rectangle.t | `Line of Line.t ]
  let make_rectangle = Rectangle.make
  let make_line = Line.make
```



```

    let area = function
      `Rect r -> Rectangle.area r
    | `Line l -> Line.area l
    let position = function
      `Rect r -> Rectangle.position r
    | `Line l -> Line.position l
  end;;

```

In fact, confronted with this boilerplate, we would probably choose not use modules at all, but simply define a single module with a variant type and the code for all of the shapes. This isn't to say that separate code for separate shapes is bad, it just means that the language doesn't support it well (at least with standard modules).

With first-class modules, the situation changes, but we have to dispense with the representation type altogether. For immutable shapes, the implementation is now trivial.

```

# module type Shape = sig
  val area : int
  val position : int * int
end;;
module type Shape = sig val area : int val position : int * int end
# let make_rectangle ~x ~y ~width ~height =
  let module Rectangle = struct
    let area = width * height
    let position = (x, y)
  end in
  (module Rectangle : Shape);;
val make_rectangle :
  x:int -> y:int -> width:int -> height:int -> (module Shape) = <fun>
# let make_line ~x ~y ~dx ~dy =
  let module Line = struct
    let area = 0
    let position = (x, y)
  end in
  (module Line : Shape);;
val make_line : x:int -> y:int -> dx:'a -> dy:'b -> (module Shape) = <fun>

```

For mutable shapes, it isn't much different, but we have to include the state as values in the module implementations. For this, we'll define a representation type `t` in the module implementation, and for rectangles, a value `rect` of that type. The code for lines is similar.

```

# module type Shape = sig
  val area : unit -> int
  val position : unit -> int * int
  val moveby : dx:int -> dy:int -> unit
  val enlargeby : size:int -> unit
end;;
module type Shape = ...
# let make_rectangle ~x ~y ~width ~height =
  let module Rectangle = struct
    type t = { mutable x : int; mutable y : int;
               mutable width : int; mutable height : int }

```

```

    let rect = { x = x; y = y; width = width; height = height }
    let area () = rect.width * rect.height
    let position () = (rect.x, rect.y)
    let moveby ~dx ~dy =
      rect.x <- rect.x + dx;
      rect.y <- rect.y + dy
    let enlargeby ~size =
      rect.width <- rect.width * size;
      rect.height <- rect.height * size
  end in
  (module Rectangle : Shape);;
val make_rectangle :
  x:int -> y:int -> width:int -> height:int -> (module Shape) = <fun>

```

A more complete example -- containers

So far, we haven't done anything that really needs modules. The type `Shape` could just as well be specified as a record type `type shape = { area : int; position : int * int; ... }`.

To explore the topic more fully, let's implement a system of dynamic containers. OCaml already provides a set of standard containers like `List`, `Set`, `Hashtbl`, etc., but these types have to be selected statically. If a function expects a value of type `Set.Make(Element Type).t`, then you have to pass it a set of exactly that type. What we would like is a kind of container where the container implementation is chosen by the caller. We define an abstract *interface*, as a module type, then define one or more concrete module implementations.

Let's start by defining an abstract container interface. It contains some elements of type `elt`, and functions to examine and iterate through the contents. For convenience, we also define a normal type `'a container` to represent containers with elements of type `'a`.

```

module type Container = sig
  type elt
  val empty : unit -> bool
  val iter : (elt -> unit) -> unit
  val fold : ('a -> elt -> 'a) -> 'a -> 'a
end;;

type 'a container = (module Container with type elt = 'a)

```

Imperative containers

For imperative containers, we will also want functions to mutate the contents by adding or removing elements. For example, a stack can be implemented as a module `Stack` that includes all the functions in the generic `Container` module, as well as functions to push and pop elements.

```

module type Stack = sig
  include Container

```

```

    val push : elt -> unit
    val pop : unit -> elt
end;;

type 'a stack = (module Stack with type elt = 'a)

```

Now that the types are defined, the next step is to define a concrete container implementation. For this simple example, we'll use a list to represent a stack. The function `make_list_stack` constructs module implementation using a `let module` construction, then returns the result.

```

# let make_list_stack (type element) () : element stack =
  let module ListStack = struct
    type elt = element
    let contents = ref []
    let empty () = !contents = []
    let iter f = List.iter f !contents
    let fold f x = List.fold_left f x !contents
    let push x = contents := x :: !contents
    let pop () =
      match !contents with
      | x :: rest -> contents := rest; x
      | [] -> raise (Invalid_argument "stack is empty")
  end in
  (module ListStack : Stack with type elt = element);;
val make_list_stack : unit -> 'a stack = <fun>

```

Note the use of the explicit type parameter `element`. This is required because the use of a type variable in the module definition (like `type elt = 'a`) would be rejected by the compiler. The construction and use of the stack is straightforward.

```

# let demo (s : int stack) =
  let module S = (val s) in
    S.push 5;
    S.push 17;
    S.iter (fun i -> Printf.printf "Element: %d\n" i);;
val demo : int stack -> unit = <fun>
# demo (make_list_stack ());;
Element: 17
Element: 5
- : unit = ()

```

The `demo` function is entirely oblivious to the implementation of the stack. Instead of passing a module implementation based on lists, we could pass a different implementation based on arrays.

We could go on to define other containers, sets, dictionaries, queues, etc. but the implementations would be similar to what we have seen. Instead, let's look at functional data structures, which require a little more work to express.

Pure functional containers

Imperative data structures have simpler types than functional ones because the return type of imperative functions is just `unit`. When we look at pure functional data structures, we immediately run into a problem with type recursion.

```
# module type Container = sig
  type elt
  val empty : bool
  val iter : (elt -> unit) -> unit
  val fold : ('a -> elt -> 'a) -> 'a -> 'a
  val add : elt -> (module Container)
end;;
Characters 160-178:
  val add : elt -> (module Container)
                      ^^^^^^^^^^^^^^^^^^^
Error: Unbound module type Container
```

The problem here is that module type definitions are not recursive -- we can't use the type being defined in its own definition.

Recursive modules provide a solution, but it requires a "trick", where we define a module that is equal to itself. This module contains only type definitions, and the only purpose of the outer recursive module is to allow the recursion in the definition. While we're at it, let's include a `map` function with the usual semantics.

```
module rec Container : sig
  module type T = sig
    type elt
    val empty : bool
    val iter : (elt -> unit) -> unit
    val fold : ('a -> elt -> 'a) -> 'a -> 'a
    val map : (elt -> 'a) -> 'a Container.t
    val add : elt -> elt Container.t
  end
  type 'a t = (module Container.T with type elt = 'a)
end = Container;;
```

There are several ways to write this module, but this definition is convenient because it defines both a module type `Container.T` and a value type `'a Container.t`. The outer recursive module `Container` allows the module type `T` to refer to the value type `t` and *vice versa*. Note that the module `Container` is defined as itself (as `Container`).

With this first technicality out of the way, the next one is how to construct values of type `Container.t`. In the imperative version of the stack, we used a function `make_list_stack`. We want to do the same here, but the function definition must be both recursive and polymorphic.

```
# let make_stack () =
  let rec make : 'a. 'a list -> 'a Container.t = fun
    (type element) (contents : element list) ->
```

```

    let module NewList = struct
      type elt = element
      let empty = contents = []
      let iter f = List.iter f contents
      let fold f x = List.fold_left f x contents
      let map f = make (List.map f contents)
      let add x = make (x :: contents)
    end in
    (module NewList : Container.T with type elt = element)
  in
  make [];;
val make_stack : unit -> 'a Container.t = <fun>

```

The recursion here is particularly important. The functions `map` and `add` return new collections, so they call the function `make` recursively. The explicit polymorphic type `make : 'a. 'a list -> 'a Container.t` means that the function `make` is properly polymorphic, so that the `map` function is polymorphic.

Now that the construction is done, the usage is similar to the imperative case, except that now the data structure is functional.

```

# let demo (s : int Container.t) =
  let module S = (val s) in
  let module S = (val (S.add 5)) in
  let module S = (val (S.add 17)) in
  S.iter (fun i -> Printf.printf "Int Element: %d\n" i);
  let s = S.map (fun i -> float_of_int i +. 0.1) in
  let module S = (val s) in
  S.iter (fun x -> Printf.printf "Float Element: %f\n" x);
  s;;
val demo : int Container.t -> float Container.t = <fun>
# demo (make_stack ());;
Int Element: 17
Int Element: 5
Float Element: 17.100000
Float Element: 5.100000
- : unit = ()

```

The syntactic load here is pretty high, requiring a `let module` expression to name every intermediate value. First-class modules are fairly new to the language, and this is likely to change, but in the meantime the syntactic load can be pretty daunting.

Let's look at some other more typical examples, where dynamic module selection is more localized.

_(jyh: This is a rough draft, I'm not sure about the ordering and the topics, yet. Switching back to Ron's text now.)

Dynamically choosing a module

Perhaps the simplest thing you can do with first-class modules that you can't do without them is to pick the implementation of a module at runtime.

Consider an application that does I/O multiplexing using a system call like `select` to determine which file descriptors are ready to use. There are in fact multiple APIs you might want to use, including `select` itself, `epoll`, and `libev`, where different multiplexers make somewhat different performance and portability trade-offs. You could support all of these in one application by defining a single module, let's call it `Mutli plexer`, whose implementation is chosen at run-time based on an environment variable.

To do this, you'd first need an interface `S` that all of the different multiplexer implementations would need to match, and then an implementation of each multiplexer.

```
(* file: multiplexer.ml *)

(* An interface the OS-specific functionality *)
module type S = sig ... end

(* The implementations of each individual multiplexer *)
module Select : S = struct ... end
module Epoll  : S = struct ... end
module Libev  : S = struct ... end
```

We can choose the first-class module that we want based on looking up an environment variable.

```
let multiplexer =
  match Sys.getenv "MULTIPLEXER" with
  | None
  | Some "select" -> (module Select : S)
  | Some "epoll"  -> (module Epoll  : S)
  | Some "libev"  -> (module Libev  : S)
  | Some other   -> failwithf "Unknown multiplexer: %s" other ()
```

Finally, we can convert the resulting first-class module back to an ordinary module, and then include that so it becomes part of the body of our module.

```
(* The final, dynamically chosen, implementation *)
include (val multiplexer : S)
```

Example: A service bundle

This section describe the design of a library for bundling together multiple services, where a service is a piece of code that exports a query interface. A service bundle combines together multiple individual services under a single query interface that works by dispatching incoming queries to the appropriate underlying service.

The following is a first attempt at an interface for our `Service` module, which contains both a module type `S`, which is the interface that a service should meet, as well as a `Bundle` module which is for combining multiple services.

```
(* file: service.mli *)
```

```

open Core.Std

(** The module type for a service. *)
module type S = sig
  type t
  val name      : string
  val create    : unit -> t
  val handle_request : t -> Sexp.t -> Sexp.t Or_error.t
end

(** Bundles multiple services together *)
module Bundle : sig
  type t
  val create : (module S) list -> t
  val handle_request : t -> Sexp.t -> Sexp.t Or_error.t
  val service_names  : t -> string list
end

```

Here, a service has a state, represented by the type `t`, a name by which the service can be referenced, a function `create` for instantiating a service, and a function by which a service can actually handle a request. Here, requests and responses are delivered as s-expressions. At the `Bundle` level, the s-expression of a request is expected to be formatted as follows:

```
(<service-name> <body>)
```

where `<service_name>` is the service that should handle the request, and `<body>` is the body of the request.

Now let's look at how to implement `Service`. The core datastructure of `Bundle` is a hashtable of request handlers, one per service. Each request handler is a function of type `(Sexp.t -> Sexp.t Or_error.t)`. These request handlers really stand in for the underlying service, with the particular state of the service in question being hidden inside of the request handler.

The first part of `service.ml` is just the preliminaries: the definition of the module type `S`, and the definition of the type `Bundle.t`.

```

(* file: service.ml *)

open Core.Std

module type S = sig
  type t
  val name      : string
  val create    : unit -> t
  val handle_request : t -> Sexp.t -> Sexp.t Or_error.t
end

module Bundle = struct
  type t = { handlers: (Sexp.t -> Sexp.t Or_error.t) String.Table.t; }

```

The next thing we need is a function for creating a `Bundle.t`. This `create` function builds a table to hold the request handlers, and then iterates through the services, unpacking each module, constructing the request handler, and then putting that request handler in the table.

```
(** Creates a handler given a list of services *)
let create services =
  let handlers = String.Table.create () in
  List.iter services ~f:(fun service_m ->
    let module Service = (val service_m : S) in
    let service = Service.create () in
    if Hashtbl.mem handlers Service.name then
      failwith ("Attempt to register duplicate handler for " ^ Service.name);
    Hashtbl.replace handlers ~key:Service.name
      ~data:(fun sexp -> Service.handle_request service sexp)
  );
  {handlers}
```

Note that the `Service.t` that is created is referenced by the corresponding request handler, so that it is effectively hidden behind the function in the `handlers` table.

Now we can write the function for the bundle to handle requests. The handler will examine the s-expression to determine the body of the query and the name of the service to dispatch to. It then looks up the handler calls it to generate the response.

```
let handle_request t sexp =
  match sexp with
  | Sexp.List [Sexp.Atom name; query] ->
    begin match Hashtbl.find t.handlers name with
    | None -> Or_error.error_string ("Unknown service: " ^ name)
    | Some handler ->
      try handler query
      with exn -> Error (Error.of_exn exn)
    end
  | _ -> Or_error.error_string "Malformed query"
```

Last of all, we define a function for looking up the names of the available services.

```
let service_names t = Hashtbl.keys t.handlers

end
```

To see this system in action, we need to define some services, create the corresponding bundle, and then hook that bundle up to some kind of client. For simplicity, we'll build a simple command-line interface. There are two functions below: `handle_one`, which handles a single interaction; and `handle_loop`, which creates the bundle and then runs `handle_one` in a loop.

```
(* file: service_client.ml *)

open Core.Std
```



```

(** Handles a single request coming from stdin *)
let handle_one bundle =
  printf ">>> %!"; (* prompt *)
  match In_channel.input_line stdin with
  | None -> `Stop (* terminate on end-of-stream, so Ctrl-D will exit *)
  | Some line ->
    let line = String.strip line in (* drop leading and trailing whitespace *)
    if line = "" then `Continue
    else match Or_error.try_with (fun () -> Sexp.of_string line) with
    | Error err ->
      eprintf "Couldn't parse query: %s\n%!" (Error.to_string_hum err);
      `Continue
    | Ok query_sexp ->
      let resp = Service.Bundle.handle_request bundle query_sexp in
      Sexp.output_hum stdout (<:sexp_of<Sexp.t Or_error.t>> resp);
      Out_channel.newline stdout;
      `Continue

let handle_loop services =
  let bundle = Service.Bundle.create services in
  let rec loop () =
    match handle_one bundle with
    | `Stop -> ()
    | `Continue -> loop ()
  in
  loop ()

```

Now we'll create a couple of toy services. One service is a counter that can be updated by query; and the other service lists a directory. The last line then kicks off the shell with the services we've defined.

```

module Counter : Service.S = struct
  type t = int ref

  let name = "update-counter"
  let create () = ref 0

  let handle_request t sexp =
    match Or_error.try_with (fun () -> int_of_sexp sexp) with
    | Error _ as err -> err
    | Ok x ->
      t := !t + x;
      Ok (sexp_of_int !t)
end

module List_dir : Service.S = struct
  type t = unit

  let name = "ls"
  let create () = ()

  let handle_request () sexp =
    match Or_error.try_with (fun () -> string_of_sexp sexp) with

```

```

      | Error _ as err -> err
      | Ok dir -> Ok (Array.sexp_of_t String.sexp_of_t (Sys.readdir dir))
    end

let () =
  handle_loop [(module List_dir : Service.S); (module Counter : Service.S)]

```

And now we can go ahead and start up the client.

```

$ ./service_client.byte
>>> (update-counter 1)
(Ok 1)
>>> (update-counter 10)
(Ok 11)
>>> (ls .)
(Ok
 (_build_tags service.ml service.mli service.mli~ service.ml~
  service_client.byte service_client.ml service_client.ml~))
>>>

```

Now, let's consider what happens to the design when we want to make the interface of a service a bit more realistic. In particular, right now services are created without any configuration. Let's add a config type to each service, and change the interface of `Bundle` so that services can be registered along with their configs. At the same time, we'll change the `Bundle` API to allow services to be changed dynamically, rather than just added at creation time.

Syntax Extensions

(yminsky: still very very rough)

This chapter covers several extensions to OCaml's syntax that are distributed with Core. Before diving into the details of the syntax extensions, let's take a small detour that will explain the motivation behind creating them in the first place.

Serialization with s-expressions

Serialization, *i.e.* reading and writing program data to a sequence of bytes, is an important and common programming task. To this end, Core comes with good support for *s-expressions*, which are a convenient general-purpose serialization format. The type of an s-expression is as follows:

```
module Sexp : sig
  type t = Atom of string | List of t list
end
```

An s-expression is in essence a nested parenthetical list whose atomic values are strings. The `Sexp` module comes with functionality for parsing and printing s-expressions.

```
# let sexp =
  let a x = Sexp.Atom x and l x = Sexp.List x in
  l [a "this"; l [a "is"; a "an"]; l [a "s"; a "expression"]];;
val sexp : Sexp.t = (this (is an) (s expression))
```

In addition, most of the base types in Core support conversion to and from s-expressions. For example, we can write:

```
# Int.sexp_of_t 3;;
- : Sexp.t = 3
# List.sexp_of_t;;
- : ('a -> Sexp.t) -> 'a List.t -> Sexp.t = <fun>
# List.sexp_of_t Int.sexp_of_t [1;2;3];;
- : Sexp.t = (1 2 3)
```

Notice that `List.sexp_of_t` is polymorphic, and takes as its first argument another conversion function to handle the elements of the list to be converted. Core uses this scheme more generally for defining sexp-converters for polymorphic types.

But what if you want a function to convert some brand new type to an s-expression? You can of course write it yourself:

```
# type t = { foo: int; bar: float };;
# let sexp_of_t t =
  let a x = Sexp.Atom x and l x = Sexp.List x in
  l [ l [a "foo"; Int.sexp_of_t t.foo ];
      l [a "bar"; Float.sexp_of_t t.bar]; ]
;;
val sexp_of_t : t -> Core.Std.Sexp.t = <fun>
# sexp_of_t { foo = 3; bar = -5.5 };;
- : Core.Std.Sexp.t = ((foo 3) (bar -5.5))
```

This is somewhat tiresome to write, and it gets more so when you consider the parser, *i.e.*, `t_of_sexp`, which is considerably more complex. Writing this kind of parsing and printing code by hand is mechanical and error prone, not to mention a drag.

Given how mechanical the code is, you could imagine writing a program that inspected the type definition and auto-generated the conversion code for you. That is precisely where syntax extensions come in. Using `Sexplib` and adding `with sexp` as an annotation to our type definition, we get the functions we want for free.

```
# type t = { foo: int; bar: float } with sexp;;
type t = { foo : int; bar : float; }
val t_of_sexp__ : Sexplib.Sexp.t -> t = <fun>
val t_of_sexp : Sexplib.Sexp.t -> t = <fun>
val sexp_of_t : t -> Sexplib.Sexp.t = <fun>
# t_of_sexp (Sexp.of_string "((bar 35) (foo 3))");;
- : t = {foo = 3; bar = 35.}
```

(You can ignore `t_of_sexp__`, which is a helper function that is needed in very rare cases.)

The syntax-extensions in Core that we're going to discuss all have this same basic structure: they auto-generate code based on type definitions, implementing functionality that you could in theory have implemented by hand, but with far less programmer effort.

There are several syntax extensions distributed with Core, including:

- **Sexplib**: provides serialization for s-expressions.
- **Bin_prot**: provides serialization to an efficient binary format.
- **Fieldslib**: generates first-class values that represent fields of a record, as well as accessor functions and setters for mutable record fields.
- **Variantslib**: like `Fieldslib` for variants, producing first-class variants and other helper functions for interacting with variant types.

- **Pa_compare**: generates efficient, type-specialized comparison functions.
- **Pa_typehash**: generates a hash value for a type definition, *i.e.*, an integer that is highly unlikely to be the same for two distinct types.

We'll discuss each of these syntax extensions in detail, starting with Sexplib.

Sexplib

Formatting of s-expressions

Sexplib's format for s-expressions is pretty straightforward: an s-expression is written down as a nested parenthetical expression, with whitespace-separated strings as the atoms. Quotes are used for atoms that contain parenthesis or spaces themselves, backslash is the escape character, and semicolons are used to introduce comments. Thus, if you create the following file:

```
;; foo.scm

((foo 3.3) ;; Shall I compare thee to a summer's dream?
 (bar "this is () an \" atom"))
```

we can load it up and print it back out again:

```
# Sexp.load_sexp "foo.scm";;
- : Sexp.t = ((foo 3.3) (bar "this is () an \" atom"))
```

Note that the comments were dropped from the file upon reading. This is expected, since there's no place in the `Sexp.t` type to store comments.

If we introduce an error into our s-expression, by, say, deleting the open-paren in front of `bar`, we'll get a parse error:

```
# Exn.handle_uncaught ~exit:false (fun () ->
  ignore (Sexp.load_sexp "foo.scm"));;
Uncaught exception:

(Sexplib.Sexp.Parse_error
 ((location parse) (err_msg "unexpected character: ')'"') (text_line 4)
 (text_char 29) (global_offset 94) (buf_pos 94)))
```

(In the above, we use `Exn.handle_uncaught` to make sure that the exception gets printed out in full detail.)

Sexp converters

The most important functionality provided by Sexplib is the auto-generation of converters for new types. We've seen a bit of how this works already, but let's walk through

a complete example. Here's the source for the beginning of a library for representing integer intervals.

```
(* file: int_interval.ml *)
(* Module for representing closed integer intervals *)

open Core.Std

(* Invariant: For any Range (x,y), y > x *)
type t = | Range of int * int
        | Empty
with sexp

let is_empty = function Empty -> true | Range _ -> false
let create x y = if x > y then Empty else Range (x,y)
let contains i x = match i with
  | Empty -> false
  | Range (low,high) -> x >= low && x <= high
```

We can now use this module as follows:

```
(* file: test_interval.ml *)

open Core.Std

let intervals =
  let module I = Int_interval in
  [ I.create 3 4;
    I.create 5 4; (* should be empty *)
    I.create 2 3;
    I.create 1 6;
  ]

let () =
  intervals
  |! List.sexp_of_t Int_interval.sexp_of_t
  |! Sexp.to_string_hum
  |! print_endline
```

But we're still missing something: we haven't created an `mli` for `Int_interval` yet. Note that we need to explicitly export the s-expression converters that were created within the `ml`. If we don't:

```
(* file: int_interval.mli *)
(* Module for representing closed integer intervals *)

type t

val is_empty : t -> bool
val create : int -> int -> t
val contains : t -> int -> bool
```

then we'll get the following error:

```
File "test_interval.ml", line 15, characters 20-42:
Error: Unbound value Int_interval.sexp_of_t
Command exited with code 2.
```

We could export the types by hand:

```
type t
val sexp_of_t : Sexp.t -> t
val t_of_sexp : t -> Sexp.t
```

But Sexplib has a shorthand for this as well, so that we can instead write simply:

```
type t with sexp
```

at which point `test_interval.ml` will compile again, and if we run it, we'll get the following output:

```
$ ./test_interval.native
((Range 3 4) Empty (Range 2 3) (Range 1 6))
```

Preserving invariants

One easy mistake to make when dealing with sexp converters is to ignore the fact that those converters can violate the invariants of your code. For example, the `Int_interval` module depends for the correctness of the `is_empty` check on the fact that for any value `Range (x,y)`, `y` is greater than or equal to `x`. The `create` function preserves this invariant, but the `t_of_sexp` function does not.

We can fix this problem by writing a custom sexp-converter, in this case, using the sexp-converter that we already have:

```
type t = | Range of int * int
         | Empty
with sexp

let create x y = if x > y then Empty else Range (x,y)

let t_of_sexp sexp =
  let t = t_of_sexp sexp in
  begin match t with
  | Range (x,y) when y < x ->
    of_sexp_error "Upper and lower bound of Range swapped" sexp
  | Empty | Range _ -> ()
  end;
  t
```

We call the function `of_sexp_error` to raise an exception because that improves the error reporting that Sexplib can provide when a conversion fails.

Getting good error messages

There are two steps to deserializing a type from an s-expression: first, converting the bytes in a file to an s-expression, and the second, converting that s-expression into the type in question. One problem with this is that it can be hard to localize errors to the right place using this scheme. Consider the following example:

```
(* file: read_foo.ml *)

open Core.Std

type t = { a: string; b: int; c: float option } with sexp

let run () =
  let t =
    Sexp.load_sexp "foo.scm"
    |! t_of_sexp
  in
  printf "b is: %d\n%" t.b

let () =
  Exn.handle_uncaught ~exit:true run
```

If you were to run this on a malformed file, say, this one:

```
;; foo.scm
((a not-an-integer)
 (b not-an-integer)
 (c ()))
```

you'll get the following error:

```
read_foo $ ./read_foo.native
Uncaught exception:

(Sexplib.Conv.Of_sexp_error
 (Failure "int_of_sexp: (Failure int_of_string)" ) not-an-integer)
```

If all you have is the error message and the string, it's not terribly informative. In particular, you know that the parsing errored out on the atom "not-an-integer", but you don't know which one! In a large file, this kind of bad error message can be pure misery.

But there's hope! If we make a small change to the `run` function as follows:

```
let run () =
  let t = Sexp.load_sexp_conv_exn "foo.scm" t_of_sexp in
  printf "b is: %d\n%" t.b
```

and run it again, we'll get the following much more helpful error message:

```
read_foo $ ./read_foo.native
Uncaught exception:
```



```
(Sexplib.Conv.Of_sexp_error
 (Sexplib.Sexp.Annotated.Conv_exn foo.scm:3:4
  (Failure "int_of_sexp: (Failure int_of_string)")
  not-an-integer)
```

In the above error, "foo.scm:3:4" tells us that the error occurred on "foo.scm", line 3, character 4, which is a much better start for figuring out what has gone wrong.

Sexp-conversion directives

Sexplib supports a collection of directives for modifying the default behavior of the autogenerated sexp-converters. These directives allow you to customize the way in which types are represented as s-expressions without having to write a custom parser. We describe these directives below.

sexp-opaque

The most commonly used directive is `sexp_opaque`, whose purpose is to mark a given component of a type as being unconvertable. Anything marked with `sexp_opaque` will be presented as the atom `<opaque>` by the to-sexp converter, and will trigger an exception from the from-sexp converter. Note that the type of a component marked as opaque doesn't need to have a sexp-converter defined. Here, if we define a type without a sexp-converter, and then try to use it another type with a sexp-converter, we'll error out:

```
# type no_converter = int * int;;
type no_converter = int * int
# type t = { a: no_converter; b: string } with sexp;;
Characters 14-26:
  type t = { a: no_converter; b: string } with sexp;;
                ^^^^^^^^^^^^^^^
Error: Unbound value no_converter_of_sexp
```

But with `sexp_opaque`, we won't:

```
# type t = { a: no_converter sexp_opaque; b: string } with sexp;;
type t = { a : no_converter Core.Std.sexp_opaque; b : string; }
val t_of_sexp__ : Sexplib.Sexp.t -> t = <fun>
val t_of_sexp : Sexplib.Sexp.t -> t = <fun>
val sexp_of_t : t -> Sexplib.Sexp.t = <fun>
```

And if we now convert a value of this type to an s-expression, we'll see the contents of field `a` marked as opaque:

```
# sexp_of_t { a = (3,4); b = "foo" };;
- : Sexplib.Sexp.t = ((a <opaque>) (b foo))
```

sexp_option

Another common directive is `sexp_opaque`, which is used to make an optional field in a record. Ordinary optional values are represented either as `()` for `None`, or as `(x)` for `Some x`. If you put an option in a record field, then the record field will always be required, and its value will be presented in the way an ordinary optional value would. For example:

```
# type t = { a: int option; b: string } with sexp;;
# sexp_of_t { a = None; b = "hello" };;
- : Sexp.t = ((a ()) (b hello))
# sexp_of_t { a = Some 3; b = "hello" };;
- : Sexp.t = ((a (3)) (b hello))
```

But what if we want a field to be optional, *i.e.*, we want to allow it to be omitted from the record entirely? In that case, we can mark it with `sexp_option`:

```
# type t = { a: int sexp_option; b: string } with sexp;;
# sexp_of_t { a = Some 3; b = "hello" };;
- : Sexp.t = ((a 3) (b hello))
# sexp_of_t { a = None; b = "hello" };;
- : Sexp.t = ((b hello))
```

sexp_list

One problem with the autogenerated sexp-converter is that they can have more parentheses than one would ideally like. Consider, for example, the following variant type:

```
# type compatible_versions = | Specific of string list
                             | All
    with sexp;;
# sexp_of_compatible_versions (Specific ["3.12.0"; "3.12.1"; "3.13.0"]);;
- : Sexp.t = (Specific (3.12.0 3.12.1 3.13.0))
```

You might prefer to make the syntax a bit less parenthesis-laden by dropping the parentheses around the list. `sexp_list` gives us this alternate syntax:

```
# type compatible_versions = | Specific of string sexp_list
                             | All
    with sexp;;
# sexp_of_compatible_versions (Specific ["3.12.0"; "3.12.1"; "3.13.0"]);;
- : Sexp.t = (Specific 3.12.0 3.12.1 3.13.0)
```

Bin_prot

S-expressions are a good serialization format when you need something machine-parseable as well as human readable and editable. But Sexplib's s-expressions are not particularly performant. There are a number of reasons for this. For one thing, s-expression serialization goes through an intermediate type, `Sexp.t`, which must be allo-

cated and is then typically thrown away, putting non-trivial pressure on the GC. In addition, parsing and printing to strings in an ASCII format can be expensive for types like `ints`, `floats` and `Time.ts` where some real computation needs to be done to produce or parse the ASCII representation.

`Bin_prot` is a library designed to address these issues by providing fast serialization in a compact binary format. Kicking off the syntax extension is done by putting `with bin_io`. (This looks a bit unsightly in the top-level because of all the definitions that are generated. We'll elide those definitions here, but you can see it for yourself in the top-level.)

Here's a small complete example of a program that can read and write values using `bin_io`. Here, the serialization is of types that might be used as part of a message-queue, where each message has a topic, some content, and a source, which is in turn a hostname and a port.

```
(* file: message_example.ml *)

open Core.Std

(* The type of a message *)
module Message = struct
  module Source = struct
    type t = { hostname: string;
               port: int;
             }
    with bin_io
  end

  type t = { topic: string;
             content: string;
             source: Source.t;
           }
  with bin_io
end

(* Create the 1st-class module providing the binability of messages *)
let binable = (module Message : Binable.S with type t = Message.t)

(* Saves a message to an output channel. The message is serialized to
   a bigstring before being written out to the channel. Also, a
   binary encoding of an integer is written out to tell the reader how
   long of a message to expect. *)
let save_message outc msg =
  let s = Binable.to_bigstring binable msg in
  let len = Bigstring.length s in
  Out_channel.output_binary_int outc len;
  Bigstring.really_output outc s

(* Loading the message is done by first reading in the length, and by
   then reading in the appropriate number of bytes into a Bigstring
   created for that purpose. *)
```

```

let load_message inc =
  match In_channel.input_binary_int inc with
  | None -> failwith "Couldn't load message: length missing from header"
  | Some len ->
    let buf = Bigstring.create len in
    Bigstring.really_input ~pos:0 ~len inc buf;
    Binable.of_bigstring binable buf

(* To generate some example messages *)
let example_content =
  let source =
    { Message.Source.
      hostname = "ocaml.org"; port = 2322 }
  in
  { Message.
    topic = "two-example"; content; source; }

(* write out three messages... *)
let write_messages () =
  let outc = Out_channel.create "tmp.bin" in
  List.iter ~f:(save_message outc) [
    example "a wonderful";
    example "trio";
    example "of messages";
  ];
  Out_channel.close outc

(* ... and read them back in *)
let read_messages () =
  let inc = In_channel.create "tmp.bin" in
  for i = 1 to 3 do
    let msg = load_message inc in
    printf "msg %d: %s\n" i msg.Message.content
  done

let () =
  write_messages (); read_messages ()

```

Fieldslib

One common idiom when using records is to provide field accessor functions for a particular record.

```

type t = { topic: string;
           content: string;
           source: Source.t;
         }

let topic t = t.topic
let content t = t.content
let source t = t.source

```

Similarly, sometimes you simultaneously want an accessor to a field of a record and a textual representation of the name of that field. This might come up if you were validating a field and needed the string representation to generate an error message, or if you wanted to scaffold a form in a GUI automatically based on the fields of a record. Fieldslib provides a module `Field` for this purpose. Here's some code for creating `Field.t`'s for all the fields of our type `t`.

```
# module Fields = struct
  let topic =
    { Field.
      name   = "topic";
      setter = None;
      getter = (fun t -> t.topic);
      fset   = (fun t topic -> { t with topic });
    }
  let content =
    { Field.
      name   = "content";
      setter = None;
      getter = (fun t -> t.content);
      fset   = (fun t content -> { t with content });
    }
  let source =
    { Field.
      name   = "source";
      setter = None;
      getter = (fun t -> t.source);
      fset   = (fun t source -> { t with source });
    }
end ;;
module Fields :
sig
  val topic : (t, string list) Core.Std.Field.t
  val content : (t, string) Core.Std.Field.t
  val source : (t, Source.t) Core.Std.Field.t
end
```

2012-09-23

13:57:44

CHAPTER 10

Object Oriented Programming

(yminsky: If we don't feel like these are "great" tools, maybe we shouldn't say it!)

(yminsky: I wonder if it's worth emphasizing what makes objects unique early on. I think of them as no better of an encapsulation tool than closures. What makes them unique in my mind is that they are some combination of lighter weight and more dynamic than the alternatives (modules, records of closures, etc..))

(yminsky: I'm not sure where we should say it, but OCaml's object system is strikingly different from those that most people are used to. It would be nice if we could call those differences out clearly somewhere. The main difference I see is the fact that subtyping and inheritance are not tied together, and that subtyping is structural.)

We've already seen several tools that OCaml provides for organizing programs, particularly first-class modules. In addition, OCaml also supports object-oriented programming. There are objects, classes, and their associated types. Objects are good for encapsulation and abstraction, and classes are good for code re-use.

When to use objects

You might wonder when to use objects. First-class modules are more expressive (a module can include types, classes and objects cannot), and modules, functors, and algebraic data types offer a wide range of ways to express program structure. In fact, many seasoned OCaml programmers rarely use classes and objects, if at all.

What exactly is object-oriented programming? Mitchell [6] points out four fundamental properties.

- *Abstraction*: the details of the implementation are hidden in the object; the interface is just the set of publically-accessible methods.
- *Subtyping*: if an object *a* has all the functionality of an object *b*, then we may use *a* in any context where *b* is expected.

- *Dynamic lookup*: when a message is sent to an object, the method to be executed is determined by the implementation of the object, not by some static property of the program. In other words, different objects may react to the same message in different ways.
- *Inheritance*: the definition of one kind of object can be re-used to produce a new kind of object.

Modules already provide these features in some form, but the main focus of classes is on code re-use through inheritance and late binding of methods. This is a critical property of classes: the methods that implement an object are determined when the object is instantiated, a form of *dynamic* binding. In the meantime, while classes are being defined, it is possible (and necessary) to refer to methods without knowing statically how they will be implemented.

In contrast, modules use static (lexical) scoping. If you want to parameterize your module code so that some part of it can be implemented later, you would write a function/functor. This is more explicit, but often more verbose than overriding a method in a class.

In general, a rule of thumb might be: use classes and objects in situations where dynamic binding is a big win, for example if you have many similar variations in the implementation of a concept. Real world examples are fairly rare, but one good example is Xavier Leroy's Cryptokit (<http://gallium.inria.fr/~xleroy/software.html#cryptokit>), which provides a variety of cryptographic primitives that can be combined in building-block style.

OCaml objects

If you already know about object oriented programming in a language like Java or C++, the OCaml object system may come as a surprise. Foremost is the complete separation of subtyping and inheritance in OCaml. In a language like Java, a class name is also used as the type of objects created by instantiating it, and the subtyping rule corresponds to inheritance. For example, if we implement a class `Stack` in Java by inheriting from a class `Deque`, we would be allowed to pass a stack anywhere a deque is expected (this is a silly example of course, practitioners will point out that we shouldn't do it).

OCaml is entirely different. Classes are used to construct objects and support inheritance, including non-subtyping inheritance. Classes are not types. Instead, objects have *object types*, and if you want to use objects, you aren't required to use classes at all. Here is an example of a simple object.

```
# let p =
  object
    val mutable x = 0
    method get = x
    method set i = x <- i
```



```
end;;
val p : < get : int; set : int -> unit > = <obj>
```

The object has an integer value `x`, a method `get` that returns `x`, and a method `set` that updates the value of `x`.

The object type is enclosed in angle brackets `< ... >`, containing just the types of the methods. Fields, like `x`, are not part of the public interface of an object. All interaction with an object is through its methods. The syntax for a method invocation (also called "sending a message" to the object) uses the `#` character.

```
# p#get;
- : int = 0
# p#set 17;;
- : unit = ()
# p#get;;
- : int = 17
```

Objects can also be constructed by functions. If we want to specify the initial value of the object, we can define a function that takes the initial value and produces an object.

```
# let make i =
  object
    val mutable x = i
    method get = x
    method set y = x <- y
  end;;
val make : 'a -> < get : 'a; set : 'a -> unit > = <fun>
# let p = make 5;;
val p : < get : int; set : int -> unit > = <obj>
# p#get;;
- : int = 5
```

Note that the types of the function `make` and the returned object now use the polymorphic type `'a`. When `make` is invoked on a concrete value `5`, we get the same object type as before, with type `int` for the value.

Object Polymorphism

(yminsky: Maybe this is a good time to talk about the nature of object subtyping?)

Functions can also take object arguments. Let's construct a new object `average` that's the average of any two objects with a `get` method.

```
# let average p1 p2 =
  object
    method get = (p1#get + p2#get) / 2
  end;;
val average : < get : int; .. > -> < get : int; .. > -> < get : int > = <fun>
# let p1 = make 5;;
# let p2 = make 15;;
```

```
# let a = average p1 p2;;
# a#get;;
- : int = 10
# p2#set 25;;
# a#get;;
- : int = 15
```

Note that the type for `average` uses the object type `< get : int; .. >`. The `..` are ellipsis, standing for any other methods. The type `< get : int; .. >` specifies an object that must have at least a `get` method, and possibly some others as well. If we try using the exact type `< get : int >` for an object with more methods, type inference will fail.

```
# let (p : < get : int >) = make 5;;
Error: This expression has type < get : int; set : int -> unit >
      but an expression was expected of type < get : int >
      The second object type has no method set
```

Elisions are polymorphic

The `..` in an object type is an elision, standing for "possibly more methods." It may not be apparent from the syntax, but an elided object type is actually polymorphic. If we try to write a type definition, we get an obscure error.

```
# type point = < get:int; .. >;
Error: A type variable is unbound in this type declaration.
In type < get : int; .. > as 'a the variable 'a is unbound
```

A `..` in an object type is called a *row variable* and this typing scheme is called *row polymorphism*. Even though `..` doesn't look like a type variable, it actually is. The error message suggests a solution, which is to add the `as 'a` type constraint.

```
# type 'a point = < get:int; .. > as 'a;;
type 'a point = 'a constraint 'a = < get : int; .. >
```

In other words, the type `'a point` is equal to `'a`, where `'a = < get : int; .. >`. That may seem like an odd way to say it, and in fact, this type definition is not really an abbreviation because `'a` refers to the entire type.

An object of type `< get:int; .. >` can be any object with a method `get:int`, it doesn't matter how it is implemented. So far, we've constructed two objects with that type; the function `make` constructed one, and so did `average`. When the method `#get` is invoked, the actual method that is run is determined by the object.

```
# let print_point p = Printf.printf "Point: %d\n" p#get;;
val print_point : < get : int; .. > -> unit = <fun>
# print_point (make 5);;
Point: 5
# print_point (average (make 5) (make 15));;
Point: 10
```

Classes

Programming with objects directly is great for encapsulation, but one of the main goals of object-oriented programming is code re-use through inheritance. For inheritance, we need to introduce *classes*. In object-oriented programming, a class is a "recipe" for creating objects. The recipe can be changed by adding new methods and fields, or it can be changed by modifying existing methods.

In OCaml, class definitions must be defined as top-level statements in a module. A class is not an object, and a class definition is not an expression. The syntax for a class definition uses the keyword `class`.

```
# class point =
  object
    val mutable x = 0
    method get = x
    method set y = x <- y
  end;;
class point :
  object
    val mutable x : int
    method get : int
    method set : int -> unit
  end
```

The type `class point : ... end` is a *class type*. This particular type specifies that the `point` class defines a mutable field `x`, a method `get` that returns an `int`, and a method `set` with type `int -> unit`.

To produce an object, classes are instantiated with the keyword `new`.

```
# let p = new point;;
val p : point = <obj>
# p#get;;
- : int = 0
# p#set 5;;
- : unit = ()
# p#get;;
- : int = 5
```

(yminsky: You say that inheritance uses an existing class to define a new one, but the example below looks like using an existing class to define a new module. Is that what's going on? Or is a new class being created implicitly? If the latter, it might be better to be more explicit in this example and name the new class.)

Inheritance uses an existing class to define a new one. For example, the following class definition supports an addition method `moveby` that moves the point by a relative amount. This also makes use of the `(self : 'self)` binding after the `object` keyword. The variable `self` stands for the current object, allowing self-invocation, and the type

variable `'self'` stands for the type of the current object (which in general is a subtype of `movable_point`).

```
# class movable_point =
  object (self : 'self)
    inherit point
    method moveby dx = self#set (self#get + dx)
  end;;
```

Class parameters and polymorphism

A class definition serves as the *constructor* for the class. In general, a class definition may have parameters that must be provided as arguments when the object is created with `new`.

Let's build an example of an imperative singly-linked list using object-oriented techniques. First, we'll want to define a class for a single element of the list. We'll call it a *node*, and it will hold a value of type `'a`. When defining the class, the type parameters are placed in square brackets before the class name in the class definition. We also need a parameter `x` for the initial value.

```
class ['a] node x =
  object
    val mutable value : 'a = x
    val mutable next_node : 'a node option = None

    method get = value
    method set x = value <- x

    method next = next_node
    method set_next node = next_node <- node
  end;;
```

The `value` is the value stored in the node, and it can be retrieved and changed with the `get` and `set` methods. The `next_node` field is the link to the next element in the stack. Note that the type parameter `['a]` in the definition uses square brackets, but other uses of the type can omit them (or use parentheses if there is more than one type parameter).

The type annotations on the `val` declarations are used to constrain type inference. If we omit these annotations, the type inferred for the class will be "too polymorphic," `x` could have some type `'b` and `next_node` some type `'c option`.

```
class ['a] node x =
  object
    val mutable value = x
    val mutable next_node = None

    method get = value
    method set x = value <- x
```

```

    method next = next_node
    method set_next node = next_node <- node
  end;;
Error: Some type variables are unbound in this type:
  class ['a] node :
    'b ->
    object
      val mutable next_node : 'c option
      val mutable value : 'b
      method get : 'b
      method next : 'c option
      method set : 'b -> unit
      method set_next : 'c option -> unit
    end
  The method get has type 'b where 'b is unbound

```

In general, we need to provide enough constraints so that the compiler will infer the correct type. We can add type constraints to the parameters, to the fields, and to the methods. It is a matter of preference how many constraints to add. You can add type constraints in all three places, but the extra text may not help clarity. A convenient middle ground is to annotate the fields and/or class parameters, and add constraints to methods only if necessary.

Next, we can define the list itself. We'll keep a field `head` that refers to the first element in the list, and `last` refers to the final element in the list. The method `insert` adds an element to the end of the list.

```

class ['a] slist =
  object
    val mutable first : ('a) node option = None
    val mutable last : ('a) node option = None

    method is_empty = first = None

    method insert x =
      let new_node = Some (new node x) in
      match last with
      | Some last_node ->
        last_node#set_next new_node;
        last <- new_node
      | None ->
        first <- new_node;
        last <- new_node
  end;;

```

Object types

This definition of the class `slist` is not complete, we can construct lists, but we also need to add the ability to traverse the elements in the list. One common style for doing this is to define a class for an `iterator` object. An iterator provides a generic mechanism

to inspect and traverse the elements of a collection. This pattern isn't restricted to lists, it can be used for many different kinds of collections.

There are two common styles for defining abstract interfaces like this. In Java, an iterator would normally be specified with an interface, which specifies a set of method types. In languages without interfaces, like C++, the specification would normally use *abstract* classes to specify the methods without implementing them (C++ uses the "`= 0`" definition to mean "not implemented").

```
// Java-style iterator, specified as an interface.
interface <T> iterator {
    T Get();
    boolean HasValue();
    void Next();
};

// Abstract class definition in C++.
template<typename T>
class Iterator {
public:
    virtual ~Iterator() {}
    virtual T get() const = 0;
    virtual bool has_value() const = 0;
    virtual void next() = 0;
};
```

OCaml support both styles. In fact, OCaml is more flexible than these approaches because an object type can be implemented by any object with the appropriate methods, it does not have to be specified by the object's class *a priori*. We'll leave abstract classes for later. Let's demonstrate the technique using object types.

First, we'll define an object type `iterator` that specifies the methods in an iterator.

```
type 'a iterator = < get : 'a; has_value : bool; next : unit >;`
```

Next, we'll define an actual iterator for the class `slist`. We can represent the position in the list with a field `current`, following links as we traverse the list.

```
class ['a] slist_iterator cur =
object
  val mutable current : 'a node option = cur

  method has_value = current <> None

  method get =
    match current with
    | Some node -> node#get
    | None -> raise (Invalid_argument "no value")

  method next =
    match current with
    | Some node -> current <- node#next
```

```
      | None -> raise (Invalid_argument "no value")
    end;;
```

Finally, we add a method `iterator` to the `slist` class to produce an iterator. To do so, we construct an `slist_iterator` that refers to the first node in the list, but we want to return a value with the object type `iterator`. This requires an explicit coercion using the `:>` operator.

```
class ['a] slist = object
...
  method iterator = (new slist_iterator first :> 'a iterator)
end

# let l = new slist;;
# l.insert 5;;
# l.insert 4;;
# let it = l#iterator;;
# it#get;;
- : int = 5
# it#next;;
- : unit = ()
# it#get;;
- : int = 4
# it#next;;
- : unit = ()
# it#has_value;;
- : bool = false
```

We may also wish to define functional-style methods, `iter f` takes a function `f` and applies it to each of the elements of the list.

```
method iter f =
  let it = self#iterator in
  while it#has_value do
    f it#get
    it#next
  end
```

What about functional operations similar to `List.map` or `List.fold`? In general, these methods take a function that produces a value of some other type than the elements of the set. For example, the function `List.fold` has type `'a list -> ('b -> 'a -> 'b) -> 'b -> 'b`, where `'b` is an arbitrary type. To replicate this in the `slist` class, we need a method type `('b -> 'a -> 'b) -> 'b -> 'b`, where the method type is polymorphic over `'b`.

The solution is to use a type quantifier, as shown in the following example. The method type must be specified directly after the method name, which means that method parameters must be expressed using a `fun` or `function` expression.

```
method fold : 'b. ('b -> 'a -> 'b) -> 'b -> 'b =
  (fun f x ->
```

```

let y = ref x in
let it = self#iterator in
while it#has_value do
  y := f !y it#get;
  it#next
done;
!y)

```

Immutable objects

Many people consider object-oriented programming to be intrinsically imperative, where an object is like a state machine. Sending a message to an object causes it to change state, possibly sending messages to other objects.

Indeed, in many programs, this makes sense, but it is by no means required. Let's define an object-oriented version of lists similar to the imperative list above. We'll implement it with a regular list type 'a list, and insertion will be to the beginning of the list instead of to the end.

```

class ['a] flist =
object (self : 'self)
  val elements : 'a list = []

  method is_empty = elements = []

  method insert x : 'self = {< elements = x :: elements >}

  method iterator =
    (new flist_iterator elements :> 'a iterator)

  method iter (f : 'a -> unit) = List.iter f elements

  method fold : 'b. ('b -> 'a -> 'b) -> 'b -> 'b =
    (fun f x -> List.fold_left f x elements)
end;;

```

A key part of the implementation is the definition of the method `insert`. The expression `{< ... >}` produces a copy of the current object, with the same type, and the specified fields updated. In other words, the `new_fst new_x` method produces a copy of the object, with `x` replaced by `new_x`. The original object is not modified, and the value of `y` is also unaffected.

There are some restriction on the use of the expression `{< ... >}`. It can be used only within a method body, and only the values of fields may be updated. Method implementations are fixed at the time the object is created, they cannot be changed dynamically.

We use the same object type `iterator` for iterators, but implement it differently.

```

class ['a] flist_iterator l =

```



```

object
  val mutable elements : 'a list = []

  method has_value = l <> []

  method get =
    match l with
    | h :: _ -> h
    | [] -> raise (Invalid_argument "list is empty")

  method next =
    match l with
    | _ :: l -> elements <- l
    | [] -> raise (Invalid_argument "list is empty")
end;;

```

Class types

Once we have defined the list implementation, the next step is to wrap it in a module or .ml file and give it a type so that it can be used in the rest of our code. What is the type?

Before we begin, let's wrap up the implementation in an explicit module (we'll use explicit modules for illustration, but the process is similar when we want to define a .mli file). In keeping with the usual style for modules, we define a type 'a t to represent the type of list values.

```

module SList = struct
  type 'a iterator = < get : 'a; has_value : bool; next : unit >
  type 'a t = < is_empty : bool; insert : 'a -> unit; iterator : 'a iterator >

  class ['a] node x = object ... end
  class ['a] slist_iterator cur = object ... end
  class ['a] slist = object ... end

  let make () = new slist
end;;

```

We have multiple choices in defining the module type, depending on how much of the implementation we want to expose. At one extreme, a maximally-abstract signature would completely hide the class definitions.

```

module AbstractSList : sig
  type 'a iterator = < get : 'a; has_value : bool; next : unit >
  type 'a t = < is_empty : bool; insert : 'a -> unit; iterator : 'a iterator >

  val make : unit -> 'a t
end = SList

```

The abstract signature is simple because we ignore the classes. But what if we want to include them in the signature, so that other modules can inherit from the class definitions? For this, we need to specify types for the classes, called *class types*. Class types

do not appear in mainstream object-oriented programming languages, so you may not be familiar with them, but the concept is pretty simple. A class type specifies the type of each of the visible parts of the class, including both fields and methods. Just like for module types, you don't have to give a type for everything; anything you omit will be hidden.

```
module VisibleSList : sig
  type 'a iterator = < get : 'a; has_value : bool; next : unit >
  type 'a t = < is_empty : bool; insert : 'a -> unit; iterator : 'a iterator >

  class ['a] node : 'a ->
  object
    method get : 'a
    method set : 'a -> unit
    method next : 'a node option
    method set_next : 'a node option -> unit
  end

  class ['a] slist_iterator : 'a node option ->
  object
    method has_value : bool
    method get : 'a
    method next : unit
  end

  class ['a] slist :
  object
    val mutable first : 'a node option
    val mutable last : 'a node option
    method is_empty : bool
    method insert : 'a -> unit
    method iterator : 'a iterator
  end

  val make : unit -> 'a slist
end = SList
```

In this signature, we've chosen to make nearly everything visible. The class type for `slist` specifies the types of the fields `first` and `last`, as well as the types of each of the methods. We've also included a class type for `slist_iterator`, which is of somewhat more questionable value, since the type doesn't appear in the type for `slist` at all.

One more thing, in this example the function `make` has type `unit -> 'a slist`. But wait, we've stressed *classes are not types*, so what's up with that? In fact, what we've said is entirely true, classes and class names *are not* types. However, class names can be used to stand for types. When the compiler sees a class name in type position, it automatically constructs an object type from it by erasing all the fields and keeping only the method types. In this case, the type expression `'a slist` is exactly equivalent to `'a t`.

Subtyping

Subtyping is a central concept in object-oriented programming. It governs when an object with one type *A* can be used in an expression that expects an object of another type *B*. When this is true, we say that *A* is a *subtype* of *B*. Actually, more concretely, subtyping determines when the coercion operator `e :> t` can be applied. This coercion works only if the expression *e* has some type *s* and *s* is a subtype of *t*.

To explore this, let's define some simple classes for geometric shapes. The generic type `shape` has a method to compute the area, and a `square` is a specific kind of `shape`.

```
type shape = < area : float >;

class square w =
object (self : 'self)
  method area = self#width *. self#width
  method width = w
end;;
```

A `square` has a method `area` just like a `shape`, and an additional method `width`. Still, we expect a `square` to be a `shape`, and it is. The coercion `:>` must be explicit.

```
# let new_square x : shape = new square x;;
Characters 27-39:
  let new_square x : shape = new square x;;
                        ^^^^^^^^^^^^^^^
Error: This expression has type square but an expression was expected of type shape
The second object type has no method width
# let new_square x : shape = (new square x :> shape);;
val new_square : float -> shape = <fun>
```

What are the rules for subtyping? In general, object subtyping has two general forms, called *width* and *depth* subtyping. Width subtyping means that an object type *A* is a subtype of *B*, if *A* has all of the methods of *B*, and possibly more. A `square` is a subtype of `shape` because it implements all of the methods of `shape` (the `area` method).

The subtyping rules are purely technical, they have no relation to object semantics. We can define a class `rectangle` that has all of the methods of a `square`, so it is a subtype of `square` and can be used wherever a `square` is expected.

```
# class rectangle h w =
object (self : 'self)
  inherit square w
  method area = self#width *. self#height
  method height = h
end;;
# let square_rectangle h w : square = (new rectangle h w :> square);;
val square_rectangle : float -> float -> square = <fun>
```

This may seem absurd, but this concept is expressible in all object-oriented languages. The contradiction is semantic -- we know that in the real world, not all rectangles are squares; but in the programming world, rectangles have all of the features of squares (according to our definition), so they can be used just like squares. Suffice it to say that it is usually better to avoid such apparent contradictions.

Next, let's take a seemingly tiny step forward, and start building collections of shapes. It is easy enough to define a `slist` of squares.

```
# let squares =
  let l = Slist.make () in
  l#insert (new square 1.0);
  l#insert (new square 2.0);
  l;;
val squares : square slist = <obj>
```

We can also define a function to calculate the total area of a list of shapes. There is no reason to restrict this to squares, it should work for any list of shapes with type `shape slist`. The problem is that doing so raises some serious typing questions -- can a `square slist` be passed to a function that expects a `shape slist`? If we try it, the compiler produces a verbose error message.

```
# let total_area (l : shape slist) : float =
  let total = ref 0.0 in
  let it = l#iterator in
  while it#has_value do
    total := !total +. it#get#area;
    it#next
  done;
  !total;;
val total_area : shape slist -> float = <fun>
# total_area squares;;
Characters 11-18:
  total_area squares;;
      ^^^^^^^
Error: This expression has type
      square slist =
        < insert : square -> unit; is_empty : bool;
          iterator : square iterator >
      but an expression was expected of type
      shape slist =
        < insert : shape -> unit; is_empty : bool;
          iterator : shape iterator >
Type square = < area : float; width : float >
is not compatible with type shape = < area : float >
The second object type has no method width
```

It might seem tempting to give up at this point, especially because the subtyping is not even true -- the type `square slist` is not a subtype of `shape slist`. The problem is with the `insert` method. For `shape slist`, the `insert` method takes an arbitrary `shape` and

inserts it into the list. So if we could coerce a `square slist` to a `shape slist`, then it would be possible to insert an arbitrary shape into the list, which would be an error.

Using more precise types to address subtyping problems

Still, the `total_area` function should be fine, in principle. It doesn't call `insert`, so it isn't making that error. To make it work, we need to use a more precise type that indicates we are not going to be mutating the list. We define a type `readonly_shape_slist` and confirm that we can coerce the list of squares.

```
# type readonly_shape_slist = < iterator : shape iterator >;
type readonly_shape_slist = < iterator : shape iterator >
# (squares :> readonly_shape_slist);;
- : readonly_shape_slist = <obj>
# let total_area (l : readonly_shape_slist) : float = ...;;
val total_area : readonly_shape_slist -> float = <fun>
# total_area (squares :> readonly_shape_slist);;
- : float = 5.
```

Why does this work, why is a `square slist` a subtype of `readonly_shape_slist`. The reasoning is in two steps. First, the easy part is width subtyping: we can drop the other methods to see that `square slist` is a subtype of `< iterator : square iterator >`. The next step is to use *depth* subtyping, which, in its general form, says that an object type `< m : t1 >` is a subtype of a type `< m : t2 >` iff `t1` is a subtype of `t2`. In other words, instead of reasoning about the number of methods in a type (the width), the number of methods is fixed, and we look within the method types themselves (the "depth").

In this particular case, depth subtyping on the `iterator` method requires that `square iterator` be a subtype of `shape iterator`. Expanding the type definition for the type `iterator`, we again invoke depth subtyping, and we need to show that the type `< get : square >` is a subtype of `< get : shape >`, which follows because `square` is a subtype of `shape`.

This reasoning may seem fairly long and complicated, but it should be pointed out that this typing *works*, and in the end the type annotations are fairly minor. In most typed object-oriented languages, the coercion would simply not be possible. For example, in C++, a STL type `slist<T>` is invariant in `T`, it is simply not possible to use `slist<square>` where `slist<shape>` is expected (at least safely). The situation is similar in Java, although Java supports has an escape hatch that allows the program to fall back to dynamic typing. The situation in OCaml is much better; it works, it is statically checked, and the annotations are pretty simple.

Using elided types to address subtyping problems

Before we move to the next topic, there is one more thing to address. The typing we gave above, using `readonly_shape_slist`, requires that the caller perform an explicit

coercion before calling the `total_area` function. We would like to give a better type that avoids the coercion.

A solution is to use an elided type. Instead of `shape`, we can use the elided type `< area : float; .. >`. In fact, once we do this, it also becomes possible to use the `slist` type.

```
# let total_area (l : < area : float; .. > slist) : float = ...;;
val total_area : < area : float; .. > slist -> float = <fun>
# total_area squares;;
- : float = 5.
```

This works, and it removes the need for explicit coercions. This type is still fairly simple, but it does have the drawback that the programmer needs to remember that the types `< area : float; .. >` and `shape` are related.

OCaml supports an abbreviation in this case, but it works only for classes, not object types. The type expression `# classname` is an abbreviation for an elided type containing all of the methods in the named class, and more. Since `shape` is an object type, we can't write `#shape`. However, if a class definition is available, this abbreviation can be useful. The following definition is exactly equivalent to the preceeding.

```
# class cshape = object method area = 0.0 end;;
class cshape : object method area : float end
# let total_area (l : #cshape list) : float = ...;;
val total_area : #cshape slist -> float = <fun>
# total_area squares;;
- : float = 5.
```

Narrowing

Narrowing, also called *down casting*, is the ability to coerce an object to one of its subtypes. For example, if we have a list of shapes `shape slist`, we might know (for some reason) what the actual type of each shape is. Perhaps we know that all objects in the list have type `square`. In this case, *narrowing* would allow the re-casting of the object from type `shape` to type `square`. Many languages support narrowing through dynamic type checking. For example, in Java, a coercion `(Square) x` is allowed if the value `x` has type `Square` or one of its subtypes; otherwise the coercion throws an exception.

Narrowing is *not permitted* in OCaml. Period.

Why? There are two reasonable explanations, one based on a design principle, and another technical (the technical reason is simple: it is hard to implement).

The design argument is this: narrowing violates abstraction. In fact, with a structural typing system like in OCaml, narrowing would essentially provide the ability to enumerate the methods in an object. To check whether an object `obj` has some method `foo : int`, one would attempt a coercion `(obj :> < foo : int >)`.

More commonly, narrowing leads to poor object-oriented style. Consider the following Java code, which returns the name of a shape object.

```
String GetShapeName(Shape s) {
    if (s instanceof Square) {
        return "Square";
    } else if (s instanceof Circle) {
        return "Circle";
    } else {
        return "Other";
    }
}
```

Most programmers would consider this code to be "wrong." Instead of performing a case analysis on the type of object, it would be better to define a method to return the name of the shape. Instead of calling `GetShapeName(s)`, we should call `s.Name()` instead.

However, the situation is not always so obvious. The following code checks whether an array of shapes looks like a "barbell," composed to two `Circle` objects separated by a `Line`, where the circles have the same radius.

```
boolean IsBarBell(Shape[] s) {
    return s.length == 3 && (s[0] instanceof Circle) &&
        (s[1] instanceof Line) && (s[2] instanceof Circle) &&
        ((Circle) s[0]).radius() == ((Circle) s[2]).radius();
}
```

In this case, it is much less clear how to augment the `Shape` class to support this kind of pattern analysis. It is also not obvious that object-oriented programming is well-suited for this situation. Pattern matching seems like a better fit.

```
let is_bar_bell = function
| [Circle r1; Line _; Circle r2] when r1 == r2 -> true
| _ -> false;;
```

Regardless, there is a solution if you find yourself in this situation, which is to augment the classes with variants. You can define a method `variant` that injects the actual object into a variant type.

```
type shape = < variant : repr; area : float>
and circle = < variant : repr; area : float; radius : float >
and line = < variant : repr; area : float; length : float >
and repr =
| Circle of circle
| Line of line;;

let is_bar_bell = function
| [s1; s2; s3] ->
    (match s1#variant, s2#variant, s3#variant with
    | Circle c1, Line _, Circle c2 when c1#radius == c2#radius -> true
```

```
| _ -> false)
| _ -> false;;
```

This pattern works, but it has drawbacks. In particular, the recursive type definition should make it clear that this pattern is essentially equivalent to using variants, and that objects do not provide much value here.

Binary methods

A *binary method* is a method that takes an object of `self` type. One common example is defining a method for equality.

```
# class square w =
  object (self : 'self)
    method width = w
    method area = self#width * self#width
    method equals (other : 'self) = other#width = self#width
  end;;
class square : int ->
  object ('a)
    method area : int
    method equals : 'a -> bool
    method width : int
  end
# class rectangle w h =
  object (self : 'self)
    method width = w
    method height = h
    method area = self#width * self#height
    method equals (other : 'self) = other#width = self#width && other#height = self#height
  end;;
...
# (new square 5)#equals (new square 5);;
- : bool = true
# (new rectangle 5 6)#equals (new rectangle 5 7);;
- : bool = false
```

This works, but there is a problem lurking here. The method `equals` takes an object of the exact type `square` or `rectangle`. Because of this, we can't define a common base class `shape` that also includes an equality method.

```
# type shape = < equals : shape -> bool; area : int >;
# let sq = new square 5;;
# (sq :> shape);;
Characters 0-13:
  (sq :> shape);;
^^^^^^^^^^^^^^
Error: Type square = < area : int; equals : square -> bool; width : int >
      is not a subtype of shape = < area : int; equals : shape -> bool >
Type shape = < area : int; equals : shape -> bool > is not a subtype of
  square = < area : int; equals : square -> bool; width : int >
```


The problem is that a `square` expects to be compared with a `square`, not an arbitrary shape; similarly for `rectangle`.

This problem is fundamental. Many languages solve it either with narrowing (with dynamic type checking), or by method overloading. Since OCaml has neither of these, what can we do?

One proposal we could consider is, since the problematic method is equality, why not just drop it from the base type `shape` and use polymorphic equality instead? Unfortunately, the builtin equality has very poor behavior when applied to objects.

```
# (object method area = 5 end) = (object method area = 5 end);;
- : bool = false
```

The problem here is that the builtin polymorphic equality compares the method implementations, not their return values. The method implementations (the function values that implement the methods) are different, so the equality comparison is false. There are other reasons not to use the builtin polymorphic equality, but these false negatives are a showstopper.

If we want to define equality for shapes in general, the remaining solution is to use the same approach as we described for narrowing. That is, introduce a *representation* type implemented using variants, and implement the comparison based on the representation type.

```
type shape_repr =
  | Square of int
  | Circle of int
  | Rectangle of int * int;;

type shape = < repr : shape_repr; equals : shape -> bool; area : int >;;

class square w =
  object (self : 'self)
    method width = w
    method area = self#width * self#width
    method repr = Square self#width
    method equals (other : shape) = self#repr = other#repr
  end;;
```

The binary method `equals` is now implemented in terms of the concrete type `shape_repr`. In fact, the objects are now isomorphic to the `shape_repr` type. When using this pattern, you will not be able to hide the `repr` method, but you can hide the type definition using the module system.

```
module Shapes : sig
  type shape_repr
  type shape = < repr : shape_repr; equals : shape -> bool; area -> int >

  class square : int ->
```

```

    object
      method width : int
      method area : int
      method repr : shape_repr
      method equals : shape -> bool
    end
end = struct
  type shape_repr = Square of int | Circle of int | Rectangle of int * int
  ...
end;;

```

Private methods

Methods can be declared *private*, which means that they may be called by subclasses, but they are not visible otherwise (similar to a *protected* method in C++).

To illustrate, let's build a class `vector` that contains an array of integers, resizing the storage array on demand. The field `values` contains the actual values, and the `get`, `set`, and `length` methods implement the array access. For clarity, the resizing operation is implemented as a private method `ensure_capacity` that resizes the array if necessary.

```

# class vector =
  object (self : 'self)
    val mutable values : int array = [|]

    method get i = values.(i)
    method set i x =
      self#ensure_capacity i;
      values.(i) <- x
    method length = Array.length values

    method private ensure_capacity i =
      if self#length <= i then
        let new_values = Array.create (i + 1) 0 in
        Array.blit values 0 new_values 0 (Array.length values);
        values <- new_values
      end;;

  # let v = new vector;;
  # v#set 5 2;;
  # v#get 5;;
  - 2 : int
  # v#ensure_capacity 10;;
  Characters 0-1:
  v#ensure_capacity 10;;
  ^
Error: This expression has type vector
      It has no method ensure_capacity

```

To be precise, the method `ensure_capacity` is part of the class type, but it is not part of the object type. This means the object `v` has no method `ensure_capacity`. However, it is available to subclasses. We can extend the class, for example, to include a method `swap` that swaps two elements.

```
# class swappable_vector =
  object (self : 'Tself)
    inherit vector

    method swap i j =
      self#ensure_capacity (max i j);
      let tmp = values.(i) in
      values.(i) <- values.(j);
      values.(j) <- tmp
  end;;
```

Yet another reason for private methods is to factor the implementation and support recursion. Moving along with this example, let's build a binary heap, which is a binary tree in heap order: where the label of parent elements is smaller than the labels of its children. One efficient implementation is to use an array to represent the values, where the root is at index 0, and the children of a parent node at index i are at indexes $2 * i$ and $2 * i + 1$. To insert a node into the tree, we add it as a leaf, and then recursively move it up the tree until we restore heap order.

```
class binary_heap =
  object (self : 'self)
    val values = new swappable_vector

    method min =
      if values#length = 0 then
        raise (Invalid_argument "heap is empty");
      values#get 0

    method add x =
      let pos = values#length in
      values#set pos x;
      self#move_up pos

    method private move_up i =
      if i > 0 then
        let parent = (i - 1) / 2 in
        if values#get i < values#get parent then begin
          values#swap i parent;
          self#move_up parent
        end
      end
  end;;
```

The method `move_up` implements the process of restoring heap order as a recursive method (though it would be straightforward avoid the recursion and use iteration here).

The key property of private methods is that they are visible to subclasses, but not anywhere else. If you want the stronger guarantee that a method is *really* private, not even accessible in subclasses, you can use an explicit typing that omits the method. In the following code, the `move_up` method is explicitly omitted from the object type, and it can't be invoked in subclasses.

```
# class binary_heap :
  object
    method min : int
    method add : int -> unit
  end =
  object (self : 'self) {
    ...
    method private move_up i = ...
  }
end;;
```

Virtual classes and methods

A *virtual* class is a class where some methods or fields are declared, but not implemented. This should not be confused with the word "virtual" as it is used in C++. In C++, a "virtual" method uses dynamic dispatch, regular non-virtual methods use static dispatch. In OCaml, *all* methods use dynamic dispatch, but the keyword *virtual* means the method or field is not implemented.

In the previous section, we defined a class `swappable_vector` that inherits from `array_vector` and adds a `swap` method. In fact, the `swap` method could be defined for any object with `get` and `set` methods; it doesn't have to be the specific class `array_vector`.

One way to do this is to declare the `swappable_vector` abstractly, declaring the methods `get` and `set`, but leaving the implementation for later. However, the `swap` method can be defined immediately.

```
class virtual abstract_swappable_vector =
  object (self : 'self)
    method virtual get : int -> int
    method virtual set : int -> int -> unit
    method swap i j =
      let tmp = self#get i in
      self#set i (self#get j);
      self#set j tmp
  end;;
```

At some future time, we may settle on a concrete implementation for the vector. We can inherit from the `abstract_swappable_bvector` to get the `swap` method "for free." Here's one implementation using arrays.

```
class array_vector =
  object (self : 'self)
    inherit abstract_swappable_vector

    val mutable values = []
    method get i = values.(i)
    method set i x =
      self#ensure_capacity i;
```

```

        values.(i) <- x
    method length = Array.length values

    method private ensure_capacity i =
        if self#length <= i then
            let new_values = Array.create (i + 1) 0 in
                Array.blit values 0 new_values 0 (Array.length values);
            values <- new_values
        end
end

```

Here's a different implementation using HashTbl.

```

class hash_vector =
object (self : 'self)
    inherit abstract_swappable_vector

    val table = Hashtbl.create 19

    method get i =
        try Hashtbl.find table i with
            Not_found -> 0

    method set = Hashtbl.add table
end;;

```

One way to view a virtual class is that it is like a functor, where the "inputs" are the declared, but not defined, virtual methods and fields. The functor application is implemented through inheritance, when virtual methods are given concrete implementations.

We've been mentioning that fields can be virtual too. Here is another implementation of the swapper, this time with direct access to the array of values.

```

class virtual abstract_swappable_array_vector =
object (self : 'self)
    val mutable virtual values : int array
    method private virtual ensure_capacity : int -> unit

    method swap i j =
        self#ensure_capacity (max i j);
        let tmp = values.(i) in
            values.(i) <- values.(j);
            values.(j) <- tmp
        end;;
end;;

```

This level of dependency on the implementation details is possible, but it is hard to justify the use of a virtual class -- why not just define the `swap` method as part of the concrete class? Virtual classes are better suited for situations where there are multiple (useful) implementations of the virtual parts. In most cases, this will be public virtual methods.

Multiple inheritance

When a class inherits from more than one superclass, it is using *multiple inheritance*. Multiple inheritance extends the variety of ways in which classes can be combined, and it can be quite useful, particularly with virtual classes. However, it can be tricky to use, particularly when the inheritance hierarchy is a graph rather than a tree, so it should be used with care.

How names are resolved

The main "trickiness" of multiple inheritance is due to naming -- what happens when a method or field with some name is defined in more than one class?

If there is one thing to remember about inheritance in OCaml, it is this: inheritance is like textual inclusion. If there is more than one definition for a name, the last definition wins. Let's look at some artificial, but illustrative, examples.

First, let's consider what happens when we define a method more than once. In the following example, the method `get` is defined twice; the second definition "wins," meaning that it overrides the first one.

```
# class m1 =
object (self : 'self)
  method get = 1
  method f = self#get
  method get = 2
end;;
class m1 : object method f : int method get : int end
# (new m1)#f;;
- : int = 2
```

Fields have similar behavior, though the compiler produces a warning message about the override.

```
# class m2 =
# class m2 =
  object (self : 'self)
    val x = 1
    method f = x
    val x = 2
  end;;
Characters 69-74:
  val x = 2
      ^^^^^
Warning 13: the instance variable x is overridden.
The behaviour changed in ocaml 3.10 (previous behaviour was hiding.)
class m2 : object val x : int method f : int end
# (new m2)#f;;
- : int = 2
```

Of course, it is unlikely that you will define two methods or two fields of the same name in the same class. However, the rules for inheritance follow the same pattern: the last definition wins. In the following definition, the `inherit` declaration comes last, so the method definition `method get = 2` overrides the previous definition, always returning 2.

```
# class m4 = object method get = 2 end;;
# class m5 =
  object
    val mutable x = 1
    method get = x
    method set x' = x <- x'
    inherit m4
  end;;
class m5 : object val mutable x : int method get : int method set : int -> unit end
# let x = new m5;;
val x : m5 = <obj>
# x#set 5;;
- : unit = ()
# x#get;;
- : int = 2
```

To reiterate, to understand what inheritance means, replace each `inherit` directive with its definition, and take the last definition of each method or field. This holds even for private methods. However, it does *not* hold for private methods that are "really" private, meaning that they have been hidden by a type constraint. In the following definitions, there are three definitions of the private method `g`. However, the definition of `g` in `m8` is not overridden, because it is not part of the class type for `m8`.

```
# class m6 =
  object (self : 'self)
    method f1 = self#g
    method private g = 1
  end;;
class m6 : object method f1 : int method private g : int end
# class m7 =
  object (self : 'self)
    method f2 = self#g
    method private g = 2
  end;;
class m7 : object method f2 : int method private g : int end
# class m8 : object method f3 : int end =
  object (self : 'self)
    method f3 = self#g
    method private g = 3
  end;;
class m8 : object method f3 : int end
# class m9 =
  object (self : 'self)
    inherit m6
    inherit m7
    inherit m8
  end;;
```

```
# class m9 :
  object
    method f1 : int
    method f2 : int
    method f3 : int
    method private g : int
  end
# let x = new m9;;
val x : m9 = <obj>
# x#f1;;
- : int = 2
# x#f3;;
- : int = 3
```

Mixins

When should you use multiple inheritance? If you ask multiple people, you're likely to get multiple (perhaps heated) answers. Some will argue that multiple inheritance is overly complicated; others will argue that inheritance is problematic in general, and one should use object composition instead. But regardless of who you talk to, you will rarely hear that multiple inheritance is great and you should use it widely.

In any case, if you're programming with objects, there's one general pattern for multiple inheritance that is both useful and reasonably simple, the *mixin* pattern. Generically, a *mixin* is just a virtual class that implements a feature based on another one. If you have a class that implements methods *A*, and you have a mixin *M* that provides methods *B* from *A*, then you can inherit from *M* -- "mixing" it in -- to get features *B*.

That's too abstract, so let's give an example based on collections. In Section XXX: Objecttypes, we introduced the *iterator* pattern, where an *iterator* object is used to enumerate the elements of a collection. Lots of containers can have iterators, singly-linked lists, dictionaries, vectors, etc.

```
type 'a iterator = < get : 'a; has_value : bool; next : unit >;
class ['a] slist : object ... method iterator : 'a iterator end;;
class ['a] vector : object ... method iterator : 'a iterator end;;
class ['a] deque : object ... method iterator : 'a iterator end;;
class ['a, 'b] map : object ... method iterator : 'b iterator end;;
...
```

The collections are different in some ways, but they share a common pattern for iteration that we can re-use. For a simple example, let's define a mixin that implements an arithmetic sum for a collection of integers.

```
# class virtual int_sum_mixin =
  object (self : 'self)
    method virtual iterator : int iterator
    method sum =
      let it = self#iterator in
      let total = ref 0 in
```



```

        while it#has_value do
            total := !total + it#get;
            it#next
        done;
        !total
    end;;
# class int_slist =
  object
    inherit [int] slist
    inherit int_sum_mixin
  end;;
# let l = new int_slist;;
val l : int_slist = <obj>
# l#insert 5;;
# l#insert 12;;
# l#sum;;
- : int = 17
# class int_deque =
  object
    inherit [int] deque
    inherit int_sum_mixin
  end;;

```

In this particular case, the mixin works only for a collection of integers, so we can't add the mixin to the polymorphic class definition `['a] slist` itself. However, the result of using the mixin is that the integer collection has a method `sum`, and it is done with very little of the fuss we would need if we used object composition instead.

The mixin pattern isn't limited to non-polymorphic classes, of course. We can use it to implement generic features as well. The following mixin defines functional-style iteration in terms of the imperative iterator pattern.

```

class virtual [ 'a ] fold_mixin =
  object (self : 'self)
    method virtual iterator : 'a iterator
    method fold : 'b. ('b -> 'a -> 'b) -> 'b -> 'b =
      (fun f x ->
        let y = ref x in
        let it = self#iterator in
        while it#has_value do
          y := f !y it#get;
          it#next
        done;
        !y)
  end;;

class [ 'a ] slist_with_fold =
  object
    inherit [ 'a ] slist
    inherit [ 'a ] fold_mixin
  end;;

```

2012-09-23

13:57:45

CHAPTER 11

Concurrent Programming with Lwt

As soon as you start building OCaml code that interfaces with external systems, you'll need to handle concurrent, blocking operations. A web server sending a large file to many clients or a GUI waiting for a mouse click are both applications of this sort. These applications need to keep track of how blocking code is woken up in response to external I/O, and do so efficiently for many instances of these network connections or GUI elements.

In some programming languages such as Java or C#, you've probably used preemptive system threads to handle such operations. Other languages like Javascript are single-threaded, and an application must register callbacks to be triggered upon an external event such as a timeout or a browser click. Both methods have tradeoffs: threads are more memory hungry and require careful locking, but event callbacks quickly descend into a spaghetti of callbacks.

In OCaml, the Lwt library offers an interesting hybrid that lets you write straight-line blocking code that is internally evaluated via a single event-loop. Lwt threads are simply normal OCaml heap-allocated values, without any runtime magic, that hide internal state using the abstract types described earlier. These lightweight threads are limited only by your main memory and can be interfaced with a variety of network, storage and graphical outputs (including web browsers). In this chapter, we'll focus on the basics of Lwt and how to use it for building network services. Later, we'll describe more exotic platforms such as compiling the same code to Javascript (Chapter {???}).

Lets begin by constructing our first thread. Lwt is just a normal library, so open it in your toplevel and create your first thread:

```
# require "lwt" ;;  
# open Lwt ;;  
# return 5 ;;  
- : int Lwt.t = <abstr>
```

`return` constructs a thread that returns immediately, and above we've built one that returns a constant 5. Notice that the return type is not a normal `int`, but instead `int`

`Lwt.t`. The additional type parameter marks the value as a lightweight thread, which can internally be blocked, raising an exception, or completed. We can only *use* the return value by binding a further function to be invoked after the input thread has finished.

```
# let x = return 5 ;;
val x : int Lwt.t = <abstr>
# let y = bind x (fun a -> return (string_of_int a)) ;;
val y : string Lwt.t = <abstr>
```

Here, we've bound a function to `x` that will convert it to a string. Notice that while both `x` and `y` share a common `Lwt.t` type, their type variables differ based on return type of the thread. This can be really useful in large codebases, as you can tell if any function will block simply by the presence of an `Lwt.t` in the signature.

Lets examine the function signatures of `bind` and `return` more closely.

```
# return ;;
- : 'a -> 'a Lwt.t = <fun>
# bind ;;
- : 'a Lwt.t -> ('a -> 'b Lwt.t) -> 'b Lwt.t = <fun>
```

`return`, `bind` and the `Lwt.t` type all contain polymorphic type variables that are automatically inferred based on how they are used in your code. `bind` is particularly interesting as the the callback argument `'a` *must* be the same as the return type of the input thread, preventing runtime mismatches between callbacks. Both `bind` and `return` form a design pattern in functional programming known as *monads*, and you will run across this signature in many applications beyond just threads.

```
# #require "lwt.unix" ;;
# Lwt_unix.run ;;
- : 'a Lwt.t -> 'a = <fun>
# Lwt_unix.run y;;
- : string = "5"
```

`Lwt_unix.run` executes a thread until it completes, and returns a normal OCaml value. This usually forms the main loop of your program, as threads cannot be unblocked unless they run within the `run` function.

Timing and Thread Composition

Our examples so far have been with static threads, and now we'll look at how to coordinate multiple threads and timeouts. Lets write a program that spins off two threads, each of which sleep for some random amount of time, and then one prints "Heads" and the other "Tails", and finally prints "Finished" before exiting.

```
open Lwt
open Printf
```

```

let main () =
  bind (join [
    bind (Lwt_unix.sleep (Random.float 3.0)) (fun () ->
      print_endline "Heads";
      return ())
  );
  bind (Lwt_unix.sleep (Random.float 3.0)) (fun () ->
    print_endline "Tails";
    return ())
  );
  ]) (fun () ->
    print_endline "Finished";
    return ())
  )

let _ = Lwt_unix.run (main ())

```

This is a full code example that you can compile via (???). The `bind` function is joined by couple of new functions. `Lwt_unix.sleep` puts a thread to sleep for a given time, and `join` takes a list of threads and waits for all of them to terminate. If at least one thread fails then `join` fails with the same exception as the first to fail *after* all threads terminate. When run, this program immediately spawns two coin threads, and waits on them to complete before calling the final "Finished" closure.

The control flow above is somewhat hard to follow due to all the nested binds, and so Lwt provides infix operators with the same behaviour.

Function	Operator	Behaviour
bind	>>=	Wait for thread to finish, and apply return to new thread
join	<&>	Wait for two threads to finish and return unit
choose	<?>	Wait for the first thread to finish, cancel rest
map	> =	Map a non-blocking function over a blocking thread

We can now rewrite the earlier coin-flipping example using these operators. Notice that we can explicitly name threads simply by binding them via `let`, and they execute in parallel until joined together.

```

let main () =
  let t1 =
    Lwt_unix.sleep (Random.float 3.0) >>= fun () ->
      return (print_endline "Heads")
  in
  let t2 =
    Lwt_unix.sleep (Random.float 3.0) >>= fun () ->
      return (print_endline "Tails")
  in
  (t1 <&> t2) >>= fun () ->
    return (print_endline "Finished")

```

Syntax Extensions

```
let main () =  
  let t1 =  
    Lwt_unix.sleep (Random.float 3.0) >>  
    return (print_endline "Heads")  
  in  
  let t2 =  
    Lwt_unix.sleep (Random.float 3.0) >>  
    return (print_endline "Tails")  
  in  
  let () = t1 <&> t2 in  
  return (print_endline "Finished")
```

Cancellation

choose behaves as the first thread in l to terminate. If several threads are already terminated, one is chosen at random. Mixing normal exceptions and Lwt exceptions is bad.

A simple TCP Echo Server

Not using Lwt_daemon, but directly. This will be UNIX-only from this stage on, hmm...

Onto an HTTP Server

Describe cohttp (much simpler than Ocsigen at this stage).

Binding to the Github API

Show how we can use a monadic style to bind to the Github API and make simple JSON requests/responses.

A Note on Portability

Explain libev and why its needed here.

CHAPTER 12

DocBook Playground

A highlights section at the beginning of a chapter looks like this. It will:

- Have a set of useful bits.
- List entry 2.
- List entry 3.

Break up the notes with a normal paragraph of text.



This is a tip in Docbook. Lorem ipsum dolor sit amet, consectetur adipiscing elit, sed diam nonummy nibh euismod tincidunt ut laoreet dolore magna aliquam erat volutpat. Ut wisi enim ad minim veniam, quis nostrud exerci tation ullamcorper suscipit lobortis nisl ut aliquip ex ea commodo consequat. Duis autem vel eum iriure dolor in hendrerit in vulputate velit esse molestie consequat, vel illum dolore eu feugiat nulla facilisis at vero eros et accumsan et iusto odio dignissim qui blandit praesent luptatum zzril delenit augue dui dolore te feugait nulla facilisi. Nam liber tempor cum soluta nobis eleifend option congue nihil imperdiet doming id quod mazim placerat facer possim assum. Typi non habent claritatem insitam; est usus legentis in iis qui facit eorum claritatem. Investigationes demonstraverunt lectores legere me lius quod ii legunt saepius.

**this is a note title**

this is a tip in docbook. lorem ipsum dolor sit amet, consectetur adipiscing elit, sed diam nonummy nibh euismod tincidunt ut laoreet dolore magna aliquam erat volutpat. ut wisi enim ad minim veniam, quis nostrud exerci tation ullamcorper suscipit lobortis nisl ut aliquip ex ea commodo consequat. dui autem vel eum iriure dolor in hendrerit in vulputate velit esse molestie consequat, vel illum dolore eu feugiat nulla facilisis at vero eros et accumsan et iusto odio dignissim qui blandit praesent luptatum zzril delenit augue dui dolore te feugait nulla facilisi.

Cross reference example


This is a cross reference to another chapter.



Don't use `Obj.magic`!

As Xavier Leroy said: “Repeat after me: “`Obj.magic` is not part of the OCaml language””.

break up the notes with a normal paragraph of text.



This is a warning

It's very, very important to not run with scissors!

Break up the notes with a normal paragraph of text.

Q: To be, or not to be?

A: That is the question.

CHAPTER 13

Installation

avsm: these are just notes so far until we decide on firm recommendations for all these

Base Installation

MacOS X

Homebrew is probably the best solution here.

Windows

Protzenko's Windows installer.

Linux

Debian/Ubuntu packages. RHEL/Fedora RPMs.

Useful Libraries

Core, Lwt, mainly. Mention OPAM and OASIS-db, whichever works. Many packages maintained on github these days.

Environment

Command Line

rlwrap (<http://utopia.knoware.nl/~hlub/uck/rlwrap/>) provides line-editing support. An `.ocamlinit` file in your home directory will set up your environment with useful libraries and syntax extensions open, e.g.:

```
#use "topfind";;  
#load "dynlink.cma";;  
#camlp4o;;  
#require "lwt.syntax";;  
#require "lwt.unix";;  
open Lwt;;
```

Editors

Emacs users have tuareg and Typex (http://www.typerex.org/).

Vim users can use the built-in style, and ocaml-annot (http://github.com/avsm/ocaml-annot) may also be useful.

Eclipse plugins: which one is maintained?