

Sh4q Private Alpha Guide

Sh4q is a policy-controlled reconnaissance tool for domains you own or are explicitly authorised to test. It records what it observed, where the observation came from, and why a request or result was accepted or rejected.

Install

```
bash
```

```
git clone
```

```
cd sh4q
```

```
python3 -m venv venv
```

```
source venv/bin/activate
```

```
python -m pip install -e .
```

```
Subfinder is optional. The normal scan works without it. Add it only when you want passive subdomain discovery.
```

```
```bash
sh4q scan your-authorized-domain.example --sub
```

## First Scan

```
bash
```

```
sh4q scan your-authorized-domain.example
```

```
The scan runs DNS, HTTP, and certificate-transparency checks. With `--sub`, it also runs Subfinder and probes.
```

```
Read Results
```

```
```bash
sh4q show --latest --target your-authorized-domain.example
sh4q results --latest --target your-authorized-domain.example --type domain
sh4q results --latest --target your-authorized-domain.example --type url
sh4q results --latest --target your-authorized-domain.example --type technology
sh4q results --latest --target your-authorized-domain.example --failures
```

HTTP status codes such as 403 and 404 mean that a server responded. They do not mean that access was granted or that the application is healthy.

Export

```
bash
```

```
sh4q export --latest --target your-authorized-domain.example --format csv --output results.csv
```

```
sh4q export --latest --target your-authorized-domain.example --alive dns --format csv --output dns-alive.csv
```

```
sh4q export --latest --target your-authorized-domain.example --alive http --format csv --output http-alive.csv
```

```
sh4q export --latest --target your-authorized-domain.example --type technology --format json --output
technologies.json
```