

Sh4q Private Alpha Guide

Sh4q is a policy-controlled reconnaissance tool for domains you own or are explicitly authorised to test. It records what it observed, where the observation came from, and why a request or result was accepted or rejected.

Install

```
bash
```

```
git clone
```

```
cd sh4q
```

```
python3 -m venv venv
```

```
source venv/bin/activate
```

```
python -m pip install -e .
```

```
Subfinder is optional. The normal scan works without it. Add it only when you want passive subdomain discovery.
```

```
```bash
sh4q scan your-authorized-domain.example --sub
```

## First Scan

```
bash
```

```
sh4q scan your-authorized-domain.example
```

```
The scan runs DNS, HTTP, and certificate-transparency checks. With `--sub`, it also runs Subfinder and probes.
```

```
Read Results
```

```
```bash
sh4q show --latest --target your-authorized-domain.example
sh4q results --latest --target your-authorized-domain.example --type domain
sh4q results --latest --target your-authorized-domain.example --type url
sh4q results --latest --target your-authorized-domain.example --type technology
sh4q results --latest --target your-authorized-domain.example --failures
```

HTTP status codes such as 403 and 404 mean that a server responded. They do not mean that access was granted or that the application is healthy.

Technology observations are matched locally from the authorised response already collected by Sh4q. Empty version fields mean the inspected response did not explicitly disclose a version.

Export

```
bash
```

```
sh4q export --latest --target your-authorized-domain.example --format csv --output results.csv
```

```
sh4q export --latest --target your-authorized-domain.example --alive dns --format csv --output dns-alive.csv
```

```
sh4q export --latest --target your-authorized-domain.example --alive http --format csv --output http-alive.csv
```

```
sh4q export --latest --target your-authorized-domain.example --type technology --format json --output technologies.json
```

```
sh4q export --latest --target your-authorized-domain.example --type http-inventory --format csv --output http-inventory.csv
```