Architecture and data-flow diagrams

Drawn from the default branch of each repository under github.com/0x90-Problems. Commits: hackohio-2026 `2820c6f`, 0x90-NextJS-Backend `ebbda2a`, Buc2AgentMCP `f8ee271`, Buc2AgentTerraform `ed818a8`, nextjsapp `87f2903`, Buc2AgentNamespaceGitTracking `0033cc7`.

Nutshell is one board with two histories. The ticket board lives in MongoDB Atlas database `hackathon`. A separate git changelog, buck-track, stores immutable card versions on a VPS. People sign in through LLDAP. Agents act with the bearer of the person they work for.

☐ Caller or edge ☐ Process ☐ Store ☐ Reachable from the internet ☐ Present, not the path to use

Repositories

Repository	What it runs	What it stores
hackohio-2026	Nutshell UI on Vercel. Pages for home, projects, board, ticket, agents, teams, organization, profile, login. Routes `/auth/*`, `/api/board`, `/mcp`, and `/api/chat`.	No database of its own. Reads and writes Atlas. Proxies sign-in and MCP to the board API.
0x90-NextJS-Backend	Ticket API and an in-process MCP handler named `nutshell`. Vercel rewrite sends every path to `api/index.mjs`. A Fargate image can listen on port 3000.	When `MONGODB_URI` is set, loads and saves Atlas. Without it, the process memory demo board.
Buc2AgentMCP	Python FastMCP on port 8080, path `/mcp`. Forwards the caller bearer to `BOARD_API_URL`.	Nothing. Health is `/health`.
nextjsapp	Extracted Next.js app on branch `nazy-u-nextjs-app-extraction`. Chat attachments and the ClamAV worker installed on the VPS.	Upload state plus the same board proxies. Scanner source is this repo.
Buc2AgentNamespaceGitTracking	`buck-track` HTTP on port 8787 and a CLI. Same template catalog as the app.	Board folders, version files, and a git repo per board directory.
Buc2AgentTerraform	VPC `10.42.0.0/16` in us-east-1. Fargate tasks, one VPS, S3, SQS, an MCP load balancer.	SSM SecureStrings. Terraform state stays on the operator machine.

Live IPv4 addresses change when a task or the VPS is replaced. The current snapshot is `Buc2AgentTerraform/docs/endpoints.md`. This document uses names and ports.