10. Stores

Store	Keeps	Loses on restart
Atlas hackathon	Users, projects with layout and columns, tickets, comments, events, agents, organization settings, agent token hashes, auth token secrets, rest_state snapshot.	Nothing that persistBoard or /api/board already wrote.
Fargate board process	Demo board in memory when MONGODB_URI is absent. The task definition sets only PORT.	Tickets and tokens created in that process.
LLDAP task disk	Directory dc=hackohio,dc=local. Local compose keeps data/lldap and that directory is not in git.	Users created during the event, when the task is replaced.
Redis	Rate counters and pub/sub. No AOF and no RDB.	Counters and live subscribers.
VPS data volume	buck-track boards and their git repositories. Encrypted 20 GB volume plus encrypted root.	Survives reboot. terraform destroy deletes the volume.
S3 quarantine	Unscanned chat bytes.	Lifecycle deletes objects after one day.
S3 clean	Objects the scanner accepted.	Kept until the app deletes them.
SSM /buc2agent/*	Generated passwords and the Mongo URI.	Kept. Not in the Terraform repository.

Names the code shares

Scopes: `tickets:read`, `tickets:write`, `comments:write`, `tickets:close`. Actor types: human, agent. Agent connection: mcp or api_key. Event actions include ticket_created, ticket_moved, comment_added, commit_linked, and ticket_closed. Organization rules: approve_before_close, commit_on_move, log_agent_actions. Default organization name in the API is HackOHI/O 2026. Default team is 0x90 Problems. Default ticket prefix is CLW.

Paths that are specified and not joined

- The UI board route and the ticket API both write Atlas. A browser write does not pass the approval and commit rules.
- buck-track is a third board. Nothing in the ticket API or MCP calls port 8787.
- The app task on port 3000 is a TCP stand-in. It is not Nutshell and it is not the ticket API.
- Python MCP and the in-process MCP are two servers. Clients are directed to the Vercel URL because that URL accepts the tokens Atlas stores.
- The contract text still says the Next.js app renders mock data. The product repo's board route reads Atlas. The mock module remains in the tree for empty and offline states.

Source files: hackohio-2026 web/lib/board-proxy.ts, web/lib/auth-upstream.ts, web/app/api/board/route.ts, web/app/mcp/route.ts, web/app/api/chat/route.ts; 0x90-NextJS-Backend src/http.ts, src/mcp-http.ts, src/mongo-state.ts, src/store.ts, api/index.mjs, vercel.json; Buc2AgentMCP buc2agent_mcp/server.py; nextjsapp scanner/worker.mjs and web/app/api/chat/attachments; Buc2AgentTerraform README.md, docs/endpoints.md, board.tf, upload-scanning.tf; Buc2AgentNamespaceGitTracking docs/agent-contract.md.