

BENCHMARK COMPLIANCE AUDIT REPORT

CIS | NIST SP 800-53 | DISA STIG | ISO 27001

Generated: 2026-09-10 15:15:29

Devices Audited: 1

DEVICE 1/1: ASA.txt

Config File: /Users/kkrishnabhanushali/Documents/sih26155-poc/uploads/ASA.txt

Vendor: Cisco ASA

Total Rules: 61

Score: 82 / 184

Risk Level: **HIGH**

PASSED RULES (30)

PASS AUTH-001 Enable AAA new-model for centralized authentication, authorization, and accounting

Evidence: Line 80: aaa authentication ssh console LOCAL | Line 81: aaa authentication login-history

PASS AUTH-002 AAA authentication must be configured for SSH, login, or enable access

Evidence: Line 80: aaa authentication ssh console LOCAL | Line 81: aaa authentication login-history

PASS AUTH-003 AAA authentication login history should be enabled for audit trail

Evidence: Line 81: aaa authentication login-history

PASS AUTH-006 Local user accounts must use strong passwords (min 8 chars, not easily guessable)

Evidence: Line 97: username Marcraft privilege 15 password Marcraft1

PASS ACCESS-001 Telnet must be disabled on all VTY lines; use SSH only

Evidence: Not present (compliant)

PASS ACCESS-002 SSH must be configured as the only remote access method on VTY lines

Evidence: Line 89: ssh 192.168.5.0 255.255.255.0 inside

PASS ACCESS-003 SSH access must be restricted to specific subnets/interfaces

Evidence: Line 89: ssh 192.168.5.0 255.255.255.0 inside

PASS ACCESS-004 SSH strict host key checking should be enabled to prevent MITM attacks

Evidence: Line 88: ssh stricthostkeycheck

PASS ACCESS-005 SSH session timeout must be configured to prevent idle sessions

Evidence: Line 90: ssh timeout 15

PASS ACCESS-009 VTY lines should have access-class applied to restrict management access to trusted IPs

Evidence: Line 89: ssh 192.168.5.0 255.255.255.0 inside

PASS ACCESS-010 Exec timeout must be set on console and VTY lines to auto-disconnect idle sessions

Evidence: Line 90: ssh timeout 15 | Line 92: console timeout 0

PASS SNMP-001 Default SNMP community string 'public' must not be used

Evidence: Not present (compliant)

PASS SNMP-002 Default SNMP community string 'private' must not be used

Evidence: Not present (compliant)

PASS SNMP-004 SNMP location should be cleared or set to a non-revealing value to avoid information disclosure

Evidence: Line 82: no snmp-server location

PASS SNMP-005 SNMP contact should be cleared or set to a non-revealing value to avoid information disclosure

Evidence: Line 83: no snmp-server contact

PASS SVC-012 FTP passive mode should be configured for secure file transfers

Evidence: Line 61: ftp mode passive

PASS SVC-013 ASDM history should be disabled if ASDM is not in active use

Evidence: Line 65: no asdm history enable

PASS SVC-014 Call-home and anonymous reporting should be disabled to prevent information disclosure

Evidence: Line 101: no call-home reporting anonymous | Line 104: no active

PASS SVC-015 ICMP unreachable messages should be rate-limited to mitigate reconnaissance

Evidence: Line 64: icmp unreachable rate-limit 1 burst-size 1

PASS SVC-016 ARP rate limiting should be configured to mitigate ARP flooding attacks

Evidence: Line 68: arp rate-limit 16384

PASS SVC-017 Non-connected ARP entries should be denied to prevent ARP spoofing

Evidence: Line 67: no arp permit-nonconnected

PASS CRYPTO-001 IPsec SA PMTU aging should be configured for proper tunnel maintenance

Evidence: Line 85: crypto ipsec security-association pmtu-aging infinite

PASS CRYPTO-002 CA trustpool policy should be configured for certificate validation

Evidence: Line 86: crypto ca trustpool policy

PASS MGMT-003 Hostname must be set for device identification in logs and management

Evidence: Line 3: hostname ciscoasa | Line 100: prompt hostname context

PASS THREAT-001 Basic threat detection must be enabled to identify common attack patterns

Evidence: Line 93: threat-detection basic-threat

PASS THREAT-002 Threat detection ACL statistics should be enabled for monitoring denied traffic patterns

Evidence: Line 94: threat-detection statistics access-list

PASS THREAT-003 TCP intercept statistics should be enabled for SYN flood detection

Evidence: Line 95: no threat-detection statistics tcp-intercept

PASS INTF-001 Unused interfaces should be administratively shut down to reduce attack surface

Evidence: Line 13: shutdown | Line 19: shutdown | Line 25: shutdown

PASS INTF-002 Management interface should be restricted to management traffic only

Evidence: Line 55: management-only

PASS DAP-001 Dynamic access policy should be configured for VPN access control

Evidence: Line 96: dynamic-access-policy-record DfltAccessPolicy

FAILED RULES (31)**FAIL HIGH AUTH-004** Cleartext 'enable password' should not be used; use 'enable secret' with st...

Evidence: VIOLATION FOUND - Line 4: enable password Marcraft1

Remediation: no enable password

FAIL HIGH AUTH-005 Password encryption service must be enabled to protect stored passwords

Evidence: Configuration not found

Remediation: service password-encryption

FAIL MEDIUM AUTH-007 AAA accounting must be configured to log all administrative actions

Evidence: Configuration not found

Remediation: aaa accounting exec default start-stop group tacacs+

FAIL MEDIUM AUTH-008 AAA authorization must be configured for command-level access control

Evidence: Configuration not found

Remediation: aaa authorization exec default local

FAIL HIGH ACCESS-006 SSH key exchange must use strong groups (dh-group14-sha256 or higher); dh-g...

Evidence: VIOLATION - Line 91: ssh key-exchange group dh-group1-sha1

Remediation: `ssh key-exchange group dh-group14-sha256`

FAIL HIGH ACCESS-007 Console timeout must be set to a non-zero value to prevent unauthorized acc...

Evidence: VIOLATION - Line 92: console timeout 0

Remediation: `console timeout 5`

FAIL HIGH ACCESS-008 Telnet timeout configuration suggests Telnet may be in use; Telnet should b...

Evidence: VIOLATION FOUND - Line 87: telnet timeout 5

Remediation: `no telnet timeout`

FAIL HIGH ACCESS-011 SSH version 2 must be enforced; SSH version 1 has known vulnerabilities

Evidence: Configuration not found

Remediation: `ip ssh version 2`

FAIL MEDIUM SNMP-003 SNMPv3 should be configured for encrypted and authenticated SNMP communications

Evidence: Configuration not found

Remediation: `snmp-server group <group-name> v3 priv`

FAIL HIGH SVC-001 HTTP server must be disabled to prevent unencrypted management access

Evidence: Configuration not found

Remediation: `no ip http server`

FAIL MEDIUM SVC-002 HTTPS server should be disabled unless explicitly required for device management

Evidence: Configuration not found

Remediation: `no ip http secure-server`

FAIL MEDIUM SVC-003 CDP should be disabled globally or on untrusted interfaces to prevent infor...

Evidence: Configuration not found

Remediation: `no cdp run`

FAIL MEDIUM SVC-004 LLDP should be disabled to prevent network topology disclosure

Evidence: Configuration not found

Remediation: `no lldp run`

FAIL HIGH SVC-005 IP source routing must be disabled to prevent routing manipulation attacks

Evidence: Configuration not found

Remediation: `no ip source-route`

FAIL HIGH SVC-006 IP directed broadcasts must be disabled to prevent smurf amplification attacks

Evidence: Configuration not found

Remediation: `no ip directed-broadcast`

FAIL MEDIUM SVC-007 Finger service must be disabled to prevent user enumeration

Evidence: Configuration not found

Remediation: `no service finger`

FAIL MEDIUM SVC-008 BOOTP server must be disabled to prevent unauthorized network booting

Evidence: Configuration not found

Remediation: `no ip bootp server`

FAIL MEDIUM SVC-009 Proxy ARP must be disabled to prevent traffic interception

Evidence: Configuration not found

Remediation: `no ip proxy-arp`

FAIL LOW SVC-010 TCP keepalives (inbound) should be enabled to clean up dead sessions

Evidence: Configuration not found

Remediation: `service tcp-keepalives-in`

FAIL LOW SVC-011 TCP keepalives (outbound) should be enabled to clean up dead sessions

Evidence: Configuration not found

Remediation: `service tcp-keepalives-out`

FAIL HIGH LOG-001 Syslog server must be configured for centralized log collection and analysis

Evidence: Configuration not found

Remediation: logging host <syslog-server-ip>

FAIL MEDIUM LOG-002 Local logging buffer must be configured for on-device log retention

Evidence: Configuration not found

Remediation: logging buffered informational

FAIL MEDIUM LOG-003 Log messages must include timestamps with date/time for accurate forensic analysis

Evidence: Configuration not found

Remediation: service timestamps log datetime msec localtime show-timezone

FAIL MEDIUM LOG-004 Logging trap level should be configured for appropriate syslog message filtering

Evidence: Configuration not found

Remediation: logging trap informational

FAIL HIGH CRYPTO-003 RSA keys must be generated with a minimum modulus of 2048 bits for SSH

Evidence: Configuration not found

Remediation: crypto key generate rsa modulus 2048

FAIL MEDIUM MGMT-001 Login banner must be configured to display legal/warning notice before authentication

Evidence: Configuration not found

Remediation: banner login @

FAIL LOW MGMT-002 MOTD banner should be configured to display operational warnings

Evidence: Configuration not found

Remediation: banner motd @

FAIL HIGH NTP-001 NTP server must be configured for accurate time synchronization across all log sources

Evidence: Configuration not found

Remediation: ntp server <ntp-server-ip>

FAIL MEDIUM NTP-002 NTP authentication must be enabled to prevent time-source spoofing

Evidence: Configuration not found

Remediation: ntp authenticate

FAIL MEDIUM ROUTE-001 OSPF authentication must be enabled to prevent unauthorized route injection

Evidence: Configuration not found

Remediation: interface <interface>

FAIL MEDIUM ROUTE-002 BGP neighbor authentication must be configured to prevent unauthorized peering

Evidence: Configuration not found

Remediation: router bgp <as-number>

UNKNOWN COMMANDS - NEEDS HUMAN REVIEW (2)**UNKNOWN L66** arp timeout 14400

Needs human review

UNKNOWN L84 service sw-reset-button

Needs human review