

# This is CS50x

OpenCourseWare

Donate (<https://cs50.harvard.edu/donate>) [↗](https://community.alumni.harvard.edu/give/59206872) (<https://community.alumni.harvard.edu/give/59206872>)

David J. Malan (<https://cs.harvard.edu/malan/>)  
malan@harvard.edu

[f](https://www.facebook.com/dmalan) (<https://www.facebook.com/dmalan>) [G](https://github.com/dmalan) (<https://github.com/dmalan>) [@](https://www.instagram.com/davidjmalan/) (<https://www.instagram.com/davidjmalan/>) [in](https://www.linkedin.com/in/malan/) (<https://www.linkedin.com/in/malan/>) [id](https://orcid.org/0000-0001-5338-2522) (<https://orcid.org/0000-0001-5338-2522>) [Q](https://www.quora.com/profile/David-J-Malan) (<https://www.quora.com/profile/David-J-Malan>) [r](https://www.reddit.com/user/davidjmalan) (<https://www.reddit.com/user/davidjmalan>) [T](https://twitter.com/davidjmalan) (<https://twitter.com/davidjmalan>)

## Mario

### World 1-1

Toward the beginning of World 1-1 in Nintendo’s Super Mario Brothers, Mario must hop over adjacent pyramids of blocks, per the below.



Let’s recreate those pyramids in C, albeit in text, using hashes (`#`) for bricks, a la the below. Each hash is a bit taller than it is wide, so the pyramids themselves are also be taller than they are wide.

```
# #
## ##
### ###
#### ####
```

The program we’ll write will be called `mario`. And let’s allow the user to decide just how tall the pyramids should be by first prompting them for a positive integer between, say, 1 and 8, inclusive.

Here’s how the program might work if the user inputs `8` when prompted:

```
$ ./mario
Height: 8
# #
## ##
### ###
#### ####
##### #####
##### #####
##### #####
##### #####
```

Here’s how the program might work if the user inputs `4` when prompted:

```
$ ./mario
Height: 4
# #
## ##
### ###
#### ####
```

Here’s how the program might work if the user inputs `2` when prompted:

```
$ ./mario
Height: 2
  #  #
##  ##
```

And here’s how the program might work if the user inputs `1` when prompted:

```
$ ./mario
Height: 1
#  #
```

If the user doesn’t, in fact, input a positive integer between 1 and 8, inclusive, when prompted, the program should re-prompt the user until they cooperate:

```
$ ./mario
Height: -1
Height: 0
Height: 42
Height: 50
Height: 4
  #  #
##  ##
### ###
#### ####
```

Notice that width of the “gap” between adjacent pyramids is equal to the width of two hashes, irrespective of the pyramids’ heights.

Create a new directory (i.e., folder) called `mario` inside of your `pset1` directory, by executing

```
~/ $ mkdir ~/pset1/mario
```

Create a new file called `mario.c` inside your `mario` directory. Modify `mario.c` in such a way that it implements this program as described!

Walkthrough

How to Test Your Code

Does your code work as prescribed when you input

- (or other negative numbers)?
- ?
- through ?
- or other positive numbers?
- letters or words?
- no input at all, when you only hit Enter?

You can also execute the below to evaluate the correctness of your code using `check50`. But be sure to compile and test it yourself as well!

```
check50 cs50/problems/2021/x/mario/more
```

Execute the below to evaluate the style of your code using `style50`.

```
style50 mario.c
```

## How to Submit

Execute the below, logging in with your GitHub username and password when prompted. For security, you'll see asterisks (`*`) instead of the actual characters in your password.

```
submit50 cs50/problems/2021/x/mario/more
```