#### SIAL

2860 Boul. Le Corbusier Laval, Qc.,H7L 3S1

Tel: (450) 687-4046 Fax: (450) 687-4105

#### MATERIAL SAFETY DATA SHEET

## SECTION 1 IDENTIFICATION OF PRODUCT

Description China Slip
Product Name 124M Slip
Used For Ceramic casting

## SECTION 2 HAZARDOUS INGREDIENTS

Hazardous ingredient % CAS Number Specification

Respirable Free Silica (Quartz) < 3.5 % 14808-60-7 Barium Carbonate < 0.015 % 513-77-9

\*Note: Free Silica is not a hazard in moist or wet form; it is only a hazard if slip is dry and dust is generated

#### SECTION 3 PHYSICAL DATA

Appearance: Liquid
Odor: None
Color: Gray

Density: 1780 g/l (±5g/l)

Melting Point: -2°C
Boiling Point: 102°C
Vapor Pressure: N/A
Solubility in Water: Unlimited
Percent Volatile: N/A
pH: 7.8 (±0.5)

## SECTION 4 FIRE AND EXPLOSION HAZARD DATA

None

SECTION 5 REACTIVITY DATA

General Reactivity: None Incompatibility: None

## SECTION 6 HEALTH HAZARD INFORMATION

Inhalation: None; No special protection required

Ingestion: None Skin Contact: None

Eye Contact: Flush with water; consult physician if irritation

persist

Dried Dust Inhalation: Long term respiratory difficulties (silicosis). Wear

NIOSH/MSHA/OSHA approved respirator, if handling or processing dried greenware

## **SECTION 7**

## PROCEDURES DISPOSAL REQUIREMENTS

• Steps to be taken IN CASE MATERIAL IS RELEASED OR SPILLED:

Material is not dangerous if spilled. Simply wash away with water. If uncontaminated, recover and use. Avoid creating dust if dried. Avoid breathing dust. Wear a NIOSH/MSHA/OSHA approved respirator. Good housekeeping practices recommended.

• WASTE AND CONTAINER DISPOSAL METHODS:

Disposal methods for non-hazardous materials should be complied with. May be buried in approved land disposal facility, in accordance with Federal, State/Provincial, and local regulations. The ceramic slip is not regulated by DOT.

# SECTION 8 SPECIAL PROTECTION INFORMATION

Eye Protection: Safety glasses optional, but recommended

Protective Gloves: Optional, but recommended

Respiratory Protection: None if working with slip;; NIOSH/MSHA/OSHA

approved respirator in processing greenware products

Ventilation: Not necessary

SECTION 9	CHEMICAL COMPOSITION (after firing)
BaO	0.02%
CaO	0.40%
MgO	1.60%
K <sub>2</sub> O	1.71%
Na <sub>2</sub> O	3.18%
Fe2O <sub>3</sub>	0.01%
$Al_2O_3$	38.76%
$SiO_2$	54.33%

## SECTION 10 SPECIAL REQUIREMENT/PRECAUTIONS

#### Storage Requirements:

#### Avoid freezing

The information contained herein is believed to be accurate, but SIAL makes no warranty with respect there to and disclaims responsibility for reliance thereon. This information applies only to the specific material described herein, and does not relate to use in connection with any other materials or in any process.

SIAL makes no warranties, express or implied, concerning this product. No warranty or fitness for any particular purpose is made and we assume no responsibility whatever for any use of this product. This product should be used by properly trained personnel in compliance with applicable health and safety laws and regulations.

Revised date: July 2014