# COMSATS University Islamabad, Lahore Campus

## Mid Term, Examination – Spring 2024

| | | | | | | | |
|---|---|---|---|---|---|---|---|
| Course Title: | Web Technologies | | | Course Code: | CSC336 | Credit | 4(3,1) |
| Course Instructor/s: | Asif Shahzad | | | Programme Name: | BSSE | | |
| Semester: | 4 | Batch: FA22 | Section: | C, D | Date: | Apr. 24, 2024 | |
| Time Allowed: | 1.5 Hour | | | Maximum Mark[redacted] | 50 | | |
| Student's Name: [redacted] | | | | Reg. No. | [redacted] | | |

**Important Instructions / Guidelines:**
Please implement functionality that is asked, do not do any extra work. Present your work with good UI.

**Question 1 [CLO-1]**

Write 5 HTTP headers names with an example value of each. Write 2-3 lines about each header to explain its objective or functionality? [10 Marks]

**Question 2 [CLO-2]**

(Do not use Bootstrap for this) Using media queries and mobile first design principle, write HTML and CSS such that, there shall be 4 links that shall appear vertically stacked on small devices but for devices with 400px or higher width, links shall appear horizontal i.e. in a single row (assume they are header links). [10 Marks]

**Question 3 [CLO-4]**

Write HTML and JavaScript. Add paragraph using "p" element having a short text with id="para", add 4 radio buttons, labeled with different color names e.g. red, green, blue, brown, etc. Also add an Apply button. When the button is clicked, selected color in the radio box shall be applied to paragraph background. [15 Marks]

Compiled by Hafiz Ahmad
Owner of SuperCUI

**Question 4 [CLO-3]**

Assume an HTTP end point *example.com/products.json* returns JSON i.e. an array of objects where each object contains different attributes of a product. Write only JavaScript code, such that, on page load, it shall fetch products using AJAX and create an HTML table. Embed the created table in inner HTML of an already existing div with id "canvas". You must display all attributes of each product, so the number of columns shall be equal to number of product attributes. Assume all products have same field names and all fields are initialized with an atomic value of type number, string, Boolean, etc, (but not an array). [15 Marks]