COMSATS University Islamabad, Lahore Campus

Midterm Examination – SPRING 2023

Course Title:	Web Technologies			Course Code:	CSC336	Credit Hours:	4(3,1)
Instructor/s:	Muhammad Usman Akram, Asif Shahzad, Ali Hassan			Program Name:	BSCS, BSSE		
Semester:		Batch:	Section:		Date:	08-05-2023	
Time Allowed:	1.5 Hours			Maximum Marks:		50	
Student's Name:	M. Awais Akhter			Reg. No.	FA20-BSE-021		

Important Instructions / Guidelines:

- Please be to the point. No need to add unnecessary details.
- Please make sure to review all the answers before submitting the paper.
- Please spend some time understanding the question and plan for the answer.
- Minor mistakes of syntax are not a big issue.

Question 1 [CLO-1] **[15]**

Below is the HTML code for a form. Write only CSS code to style the form, such that:

1. Labels and inputs shall appear side by side with label taking 30% and rest shall go to input field/s
2. Each form row (assume, label and its input field as a row), shall be 20px apart from previous row
3. Text input fields shall have 5px padding from top and bottom and 10px padding from left & right
4. Each form row shall have 20px padding and light gray background color
5. Form shall display at the center of the page and shall take only 800px width

```
<form>
<div><label>Name</label><input type="text" name="name"/></div>
<div><label>Email </label><input type="text" name="email" value="" /></div>
<div><label>Gender </label><div>
  <input type="radio" name="gender" value="m" /> Male
  <input type="radio" name="gender" value="f" /> Female</div></div>
<div><label>Subjects </label><div>
 <input type="checkbox" name="subject" value="OOP" /> OOP
 <input type="checkbox" name="subject" value="DB" checked /> Database</div> </div>
<div><input type="submit" value="Submit"></div>
</form>
```

Compiled by Hafiz Ahmad
Owner of SuperCUI

Question 2 [CLO-2] **[15]**

Write HTML code that shall make use of Bootstrap built-in classes. Define a container div having one row and 3 columns (may change, based on device). For extra-small and small devices, the first cell/column shall take 100% width of container and other two shall take 50% and 50% width of container (so, 3 divs shall come in two rows, in this case). For medium width screens, all columns shall take equal width and come in a single row. For larger width screens, each cell shall take 25% of container and justify as spaced between.

Question 3 [CLO-3] **[10]**

Consider below given HTML code, write JavaScript to define the event handler for the button that shall add a new item to the list. The text for the new item shall be used from the text input field. Bind the handler to the button click event, when the page loads.

```
<ul id="myList">
   <li>Item 1</li>
   <li>Item 2</li>
   <li>Item 3</li>
</ul>
<input type="text" id="newItem">
<button id="addItem">Add Item</button>
```

Question 4 [CLO-3] **[10]**

Assume an API endpoint return list of users in JSON format (as given below). Using JavaScript, on page load, make an AJAX call to the API and display the list of users in a table. Render the table inside a div with id "result".

```
[
 {
    "id":1,
    "name":"Ali Khan",
    "username":"Ali",
    "email":"ali@gmail.com",
    "phone":"302-548787",
    "website":"aliblog.org"
  }
]
```

Compiled by Hafiz Ahmad
Owner of SuperCUI