Sensitive Response

```
HTTP/1.1 200 OK
Content-Length: Number
Content-Type: application/json

{
  "phone" : "01*********",
  "token" : "**************"

}
```


Mahmoud M. Awali

@0xAwali

attacker

My Methodology

Try To Inject Origin Header e.g. Origin: http://me.com And If Response Contains Access-Control-Allow-Origin: http://me.com AND Access-Control-Allow-Credentials: True , There is CORS

- Writeup
- Writeup
- Writeup

```
GET /getInfo HTTP/1.1
Host: www.company.com
User-Agent: Mozilla/5.0
Referer: https://previous.com/path
Origin: http://me.com
```

attacker

My Methodology

Try To Inject Origin Header With Your Domain e.g. http://company.com.me.com , http://Acompany.com , http://companyAcom , http://company.comA And null To Get CORS

- Video
- Video
- Tweet

```
GET /getInfo HTTP/1.1
Host: www.company.com
User-Agent: Mozilla/5.0
Referer: https://previous.com/path
Origin: http://company.com.me.com
```

attacker

My Methodology

Try To Inject Origin Header With Special Chars e.g. , & ' " ; ! $ ^ * ( ) + = ` ~ - _ = | { } % OR Non Printable Chars e.g. %01-08 , %0b , %0c , %0e , %0f , %10-%1f AND %7f

- Blog
- Writeup

```
GET /getInfo HTTP/1.1
Host: www.company.com
User-Agent: Mozilla/5.0
Referer: https://previous.com/path
Origin: http://me.com`.company.com
```

attacker

My Methodology

Try To Inject Origin Header e.g. Origin: http://me.com And If Response Contains Access-Control-Allow-Origin: * AND There Is Cache-Control: no-cache Header Try Use This POC

- Writeup
- Blog
- Tweet

```
<html>
<script>
var url = "https://www.company.com/getInfo";
fetch(url, {
    method: 'GET',
    cache: 'force-cache'
    });
</script>
</html>
```

attacker

My Methodology

Try To Use Web Cache Deception Attack , Add Static File e.g. nonexistent.css OR logo.png To Your Endpoint To Cache Sensitive Response

- Slides
- Writeup
- Writeup
- Writeup
- Writeup

```
GET /getInfo/nonexistent.css HTTP/1.1
Host: www.company.com
User-Agent: Mozilla/5.0
Referer: https://previous.com/path
Origin: https://www.company.com
```

attacker

My Methodology

Try To Add jsonp OR callback To Any Sensitive Endpoints e.g. http://company.com/getInfo?jsonp=function To You Can Read The Response

- Tweet
- Writeup



attacker

My Methodology

Try To Figure Out , There Is **Cache-Control: no-cache** Header In HTTP/1.1 Response OR **Pragma: no-cache** Header In HTTP/1.0 Response , If Yes There Is Issue Here

- Tweet

```
HTTP/1.1 200 OK
Content-Length: Number
Cache-Control: no-cache , no-store , must-revalidate
Content-Type: application/json

{
  "phone" : "01*********",
  "token" : "*************"

}
```

attacker

My Methodology

Try To Figure Out , There Is X-Frame-Option Header OR Not In The Response

- Blog
- Writeup
- Writeup

```
HTTP/1.1 200 OK
Content-Length: Number
X-Frame-Option: SAMEORIGIN
Content-Type: application/json

{
  "phone" : "01*********",
  "token" : "*************"

}
```

attacker

My Methodology

There Are JSONP Endpoints OR JavaScript URL e.g. http://company.com/getInfo.js Contains Sensitive Data Based Only On Cookie , Try To Include It To Achieve XSSI

- Slides
- Blog
- Writeup

Steps to produce :-

1 - Filter Burp Suite History To MIME type Script
2 - Lookout For JS Endpoints Without
X-Content-Type-Options: nosniff
3 - Search About
Sensitive Data
4 - Make Sure There Isn't Authorization Headers

attacker

My Methodology

Try To Figure Out , There Is postMessage API e.g. Window.postMessage("text", "*");
OR addEventListener("message", function(message){message.origin});

- Blog
- Blog
- Blog
- Blog
- Blog

Steps to produce :-

1 - Browse To http://company.com/getInfo
2 - Right Clicking , Click On View Page Source
3 - Search About
postMessage With *
addEventListener With Argument-Function.origin

Thank You

Mahmoud M. Awali

@0xAwali