

# Introduction to Scientific Typesetting

## Lesson 16: Plotting data using $\text{\LaTeX}$

Ryan Higginbottom

January 26, 2012

An Overview  
Using Data in  $\text{\LaTeX}$   
Documents

---

Line Graphs

---

Bar Graphs

## Line Graphs

## Bar Graphs

# Using Data in $\text{\LaTeX}$ Documents

An Overview  
Using Data in  $\text{\LaTeX}$   
Documents

Line Graphs

Bar Graphs

You can imagine situations where data are collected and then need to be presented in a document or presentation. Of course, we'll want to use  $\text{\LaTeX}$  for this document/presentation!

How should we get graphs into our  $\text{\LaTeX}$  documents?

There are two main ways to proceed:

1. Create a graph in some other program (Excel, Mathematica, SPSS, etc), export the image and include it in your  $\text{\LaTeX}$  document with the `\includegraphics` command.
  - ▶ **Positive:** Familiar, quick
  - ▶ **Negative:** Have little control over the appearance
2. Create the graph within  $\text{\LaTeX}$  itself.

An Overview  
Using Data in  $\text{\LaTeX}$   
Documents

---

## Line Graphs

The `psgraph`  
environment  
Making  $\text{\LaTeX}$  read your  
data  
Commands for the  
initial graph  
Plotting multiple data  
sets on one axis  
Legends for graphs  
More on the legend  
Labels for the axis  
Practice

---

## Bar Graphs

# Line Graphs

# The psgraph environment

An Overview  
Using Data in  $\text{\LaTeX}$   
Documents

## Line Graphs

The `psgraph`  
environment

Making  $\text{\LaTeX}$  read your  
data

Commands for the  
initial graph

Plotting multiple data  
sets on one axis

Legends for graphs

More on the legend

Labels for the axis

Practice

## Bar Graphs

The container for our line graphs will be the `psgraph` environment.

```
\begin{psgraph}[Options]{<arrows>}  
(x0,y0)(xm,ym)(xM,yM){xL}{yL} ...  
\end{psgraph}
```

<code>x0</code>	$x$ -coordinate of the origin
<code>y0</code>	$y$ -coordinate of the origin
<code>xm</code>	smallest $x$ -coordinate
<code>ym</code>	smallest $y$ -coordinate
<code>xM</code>	biggest $x$ -coordinate
<code>yM</code>	biggest $y$ -coordinate
<code>xL</code>	horizontal length of graph
<code>yL</code>	vertical length of graph

The `Options` in the `psgraph` environment are the same ones that apply for the `psaxes` environment.

# Making L<sup>A</sup>T<sub>E</sub>X read your data

An Overview  
Using Data in L<sup>A</sup>T<sub>E</sub>X Documents

## Line Graphs

The `psgraph` environment  
Making L<sup>A</sup>T<sub>E</sub>X read your data  
Commands for the initial graph  
Plotting multiple data sets on one axis  
Legends for graphs  
More on the legend  
Labels for the axis  
Practice

## Bar Graphs

The key part of all of this (which is not L<sup>A</sup>T<sub>E</sub>X-dependent) is *producing the data*. For line graphs, L<sup>A</sup>T<sub>E</sub>X is looking for ordered pairs of numbers to plot — you must supply the *coordinates* of the data points for the graph. There are two ways that L<sup>A</sup>T<sub>E</sub>X can read your data once it is produced.

1. Keeping the data in a separate file, like `clinic.dat`.
  - ▶ ordered pairs can be separated by spaces, commas, parentheses, etc.
2. Writing the data in the `.tex` file itself.

Look at the first example file (`.tex`) for examples of both of these methods. Make sure that you have the file `data1.dat` in the same folder as your example `.tex` file.

# Commands for the initial graph

An Overview  
Using Data in  $\text{\LaTeX}$   
Documents

## Line Graphs

The `psgraph`  
environment

Making  $\text{\LaTeX}$  read your  
data

Commands for the  
initial graph

Plotting multiple data  
sets on one axis

Legends for graphs

More on the legend

Labels for the axis

Practice

## Bar Graphs

Two important commands:

- `\readdata{macro}{file}` — this stores your data in a macro that  $\text{\LaTeX}$  can use
  - `macro` should be something like `\data` or `\dataA` — no numbers allowed!
  - `file` is the name of the data file, including file extension
- `\listplot[options]{macro}` — the command to plot the data
  - `options` can include line thickness, line color, whether or not to show the data points

# Plotting multiple data sets on one axis

An Overview  
Using Data in  $\text{\LaTeX}$   
Documents

## Line Graphs

The `psgraph`  
environment  
Making  $\text{\LaTeX}$  read your  
data  
Commands for the  
initial graph  
Plotting multiple data  
sets on one axis  
Legends for graphs  
More on the legend  
Labels for the axis  
Practice

## Bar Graphs

It is easy to plot multiple sets of data on the same set of axes.

Open up the second example file (`.tex`), build and view.

When plotting multiple sets of data on one set of axes, it is standard to include a *key* or *legend* to help your reader distinguish between the two sets of data.

Uncomment the bottom part of the last example file, build and view.



# Legends for graphs

An Overview  
Using Data in  $\text{\LaTeX}$   
Documents

## Line Graphs

The `psgraph`  
environment  
Making  $\text{\LaTeX}$  read your  
data  
Commands for the  
initial graph  
Plotting multiple data  
sets on one axis  
Legends for graphs  
More on the legend  
Labels for the axis  
Practice

## Bar Graphs

The command to make a legend for your graph is this:

```
\pslegend[reference](xoffset,yoffset){text}
```

- `reference` — must be one of `lb`, `lt`, `rb`, or `rt`, where `rt` is the default
- `xoffset` and `yoffset` — units (multiples of 1 point) to move the legend away from the specified corner of the graph
- `text` — the contents of the legend, typeset in a tabular environment

Example of legend text:

```
\pslegend[lt]{  
  \red\rule[1ex]{2em}{1pt} & Data I\\  
  \blue\rule[1ex]{2em}{1pt} & Data II}
```

Two notes on legends:

- Any color that has *already been defined* can be used as a command (as in the previous example with `\red` and `\blue`).
- The legend must be defined *before* the `psgraph` environment.

Obtaining labels for the axes:

```
\psset{xAxisLabel=Time,yAxisLabel=Height}
```

This command needs to come *before* the `psgraph` environment.

To position the axis labels:

```
\psset{xAxisLabelPos={c,-.4in},  
       yAxisLabelPos={-.4in,c}}
```

Open the third example file (`.tex`), build and view.

An Overview  
Using Data in  $\text{\LaTeX}$   
Documents

## Line Graphs

The `psgraph`  
environment  
Making  $\text{\LaTeX}$  read your  
data  
Commands for the  
initial graph  
Plotting multiple data  
sets on one axis  
Legends for graphs  
More on the legend  
Labels for the axis  
Practice

## Bar Graphs

## Let's practice!

Open the fourth example file ( `.pdf` ) and reproduce it.

An Overview  
Using Data in  $\text{\LaTeX}$   
Documents

Line Graphs

---

**Bar Graphs**

---

The data  
Different bar styles  
Example  
Bar width and  
separation  
The appearance of the  
bar labels  
Practice

# Bar Graphs

It is best for  $\text{\LaTeX}$  to read `.csv` files when creating bar graphs. The first row should be the labels, the second row should be the values. The `.csv` file can either be written within  $\text{\LaTeX}$  using the `filecontents*` environment (note the `*`) or written with an external program.

► The command to store the data in a macro is `\readpsbardata{macro}{file}`.

► The command to produce the bar chart is `\psbarchart[options]{macro}`

Open the fifth example file (`.tex`), build and view.

# Different bar styles

An Overview  
Using Data in L<sup>A</sup>T<sub>E</sub>X  
Documents

Line Graphs

Bar Graphs

The data

Different bar styles

Example

Bar width and  
separation

The appearance of the  
bar labels

Practice

The appearance of the bars is set through the `barstyle=style` option on `\psbarchart`. The available barstyles:

■ black	■ white
■ gray	■ red
■ darkgray	■ green
■ lightgray	■ blue

It's not too hard to define one's own barstyle:

```
\newrgbcolor{mypurple}{.5 0 .5}
\newpsbarstyle{spiffy}
    {fillcolor=mypurple,fillstyle=solid}
...
\psbarchart[barstyle=spiffy]{...}
```

An Overview  
Using Data in  $\text{\LaTeX}$   
Documents

Line Graphs

---

Bar Graphs

---

The data

Different bar styles

**Example**

Bar width and  
separation

The appearance of the  
bar labels

Practice

Open the sixth example file (`.tex`) posted on Sakai.

Build and view.



# Bar width and separation

An Overview  
Using Data in L<sup>A</sup>T<sub>E</sub>X  
Documents

Line Graphs

Bar Graphs

The data

Different bar styles

Example

Bar width and  
separation

The appearance of the  
bar labels

Practice

Changing the bar width:

```
\setlength{\psxunit}{newwidth}
```

► This is a command itself that must go *within* the `psgraph` environment but before the `\psbarchart` command.

Changing the space between bars:

```
barcolsep=newseparation
```

► This is an option in the `\psbarchart` command.

► Default is 0.4.

Uncomment the last part of the previous example file. Build and view.

# The appearance of the bar labels

An Overview  
Using Data in L<sup>A</sup>T<sub>E</sub>X  
Documents

Line Graphs

Bar Graphs

The data

Different bar styles

Example

Bar width and  
separation

The appearance of the  
bar labels

Practice

The bar labels can be rotated.

`barlabelrot=angle`

- ▶ This is an option in the `\psbarchart` command.
- ▶ Default is 0.

The separation between the bar labels and the horizontal axis can be changed.

`labelsep=newseparation`

- ▶ This is an option in the `\psbarchart` command.

Open the seventh example file (`.tex`) from Sakai. Build and view.

An Overview  
Using Data in  $\text{\LaTeX}$   
Documents

Line Graphs

---

Bar Graphs

---

The data  
Different bar styles  
Example  
Bar width and  
separation  
The appearance of the  
bar labels

Practice

## Let's practice!

Open the eighth example file (`.pdf`) and reproduce it.