Module 3

Understanding and countering malware's evasion and self-defence

Fingerprinting for evasion

Fingerprinting for evasion

- Fingerprinting = gathering information about the environment where the executable was deployed

- It is used by malware to determine whether it is deployed in a controlled enviromnent, i.e. sandbox, analysis machine

- Open source projects with rich sets of techniques:

    - https://github.com/a0rtega/pafish
    - https://github.com/LordNoteworthy/al-khaser
    - https://www.aldeid.com/wiki/ScoopyNG

- Presented demos you can find at:

    - https://github.com/hasherezade/antianalysis_demos

Fingerprinting for evasion

- PaFish in action:

Fingerprinting for evasion

- Al-Khaser in action:

Fingerprinting for evasion

- Most of the malware stop their execution once they observe being analyzed – that's how they protect their real mission from being revealed. Common reactions:
  - ExitProcess
  - Infinite sleep loop
- Some malware are more tricky, and:
  - deploy a decoy (i.e. an old variant of Andromeda)
  - corrupt their execution (i.e. Kronos) to crash at further point

Classic debugger detection techniques

Anti-debugger: the classic set

- The fact that the application is being debugged leaves some artefacts in the execution environment

- Malware tries to pick them up, and terminate or alter execution on such event

- There is a list of classic, well-known techniques, that malware authors keep using from years, and probably will keep using in the future

- Let's take a look at them...

Anti-debugger: approaches

- Using flags in internal process structures: EPROCESS, PEB
  - Some of those checks can be invoked via APIs

- Breakpoint detection

- Reaction on exceptions

- Time checks

- Searching for the physical presence of the debugger in the system: checking running processes, windows names/classes, installation artifacts of a debugger

Detecting debugger: basic API

The most basic method, using: `IsDebuggerPresent` and/or `CheckRemoteDebuggerPresent`

```cpp
bool is_debugger_api()
{
        if (IsDebuggerPresent()) return true;

        BOOL has_remote = FALSE;
        CheckRemoteDebuggerPresent(GetCurrentProcess(), &has_remote);

        return has_remote ? true: false;
}
```

Detecting debugger: basic API

The most basic method, using: `IsDebuggerPresent`

IsDebuggerPresent(32-bit ver.)

```
75621E2E <kernelbase.IsDebuggerPresent>
mov eax,dword ptr fs:[18]
mov eax,dword ptr ds:[eax+30]
movzx eax,byte ptr ds:[eax+2]
ret
```

1. Get **TEB**
2. Get **PEB**
3. Get: **BeingDebugged** Flag

PEB

```
lkd> dt nt!_PEB
   +0x000 InheritedAddressSpace    : UChar
   +0x001 ReadImageFileExecOptions : UChar
   +0x002 BeingDebugged            : UChar
   +0x003 BitField                 : UChar
   +0x003 ImageUsesLargePages      : Pos 0, 1 Bit
   +0x003 IsProtectedProcess       : Pos 1, 1 Bit
   +0x003 IsImageDynamicallyRelocated : Pos 2, 1 Bit
   +0x003 SkipPatchingUser32Forwarders : Pos 3, 1 Bit
   +0x003 IsPackagedProcess        : Pos 4, 1 Bit
   +0x003 IsAppContainer           : Pos 5, 1 Bit
```

Anti-debugger: PEB

- PEB contains information about the environment where the process was executed, and as well contains a lot of information relevant to detecting a debugger...

- Using it is more stealthy then using API, and also easy to do in pure assembly (convenient for a shellcode)

Detecting debugger: PEB

The more stealthy variant of the previous method is getting the BeingDebugged flag via PEB

```
lkd> dt nt!_PEB
   +0x000 InheritedAddressSpace : UChar
   +0x001 ReadImageFileExecOptions : UChar
   +0x002 BeingDebugged        : UChar
   +0x003 BitField             : UChar
   +0x003 ImageUsesLargePages  : Pos 0, 1 Bit
   +0x003 IsProtectedProcess   : Pos 1, 1 Bit
   +0x003 IsImageDynamicallyRelocated : Pos 2, 1 Bit
   +0x003 SkipPatchingUser32Forwarders : Pos 3, 1 Bit
   +0x003 IsPackagedProcess    : Pos 4, 1 Bit
   +0x003 IsAppContainer       : Pos 5, 1 Bit
```

Related API:
- IsDebuggerPresent

Detecting debugger: PEB

Another flag in PEB related to being debugged is NtGlobalFlag (more recent addition: NtGlobalFlag2)

```
Command
    +0x080 TlsBitmapBits       : [2] Uint4B
    +0x088 ReadOnlySharedMemoryBase : Ptr64 Void
    +0x090 SharedData          : Ptr64 Void
    +0x098 ReadOnlyStaticServerData : Ptr64 Ptr64 Void
    +0x0a0 AnsiCodePageData    : Ptr64 Void
    +0x0a8 OemCodePageData     : Ptr64 Void
    +0x0b0 UnicodeCaseTableData : Ptr64 Void
    +0x0b8 NumberOfProcessors  : Uint4B
    +0x0bc NtGlobalFlag        : Uint4B
    +0x0c0 CriticalSectionTimeout : _LARGE_INTEGER
    +0x0c8 HeapSegmentReserve  : Uint8B
    +0x0d0 HeapSegmentCommit   : Uint8B
```

NTGlobalFlag is set when the stack of the application is being watched

Related API:
- `RtlGetCurrentPeb()`
`PEB->NtGlobalFlag`
`PEB->NtGlobalFlag2`

Detecting debugger: PEB

If the process is **not** being debugged: NtGlobalFlag == 0

Otherwise, the following flags are set (NtGlobalFlag == 0x70):

```
FLG_HEAP_ENABLE_TAIL_CHECK    0x10
FLG_HEAP_ENABLE_FREE_CHECK    0x20
FLG_HEAP_VALIDATE_PARAMETERS 0x40
```

Detecting debugger: PEB

PEB.ProcessHeap.Flags:

- If not degugged:

  HEAP_GROWABLE (0x2)

- Otherwise:

```
HEAP_GROWABLE                              0x2
HEAP_TAIL_CHECKING_ENABLED                 0x20
HEAP_FREE_CHECKING_ENABLED                 0x40
HEAP_SKIP_VALIDATION_CHECKS         0x10000000
HEAP_VALIDATE_PARAMETERS_ENABLED    0x40000000
```

Detecting debugger: PEB

PEB.ProcessHeap.ForceFlags:

- If not degugged: 0

- Otherwise: related to PEB.ProcessHeap.Flags:

```
PEB.ProcessHeapFlags & 0x6001007D
```

Detecting debugger: basic API

The most basic method, using: CheckRemoteDebuggerPresent

CheckRemoteDebuggerPresent

```
kernel32.76663F94
 push 0 ; ReturnLength
 push 4 ; ProcessInformationLength
 lea eax,dword ptr ss:[ebp+8]
 push eax ; ProcessInformation
 push 7 ; ProcessInformationClass -> ProcessDebugPort
 push dword ptr ss:[ebp+8] ; ProcessHandle
 call dword ptr ds:[<&NtQueryInformationProcess>]
 test eax,eax
 jl kernel32.76669176
```

EPROCESS

```
lkd> dt nt!_EPROCESS
   +0x000 Pcb             : _KPROCESS
   +0x2d8 ProcessLock     : _EX_PUSH_LOCK
   +0x2e0 UniqueProcessId : Ptr64 Void
   +0x2e8 ActiveProcessLinks : _LIST_ENTRY
   +0x2f8 RundownProtect  : _EX_RUNDOWN_REF
   +0x300 Flags2          : Uint4B
...
   +0x3f8 Peb             : Ptr64 _PEB
   +0x400 Session         : Ptr64 _MM_SESSION_SPACE
   +0x408 Spare1          : Ptr64 Void
   +0x410 QuotaBlock      : Ptr64 _EPROCESS_QUOTA_BLOCK
   +0x418 ObjectTable     : Ptr64 _HANDLE_TABLE
   +0x420 DebugPort       : Ptr64 Void
   +0x428 Wow64Process    : Ptr64 _EWOW64PROCESS
```

Detecting debugger: API

Some of the mentioned artifacts (and more) can be retrieved using `NtQueryInformationProcess`

Relevant parameters:

```
ProcessDebugPort              0x7 -> EPROCESS.DebugPort
ProcessDebugFlags            0x1F -> !(EPROCESS.NoDebugInherit)
ProcessDebugObjectHandle     0x1E -> returns DebugObject
ProcessBasicInformation       0x0 -> to get the parent process
```

Reaction on exceptions

If the debugger is present, it will try to handle the exception:

```cpp
bool exception_is_dbg()
{
    __try {
        RaiseException(DBG_PRINTEXCEPTION_C, 0, 0, 0);
    } __except (EXCEPTION_EXECUTE_HANDLER) {
        return false;
    }


    return true;
}
```

Hardware breakpoints

- There are 4 Debug registrs that we can use for setting Hardware Breakpoints:
  - DR0-DR3

- Once we set the Hardware Breakpoint, the relevant address is filled in one of those registers. Example:

```
DR0  00413AB7          remcos.00413AB7
DR1  00000000
DR2  00000000
DR3  00000000
DR6  00000000
DR7  00000001
```

- DR6 – flags indicating the Debug Register which's breakpoint got hit
- DR7 – flags indicating which of the Debug Registers are set

Hardware breakpoints

Checking if the Hardware Breakpoints have been set:

```cpp
bool hardware_bp_is_dbg()
{
        CONTEXT ctx = { 0 };
        bool is_hardware_bp = false;

        HANDLE thread = OpenThread(THREAD_ALL_ACCESS, FALSE, GetCurrentThreadId());
        ctx.ContextFlags = CONTEXT_DEBUG_REGISTERS;
        if (GetThreadContext(thread, &ctx)) {
                is_hardware_bp = (ctx.Dr0 | ctx.Dr1 | ctx.Dr2 | ctx.Dr3) != 0;
        }
        CloseHandle(thread);

        return is_hardware_bp;
}
```

The Trap Flag: Single Stepping

- The Trap Flag is one of the Flags in the EFLAGS register


```
EFLAGS    00000246
ZF 1    PF 1    AF 0
OF 0    SF 0    DF 0
CF 0    TF 0    IF 1
```

```
EFLAGS    00000346
ZF 1    PF 1    AF 0
OF 0    SF 0    DF 0
CF 0    TF 1    IF 1
```

0x346 XOR 0x246 = 0x100 (TF)

- Setting the Trap Flag - allowing to step throught the code via INT 0x1: „Single Step" after each instruction (generates an exception)

The Trap Flag: Single Stepping

We cannot access EFLAGS directly - we need to do it via stack:

```
pushfd                              ; push all the flags
or dword ptr[esp], 0x100            ; the flags are now in [esp]
                                    ; apply the mask to set the bit
                                    ; 0x100, that means TF
popfd                               ; load the flags from the stack again
```

If we are single-stepping through the code, the debugger will handle the generated interrupt. Otherwise, setting of the Trap Flag will generates an exception.

The time check

- Debugging (also: emulation, or tracing the application by instrumentation tools) often slows down the execution

- The time check is a simple way to find out that the application may be under control of analysis tools

- The time check is often implemented with the help or `RTDSC` (Read Time-Stamp Counter) instruction

```
RTDCS -> EDX:EAX = TimeStampCounter
```

The time check

The time should be measured at least twice, and compared with a threshold.
Example:

```
bool antidbg_timer_check()
{
    static ULONGLONG time = 0;
    if (time == 0) {
        time = __rdtsc();
        return false;
    }
    ULONGLONG second_time = __rdtsc();
    ULONGLONG diff = (second_time - time) >> 20;
    if (diff > 0x100) {
        time = second_time;
        return true;
    }
    return false;
}
```

Defense against anti-debug

- Debugger Plugins, i.e.
  - [ScyllaHide](#) (using user-mode hooking)
  - [TitanHide](#) (using kernel-mode hooking)
  - SharpOD

- OllyDbg plugins (older, classics):
  - OllyAdvanced
  - Phantom
  - StrongOD

https://github.com/fr0gger/awesome-ida-x64-olly-plugin

Classic anti-VM techniques

Anti-VM fingerprinting

- Virutal Machine emulates the real one to big extend, but still there are some artifacts in the environment that makes it distinguishable

- Depending which hypervisor do we use, those artifacts will differ

- It is quite common among malware to look for some of those artifacts in order to detect the Virtual Machine

- Some checks base on the presence of some particular names, related to the hypervisor, other – on some loosely related features (i.e. relatively weak parameters, one processor, etc)

Anti-VM: approaches

- Using presence/absence of some intstructions

- Identifiers returned by CPUID

- Memory-specific („The Red Pill" – IDT checking; GDT, LDT checks)

- Time checks

- Weaker hardware parameters (comparing to most modern physical machines)

- Searching for the physical presence of the VM-related artifacts: checking running processes, windows names/classes, registry keys, etc.

CPUID (1)

- One of the low-level anti-vm techniques, is a check using `CPUID` instruction
- Check for processof features:

```
mov is_bit_set, 0
mov eax, 1 ; the parameter given to CPUID
cpuid
bt   ecx, 0x1f; bit 31
jnc  finish
  mov is_bit_set, 1 ; if the bit is set, it is a VM
finish:
```

CPUID (0x40000000)

- One of the low-level anti-vm techniques, is a check using **CPUID** instruction
- Check for the hypervisor brand:

```
mov eax, 0x40000000; the parameter given to CPUID
cpuid
mov brand_id_0, ebx
mov brand_id_1, ecx
mov brand_id_2, edx
```

https://c9x.me/x86/html/file_module_x86_id_45.html

(PUID (0x40000000)

- One of the low-level anti-vm techniques, is a check using **CPUID** instruction

```
"KVMKVMKVM\0\0\0"; // KVM
"Microsoft Hv"; // MS Hyper-V or Virtual PC
"VMwareVMware"; // VMware
"XenVMMXenVMM"; // Xen
"prl hyperv  "; // Parallels
"VBoxVBoxVBox"; // VirtualBox
```

CPUID - defense

- Fortunately, we often can overwrite the values returned by CPUID by our own
- Appropriate settings may force the VM to supply our custom values instead of the hardcodes ones...

https://www.vmray.com/cyber-security-blog/a-pafish-primer/

CPUID - defense

- In VMWare: settings can be changed in the .vmx file

- Anti bit-check - CPUID (1)

```
cpuid.1.ecx="0---:----:----:----:----:----:----:----"
```

- Anti brand-check (0x40000000)

```
cpuid.40000000.ecx="0000:0000:0000:0000:0000:0000:0000:0000"
cpuid.40000000.edx="0000:0000:0000:0000:0000:0000:0000:0000"
```

VMWare I/O port

- Trying to read the special I/O port, used by VMware to communicate with host, with the help of `IN` instruction

- On a physical machine, the exception will occur

```
mov eax, 'VMXh'
mov ebx,0
mov ecx, 10
Mov edx, 'VX'
in eax, dx
cmp ebx,'VMXh'
```

TODO...

- To be continued