



Road to Mercari

Gopher Dojo module 03

Summary: This document is the subject for the Gopher Dojo module 03 of the Road to Mercari @ 42 Tokyo.



Contents

I	Instructions	2
II	Foreword	3
III	Exercise 00 : Omikuji API	4

Chapter I

Instructions

- Only this page will serve as reference; do not trust rumors.
- Watch out! This document could potentially change up to an hour before submission.
- These exercises are carefully laid out by order of difficulty - from easiest to hardest. We **will not** take into account a successfully completed harder exercise if an easier one is not perfectly functional.
- Make sure you have the appropriate permissions on your files and directories.
- You have to follow the submission procedures for every exercise.
- Your exercises will be checked and graded by your fellow classmates.
- You cannot leave any additional file in your directory than those specified in the subject.
- Got a question? Ask your peer on the right. Otherwise, try your peer on the left.
- Your reference guide is called `Google / man / the Internet /`
- Examine the examples thoroughly. They could very well call for details that are not explicitly mentioned in the subject...
- If no other explicit information is displayed, you must use the latest versions of Go.


Chapter II

Foreword

<https://gopherdojo.org/>

Chapter III

Exercise 00 : Omikuji API

	Exercise 00
HTTP API and JSON	
Turn-in directory : <i>ex00/</i>	
Files to turn in : *	

Create an omikuji API that follows the following specifications.

- Your API endpoint should be hosted on port given by a command line argument.
- When the endpoint is called, your API should return a random omikuji and an HTTP 200 status code.
- The API should return the omikuji in JSON format.
- The `fortune` property is required, and must contain one of the following values: "Dai-kichi", "Kichi", "Chuu-kichi", "Sho-kichi", "Sue-kichi", "Kyo", "Dai-kyo"
- Aside from `fortune`, the returned JSON must contain at least one other property. All other properties and their values are optional.
- Example of json:

```
{
  "fortune": "Dai-kichi",
  "health": "You will fully recover, but stay attentive after you do.",
  "residence": "You will have good fortune with a new house.",
  "travel": "When traveling, you may find something to treasure.",
  "study": "Things will be better. It may be worth aiming for a school in a different area.",
  "love": "The person you are looking for is very close to you."
}
```

- Your omikuji can only return Dai-kichi during Shogatsu (1/1 - 1/3). (use the servers real time to implement this feature.)
- When you retrieve the actual time, it should be implemented so that the test is mockable.

- Your omikujii program should handle all the errors without crashing.
- Example of execution:

```
?> ./omikujii 4242 &
[1] 81634
?> curl localhost:4242
{"fortune":"Kyo","health":"You will partially recover, but stay attentive after you do.,"residence
 ": "You will have good fortune with a new house.,"travel":"When traveling, you may find
 something to treasure.,"study":"Things will be better. It may be worth aiming for a school in
 a different area.,"love":"The person you are looking for is very close to you."}
```

- Write a test for your http handler and also for self implemented package.
- Example of test execution:

```
?> go test -cover ./...
ok      _/XX/XX/ex00    0.385s coverage: 58.3% of statements
ok      _/XX/XX/ex00/omikuzi 0.239s coverage: 44.0% of statements
```



<https://pkg.go.dev/testing>



<https://pkg.go.dev/net/http/httpptest>